



Resource Groups API Reference

AWS Resource Groups



AWS Resource Groups: Resource Groups API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateGroup	3
Request Syntax	3
URI Request Parameters	4
Request Body	4
Response Syntax	6
Response Elements	7
Errors	7
Examples	8
See Also	15
DeleteGroup	16
Request Syntax	16
URI Request Parameters	16
Request Body	16
Response Syntax	17
Response Elements	17
Errors	17
Examples	18
See Also	19
GetAccountSettings	21
Request Syntax	21
URI Request Parameters	21
Request Body	21
Response Syntax	21
Response Elements	21
Errors	22
Examples	22
See Also	23
GetGroup	25
Request Syntax	25
URI Request Parameters	25
Request Body	25
Response Syntax	26

Response Elements	26
Errors	26
Examples	27
See Also	28
GetGroupConfiguration	30
Request Syntax	30
URI Request Parameters	30
Request Body	30
Response Syntax	31
Response Elements	31
Errors	32
Examples	33
See Also	37
GetGroupQuery	38
Request Syntax	38
URI Request Parameters	38
Request Body	38
Response Syntax	39
Response Elements	39
Errors	40
Examples	40
See Also	42
GetTags	43
Request Syntax	43
URI Request Parameters	43
Request Body	43
Response Syntax	43
Response Elements	44
Errors	44
Examples	45
See Also	46
GroupResources	48
Request Syntax	48
URI Request Parameters	48
Request Body	48
Response Syntax	49

Response Elements	50
Errors	50
Examples	51
See Also	52
ListGroupResources	54
Request Syntax	54
URI Request Parameters	54
Request Body	54
Response Syntax	57
Response Elements	57
Errors	58
Examples	59
See Also	61
ListGroups	62
Request Syntax	62
URI Request Parameters	62
Request Body	63
Response Syntax	64
Response Elements	64
Errors	65
Examples	66
See Also	68
PutGroupConfiguration	70
Request Syntax	70
URI Request Parameters	70
Request Body	70
Response Syntax	71
Response Elements	71
Errors	72
Examples	73
See Also	77
SearchResources	78
Request Syntax	78
URI Request Parameters	78
Request Body	78
Response Syntax	79

Response Elements	80
Errors	81
Examples	82
See Also	83
Tag	84
Request Syntax	84
URI Request Parameters	84
Request Body	85
Response Syntax	85
Response Elements	85
Errors	86
Examples	87
See Also	88
UngroupResources	90
Request Syntax	90
URI Request Parameters	90
Request Body	90
Response Syntax	91
Response Elements	91
Errors	92
Examples	93
See Also	94
Untag	96
Request Syntax	96
URI Request Parameters	96
Request Body	96
Response Syntax	97
Response Elements	97
Errors	98
Examples	99
See Also	100
UpdateAccountSettings	101
Request Syntax	101
URI Request Parameters	101
Request Body	101
Response Syntax	101

Response Elements	102
Errors	102
Examples	103
See Also	104
UpdateGroup	105
Request Syntax	105
URI Request Parameters	105
Request Body	105
Response Syntax	106
Response Elements	106
Errors	107
Examples	108
See Also	109
UpdateGroupQuery	110
Request Syntax	110
URI Request Parameters	110
Request Body	110
Response Syntax	111
Response Elements	112
Errors	112
Examples	113
See Also	114
Data Types	116
AccountSettings	117
Contents	117
See Also	118
FailedResource	119
Contents	119
See Also	120
Group	121
Contents	121
See Also	122
GroupConfiguration	123
Contents	123
See Also	124
GroupConfigurationItem	125

Contents	125
See Also	125
GroupConfigurationParameter	127
Contents	127
See Also	127
GroupFilter	129
Contents	129
See Also	129
GroupIdIdentifier	131
Contents	131
See Also	131
GroupQuery	133
Contents	133
See Also	133
ListGroupResourcesItem	135
Contents	135
See Also	135
PendingResource	137
Contents	137
See Also	137
QueryError	138
Contents	138
See Also	138
ResourceFilter	140
Contents	140
See Also	140
ResourceIdentifier	142
Contents	142
See Also	142
ResourceQuery	144
Contents	144
See Also	146
ResourceStatus	148
Contents	148
See Also	148
Making API requests	149

Resource Groups endpoints	149
Query parameters	149
Request identifiers	149
Query API authentication	150
Available libraries	150
Making API requests using the POST method	150
Common Parameters	153
Common Errors	156

Welcome

AWS Resource Groups lets you organize AWS resources such as Amazon Elastic Compute Cloud instances, Amazon Relational Database Service databases, and Amazon Simple Storage Service buckets into groups using criteria that you define as tags. A resource group is a collection of resources that match the resource types specified in a query, and share one or more tags or portions of tags. You can create a group of resources based on their roles in your cloud infrastructure, lifecycle stages, regions, application layers, or virtually any criteria. Resource Groups enable you to automate management tasks, such as those in AWS Systems Manager Automation documents, on tag-related resources in AWS Systems Manager. Groups of tagged resources also let you quickly view a custom console in AWS Systems Manager that shows AWS Config compliance and other monitoring data about member resources.

To create a resource group, build a resource query, and specify tags that identify the criteria that members of the group have in common. Tags are key-value pairs.

For more information about Resource Groups, see the [AWS Resource Groups User Guide](#).

AWS Resource Groups uses a REST-compliant API that you can use to perform the following types of operations.

- Create, Read, Update, and Delete (CRUD) operations on resource groups and resource query entities
- Applying, editing, and removing tags from resource groups
- Resolving resource group member ARNs so they can be returned as search results
- Getting data about resources that are members of a group
- Searching AWS resources based on a resource query

This document was last published on April 8, 2024.

Actions

The following actions are supported:

- [CreateGroup](#)
- [DeleteGroup](#)
- [GetAccountSettings](#)
- [GetGroup](#)
- [GetGroupConfiguration](#)
- [GetGroupQuery](#)
- [GetTags](#)
- [GroupResources](#)
- [ListGroupResources](#)
- [ListGroups](#)
- [PutGroupConfiguration](#)
- [SearchResources](#)
- [Tag](#)
- [UngroupResources](#)
- [Untag](#)
- [UpdateAccountSettings](#)
- [UpdateGroup](#)
- [UpdateGroupQuery](#)

CreateGroup

Creates a resource group with the specified name and description. You can optionally include either a resource query or a service configuration. For more information about constructing a resource query, see [Build queries and groups in AWS Resource Groups](#) in the *AWS Resource Groups User Guide*. For more information about service-linked groups and service configurations, see [Service configurations for Resource Groups](#).

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:CreateGroup`

Request Syntax

```
POST /groups HTTP/1.1
Content-type: application/json

{
  "ConfigurationParametersNameValuesTypeDescriptionNameResourceQueryQueryTypeTags
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Name

The name of the group, which is the identifier of the group in other operations. You can't change the name of a resource group after you create it. A resource group name can consist of letters, numbers, hyphens, periods, and underscores. The name cannot start with AWS, aws, or any other possible capitalization; these are reserved. A resource group name must be unique within each AWS Region in your AWS account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\.-]+

Required: Yes

Configuration

A configuration associates the resource group with an AWS service and specifies how the service can interact with the resources in the group. A configuration is an array of [GroupConfigurationItem](#) elements. For details about the syntax of service configurations, see [Service configurations for Resource Groups](#).

 **Note**

A resource group can contain either a Configuration or a ResourceQuery, but not both.

Type: Array of [GroupConfigurationItem](#) objects

Array Members: Maximum number of 2 items.

Required: No

Description

The description of the resource group. Descriptions can consist of letters, numbers, hyphens, underscores, periods, and spaces.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: [\sa-zA-Z0-9_\.-]*

Required: No

ResourceQuery

The resource query that determines which AWS resources are members of this group. For more information about resource queries, see [Create a tag-based group in Resource Groups](#).

Note

A resource group can contain either a ResourceQuery or a Configuration, but not both.

Type: [ResourceQuery object](#)

Required: No

Tags

The tags to add to the group. A tag is key-value pair string.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)\$

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: ^([\p{L}\p{Z}\p{N}_.:/=+\-@]*)\$

Required: No

Response Syntax

HTTP/1.1 200
Content-type: application/json

```
{  
    "Group": {  
        "Description": "string",  
        "GroupArn": "string",  
        "Name": "string"  
    },  
    "GroupConfiguration": {  
        "Configuration": [  
            {  
                "Parameters": [  
                    {  
                        "Name": "string",  
                        "Values": [ "string" ]  
                    }  
                ],  
                "Type": "string"  
            }  
        ],  
        "FailureReason": "string",  
        "ProposedConfiguration": [  
            {  
                "Parameters": [  
                    {  
                        "Name": "string",  
                        "Values": [ "string" ]  
                    }  
                ],  
                "Type": "string"  
            }  
        ],  
        "Status": "string"  
    },  
    "ResourceQuery": {  
        "Query": "string",  
        "Type": "string"  
    },  
    "Tags": {  
        "string" : "string"  
    }  
}
```

```
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Group

The description of the resource group.

Type: [Group](#) object

GroupConfiguration

The service configuration associated with the resource group. For details about the syntax of a service configuration, see [Service configurations for Resource Groups](#).

Type: [GroupConfiguration](#) object

ResourceQuery

The resource query associated with the group. For more information about resource queries, see [Create a tag-based group in Resource Groups](#).

Type: [ResourceQuery](#) object

Tags

The tags associated with the group.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: $^([\backslash p\{L\}\backslash p\{Z\}\backslash p\{N\}_.:/+\\-@]*$$

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: $^([\backslash p\{L\}\backslash p\{Z\}\backslash p\{N\}_.:/+\\-@]*$$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example creates a resource group in the us-west-2 Region of the calling account. The resource group has a query that specifies that any resources in the account that are tagged with the key Stage and a value of Test are members of the group. The group itself (not its members) is tagged with a key named Department and a value of Finance.

Sample Request

```
POST /groups HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
```

```
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.create-group
X-Amz-Date: 20220113T175008Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 283

{
  "Description": "Resources created for the testing stage.",
  "Name": "QueryGroup",
  "ResourceQuery": {
    "Query": "{\"ResourceTypeFilters\":[\"AWS::AllSupported\"],\"TagFilters\": [{\"Key\":\"Stage\", \"Values\":[\"Test\"]}]}",
    "Type": "TAG_FILTERS_1_0"
  },
  "Tags": {"Department": "Finance"}
}
```

```
HTTP/1.1 200 OK
Date: Thu, 13 Jan 2022 17:50:08 GMT
Content-Type: application/json
Content-Length: 384
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
  "Group": {
    "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/QueryGroup",
    "Name": "QueryGroup",
    "Description": "Resources created for the testing stage.",
    "OwnerId": "123456789012"
  },
  "ResourceQuery": {
    "Type": "TAG_FILTERS_1_0",
    "Query": "{\"ResourceTypeFilters\":[\"AWS::AllSupported\"],\"TagFilters\": [{\"Key\":\"Stage\", \"Values\":[\"Test\"]}]}"
  },
  "Tags": {"Department": "Finance"}
```

```
}
```

Example

The following example creates a resource group with a configuration that makes the group serve as a capacity reservation pool by Amazon Elastic Compute Cloud. This group can contain only Amazon EC2 capacity reservations that you add by using the [GroupResources](#) operation.

Sample Request

```
POST /groups HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.create-group
X-Amz-Date: 20220113T180534Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>Content-Length: 320
Content-Length: 320

{
  "Name": "CRPGroup",
  "Description": "Resource group for capacity reservations.",
  "Configuration": [
    {
      "Type": "AWS::EC2::CapacityReservationPool"
    },
    {
      "Type": "AWS::ResourceGroups::Generic",
      "Parameters": [
        {
          "Name": "allowed-resource-types",
          "Values": [
            "AWS::EC2::CapacityReservation"
          ]
        }
      ]
    }
  ],
  "Tags": {
    "Department": "Finance"
  }
}
```

```
    }  
}
```

Sample Response

```
HTTP/1.1 200 OK  
Date: Thu, 13 Jan 2022 18:05:34 GMT  
Content-Type: application/json  
Content-Length: 561  
x-amzn-RequestId: <VARIES>  
x-amz-apigw-id: <VARIES>  
X-Amzn-Trace-Id: Root=<VARIES>  
Connection: keep-alive  
  
{  
  "Group":{  
    "GroupArn":"arn:aws:resource-groups:us-west-2:123456789012:group/CRPGroup",  
    "Name":"CRPGroup",  
    "Description":"Resource group for capacity reservations.",  
    "OwnerId":"123456789012"  
  },  
  "Tags":{  
    "Department":"Finance"  
  },  
  "GroupConfiguration":{  
    "GroupParameters": [  
      {  
        "Name":"allowed-resource-types",  
        "Values": [  
          "AWS::EC2::CapacityReservation"  
        ]  
      }  
    ],  
    "Configuration": [  
      {  
        "Type":"AWS::EC2::CapacityReservationPool"  
      },  
      {  
        "Type":"AWS::ResourceGroups::Generic",  
        "Parameters": [  
          {  
            "Name":"allowed-resource-types",  
            "Values": [  
              "AWS::EC2::CapacityReservation"  
            ]  
          }  
        ]  
      }  
    ]  
  }  
}
```

```
        "AWS::EC2::CapacityReservation"
    ]
}
]
},
"Status": "UPDATE_COMPLETE"
}
}
```

Example

The following example creates a resource group that can contain only Amazon EC2 hosts. Each instance launched into the group is automatically configured to use any of the available core/socket based license configurations you have defined in AWS License Manager.

Sample Request

```
POST /groups HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.create-group
X-Amz-Date: 20220113T182832Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 362

{
  "Name": "HostManagementGroup",
  "Configuration": [
    {
      "Type": "AWS::EC2::HostManagement",
      "Parameters": [
        {
          "Name": "any-host-based-license-configuration",
          "Values": [
            "true"
          ]
        }
      ]
    }
  ]
}
```

```
        },
        {
            "Type": "AWS::ResourceGroups::Generic",
            "Parameters": [
                {
                    "Name": "allowed-resource-types",
                    "Values": [
                        "AWS::EC2::Host"
                    ]
                },
                {
                    "Name": "deletion-protection",
                    "Values": [
                        "UNLESS_EMPTY"
                    ]
                }
            ]
        }
    }
}
```

```
role="response">>HTTP/1.1 200 OK
Date: Thu, 13 Jan 2022 18:28:33 GMT
Content-Type: application/json
Content-Length: 881
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "Group": {
        "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/HostManagementGroup",
        "Name": "HostManagementGroup",
        "OwnerId": "123456789012"
    },
    "GroupConfiguration": {
        "GroupParameters": [
            {
                "Name": "allowed-resource-types",
                "Values": [
                    "AWS::EC2::Host"
                ]
            }
        ]
    }
}
```

```
        ],
    },
    {
        "Name": "deletion-protection",
        "Values": [
            "UNLESS_EMPTY"
        ]
    }
],
"ResourceTypeParameters": [
    {
        "ResourceType": "AWS::EC2::Host",
        "Name": "exclusive-membership",
        "Values": [
            "ACROSS_SAME_SERVICE_LINK_TYPE"
        ]
    }
],
"ServiceLinkParameters": [
    {
        "Name": "any-host-based-license-configuration",
        "Values": [
            "true"
        ]
    }
],
"Configuration": [
    {
        "Type": "AWS::EC2::HostManagement",
        "Parameters": [
            {
                "Name": "any-host-based-license-configuration",
                "Values": [
                    "true"
                ]
            }
        ]
    },
    {
        "Type": "AWS::ResourceGroups::Generic",
        "Parameters": [
            {
                "Name": "allowed-resource-types",
                "Values": [

```

```
        "AWS::EC2::Host"
    ],
},
{
    "Name": "deletion-protection",
    "Values": [
        "UNLESS_EMPTY"
    ]
}
],
"Status": "UPDATE_COMPLETE"
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteGroup

Deletes the specified resource group. Deleting a resource group does not delete any resources that are members of the group; it only deletes the group structure.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:DeleteGroup`

Request Syntax

```
POST /delete-group HTTP/1.1
Content-type: application/json

{
    "Group": "string",
    "GroupName": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Group

The name or the ARN of the resource group to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: (`arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`

Required: No

GroupName

Deprecated - don't use this parameter. Use Group instead.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\.-]+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Group": {
    "DescriptionGroupArn": "string",
    "Name": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Group

A full description of the deleted resource group.

Type: [Group](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example deletes the resource group with the name MyGroup in the us-west-2 Region of the calling account.

Sample Request

```
POST /delete-group HTTP/1.1
```

```
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.delete-group
X-Amz-Date: 20220113T205913Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 20

{ "Group": "MyGroup" }
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 13 Jan 2022 20:59:14 GMT
Content-Type: application/json
Content-Length: 127
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
  "Group": {
    "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/MyGroup",
    "Name": "MyGroup",
    "OwnerId": "123456789012"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccountSettings

Retrieves the current status of optional features in Resource Groups.

Request Syntax

```
POST /get-account-settings HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AccountSettings": {
    "GroupLifecycleEventsDesiredStatus": "string",
    "GroupLifecycleEventsStatus": "string",
    "GroupLifecycleEventsStatusMessage": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AccountSettings

The current settings for the optional features in Resource Groups.

Type: AccountSettings object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example retrieves the current Resource Groups account settings for the calling AWS account:

Sample Request

```
POST /get-account-settings HTTP/1.1
```

```
Host: resource-groups.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: <VRIES>
X-Amz-Date: 20221213T214448Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
```

Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 13 Dec 2022 21:44:48 GMT
Content-Type: application/json
Content-Length: 61
x-amzn-RequestId: <VRIES>
x-amz-apigw-id: <VRIES>
X-Amzn-Trace-Id: Root=<VRIES>
Connection: keep-alive

{
    "AccountSettings": {
        "GroupLifecycleEventsStatus": "INACTIVE"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetGroup

Returns information about a specified resource group.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:GetGroup`

Request Syntax

```
POST /get-group HTTP/1.1
Content-type: application/json

{
    "GroupGroupName
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Group

The name or the ARN of the resource group to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: (`arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`)

Required: No

GroupName

Deprecated - don't use this parameter. Use Group instead.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\.-]+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "GroupDescriptionGroupArnName
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Group

A structure that contains the metadata details for the specified resource group. Use [GetGroupQuery](#) and [GetGroupConfiguration](#) to get those additional details of the resource group.

Type: [Group](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example displays the metadata about a resource group in the us-west-2 Region for the calling AWS account. You can then use [GetGroupQuery](#) and [GetGroupConfiguration](#) to get the details of the resource group.

Sample Request

```
POST /get-group HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.get-group
X-Amz-Date: 20220113T211658Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 21

{"Group": "CRPGroup"}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 13 Jan 2022 21:16:58 GMT
Content-Type: application/json
Content-Length: 193
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "Group": {
        "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/CRPGroup",
        "Name": "CRPGroup",
        "Description": "Resource group for capacity reservations.",
        "OwnerId": "123456789012"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetGroupConfiguration

Retrieves the service configuration associated with the specified resource group. For details about the service configuration syntax, see [Service configurations for Resource Groups](#).

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:GetGroupConfiguration`

Request Syntax

```
POST /get-group-configuration HTTP/1.1
Content-type: application/json

{
    "Group
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Group

The name or the ARN of the resource group for which you want to retrieve the service configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: (`arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "GroupConfiguration": [
        "Configuration": [
            {
                "Parameters": [
                    {
                        "Name": "string",
                        "Values": [ "string" ]
                    }
                ],
                "Type": "string"
            }
        ],
        "FailureReason": "string",
        "ProposedConfiguration": [
            {
                "Parameters": [
                    {
                        "Name": "string",
                        "Values": [ "string" ]
                    }
                ],
                "Type": "string"
            }
        ],
        "Status": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[GroupConfiguration](#)

A structure that describes the service configuration attached with the specified group. For details about the service configuration syntax, see [Service configurations for Resource Groups](#).

Type: [GroupConfiguration](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example shows the typical output of a resource group that contains capacity reservations.

Sample Request

```
POST /get-group-configuration HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.get-group-configuration
X-Amz-Date: 20220113T213346Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 21

{
    "Group": "CRPGroup"
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 13 Jan 2022 21:33:46 GMT
Content-Type: application/json
Content-Length: 461
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupIdentifier": {
        "GroupName": "CRPGroup",
        "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/CRPGroup"
    }
}
```

```
},
"GroupConfiguration": [
    "GroupParameters": [
        {
            "Name": "allowed-resource-types",
            "Values": [
                "AWS::EC2::CapacityReservation"
            ]
        }
    ],
    "Configuration": [
        {
            "Type": "AWS::EC2::CapacityReservationPool"
        },
        {
            "Type": "AWS::ResourceGroups::Generic",
            "Parameters": [
                {
                    "Name": "allowed-resource-types",
                    "Values": [
                        "AWS::EC2::CapacityReservation"
                    ]
                }
            ]
        }
    ],
    "Status": "UPDATE_COMPLETE"
}
]
```

Example

The following example shows the typical output of a resource group that contains a configuration for Amazon EC2 dedicated hosts.

Sample Request

```
POST /get-group-configuration HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.get-group-configuration
X-Amz-Date: 20220113T213500Z
```

```
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 32

{
    "Group": "HostManagementGroup"
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 13 Jan 2022 21:35:00 GMT
Content-Type: application/json
Content-Length: 871
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupIdentifier": {
        "GroupName": "HostManagementGroup",
        "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/
HostManagementGroup"
    },
    "GroupConfiguration": {
        "GroupParameters": [
            {
                "Name": "allowed-resource-types",
                "Values": [
                    "AWS::EC2::Host"
                ]
            },
            {
                "Name": "deletion-protection",
                "Values": [
                    "UNLESS_EMPTY"
                ]
            }
        ],
        "ResourceTypeParameters": [

```

```
{  
    "ResourceType": "AWS::EC2::Host",  
    "Name": "exclusive-membership",  
    "Values": [  
        "ACROSS_SAME_SERVICE_LINK_TYPE"  
    ]  
},  
],  
"ServiceLinkParameters": [  
    {  
        "Name": "any-host-based-license-configuration",  
        "Values": [  
            "true"  
        ]  
    }  
],  
"Configuration": [  
    {  
        "Type": "AWS::EC2::HostManagement",  
        "Parameters": [  
            {  
                "Name": "any-host-based-license-configuration",  
                "Values": [  
                    "true"  
                ]  
            }  
        ]  
    },  
    {  
        "Type": "AWS::ResourceGroups::Generic",  
        "Parameters": [  
            {  
                "Name": "allowed-resource-types",  
                "Values": [  
                    "AWS::EC2::Host"  
                ]  
            },  
            {  
                "Name": "deletion-protection",  
                "Values": [  
                    "UNLESS_EMPTY"  
                ]  
            }  
        ]  
    }  
]
```

```
        },
    ],
    "Status": "UPDATE_COMPLETE"
}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetGroupQuery

Retrieves the resource query associated with the specified resource group. For more information about resource queries, see [Create a tag-based group in Resource Groups](#).

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:GetGroupQuery`

Request Syntax

```
POST /get-group-query HTTP/1.1
Content-type: application/json

{
    "Group": "string",
    "GroupName": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Group

The name or the ARN of the resource group to query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: (`arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`)

Required: No

GroupName

This parameter has been deprecated.

Don't use this parameter. Use Group instead.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\-.]+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "GroupQuery": {
    "GroupName": "string",
    "ResourceQuery": {
      "Query": "string",
      "Type": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GroupQuery

The resource query associated with the specified group. For more information about resource queries, see [Create a tag-based group in Resource Groups](#).

Type: [GroupQuery](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

This example illustrates one usage of GetGroupQuery.

Sample Request

```
POST /get-group-query HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.get-group-query
X-Amz-Date: 20220114T180718Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 19

{
    "Group": "MyTagQueryGroup"
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 14 Jan 2022 18:07:18 GMT
Content-Type: application/json
Content-Length: 206
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupQuery": {
        "GroupName": "MyTagQueryGroup",
        "ResourceQuery": {
            "Type": "TAG_FILTERS_1_0",
            "Query": "{\"ResourceTypeFilters\":[\"AWS::EC2::Instance\"],\"TagFilters\":[{\"Key\":\"Name\", \"Values\":[\"WebServers\"]}]}"
        }
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTags

Returns a list of tags that are associated with a resource group, specified by an ARN.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:GetTags`

Request Syntax

```
GET /resources/Arn/tags HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Arn

The ARN of the resource group whose tags you want to retrieve.

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: `arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
```

```
"Tags": {  
    "string" : "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the tagged resource group.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}

Tags

The tags associated with the specified resource group.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^([\p{L}\p{Z}\p{N}_.:=/=+\-@]*)\$

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: ^([\p{L}\p{Z}\p{N}_.:=/=+\-@]*)\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example retrieves the tags attached to the resource group with this ARN:

```
arn:aws:resource-groups:us-east-1:123456789012:group/MyGroup/tags
```

by querying the service's endpoint in us-east-1. Note that the ARN must be [URL encoded](#).

Sample Request

```
GET /resources/arn%3Aaws%3Aresource-groups%3Aus-east-1%3A123456789012%3Agroup%2FMyGroup/tags HTTP/1.1
```

```
Host: resource-groups.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.get-tags
X-Amz-Date: 20211201T173340Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
```

Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 14 Jan 2022 18:40:33 GMT
Content-Type: application/json
Content-Length: 97
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "Arn": "arn:aws:resource-groups:us-east-1:123456789012:group/MyGroup",
    "Tags": {
        "Stage": "Production"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GroupResources

Adds the specified resources to the specified group.

Important

You can use this operation with only resource groups that are configured with the following types:

- AWS::EC2::HostManagement
- AWS::EC2::CapacityReservationPool

Other resource group type and resource types aren't currently supported by this operation.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:GroupResources`

Request Syntax

```
POST /group-resources HTTP/1.1
Content-type: application/json

{
    "Group": "string",
    "ResourceArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Group

The name or the ARN of the resource group to add resources to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `(arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`

Required: Yes

ResourceArns

The list of ARNs of the resources to be added to the group.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: `arn:aws(-[a-z]+)*:[a-zA-Z0-9_\.-]*:([a-z]{2}(-[a-z]+)+-\d{1})?:([0-9]{12})?::.+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FailedErrorCodeErrorMessageResourceArnPendingResourceArn
```

```
],  
  "Succeeded}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Failed

A list of ARNs of any resources that this operation failed to add to the group.

Type: Array of [FailedResource](#) objects

Pending

A list of ARNs of any resources that this operation is still in the process adding to the group. These pending additions continue asynchronously. You can check the status of pending additions by using the [ListGroupResources](#) operation, and checking the Resources array in the response and the Status field of each object in that array.

Type: Array of [PendingResource](#) objects

Succeeded

A list of ARNs of the resources that this operation successfully added to the group.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: arn:aws(-[a-z]+)*:[a-zA-Z0-9\-_]*:([a-z]{2}(-[a-z]+)+-\d{1})?:([0-9]{12})?::.+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example adds two Amazon EC2 capacity reservations to the specified resource group. The group is configured to allow only capacity reservations as group members.

Sample Request

```
POST /group-resources HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
```

```
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.group-resources
X-Amz-Date: 20220114T203701Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 199

{
    "Group": "CRPGroup",
    "ResourceArns": [
        "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-0070b00d13EXAMPLE",
        "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-061abec820EXAMPLE"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 14 Jan 2022 20:37:01 GMT
Content-Type: application/json
Content-Length: 119
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "Succeeded": [
        "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-0070b00d13EXAMPLE",
        "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-061abec820EXAMPLE"
    ],
    "Failed": [],
    "Pending": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListGroupResources

Returns a list of ARNs of the resources that are members of a specified resource group.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:ListGroupResources`
- `cloudformation:DescribeStacks`
- `cloudformation>ListStackResources`
- `tag:GetResources`

Request Syntax

```
POST /list-group-resources HTTP/1.1
Content-type: application/json

{
  "FiltersNameValuesGroupGroupNameMaxResultsNextToken
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Filters

Filters, formatted as [ResourceFilter](#) objects, that you want to apply to a `ListGroupResources` operation. Filters the results to include only those of the specified resource types.

- `resource-type` - Filter resources by their type. Specify up to five resource types in the format `AWS::ServiceCode::ResourceType`. For example, `AWS::EC2::Instance`, or `AWS::S3::Bucket`.

When you specify a `resource-type` filter for `ListGroupResources`, AWS Resource Groups validates your filter resource types against the types that are defined in the query associated with the group. For example, if a group contains only S3 buckets because its query specifies only that resource type, but your `resource-type` filter includes EC2 instances, AWS Resource Groups does not filter for EC2 instances. In this case, a `ListGroupResources` request returns a `BadRequestException` error with a message similar to the following:

The resource types specified as filters in the request are not valid.

The error includes a list of resource types that failed the validation because they are not part of the query associated with the group. This validation doesn't occur when the group query specifies `AWS::AllSupported`, because a group based on such a query can contain any of the allowed resource types for the query type (tag-based or Amazon CloudFront stack-based queries).

Type: Array of [ResourceFilter](#) objects

Required: No

Group

The name or the ARN of the resource group

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `(arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`

Required: No

GroupName

⚠ Important

Deprecated - don't use this parameter. Use the Group request field instead.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\.-]+

Required: No

MaxResults

The total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the maximum you specify, the NextToken response element is present and has a value (is not null). Include that value as the NextToken request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

NextToken

The parameter for receiving additional results if you receive a NextToken response in a previous request. A NextToken response indicates that more output is available. Set this parameter to the value provided by a previous call's NextToken response to indicate where the output should continue from.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: ^[a-zA-Z0-9+/-]{0,2}\$

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "NextToken": "string",
    "QueryErrors": [
        {
            "ErrorCode": "string",
            "Message": "string"
        }
    ],
    "ResourceIdentifiers": [
        {
            "ResourceArn": "string",
            "ResourceType": "string"
        }
    ],
    "Resources": [
        {
            "Identifier": {
                "ResourceArn": "string",
                "ResourceType": "string"
            },
            "Status": {
                "Name": "string"
            }
        }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

If present, indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: ^[a-zA-Z0-9+/-]{0,2}\$

QueryErrors

A list of QueryError objects. Each error contains an ErrorCode and Message.

Possible values for ErrorCode are CLOUDFORMATION_STACK_INACTIVE, CLOUDFORMATION_STACK_NOT_EXISTING, CLOUDFORMATION_STACK_UNASSUMABLE_ROLE and RESOURCE_TYPE_NOT_SUPPORTED.

Type: Array of [QueryError](#) objects

Resourceldentifiers

Important

Deprecated - don't use this parameter. Use the Resources response field instead.

Type: Array of [Resourcelentifier](#) objects

Resources

An array of resources from which you can determine each resource's identity, type, and group membership status.

Type: Array of [ListGroupResourcesItem](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

UnauthorizedException

The request was rejected because it doesn't have valid credentials for the target resource.

HTTP Status Code: 401

Examples

Example

This example illustrates one usage of ListGroupResources.

Sample Request

```
POST /list-group-resources HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.list-group-resources
X-Amz-Date: 20220114T205755Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 21

{
  "Group": "CRPGroup"
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 14 Jan 2022 20:57:55 GMT
Content-Type: application/json
Content-Length: 654
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
  "Resources": [
    {
      "Identifier": {
        "ResourceArn": "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/
cr-0070b00d13EXAMPLE",
        "ResourceType": "AWS::EC2::CapacityReservation"
      }
    },
    {
      "Identifier": {
        "ResourceArn": "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/
cr-061abec820EXAMPLE",
        "ResourceType": "AWS::EC2::CapacityReservation"
      }
    }
  ]
}
```

```
        }
    ],
    "QueryErrors": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListGroups

Returns a list of existing Resource Groups in your account.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:ListGroup`

Request Syntax

```
POST /groups-list?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
Content-type: application/json

{
  "FiltersNamestring",
      "Valuesstring" ]
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the maximum you specify, the `NextToken` response element is present and has a value (is not null). Include that value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Valid Range: Minimum value of 1. Maximum value of 50.

NextToken

The parameter for receiving additional results if you receive a NextToken response in a previous request. A NextToken response indicates that more output is available. Set this parameter to the value provided by a previous call's NextToken response to indicate where the output should continue from.

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: ^[a-zA-Z0-9+/-]*={0,2}\$

Request Body

The request accepts the following data in JSON format.

Filters

Filters, formatted as [GroupFilter](#) objects, that you want to apply to a ListGroups operation.

- resource-type - Filter the results to include only those resource groups that have the specified resource type in their ResourceTypeFilter. For example, AWS::EC2::Instance would return any resource group with a ResourceTypeFilter that includes AWS::EC2::Instance.
- configuration-type - Filter the results to include only those groups that have the specified configuration types attached. The current supported values are:
 - AWS::AppRegistry::Application
 - AWS::AppRegistry::ApplicationResourceGroups
 - AWS::CloudFormation::Stack
 - AWS::EC2::CapacityReservationPool
 - AWS::EC2::HostManagement
 - AWS::NetworkFirewall::RuleGroup

Type: Array of [GroupFilter](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "GroupIdentifiers": [
        {
            "GroupArnGroupNameGroups": [
        {
            "DescriptionGroupArnNameNextToken
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

GroupIdentifiers

A list of [GroupIdentifier](#) objects. Each identifier is an object that contains both the Name and the GroupArn.

Type: Array of [GroupIdentifier](#) objects

Groups

⚠ Important

Deprecated - don't use this field. Use the [GroupIdentifiers](#) response field instead.

Type: Array of [Group](#) objects

NextToken

If present, indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: ^[a-zA-Z0-9+/-]{0,2}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example lists all of the resource groups in the specified AWS Region and account.

Sample Request

```
POST /groups-list HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.list-groups
X-Amz-Date: 20220119T231526Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 0
```

Sample Response

```
HTTP/1.1 200 OK
Date: Wed, 19 Jan 2022 23:15:26 GMT
Content-Type: application/json
Content-Length: 5655
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupIdentifiers": [
        {
            "GroupName": "Group1",
            "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/Group1",
            "OwnerId": "123456789012"
        },
        {
            "GroupName": "Group2",
            "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/Group2",
            "OwnerId": "123456789012"
        },
    ],
}
```

```
{  
    "GroupName": "Group3",  
    "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/Group3",  
    "OwnerId": "123456789012"  
}  
,  
"Groups": [ ... DEPRECATED ... DO NOT USE ... ]  
}
```

Example

The following example lists all resource groups that are configured with a configuration type of AWS::EC2::HostManagement.

Sample Request

```
POST /groups-list HTTP/1.1  
Host: resource-groups.us-west-2.amazonaws.com  
Accept-Encoding: identity  
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/  
resource-groups.list-groups  
X-Amz-Date: 20220119T232648Z  
X-Amz-Security-Token: <SECURITY-TOKEN>  
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/  
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-  
token,Signature=<SIGV4-SIGNATURE>  
Content-Length: 85  
  
{  
    "Filters": [  
        {  
            "Name": "configuration-type",  
            "Values": [  
                "AWS::EC2::HostManagement"  
            ]  
        }  
    ]  
}
```

Sample Response

```
HTTP/1.1 200 OK  
Date: Wed, 19 Jan 2022 23:26:48 GMT
```

```
Content-Type: application/json
Content-Length: 621
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupIdentifiers": [
        {
            "GroupName": "HostManagementGroup1",
            "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/
HostManagementGroup1",
            "OwnerId": "123456789012"
        },
        {
            "GroupName": "HostManagementGroup2",
            "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/
HostManagementGroup2",
            "OwnerId": "123456789012"
        }
    ],
    "Groups": [ ... DEPRECATED ... DO NOT USE ... ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutGroupConfiguration

Attaches a service configuration to the specified group. This occurs asynchronously, and can take time to complete. You can use [GetGroupConfiguration](#) to check the status of the update.

Minimum permissions

To run this command, you must have the following permissions:

- resource-groups:PutGroupConfiguration

Request Syntax

```
POST /put-group-configuration HTTP/1.1
Content-type: application/json

{
  "ConfigurationParametersNamestring",
          "Valuesstring" ]
        }
      ],
      "Typestring"
    }
  ],
  "Groupstring"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Configuration

The new configuration to associate with the specified group. A configuration associates the resource group with an AWS service and specifies how the service can interact with the resources in the group. A configuration is an array of [GroupConfigurationItem](#) elements.

For information about the syntax of a service configuration, see [Service configurations for Resource Groups](#).

 **Note**

A resource group can contain either a Configuration or a ResourceQuery, but not both.

Type: Array of [GroupConfigurationItem](#) objects

Array Members: Maximum number of 2 items.

Required: No

Group

The name or ARN of the resource group with the configuration that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `(arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`

Required: No

Response Syntax

HTTP/1.1 202

Response Elements

If the action is successful, the service sends back an HTTP 202 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example 1: Configure a resource group to contain Amazon EC2 capacity reservations

The following example attaches a configuration that limits the group to containing Amazon EC2 capacity reservations.

Sample Request

```
POST /put-group-configuration HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.put-group-configuration
X-Amz-Date: 20220120T204033Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 226

{
    "Group": "CRPGroup",
    "Configuration": [
        {
            "Type": "AWS::EC2::CapacityReservationPool"
        },
        {
            "Type": "AWS::ResourceGroups::Generic",
            "Parameters": [
                {
                    "Name": "allowed-resource-types",
                    "Values": [
                        "AWS::EC2::CapacityReservation"
                    ]
                }
            ]
        }
    ]
}
```

Sample Response

```
HTTP/1.1 202 Accepted
Date: Thu, 20 Jan 2022 20:40:33 GMT
Content-Type: application/json
Content-Length: 337
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupIdentifier": {
        "GroupName": "CRPGroup",
        "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/CRPGroup"
    },
    "GroupConfiguration": {
        "Configuration": [
            {
                "Type": "AWS::EC2::CapacityReservationPool"
            },
            {
                "Type": "AWS::ResourceGroups::Generic",
                "Parameters": [
                    {
                        "Name": "allowed-resource-types",
                        "Values": [
                            "AWS::EC2::CapacityReservation"
                        ]
                    }
                ]
            }
        ]
    }
}
```

Example 2: Configure a resource group to contain Amazon EC2 hosts of family type C5 with license support

The following example attaches a configuration to the resource group that limits the group to containing only Amazon EC2 hosts and provides settings that are enforced on any Amazon EC2 instances that are launched into this group.

Sample Request

```
POST /put-group-configuration HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.put-group-configuration
X-Amz-Date: 20220120T204033Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 314

{
    "Group": "HostManagementGroup",
    "Configuration": [
        {
            "Type": "AWS::EC2::HostManagement",
            "Parameters": [
                {
                    "Name": "any-host-based-license-configuration",
                    "Values": ["true"]
                },
                {
                    "Name": "allowed-host-families",
                    "Values": ["c5"]
                }
            ]
        },
        {
            "Type": "AWS::ResourceGroups::Generic",
            "Parameters": [
                {
                    "Name": "allowed-resource-types",
                    "Values": ["AWS::EC2::Host"]
                },
                {
                    "Name": "deletion-protection",
                    "Values": ["UNLESS_EMPTY"]
                }
            ]
        }
    ]
}
```

```
}
```

Sample Response

```
HTTP/1.1 202 Accepted
Date: Thu, 20 Jan 2022 20:40:33 GMT
Content-Type: application/json
Content-Length: 337
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupIdentifier": {
        "GroupName": "HostManagementGroup",
        "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/HostManagementGroup"
    },
    "GroupConfiguration": {
        "Configuration": [
            {
                "Type": "AWS::EC2::HostManagement",
                "Parameters": [
                    {
                        "Name": "any-host-based-license-configuration",
                        "Values": ["true"]
                    },
                    {
                        "Name": "allowed-host-families",
                        "Values": ["c5"]
                    }
                ]
            },
            {
                "Type": "AWS::ResourceGroups::Generic",
                "Parameters": [
                    {
                        "Name": "allowed-resource-types",
                        "Values": ["AWS::EC2::Host"]
                    },
                    {
                        "Name": "deletion-protection",

```

```
        "Values": ["UNLESS_EMPTY"]
    }
]
}
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SearchResources

Returns a list of AWS resource identifiers that matches the specified query. The query uses the same format as a resource query in a [CreateGroup](#) or [UpdateGroupQuery](#) operation.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:SearchResources`
- `cloudformation:DescribeStacks`
- `cloudformation>ListStackResources`
- `tag:GetResources`

Request Syntax

```
POST /resources/search HTTP/1.1
Content-type: application/json

{
    "MaxResults": number,
    "NextToken": "string",
    "ResourceQuery": {
        "Query": "string",
        "Type": "string"
    }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[ResourceQuery](#)

The search query, using the same formats that are supported for resource group definition. For more information, see [CreateGroup](#).

Type: [ResourceQuery object](#)

Required: Yes

[MaxResults](#)

The total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the maximum you specify, the NextToken response element is present and has a value (is not null). Include that value as the NextToken request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

[NextToken](#)

The parameter for receiving additional results if you receive a NextToken response in a previous request. A NextToken response indicates that more output is available. Set this parameter to the value provided by a previous call's NextToken response to indicate where the output should continue from.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: ^[a-zA-Z0-9+/-]*={0,2}\\$

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "NextToken": "string",
```

```
"QueryErrors": [  
    {  
        "ErrorCode": "string",  
        "Message": "string"  
    }  
,  
    "ResourceIdentifiers": [  
        {  
            "ResourceArn": "string",  
            "ResourceType": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

If present, indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 8192.

Pattern: ^[a-zA-Z0-9+/]*={0,2}\$

QueryErrors

A list of QueryError objects. Each error contains an ErrorCode and Message.

Possible values for ErrorCode:

- CLOUDFORMATION_STACK_INACTIVE
- CLOUDFORMATION_STACK_NOT_EXISTING
- CLOUDFORMATION_STACK_UNASSUMABLE_ROLE

Type: Array of [QueryError](#) objects

Resourcelidentifiers

The ARNs and resource types of resources that are members of the group that you specified.

Type: Array of [Resourcelidentifier](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

UnauthorizedException

The request was rejected because it doesn't have valid credentials for the target resource.

HTTP Status Code: 401

Examples

Example

The following example retrieves a list of resources of all types that are tagged with a key of Stage and a value of either Test or Prod.

Sample Request

```
POST /resources/search HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.search-resources
X-Amz-Date: 20220120T213215Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 176

{
    "ResourceQuery": {
        "Query": "{\"ResourceTypeFilters\":[\"AWS::AllSupported\"],\"TagFilters\": [{\"Key\":\"Stage\", \"Values\":[\"Test\", \"Prod\"]}]}",
        "Type": "TAG_FILTERS_1_0"
    }
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 20 Jan 2022 21:32:15 GMT
Content-Type: application/json
Content-Length: 161
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "ResourceIdentifiers": [
```

```
{  
    "ResourceArn": "arn:aws:ec2:us-west-2:123456789012:dhcp-options/  
dopt-1a2b3c4d",  
    "ResourceType": "AWS::EC2::DHCPOptions"  
}  
,  
"QueryErrors": []  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Tag

Adds tags to a resource group with the specified ARN. Existing tags on a resource group are not changed if they are not specified in the request parameters.

Important

Do not store personally identifiable information (PII) or other confidential or sensitive information in tags. We use tags to provide you with billing and administration services. Tags are not intended to be used for private or sensitive data.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:Tag`

Request Syntax

```
PUT /resources/Arn/tags HTTP/1.1
Content-type: application/json

{
  "Tags": {
    "string": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

Arn

The ARN of the resource group to which to add tags.

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: `arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Tags

The tags to add to the specified resource group. A tag is a string-to-string map of key-value pairs.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^([\p{L}\p{Z}]\p{N}_.:/=+\-@]*$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^([\p{L}\p{Z}]\p{N}_.:/=+\-@]*$`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Arn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the tagged resource.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}

Tags

The tags that have been added to the specified resource group.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: ^([\p{L}\p{Z}\p{N}_.:=/=+\-@]*)\$

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: ^([\p{L}\p{Z}\p{N}_.:=/=+\-@]*)\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example attaches two tags to the specified resource group. The first tag has a key of Department and a value of Finance, and the second has a key of Env and a value of Prod. Note that this tags only the group itself; it doesn't tag any members of the group.

The ARN in the PUT element must be [URL encoded](#).

Sample Request

```
PUT /resources/arn%3Aaws%3Aresource-groups%3Aus-west-2%3A123456789012%3Agroup%2FMyTest/tags HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/resource-groups.tag
X-Amz-Date: 20220120T220458Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-token,Signature=<SIGV4-SIGNATURE>
```

```
Content-Length: 50

{
    "Tags": {
        "Department": "Finance",
        "Env": "Prod"
    }
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 20 Jan 2022 22:04:58 GMT
Content-Type: application/json
Content-Length: 114
x-amzn-RequestId: <VARIABLES>
x-amz-apigw-id: <VARIABLES>
X-Amzn-Trace-Id: Root=<VARIABLES>
Connection: keep-alive

{
    "Arn": "arn:aws:resource-groups:us-west-2:123456789012:group/MyTest",
    "Tags": {
        "Department": "Finance",
        "Env": "Prod"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UngroupResources

Removes the specified resources from the specified group. This operation works only with static groups that you populated using the [GroupResources](#) operation. It doesn't work with any resource groups that are automatically populated by tag-based or AWS CloudFormation stack-based queries.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:UngroupResources`

Request Syntax

```
POST /ungroup-resources HTTP/1.1
Content-type: application/json

{
  "Group": "string",
  "ResourceArnsstring" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Group

The name or the ARN of the resource group from which to remove the resources.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: (`arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}`)

Required: Yes

ResourceArns

The ARNs of the resources to be removed from the group.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: `arn:aws(-[a-z]+)*:[a-zA-Z0-9\-\-]*:([a-zA-Z]{2})(-[a-zA-Z]+)\d{1}\d{12}?:\.\+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "FailedErrorCodeErrorMessageResourceArnPendingResourceArnSucceeded
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Failed

A list of any resources that failed to be removed from the group by this operation.

Type: Array of [FailedResource](#) objects

Pending

A list of any resources that are still in the process of being removed from the group by this operation. These pending removals continue asynchronously. You can check the status of pending removals by using the [ListGroupResources](#) operation. After the resource is successfully removed, it no longer appears in the response.

Type: Array of [PendingResource](#) objects

Succeeded

A list of resources that were successfully removed from the group by this operation.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: arn:aws(-[a-z]+)*:[a-z0-9\-\-]*:([a-z]{2}(-[a-z]+)-\d{1})?:(\d{12})?::.+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example removes two resources from the specified group.

Sample Request

```
POST /ungroup-resources HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.ungroup-resources
X-Amz-Date: 20220114T205720Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 199

{
    "Group": "CRPGroup",
    "ResourceArns": [
        "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-0070b00d13EXAMPLE",
```

```
        "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-061abec820EXAMPLE"
    ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 14 Jan 2022 20:57:20 GMT
Content-Type: application/json
Content-Length: 198
x-amzn-RequestId: <VARIABLE>
x-amz-apigw-id: <VARIABLE>
X-Amzn-Trace-Id: Root=<VARIABLE>
Connection: keep-alive

{
  "Succeeded": [
    "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-0070b00d13EXAMPLE",
    "arn:aws:ec2:us-west-2:123456789012:capacity-reservation/cr-061abec820EXAMPLE"
  ],
  "Failed": [],
  "Pending": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Untag

Deletes tags from a specified resource group.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:Untag`

Request Syntax

```
PATCH /resources/Arn/tags HTTP/1.1
Content-type: application/json

{
  "Keysstring" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

Arn

The ARN of the resource group from which to remove tags. The command removed both the specified keys and any values associated with those keys.

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: `arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Keys

The keys of the tags to be removed.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^([\p{L}\p{Z}\p{N}_.:=/=+\-@\"]*)\$

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "Keys": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN of the resource group from which tags have been removed.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}

Keys

The keys of the tags that were removed.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^([\p{L}\p{Z}\p{N}_.:/-+@\"]*)\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example removes the tag with the key Department from the specified resource group. Note that this updates the tags on only the group itself; it doesn't touch the tags on any group members.

The ARN in the PATCH element must be [URL encoded](#).

Sample Request

```
PATCH /resources/arn%3Aaws%3Aresource-groups%3Aus-west-2%3A123456789012%3Agroup
%2FMyTest/tags HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.untag
X-Amz-Date: 20220120T221301Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 24

{
  "Keys": [
    "Department"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 20 Jan 2022 22:13:01 GMT
Content-Type: application/json
Content-Length: 91
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive
```

```
{  
    "Arn": "arn:aws:resource-groups:us-west-2:123456789012:group/MyTest",  
    "Keys": [  
        "Department"  
    ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAccountSettings

Turns on or turns off optional features in Resource Groups.

The preceding example shows that the request to turn on group lifecycle events is IN_PROGRESS. You can call the [GetAccountSettings](#) operation to check for completion by looking for GroupLifecycleEventsStatus to change to ACTIVE.

Request Syntax

```
POST /update-account-settings HTTP/1.1
Content-type: application/json

{
    "GroupLifecycleEventsDesiredStatus": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[GroupLifecycleEventsDesiredStatus](#)

Specifies whether you want to turn [group lifecycle events](#) on or off.

Type: String

Valid Values: ACTIVE | INACTIVE

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
    "AccountSettings": {  
        "GroupLifecycleEventsDesiredStatus": "string",  
        "GroupLifecycleEventsStatus": "string",  
        "GroupLifecycleEventsStatusMessage": "string"  
    }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccountSettings](#)

A structure that displays the status of the optional features in the account.

Type: [AccountSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example turns on the group lifecycle events setting for the calling AWS account:

Sample Request

```
POST /update-account-settings HTTP/1.1
Host: resource-groups.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: <VARIES>
X-Amz-Date: 20221213T215349Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 47

{
    "GroupLifecycleEventsDesiredStatus": "ACTIVE"
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Tue, 13 Dec 2022 21:53:49 GMT
Content-Type: application/json
Content-Length: 109
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive
```

```
{  
    "AccountSettings": {  
        "GroupLifecycleEventsDesiredStatus": "ACTIVE",  
        "GroupLifecycleEventsStatus": "IN_PROGRESS"  
    }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateGroup

Updates the description for an existing group. You cannot update the name of a resource group.

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:UpdateGroup`

Request Syntax

```
POST /update-group HTTP/1.1
Content-type: application/json

{
    "DescriptionGroupGroupName
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Description

The new description that you want to update the resource group with. Descriptions can contain letters, numbers, hyphens, underscores, periods, and spaces.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: [\sa-zA-Z0-9\.\-]*

Required: No

Group

The name or the ARN of the resource group to modify.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: (arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}

Required: No

GroupName

This parameter has been deprecated.

Don't use this parameter. Use Group instead.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\.-]+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Group": {
    "DescriptionGroupArn": "string",
    "Name": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Group

The update description of the resource group.

Type: [Group](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example adds or updates the description attached to the specified resource group.

Sample Request

```
POST /update-group HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.update-group
X-Amz-Date: 20220120T224252Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 51

{
    "Group": "MyTest",
    "Description": "My Test group"
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 20 Jan 2022 22:42:52 GMT
Content-Type: application/json
Content-Length: 155
x-amzn-RequestId: <VRIES>
x-amz-apigw-id: <VRIES>
X-Amzn-Trace-Id: Root=<VRIES>
Connection: keep-alive

{
    "Group": {
        "GroupArn": "arn:aws:resource-groups:us-west-2:123456789012:group/MyTest",
        "Name": "MyTest",
```

```
        "Description": "My Test group",
        "OwnerId": "123456789012"
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateGroupQuery

Updates the resource query of a group. For more information about resource queries, see [Create a tag-based group in Resource Groups](#).

Minimum permissions

To run this command, you must have the following permissions:

- `resource-groups:UpdateGroupQuery`

Request Syntax

```
POST /update-group-query HTTP/1.1
Content-type: application/json

{
  "Group": "string",
  "GroupName": "string",
  "ResourceQuery": {
    "Query": "string",
    "Type": "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ResourceQuery

The resource query to determine which AWS resources are members of this resource group.

Note

A resource group can contain either a Configuration or a ResourceQuery, but not both.

Type: [ResourceQuery](#) object

Required: Yes

Group

The name or the ARN of the resource group to query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: (arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/)?[a-zA-Z0-9_\.-]{1,300}

Required: No

GroupName

This parameter has been deprecated.

Don't use this parameter. Use Group instead.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\.-]+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "GroupQuery": {  
    "GroupName": "string",  
    "ResourceQuery": {  
      "Query": "string",  
      "Type": "string"  
    }  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[GroupQuery](#)

The updated resource query associated with the resource group after the update.

Type: [GroupQuery](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

BadRequestException

The request includes one or more parameters that violate validation rules.

HTTP Status Code: 400

ForbiddenException

The caller isn't authorized to make the request. Check permissions.

HTTP Status Code: 403

InternalServerErrorException

An internal error occurred while processing the request. Try again later.

HTTP Status Code: 500

MethodNotAllowedException

The request uses an HTTP method that isn't allowed for the specified resource.

HTTP Status Code: 405

NotFoundException

One or more of the specified resources don't exist.

HTTP Status Code: 404

TooManyRequestsException

You've exceeded throttling limits by making too many requests in a period of time.

HTTP Status Code: 429

Examples

Example

The following example updates the query of the specified resource group. A resource group query requires that you supply both a Type parameter and a Query string parameter. The Query parameter is a JSON representation of the query as a single string.

Sample Request

```
POST /update-group-query HTTP/1.1
Host: resource-groups.us-west-2.amazonaws.com
Accept-Encoding: identity
User-Agent: aws-cli/2.2.40 Python/3.8.8 Windows/10 exe/AMD64 prompt/off command/
resource-groups.update-group-query
X-Amz-Date: 20220120T225422Z
X-Amz-Security-Token: <SECURITY-TOKEN>
Authorization: AWS4-HMAC-SHA256 Credential=<ACCESS-KEY>/20220113/us-west-2/
resource-groups/aws4_request,SignedHeaders=host;x-amz-date;x-amz-security-
token,Signature=<SIGV4-SIGNATURE>
Content-Length: 197

{
    "GroupName": "MyTest",
    "ResourceQuery": {
```

```
"Type": "TAG_FILTERS_1_0",
"Query": "{\"ResourceTypeFilters\":[\"AWS::EC2::Instance\"],\"TagFilters\":
[{\\"Key\\\":\"Name\", \\"Values\":[\"WebServers\"]}]}"}}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 20 Jan 2022 22:54:23 GMT
Content-Type: application/json
Content-Length: 206
x-amzn-RequestId: <VARIES>
x-amz-apigw-id: <VARIES>
X-Amzn-Trace-Id: Root=<VARIES>
Connection: keep-alive

{
    "GroupQuery": {
        "GroupName": "MyTest",
        "ResourceQuery": {
            "Type": "TAG_FILTERS_1_0",
            "Query": "{\"ResourceTypeFilters\":[\"AWS::EC2::Instance\"],\"TagFilters\":
[{\\"Key\\\":\"Name\", \\"Values\":[\"WebServers\"]}]}"}
        }
    }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

Data Types

The AWS Resource Groups API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccountSettings](#)
- [FailedResource](#)
- [Group](#)
- [GroupConfiguration](#)
- [GroupConfigurationItem](#)
- [GroupConfigurationParameter](#)
- [GroupFilter](#)
- [GroupIdentifier](#)
- [GroupQuery](#)
- [ListGroupResourcesItem](#)
- [PendingResource](#)
- [QueryError](#)
- [ResourceFilter](#)
- [ResourceIdentifier](#)
- [ResourceQuery](#)
- [ResourceStatus](#)

AccountSettings

The Resource Groups settings for this AWS account.

Contents

Note

In the following list, the required parameters are described first.

GroupLifecycleEventsDesiredStatus

The desired target status of the group lifecycle events feature. If

Type: String

Valid Values: ACTIVE | INACTIVE

Required: No

GroupLifecycleEventsStatus

The current status of the group lifecycle events feature.

Type: String

Valid Values: ACTIVE | INACTIVE | IN_PROGRESS | ERROR

Required: No

GroupLifecycleEventsStatusMessage

The text of any error message occurs during an attempt to turn group lifecycle events on or off.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FailedResource

A resource that failed to be added to or removed from a group.

Contents

Note

In the following list, the required parameters are described first.

ErrorCode

The error code associated with the failure.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

ErrorMessage

The error message text associated with the failure.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

ResourceArn

The ARN of the resource that failed to be added or removed.

Type: String

Pattern: `arn:aws(-[a-z]+)*:[a-zA-Z0-9\-_]*:(\w{2}(-\w+)+-\d{1})?:(\w{0-9}\{12\})?:\.\+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Group

A resource group that contains AWS resources. You can assign resources to the group by associating either of the following elements with the group:

- [ResourceQuery](#) - Use a resource query to specify a set of tag keys and values. All resources in the same AWS Region and AWS account that have those keys with the same values are included in the group. You can add a resource query when you create the group, or later by using the [PutGroupConfiguration](#) operation.
- [GroupConfiguration](#) - Use a service configuration to associate the group with an AWS service. The configuration specifies which resource types can be included in the group.

Contents

Note

In the following list, the required parameters are described first.

GroupArn

The ARN of the resource group.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: `arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}`

Required: Yes

Name

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `[a-zA-Z0-9_\.-]+`

Required: Yes

Description

The description of the resource group.

Type: String

Length Constraints: Maximum length of 1024.

Pattern: [\sa-zA-Z0-9_\.-]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GroupConfiguration

A service configuration associated with a resource group. The configuration options are determined by the AWS service that defines the Type, and specifies which resources can be included in the group. You can add a service configuration when you create the group by using [CreateGroup](#), or later by using the [PutGroupConfiguration](#) operation. For details about group service configuration syntax, see [Service configurations for resource groups](#).

Contents

Note

In the following list, the required parameters are described first.

Configuration

The configuration currently associated with the group and in effect.

Type: Array of [GroupConfigurationItem](#) objects

Array Members: Maximum number of 2 items.

Required: No

FailureReason

If present, the reason why a request to update the group configuration failed.

Type: String

Required: No

ProposedConfiguration

If present, the new configuration that is in the process of being applied to the group.

Type: Array of [GroupConfigurationItem](#) objects

Array Members: Maximum number of 2 items.

Required: No

Status

The current status of an attempt to update the group configuration.

Type: String

Valid Values: UPDATING | UPDATE_COMPLETE | UPDATE_FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GroupConfigurationItem

An item in a group configuration. A group service configuration can have one or more items. For details about group service configuration syntax, see [Service configurations for resource groups](#).

Contents

Note

In the following list, the required parameters are described first.

Type

Specifies the type of group configuration item. Each item must have a unique value for type. For the list of types that you can specify for a configuration item, see [Supported resource types and parameters](#).

Type: String

Length Constraints: Maximum length of 40.

Pattern: AWS ::[a-zA-Z0-9]+ ::[a-zA-Z0-9]+

Required: Yes

Parameters

A collection of parameters for this group configuration item. For the list of parameters that you can use with each configuration item type, see [Supported resource types and parameters](#).

Type: Array of [GroupConfigurationParameter](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GroupConfigurationParameter

A parameter for a group configuration item. For details about group service configuration syntax, see [Service configurations for resource groups](#).

Contents

Note

In the following list, the required parameters are described first.

Name

The name of the group configuration parameter. For the list of parameters that you can use with each configuration item type, see [Supported resource types and parameters](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 80.

Pattern: [a-zA-Z0-9:\/_\-_]+

Required: Yes

Values

The value or values to be used for the specified parameter. For the list of values you can use with each parameter, see [Supported resource types and parameters](#).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9:\/_\-_]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GroupFilter

A filter collection that you can use to restrict the results from a `List` operation to only those you want to include.

Contents

Note

In the following list, the required parameters are described first.

Name

The name of the filter. Filter names are case-sensitive.

Type: String

Valid Values: `resource-type` | `configuration-type`

Required: Yes

Values

One or more filter values. Allowed filter values vary by group filter name, and are case-sensitive.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `AWS::(AllSupported|[a-zA-Z0-9]+:[a-zA-Z0-9]+)`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GroupIdentifier

The unique identifiers for a resource group.

Contents

Note

In the following list, the required parameters are described first.

GroupArn

The ARN of the resource group.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 1600.

Pattern: `arn:aws(-[a-z]+)*:resource-groups:[a-z]{2}(-[a-z]+)+-\d{1}:[0-9]{12}:group/[a-zA-Z0-9_\.-]{1,300}`

Required: No

GroupName

The name of the resource group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `[a-zA-Z0-9_\.-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GroupQuery

A mapping of a query attached to a resource group that determines the AWS resources that are members of the group.

Contents

Note

In the following list, the required parameters are described first.

GroupName

The name of the resource group that is associated with the specified resource query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: [a-zA-Z0-9_\.-]+

Required: Yes

ResourceQuery

The resource query that determines which AWS resources are members of the associated resource group.

Type: [ResourceQuery object](#)

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListGroupResourcesItem

A structure returned by the [ListGroupResources](#) operation that contains identity and group membership status information for one of the resources in the group.

Contents

 **Note**

In the following list, the required parameters are described first.

Identifier

A structure that contains the ARN of a resource and its resource type.

Type: [ResourceIdentifier](#) object

Required: No

Status

A structure that contains the status of this resource's membership in the group.

 **Note**

This field is present in the response only if the group is of type AWS::EC2::HostManagement.

Type: [ResourceStatus](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PendingResource

A structure that identifies a resource that is currently pending addition to the group as a member. Adding a resource to a resource group happens asynchronously as a background task and this one isn't completed yet.

Contents

Note

In the following list, the required parameters are described first.

ResourceArn

The Amazon resource name (ARN) of the resource that's in a pending state.

Type: String

Pattern: `arn:aws(-[a-z]+)*:[a-zA-Z0-9\-\-]*:([a-z]{2})(-[a-z]+)-\d{1})?:(\d{0-9}\{12\})?::.+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryError

A two-part error structure that can occur in `ListGroupResources` or `SearchResources`.

Contents

Note

In the following list, the required parameters are described first.

ErrorCode

Specifies the error code that was raised.

Type: String

Valid Values: CLOUDFORMATION_STACK_INACTIVE |
CLOUDFORMATION_STACK_NOT_EXISTING |
CLOUDFORMATION_STACK_UNASSUMABLE_ROLE | RESOURCE_TYPE_NOT_SUPPORTED

Required: No

Message

A message that explains the ErrorCode.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceFilter

A filter name and value pair that is used to obtain more specific results from a list of resources.

Contents

Note

In the following list, the required parameters are described first.

Name

The name of the filter. Filter names are case-sensitive.

Type: String

Valid Values: resource-type

Required: Yes

Values

One or more filter values. Allowed filter values vary by resource filter name, and are case-sensitive.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: AWS:::[a-zA-Z0-9]+::[a-zA-Z0-9]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Resourcelidentifier

A structure that contains the ARN of a resource and its resource type.

Contents

Note

In the following list, the required parameters are described first.

ResourceArn

The ARN of a resource.

Type: String

Pattern: arn:aws(-[a-z]+)*:[a-zA-Z0-9\-.]*:([a-z]{2}(-[a-z]+)+-\d{1})?:([0-9]{12})?::.+

Required: No

ResourceType

The resource type of a resource, such as AWS::EC2::Instance.

Type: String

Pattern: AWS::[a-zA-Z0-9]+::\w+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

ResourceQuery

The query you can use to define a resource group or a search for resources. A ResourceQuery specifies both a query Type and a Query string as JSON string objects. See the examples section for example JSON strings. For more information about creating a resource group with a resource query, see [Build queries and groups in AWS Resource Groups](#) in the *AWS Resource Groups User Guide*

When you combine all of the elements together into a single string, any double quotes that are embedded inside another double quote pair must be escaped by preceding the embedded double quote with a backslash character (\). For example, a complete ResourceQuery parameter must be formatted like the following CLI parameter example:

```
--resource-query '{"Type":"TAG_FILTERS_1_0","Query":"{\\"ResourceTypeFilters\\":\[\"AWS::AllSupported\"],\"TagFilters\":[{\\"Key\\\":\"Stage\",\"Values\\\":\[\"Test\"]}]}}"
```

In the preceding example, all of the double quote characters in the value part of the Query element must be escaped because the value itself is surrounded by double quotes. For more information, see [Quoting strings](#) in the *AWS Command Line Interface User Guide*.

For the complete list of resource types that you can use in the array value for ResourceTypeFilters, see [Resources you can use with AWS Resource Groups and Tag Editor](#) in the *AWS Resource Groups User Guide*. For example:

```
"ResourceTypeFilters": ["AWS::S3::Bucket", "AWS::EC2::Instance"]
```

Contents

Note

In the following list, the required parameters are described first.

Query

The query that defines a group or a search. The contents depends on the value of the Type element.

- **ResourceTypeFilters** – Applies to all ResourceQuery objects of either Type. This element contains one of the following two items:
 - The value AWS::AllSupported. This causes the ResourceQuery to match resources of any resource type that also match the query.
 - A list (a JSON array) of resource type identifiers that limit the query to only resources of the specified types. For the complete list of resource types that you can use in the array value for ResourceTypeFilters, see [Resources you can use with AWS Resource Groups and Tag Editor](#) in the *AWS Resource Groups User Guide*.

Example: "ResourceTypeFilters": ["AWS::AllSupported"] or
"ResourceTypeFilters": ["AWS::EC2::Instance", "AWS::S3::Bucket"]

- **TagFilters** – applicable only if Type = TAG_FILTERS_1_0. The Query contains a JSON string that represents a collection of simple tag filters. The JSON string uses a syntax similar to the [GetResources](#) operation, but uses only the [ResourceTypeFilters](#) and [TagFilters](#) fields. If you specify more than one tag key, only resources that match all tag keys, and at least one value of each specified tag key, are returned in your query. If you specify more than one value for a tag key, a resource matches the filter if it has a tag key value that matches *any* of the specified values.

For example, consider the following sample query for resources that have two tags, Stage and Version, with two values each:

```
[{"Stage": ["Test", "Deploy"]}, {"Version": ["1", "2"]} ]
```

The results of this resource query could include the following.

- An Amazon EC2 instance that has the following two tags: {"Stage": "Deploy"}, and {"Version": "2"}
- An S3 bucket that has the following two tags: {"Stage": "Test"}, and {"Version": "1"}

The resource query results would *not* include the following items in the results, however.

- An Amazon EC2 instance that has only the following tag: {"Stage": "Deploy"}.

The instance does not have **all** of the tag keys specified in the filter, so it is excluded from the results.

- An RDS database that has the following two tags: {"Stage": "Archived"} and {"Version": "4"}

The database has all of the tag keys, but none of those keys has an associated value that matches at least one of the specified values in the filter.

Example: "TagFilters": [{ "Key": "Stage", "Values": ["Gamma", "Beta"] }]

- **StackIdentifier** – applicable only if Type = CLOUDFORMATION_STACK_1_0. The value of this parameter is the Amazon Resource Name (ARN) of the AWS CloudFormation stack whose resources you want included in the group.

Type: String

Length Constraints: Maximum length of 4096.

Pattern: [\s\S]*

Required: Yes

Type

The type of the query to perform. This can have one of two values:

- *CLOUDFORMATION_STACK_1_0*: Specifies that you want the group to contain the members of an AWS CloudFormation stack. The Query contains a StackIdentifier element with an ARN for a CloudFormation stack.
- *TAG_FILTERS_1_0*: Specifies that you want the group to include resource that have tags that match the query.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^\w+\\$

Valid Values: TAG_FILTERS_1_0 | CLOUDFORMATION_STACK_1_0

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceStatus

A structure that identifies the current group membership status for a resource. Adding a resource to a resource group is performed asynchronously as a background task. A PENDING status indicates, for this resource, that the process isn't completed yet.

Contents

Note

In the following list, the required parameters are described first.

Name

The current status.

Type: String

Valid Values: PENDING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Making API requests

Query requests for the AWS Resource Groups are HTTP or HTTPS requests that use an HTTP verb such as GET or POST.

Resource Groups endpoints

An *endpoint* is a URL that serves as an entry point for a web service. You can select an appropriate AWS Region endpoint when you make your requests to reduce latency. For information about the endpoints used by Resource Groups, see [AWS Resource Groups](#) in the *Amazon Web Services General Reference*.

Query parameters

Each query request must include some common parameters to handle authentication and selection of an action. For more information, see [Common Parameters](#).

Some API operations take lists of parameters. These lists are specified using the following notation:

```
param.member.n
```

Values of n are integers starting from 1. All lists of parameters must follow this notation, including lists that contain only one parameter. A query parameter list looks like the following example.

```
&attribute.member.1=this  
&attribute.member.2=that
```

Request identifiers

In every response from an AWS Query API, there is a ResponseMetadata element, which contains a RequestId element. This string is a unique identifier that AWS assigns to provide tracking information. Although RequestId is included as part of every response, it isn't listed on the individual API documentation pages to improve readability and to reduce redundancy.

Query API authentication

You can send query requests over either HTTP or HTTPS. Regardless of which protocol you use, you must include a signature in every query request. For more information about creating and including a signature, see [Signing AWS API Requests](#) in the *Amazon Web Services General Reference*.

Available libraries

AWS provides libraries, sample code, tutorials, and other resources for software developers who prefer to build applications using language-specific APIs instead of the command-line tools and Query API. These libraries provide basic functions (not included in the APIs), such as request authentication, request retries, and error handling so that it's easier to get started. Resource Groups libraries and resources are available for the following languages and platforms:

- [AWS SDK for Go](#)
- [AWS SDK for Java 2.x](#)
- [AWS SDK for Java 1.x](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for JavaScript in Node.js](#)
- [AWS SDK for .NET](#)
- [AWS SDK for PHP](#)
- [AWS SDK for Python \(Boto\)](#)
- [AWS SDK for Ruby](#)
- [AWS SDK for Rust](#)

For more information about libraries and sample code in all languages, see [Sample Code & Libraries](#).

Making API requests using the POST method

If you don't use one of the AWS SDKs, you can make Resource Groups requests over HTTP using the POST request method. The POST method requires that you specify the operation in the header of the request and provide the data for the operation in JSON format in the body of the request.

Header name	Header value
Host	The AWS Resource Groups endpoint. For example: tagging.us-east-1.amazonaws.com
X-Amz-Date	<p>You must provide the timestamp in either the HTTP Date header or the AWS <i>x-amz-date</i> header. Some HTTP client libraries don't let you set the Date header. When an <i>x-amz-date</i> header is present, the system ignores any Date header during the request authentication.</p> <p>The <i>x-amz-date</i> header must be specified in ISO 8601 basic format. For example: 20130315T092054Z</p>
Authorization	The set of authorization parameters that AWS uses to ensure the validity and authenticity of the request. For more information about constructing this header, see Signature Version 4 Signing Process in the Amazon Web Services General Reference .
X-Amz-Target	<p>Specifies the Resource Groups namespace and version, and the operation that you want to perform.</p> <p>ResourceGroupsTaggingAPI_20170126. <i>API Name</i></p> <div style="border: 1px solid #ccc; padding: 10px; margin-top: 10px;"><p> Note</p><p>For the Resource Groups, always use the version 20170126.</p></div> <p>For example, to call the GetTagValues operation, use the following target value.</p> <p>ResourceGroupsTaggingAPI_20170126.GetTagValues</p>
Content-Type	Specifies the input format. Use the following value. application/json
Accept	Specifies the response format. Use the following value.

Header name	Header value
	application/json
Content-Length	Size of the payload in bytes.
Content-Encoding	Specifies the encoding format of the input and output. Use the following value. amz-1.0

The following is an example header for an HTTP request to create a resource group that includes all resources that are tagged Stage=Test. In this example, the Authorization line is word-wrapped here for easier reading. Don't word wrap it in your actual request.

```

POST / HTTP/1.1
Host: resource-groups.us-east-1.amazonaws.com
X-Amz-Date: 20180112T092034Z
Accept-Encoding: identity
Authorization: AWS4-HMAC-SHA256 Credential=REDACTED/20220113/us-west-2/resource-groups/
aws4_request,
    SignedHeaders=content-encoding;content-length;content-type;host;x-amz-date;x-
amz-target,
    Signature=EXAMPLE5cb91f88f1EXAMPLEa02d3af93dEXAMPLE91e5d03588EXAMPLE88ff1d
Content-Type: application/json
Accept: application/json
Content-Length: 283

{
    "Description": "Resources created for the testing stage.",
    "Name": "QueryGroup",
    "ResourceQuery": {
        "Query": "{\"ResourceTypeFilters\":[\"AWS::AllSupported\"],\"TagFilters\": [{\"Key\":\"Stage\", \"Values\":[\"Test\"]}]}",
        "Type": "TAG_FILTERS_1_0"
    },
    "Tags": {"Department": "Finance"}
}

```

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400