
Amazon CloudWatch Events

API Reference

API Version 2015-10-07



Amazon CloudWatch Events: API Reference

Copyright © 2019 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
DeleteRule	3
Request Syntax	3
Request Parameters	3
Response Elements	3
Errors	4
Example	4
See Also	5
DescribeEventBus	6
Response Syntax	6
Response Elements	6
Errors	6
Examples	6
See Also	7
DescribeRule	9
Request Syntax	9
Request Parameters	9
Response Syntax	9
Response Elements	9
Errors	10
Example	11
See Also	11
DisableRule	13
Request Syntax	13
Request Parameters	13
Response Elements	13
Errors	13
Example	14
See Also	14
EnableRule	16
Request Syntax	16
Request Parameters	16
Response Elements	16
Errors	16
Example	17
See Also	17
ListRuleNamesByTarget	19
Request Syntax	19
Request Parameters	19
Response Syntax	19
Response Elements	20
Errors	20
Example	20
See Also	21
ListRules	22
Request Syntax	22
Request Parameters	22
Response Syntax	22
Response Elements	23
Errors	23
Example	23
See Also	24
ListTagsForResource	25

Request Syntax	25
Request Parameters	25
Response Syntax	25
Response Elements	25
Errors	25
Example	26
See Also	26
ListTargetsByRule	28
Request Syntax	28
Request Parameters	28
Response Syntax	28
Response Elements	29
Errors	30
Example	30
See Also	31
PutEvents	32
Request Syntax	32
Request Parameters	32
Response Syntax	32
Response Elements	32
Errors	33
Example	33
See Also	34
PutPermission	35
Request Syntax	35
Request Parameters	35
Response Elements	36
Errors	36
Examples	37
See Also	38
PutRule	39
Request Syntax	39
Request Parameters	40
Response Syntax	41
Response Elements	41
Errors	41
Example	42
See Also	43
PutTargets	44
Request Syntax	45
Request Parameters	46
Response Syntax	46
Response Elements	47
Errors	47
Examples	48
See Also	54
RemovePermission	55
Request Syntax	55
Request Parameters	55
Response Elements	55
Errors	55
See Also	56
RemoveTargets	57
Request Syntax	57
Request Parameters	57
Response Syntax	58
Response Elements	58

Errors	58
Example	59
See Also	59
TagResource	61
Request Syntax	61
Request Parameters	61
Response Elements	61
Errors	62
Example	62
See Also	63
TestEventPattern	64
Request Syntax	64
Request Parameters	64
Response Syntax	64
Response Elements	64
Errors	65
Example	65
See Also	66
UntagResource	67
Request Syntax	67
Request Parameters	67
Response Elements	67
Errors	67
Example	68
See Also	68
Data Types	69
AwsVpcConfiguration	70
Contents	70
See Also	70
BatchArrayProperties	71
Contents	71
See Also	71
BatchParameters	72
Contents	72
See Also	72
BatchRetryStrategy	73
Contents	73
See Also	73
Condition	74
Contents	74
See Also	74
EcsParameters	75
Contents	75
See Also	76
InputTransformer	77
Contents	77
See Also	78
KinesisParameters	79
Contents	79
See Also	79
NetworkConfiguration	80
Contents	80
See Also	80
PutEventsRequestEntry	81
Contents	81
See Also	81
PutEventsResultEntry	83

Contents	83
See Also	83
PutTargetsResultEntry	84
Contents	84
See Also	84
RemoveTargetsResultEntry	85
Contents	85
See Also	85
Rule	86
Contents	86
See Also	87
RunCommandParameters	88
Contents	88
See Also	88
RunCommandTarget	89
Contents	89
See Also	89
SqsParameters	90
Contents	90
See Also	90
Tag	91
Contents	91
See Also	91
Target	92
Contents	92
See Also	93
Making API Requests	95
CloudWatch Events Endpoints	95
Query Parameters	95
Request Identifiers	95
Query API Authentication	95
Available Libraries	95
Common Parameters	97
Common Errors	99

Welcome

Amazon CloudWatch Events helps you to respond to state changes in your AWS resources. When your resources change state, they automatically send events into an event stream. You can create rules that match selected events in the stream and route them to targets to take action. You can also use rules to take action on a schedule. For example, you can configure rules to:

- Automatically invoke an AWS Lambda function to update DNS entries when an event notifies you that an EC2 instance entered the running state.
- Direct specific API records from CloudTrail to an Kinesis stream for detailed analysis of potential security or availability risks.
- Periodically invoke a built-in target to create a snapshot of an Amazon EBS volume.

For more information about CloudWatch Events features, see the [Amazon CloudWatch Events User Guide](#).

Use the following links to get started using the CloudWatch Events Query API:

- [Actions \(p. 2\)](#): An alphabetical list of all CloudWatch Events actions.
- [Data Types \(p. 69\)](#): An alphabetical list of all CloudWatch Events data types.
- [Common Parameters \(p. 97\)](#): Parameters that all Query actions can use.
- [Common Errors \(p. 99\)](#): Client and server errors that all actions can return.
- [Regions and Endpoints](#): Supported regions and endpoints for all AWS products.

Alternatively, you can use one of the [AWS SDKs](#) to access CloudWatch Events using an API tailored to your programming language or platform.

Developers in the AWS developer community also provide their own libraries, which you can find at the following AWS developer centers:

- [Java Developer Center](#)
- [JavaScript Developer Center](#)
- [AWS Mobile Services](#)
- [PHP Developer Center](#)
- [Python Developer Center](#)
- [Ruby Developer Center](#)
- [Windows and .NET Developer Center](#)

Actions

The following actions are supported:

- [DeleteRule](#) (p. 3)
- [DescribeEventBus](#) (p. 6)
- [DescribeRule](#) (p. 9)
- [DisableRule](#) (p. 13)
- [EnableRule](#) (p. 16)
- [ListRuleNamesByTarget](#) (p. 19)
- [ListRules](#) (p. 22)
- [ListTagsForResource](#) (p. 25)
- [ListTargetsByRule](#) (p. 28)
- [PutEvents](#) (p. 32)
- [PutPermission](#) (p. 35)
- [PutRule](#) (p. 39)
- [PutTargets](#) (p. 44)
- [RemovePermission](#) (p. 55)
- [RemoveTargets](#) (p. 57)
- [TagResource](#) (p. 61)
- [TestEventPattern](#) (p. 64)
- [UntagResource](#) (p. 67)

DeleteRule

Deletes the specified rule.

Before you can delete the rule, you must remove all targets, using [RemoveTargets \(p. 57\)](#).

When you delete a rule, incoming events might continue to match to the deleted rule. Allow a short period of time for changes to take effect.

Managed rules are rules created and managed by another AWS service on your behalf. These rules are created by those other AWS services to support functionality in those services. You can delete these rules using the `Force` option, but you should do so only if you are sure the other service is not still using that rule.

Request Syntax

```
{  
  "Force": boolean,  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Force (p. 3)

If this is a managed rule, created by an AWS service on your behalf, you must specify `Force` as `True` to delete the rule. This parameter is ignored for rules that are not managed rules. You can check whether a rule is a managed rule by using `DescribeRule` or `ListRules` and checking the `ManagedBy` field of the response.

Type: Boolean

Required: No

Name (p. 3)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\.\-_A-Za-z0-9]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force` parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

Example

Deletes a rule named "test"

The following is an example of a `DeleteRule` request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.DeleteRule

{
  "Name": "test"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeEventBus

Displays the external AWS accounts that are permitted to write events to your account using your account's event bus, and the associated policy. To enable your account to receive events from other accounts, use [PutPermission \(p. 35\)](#).

Response Syntax

```
{  
  "Arn": "string",  
  "Name": "string",  
  "Policy": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn (p. 6)

The Amazon Resource Name (ARN) of the account permitted to write events to the current account.

Type: String

Name (p. 6)

The name of the event bus. Currently, this is always `default`.

Type: String

Policy (p. 6)

The policy that enables the external account to send events to your account.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Examples

The following example is run in account 444455556666, which has granted permission to AWS account 111122223333 to send events to 444455556666.

Example

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.DescribeEventBus
```

Example

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "Policy":
  {
    "Version": "2012-10-17",
    "Statement": [
      {
        "Sid": "mysid",
        "Effect": "Allow",
        "Principal": {
          "AWS": "arn:aws:iam::111122223333:root"
        },
        "Action": "events:PutEvents",
        "Resource": "arn:aws:events:us-east-1:444455556666:event-bus/default"
      }
    ]
  },
  "Name": "default",
  "Arn": "arn:aws:events:us-east-1:444455556666:event-bus/default"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeRule

Describes the specified rule.

DescribeRule does not list the targets of a rule. To see the targets associated with a rule, use [ListTargetsByRule](#) (p. 28).

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 97).

The request accepts the following data in JSON format.

Name (p. 9)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [`\. \- _A-Za-z0-9`]+

Required: Yes

Response Syntax

```
{  
  "Arn": "string",  
  "Description": "string",  
  "EventPattern": "string",  
  "ManagedBy": "string",  
  "Name": "string",  
  "RoleArn": "string",  
  "ScheduleExpression": "string",  
  "State": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn (p. 9)

The Amazon Resource Name (ARN) of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

[Description \(p. 9\)](#)

The description of the rule.

Type: String

Length Constraints: Maximum length of 512.

[EventPattern \(p. 9\)](#)

The event pattern. For more information, see [Events and Event Patterns](#) in the *Amazon CloudWatch Events User Guide*.

Type: String

[ManagedBy \(p. 9\)](#)

If this is a managed rule, created by an AWS service on your behalf, this field displays the principal name of the AWS service that created the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

[Name \(p. 9\)](#)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\ . \ - \ _ A - Z a - z 0 - 9] +

[RoleArn \(p. 9\)](#)

The Amazon Resource Name (ARN) of the IAM role associated with the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

[ScheduleExpression \(p. 9\)](#)

The scheduling expression. For example, "cron(0 20 * * ? *)", "rate(5 minutes)".

Type: String

Length Constraints: Maximum length of 256.

[State \(p. 9\)](#)

Specifies whether the rule is enabled or disabled.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Describes a rule named "test"

The following is an example of a DescribeRule request and response.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.DescribeRule

{
  "Name": "test"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "Name": "test",
  "EventPattern": "{\"source\": [\"aws.autoscaling\"], \"detail-type\": [\"EC2 Instance Launch Successful\", \"EC2 Instance Terminate Successful\", \"EC2 Instance Launch Unsuccessful\", \"EC2 Instance Terminate Unsuccessful\"]}\",
  "State": "ENABLED",
  "Arn": "arn:aws:events:us-east-1:123456789012:rule/test",
  "Description": "Test rule for Auto Scaling events"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DisableRule

Disables the specified rule. A disabled rule won't match any events, and won't self-trigger if it has a schedule expression.

When you disable a rule, incoming events might continue to match to the disabled rule. Allow a short period of time for changes to take effect.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Name (p. 13)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\ . \ - \ _ A - Z a - z 0 - 9] +

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force`

parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Disables a rule named "test"

The following is an example of a `DisableRule` request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.DisableRule

{
  "Name": "test"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

EnableRule

Enables the specified rule. If the rule does not exist, the operation fails.

When you enable a rule, incoming events might not immediately start matching to a newly enabled rule. Allow a short period of time for changes to take effect.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Name (p. 16)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\ . \ _ _ A - Z a - z 0 - 9] +

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force`

parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Enables a rule named "test"

The following is an example of an `EnableRule` request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.EnableRule

{
  "Name": "test"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListRuleNamesByTarget

Lists the rules for the specified target. You can see which of the rules in Amazon CloudWatch Events can invoke a specific target in your account.

Request Syntax

```
{  
  "Limit": number,  
  "NextToken": "string",  
  "TargetArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Limit (p. 19)

The maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 19)

The token returned by a previous call to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

TargetArn (p. 19)

The Amazon Resource Name (ARN) of the target resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

Response Syntax

```
{  
  "NextToken": "string",  
  "RuleNames": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 19)

Indicates whether there are additional results to retrieve. If there are no more results, the value is null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

RuleNames (p. 19)

The names of the rules that can invoke the given target.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\ . \ - \ _ A - Z a - z 0 - 9] +

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

Example

Lists rule names by target with the specified ARN

The following is an example of a ListRuleNamesByTarget request and response.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.ListRuleNamesByTarget

{
  "TargetArn": "arn:aws:lambda:us-east-1:123456789012:function:MyFunction",
  "NextToken": "",
}
```

```
"Limit": 0  
}
```

Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: <RequestId>  
Content-Type: application/x-amz-json-1.1  
Content-Length: <PayloadSizeBytes>  
Date: <Date>  
  
{  
  "RuleNames": [  
    "test1",  
    "test2",  
    "test3",  
    "test4",  
    "test5"  
  ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListRules

Lists your Amazon CloudWatch Events rules. You can either list all the rules or you can provide a prefix to match to the rule names.

ListRules does not list the targets of a rule. To see the targets associated with a rule, use [ListTargetsByRule](#) (p. 28).

Request Syntax

```
{  
  "Limit": number,  
  "NamePrefix": "string",  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 97).

The request accepts the following data in JSON format.

Limit (p. 22)

The maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NamePrefix (p. 22)

The prefix matching the rule name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\ . \ - \ _ A - Z a - z 0 - 9] +

Required: No

NextToken (p. 22)

The token returned by a previous call to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"Rules": [
  {
    "Arn": "string",
    "Description": "string",
    "EventPattern": "string",
    "ManagedBy": "string",
    "Name": "string",
    "RoleArn": "string",
    "ScheduleExpression": "string",
    "State": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 22)

Indicates whether there are additional results to retrieve. If there are no more results, the value is null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Rules (p. 22)

The rules that match the specified criteria.

Type: Array of [Rule \(p. 86\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

Example

Lists all the rules that start with the letter "t" with a page size of 1

The following is an example of a ListRules request and response.

Sample Request

```
POST / HTTP/1.1
```

```
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.ListRules

{
  "NamePrefix": "t",
  "Limit": 1
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "Rules": [
    {
      "EventPattern": "{\"source\": [\"aws.autoscaling\"], \"detail-type\": [\"EC2 Instance Launch Successful\", \"EC2 Instance Terminate Successful\", \"EC2 Instance Launch Unsuccessful\", \"EC2 Instance Terminate Unsuccessful\"]}",
      "State": "DISABLED",
      "Name": "test",
      "Arn": "arn:aws:events:us-east-1:123456789012:rule/test",
      "Description": "Test rule for Auto Scaling events"
    }
  ],
  "NextToken": "ABCDEgAAAAAAAAAAQAAABCXtD8i7XlyFv5XFKH8GrudAAAAQIoQ0+7qXp63vQf1pvVklfHfd+p2QgY36pjlAqsSsrkNbOtTePaCeJqN80+jbu66UhpJh7huA9r0iY9zjdtZ3vsAAAAGAAAAAAAAAF5MZWkt1lmMuLd9gUjryM4sL9EG5IkcPUM60Vq1tzyYw=="
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListTagsForResource

Displays the tags associated with a CloudWatch Events resource. In CloudWatch Events, rules can be tagged.

Request Syntax

```
{  
  "ResourceARN": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

ResourceARN (p. 25)

The ARN of the CloudWatch Events rule for which you want to view tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

Response Syntax

```
{  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags (p. 25)

The list of tag keys and values associated with the rule you specified

Type: Array of [Tag \(p. 91\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Removes two tags from a CloudWatch Events rule

The following is an example of an `UntagResource` request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.ListTagsForResource

{
  "ResourceARN": "arn:aws:events:us-west-1:123456789012:rule/test",
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "Tags": [
    {
      "Key": "Stack",
      "Value": "Prod"
    },
    {
      "Key": "CostCenter",
      "Value": "12345"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListTargetsByRule

Lists the targets assigned to the specified rule.

Request Syntax

```
{  
  "Limit": number,  
  "NextToken": "string",  
  "Rule": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Limit (p. 28)

The maximum number of results to return.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

NextToken (p. 28)

The token returned by a previous call to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Rule (p. 28)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [`\. \- _A-Za-z0-9`]+

Required: Yes

Response Syntax

```
{  
  "NextToken": "string",  
  "Targets": [  
    {  
      "Arn": "string",  
      "BatchParameters": {
```

```

    "ArrayProperties": {
      "Size": number
    },
    "JobDefinition": "string",
    "JobName": "string",
    "RetryStrategy": {
      "Attempts": number
    }
  },
  "EcsParameters": {
    "Group": "string",
    "LaunchType": "string",
    "NetworkConfiguration": {
      "awsvpcConfiguration": {
        "AssignPublicIp": "string",
        "SecurityGroups": [ "string" ],
        "Subnets": [ "string" ]
      }
    },
    "PlatformVersion": "string",
    "TaskCount": number,
    "TaskDefinitionArn": "string"
  },
  "Id": "string",
  "Input": "string",
  "InputPath": "string",
  "InputTransformer": {
    "InputPathsMap": {
      "string" : "string"
    }
  },
  "InputTemplate": "string"
},
"KinesisParameters": {
  "PartitionKeyPath": "string"
},
"RoleArn": "string",
"RunCommandParameters": {
  "RunCommandTargets": [
    {
      "Key": "string",
      "Values": [ "string" ]
    }
  ]
},
"SqsParameters": {
  "MessageGroupId": "string"
}
}
]
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken (p. 28)

Indicates whether there are additional results to retrieve. If there are no more results, the value is null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Targets (p. 28)

The targets assigned to the rule.

Type: Array of [Target \(p. 92\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Lists the targets associated with a rule named "test"

The following is an example of a ListTargetsByRule request and response.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.ListTargetsByRule

{
  "Rule": "test"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
```

```
"Targets": [  
  {  
    "Id": "MyTargetId",  
    "Arn": "arn:aws:lambda:us-east-1:123456789012:function:MyFunction"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

PutEvents

Sends custom events to Amazon CloudWatch Events so that they can be matched to rules.

Request Syntax

```
{
  "Entries": [
    {
      "Detail": "string",
      "DetailType": "string",
      "Resources": [ "string" ],
      "Source": "string",
      "Time": number
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 97).

The request accepts the following data in JSON format.

Entries (p. 32)

The entry that defines an event in your system. You can specify several parameters for the entry such as the source and type of the event, resources associated with the event, and so on.

Type: Array of [PutEventsRequestEntry](#) (p. 81) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
{
  "Entries": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "EventId": "string"
    }
  ],
  "FailedEntryCount": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entries (p. 32)

The successfully and unsuccessfully ingested events results. If the ingestion was successful, the entry has the event ID in it. Otherwise, you can use the error code and error message to identify the problem with the entry.

Type: Array of [PutEventsResultEntry \(p. 83\)](#) objects

FailedEntryCount (p. 32)

The number of failed entries.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

Example

Sends two custom events

The following is an example of a PutEvents request and response.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutEvents

{
  "Entries": [
    {
      "Source": "com.mycompany.myapp",
      "Detail": "{ \"key1\": \"value1\", \"key2\": \"value2\" }",
      "Resources": [
        "resource1",
        "resource2"
      ],
      "DetailType": "myDetailType"
    },
    {
      "Source": "com.mycompany.myapp",
      "Detail": "{ \"key1\": \"value3\", \"key2\": \"value4\" }",
      "Resources": [
        "resource1",
```

```
        "resource2"
      ],
      "DetailType": "myDetailType"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "FailedEntryCount": 0,
  "Entries": [
    {
      "EventId": "11710aed-b79e-4468-a20b-bb3c0c3b4860"
    },
    {
      "EventId": "d804d26a-88db-4b66-9eaf-9a11c708ae82"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

PutPermission

Running `PutPermission` permits the specified AWS account or AWS organization to put events to your account's default *event bus*. CloudWatch Events rules in your account are triggered by these events arriving to your default event bus.

For another account to send events to your account, that external account must have a CloudWatch Events rule with your account's default event bus as a target.

To enable multiple AWS accounts to put events to your default event bus, run `PutPermission` once for each of these accounts. Or, if all the accounts are members of the same AWS organization, you can run `PutPermission` once specifying `Principal` as "*" and specifying the AWS organization ID in `Condition`, to grant permissions to all accounts in that organization.

If you grant permissions using an organization, then accounts in that organization must specify a `RoleArn` with proper permissions when they use `PutTarget` to add your account's event bus as a target. For more information, see [Sending and Receiving Events Between AWS Accounts](#) in the *Amazon CloudWatch Events User Guide*.

The permission policy on the default event bus cannot exceed 10 KB in size.

Request Syntax

```
{
  "Action": "string",
  "Condition": {
    "Key": "string",
    "Type": "string",
    "Value": "string"
  },
  "Principal": "string",
  "StatementId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Action (p. 35)

The action that you are enabling the other account to perform. Currently, this must be `events:PutEvents`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `events:[a-zA-Z]+`

Required: Yes

Condition (p. 35)

This parameter enables you to limit the permission to accounts that fulfill a certain condition, such as being a member of a certain AWS organization. For more information about AWS Organizations, see [What Is AWS Organizations](#) in the *AWS Organizations User Guide*.

If you specify `Condition` with an AWS organization ID, and specify "*" as the value for `Principal`, you grant permission to all the accounts in the named organization.

The `Condition` is a JSON string which must contain `Type`, `Key`, and `Value` fields.

Type: [Condition \(p. 74\)](#) object

Required: No

Principal (p. 35)

The 12-digit AWS account ID that you are permitting to put events to your default event bus. Specify "*" to permit any account to put events to your default event bus.

If you specify "*" without specifying `Condition`, avoid creating rules that may match undesirable events. To create more secure rules, make sure that the event pattern for each rule contains an `account` field with a specific account ID from which to receive events. Rules with an `account` field do not match any events sent from other accounts.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `(\d{12}|*)`

Required: Yes

StatementId (p. 35)

An identifier string for the external account that you are granting permissions to. If you later want to revoke the permission for this external account, specify this `StatementId` when you run [RemovePermission \(p. 55\)](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9-_\+]`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

PolicyLengthExceededException

The event bus policy is too long. For more information, see the limits.

HTTP Status Code: 400

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Examples

The following example enables the current account to receive events from account 111122223333.

Example

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutPermission

{
  "Action": "events:PutEvents"
  "Principal": "111122223333"
  "StatementId": "MyStatement"
}
```

Example

The following example grants permissions to all accounts in the organization with an ID of o-1234567890

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutPermission

{
  "Action": "events:PutEvents"
  "Principal": "*"
}
```

```
"Condition": '{"Type" : "StringEquals", "Key": "aws:PrincipalOrgID", "Value":  
"o-1234567890"}'  
  "StatementId": "MyStatement"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

PutRule

Creates or updates the specified rule. Rules are enabled by default, or based on value of the state. You can disable a rule using [DisableRule \(p. 13\)](#).

If you are updating an existing rule, the rule is replaced with what you specify in this `PutRule` command. If you omit arguments in `PutRule`, the old values for those arguments are not kept. Instead, they are replaced with null values.

When you create or update a rule, incoming events might not immediately start matching to new or updated rules. Allow a short period of time for changes to take effect.

A rule must contain at least an `EventPattern` or `ScheduleExpression`. Rules with `EventPatterns` are triggered when a matching event is observed. Rules with `ScheduleExpressions` self-trigger based on the given schedule. A rule can have both an `EventPattern` and a `ScheduleExpression`, in which case the rule triggers on matching events as well as on a schedule.

When you initially create a rule, you can optionally assign one or more tags to the rule. Tags can help you organize and categorize your resources. You can also use them to scope user permissions, by granting a user permission to access or change only rules with certain tag values. To use the `PutRule` operation and assign tags, you must have both the `events:PutRule` and `events:TagResource` permissions.

If you are updating an existing rule, any tags you specify in the `PutRule` operation are ignored. To update the tags of an existing rule, use [TagResource \(p. 61\)](#) and [UntagResource \(p. 67\)](#).

Most services in AWS treat `:` or `/` as the same character in Amazon Resource Names (ARNs). However, CloudWatch Events uses an exact match in event patterns and rules. Be sure to use the correct ARN characters when creating event patterns so that they match the ARN syntax in the event you want to match.

In CloudWatch Events, it is possible to create rules that lead to infinite loops, where a rule is fired repeatedly. For example, a rule might detect that ACLs have changed on an S3 bucket, and trigger software to change them to the desired state. If the rule is not written carefully, the subsequent change to the ACLs fires the rule again, creating an infinite loop.

To prevent this, write the rules so that the triggered actions do not re-fire the same rule. For example, your rule could fire only if ACLs are found to be in a bad state, instead of after any change.

An infinite loop can quickly cause higher than expected charges. We recommend that you use budgeting, which alerts you when charges exceed your specified limit. For more information, see [Managing Your Costs with Budgets](#).

Request Syntax

```
{
  "Description": "string",
  "EventPattern": "string",
  "Name": "string",
  "RoleArn": "string",
  "ScheduleExpression": "string",
  "State": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Description (p. 39)

A description of the rule.

Type: String

Length Constraints: Maximum length of 512.

Required: No

EventPattern (p. 39)

The event pattern. For more information, see [Events and Event Patterns](#) in the *Amazon CloudWatch Events User Guide*.

Type: String

Required: No

Name (p. 39)

The name of the rule that you are creating or updating.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\ . \ - \ _ A - Z a - z 0 - 9] +

Required: Yes

RoleArn (p. 39)

The Amazon Resource Name (ARN) of the IAM role associated with the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

ScheduleExpression (p. 39)

The scheduling expression. For example, "cron(0 20 * * ? *)" or "rate(5 minutes)".

Type: String

Length Constraints: Maximum length of 256.

Required: No

State (p. 39)

Indicates whether the rule is enabled or disabled.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

Tags (p. 39)

The list of key-value pairs to associate with the rule.

Type: Array of [Tag \(p. 91\)](#) objects

Required: No

Response Syntax

```
{  
  "RuleArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

RuleArn (p. 41)

The Amazon Resource Name (ARN) of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

InvalidEventPatternException

The event pattern is not valid.

HTTP Status Code: 400

LimitExceededException

You tried to create more rules or add more targets to a rule than is allowed.

HTTP Status Code: 400

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force` parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

Example

Creates a rule named "test" that matches events from Amazon EC2. The rule is also given two tags.

The following is an example of a `PutRule` request and response.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutRule

{
  "Name": "test",
  "EventPattern": "{ \"source\": [\"aws.ec2\"] }",
  "Tags": [
    {
      "Key": "Stack",
      "Value": "Prod"
    },
    {
      "Key": "CostCenter",
      "Value": "12345"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "RuleArn": "arn:aws:events:us-east-1:123456789012:rule/test"
}
```


See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

PutTargets

Adds the specified targets to the specified rule, or updates the targets if they are already associated with the rule.

Targets are the resources that are invoked when a rule is triggered.

You can configure the following as targets for CloudWatch Events:

- EC2 instances
- SSM Run Command
- SSM Automation
- AWS Lambda functions
- Data streams in Amazon Kinesis Data Streams
- Data delivery streams in Amazon Kinesis Data Firehose
- Amazon ECS tasks
- AWS Step Functions state machines
- AWS Batch jobs
- AWS CodeBuild projects
- Pipelines in AWS CodePipeline
- Amazon Inspector assessment templates
- Amazon SNS topics
- Amazon SQS queues, including FIFO queues
- The default event bus of another AWS account

Creating rules with built-in targets is supported only in the AWS Management Console. The built-in targets are `EC2 CreateSnapshot` API call, `EC2 RebootInstances` API call, `EC2 StopInstances` API call, and `EC2 TerminateInstances` API call.

For some target types, `PutTargets` provides target-specific parameters. If the target is a Kinesis data stream, you can optionally specify which shard the event goes to by using the `KinesisParameters` argument. To invoke a command on multiple EC2 instances with one rule, you can use the `RunCommandParameters` field.

To be able to make API calls against the resources that you own, Amazon CloudWatch Events needs the appropriate permissions. For AWS Lambda and Amazon SNS resources, CloudWatch Events relies on resource-based policies. For EC2 instances, Kinesis data streams, and AWS Step Functions state machines, CloudWatch Events relies on IAM roles that you specify in the `RoleARN` argument in `PutTargets`. For more information, see [Authentication and Access Control](#) in the *Amazon CloudWatch Events User Guide*.

If another AWS account is in the same region and has granted you permission (using `PutPermission`), you can send events to that account. Set that account's event bus as a target of the rules in your account. To send the matched events to the other account, specify that account's event bus as the `Arn` value when you run `PutTargets`. If your account sends events to another account, your account is charged for each sent event. Each event sent to another account is charged as a custom event. The account receiving the event is not charged. For more information, see [Amazon CloudWatch Pricing](#).

If you are setting the event bus of another account as the target, and that account granted permission to your account through an organization instead of directly by the account ID, then you must specify a `RoleArn` with proper permissions in the `Target` structure. For more information, see [Sending and Receiving Events Between AWS Accounts](#) in the *Amazon CloudWatch Events User Guide*.

For more information about enabling cross-account events, see [PutPermission \(p. 35\)](#).

Input, **InputPath**, and **InputTransformer** are mutually exclusive and optional parameters of a target. When a rule is triggered due to a matched event:

- If none of the following arguments are specified for a target, then the entire event is passed to the target in JSON format (unless the target is Amazon EC2 Run Command or Amazon ECS task, in which case nothing from the event is passed to the target).
- If **Input** is specified in the form of valid JSON, then the matched event is overridden with this constant.
- If **InputPath** is specified in the form of JSONPath (for example, `$.detail`), then only the part of the event specified in the path is passed to the target (for example, only the detail part of the event is passed).
- If **InputTransformer** is specified, then one or more specified JSONPaths are extracted from the event and used as values in a template that you specify as the input to the target.

When you specify `InputPath` or `InputTransformer`, you must use JSON dot notation, not bracket notation.

When you add targets to a rule and the associated rule triggers soon after, new or updated targets might not be immediately invoked. Allow a short period of time for changes to take effect.

This action can partially fail if too many requests are made at the same time. If that happens, `FailedEntryCount` is non-zero in the response and each entry in `FailedEntries` provides the ID of the failed target and the error code.

Request Syntax

```
{
  "Rule": "string",
  "Targets": [
    {
      "Arn": "string",
      "BatchParameters": {
        "ArrayProperties": {
          "Size": number
        },
        "JobDefinition": "string",
        "JobName": "string",
        "RetryStrategy": {
          "Attempts": number
        }
      },
      "EcsParameters": {
        "Group": "string",
        "LaunchType": "string",
        "NetworkConfiguration": {
          "awsvpcConfiguration": {
            "AssignPublicIp": "string",
            "SecurityGroups": [ "string" ],
            "Subnets": [ "string" ]
          }
        },
        "PlatformVersion": "string",
        "TaskCount": number,
        "TaskDefinitionArn": "string"
      },
      "Id": "string",
      "Input": "string",
      "InputPath": "string",
      "InputTransformer": {
        "InputPathsMap": {
          "string" : "string"
        }
      }
    }
  ]
}
```

```
    },
    "InputTemplate": "string"
  },
  "KinesisParameters": {
    "PartitionKeyPath": "string"
  },
  "RoleArn": "string",
  "RunCommandParameters": {
    "RunCommandTargets": [
      {
        "Key": "string",
        "Values": [ "string" ]
      }
    ]
  },
  "SqsParameters": {
    "MessageGroupId": "string"
  }
}
]
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Rule (p. 45)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\. \- _A-Za-z0-9]+

Required: Yes

Targets (p. 45)

The targets to update or add to the rule.

Type: Array of [Target \(p. 92\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

Response Syntax

```
{
  "FailedEntries": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "TargetId": "string"
    }
  ]
}
```

```
    }  
  ],  
  "FailedEntryCount": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailedEntries (p. 46)

The failed target entries.

Type: Array of [PutTargetsResultEntry](#) (p. 84) objects

FailedEntryCount (p. 46)

The number of failed entries.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 99).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

LimitExceededException

You tried to create more rules or add more targets to a rule than is allowed.

HTTP Status Code: 400

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force` parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Examples

Adds a target to a Lambda function with the ID "MyTargetId" to the rule named "test"

The following is an example of a PutTargets request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "test",
  "Targets": [
    {
      "Id": "MyTargetId",
      "Arn": "arn:aws:lambda:us-east-1:123456789012:function:MyFunction"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "FailedEntries": [],
  "FailedEntryCount": 0
}
```

Uses Input Transformer to extract data from an event and input that data to the target

This example extracts the instance and state from an event, puts them into a simple text template, and passes this data to a Lambda function called MyFunction.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
```

```
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "testrule",
  "Targets": [
    {
      "Id": "MyTargetId",
      "Arn": "arn:aws:lambda:us-east-1:123456789012:function:MyFunction"
      "InputTransformer":
        {
          "InputPathsMap": {"instance": "$.detail.instance", "status":
            "$.detail.status"},
          "InputTemplate": "<instance> is in state <status>"
        }
    }
  ]
}
```

Example

Here is another sample request using `InputTransformer`. The input to the Lambda function is in JSON format, with an array substituted. Below that sample request are examples of an event and the resulting output to the target, using this sample request.

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "testrule",
  "Targets": [
    {
      "Id": "MyTargetId",
      "Arn": "arn:aws:lambda:us-east-1:123456789012:function:MyFunction"
      "InputTransformer":
        {
          "InputPathsMap": {"commandsToRun": "$.detail.commands"}
          "InputTemplate": "{$\"commands\": <commandsToRun>}"
        }
    }
  ]
}
```

Incoming event:

```
{
  "Time": 1225864800,
  "Source": "foo",
  "Resources": ["foo", "foo"],
  "DetailType": "foo",
  "Detail": {
    "commands": ["ls -lrt", "echo HelloWorld!"]
  }
}
```

```
}
```

Output sent to the target:

```
{  
  "commands" : ["ls -lrt", "echo HelloWorld!"]  
}
```

Sends a command to a list of EC2 instances specified by InstanceIds, using Amazon EC2 Run Command

```
POST / HTTP/1.1  
Host: events.<region>.<domain>  
x-amz-Date: <Date>  
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>  
User-Agent: <UserAgentString>  
Content-Type: application/x-amz-json-1.1  
Content-Length: <PayloadSizeBytes>  
Connection: Keep-Alive  
X-Amz-Target: AWSEvents.PutTargets  
  
{  
  "Rule": "testrule",  
  "Targets": [  
    {  
      "Id": "id123456789",  
      "Arn": "arn:aws:ssm:us-east-1:12345679012:document/RestartLinuxService",  
      "RoleArn": "arn:aws:iam::123456789012:role/MyRoleToAccessEC2"  
      "RunCommandParameters": {  
        "RunCommandTargets": [  
          {  
            "Key": "InstanceIds",  
            "Values": ["i-123456789012", "i-098765432109"]  
          }  
        ]  
      }  
    }  
  ]  
}
```

Sends a batch job command to an AWS Batch job queue

When the target is an AWS Batch job queue, the Arn field specifies the ARN of the job queue, while JobDefinition specifies the ARN of the job definition.

```
POST / HTTP/1.1  
Host: events.<region>.<domain>  
x-amz-Date: <Date>  
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>  
User-Agent: <UserAgentString>  
Content-Type: application/x-amz-json-1.1
```



```
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "batch-job-rule",
  "Targets": [
    {
      "Id": "id123456789",
      "Arn": "arn:aws:batch:us-west-2:012345678910:job-queue/default",
      "BatchParameters": {
        "ArrayProperties": {
          "Size": 25
        },
        "JobDefinition": "arn:aws:batch:us-west-2:012345678910:job-definition/nvidia-
smi:1",
        "JobName": "unique-job-name",
        "RetryStrategy": {
          "Attempts": 5
        }
      }
    }
  ]
}
```

Uses KinesisParameters to control the shard assignment

In this example, `KinesisParameters` is used to specify that events related to status changes are sent to a shard specific to the affected instance ID.

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-
type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "StatusChangeRule",
  "Targets": [
    {
      "Id": "1",
      "Arn": "arn:aws:kinesis:us-east-1:123456789012:function:stream/mystream",
      "KinesisParameters": {
        "PartitionKeyPath": "$.detail.instance-id"
      }
    }
  ]
}
```

Adds an Amazon Kinesis Data Firehose data delivery stream as a target

This example sets a Kinesis data delivery stream named `target-stream-name` as a target.

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
```

```
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "FirehoseExample",
  "Targets": [
    {
      "Id" : "FirehoseStream",
      "Arn": "arn:aws:firehose:us-east-1:123456789012:deliverystream/target-stream-name",
    }
  ]
}
```

Adds a Step Functions state machine as a target

This example targets a state machine called "HelloWorld", and sends the input constant "Hello World!" to that target.

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "testrule",
  "Targets": [
    {
      "RoleArn": "arn:aws:iam::123456789012:role/MyRoleToAccessStepFunctions"
      "Arn": "arn:aws:states:us-east-1:123456789012:stateMachine:HelloWorld",
      "Input": "HelloWorld!"
    }
  ]
}
```

Adds a target that creates three Amazon ECS tasks based on a task definition

This example uses Amazon ECS as the target. You must have already created the task definition and cluster in Amazon ECS.

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets
```

```
{
  "Rule": "test",
  "Targets": [
    {
      "Id": "Target1",
      "RoleArn": "arn:aws:iam::123456789012:role/MyRoleToAccessECS"
      "Arn": "arn:aws:ecs:us-east-1:123456789012:cluster/example-cluster",
      "ECSPParameters": {
        "TaskDefinitionArn": "arn:aws:ecs:us-east-1:123456789012:task-definition/
example",
        "TaskCount": 3
      }
    }
  ]
}
```

Specifying two targets with one command

This example sets two simple targets with one command. In this example, both targets are AWS Lambda functions, but the two targets could be different AWS services as well.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-
type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "test",
  "Targets": [
    {
      "Id": "MyTargetId",
      "Arn": "arn:aws:lambda:us-east-1:123456789012:function:MyFunction"
    }
    {
      "Id": "MyTargetId2",
      "Arn": "arn:aws:lambda:us-east-1:123456789012:function:MyFunction2"
    }
  ]
}
```

Specifying another AWS account as a target

This example shows cross-account event delivery. The target being added is the event bus of a separate AWS account, which has the AWS account ID of 444455556666.

Sample Request

```
POST / HTTP/1.1
```

```
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-
type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.PutTargets

{
  "Rule": "producer-rule",
  "Targets": [
    {
      "Id": "CrossAccountTargetId",
      "Arn": "arn:aws:events:us-east-1:444455556666:event-bus/default"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

RemovePermission

Revokes the permission of another AWS account to be able to put events to your default event bus. Specify the account to revoke by the `StatementId` value that you associated with the account when you granted it permission with `PutPermission`. You can find the `StatementId` by using [DescribeEventBus](#) (p. 6).

Request Syntax

```
{  
  "StatementId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 97).

The request accepts the following data in JSON format.

StatementId (p. 55)

The statement ID corresponding to the account that is no longer allowed to put events to the default event bus.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9-_]+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 99).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

RemoveTargets

Removes the specified targets from the specified rule. When the rule is triggered, those targets are no longer be invoked.

When you remove a target, when the associated rule triggers, removed targets might continue to be invoked. Allow a short period of time for changes to take effect.

This action can partially fail if too many requests are made at the same time. If that happens, `FailedEntryCount` is non-zero in the response and each entry in `FailedEntries` provides the ID of the failed target and the error code.

Request Syntax

```
{
  "Force": boolean,
  "Ids": [ "string" ],
  "Rule": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Force (p. 57)

If this is a managed rule, created by an AWS service on your behalf, you must specify `Force` as `True` to remove targets. This parameter is ignored for rules that are not managed rules. You can check whether a rule is a managed rule by using `DescribeRule` or `ListRules` and checking the `ManagedBy` field of the response.

Type: Boolean

Required: No

Ids (p. 57)

The IDs of the targets to remove from the rule.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\._-_A-Za-z0-9]+`

Required: Yes

Rule (p. 57)

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [\.\-_\A-Za-z0-9]+

Required: Yes

Response Syntax

```
{
  "FailedEntries": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "TargetId": "string"
    }
  ],
  "FailedEntryCount": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

FailedEntries (p. 58)

The failed target entries.

Type: Array of [RemoveTargetsResultEntry \(p. 85\)](#) objects

FailedEntryCount (p. 58)

The number of failed entries.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force` parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Removes a target with ID "MyTargetId" from a rule named "test"

The following is an example of a RemoveTargets request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.RemoveTargets

{
  "Rule": "test",
  "Ids": [
    "MyTargetId"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "FailedEntries": [],
  "FailedEntryCount": 0
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)

- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

TagResource

Assigns one or more tags (key-value pairs) to the specified CloudWatch Events resource. Tags can help you organize and categorize your resources. You can also use them to scope user permissions by granting a user permission to access or change only resources with certain tag values. In CloudWatch Events, rules can be tagged.

Tags don't have any semantic meaning to AWS and are interpreted strictly as strings of characters.

You can use the `TagResource` action with a rule that already has tags. If you specify a new tag key for the rule, this tag is appended to the list of tags associated with the rule. If you specify a tag key that is already associated with the rule, the new tag value that you specify replaces the previous value for that tag.

You can associate as many as 50 tags with a resource.

Request Syntax

```
{
  "ResourceARN": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

ResourceARN (p. 61)

The ARN of the CloudWatch Events rule that you're adding tags to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

Tags (p. 61)

The list of key-value pairs to associate with the rule.

Type: Array of [Tag \(p. 91\)](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force` parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Adds two tags to a CloudWatch Events rule

The following is an example of a `TagResource` request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.TagResource

{
  "ResourceARN": "arn:aws:events:us-west-1:123456789012:rule/test",
  "Tags": [
    {
      "Key": "Stack",
      "Value": "Prod"
    },
    {
      "Key": "Team",
      "Value": "Green"
    }
  ]
}
```

```
}  
  ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

TestEventPattern

Tests whether the specified event pattern matches the provided event.

Most services in AWS treat `:` or `/` as the same character in Amazon Resource Names (ARNs). However, CloudWatch Events uses an exact match in event patterns and rules. Be sure to use the correct ARN characters when creating event patterns so that they match the ARN syntax in the event you want to match.

Request Syntax

```
{  
  "Event": "string",  
  "EventPattern": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

Event (p. 64)

The event, in JSON format, to test against the event pattern.

Type: String

Required: Yes

EventPattern (p. 64)

The event pattern. For more information, see [Events and Event Patterns](#) in the *Amazon CloudWatch Events User Guide*.

Type: String

Required: Yes

Response Syntax

```
{  
  "Result": boolean  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Result (p. 64)

Indicates whether the event matches the event pattern.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

InvalidEventPatternException

The event pattern is not valid.

HTTP Status Code: 400

Example

Tests that a given event matches a given event pattern

The following is an example of a TestEventPattern request and response.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.TestEventPattern

{
  "EventPattern": "{\"source\": [\"com.mycompany.myapp\"]}",
  "Event": "{\"id\": \"e00c66cb-fe7a-4fcc-81ad-58eb60f5d96b\", \"detail-type\": \"myDetailType\", \"source\": \"com.mycompany.myapp\", \"account\": \"123456789012\", \"time\": \"2016-01-10T01:29:23Z\", \"region\": \"us-east-1\", \"resources\": [\"resource1\", \"resource2\"], \"detail\": {\"key1\": \"value1\", \"key2\": \"value2\"}}}"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "Result": true
}
```

}

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

UntagResource

Removes one or more tags from the specified CloudWatch Events resource. In CloudWatch Events, rules can be tagged.

Request Syntax

```
{  
  "ResourceARN": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 97\)](#).

The request accepts the following data in JSON format.

ResourceARN (p. 67)

The ARN of the CloudWatch Events rule from which you are removing tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

TagKeys (p. 67)

The list of tag keys to remove from the resource.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 99\)](#).

ConcurrentModificationException

There is concurrent modification on a rule or target.

HTTP Status Code: 400

InternalException

This exception occurs due to unexpected causes.

HTTP Status Code: 500

ManagedRuleException

This rule was created by an AWS service on behalf of your account. It is managed by that service. If you see this error in response to `DeleteRule` or `RemoveTargets`, you can use the `Force` parameter in those calls to delete the rule or remove targets from the rule. You cannot modify these managed rules by using `DisableRule`, `EnableRule`, `PutTargets`, `PutRule`, `TagResource`, or `UntagResource`.

HTTP Status Code: 400

ResourceNotFoundException

An entity that you specified does not exist.

HTTP Status Code: 400

Example

Removes two tags from a CloudWatch Events rule

The following is an example of an `UntagResource` request.

Sample Request

```
POST / HTTP/1.1
Host: events.<region>.<domain>
x-amz-Date: <Date>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=content-type;date;host;user-agent;x-amz-date;x-amz-target;x-amzn-requestid, Signature=<Signature>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.1
Content-Length: <PayloadSizeBytes>
Connection: Keep-Alive
X-Amz-Target: AWSEvents.UntagResource

{
  "ResourceARN": "arn:aws:events:us-west-1:123456789012:rule/test",
  "TagKeys": [ "CostCenter", "Team" ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

Data Types

The Amazon CloudWatch Events API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AwsVpcConfiguration](#) (p. 70)
- [BatchArrayProperties](#) (p. 71)
- [BatchParameters](#) (p. 72)
- [BatchRetryStrategy](#) (p. 73)
- [Condition](#) (p. 74)
- [EcsParameters](#) (p. 75)
- [InputTransformer](#) (p. 77)
- [KinesisParameters](#) (p. 79)
- [NetworkConfiguration](#) (p. 80)
- [PutEventsRequestEntry](#) (p. 81)
- [PutEventsResultEntry](#) (p. 83)
- [PutTargetsResultEntry](#) (p. 84)
- [RemoveTargetsResultEntry](#) (p. 85)
- [Rule](#) (p. 86)
- [RunCommandParameters](#) (p. 88)
- [RunCommandTarget](#) (p. 89)
- [SqsParameters](#) (p. 90)
- [Tag](#) (p. 91)
- [Target](#) (p. 92)

AwsVpcConfiguration

This structure specifies the VPC subnets and security groups for the task, and whether a public IP address is to be used. This structure is relevant only for ECS tasks that use the `awsvpc` network mode.

Contents

AssignPublicIp

Specifies whether the task's elastic network interface receives a public IP address. You can specify `ENABLED` only when `LaunchType` in `EcsParameters` is set to `FARGATE`.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

SecurityGroups

Specifies the security groups associated with the task. These security groups must all be in the same VPC. You can specify as many as five security groups. If you do not specify a security group, the default security group for the VPC is used.

Type: Array of strings

Required: No

Subnets

Specifies the subnets associated with the task. These subnets must all be in the same VPC. You can specify as many as 16 subnets.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

BatchArrayProperties

The array properties for the submitted job, such as the size of the array. The array size can be between 2 and 10,000. If you specify array properties for a job, it becomes an array job. This parameter is used only if the target is an AWS Batch job.

Contents

Size

The size of the array, if this is an array batch job. Valid values are integers between 2 and 10,000.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

BatchParameters

The custom parameters to be used when the target is an AWS Batch job.

Contents

ArrayProperties

The array properties for the submitted job, such as the size of the array. The array size can be between 2 and 10,000. If you specify array properties for a job, it becomes an array job. This parameter is used only if the target is an AWS Batch job.

Type: [BatchArrayProperties \(p. 71\)](#) object

Required: No

JobDefinition

The ARN or name of the job definition to use if the event target is an AWS Batch job. This job definition must already exist.

Type: String

Required: Yes

JobName

The name to use for this execution of the job, if the target is an AWS Batch job.

Type: String

Required: Yes

RetryStrategy

The retry strategy to use for failed jobs, if the target is an AWS Batch job. The retry strategy is the number of times to retry the failed job execution. Valid values are 1–10. When you specify a retry strategy here, it overrides the retry strategy defined in the job definition.

Type: [BatchRetryStrategy \(p. 73\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

BatchRetryStrategy

The retry strategy to use for failed jobs, if the target is an AWS Batch job. If you specify a retry strategy here, it overrides the retry strategy defined in the job definition.

Contents

Attempts

The number of times to attempt to retry, if the job fails. Valid values are 1–10.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Condition

A JSON string which you can use to limit the event bus permissions you are granting to only accounts that fulfill the condition. Currently, the only supported condition is membership in a certain AWS organization. The string must contain `Type`, `Key`, and `Value` fields. The `Value` field specifies the ID of the AWS organization. Following is an example value for `Condition`:

```
'{"Type" : "StringEquals", "Key": "aws:PrincipalOrgID", "Value":  
"o-1234567890"}'
```

Contents

Key

Specifies the key for the condition. Currently the only supported key is `aws:PrincipalOrgID`.

Type: String

Required: Yes

Type

Specifies the type of condition. Currently the only supported value is `StringEquals`.

Type: String

Required: Yes

Value

Specifies the value for the key. Currently, this must be the ID of the organization.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

EcsParameters

The custom parameters to be used when the target is an Amazon ECS task.

Contents

Group

Specifies an ECS task group for the task. The maximum length is 255 characters.

Type: String

Required: No

LaunchType

Specifies the launch type on which your task is running. The launch type that you specify here must match one of the launch type (compatibilities) of the target task. The `FARGATE` value is supported only in the Regions where AWS Fargate with Amazon ECS is supported. For more information, see [AWS Fargate on Amazon ECS](#) in the *Amazon Elastic Container Service Developer Guide*.

Type: String

Valid Values: `EC2` | `FARGATE`

Required: No

NetworkConfiguration

Use this structure if the ECS task uses the `awsvpc` network mode. This structure specifies the VPC subnets and security groups associated with the task, and whether a public IP address is to be used. This structure is required if `LaunchType` is `FARGATE` because the `awsvpc` mode is required for Fargate tasks.

If you specify `NetworkConfiguration` when the target ECS task does not use the `awsvpc` network mode, the task fails.

Type: [NetworkConfiguration \(p. 80\)](#) object

Required: No

PlatformVersion

Specifies the platform version for the task. Specify only the numeric portion of the platform version, such as `1.1.0`.

This structure is used only if `LaunchType` is `FARGATE`. For more information about valid platform versions, see [AWS Fargate Platform Versions](#) in the *Amazon Elastic Container Service Developer Guide*.

Type: String

Required: No

TaskCount

The number of tasks to create based on `TaskDefinition`. The default is 1.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

TaskDefinitionArn

The ARN of the task definition to use if the event target is an Amazon ECS task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

InputTransformer

Contains the parameters needed for you to provide custom input to a target based on one or more pieces of data extracted from the event.

Contents

InputPathsMap

Map of JSON paths to be extracted from the event. You can then insert these in the template in `InputTemplate` to produce the output you want to be sent to the target.

`InputPathsMap` is an array key-value pairs, where each value is a valid JSON path. You can have as many as 10 key-value pairs. You must use JSON dot notation, not bracket notation.

The keys cannot start with "AWS."

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Key Pattern: `[A-Za-z0-9_\\-]+`

Value Length Constraints: Maximum length of 256.

Required: No

InputTemplate

Input template where you specify placeholders that will be filled with the values of the keys from `InputPathsMap` to customize the data sent to the target. Enclose each `InputPathsMaps` value in brackets: `<value>` The `InputTemplate` must be valid JSON.

If `InputTemplate` is a JSON object (surrounded by curly braces), the following restrictions apply:

- The placeholder cannot be used as an object key.
- Object values cannot include quote marks.

The following example shows the syntax for using `InputPathsMap` and `InputTemplate`.

```
"InputTransformer":
{
  "InputPathsMap": {"instance": "$.detail.instance", "status":
    "$.detail.status"},
  "InputTemplate": "<instance> is in state <status>"
}
```

To have the `InputTemplate` include quote marks within a JSON string, escape each quote marks with a slash, as in the following example:

```
"InputTransformer":
{
  "InputPathsMap": {"instance": "$.detail.instance", "status":
    "$.detail.status"},
  "InputTemplate": "<instance> is in state <status>"
}
```

```
"InputTemplate": "<instance> is in state \<status>"  
}
```

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8192.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

KinesisParameters

This object enables you to specify a JSON path to extract from the event and use as the partition key for the Amazon Kinesis data stream, so that you can control the shard to which the event goes. If you do not include this parameter, the default is to use the `eventId` as the partition key.

Contents

PartitionKeyPath

The JSON path to be extracted from the event and used as the partition key. For more information, see [Amazon Kinesis Streams Key Concepts](#) in the *Amazon Kinesis Streams Developer Guide*.

Type: String

Length Constraints: Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

NetworkConfiguration

This structure specifies the network configuration for an ECS task.

Contents

awsvpcConfiguration

Use this structure to specify the VPC subnets and security groups for the task, and whether a public IP address is to be used. This structure is relevant only for ECS tasks that use the `awsvpc` network mode.

Type: [AwsVpcConfiguration \(p. 70\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

PutEventsRequestEntry

Represents an event to be submitted.

Contents

Detail

A valid JSON string. There is no other schema imposed. The JSON string may contain fields and nested subobjects.

Type: String

Required: No

DetailType

Free-form string used to decide what fields to expect in the event detail.

Type: String

Required: No

Resources

AWS resources, identified by Amazon Resource Name (ARN), which the event primarily concerns. Any number, including zero, may be present.

Type: Array of strings

Required: No

Source

The source of the event. This field is required.

Type: String

Required: No

Time

The time stamp of the event, per [RFC3339](#). If no time stamp is provided, the time stamp of the [PutEvents](#) (p. 32) call is used.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

PutEventsResultEntry

Represents an event that failed to be submitted.

Contents

ErrorCode

The error code that indicates why the event submission failed.

Type: String

Required: No

ErrorMessage

The error message that explains why the event submission failed.

Type: String

Required: No

EventId

The ID of the event.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

PutTargetsResultEntry

Represents a target that failed to be added to a rule.

Contents

ErrorCode

The error code that indicates why the target addition failed. If the value is `ConcurrentModificationException`, too many requests were made at the same time.

Type: String

Required: No

ErrorMessage

The error message that explains why the target addition failed.

Type: String

Required: No

TargetId

The ID of the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\ . \ _ _ A - Z a - z 0 - 9] +`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

RemoveTargetsResultEntry

Represents a target that failed to be removed from a rule.

Contents

ErrorCode

The error code that indicates why the target removal failed. If the value is `ConcurrentModificationException`, too many requests were made at the same time.

Type: String

Required: No

ErrorMessage

The error message that explains why the target removal failed.

Type: String

Required: No

TargetId

The ID of the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\ . \ _ _ A - Z a - z 0 - 9] +`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Rule

Contains information about a rule in Amazon CloudWatch Events.

Contents

Arn

The Amazon Resource Name (ARN) of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

Description

The description of the rule.

Type: String

Length Constraints: Maximum length of 512.

Required: No

EventPattern

The event pattern of the rule. For more information, see [Events and Event Patterns](#) in the *Amazon CloudWatch Events User Guide*.

Type: String

Required: No

ManagedBy

If the rule was created on behalf of your account by an AWS service, this field displays the principal name of the service that created the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

Name

The name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\.__A-Za-z0-9]+`

Required: No

RoleArn

The Amazon Resource Name (ARN) of the role that is used for target invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

ScheduleExpression

The scheduling expression. For example, "cron(0 20 * * ? *)", "rate(5 minutes)".

Type: String

Length Constraints: Maximum length of 256.

Required: No

State

The state of the rule.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

RunCommandParameters

This parameter contains the criteria (either InstanceIds or a tag) used to specify which EC2 instances are to be sent the command.

Contents

RunCommandTargets

Currently, we support including only one RunCommandTarget block, which specifies either an array of InstanceIds or a tag.

Type: Array of [RunCommandTarget \(p. 89\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

RunCommandTarget

Information about the EC2 instances that are to be sent the command, specified as key-value pairs. Each `RunCommandTarget` block can include only one key, but this key may specify multiple values.

Contents

Key

Can be either `tag`: *tag-key* or `InstanceIds`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^\p{L}\p{Z}\p{N}_ : / = + \ - @] * $`

Required: Yes

Values

If `Key` is `tag`: *tag-key*, `Values` is a list of tag values. If `Key` is `InstanceIds`, `Values` is a list of Amazon EC2 instance IDs.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

SqsParameters

This structure includes the custom parameter to be used when the target is an SQS FIFO queue.

Contents

MessageGroupId

The FIFO message group ID to use as the target.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Tag

A key-value pair associated with an AWS resource. In CloudWatch Events, rules support tagging.

Contents

Key

A string you can use to assign a value. The combination of tag keys and values can help you organize and categorize your resources.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Value

The value for the specified tag key.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Target

Targets are the resources to be invoked when a rule is triggered. For a complete list of services and resources that can be set as a target, see [PutTargets \(p. 44\)](#).

If you are setting the event bus of another account as the target, and that account granted permission to your account through an organization instead of directly by the account ID, then you must specify a `RoleArn` with proper permissions in the `Target` structure. For more information, see [Sending and Receiving Events Between AWS Accounts](#) in the *Amazon CloudWatch Events User Guide*.

Contents

Arn

The Amazon Resource Name (ARN) of the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: Yes

BatchParameters

If the event target is an AWS Batch job, this contains the job definition, job name, and other parameters. For more information, see [Jobs](#) in the *AWS Batch User Guide*.

Type: [BatchParameters \(p. 72\)](#) object

Required: No

EcsParameters

Contains the Amazon ECS task definition and task count to be used, if the event target is an Amazon ECS task. For more information about Amazon ECS tasks, see [Task Definitions](#) in the *Amazon EC2 Container Service Developer Guide*.

Type: [EcsParameters \(p. 75\)](#) object

Required: No

Id

The ID of the target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\. _ - _A - Z a - z 0 - 9] +`

Required: Yes

Input

Valid JSON text passed to the target. In this case, nothing from the event itself is passed to the target. For more information, see [The JavaScript Object Notation \(JSON\) Data Interchange Format](#).

Type: String

Length Constraints: Maximum length of 8192.

Required: No

InputPath

The value of the JSONPath that is used for extracting part of the matched event when passing it to the target. You must use JSON dot notation, not bracket notation. For more information about JSON paths, see [JSONPath](#).

Type: String

Length Constraints: Maximum length of 256.

Required: No

InputTransformer

Settings to enable you to provide custom input to a target based on certain event data. You can extract one or more key-value pairs from the event and then use that data to send customized input to the target.

Type: [InputTransformer \(p. 77\)](#) object

Required: No

KinesisParameters

The custom parameter you can use to control the shard assignment, when the target is a Kinesis data stream. If you do not include this parameter, the default is to use the `eventId` as the partition key.

Type: [KinesisParameters \(p. 79\)](#) object

Required: No

RoleArn

The Amazon Resource Name (ARN) of the IAM role to be used for this target when the rule is triggered. If one rule triggers multiple targets, you can use a different IAM role for each target.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Required: No

RunCommandParameters

Parameters used when you are using the rule to invoke Amazon EC2 Run Command.

Type: [RunCommandParameters \(p. 88\)](#) object

Required: No

SqsParameters

Contains the message group ID to use when the target is a FIFO queue.

If you specify an SQS FIFO queue as a target, the queue must have content-based deduplication enabled.

Type: [SqsParameters \(p. 90\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Go - Pilot](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Making API Requests

Query requests used with CloudWatch Events are HTTP or HTTPS requests that use the HTTP verb GET or POST and a Query parameter named `Action` or `Operation`. This documentation uses `Action`, although `Operation` is supported for backward compatibility.

CloudWatch Events Endpoints

An endpoint is a URL that serves as an entry point for a web service. You can select a regional endpoint when you make your requests to reduce latency. For information about the endpoints used with CloudWatch Events, see [Regions and Endpoints](#) in the *Amazon Web Services General Reference*.

Query Parameters

Each query request must include some common parameters to handle authentication and selection of an action. For more information, see [Common Parameters \(p. 97\)](#).

Some API operations take lists of parameters. These lists are specified using the following notation: `param.member.n`. Values of `n` are integers starting from 1. All lists of parameters must follow this notation, including lists that contain only one parameter. For example, a Query parameter list looks like this:

```
&attribute.member.1=this  
&attribute.member.2=that
```

Request Identifiers

In every response from an AWS Query API, there is a `ResponseMetadata` element, which contains a `RequestId` element. This string is a unique identifier that AWS assigns to provide tracking information. Although `RequestId` is included as part of every response, it is not listed on the individual API documentation pages to improve readability and to reduce redundancy.

Query API Authentication

You can send query requests over either HTTP or HTTPS. Regardless of which protocol you use, you must include a signature in every query request. For more information about creating and including a signature, see [Signing AWS API Requests](#) in the *Amazon Web Services General Reference*.

Available Libraries

AWS provides libraries, sample code, tutorials, and other resources for software developers who prefer to build applications using language-specific APIs instead of the command-line tools and Query API. These libraries provide basic functions (not included in the APIs), such as request authentication, request

retries, and error handling so that it is easier to get started. Libraries and resources are available for the following languages and platforms:

- [AWS Mobile SDK for Android](#)
- [AWS SDK for Go](#)
- [AWS Mobile SDK for iOS](#)
- [AWS SDK for Java 2.x](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for JavaScript in Node.js](#)
- [AWS SDK for .NET](#)
- [AWS SDK for PHP](#)
- [AWS SDK for Python \(Boto\)](#)
- [AWS SDK for Ruby](#)

For libraries and sample code in all languages, see [Sample Code & Libraries](#).

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400