
Amazon EC2 Container Registry

API Reference

API Version 2015-09-21



Amazon EC2 Container Registry: API Reference

Copyright © 2018 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchCheckLayerAvailability	3
Request Syntax	3
Request Parameters	3
Response Syntax	4
Response Elements	4
Errors	4
Example	5
See Also	6
BatchDeleteImage	7
Request Syntax	7
Request Parameters	7
Response Syntax	8
Response Elements	8
Errors	8
Examples	9
See Also	10
BatchGetImage	12
Request Syntax	12
Request Parameters	12
Response Syntax	13
Response Elements	13
Errors	13
Example	14
See Also	15
CompleteLayerUpload	16
Request Syntax	16
Request Parameters	16
Response Syntax	17
Response Elements	17
Errors	18
See Also	18
CreateRepository	20
Request Syntax	20
Request Parameters	20
Response Syntax	20
Response Elements	20
Errors	21
Example	21
See Also	22
DeleteLifecyclePolicy	23
Request Syntax	23
Request Parameters	23
Response Syntax	23
Response Elements	23
Errors	24
Example	25
See Also	25
DeleteRepository	27
Request Syntax	27
Request Parameters	27
Response Syntax	27
Response Elements	28

Errors	28
Example	28
See Also	29
DeleteRepositoryPolicy	30
Request Syntax	30
Request Parameters	30
Response Syntax	30
Response Elements	30
Errors	31
Example	31
See Also	32
DescribeImages	34
Request Syntax	34
Request Parameters	34
Response Syntax	35
Response Elements	35
Errors	36
Example	36
See Also	38
DescribeRepositories	39
Request Syntax	39
Request Parameters	39
Response Syntax	40
Response Elements	40
Errors	40
Example	41
See Also	42
GetAuthorizationToken	43
Request Syntax	43
Request Parameters	43
Response Syntax	43
Response Elements	43
Errors	44
Example	44
See Also	45
GetDownloadUrlForLayer	46
Request Syntax	46
Request Parameters	46
Response Syntax	47
Response Elements	47
Errors	47
See Also	48
GetLifecyclePolicy	49
Request Syntax	49
Request Parameters	49
Response Syntax	49
Response Elements	49
Errors	50
Example	51
See Also	51
GetLifecyclePolicyPreview	53
Request Syntax	53
Request Parameters	53
Response Syntax	54
Response Elements	55
Errors	56
Example	56

See Also	57
GetRepositoryPolicy	58
Request Syntax	58
Request Parameters	58
Response Syntax	58
Response Elements	58
Errors	59
Example	59
See Also	60
InitiateLayerUpload	62
Request Syntax	62
Request Parameters	62
Response Syntax	62
Response Elements	62
Errors	63
See Also	63
ListImages	64
Request Syntax	64
Request Parameters	64
Response Syntax	65
Response Elements	65
Errors	66
Example	66
See Also	67
PutImage	68
Request Syntax	68
Request Parameters	68
Response Syntax	69
Response Elements	69
Errors	69
Example	70
See Also	71
PutLifecyclePolicy	72
Request Syntax	72
Request Parameters	72
Response Syntax	72
Response Elements	73
Errors	73
Example	73
See Also	74
SetRepositoryPolicy	76
Request Syntax	76
Request Parameters	76
Response Syntax	77
Response Elements	77
Errors	77
Example	78
See Also	79
StartLifecyclePolicyPreview	80
Request Syntax	80
Request Parameters	80
Response Syntax	80
Response Elements	81
Errors	81
Example	82
See Also	83
UploadLayerPart	84

Request Syntax	84
Request Parameters	84
Response Syntax	85
Response Elements	85
Errors	86
See Also	86
Data Types	88
AuthorizationData	89
Contents	89
See Also	89
DescribeImagesFilter	90
Contents	90
See Also	90
Image	91
Contents	91
See Also	91
ImageDetail	92
Contents	92
See Also	93
ImageFailure	94
Contents	94
See Also	94
ImageIdentifier	95
Contents	95
See Also	95
Layer	96
Contents	96
See Also	96
LayerFailure	97
Contents	97
See Also	97
LifecyclePolicyPreviewFilter	98
Contents	98
See Also	98
LifecyclePolicyPreviewResult	99
Contents	99
See Also	99
LifecyclePolicyPreviewSummary	100
Contents	100
See Also	100
LifecyclePolicyRuleAction	101
Contents	101
See Also	101
ListImagesFilter	102
Contents	102
See Also	102
Repository	103
Contents	103
See Also	103
Common Parameters	105
Common Errors	107

Welcome

Amazon Elastic Container Registry (Amazon ECR) is a managed Docker registry service. Customers can use the familiar Docker CLI to push, pull, and manage images. Amazon ECR provides a secure, scalable, and reliable registry. Amazon ECR supports private Docker repositories with resource-based permissions using IAM so that specific users or Amazon EC2 instances can access repositories and images. Developers can use the Docker CLI to author and manage images.

This document was last published on March 22, 2018.

Actions

The following actions are supported:

- [BatchCheckLayerAvailability](#) (p. 3)
- [BatchDeleteImage](#) (p. 7)
- [BatchGetImage](#) (p. 12)
- [CompleteLayerUpload](#) (p. 16)
- [CreateRepository](#) (p. 20)
- [DeleteLifecyclePolicy](#) (p. 23)
- [DeleteRepository](#) (p. 27)
- [DeleteRepositoryPolicy](#) (p. 30)
- [DescribeImages](#) (p. 34)
- [DescribeRepositories](#) (p. 39)
- [GetAuthorizationToken](#) (p. 43)
- [GetDownloadUrlForLayer](#) (p. 46)
- [GetLifecyclePolicy](#) (p. 49)
- [GetLifecyclePolicyPreview](#) (p. 53)
- [GetRepositoryPolicy](#) (p. 58)
- [InitiateLayerUpload](#) (p. 62)
- [ListImages](#) (p. 64)
- [PutImage](#) (p. 68)
- [PutLifecyclePolicy](#) (p. 72)
- [SetRepositoryPolicy](#) (p. 76)
- [StartLifecyclePolicyPreview](#) (p. 80)
- [UploadLayerPart](#) (p. 84)

BatchCheckLayerAvailability

Check the availability of multiple image layers in a specified registry and repository.

Note

This operation is used by the Amazon ECR proxy, and it is not intended for general use by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

Request Syntax

```
{  
  "layerDigests": [ "string" ],  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[layerDigests \(p. 3\)](#)

The digests of the image layers to check.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: Yes

[registryId \(p. 3\)](#)

The AWS account ID associated with the registry that contains the image layers to check. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 3\)](#)

The name of the repository that is associated with the image layers to check.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "layerDigest": "string"
    }
  ],
  "layers": [
    {
      "layerAvailability": "string",
      "layerDigest": "string",
      "layerSize": number,
      "mediaType": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failures (p. 4)

Any failures associated with the call.

Type: Array of [LayerFailure \(p. 97\)](#) objects

layers (p. 4)

A list of image layer objects corresponding to the image layer references in the request.

Type: Array of [Layer \(p. 96\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example checks the availability of an image layer in the amazonlinux repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 126
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchCheckLayerAvailability
X-Amz-Date: 20161216T195733Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "layerDigests": [
    "sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8"
  ],
  "repositoryName": "amazonlinux"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 19:57:33 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 233
Connection: keep-alive
x-amzn-RequestId: e2422faf-c3c9-11e6-a3ee-63b3b5dcf3b9

{
  "failures": [],
  "layers": [
    {
      "layerAvailability": "AVAILABLE",
      "layerDigest":
        "sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8",
      "layerSize": 91768077,
      "mediaType": "application/vnd.docker.image.rootfs.diff.tar.gzip"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

BatchDeleteImage

Deletes a list of specified images within a specified repository. Images are specified with either `imageTag` or `imageDigest`.

You can remove a tag from an image by specifying the image's tag in your request. When you remove the last tag from an image, the image is deleted from your repository.

You can completely delete an image (and all of its tags) by specifying the image's digest in your request.

Request Syntax

```
{
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

imageIds (p. 7)

A list of image ID references that correspond to images to delete. The format of the `imageIds` reference is `imageTag=tag` or `imageDigest=digest`.

Type: Array of [ImageIdentifier \(p. 95\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

registryId (p. 7)

The AWS account ID associated with the registry that contains the image to delete. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName (p. 7)

The repository that contains the image to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "imageId": {
        "imageDigest": "string",
        "imageTag": "string"
      }
    }
  ],
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failures (p. 8)

Any failures associated with the call.

Type: Array of [ImageFailure \(p. 94\)](#) objects

imageIds (p. 8)

The image IDs of the deleted images.

Type: Array of [ImageIdentifier \(p. 95\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Examples

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes an image in the ubuntu repository with the `imageTag` value of `xenial`.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 66
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchDeleteImage
X-Amz-Date: 20161216T193711Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu",
  "imageIds": [
    {
      "imageTag": "xenial"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 19:37:11 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 138
Connection: keep-alive
x-amzn-RequestId: 09cc7023-c3c7-11e6-8acf-61b7dd8abe56

{
  "failures": [],
  "imageIds": [
    {
      "imageDigest":
"sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a",
      "imageTag": "xenial"
    }
  ]
}
```

```
}  
]  
}
```

Example

This example deletes an image (and all of its tags) in the `ubuntu` repository with the `imageDigest` value of `sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a`.

Sample Request

```
POST / HTTP/1.1  
Host: ecr.us-west-2.amazonaws.com  
Accept-Encoding: identity  
Content-Length: 134  
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchDeleteImage  
X-Amz-Date: 20161216T194250Z  
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79  
Content-Type: application/x-amz-json-1.1  
Authorization: AUTHPARAMS  
  
{  
  "repositoryName": "ubuntu",  
  "imageIds": [  
    {  
      "imageDigest":  
      "sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a"  
    }  
  ]  
}
```

Sample Response

```
HTTP/1.1 200 OK  
Server: Server  
Date: Fri, 16 Dec 2016 19:42:50 GMT  
Content-Type: application/x-amz-json-1.1  
Content-Length: 248  
Connection: keep-alive  
x-amzn-RequestId: d441a9f6-c3c7-11e6-8acf-61b7dd8abe56  
  
{  
  "failures": [],  
  "imageIds": [  
    {  
      "imageDigest":  
      "sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a",  
      "imageTag": "xenial"  
    },  
    {  
      "imageDigest":  
      "sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a",  
      "imageTag": "latest"  
    }  
  ]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

BatchGetImage

Gets detailed information for specified images within a specified repository. Images are specified with either `imageTag` or `imageDigest`.

Request Syntax

```
{
  "acceptedMediaTypes": [ "string" ],
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[acceptedMediaTypes \(p. 12\)](#)

The accepted media types for the request.

Valid values: `application/vnd.docker.distribution.manifest.v1+json` | `application/vnd.docker.distribution.manifest.v2+json` | `application/vnd.oci.image.manifest.v1+json`

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

[imageIds \(p. 12\)](#)

A list of image ID references that correspond to images to describe. The format of the `imageIds` reference is `imageTag=tag` or `imageDigest=digest`.

Type: Array of [ImageIdentifier \(p. 95\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

[registryId \(p. 12\)](#)

The AWS account ID associated with the registry that contains the images to describe. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName (p. 12)

The repository that contains the images to describe.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "failures": [
    {
      "failureCode": "string",
      "failureReason": "string",
      "imageId": {
        "imageDigest": "string",
        "imageTag": "string"
      }
    }
  ],
  "images": [
    {
      "imageId": {
        "imageDigest": "string",
        "imageTag": "string"
      },
      "imageManifest": "string",
      "registryId": "string",
      "repositoryName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

failures (p. 13)

Any failures associated with the call.

Type: Array of [ImageFailure \(p. 94\)](#) objects

images (p. 13)

A list of image objects corresponding to the image references in the request.

Type: Array of [Image \(p. 91\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes an image in the amazonlinux repository with the imageTag value of latest.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 71
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.BatchGetImage
X-Amz-Date: 20161216T195356Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "amazonlinux",
  "imageIds": [
    {
      "imageTag": "latest"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
```

```
Date: Fri, 16 Dec 2016 19:53:56 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 800
Connection: keep-alive
x-amzn-RequestId: 60dc1ea1-c3c9-11e6-aa04-25c3a5fb1b54

{
  "failures": [],
  "images": [
    {
      "imageId": {
        "imageDigest":
          "sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
        "imageTag": "latest"
      },
      "imageManifest": "{\n  \"schemaVersion\": 2,\n  \"mediaType\": \"application/
vnd.docker.distribution.manifest.v2+json\",\n  \"config\": {\n    \"mediaType\":
\"application/vnd.docker.container.image.v1+json\",\n    \"size\": 1486,\n
    \"digest\": \"sha256:5b52b314511a611975c2c65e695d920acdf8ae8848fe0ef00b7d018d1f118b64\"\n
  },\n  \"layers\": [\n    {\n      \"mediaType\": \"application/
vnd.docker.image.rootfs.diff.tar.gzip\",\n      \"size\": 91768077,\n      \"digest
\": \"sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8\"\n
    }]\n}",
      "registryId": "012345678910",
      "repositoryName": "amazonlinux"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

CompleteLayerUpload

Informs Amazon ECR that the image layer upload has completed for a specified registry, repository name, and upload ID. You can optionally provide a sha256 digest of the image layer for data validation purposes.

Note

This operation is used by the Amazon ECR proxy, and it is not intended for general use by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

Request Syntax

```
{
  "layerDigests": [ "string" ],
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[layerDigests \(p. 16\)](#)

The sha256 digest of the image layer.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Pattern: [a-zA-Z0-9-_.]+:[a-fA-F0-9]+

Required: Yes

[registryId \(p. 16\)](#)

The AWS account ID associated with the registry to which to upload layers. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 16\)](#)

The name of the repository to associate with the image layer.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

[uploadId \(p. 16\)](#)

The upload ID from a previous [InitiateLayerUpload \(p. 62\)](#) operation to associate with the image layer.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

Response Syntax

```
{
  "layerDigest": "string",
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[layerDigest \(p. 17\)](#)

The sha256 digest of the image layer.

Type: String

Pattern: [a-zA-Z0-9-_.]+:[a-fA-F0-9]+

[registryId \(p. 17\)](#)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

[repositoryName \(p. 17\)](#)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

[uploadId \(p. 17\)](#)

The upload ID associated with the layer.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

EmptyUploadException

The specified layer upload does not contain any layer parts.

HTTP Status Code: 400

InvalidLayerException

The layer digest calculation performed by Amazon ECR upon receipt of the image layer does not match the digest specified.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LayerAlreadyExistsException

The image layer already exists in the associated repository.

HTTP Status Code: 400

LayerPartTooSmallException

Layer parts must be at least 5 MiB in size.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

UploadNotFoundException

The upload could not be found, or the specified upload id is not valid for this repository.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

CreateRepository

Creates an image repository.

Request Syntax

```
{  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

repositoryName (p. 20)

The name to use for the repository. The repository name may be specified on its own (such as `nginx-web-app`) or it can be prepended with a namespace to group the repository into a category (such as `project-a/nginx-web-app`).

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "repository": {  
    "createdAt": number,  
    "registryId": "string",  
    "repositoryArn": "string",  
    "repositoryName": "string",  
    "repositoryUri": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

repository (p. 20)

The repository that was created.

Type: [Repository \(p. 103\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR Default Service Limits](#) in the Amazon Elastic Container Registry User Guide.

HTTP Status Code: 400

RepositoryAlreadyExistsException

The specified repository already exists in the specified registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a repository called `nginx-web-app` inside the `project-a` namespace in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 45
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.CreateRepository
X-Amz-Date: 20151130T203458Z
User-Agent: aws-cli/1.9.9 Python/2.7.10 Darwin/14.5.0 botocore/1.3.9
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "project-a/nginx-web-app"
```

```
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Mon, 30 Nov 2015 20:34:58 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 175
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "repository": {
    "registryId": "012345678910",
    "repositoryArn": "arn:aws:ecr:us-east-1:012345678910:repository/project-a/nginx-web-
app",
    "repositoryName": "project-a/nginx-web-app"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteLifecyclePolicy

Deletes the specified lifecycle policy.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[registryId \(p. 23\)](#)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 23\)](#)

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "lastEvaluatedAt": number,  
  "lifecyclePolicyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lastEvaluatedAt (p. 23)

The time stamp of the last time that the lifecycle policy was run.

Type: Timestamp

lifecyclePolicyText (p. 23)

The JSON lifecycle policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 10240.

registryId (p. 23)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName (p. 23)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LifecyclePolicyNotFoundException

The lifecycle policy could not be found, and no policy is set to the repository.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a lifecycle policy for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DeleteLifecyclePolicy
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T223937Z
Authorization: AUTHPARAMS
Content-Length: 48

{
  "repositoryName": "project-a/amazon-ecs-sample",
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 19:42:18 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 340
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lastEvaluatedAt": 1.504295007E9,
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\": 1,\n      \"description\": \"Expire images older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n        \"countType\": \"sinceImagePushed\",\n        \"countUnit\": \"days\",\n        \"countNumber\": 14\n      },\n      \"action\": {\n        \"type\": \"expire\"\n      }\n    }\n  ],\n  \"registryId\": \"012345678910\",\n  \"repositoryName\": \"project-a/amazon-ecs-sample\"\n}",
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteRepository

Deletes an existing image repository. If a repository contains images, you must use the `force` option to delete it.

Request Syntax

```
{  
  "force": boolean,  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 105).

The request accepts the following data in JSON format.

force (p. 27)

If a repository contains images, forces the deletion.

Type: Boolean

Required: No

registryId (p. 27)

The AWS account ID associated with the registry that contains the repository to delete. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName (p. 27)

The name of the repository to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "repository": {  
    "createdAt": number,  
    "registryId": "string",  
  }  
}
```

```
"repositoryArn": "string",  
"repositoryName": "string",  
"repositoryUri": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[repository \(p. 27\)](#)

The repository that was deleted.

Type: [Repository \(p. 103\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotEmptyException

The specified repository contains images. To delete a repository that contains images, you must force the deletion with the `force` parameter.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (`AUTHPARAMS`) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes a repository named `ubuntu` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 43
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DeleteRepository
X-Amz-Date: 20151130T201424Z
User-Agent: aws-cli/1.9.9 Python/2.7.10 Darwin/14.5.0 botocore/1.3.9
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu",
  "force": true
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Mon, 30 Nov 2015 20:14:24 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 141
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "repository": {
    "registryId": "012345678910",
    "repositoryArn": "arn:aws:ecr:us-east-1:012345678910:repository/ubuntu",
    "repositoryName": "ubuntu"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteRepositoryPolicy

Deletes the repository policy from a specified repository.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[registryId \(p. 30\)](#)

The AWS account ID associated with the registry that contains the repository policy to delete. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 30\)](#)

The name of the repository that is associated with the repository policy to delete.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "policyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText (p. 30)

The JSON repository policy that was deleted from the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId (p. 30)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName (p. 30)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

RepositoryPolicyNotFoundException

The specified repository and registry combination does not have an associated repository policy.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (`AUTHPARAMS`) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example deletes the repository policy from the ubuntu repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 28
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DeleteRepositoryPolicy
X-Amz-Date: 20151215T003722Z
User-Agent: aws-cli/1.9.10 Python/2.7.10 Darwin/14.5.0 botocore/1.3.10
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Tue, 15 Dec 2015 00:37:22 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 301
Connection: keep-alive
x-amzn-RequestId: 01817918-a2c4-11e5-a19f-014c7a9aad99

{
  "policyText": "{\n  \"Version\" : \"2012-10-17\",\n  \"Statement\" : [ {\n    \"Sid\" :  
    \"AllowPull\",\n    \"Effect\" : \"Allow\",\n    \"Principal\" : \"*\",\n    \"Action\" :  
    [ \"ecr:BatchGetImage\", \"ecr:GetDownloadUrlForLayer\" ]\n  } ]\n}",
  "registryId": "012345678910",
  "repositoryName": "ubuntu"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeImages

Returns metadata about the images in a repository, including image size, image tags, and creation date.

Note

Beginning with Docker version 1.9, the Docker client compresses image layers before pushing them to a V2 Docker registry. The output of the `docker images` command shows the uncompressed image size, so it may return a larger image size than the image sizes returned by [DescribeImages](#) (p. 34).

Request Syntax

```
{
  "filter": {
    "tagStatus": "string"
  },
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 105).

The request accepts the following data in JSON format.

filter (p. 34)

The filter key and value with which to filter your `DescribeImages` results.

Type: [DescribeImagesFilter](#) (p. 90) object

Required: No

imageIds (p. 34)

The list of image IDs for the requested repository.

Type: Array of [ImageIdentifier](#) (p. 95) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

maxResults (p. 34)

The maximum number of repository results returned by `DescribeImages` in paginated output. When this parameter is used, `DescribeImages` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `DescribeImages` request with the returned `nextToken` value. This value can be between 1 and 100. If this parameter is not used, then `DescribeImages` returns up to 100 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken \(p. 34\)](#)

The `nextToken` value returned from a previous paginated `DescribeImages` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return.

Type: String

Required: No

[registryId \(p. 34\)](#)

The AWS account ID associated with the registry that contains the repository in which to describe images. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

[repositoryName \(p. 34\)](#)

A list of repositories to describe. If this parameter is omitted, then all repositories in a registry are described.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "imageDetails": [
    {
      "imageDigest": "string",
      "imagePushedAt": number,
      "imageSizeInBytes": number,
      "imageTags": [ "string" ],
      "registryId": "string",
      "repositoryName": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

imageDetails (p. 35)

A list of [ImageDetail \(p. 92\)](#) objects that contain data about the image.

Type: Array of [ImageDetail \(p. 92\)](#) objects

nextToken (p. 35)

The `nextToken` value to include in a future `DescribeImages` request. When the results of a `DescribeImages` request exceed `maxResults`, this value can be used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

ImageNotFoundException

The image requested does not exist in the specified repository.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (`AUTHPARAMS`) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes the images in a repository named `ubuntu` in the default account. Note that the image with the digest

sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a is tagged as latest and xenial.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 28
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeImages
X-Amz-Date: 20161216T193133Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1

Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 19:31:33 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 1107
Connection: keep-alive
x-amzn-RequestId: 404826b1-c3c6-11e6-a9e5-e3c203a2f07f

{
  "imageDetails": [
    {
      "imageDigest":
"sha256:7c70a5ebcc7fcaa22974a71175ba674efce3951fbec624943c891e9d256927c1",
      "imagePushedAt": 1452721263,
      "imageSizeInBytes": 44194573,
      "registryId": "012345678910",
      "repositoryName": "ubuntu"
    },
    {
      "imageDigest":
"sha256:abdc090336ba4503bd72d0961a4f3d45134900d9a793d3f0c06a64d2555fbab7",
      "imagePushedAt": 1481916613,
      "imageSizeInBytes": 39142127,
      "imageTags": [
        "precise"
      ],
      "registryId": "012345678910",
      "repositoryName": "ubuntu"
    },
    {
      "imageDigest":
"sha256:78dea3347768ba553ee8971cfb2dfa4c3efcd96db84ebfcdda59ba8d6057941b",
      "imagePushedAt": 1452721207,
      "imageSizeInBytes": 65747044,
      "registryId": "012345678910",
      "repositoryName": "ubuntu"
    }
  ]
}
```

```
    "imageDigest":  
    "sha256:7a64bc9c8843b0a8c8b8a7e4715b7615e4e1b0d8ca3c7e7a76ec8250899c397a",  
    "imagePushedAt": 1481916523,  
    "imageSizeInBytes": 50223482,  
    "imageTags": [  
      "xenial",  
      "latest"  
    ],  
    "registryId": "012345678910",  
    "repositoryName": "ubuntu"  
  },  
  {  
    "imageDigest":  
    "sha256:881befbe6f54c1e85029fe3a11554342bf765a0849600ecb8fa2f922798b4925",  
    "imagePushedAt": 1481916647,  
    "imageSizeInBytes": 65770577,  
    "imageTags": [  
      "trusty"  
    ],  
    "registryId": "012345678910",  
    "repositoryName": "ubuntu"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeRepositories

Describes image repositories in a registry.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "registryId": "string",  
  "repositoryNames": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[maxResults \(p. 39\)](#)

The maximum number of repository results returned by `DescribeRepositories` in paginated output. When this parameter is used, `DescribeRepositories` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `DescribeRepositories` request with the returned `nextToken` value. This value can be between 1 and 100. If this parameter is not used, then `DescribeRepositories` returns up to 100 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken \(p. 39\)](#)

The `nextToken` value returned from a previous paginated `DescribeRepositories` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return.

Note

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

[registryId \(p. 39\)](#)

The AWS account ID associated with the registry that contains the repositories to be described. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryNames \(p. 39\)](#)

A list of repositories to describe. If this parameter is omitted, then all repositories in a registry are described.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "repositories": [
    {
      "createdAt": number,
      "registryId": "string",
      "repositoryArn": "string",
      "repositoryName": "string",
      "repositoryUri": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken \(p. 40\)](#)

The `nextToken` value to include in a future `DescribeRepositories` request. When the results of a `DescribeRepositories` request exceed `maxResults`, this value can be used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

[repositories \(p. 40\)](#)

A list of repository objects corresponding to valid repositories.

Type: Array of [Repository \(p. 103\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example describes the repositories in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.DescribeRepositories
X-Amz-Date: 20161216T200121Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 20:01:21 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 972
Connection: keep-alive
x-amzn-RequestId: 6a1ca1a2-c3ca-11e6-aacd-d3a31c48f08c

{
  "repositories": [
    {
      "createdAt": 1450223349,
      "registryId": "012345678910",
      "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/ubuntu",

```

```
    "repositoryName": "ubuntu",
    "repositoryUri": "012345678910.dkr.ecr.us-west-2.amazonaws.com/ubuntu"
  },
  {
    "createdAt": 1481915414,
    "registryId": "012345678910",
    "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/amazonlinux",
    "repositoryName": "amazonlinux",
    "repositoryUri": "012345678910.dkr.ecr.us-west-2.amazonaws.com/amazonlinux"
  },
  {
    "createdAt": 1481845593,
    "registryId": "012345678910",
    "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/iis",
    "repositoryName": "iis",
    "repositoryUri": "012345678910.dkr.ecr.us-west-2.amazonaws.com/iis"
  },
  {
    "createdAt": 1479253336,
    "registryId": "012345678910",
    "repositoryArn": "arn:aws:ecr:us-west-2:012345678910:repository/windows_sample_app",
    "repositoryName": "windows_sample_app",
    "repositoryUri": "012345678910.dkr.ecr.us-west-2.amazonaws.com/windows_sample_app"
  }
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

GetAuthorizationToken

Retrieves a token that is valid for a specified registry for 12 hours. This command allows you to use the `docker` CLI to push and pull images with Amazon ECR. If you do not specify a registry, the default registry is assumed.

The `authorizationToken` returned for each registry specified is a base64 encoded string that can be decoded and used in a `docker login` command to authenticate to a registry. The AWS CLI offers an `aws ecr get-login` command that simplifies the login process.

Request Syntax

```
{
  "registryIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 105).

The request accepts the following data in JSON format.

registryIds (p. 43)

A list of AWS account IDs that are associated with the registries for which to get authorization tokens. If you do not specify a registry, the default registry is assumed.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Pattern: [0-9]{12}

Required: No

Response Syntax

```
{
  "authorizationData": [
    {
      "authorizationToken": "string",
      "expiresAt": number,
      "proxyEndpoint": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[authorizationData \(p. 43\)](#)

A list of authorization token data objects that correspond to the `registryIds` values in the request.

Type: Array of [AuthorizationData \(p. 89\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (`AUTHPARAMS`) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example gets an authorization token for your default registry.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 2
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetAuthorizationToken
X-Amz-Date: 20151129T221940Z
User-Agent: aws-cli/1.9.9 Python/2.7.10 Darwin/14.5.0 botocore/1.3.9
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Sun, 29 Nov 2015 22:19:39 GMT
```

```
Content-Type: application/x-amz-json-1.1
Content-Length: 1590
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "authorizationData": [
    {
      "authorizationToken": "QVdT0kNpQzErSHF1ZXZPcUR...",
      "expiresAt": 1448878779.809,
      "proxyEndpoint": "https://012345678910.dkr.ecr.us-east-1.amazonaws.com"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

GetDownloadUrlForLayer

Retrieves the pre-signed Amazon S3 download URL corresponding to an image layer. You can only get URLs for image layers that are referenced in an image.

Note

This operation is used by the Amazon ECR proxy, and it is not intended for general use by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

Request Syntax

```
{
  "layerDigest": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

layerDigest (p. 46)

The digest of the image layer to download.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Required: Yes

registryId (p. 46)

The AWS account ID associated with the registry that contains the image layer to download. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName (p. 46)

The name of the repository that is associated with the image layer to download.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{  
  "downloadUrl": "string",  
  "layerDigest": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

downloadUrl (p. 47)

The pre-signed Amazon S3 download URL for the requested layer.

Type: String

layerDigest (p. 47)

The digest of the image layer to download.

Type: String

Pattern: [a-zA-Z0-9-_.]+:[a-fA-F0-9]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 107).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LayerInaccessibleException

The specified layer is not available because it is not associated with an image. Unassociated image layers may be cleaned up at any time.

HTTP Status Code: 400

LayersNotFoundException

The specified layers could not be found, or the specified layer is not valid for this repository.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

GetLifecyclePolicy

Retrieves the specified lifecycle policy.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

registryId (p. 49)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName (p. 49)

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "lastEvaluatedAt": number,  
  "lifecyclePolicyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lastEvaluatedAt (p. 49)

The time stamp of the last time that the lifecycle policy was run.

Type: Timestamp

lifecyclePolicyText (p. 49)

The JSON lifecycle policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 10240.

registryId (p. 49)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName (p. 49)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LifecyclePolicyNotFoundException

The lifecycle policy could not be found, and no policy is set to the repository.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example retrieves the lifecycle policy for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetLifecyclePolicy
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T210647Z
Authorization: AUTHPARAMS
Content-Length: 48

{
  "repositoryName": "project-a/amazon-ecs-sample"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 21:06:48 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 372
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lastEvaluatedAt": 1.504295007E9,
  "lifecyclePolicyText": "{\n\"rules\":[\n{\n\"rulePriority\":1,\n\"description\":\n\"Expire images older than 14 days\",\n\"selection\":{\n\"tagStatus\":\n\"untagged\",\n\"countType\":\n\"sinceImagePushed\",\n\"countUnit\":\n\"days\",\n\"countNumber\":14},\n\"action\":{\n\"type\":\n\"expire\"}}}],\n\"registryId\":\n\"012345678910\",\n\"repositoryName\":\n\"project-a/amazon-ecs-sample\"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

GetLifecyclePolicyPreview

Retrieves the results of the specified lifecycle policy preview request.

Request Syntax

```
{
  "filter": {
    "tagStatus": "string"
  },
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

filter (p. 53)

An optional parameter that filters results based on image tag status and all tags, if tagged.

Type: [LifecyclePolicyPreviewFilter \(p. 98\)](#) object

Required: No

imageIds (p. 53)

The list of imageIDs to be included.

Type: Array of [ImageIdentifier \(p. 95\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

maxResults (p. 53)

The maximum number of repository results returned by `GetLifecyclePolicyPreviewRequest` in paginated output. When this parameter is used, `GetLifecyclePolicyPreviewRequest` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `GetLifecyclePolicyPreviewRequest` request with the returned `nextToken` value. This value can be between 1 and 100. If this parameter is not used, then `GetLifecyclePolicyPreviewRequest` returns up to 100 results and a `nextToken` value, if

applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken (p. 53)

The `nextToken` value returned from a previous paginated `GetLifecyclePolicyPreviewRequest` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return.

Type: String

Required: No

registryId (p. 53)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: `[0-9]{12}`

Required: No

repositoryName (p. 53)

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

Required: Yes

Response Syntax

```
{
  "lifecyclePolicyText": "string",
  "nextToken": "string",
  "previewResults": [
    {
      "action": {
        "type": "string"
      },
      "appliedRulePriority": number,
      "imageDigest": "string",
      "imagePushedAt": number,
      "imageTags": [ "string" ]
    }
  ],
  "registryId": "string",
  "repositoryName": "string",
  "status": "string",
}
```

```
"summary": {  
  "expiringImageTotalCount": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicyText (p. 54)

The JSON lifecycle policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 10240.

nextToken (p. 54)

The `nextToken` value to include in a future `GetLifecyclePolicyPreview` request. When the results of a `GetLifecyclePolicyPreview` request exceed `maxResults`, this value can be used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

previewResults (p. 54)

The results of the lifecycle policy preview request.

Type: Array of [LifecyclePolicyPreviewResult](#) (p. 99) objects

registryId (p. 54)

The registry ID associated with the request.

Type: String

Pattern: `[0-9]{1,2}`

repositoryName (p. 54)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: `(?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*`

status (p. 54)

The status of the lifecycle policy preview request.

Type: String

Valid Values: `IN_PROGRESS` | `COMPLETE` | `EXPIRED` | `FAILED`

summary (p. 54)

The list of images that is returned as a result of the action.

Type: [LifecyclePolicyPreviewSummary](#) (p. 100) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LifecyclePolicyPreviewNotFoundException

There is no dry run for this repository.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example retrieves the result of a lifecycle policy preview for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetLifecyclePolicyPreview
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T222304Z
Authorization: AUTHPARAMS
Content-Length: 48

{
  "repositoryName": "project-a/amazon-ecs-sample"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 22:23:06 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 640
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lifecyclePolicyText": "{\n  \\"rules\": [\n    {\n      \\"rulePriority\n": 1,\n      \\"description\": \\"Expire images older than 14 days\","n
    \\"selection\": {\n      \\"tagStatus\": \\"untagged\","n
    \\"countType\": \\"sinceImagePushed\","n      \\"countUnit\": \\"days\","n
    \\"countNumber\": 14\n    },\n    \\"action\": {\n
  \\"type\": \\"expire\\"\n    }\n  ]\n}\n",
  "previewResults": [],
  "registryId": "012345678910",
  "repositoryName": "project-a/amazon-ecs-sample",
  "status": "COMPLETE",
  "summary": {"expiringImageTotalCount": 0}
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

GetRepositoryPolicy

Retrieves the repository policy for a specified repository.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[registryId \(p. 58\)](#)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 58\)](#)

The name of the repository with the policy to retrieve.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "policyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText (p. 58)

The JSON repository policy text associated with the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId (p. 58)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName (p. 58)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

RepositoryPolicyNotFoundException

The specified repository and registry combination does not have an associated repository policy.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (`AUTHPARAMS`) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example gets the repository policy for the ubuntu repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 28
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.GetRepositoryPolicy
X-Amz-Date: 20151215T002404Z
User-Agent: aws-cli/1.9.10 Python/2.7.10 Darwin/14.5.0 botocore/1.3.10
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "repositoryName": "ubuntu"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Tue, 15 Dec 2015 00:24:04 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 301
Connection: keep-alive
x-amzn-RequestId: 25da0b72-a2c2-11e5-8543-ebda6fb1393b

{
  "policyText": "{\n  \"Version\" : \"2012-10-17\",\n  \"Statement\" : [ {\n    \"Sid\" :  
    \"AllowPull\",\n    \"Effect\" : \"Allow\",\n    \"Principal\" : \"*\",\n    \"Action\" :  
    [ \"ecr:BatchGetImage\", \"ecr:GetDownloadUrlForLayer\" ]\n  } ]\n}",
  "registryId": "012345678910",
  "repositoryName": "ubuntu"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

InitiateLayerUpload

Notify Amazon ECR that you intend to upload an image layer.

Note

This operation is used by the Amazon ECR proxy, and it is not intended for general use by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

Request Syntax

```
{  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[registryId \(p. 62\)](#)

The AWS account ID associated with the registry to which you intend to upload layers. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 62\)](#)

The name of the repository to which you intend to upload layers.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "partSize": number,  
  "uploadId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

partSize (p. 62)

The size, in bytes, that Amazon ECR expects future layer part uploads to be.

Type: Long

Valid Range: Minimum value of 0.

uploadId (p. 62)

The upload ID for the layer upload. This parameter is passed to further [UploadLayerPart \(p. 84\)](#) and [CompleteLayerUpload \(p. 16\)](#) operations.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListImages

Lists all the image IDs for a given repository.

You can filter images based on whether or not they are tagged by setting the `tagStatus` parameter to `TAGGED` or `UNTAGGED`. For example, you can filter your results to return only `UNTAGGED` images and then pipe that result to a [BatchDeleteImage \(p. 7\)](#) operation to delete them. Or, you can filter your results to return only `TAGGED` images to list all of the tags in your repository.

Request Syntax

```
{
  "filter": {
    "tagStatus": "string"
  },
  "maxResults": number,
  "nextToken": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[filter \(p. 64\)](#)

The filter key and value with which to filter your `ListImages` results.

Type: [ListImagesFilter \(p. 102\)](#) object

Required: No

[maxResults \(p. 64\)](#)

The maximum number of image results returned by `ListImages` in paginated output. When this parameter is used, `ListImages` only returns `maxResults` results in a single page along with a `nextToken` response element. The remaining results of the initial request can be seen by sending another `ListImages` request with the returned `nextToken` value. This value can be between 1 and 100. If this parameter is not used, then `ListImages` returns up to 100 results and a `nextToken` value, if applicable.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken \(p. 64\)](#)

The `nextToken` value returned from a previous paginated `ListImages` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is `null` when there are no more results to return.

Note

This token should be treated as an opaque identifier that is only used to retrieve the next items in a list and not for other programmatic purposes.

Type: String

Required: No

[registryId \(p. 64\)](#)

The AWS account ID associated with the registry that contains the repository in which to list images. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 64\)](#)

The repository with image IDs to be listed.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "imageIds": [
    {
      "imageDigest": "string",
      "imageTag": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[imageIds \(p. 65\)](#)

The list of image IDs for the requested repository.

Type: Array of [ImageIdentifier \(p. 95\)](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

[nextToken \(p. 65\)](#)

The `nextToken` value to include in a future `ListImages` request. When the results of a `ListImages` request exceed `maxResults`, this value can be used to retrieve the next page of results. This value is `null` when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example lists all of the images in the `amazonlinux` repository.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 33
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.ListImages
X-Amz-Date: 20161216T200542Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AWUTHPARAMS

{
  "repositoryName": "amazonlinux"
}
```

Sample Response

```
HTTP/1.1 200 OK
```



```
Server: Server
Date: Fri, 16 Dec 2016 20:05:42 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 235
Connection: keep-alive
x-amzn-RequestId: 05bfc4ac-c3cb-11e6-99fb-b1be070cc24b

{
  "imageIds": [
    {
      "imageDigest":
"sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
      "imageTag": "2016.09"
    },
    {
      "imageDigest":
"sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
      "imageTag": "latest"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

PutImage

Creates or updates the image manifest and tags associated with an image.

Note

This operation is used by the Amazon ECR proxy, and it is not intended for general use by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

Request Syntax

```
{
  "imageManifest": "string",
  "imageTag": "string",
  "registryId": "string",
  "repositoryName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 105).

The request accepts the following data in JSON format.

imageManifest (p. 68)

The image manifest corresponding to the image to be uploaded.

Type: String

Required: Yes

imageTag (p. 68)

The tag to associate with the image. This parameter is required for images that use the Docker Image Manifest V2 Schema 2 or OCI formats.

Type: String

Required: No

registryId (p. 68)

The AWS account ID associated with the registry that contains the repository in which to put the image. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName (p. 68)

The name of the repository in which to put the image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
  "image": {
    "imageId": {
      "imageDigest": "string",
      "imageTag": "string"
    },
    "imageManifest": "string",
    "registryId": "string",
    "repositoryName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

image (p. 69)

Details of the image uploaded.

Type: [Image \(p. 91\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

ImageAlreadyExistsException

The specified image has already been pushed, and there were no changes to the manifest or image tag after the last push.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LayersNotFoundException

The specified layers could not be found, or the specified layer is not valid for this repository.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR Default Service Limits](#) in the Amazon Elastic Container Registry User Guide.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example puts an image to the `amazonlinux` repository with the tag `2016.09`.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 653
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.PutImage
X-Amz-Date: 20161216T201255Z
User-Agent: aws-cli/1.11.22 Python/2.7.12 Darwin/16.3.0 botocore/1.4.79
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "imageManifest": "{\n  \"schemaVersion\": 2,\n  \"mediaType\": \"application/\n  vnd.docker.distribution.manifest.v2+json\",\n  \"config\": {\n    \"mediaType\":\n    \"application/vnd.docker.container.image.v1+json\",\n    \"size\": 1486,\n    \"digest\": \"sha256:5b52b314511a611975c2c65e695d920acdf8ae8848fe0ef00b7d018d1f118b64\"\n  },\n  \"layers\": [\n    {\n      \"mediaType\": \"application/\n      vnd.docker.image.rootfs.diff.tar.gzip\",\n      \"size\": 91768077,\n      \"digest\n      \": \"sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8\"\n    }\n  ]\n}\n",
  "repositoryName": "amazonlinux",
  "imageTag": "2016.09"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 16 Dec 2016 20:12:56 GMT
```

```
Content-Type: application/x-amz-json-1.1
Content-Length: 786
Connection: keep-alive
x-amzn-RequestId: 084038f1-c3cc-11e6-8d10-9da51cf53fd3

{
  "image": {
    "imageId": {
      "imageDigest":
        "sha256:f1d4ae3f7261a72e98c6ebefe9985cf10a0ea5bd762585a43e0700ed99863807",
      "imageTag": "2016.09"
    },
    "imageManifest": "{\n  \"schemaVersion\": 2,\n  \"mediaType\": \"application/
vnd.docker.distribution.manifest.v2+json\",\n  \"config\": {\n    \"mediaType\":
\"application/vnd.docker.container.image.v1+json\",\n    \"size\": 1486,\n
  \"digest\": \"sha256:5b52b314511a611975c2c65e695d920acdf8ae8848fe0ef00b7d018d1f118b64\"\n
  },\n  \"layers\": [\n    {\n      \"mediaType\": \"application/
vnd.docker.image.rootfs.diff.tar.gzip\",\n      \"size\": 91768077,\n      \"digest
\": \"sha256:8e3fa21c4cc40232e835a6761332d225c7af3235c5755f44ada2ed9d0e4ab7e8\"\n    }
  ]\n}\n",
    "registryId": "012345678910",
    "repositoryName": "amazonlinux"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

PutLifecyclePolicy

Creates or updates a lifecycle policy. For information about lifecycle policy syntax, see [Lifecycle Policy Template](#).

Request Syntax

```
{  
  "lifecyclePolicyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

[lifecyclePolicyText \(p. 72\)](#)

The JSON repository policy text to apply to the repository.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 10240.

Required: Yes

[registryId \(p. 72\)](#)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

[repositoryName \(p. 72\)](#)

The name of the repository to receive the policy.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "lifecyclePolicyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicyText (p. 72)

The JSON repository policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 10240.

registryId (p. 72)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{1,2}

repositoryName (p. 72)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 107).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (`AUTHPARAMS`) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a lifecycle policy to expire images older than 14 days for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.PutLifecyclePolicy
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T194217Z
Authorization: AUTHPARAMS
Content-Length: 535

{
  "repositoryName": "project-a/amazon-ecs-sample",
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\n\": 1,\n      \"description\": \"Expire images older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n        \"countType\": \"sinceImagePushed\",\n        \"countUnit\": \"days\",\n        \"countNumber\": 14\n      },\n      \"action\": {\n        \"type\": \"expire\"\n      }\n    }\n  ]\n}"
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Fri, 01 Sep 2017 19:42:18 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 340
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\n\": 1,\n      \"description\": \"Expire\nimages older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n        \"countType\":\n        \"sinceImagePushed\",\n        \"countUnit\": \"days\",\n        \"countNumber\": 14\n      },\n      \"action\": {\n        \"type\":\n        \"expire\"\n      }\n    }\n  ]\n}",
  "registryId": "012345678910",
  "repositoryName": "project-a/amazon-ecs-sample"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

SetRepositoryPolicy

Applies a repository policy on a specified repository to control access permissions.

Request Syntax

```
{  
  "force": boolean,  
  "policyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

force (p. 76)

If the policy you are attempting to set on a repository policy would prevent you from setting another policy in the future, you must force the [SetRepositoryPolicy \(p. 76\)](#) operation. This is intended to prevent accidental repository lock outs.

Type: Boolean

Required: No

policyText (p. 76)

The JSON repository policy text to apply to the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Required: Yes

registryId (p. 76)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName (p. 76)

The name of the repository to receive the policy.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{  
  "policyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policyText (p. 77)

The JSON repository policy text applied to the repository.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

registryId (p. 77)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName (p. 77)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 107).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

The following example sets a repository policy on the ubuntu repository that allows all AWS accounts to pull from it.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-east-1.amazonaws.com
Accept-Encoding: identity
Content-Length: 223
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.SetRepositoryPolicy
X-Amz-Date: 20151214T235302Z
User-Agent: aws-cli/1.9.10 Python/2.7.10 Darwin/14.5.0 botocore/1.3.10
Content-Type: application/x-amz-json-1.1
Authorization: AWUTHPARAMS

{
  "policyText": "{\n  \"Version\": \"2012-10-17\", \"Statement\": [\n    {\n      \"Sid\": \"AllowPull\", \"Effect\": \"Allow\", \"Action\": [\"ecr:BatchGetImage\", \"ecr:GetDownloadUrlForLayer\"], \"Principal\": \"*\"}\n  ]\n}",
  "repositoryName": "ubuntu"
}
```

Sample Response

```
HTTP/1.1 200 OK
Server: Server
Date: Mon, 14 Dec 2015 23:53:02 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 301
Connection: keep-alive
x-amzn-RequestId: cfc3ead9-a2bd-11e5-91c7-7126cb670c2b

{
  "policyText": "{\n  \"Version\" : \"2012-10-17\", \n  \"Statement\" : [ {\n    \"Sid\" : \"AllowPull\", \n    \"Effect\" : \"Allow\", \n    \"Principal\" : \"*\", \n    \"Action\" : [ \"ecr:BatchGetImage\", \"ecr:GetDownloadUrlForLayer\" ]\n  } ]\n}",
  "registryId": "012345678910",
  "repositoryName": "ubuntu"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

StartLifecyclePolicyPreview

Starts a preview of the specified lifecycle policy. This allows you to see the results before creating the lifecycle policy.

Request Syntax

```
{  
  "lifecyclePolicyText": "string",  
  "registryId": "string",  
  "repositoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 105\)](#).

The request accepts the following data in JSON format.

lifecyclePolicyText (p. 80)

The policy to be evaluated against. If you do not specify a policy, the current policy for the repository is used.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 10240.

Required: No

registryId (p. 80)

The AWS account ID associated with the registry that contains the repository. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName (p. 80)

The name of the repository to be evaluated.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

Response Syntax

```
{
```

```
"lifecyclePolicyText": "string",  
"registryId": "string",  
"repositoryName": "string",  
"status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicyText (p. 80)

The JSON repository policy text.

Type: String

Length Constraints: Minimum length of 100. Maximum length of 10240.

registryId (p. 80)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName (p. 80)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

status (p. 80)

The status of the lifecycle policy preview request.

Type: String

Valid Values: IN_PROGRESS | COMPLETE | EXPIRED | FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LifecyclePolicyNotFoundException

The lifecycle policy could not be found, and no policy is set to the repository.

HTTP Status Code: 400

LifecyclePolicyPreviewInProgressException

The previous lifecycle policy preview request has not completed. Please try again later.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Example

This example creates a lifecycle policy preview to expire images older than 14 days for a repository called `project-a/amazon-ecs-sample` in the default registry for an account.

Sample Request

```
POST / HTTP/1.1
Host: ecr.us-west-2.amazonaws.com
Accept-Encoding: identity
X-Amz-Target: AmazonEC2ContainerRegistry_V20150921.StartLifecyclePolicyPreview
Content-Type: application/x-amz-json-1.1
User-Agent: aws-cli/1.11.144 Python/3.6.1 Darwin/16.6.0 botocore/1.7.2
X-Amz-Date: 20170901T221604Z
Authorization: AUTHPARAMS
Content-Length: 535

{
  "repositoryName": "project-a/amazon-ecs-sample",
  "lifecyclePolicyText": "{\n  \"rules\": [\n    {\n      \"rulePriority\n\": 1,\n      \"description\": \"Expire images older than 14 days\",\n      \"selection\": {\n        \"tagStatus\": \"untagged\",\n        \"countType\": \"sinceImagePushed\",\n        \"countUnit\": \"days\",\n        \"countNumber\": 14\n      },\n      \"action\": {\n        \"type\": \"expire\"\n      }\n    }\n  ]\n}"
```

Sample Response

```
HTTP/1.1 200 OK
```



```
Server: Server
Date: Fri, 01 Sep 2017 22:16:05 GMT
Content-Type: application/x-amz-json-1.1
Content-Length: 583
Connection: keep-alive
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f

{
  "lifecyclePolicyText": "{\n  \\"rules\":[\n    {\n      \\"rulePriority\n\": 1,\n      \\"description\":"\"Expire images older than 14 days\", \n      \\"selection\": {\n        \\"tagStatus\": \\"untagged\", \n        \\"countType\": \\"sinceImagePushed\", \n        \\"countUnit\": \\"days\", \n        \\"countNumber\": 14\n      }, \n      \\"action\": {\n        \\"type\": \\"expire\", \n        \\"registryId\": \"012345678910\", \n        \\"repositoryName\": \"project-a/amazon-ecs-sample\", \n        \\"status\": \"IN_PROGRESS\"\n      }\n    }\n  ]\n}\n",
  "registryId": "012345678910",
  "repositoryName": "project-a/amazon-ecs-sample",
  "status": "IN_PROGRESS"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

UploadLayerPart

Uploads an image layer part to Amazon ECR.

Note

This operation is used by the Amazon ECR proxy, and it is not intended for general use by customers for pulling and pushing images. In most cases, you should use the `docker` CLI to pull, tag, and push images.

Request Syntax

```
{
  "layerPartBlob": blob,
  "partFirstByte": number,
  "partLastByte": number,
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 105).

The request accepts the following data in JSON format.

[layerPartBlob](#) (p. 84)

The base64-encoded layer part payload.

Type: Base64-encoded binary data object

Required: Yes

[partFirstByte](#) (p. 84)

The integer value of the first byte of the layer part.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

[partLastByte](#) (p. 84)

The integer value of the last byte of the layer part.

Type: Long

Valid Range: Minimum value of 0.

Required: Yes

[registryId](#) (p. 84)

The AWS account ID associated with the registry to which you are uploading layer parts. If you do not specify a registry, the default registry is assumed.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName (p. 84)

The name of the repository to which you are uploading layer parts.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)/*)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: Yes

uploadId (p. 84)

The upload ID from a previous [InitiateLayerUpload \(p. 62\)](#) operation to associate with the layer part upload.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Required: Yes

Response Syntax

```
{
  "lastByteReceived": number,
  "registryId": "string",
  "repositoryName": "string",
  "uploadId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lastByteReceived (p. 85)

The integer value of the last byte received in the request.

Type: Long

Valid Range: Minimum value of 0.

registryId (p. 85)

The registry ID associated with the request.

Type: String

Pattern: [0-9]{12}

repositoryName (p. 85)

The repository name associated with the request.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

uploadId (p. 85)

The upload ID associated with the request.

Type: String

Pattern: [0-9a-fA-F]{8}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{4}-[0-9a-fA-F]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 107\)](#).

InvalidLayerPartException

The layer part size is not valid, or the first byte specified is not consecutive to the last byte of a previous layer part upload.

HTTP Status Code: 400

InvalidParameterException

The specified parameter is invalid. Review the available parameters for the API request.

HTTP Status Code: 400

LimitExceededException

The operation did not succeed because it would have exceeded a service limit for your account. For more information, see [Amazon ECR Default Service Limits](#) in the Amazon Elastic Container Registry User Guide.

HTTP Status Code: 400

RepositoryNotFoundException

The specified repository could not be found. Check the spelling of the specified repository and ensure that you are performing operations on the correct registry.

HTTP Status Code: 400

ServerException

These errors are usually caused by a server-side issue.

HTTP Status Code: 500

UploadNotFoundException

The upload could not be found, or the specified upload id is not valid for this repository.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

Data Types

The Amazon EC2 Container Registry API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AuthorizationData](#) (p. 89)
- [DescribeImagesFilter](#) (p. 90)
- [Image](#) (p. 91)
- [ImageDetail](#) (p. 92)
- [ImageFailure](#) (p. 94)
- [ImageIdentifier](#) (p. 95)
- [Layer](#) (p. 96)
- [LayerFailure](#) (p. 97)
- [LifecyclePolicyPreviewFilter](#) (p. 98)
- [LifecyclePolicyPreviewResult](#) (p. 99)
- [LifecyclePolicyPreviewSummary](#) (p. 100)
- [LifecyclePolicyRuleAction](#) (p. 101)
- [ListImagesFilter](#) (p. 102)
- [Repository](#) (p. 103)

AuthorizationData

An object representing authorization data for an Amazon ECR registry.

Contents

authorizationToken

A base64-encoded string that contains authorization data for the specified Amazon ECR registry. When the string is decoded, it is presented in the format `user:password` for private registry authentication using `docker login`.

Type: String

Pattern: `^\S+$`

Required: No

expiresAt

The Unix time in seconds and milliseconds when the authorization token expires. Authorization tokens are valid for 12 hours.

Type: Timestamp

Required: No

proxyEndpoint

The registry URL to use for this authorization token in a `docker login` command. The Amazon ECR registry URL format is `https://aws_account_id.dkr.ecr.region.amazonaws.com`. For example, `https://012345678910.dkr.ecr.us-east-1.amazonaws.com`.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

DescribeImagesFilter

An object representing a filter on a [DescribeImages \(p. 34\)](#) operation.

Contents

tagStatus

The tag status with which to filter your [DescribeImages \(p. 34\)](#) results. You can filter results based on whether they are `TAGGED` or `UNTAGGED`.

Type: String

Valid Values: `TAGGED` | `UNTAGGED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Image

An object representing an Amazon ECR image.

Contents

imageId

An object containing the image tag and image digest associated with an image.

Type: [ImageIdentifier](#) (p. 95) object

Required: No

imageManifest

The image manifest associated with the image.

Type: String

Required: No

registryId

The AWS account ID associated with the registry containing the image.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository associated with the image.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ImageDetail

An object that describes an image returned by a [DescribeImages \(p. 34\)](#) operation.

Contents

imageDigest

The sha256 digest of the image manifest.

Type: String

Required: No

imagePushedAt

The date and time, expressed in standard JavaScript date format, at which the current image was pushed to the repository.

Type: Timestamp

Required: No

imageSizeInBytes

The size, in bytes, of the image in the repository.

Note

Beginning with Docker version 1.9, the Docker client compresses image layers before pushing them to a V2 Docker registry. The output of the `docker images` command shows the uncompressed image size, so it may return a larger image size than the image sizes returned by [DescribeImages \(p. 34\)](#).

Type: Long

Required: No

imageTags

The list of tags associated with this image.

Type: Array of strings

Required: No

registryId

The AWS account ID associated with the registry to which this image belongs.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryName

The name of the repository to which this image belongs.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ImageFailure

An object representing an Amazon ECR image failure.

Contents

failureCode

The code associated with the failure.

Type: String

Valid Values: `InvalidImageDigest` | `InvalidImageTag` | `ImageTagDoesNotMatchDigest` | `ImageNotFound` | `MissingDigestAndTag`

Required: No

failureReason

The reason for the failure.

Type: String

Required: No

imageId

The image ID associated with the failure.

Type: [ImageIdentifier \(p. 95\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ImageIdentifier

An object with identifying information for an Amazon ECR image.

Contents

imageDigest

The sha256 digest of the image manifest.

Type: String

Required: No

imageTag

The tag used for the image.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Layer

An object representing an Amazon ECR image layer.

Contents

layerAvailability

The availability status of the image layer.

Type: String

Valid Values: `AVAILABLE` | `UNAVAILABLE`

Required: No

layerDigest

The sha256 digest of the image layer.

Type: String

Pattern: `[a-zA-Z0-9-_.]+:[a-fA-F0-9]+`

Required: No

layerSize

The size, in bytes, of the image layer.

Type: Long

Required: No

mediaType

The media type of the layer, such as `application/vnd.docker.image.rootfs.diff.tar.gzip` or `application/vnd.oci.image.layer.v1.tar+gzip`.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

LayerFailure

An object representing an Amazon ECR image layer failure.

Contents

failureCode

The failure code associated with the failure.

Type: String

Valid Values: `InvalidLayerDigest` | `MissingLayerDigest`

Required: No

failureReason

The reason for the failure.

Type: String

Required: No

layerDigest

The layer digest associated with the failure.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

LifecyclePolicyPreviewFilter

The filter for the lifecycle policy preview.

Contents

tagStatus

The tag status of the image.

Type: String

Valid Values: `TAGGED` | `UNTAGGED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

LifecyclePolicyPreviewResult

The result of the lifecycle policy preview.

Contents

action

The type of action to be taken.

Type: [LifecyclePolicyRuleAction](#) (p. 101) object

Required: No

appliedRulePriority

The priority of the applied rule.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

imageDigest

The sha256 digest of the image manifest.

Type: String

Required: No

imagePushedAt

The date and time, expressed in standard JavaScript date format, at which the current image was pushed to the repository.

Type: Timestamp

Required: No

imageTags

The list of tags associated with this image.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

LifecyclePolicyPreviewSummary

The summary of the lifecycle policy preview request.

Contents

expiringImageTotalCount

The number of expiring images.

Type: Integer

Valid Range: Minimum value of 0.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

LifecyclePolicyRuleAction

The type of action to be taken.

Contents

type

The type of action to be taken.

Type: String

Valid Values: `EXPIRE`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ListImagesFilter

An object representing a filter on a [ListImages \(p. 64\)](#) operation.

Contents

tagStatus

The tag status with which to filter your [ListImages \(p. 64\)](#) results. You can filter results based on whether they are `TAGGED` or `UNTAGGED`.

Type: String

Valid Values: `TAGGED` | `UNTAGGED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Repository

An object representing a repository.

Contents

createdAt

The date and time, in JavaScript date format, when the repository was created.

Type: Timestamp

Required: No

registryId

The AWS account ID associated with the registry that contains the repository.

Type: String

Pattern: [0-9]{12}

Required: No

repositoryArn

The Amazon Resource Name (ARN) that identifies the repository. The ARN contains the `arn:aws:ecr` namespace, followed by the region of the repository, AWS account ID of the repository owner, repository namespace, and repository name. For example, `arn:aws:ecr:region:012345678910:repository/test`.

Type: String

Required: No

repositoryName

The name of the repository.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 256.

Pattern: (?:[a-z0-9]+(?:[._-][a-z0-9]+)*/)*[a-z0-9]+(?:[._-][a-z0-9]+)*

Required: No

repositoryUri

The URI for the repository. You can use this URI for Docker `push` or `pull` operations.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400