

---

**AWS Support**  
**API Reference**  
**API Version 2013-04-15**



## **AWS Support: API Reference**

Copyright © 2020 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

# Table of Contents

Welcome .....	1
Actions .....	2
AddAttachmentsToSet .....	3
Request Syntax .....	3
Request Parameters .....	3
Response Syntax .....	3
Response Elements .....	4
Errors .....	4
See Also .....	4
AddCommunicationToCase .....	6
Request Syntax .....	6
Request Parameters .....	6
Response Syntax .....	7
Response Elements .....	7
Errors .....	7
See Also .....	7
CreateCase .....	9
Request Syntax .....	9
Request Parameters .....	9
Response Syntax .....	11
Response Elements .....	11
Errors .....	11
See Also .....	11
DescribeAttachment .....	13
Request Syntax .....	13
Request Parameters .....	13
Response Syntax .....	13
Response Elements .....	13
Errors .....	14
See Also .....	14
DescribeCases .....	15
Request Syntax .....	15
Request Parameters .....	15
Response Syntax .....	16
Response Elements .....	17
Errors .....	17
See Also .....	17
DescribeCommunications .....	19
Request Syntax .....	19
Request Parameters .....	19
Response Syntax .....	20
Response Elements .....	20
Errors .....	20
See Also .....	21
DescribeServices .....	22
Request Syntax .....	22
Request Parameters .....	22
Response Syntax .....	22
Response Elements .....	23
Errors .....	23
See Also .....	23
DescribeSeverityLevels .....	24
Request Syntax .....	24
Request Parameters .....	24

Response Syntax .....	24
Response Elements .....	24
Errors .....	25
See Also .....	25
DescribeTrustedAdvisorCheckRefreshStatuses .....	26
Request Syntax .....	26
Request Parameters .....	26
Response Syntax .....	26
Response Elements .....	26
Errors .....	27
See Also .....	27
DescribeTrustedAdvisorCheckResult .....	28
Request Syntax .....	28
Request Parameters .....	28
Response Syntax .....	29
Response Elements .....	29
Errors .....	29
See Also .....	29
DescribeTrustedAdvisorChecks .....	31
Request Syntax .....	31
Request Parameters .....	31
Response Syntax .....	31
Response Elements .....	31
Errors .....	32
See Also .....	32
DescribeTrustedAdvisorCheckSummaries .....	33
Request Syntax .....	33
Request Parameters .....	33
Response Syntax .....	33
Response Elements .....	34
Errors .....	34
See Also .....	34
RefreshTrustedAdvisorCheck .....	35
Request Syntax .....	35
Request Parameters .....	35
Response Syntax .....	35
Response Elements .....	35
Errors .....	36
See Also .....	36
ResolveCase .....	37
Request Syntax .....	37
Request Parameters .....	37
Response Syntax .....	37
Response Elements .....	37
Errors .....	38
See Also .....	38
Data Types .....	39
Attachment .....	40
Contents .....	40
See Also .....	40
AttachmentDetails .....	41
Contents .....	41
See Also .....	41
CaseDetails .....	42
Contents .....	42
See Also .....	44
Category .....	45

Contents .....	45
See Also .....	45
Communication .....	46
Contents .....	46
See Also .....	46
RecentCaseCommunications .....	47
Contents .....	47
See Also .....	47
Service .....	48
Contents .....	48
See Also .....	48
SeverityLevel .....	49
Contents .....	49
See Also .....	49
TrustedAdvisorCategorySpecificSummary .....	50
Contents .....	50
See Also .....	50
TrustedAdvisorCheckDescription .....	51
Contents .....	51
See Also .....	51
TrustedAdvisorCheckRefreshStatus .....	52
Contents .....	52
See Also .....	52
TrustedAdvisorCheckResult .....	53
Contents .....	53
See Also .....	53
TrustedAdvisorCheckSummary .....	54
Contents .....	54
See Also .....	54
TrustedAdvisorCostOptimizingSummary .....	55
Contents .....	55
See Also .....	55
TrustedAdvisorResourceDetail .....	56
Contents .....	56
See Also .....	56
TrustedAdvisorResourcesSummary .....	57
Contents .....	57
See Also .....	57
Common Parameters .....	58
Common Errors .....	60

# Welcome

The AWS Support API reference is intended for programmers who need detailed information about the AWS Support operations and data types. This service enables you to manage your AWS Support cases programmatically. It uses HTTP methods that return results in JSON format.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

The AWS Support service also exposes a set of [AWS Trusted Advisor](#) features. You can retrieve a list of checks and their descriptions, get check results, specify checks to refresh, and get the refresh status of checks.

The following list describes the AWS Support case management operations:

- **Service names, issue categories, and available severity levels.** The [DescribeServices](#) (p. 22) and [DescribeSeverityLevels](#) (p. 24) operations return AWS service names, service codes, service categories, and problem severity levels. You use these values when you call the [CreateCase](#) (p. 9) operation.
- **Case creation, case details, and case resolution.** The [CreateCase](#) (p. 9), [DescribeCases](#) (p. 15), [DescribeAttachment](#) (p. 13), and [ResolveCase](#) (p. 37) operations create AWS Support cases, retrieve information about cases, and resolve cases.
- **Case communication.** The [DescribeCommunications](#) (p. 19), [AddCommunicationToCase](#) (p. 6), and [AddAttachmentsToSet](#) (p. 3) operations retrieve and add communications and attachments to AWS Support cases.

The following list describes the operations available from the AWS Support service for Trusted Advisor:

- [DescribeTrustedAdvisorChecks](#) (p. 31) returns the list of checks that run against your AWS resources.
- Using the `checkId` for a specific check returned by [DescribeTrustedAdvisorChecks](#) (p. 31), you can call [DescribeTrustedAdvisorCheckResult](#) (p. 28) to obtain the results for the check that you specified.
- [DescribeTrustedAdvisorCheckSummaries](#) (p. 33) returns summarized results for one or more Trusted Advisor checks.
- [RefreshTrustedAdvisorCheck](#) (p. 35) requests that Trusted Advisor rerun a specified check.
- [DescribeTrustedAdvisorCheckRefreshStatuses](#) (p. 26) reports the refresh status of one or more checks.

For authentication of requests, AWS Support uses [Signature Version 4 Signing Process](#).

See [About the AWS Support API](#) in the *AWS Support User Guide* for information about how to use this service to create and manage your support cases, and how to call Trusted Advisor for results of checks on your resources.

This document was last published on November 23, 2020.

# Actions

The following actions are supported:

- [AddAttachmentsToSet](#) (p. 3)
- [AddCommunicationToCase](#) (p. 6)
- [CreateCase](#) (p. 9)
- [DescribeAttachment](#) (p. 13)
- [DescribeCases](#) (p. 15)
- [DescribeCommunications](#) (p. 19)
- [DescribeServices](#) (p. 22)
- [DescribeSeverityLevels](#) (p. 24)
- [DescribeTrustedAdvisorCheckRefreshStatuses](#) (p. 26)
- [DescribeTrustedAdvisorCheckResult](#) (p. 28)
- [DescribeTrustedAdvisorChecks](#) (p. 31)
- [DescribeTrustedAdvisorCheckSummaries](#) (p. 33)
- [RefreshTrustedAdvisorCheck](#) (p. 35)
- [ResolveCase](#) (p. 37)

# AddAttachmentsToSet

Adds one or more attachments to an attachment set.

An attachment set is a temporary container for attachments that you add to a case or case communication. The set is available for 1 hour after it's created. The `expiryTime` returned in the response is when the set expires.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{
  "attachments": [
    {
      "data": blob,
      "fileName": "string"
    }
  ],
  "attachmentSetId": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### **attachments (p. 3)**

One or more attachments to add to the set. You can add up to three attachments per set. The size limit is 5 MB per attachment.

In the `Attachment` object, use the `data` parameter to specify the contents of the attachment file. In the previous request syntax, the value for `data` appear as `blob`, which is represented as a base64-encoded string. The value for `fileName` is the name of the attachment, such as `troubleshoot-screenshot.png`.

Type: Array of [Attachment \(p. 40\)](#) objects

### **attachmentSetId (p. 3)**

The ID of the attachment set. If an `attachmentSetId` is not specified, a new attachment set is created, and the ID of the set is returned in the response. If an `attachmentSetId` is specified, the attachments are added to the specified set, if it exists.

Type: String

## Response Syntax

```
{
```



```
"attachmentSetId": "string",  
"expiryTime": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **attachmentSetId** (p. 3)

The ID of the attachment set. If an `attachmentSetId` was not specified, a new attachment set is created, and the ID of the set is returned in the response. If an `attachmentSetId` was specified, the attachments are added to the specified set, if it exists.

Type: String

### **expiryTime** (p. 3)

The time and date when the attachment set expires.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **AttachmentLimitExceeded**

The limit for the number of attachment sets created in a short period of time has been exceeded.

HTTP Status Code: 400

### **AttachmentSetExpired**

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

### **AttachmentSetIdNotFound**

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

### **AttachmentSetSizeLimitExceeded**

A limit for the size of an attachment set has been exceeded. The limits are three attachments and 5 MB per attachment.

HTTP Status Code: 400

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AddCommunicationToCase

Adds additional customer communication to an AWS Support case. Use the `caseId` parameter to identify the case to which to add communication. You can list a set of email addresses to copy on the communication by using the `ccEmailAddresses` parameter. The `communicationBody` value contains the text of the communication.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{
  "attachmentSetId": "string",
  "caseId": "string",
  "ccEmailAddresses": [ "string" ],
  "communicationBody": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

### [attachmentSetId](#) (p. 6)

The ID of a set of one or more attachments for the communication to add to the case. Create the set by calling [AddAttachmentsToSet](#) (p. 3)

Type: String

### [caseId](#) (p. 6)

The AWS Support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

### [ccEmailAddresses](#) (p. 6)

The email addresses in the CC line of an email to be added to the support case.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

### [communicationBody](#) (p. 6)

The body of an email communication to add to the support case.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

## Response Syntax

```
{  
  "result": boolean  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### result (p. 7)

True if [AddCommunicationToCase \(p. 6\)](#) succeeds. Otherwise, returns an error.

Type: Boolean

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### AttachmentSetExpired

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

### AttachmentSetIdNotFound

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

### CaseIdNotFound

The requested `caseId` could not be located.

HTTP Status Code: 400

### InternalServerError

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateCase

Creates a case in the AWS Support Center. This operation is similar to how you create a case in the AWS Support Center [Create Case](#) page.

The AWS Support API doesn't support requesting service limit increases. You can submit a service limit increase in the following ways:

- Submit a request from the AWS Support Center [Create Case](#) page.
- Use the Service Quotas [RequestServiceQuotaIncrease](#) operation.

A successful `CreateCase` request returns an AWS Support case number. You can use the [DescribeCases](#) (p. 15) operation and specify the case number to get existing AWS Support cases. After you create a case, use the [AddCommunicationToCase](#) (p. 6) operation to add additional communication or attachments to an existing case.

The `caseId` is separate from the `displayId` that appears in the [AWS Support Center](#). Use the [DescribeCases](#) (p. 15) operation to get the `displayId`.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{
  "attachmentSetId": "string",
  "categoryCode": "string",
  "ccEmailAddresses": [ "string" ],
  "communicationBody": "string",
  "issueType": "string",
  "language": "string",
  "serviceCode": "string",
  "severityCode": "string",
  "subject": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

### **attachmentSetId** (p. 9)

The ID of a set of one or more attachments for the case. Create the set by using the [AddAttachmentsToSet](#) (p. 3) operation.

Type: String

### **categoryCode (p. 9)**

The category of problem for the AWS Support case. You also use the [DescribeServices \(p. 22\)](#) operation to get the category code for a service. Each AWS service defines its own set of category codes.

Type: String

### **ccEmailAddresses (p. 9)**

A list of email addresses that AWS Support copies on case correspondence. AWS Support identifies the account that creates the case when you specify your AWS credentials in an HTTP POST method or use the [AWS SDKs](#).

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

### **communicationBody (p. 9)**

The communication body text that describes the issue. This text appears in the **Description** field on the AWS Support Center [Create Case](#) page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

### **issueType (p. 9)**

The type of issue for the case. You can specify `customer-service` or `technical`. If you don't specify a value, the default is `technical`.

Type: String

### **language (p. 9)**

The language in which AWS Support handles the case. You must specify the ISO 639-1 code for the `language` parameter if you want support in that language. Currently, English ("en") and Japanese ("ja") are supported.

Type: String

### **serviceCode (p. 9)**

The code for the AWS service. You can use the [DescribeServices \(p. 22\)](#) operation to get the possible `serviceCode` values.

Type: String

### **severityCode (p. 9)**

A value that indicates the urgency of the case. This value determines the response time according to your service level agreement with AWS Support. You can use the [DescribeSeverityLevels \(p. 24\)](#) operation to get the possible values for `severityCode`.

For more information, see [SeverityLevel \(p. 49\)](#) and [Choosing a Severity](#) in the *AWS Support User Guide*.

#### **Note**

The availability of severity levels depends on the support plan for the AWS account.

Type: String

### **subject (p. 9)**

The title of the AWS Support case. The title appears in the **Subject** field on the AWS Support Center [Create Case](#) page.

Type: String

## Response Syntax

```
{  
  "caseId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **caseId** (p. 11)

The AWS Support case ID requested or returned in the call. The case ID is an alphanumeric string in the following format: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **AttachmentSetExpired**

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

### **AttachmentSetIdNotFound**

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

### **CaseCreationLimitExceeded**

The case creation limit for the account has been exceeded.

HTTP Status Code: 400

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)



- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeAttachment

Returns the attachment that has the specified ID. Attachments can include screenshots, error logs, or other files that describe your issue. Attachment IDs are generated by the case management system when you add an attachment to a case or case communication. Attachment IDs are returned in the [AttachmentDetails \(p. 41\)](#) objects that are returned by the [DescribeCommunications \(p. 19\)](#) operation.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{  
  "attachmentId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### [attachmentId \(p. 13\)](#)

The ID of the attachment to return. Attachment IDs are returned by the [DescribeCommunications \(p. 19\)](#) operation.

Type: String

## Response Syntax

```
{  
  "attachment": {  
    "data": blob,  
    "fileName": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [attachment \(p. 13\)](#)

This object includes the attachment content and file name.

In the previous response syntax, the value for the `data` parameter appears as `blob`, which is represented as a base64-encoded string. The value for `fileName` is the name of the attachment, such as `troubleshoot-screenshot.png`.

Type: [Attachment \(p. 40\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **AttachmentIdNotFound**

An attachment with the specified ID could not be found.

HTTP Status Code: 400

### **DescribeAttachmentLimitExceeded**

The limit for the number of [DescribeAttachment \(p. 13\)](#) requests in a short period of time has been exceeded.

HTTP Status Code: 400

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeCases

Returns a list of cases that you specify by passing one or more case IDs. You can use the `afterTime` and `beforeTime` parameters to filter the cases by date. You can set values for the `includeResolvedCases` and `includeCommunications` parameters to specify how much information to return.

The response returns the following in JSON format:

- One or more [CaseDetails](#) data types.
- One or more `nextToken` values, which specify where to paginate the returned records represented by the `CaseDetails` objects.

Case data is available for 12 months after creation. If a case was created more than 12 months ago, a request might return an error.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{
  "afterTime": "string",
  "beforeTime": "string",
  "caseIdList": [ "string" ],
  "displayId": "string",
  "includeCommunications": boolean,
  "includeResolvedCases": boolean,
  "language": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

### [afterTime](#) (p. 15)

The start date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

### [beforeTime](#) (p. 15)

The end date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

### **caseIdList (p. 15)**

A list of ID numbers of the support cases you want returned. The maximum number of cases is 100.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

### **displayId (p. 15)**

The ID displayed for a case in the AWS Support Center user interface.

Type: String

### **includeCommunications (p. 15)**

Specifies whether to include communications in the `DescribeCases` response. By default, communications are included.

Type: Boolean

### **includeResolvedCases (p. 15)**

Specifies whether to include resolved support cases in the `DescribeCases` response. By default, resolved cases aren't included.

Type: Boolean

### **language (p. 15)**

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

### **maxResults (p. 15)**

The maximum number of results to return before paginating.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

### **nextToken (p. 15)**

A resumption point for pagination.

Type: String

## Response Syntax

```
{
  "cases": [
    {
      "caseId": "string",
      "categoryCode": "string",
      "ccEmailAddresses": [ "string" ],
      "displayId": "string",
      "language": "string",
      "recentCommunications": {
        "communications": [
          {
            "attachmentSet": [
              {

```

```
        "attachmentId": "string",
        "fileName": "string"
      }
    ],
    "body": "string",
    "caseId": "string",
    "submittedBy": "string",
    "timeCreated": "string"
  }
],
"nextToken": "string"
},
"serviceCode": "string",
"severityCode": "string",
"status": "string",
"subject": "string",
"submittedBy": "string",
"timeCreated": "string"
}
],
"nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **cases (p. 16)**

The details for the cases that match the request.

Type: Array of [CaseDetails \(p. 42\)](#) objects

### **nextToken (p. 16)**

A resumption point for pagination.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **CaseIdNotFound**

The requested `caseId` could not be located.

HTTP Status Code: 400

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeCommunications

Returns communications and attachments for one or more support cases. Use the `afterTime` and `beforeTime` parameters to filter by date. You can use the `caseId` parameter to restrict the results to a specific case.

Case data is available for 12 months after creation. If a case was created more than 12 months ago, a request for data might cause an error.

You can use the `maxResults` and `nextToken` parameters to control the pagination of the results. Set `maxResults` to the number of cases that you want to display on each page, and use `nextToken` to specify the resumption of pagination.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{
  "afterTime": "string",
  "beforeTime": "string",
  "caseId": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### `afterTime` (p. 19)

The start date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

### `beforeTime` (p. 19)

The end date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

### `caseId` (p. 19)

The AWS Support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String



### [maxResults \(p. 19\)](#)

The maximum number of results to return before paginating.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

### [nextToken \(p. 19\)](#)

A resumption point for pagination.

Type: String

## Response Syntax

```
{
  "communications": [
    {
      "attachmentSet": [
        {
          "attachmentId": "string",
          "fileName": "string"
        }
      ],
      "body": "string",
      "caseId": "string",
      "submittedBy": "string",
      "timeCreated": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [communications \(p. 20\)](#)

The communications for the case.

Type: Array of [Communication \(p. 46\)](#) objects

### [nextToken \(p. 20\)](#)

A resumption point for pagination.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **CaseldNotFound**

The requested caseId could not be located.

HTTP Status Code: 400

**InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DescribeServices

Returns the current list of AWS services and a list of service categories for each service. You then use service names and categories in your [CreateCase \(p. 9\)](#) requests. Each AWS service has its own set of categories.

The service codes and category codes correspond to the values that appear in the **Service** and **Category** lists on the AWS Support Center [Create Case](#) page. The values in those fields don't necessarily match the service codes and categories returned by the `DescribeServices` operation. Always use the service codes and categories that the `DescribeServices` operation returns, so that you have the most recent set of service and category codes.

### Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{
  "language": "string",
  "serviceCodeList": [ "string" ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### [language \(p. 22\)](#)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

### [serviceCodeList \(p. 22\)](#)

A JSON-formatted list of service codes available for AWS services.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

## Response Syntax

```
{
  "services": [
    {
      "categories": [
```

```
    {
      "code": "string",
      "name": "string"
    }
  ],
  "code": "string",
  "name": "string"
}
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [services \(p. 22\)](#)

A JSON-formatted list of AWS services.

Type: Array of [Service \(p. 48\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeSeverityLevels

Returns the list of severity levels that you can assign to an AWS Support case. The severity level for a case is also a field in the [CaseDetails \(p. 42\)](#) data type that you include for a [CreateCase \(p. 9\)](#) request.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{  
  "language": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### [language \(p. 24\)](#)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

## Response Syntax

```
{  
  "severityLevels": [  
    {  
      "code": "string",  
      "name": "string"  
    }  
  ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [severityLevels \(p. 24\)](#)

The available severity levels for the support case. Available severity levels are defined by your service level agreement with AWS.

Type: Array of [SeverityLevel \(p. 49\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeTrustedAdvisorCheckRefreshStatuses

Returns the refresh status of the AWS Trusted Advisor checks that have the specified check IDs. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks \(p. 31\)](#) operation.

Some checks are refreshed automatically, and you can't return their refresh statuses by using the `DescribeTrustedAdvisorCheckRefreshStatuses` operation. If you call this operation for these checks, you might see an `InvalidParameterValue` error.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{  
  "checkIds": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### [checkIds \(p. 26\)](#)

The IDs of the Trusted Advisor checks to get the status of.

#### Note

If you specify the check ID of a check that is automatically refreshed, you might see an `InvalidParameterValue` error.

Type: Array of strings

## Response Syntax

```
{  
  "statuses": [  
    {  
      "checkId": "string",  
      "millisUntilNextRefreshable": number,  
      "status": "string"  
    }  
  ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

#### [statuses \(p. 26\)](#)

The refresh status of the specified Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckRefreshStatus \(p. 52\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

#### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DescribeTrustedAdvisorCheckResult

Returns the results of the AWS Trusted Advisor check that has the specified check ID. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks \(p. 31\)](#) operation.

The response contains a [TrustedAdvisorCheckResult \(p. 53\)](#) object, which contains these three objects:

- [TrustedAdvisorCategorySpecificSummary \(p. 50\)](#)
- [TrustedAdvisorResourceDetail \(p. 56\)](#)
- [TrustedAdvisorResourcesSummary \(p. 57\)](#)

In addition, the response contains these fields:

- **status** - The alert status of the check: "ok" (green), "warning" (yellow), "error" (red), or "not\_available".
- **timestamp** - The time of the last refresh of the check.
- **checkId** - The unique identifier for the check.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{  
  "checkId": "string",  
  "language": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### **checkId (p. 28)**

The unique identifier for the Trusted Advisor check.

Type: String

### **language (p. 28)**

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

## Response Syntax

```
{
  "result": {
    "categorySpecificSummary": {
      "costOptimizing": {
        "estimatedMonthlySavings": number,
        "estimatedPercentMonthlySavings": number
      }
    },
    "checkId": "string",
    "flaggedResources": [
      {
        "isSuppressed": boolean,
        "metadata": [ "string" ],
        "region": "string",
        "resourceId": "string",
        "status": "string"
      }
    ],
    "resourcesSummary": {
      "resourcesFlagged": number,
      "resourcesIgnored": number,
      "resourcesProcessed": number,
      "resourcesSuppressed": number
    },
    "status": "string",
    "timestamp": "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### result (p. 29)

The detailed results of the Trusted Advisor check.

Type: [TrustedAdvisorCheckResult \(p. 53\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### InternalServerError

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

## DescribeTrustedAdvisorChecks

Returns information about all available AWS Trusted Advisor checks, including the name, ID, category, description, and metadata. You must specify a language code. The AWS Support API currently supports English ("en") and Japanese ("ja"). The response contains a [TrustedAdvisorCheckDescription \(p. 51\)](#) object for each check. You must set the AWS Region to us-east-1.

### Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).
- The names and descriptions for Trusted Advisor checks are subject to change. We recommend that you specify the check ID in your code to uniquely identify a check.

## Request Syntax

```
{  
  "language": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### language (p. 31)

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

## Response Syntax

```
{  
  "checks": [  
    {  
      "category": "string",  
      "description": "string",  
      "id": "string",  
      "metadata": [ "string" ],  
      "name": "string"  
    }  
  ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [checks \(p. 31\)](#)

Information about all available Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckDescription \(p. 51\)](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeTrustedAdvisorCheckSummaries

Returns the results for the AWS Trusted Advisor check summaries for the check IDs that you specified. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks \(p. 31\)](#) operation.

The response contains an array of [TrustedAdvisorCheckSummary \(p. 54\)](#) objects.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{  
  "checkIds": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### [checkIds \(p. 33\)](#)

The IDs of the Trusted Advisor checks.

Type: Array of strings

## Response Syntax

```
{  
  "summaries": [  
    {  
      "categorySpecificSummary": {  
        "costOptimizing": {  
          "estimatedMonthlySavings": number,  
          "estimatedPercentMonthlySavings": number  
        }  
      },  
      "checkId": "string",  
      "hasFlaggedResources": boolean,  
      "resourcesSummary": {  
        "resourcesFlagged": number,  
        "resourcesIgnored": number,  
        "resourcesProcessed": number,  
        "resourcesSuppressed": number  
      },  
      "status": "string",  
      "timestamp": "string"  
    }  
  ]  
}
```

```
} ]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### **summaries** (p. 33)

The summary information for the requested Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckSummary](#) (p. 54) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 60).

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# RefreshTrustedAdvisorCheck

Refreshes the AWS Trusted Advisor check that you specify using the check ID. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks \(p. 31\)](#) operation.

## Note

Some checks are refreshed automatically. If you call the `RefreshTrustedAdvisorCheck` operation to refresh them, you might see the `InvalidParameterValue` error.

The response contains a [TrustedAdvisorCheckRefreshStatus \(p. 52\)](#) object.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{  
  "checkId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 58\)](#).

The request accepts the following data in JSON format.

### checkId (p. 35)

The unique identifier for the Trusted Advisor check to refresh. **Note:** Specifying the check ID of a check that is automatically refreshed causes an `InvalidParameterValue` error.

Type: String

## Response Syntax

```
{  
  "status": {  
    "checkId": "string",  
    "millisUntilNextRefreshable": number,  
    "status": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.



### [status \(p. 35\)](#)

The current refresh status for a check, including the amount of time until the check is eligible for refresh.

Type: [TrustedAdvisorCheckRefreshStatus \(p. 52\)](#) object

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ResolveCase

Resolves a support case. This operation takes a `caseId` and returns the initial and final state of the case.

## Note

- You must have a Business or Enterprise support plan to use the AWS Support API.
- If you call the AWS Support API from an account that does not have a Business or Enterprise support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

## Request Syntax

```
{
  "caseId": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 58).

The request accepts the following data in JSON format.

### `caseId` (p. 37)

The AWS Support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

## Response Syntax

```
{
  "finalCaseStatus": "string",
  "initialCaseStatus": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### `finalCaseStatus` (p. 37)

The status of the case after the [ResolveCase](#) (p. 37) request was processed.

Type: String

### `initialCaseStatus` (p. 37)

The status of the case when the [ResolveCase](#) (p. 37) request was sent.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 60\)](#).

### **CaseIdNotFound**

The requested `caseId` could not be located.

HTTP Status Code: 400

### **InternalServerError**

An internal server error occurred.

HTTP Status Code: 500

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWS Support API contains several data types that various actions use. This section describes each data type in detail.

**Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Attachment](#) (p. 40)
- [AttachmentDetails](#) (p. 41)
- [CaseDetails](#) (p. 42)
- [Category](#) (p. 45)
- [Communication](#) (p. 46)
- [RecentCaseCommunications](#) (p. 47)
- [Service](#) (p. 48)
- [SeverityLevel](#) (p. 49)
- [TrustedAdvisorCategorySpecificSummary](#) (p. 50)
- [TrustedAdvisorCheckDescription](#) (p. 51)
- [TrustedAdvisorCheckRefreshStatus](#) (p. 52)
- [TrustedAdvisorCheckResult](#) (p. 53)
- [TrustedAdvisorCheckSummary](#) (p. 54)
- [TrustedAdvisorCostOptimizingSummary](#) (p. 55)
- [TrustedAdvisorResourceDetail](#) (p. 56)
- [TrustedAdvisorResourcesSummary](#) (p. 57)

# Attachment

An attachment to a case communication. The attachment consists of the file name and the content of the file.

## Contents

### **data**

The content of the attachment file.

Type: Base64-encoded binary data object

### **fileName**

The name of the attachment file.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# AttachmentDetails

The file name and ID of an attachment to a case communication. You can use the ID to retrieve the attachment with the [DescribeAttachment](#) (p. 13) operation.

## Contents

### **attachmentId**

The ID of the attachment.

Type: String

### **fileName**

The file name of the attachment.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

## CaseDetails

A JSON-formatted object that contains the metadata for a support case. It is contained in the response from a [DescribeCases](#) (p. 15) request. **CaseDetails** contains the following fields:

- **caseId**. The AWS Support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`.
- **categoryCode**. The category of problem for the AWS Support case. Corresponds to the `CategoryCode` values returned by a call to [DescribeServices](#) (p. 22).
- **displayId**. The identifier for the case on pages in the AWS Support Center.
- **language**. The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.
- **nextToken**. A resumption point for pagination.
- **recentCommunications**. One or more [Communication](#) (p. 46) objects. Fields of these objects are `attachments`, `body`, `caseId`, `submittedBy`, and `timeCreated`.
- **serviceCode**. The identifier for the AWS service that corresponds to the service code defined in the call to [DescribeServices](#) (p. 22).
- **severityCode**. The severity code assigned to the case. Contains one of the values returned by the call to [DescribeSeverityLevels](#) (p. 24). The possible values are: `low`, `normal`, `high`, `urgent`, and `critical`.
- **status**. The status of the case in the AWS Support Center. Valid values:
  - `opened`
  - `pending-customer-action`
  - `reopened`
  - `resolved`
  - `unassigned`
  - `work-in-progress`
- **subject**. The subject line of the case.
- **submittedBy**. The email address of the account that submitted the case.
- **timeCreated**. The time the case was created, in ISO-8601 format.

## Contents

### **caseId**

The AWS Support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

### **categoryCode**

The category of problem for the AWS Support case.

Type: String

### **ccEmailAddresses**

The email addresses that receive copies of communication about the case.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

**displayId**

The ID displayed for the case in the AWS Support Center. This is a numeric string.

Type: String

**language**

The ISO 639-1 code for the language in which AWS provides support. AWS Support currently supports English ("en") and Japanese ("ja"). Language parameters must be passed explicitly for operations that take them.

Type: String

**recentCommunications**

The five most recent communications between you and AWS Support Center, including the IDs of any attachments to the communications. Also includes a `nextToken` that you can use to retrieve earlier communications.

Type: [RecentCaseCommunications \(p. 47\)](#) object

**serviceCode**

The code for the AWS service. You can get a list of codes and the corresponding service names by calling [DescribeServices \(p. 22\)](#).

Type: String

**severityCode**

The code for the severity level returned by the call to [DescribeSeverityLevels \(p. 24\)](#).

Type: String

**status**

The status of the case.

Valid values:

- `opened`
- `pending-customer-action`
- `reopened`
- `resolved`
- `unassigned`
- `work-in-progress`

Type: String

**subject**

The subject line for the case in the AWS Support Center.

Type: String

**submittedBy**

The email address of the account that submitted the case.

Type: String

**timeCreated**

The time that the case was created in the AWS Support Center.



Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

## Category

A JSON-formatted name/value pair that represents the category name and category code of the problem, selected from the [DescribeServices \(p. 22\)](#) response for each AWS service.

### Contents

**code**

The category code for the support case.

Type: String

**name**

The category name for the support case.

Type: String

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# Communication

A communication associated with an AWS Support case. The communication consists of the case ID, the message body, attachment information, the submitter of the communication, and the date and time of the communication.

## Contents

### **attachmentSet**

Information about the attachments to the case communication.

Type: Array of [AttachmentDetails \(p. 41\)](#) objects

### **body**

The text of the communication between the customer and AWS Support.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

### **caseId**

The AWS Support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

### **submittedBy**

The identity of the account that submitted, or responded to, the support case. Customer entries include the role or IAM user as well as the email address. For example, "AdminRole (Role) <someone@example.com>". Entries from the AWS Support team display "Amazon Web Services," and do not show an email address.

Type: String

### **timeCreated**

The time the communication was created.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# RecentCaseCommunications

The five most recent communications associated with the case.

## Contents

### **communications**

The five most recent communications associated with the case.

Type: Array of [Communication](#) (p. 46) objects

### **nextToken**

A resumption point for pagination.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

## Service

Information about an AWS service returned by the [DescribeServices \(p. 22\)](#) operation.

### Contents

#### categories

A list of categories that describe the type of support issue a case describes. Categories consist of a category name and a category code. Category names and codes are passed to AWS Support when you call [CreateCase \(p. 9\)](#).

Type: Array of [Category \(p. 45\)](#) objects

#### code

The code for an AWS service returned by the [DescribeServices \(p. 22\)](#) response. The `name` element contains the corresponding friendly name.

Type: String

#### name

The friendly name for an AWS service. The `code` element contains the corresponding code.

Type: String

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

## SeverityLevel

A code and name pair that represents the severity level of a support case. The available values depend on the support plan for the account. For more information, see [Choosing a severity](#) in the *AWS Support User Guide*.

### Contents

#### code

The code for case severity level.

Valid values: `low` | `normal` | `high` | `urgent` | `critical`

Type: String

#### name

The name of the severity level that corresponds to the severity level code.

##### Note

The values returned by the API differ from the values that are displayed in the AWS Support Center. For example, for the code "low", the API name is "Low", but the name in the Support Center is "General guidance". These are the Support Center code/name mappings:

- `low`: General guidance
- `normal`: System impaired
- `high`: Production system impaired
- `urgent`: Production system down
- `critical`: Business-critical system down

For more information, see [Choosing a severity](#) in the *AWS Support User Guide*.

Type: String

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# TrustedAdvisorCategorySpecificSummary

The container for summary information that relates to the category of the Trusted Advisor check.

## Contents

### **costOptimizing**

The summary information about cost savings for a Trusted Advisor check that is in the Cost Optimizing category.

Type: [TrustedAdvisorCostOptimizingSummary \(p. 55\)](#) object

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# TrustedAdvisorCheckDescription

The description and metadata for a Trusted Advisor check.

## Contents

### **category**

The category of the Trusted Advisor check.

Type: String

### **description**

The description of the Trusted Advisor check, which includes the alert criteria and recommended operations (contains HTML markup).

Type: String

### **id**

The unique identifier for the Trusted Advisor check.

Type: String

### **metadata**

The column headings for the data returned by the Trusted Advisor check. The order of the headings corresponds to the order of the data in the **Metadata** element of the [TrustedAdvisorResourceDetail \(p. 56\)](#) for the check. **Metadata** contains all the data that is shown in the Excel download, even in those cases where the UI shows just summary data.

Type: Array of strings

### **name**

The display name for the Trusted Advisor check.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)



# TrustedAdvisorCheckRefreshStatus

The refresh status of a Trusted Advisor check.

## Contents

### **checkId**

The unique identifier for the Trusted Advisor check.

Type: String

### **millisUntilNextRefreshable**

The amount of time, in milliseconds, until the Trusted Advisor check is eligible for refresh.

Type: Long

### **status**

The status of the Trusted Advisor check for which a refresh has been requested:

- `none`: The check is not refreshed or the non-success status exceeds the timeout
- `enqueued`: The check refresh requests has entered the refresh queue
- `processing`: The check refresh request is picked up by the rule processing engine
- `success`: The check is successfully refreshed
- `abandoned`: The check refresh has failed

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# TrustedAdvisorCheckResult

The results of a Trusted Advisor check returned by [DescribeTrustedAdvisorCheckResult \(p. 28\)](#).

## Contents

### **categorySpecificSummary**

Summary information that relates to the category of the check. Cost Optimizing is the only category that is currently supported.

Type: [TrustedAdvisorCategorySpecificSummary \(p. 50\)](#) object

### **checkId**

The unique identifier for the Trusted Advisor check.

Type: String

### **flaggedResources**

The details about each resource listed in the check result.

Type: Array of [TrustedAdvisorResourceDetail \(p. 56\)](#) objects

### **resourcesSummary**

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries \(p. 33\)](#).

Type: [TrustedAdvisorResourcesSummary \(p. 57\)](#) object

### **status**

The alert status of the check: "ok" (green), "warning" (yellow), "error" (red), or "not\_available".

Type: String

### **timestamp**

The time of the last refresh of the check.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# TrustedAdvisorCheckSummary

A summary of a Trusted Advisor check result, including the alert status, last refresh, and number of resources examined.

## Contents

### **categorySpecificSummary**

Summary information that relates to the category of the check. Cost Optimizing is the only category that is currently supported.

Type: [TrustedAdvisorCategorySpecificSummary \(p. 50\)](#) object

### **checkId**

The unique identifier for the Trusted Advisor check.

Type: String

### **hasFlaggedResources**

Specifies whether the Trusted Advisor check has flagged resources.

Type: Boolean

### **resourcesSummary**

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries \(p. 33\)](#).

Type: [TrustedAdvisorResourcesSummary \(p. 57\)](#) object

### **status**

The alert status of the check: "ok" (green), "warning" (yellow), "error" (red), or "not\_available".

Type: String

### **timestamp**

The time of the last refresh of the check.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# TrustedAdvisorCostOptimizingSummary

The estimated cost savings that might be realized if the recommended operations are taken.

## Contents

### **estimatedMonthlySavings**

The estimated monthly savings that might be realized if the recommended operations are taken.

Type: Double

### **estimatedPercentMonthlySavings**

The estimated percentage of savings that might be realized if the recommended operations are taken.

Type: Double

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# TrustedAdvisorResourceDetail

Contains information about a resource identified by a Trusted Advisor check.

## Contents

### **isSuppressed**

Specifies whether the AWS resource was ignored by Trusted Advisor because it was marked as suppressed by the user.

Type: Boolean

### **metadata**

Additional information about the identified resource. The exact metadata and its order can be obtained by inspecting the [TrustedAdvisorCheckDescription](#) (p. 51) object returned by the call to [DescribeTrustedAdvisorChecks](#) (p. 31). **Metadata** contains all the data that is shown in the Excel download, even in those cases where the UI shows just summary data.

Type: Array of strings

### **region**

The AWS region in which the identified resource is located.

Type: String

### **resourceId**

The unique identifier for the identified resource.

Type: String

### **status**

The status code for the resource identified in the Trusted Advisor check.

Type: String

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# TrustedAdvisorResourcesSummary

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries](#) (p. 33).

## Contents

### **resourcesFlagged**

The number of AWS resources that were flagged (listed) by the Trusted Advisor check.

Type: Long

### **resourcesIgnored**

The number of AWS resources ignored by Trusted Advisor because information was unavailable.

Type: Long

### **resourcesProcessed**

The number of AWS resources that were analyzed by the Trusted Advisor check.

Type: Long

### **resourcesSuppressed**

The number of AWS resources ignored by Trusted Advisor because they were marked as suppressed by the user.

Type: Long

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

## X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

#### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

#### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

#### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional



# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **InvalidParameterCombination**

Parameters that must not be used together were used together.

HTTP Status Code: 400

## **InvalidParameterValue**

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

## **InvalidQueryParameter**

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

## **MalformedQueryString**

The query string contains a syntax error.

HTTP Status Code: 404

## **MissingAction**

The request is missing an action or a required parameter.

HTTP Status Code: 400

**MissingAuthenticationToken**

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

**MissingParameter**

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

**NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

**OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

**RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

**ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

**ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400