



API Reference

Amazon AppStream 2.0



API Version 2016-12-01

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon AppStream 2.0: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateAppBlockBuilderAppBlock	5
Request Syntax	5
Request Parameters	5
Response Syntax	5
Response Elements	6
Errors	6
See Also	7
AssociateApplicationFleet	8
Request Syntax	8
Request Parameters	8
Response Syntax	8
Response Elements	9
Errors	9
See Also	10
AssociateApplicationToEntitlement	11
Request Syntax	11
Request Parameters	11
Response Elements	12
Errors	12
See Also	12
AssociateFleet	14
Request Syntax	14
Request Parameters	14
Response Elements	14
Errors	15
See Also	15
BatchAssociateUserStack	17
Request Syntax	17
Request Parameters	17
Response Syntax	17
Response Elements	18
Errors	18

See Also	18
BatchDisassociateUserStack	20
Request Syntax	20
Request Parameters	20
Response Syntax	20
Response Elements	21
Errors	21
See Also	21
CopyImage	23
Request Syntax	23
Request Parameters	23
Response Syntax	24
Response Elements	24
Errors	24
See Also	25
CreateAppBlock	27
Request Syntax	27
Request Parameters	28
Response Syntax	29
Response Elements	30
Errors	31
See Also	31
CreateAppBlockBuilder	33
Request Syntax	33
Request Parameters	33
Response Syntax	36
Response Elements	37
Errors	38
See Also	39
CreateAppBlockBuilderStreamingURL	40
Request Syntax	40
Request Parameters	40
Response Syntax	40
Response Elements	41
Errors	41
See Also	41

CreateApplication	43
Request Syntax	43
Request Parameters	43
Response Syntax	46
Response Elements	47
Errors	47
See Also	48
CreateDirectoryConfig	49
Request Syntax	49
Request Parameters	49
Response Syntax	50
Response Elements	51
Errors	51
See Also	52
CreateEntitlement	53
Request Syntax	53
Request Parameters	53
Response Syntax	54
Response Elements	55
Errors	55
See Also	56
CreateFleet	57
Request Syntax	57
Request Parameters	58
Response Syntax	66
Response Elements	67
Errors	68
See Also	69
CreateImageBuilder	71
Request Syntax	71
Request Parameters	71
Response Syntax	77
Response Elements	78
Errors	78
See Also	80
CreateImageBuilderStreamingURL	81

Request Syntax	81
Request Parameters	81
Response Syntax	81
Response Elements	82
Errors	82
See Also	82
CreateStack	84
Request Syntax	84
Request Parameters	85
Response Syntax	88
Response Elements	89
Errors	89
See Also	90
CreateStreamingURL	92
Request Syntax	92
Request Parameters	92
Response Syntax	94
Response Elements	94
Errors	94
See Also	95
CreateThemeForStack	96
Request Syntax	96
Request Parameters	96
Response Syntax	98
Response Elements	98
Errors	98
See Also	99
CreateUpdatedImage	101
Request Syntax	101
Request Parameters	101
Response Syntax	103
Response Elements	104
Errors	105
See Also	106
CreateUsageReportSubscription	107
Response Syntax	107

Response Elements	107
Errors	108
See Also	108
CreateUser	109
Request Syntax	109
Request Parameters	109
Response Elements	111
Errors	111
See Also	112
DeleteAppBlock	113
Request Syntax	113
Request Parameters	113
Response Elements	113
Errors	113
See Also	114
DeleteAppBlockBuilder	115
Request Syntax	115
Request Parameters	115
Response Elements	115
Errors	115
See Also	116
DeleteApplication	117
Request Syntax	117
Request Parameters	117
Response Elements	117
Errors	117
See Also	118
DeleteDirectoryConfig	119
Request Syntax	119
Request Parameters	119
Response Elements	119
Errors	119
See Also	120
DeleteEntitlement	121
Request Syntax	121
Request Parameters	121

Response Elements	121
Errors	122
See Also	122
DeleteFleet	124
Request Syntax	124
Request Parameters	124
Response Elements	124
Errors	124
See Also	125
DeletelImage	126
Request Syntax	126
Request Parameters	126
Response Syntax	126
Response Elements	128
Errors	128
See Also	129
DeletelImageBuilder	130
Request Syntax	130
Request Parameters	130
Response Syntax	130
Response Elements	131
Errors	132
See Also	132
DeletelImagePermissions	134
Request Syntax	134
Request Parameters	134
Response Elements	134
Errors	135
See Also	135
DeleteStack	136
Request Syntax	136
Request Parameters	136
Response Elements	136
Errors	136
See Also	137
DeleteThemeForStack	138

Request Syntax	138
Request Parameters	138
Response Elements	138
Errors	138
See Also	139
DeleteUsageReportSubscription	140
Response Elements	140
Errors	140
See Also	140
DeleteUser	142
Request Syntax	142
Request Parameters	142
Response Elements	143
Errors	143
See Also	143
DescribeAppBlockBuilderAppBlockAssociations	144
Request Syntax	144
Request Parameters	144
Response Syntax	145
Response Elements	145
Errors	146
See Also	146
DescribeAppBlockBuilders	147
Request Syntax	147
Request Parameters	147
Response Syntax	148
Response Elements	149
Errors	149
See Also	149
DescribeAppBlocks	151
Request Syntax	151
Request Parameters	151
Response Syntax	152
Response Elements	153
Errors	153
See Also	154

DescribeApplicationFleetAssociations	155
Request Syntax	155
Request Parameters	155
Response Syntax	156
Response Elements	156
Errors	157
See Also	157
DescribeApplications	159
Request Syntax	159
Request Parameters	159
Response Syntax	160
Response Elements	160
Errors	161
See Also	161
DescribeDirectoryConfigs	163
Request Syntax	163
Request Parameters	163
Response Syntax	164
Response Elements	164
Errors	165
See Also	165
DescribeEntitlements	166
Request Syntax	166
Request Parameters	166
Response Syntax	167
Response Elements	167
Errors	168
See Also	168
DescribeFleets	170
Request Syntax	170
Request Parameters	170
Response Syntax	170
Response Elements	172
Errors	172
See Also	173
DescribeImageBuilders	174

Request Syntax	174
Request Parameters	174
Response Syntax	175
Response Elements	176
Errors	176
See Also	177
DescribeImagePermissions	178
Request Syntax	178
Request Parameters	178
Response Syntax	179
Response Elements	179
Errors	180
See Also	180
DescribeImages	182
Request Syntax	182
Request Parameters	182
Response Syntax	183
Response Elements	185
Errors	185
See Also	186
DescribeSessions	187
Request Syntax	187
Request Parameters	187
Response Syntax	189
Response Elements	189
Errors	190
See Also	190
DescribeStacks	191
Request Syntax	191
Request Parameters	191
Response Syntax	191
Response Elements	193
Errors	193
See Also	193
DescribeThemeForStack	195
Request Syntax	195

Request Parameters	195
Response Syntax	195
Response Elements	196
Errors	196
See Also	196
DescribeUsageReportSubscriptions	198
Request Syntax	198
Request Parameters	198
Response Syntax	198
Response Elements	199
Errors	199
See Also	200
DescribeUsers	201
Request Syntax	201
Request Parameters	201
Response Syntax	202
Response Elements	202
Errors	203
See Also	203
DescribeUserStackAssociations	204
Request Syntax	204
Request Parameters	204
Response Syntax	205
Response Elements	206
Errors	206
See Also	207
DisableUser	208
Request Syntax	208
Request Parameters	208
Response Elements	209
Errors	209
See Also	209
DisassociateAppBlockBuilderAppBlock	210
Request Syntax	210
Request Parameters	210
Response Elements	210

Errors	211
See Also	211
DisassociateApplicationFleet	213
Request Syntax	213
Request Parameters	213
Response Elements	213
Errors	214
See Also	214
DisassociateApplicationFromEntitlement	215
Request Syntax	215
Request Parameters	215
Response Elements	216
Errors	216
See Also	216
DisassociateFleet	218
Request Syntax	218
Request Parameters	218
Response Elements	218
Errors	219
See Also	219
EnableUser	221
Request Syntax	221
Request Parameters	221
Response Elements	222
Errors	222
See Also	222
ExpireSession	224
Request Syntax	224
Request Parameters	224
Response Elements	224
Errors	224
See Also	224
ListAssociatedFleets	226
Request Syntax	226
Request Parameters	226
Response Syntax	226

Response Elements	227
Errors	227
See Also	227
ListAssociatedStacks	229
Request Syntax	229
Request Parameters	229
Response Syntax	229
Response Elements	230
Errors	230
See Also	230
ListEntitledApplications	232
Request Syntax	232
Request Parameters	232
Response Syntax	233
Response Elements	233
Errors	234
See Also	234
ListTagsForResource	235
Request Syntax	235
Request Parameters	235
Response Syntax	235
Response Elements	236
Errors	236
See Also	236
StartAppBlockBuilder	238
Request Syntax	238
Request Parameters	238
Response Syntax	238
Response Elements	239
Errors	239
See Also	240
StartFleet	242
Request Syntax	242
Request Parameters	242
Response Elements	242
Errors	242

See Also	243
StartImageBuilder	245
Request Syntax	245
Request Parameters	245
Response Syntax	245
Response Elements	247
Errors	247
See Also	248
StopAppBlockBuilder	249
Request Syntax	249
Request Parameters	249
Response Syntax	249
Response Elements	250
Errors	250
See Also	251
StopFleet	252
Request Syntax	252
Request Parameters	252
Response Elements	252
Errors	252
See Also	253
StopImageBuilder	254
Request Syntax	254
Request Parameters	254
Response Syntax	254
Response Elements	255
Errors	256
See Also	256
TagResource	258
Request Syntax	258
Request Parameters	258
Response Elements	259
Errors	259
See Also	260
UntagResource	261
Request Syntax	261

Request Parameters	261
Response Elements	262
Errors	262
See Also	262
UpdateAppBlockBuilder	263
Request Syntax	263
Request Parameters	263
Response Syntax	266
Response Elements	267
Errors	267
See Also	269
UpdateApplication	270
Request Syntax	270
Request Parameters	270
Response Syntax	272
Response Elements	273
Errors	273
See Also	274
UpdateDirectoryConfig	275
Request Syntax	275
Request Parameters	275
Response Syntax	276
Response Elements	277
Errors	277
See Also	278
UpdateEntitlement	279
Request Syntax	279
Request Parameters	279
Response Syntax	280
Response Elements	281
Errors	281
See Also	282
UpdateFleet	283
Request Syntax	283
Request Parameters	284
Response Syntax	291

Response Elements	292
Errors	293
See Also	294
UpdateImagePermissions	296
Request Syntax	296
Request Parameters	296
Response Elements	297
Errors	297
See Also	297
UpdateStack	299
Request Syntax	299
Request Parameters	300
Response Syntax	303
Response Elements	304
Errors	304
See Also	306
UpdateThemeForStack	307
Request Syntax	307
Request Parameters	307
Response Syntax	309
Response Elements	310
Errors	310
See Also	311
Data Types	312
AccessEndpoint	314
Contents	314
See Also	314
AppBlock	315
Contents	315
See Also	317
AppBlockBuilder	319
Contents	319
See Also	322
AppBlockBuilderAppBlockAssociation	323
Contents	323
See Also	323

AppBlockBuilderStateChangeReason	324
Contents	324
See Also	324
Application	325
Contents	325
See Also	328
ApplicationFleetAssociation	329
Contents	329
See Also	329
ApplicationSettings	330
Contents	330
See Also	330
ApplicationSettingsResponse	331
Contents	331
See Also	331
CertificateBasedAuthProperties	333
Contents	333
See Also	333
ComputeCapacity	335
Contents	335
See Also	335
ComputeCapacityStatus	336
Contents	336
See Also	337
DirectoryConfig	339
Contents	339
See Also	340
DomainJoinInfo	341
Contents	341
See Also	341
EntitledApplication	342
Contents	342
See Also	342
Entitlement	343
Contents	343
See Also	344

EntitlementAttribute	345
Contents	345
See Also	346
ErrorDetails	347
Contents	347
See Also	347
Fleet	348
Contents	348
See Also	356
FleetError	357
Contents	357
See Also	358
Image	359
Contents	359
See Also	363
ImageBuilder	365
Contents	365
See Also	371
ImageBuilderStateChangeReason	372
Contents	372
See Also	372
ImagePermissions	373
Contents	373
See Also	373
ImageStateChangeReason	374
Contents	374
See Also	374
LastReportGenerationExecutionError	375
Contents	375
See Also	375
NetworkAccessConfiguration	376
Contents	376
See Also	376
ResourceError	377
Contents	377
See Also	378

S3Location	379
Contents	379
See Also	380
ScriptDetails	381
Contents	381
See Also	381
ServiceAccountCredentials	383
Contents	383
See Also	383
Session	384
Contents	384
See Also	386
SharedImagePermissions	387
Contents	387
See Also	387
Stack	388
Contents	388
See Also	391
StackError	392
Contents	392
See Also	392
StorageConnector	393
Contents	393
See Also	394
StreamingExperienceSettings	395
Contents	395
See Also	395
Theme	396
Contents	396
See Also	397
ThemeFooterLink	399
Contents	399
See Also	399
UsageReportSubscription	400
Contents	400
See Also	401

User	402
Contents	402
See Also	404
UserSetting	405
Contents	405
See Also	406
UserStackAssociation	407
Contents	407
See Also	408
UserStackAssociationError	409
Contents	409
See Also	409
VpcConfig	411
Contents	411
See Also	411
Common Parameters	412
Common Errors	415

Welcome

This is the *Amazon AppStream 2.0 API Reference*. This documentation provides descriptions and syntax for each of the actions and data types in AppStream 2.0. AppStream 2.0 is a fully managed, secure application streaming service that lets you stream desktop applications to users without rewriting applications. AppStream 2.0 manages the AWS resources that are required to host and run your applications, scales automatically, and provides access to your users on demand.

Note

You can call the AppStream 2.0 API operations by using an interface VPC endpoint (interface endpoint). For more information, see [Access AppStream 2.0 API Operations and CLI Commands Through an Interface VPC Endpoint](#) in the *Amazon AppStream 2.0 Administration Guide*.

To learn more about AppStream 2.0, see the following resources:

- [Amazon AppStream 2.0 product page](#)
- [Amazon AppStream 2.0 documentation](#)

This document was last published on September 3, 2025.

Actions

The following actions are supported:

- [AssociateAppBlockBuilderAppBlock](#)
- [AssociateApplicationFleet](#)
- [AssociateApplicationToEntitlement](#)
- [AssociateFleet](#)
- [BatchAssociateUserStack](#)
- [BatchDisassociateUserStack](#)
- [CopyImage](#)
- [CreateAppBlock](#)
- [CreateAppBlockBuilder](#)
- [CreateAppBlockBuilderStreamingURL](#)
- [CreateApplication](#)
- [CreateDirectoryConfig](#)
- [CreateEntitlement](#)
- [CreateFleet](#)
- [CreateImageBuilder](#)
- [CreateImageBuilderStreamingURL](#)
- [CreateStack](#)
- [CreateStreamingURL](#)
- [CreateThemeForStack](#)
- [CreateUpdatedImage](#)
- [CreateUsageReportSubscription](#)
- [CreateUser](#)
- [DeleteAppBlock](#)
- [DeleteAppBlockBuilder](#)
- [DeleteApplication](#)
- [DeleteDirectoryConfig](#)
- [DeleteEntitlement](#)

- [DeleteFleet](#)
- [DeleteImage](#)
- [DeleteImageBuilder](#)
- [DeleteImagePermissions](#)
- [DeleteStack](#)
- [DeleteThemeForStack](#)
- [DeleteUsageReportSubscription](#)
- [DeleteUser](#)
- [DescribeAppBlockBuilderAppBlockAssociations](#)
- [DescribeAppBlockBuilders](#)
- [DescribeAppBlocks](#)
- [DescribeApplicationFleetAssociations](#)
- [DescribeApplications](#)
- [DescribeDirectoryConfigs](#)
- [DescribeEntitlements](#)
- [DescribeFleets](#)
- [DescribeImageBuilders](#)
- [DescribeImagePermissions](#)
- [DescribeImages](#)
- [DescribeSessions](#)
- [DescribeStacks](#)
- [DescribeThemeForStack](#)
- [DescribeUsageReportSubscriptions](#)
- [DescribeUsers](#)
- [DescribeUserStackAssociations](#)
- [DisableUser](#)
- [DisassociateAppBlockBuilderAppBlock](#)
- [DisassociateApplicationFleet](#)
- [DisassociateApplicationFromEntitlement](#)
- [DisassociateFleet](#)

- [EnableUser](#)
- [ExpireSession](#)
- [ListAssociatedFleets](#)
- [ListAssociatedStacks](#)
- [ListEntitledApplications](#)
- [ListTagsForResource](#)
- [StartAppBlockBuilder](#)
- [StartFleet](#)
- [StartImageBuilder](#)
- [StopAppBlockBuilder](#)
- [StopFleet](#)
- [StopImageBuilder](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAppBlockBuilder](#)
- [UpdateApplication](#)
- [UpdateDirectoryConfig](#)
- [UpdateEntitlement](#)
- [UpdateFleet](#)
- [UpdateImagePermissions](#)
- [UpdateStack](#)
- [UpdateThemeForStack](#)

AssociateAppBlockBuilderAppBlock

Associates the specified app block builder with the specified app block.

Request Syntax

```
{  
  "AppBlockArn": "string",  
  "AppBlockBuilderName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppBlockArn

The ARN of the app block.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: Yes

AppBlockBuilderName

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Syntax

```
{
```

```
"AppBlockBuilderAppBlockAssociation": {  
  "AppBlockArn": "string",  
  "AppBlockBuilderName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AppBlockBuilderAppBlockAssociation](#)

The list of app block builders associated with app blocks.

Type: [AppBlockBuilderAppBlockAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateApplicationFleet

Associates the specified application with the specified fleet. This is only supported for Elastic fleets.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "FleetName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationArn

The ARN of the application.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: Yes

FleetName

The name of the fleet.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Syntax

```
{
```

```
"ApplicationFleetAssociation": {  
  "ApplicationArn": "string",  
  "FleetName": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationFleetAssociation

If fleet name is specified, this returns the list of applications that are associated to it. If application ARN is specified, this returns the list of fleets to which it is associated.

Type: [ApplicationFleetAssociation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateApplicationToEntitlement

Associates an application to entitle.

Request Syntax

```
{
  "ApplicationIdentifier": "string",
  "EntitlementName": "string",
  "StackName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationIdentifier

The identifier of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

EntitlementName

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

StackName

The name of the stack.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntitlementNotFoundException

The entitlement can't be found.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateFleet

Associates the specified fleet with the specified stack.

Request Syntax

```
{  
  "FleetName": "string",  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

FleetName

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

StackName

The name of the stack.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchAssociateUserStack

Associates the specified users with the specified stacks. Users in a user pool cannot be assigned to stacks with fleets that are joined to an Active Directory domain.

Request Syntax

```
{
  "UserStackAssociations": [
    {
      "AuthenticationType": "string",
      "SendEmailNotification": boolean,
      "StackName": "string",
      "UserName": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

UserStackAssociations

The list of UserStackAssociation objects.

Type: Array of [UserStackAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
{
  "errors": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
    }
  ]
}
```

```
    "UserStackAssociation": {  
      "AuthenticationType": "string",  
      "SendEmailNotification": boolean,  
      "StackName": "string",  
      "UserName": "string"  
    }  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[errors](#)

The list of UserStackAssociationError objects.

Type: Array of [UserStackAssociationError](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchDisassociateUserStack

Disassociates the specified users from the specified stacks.

Request Syntax

```
{
  "UserStackAssociations": [
    {
      "AuthenticationType": "string",
      "SendEmailNotification": boolean,
      "StackName": "string",
      "UserName": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

UserStackAssociations

The list of UserStackAssociation objects.

Type: Array of [UserStackAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
{
  "errors": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "UserStackAssociation": {
```

```
    "AuthenticationType": "string",
    "SendEmailNotification": boolean,
    "StackName": "string",
    "UserName": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

The list of `UserStackAssociationError` objects.

Type: Array of [UserStackAssociationError](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CopyImage

Copies the image within the same region or to a new region within the same AWS account. Note that any tags you added to the image will not be copied.

Request Syntax

```
{  
  "DestinationImageDescription": "string",  
  "DestinationImageName": "string",  
  "DestinationRegion": "string",  
  "SourceImageName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[DestinationImageDescription](#)

The description that the image will have when it is copied to the destination.

Type: String

Length Constraints: Maximum length of 256.

Required: No

[DestinationImageName](#)

The name that the image will have when it is copied to the destination.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

[DestinationRegion](#)

The destination region to which the image will be copied. This parameter is required, even if you are copying an image within the same region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Required: Yes

SourceImageName

The name of the image to copy.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Syntax

```
{
  "DestinationImageName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DestinationImageName

The name of the destination image.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAppBlock

Creates an app block.

App blocks are an Amazon AppStream 2.0 resource that stores the details about the virtual hard disk in an S3 bucket. It also stores the setup script with details about how to mount the virtual hard disk. The virtual hard disk includes the application binaries and other files necessary to launch your applications. Multiple applications can be assigned to a single app block.

This is only supported for Elastic fleets.

Request Syntax

```
{
  "Description": "string",
  "DisplayName": "string",
  "Name": "string",
  "PackagingType": "string",
  "PostSetupScriptDetails": {
    "ExecutableParameters": "string",
    "ExecutablePath": "string",
    "ScriptS3Location": {
      "S3Bucket": "string",
      "S3Key": "string"
    },
    "TimeoutInSeconds": number
  },
  "SetupScriptDetails": {
    "ExecutableParameters": "string",
    "ExecutablePath": "string",
    "ScriptS3Location": {
      "S3Bucket": "string",
      "S3Key": "string"
    },
    "TimeoutInSeconds": number
  },
  "SourceS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "Tags": {
    "string" : "string"
  }
}
```



```
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Description

The description of the app block.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

The display name of the app block. This is not displayed to the user.

Type: String

Length Constraints: Maximum length of 100.

Required: No

Name

The name of the app block.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

PackagingType

The packaging type of the app block.

Type: String

Valid Values: CUSTOM | APPSTREAM2

Required: No

PostSetupScriptDetails

The post setup script details of the app block. This can only be provided for the APPSTREAM2 PackagingType.

Type: [ScriptDetails](#) object

Required: No

SetupScriptDetails

The setup script details of the app block. This must be provided for the CUSTOM PackagingType.

Type: [ScriptDetails](#) object

Required: No

SourceS3Location

The source S3 location of the app block.

Type: [S3Location](#) object

Required: Yes

Tags

The tags assigned to the app block.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(!aws:)|[\p{L}\p{Z}\p{N}_:/+=\-\@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^([\p{L}\p{Z}\p{N}_:/+=\-\@]*)$`

Required: No

Response Syntax

```
{  
  "AppBlock": {
```

```

    "AppBlockErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string"
      }
    ],
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "Name": "string",
    "PackagingType": "string",
    "PostSetupScriptDetails": {
      "ExecutableParameters": "string",
      "ExecutablePath": "string",
      "ScriptS3Location": {
        "S3Bucket": "string",
        "S3Key": "string"
      },
      "TimeoutInSeconds": number
    },
    "SetupScriptDetails": {
      "ExecutableParameters": "string",
      "ExecutablePath": "string",
      "ScriptS3Location": {
        "S3Bucket": "string",
        "S3Key": "string"
      },
      "TimeoutInSeconds": number
    },
    "SourceS3Location": {
      "S3Bucket": "string",
      "S3Key": "string"
    },
    "State": "string"
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AppBlock](#)

The app block.

Type: [AppBlock](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAppBlockBuilder

Creates an app block builder.

Request Syntax

```
{
  "AccessEndpoints": [
    {
      "EndpointType": "string",
      "VpceId": "string"
    }
  ],
  "Description": "string",
  "DisplayName": "string",
  "EnableDefaultInternetAccess": boolean,
  "IamRoleArn": "string",
  "InstanceType": "string",
  "Name": "string",
  "Platform": "string",
  "Tags": {
    "string" : "string"
  },
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AccessEndpoints](#)

The list of interface VPC endpoint (interface endpoint) objects. Administrators can connect to the app block builder only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

Description

The description of the app block builder.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

The display name of the app block builder.

Type: String

Length Constraints: Maximum length of 100.

Required: No

EnableDefaultInternetAccess

Enables or disables default internet access for the app block builder.

Type: Boolean

Required: No

IamRoleArn

The Amazon Resource Name (ARN) of the IAM role to apply to the app block builder. To assume a role, the app block builder calls the AWS Security Token Service (STS) AssumeRole API operation and passes the ARN of the role to use. The operation creates a new session with temporary credentials. AppStream 2.0 retrieves the temporary credentials and creates the **appstream_machine_role** credential profile on the instance.

For more information, see [Using an IAM Role to Grant Permissions to Applications and Scripts Running on AppStream 2.0 Streaming Instances](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: No

InstanceType

The instance type to use when launching the app block builder. The following instance types are available:

- stream.standard.small
- stream.standard.medium
- stream.standard.large
- stream.standard.xlarge
- stream.standard.2xlarge

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Name

The unique name for the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Platform

The platform of the app block builder.

WINDOWS_SERVER_2019 is the only valid value.

Type: String

Valid Values: WINDOWS_SERVER_2019

Required: Yes

Tags

The tags to associate with the app block builder. A tag is a key-value pair, and the value is optional. For example, Environment=Test. If you do not specify a value, Environment=.

If you do not specify a value, the value is set to an empty string.

Generally allowed characters are: letters, numbers, and spaces representable in UTF-8, and the following special characters:

`_ . : / = + \ - @`

For more information, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(?!aws:)\p{L}\p{Z}\p{N}_./=+\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^( [\p{L}\p{Z}\p{N}_./=+\-@]*)$`

Required: No

VpcConfig

The VPC configuration for the app block builder.

App block builders require that you specify at least two subnets in different availability zones.

Type: [VpcConfig](#) object

Required: Yes

Response Syntax

```
{
  "AppBlockBuilder": {
```

```

    "AccessEndpoints": [
      {
        "EndpointType": "string",
        "VpceId": "string"
      }
    ],
    "AppBlockBuilderErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
      }
    ],
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "EnableDefaultInternetAccess": boolean,
    "IamRoleArn": "string",
    "InstanceType": "string",
    "Name": "string",
    "Platform": "string",
    "State": "string",
    "StateChangeReason": {
      "Code": "string",
      "Message": "string"
    },
    "VpcConfig": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
    }
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppBlockBuilder

Describes an app block builder.

Type: [AppBlockBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

RequestLimitExceededException

AppStream 2.0 can't process the request right now because the Describe calls from your AWS account are being throttled by Amazon EC2. Try again later.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAppBlockBuilderStreamingURL

Creates a URL to start a create app block builder streaming session.

Request Syntax

```
{  
  "AppBlockBuilderName": "string",  
  "Validity": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppBlockBuilderName

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Validity

The time that the streaming URL will be valid, in seconds. Specify a value between 1 and 604800 seconds. The default is 3600 seconds.

Type: Long

Required: No

Response Syntax

```
{  
  "Expires": number,  
  "StreamingURL": "string"  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Expires

The elapsed time, in seconds after the Unix epoch, when this URL expires.

Type: Timestamp

StreamingURL

The URL to start the streaming session.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateApplication

Creates an application.

Applications are an Amazon AppStream 2.0 resource that stores the details about how to launch applications on Elastic fleet streaming instances. An application consists of the launch details, icon, and display name. Applications are associated with an app block that contains the application binaries and other files. The applications assigned to an Elastic fleet are the applications users can launch.

This is only supported for Elastic fleets.

Request Syntax

```
{
  "AppBlockArn": "string",
  "Description": "string",
  "DisplayName": "string",
  "IconS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "InstanceFamilies": [ "string" ],
  "LaunchParameters": "string",
  "LaunchPath": "string",
  "Name": "string",
  "Platforms": [ "string" ],
  "Tags": {
    "string" : "string"
  },
  "WorkingDirectory": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppBlockArn

The app block ARN to which the application should be associated

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\b|\-iso|\-us\gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: Yes

Description

The description of the application.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

The display name of the application. This name is visible to users in the application catalog.

Type: String

Length Constraints: Maximum length of 100.

Required: No

IconS3Location

The location in S3 of the application icon.

Type: [S3Location](#) object

Required: Yes

InstanceFamilies

The instance families the application supports. Valid values are GENERAL_PURPOSE and GRAPHICS_G4.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: Yes

LaunchParameters

The launch parameters of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

LaunchPath

The launch path of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Name

The name of the application. This name is visible to users when display name is not specified.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Platforms

The platforms the application supports. WINDOWS_SERVER_2019 and AMAZON_LINUX2 are supported for Elastic fleets.

Type: Array of strings

Array Members: Maximum number of 4 items.

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 |
WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: Yes

Tags

The tags assigned to the application.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(?!aws:)\p{L}\p{Z}\p{N}_:/+=\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^( [\p{L}\p{Z}\p{N}_:/+=\-@]*)$`

Required: No

WorkingDirectory

The working directory of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "Application": {
    "AppBlockArn": "string",
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "Enabled": boolean,
    "IconS3Location": {
      "S3Bucket": "string",
      "S3Key": "string"
    },
    "IconURL": "string",
    "InstanceFamilies": [ "string" ],
    "LaunchParameters": "string",
    "LaunchPath": "string",
    "Metadata": {
      "string" : "string"
    }
  }
}
```

```
    },  
    "Name": "string",  
    "Platforms": [ "string" ],  
    "WorkingDirectory": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Application](#)

Describes an application in the application catalog.

Type: [Application](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDirectoryConfig

Creates a Directory Config object in AppStream 2.0. This object includes the configuration information required to join fleets and image builders to Microsoft Active Directory domains.

Request Syntax

```
{
  "CertificateBasedAuthProperties": {
    "CertificateAuthorityArn": "string",
    "Status": "string"
  },
  "DirectoryName": "string",
  "OrganizationalUnitDistinguishedNames": [ "string" ],
  "ServiceAccountCredentials": {
    "AccountName": "string",
    "AccountPassword": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

CertificateBasedAuthProperties

The certificate-based authentication properties used to authenticate SAML 2.0 Identity Provider (IdP) user identities to Active Directory domain-joined streaming instances. Fallback is turned on by default when certificate-based authentication is **Enabled** . Fallback allows users to log in using their AD domain password if certificate-based authentication is unsuccessful, or to unlock a desktop lock screen. **Enabled_no_directory_login_fallback** enables certificate-based authentication, but does not allow users to log in using their AD domain password. Users will be disconnected to re-authenticate using certificates.

Type: [CertificateBasedAuthProperties](#) object

Required: No

DirectoryName

The fully qualified name of the directory (for example, corp.example.com).

Type: String

Required: Yes

OrganizationalUnitDistinguishedNames

The distinguished names of the organizational units for computer accounts.

Type: Array of strings

Length Constraints: Maximum length of 2000.

Required: Yes

ServiceAccountCredentials

The credentials for the service account used by the fleet or image builder to connect to the directory.

Type: [ServiceAccountCredentials](#) object

Required: No

Response Syntax

```
{
  "DirectoryName": {
    "CertificateBasedAuthProperties": {
      "CertificateAuthorityArn": "string",
      "Status": "string"
    },
    "CreatedTime": number,
    "DirectoryName": "string",
    "OrganizationalUnitDistinguishedNames": [ "string" ],
    "ServiceAccountCredentials": {
      "AccountName": "string",
      "AccountPassword": "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectoryConfig

Information about the directory configuration.

Type: [DirectoryConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEntitlement

Creates a new entitlement. Entitlements control access to specific applications within a stack, based on user attributes. Entitlements apply to SAML 2.0 federated user identities. Amazon AppStream 2.0 user pool and streaming URL users are entitled to all applications in a stack. Entitlements don't apply to the desktop stream view application, or to applications managed by a dynamic app provider using the Dynamic Application Framework.

Request Syntax

```
{
  "AppVisibility": "string",
  "Attributes": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "Description": "string",
  "Name": "string",
  "StackName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppVisibility

Specifies whether all or selected apps are entitled.

Type: String

Valid Values: ALL | ASSOCIATED

Required: Yes

Attributes

The attributes of the entitlement.

Type: Array of [EntitlementAttribute](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

[Description](#)

The description of the entitlement.

Type: String

Length Constraints: Maximum length of 256.

Required: No

[Name](#)

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

[StackName](#)

The name of the stack with which the entitlement is associated.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Syntax

```
{
  "Entitlement": {
    "AppVisibility": "string",
    "Attributes": [
      {
        "Name": "string",
        "Value": "string"
      }
    ]
  }
}
```

```
    }  
  ],  
  "CreatedTime": number,  
  "Description": "string",  
  "LastModifiedTime": number,  
  "Name": "string",  
  "StackName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entitlement

The entitlement.

Type: [Entitlement](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntitlementAlreadyExistsException

The entitlement already exists.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateFleet

Creates a fleet. A fleet consists of streaming instances that your users access for their applications and desktops.

Request Syntax

```
{
  "ComputeCapacity": {
    "DesiredInstances": number,
    "DesiredSessions": number
  },
  "Description": "string",
  "DisconnectTimeoutInSeconds": number,
  "DisplayName": "string",
  "DomainJoinInfo": {
    "DirectoryName": "string",
    "OrganizationalUnitDistinguishedName": "string"
  },
  "EnableDefaultInternetAccess": boolean,
  "FleetType": "string",
  "IamRoleArn": "string",
  "IdleDisconnectTimeoutInSeconds": number,
  "ImageArn": "string",
  "ImageName": "string",
  "InstanceType": "string",
  "MaxConcurrentSessions": number,
  "MaxSessionsPerInstance": number,
  "MaxUserDurationInSeconds": number,
  "Name": "string",
  "Platform": "string",
  "SessionScriptS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "StreamView": "string",
  "Tags": {
    "string" : "string"
  },
  "UsbDeviceFilterStrings": [ "string" ],
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}
```

```
}  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ComputeCapacity](#)

The desired capacity for the fleet. This is not allowed for Elastic fleets. For Elastic fleets, specify MaxConcurrentSessions instead.

Type: [ComputeCapacity](#) object

Required: No

[Description](#)

The description to display.

Type: String

Length Constraints: Maximum length of 256.

Required: No

[DisconnectTimeoutInSeconds](#)

The amount of time that a streaming session remains active after users disconnect. If users try to reconnect to the streaming session after a disconnection or network interruption within this time interval, they are connected to their previous session. Otherwise, they are connected to a new session with a new streaming instance.

Specify a value between 60 and 36000.

Type: Integer

Required: No

[DisplayName](#)

The fleet name to display.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DomainJoinInfo

The name of the directory and organizational unit (OU) to use to join the fleet to a Microsoft Active Directory domain. This is not allowed for Elastic fleets.

Type: [DomainJoinInfo](#) object

Required: No

EnableDefaultInternetAccess

Enables or disables default internet access for the fleet.

Type: Boolean

Required: No

FleetType

The fleet type.

ALWAYS_ON

Provides users with instant-on access to their apps. You are charged for all running instances in your fleet, even if no users are streaming apps.

ON_DEMAND

Provide users with access to applications after they connect, which takes one to two minutes. You are charged for instance streaming when users are connected and a small hourly fee for instances that are not streaming apps.

Type: String

Valid Values: ALWAYS_ON | ON_DEMAND | ELASTIC

Required: No

IamRoleArn

The Amazon Resource Name (ARN) of the IAM role to apply to the fleet. To assume a role, a fleet instance calls the AWS Security Token Service (STS) AssumeRole API operation and passes the ARN of the role to use. The operation creates a new session with temporary credentials.

AppStream 2.0 retrieves the temporary credentials and creates the **appstream_machine_role** credential profile on the instance.

For more information, see [Using an IAM Role to Grant Permissions to Applications and Scripts Running on AppStream 2.0 Streaming Instances](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: No

IdleDisconnectTimeoutInSeconds

The amount of time that users can be idle (inactive) before they are disconnected from their streaming session and the `DisconnectTimeoutInSeconds` time interval begins. Users are notified before they are disconnected due to inactivity. If they try to reconnect to the streaming session before the time interval specified in `DisconnectTimeoutInSeconds` elapses, they are connected to their previous session. Users are considered idle when they stop providing keyboard or mouse input during their streaming session. File uploads and downloads, audio in, audio out, and pixels changing do not qualify as user activity. If users continue to be idle after the time interval in `IdleDisconnectTimeoutInSeconds` elapses, they are disconnected.

To prevent users from being disconnected due to inactivity, specify a value of 0. Otherwise, specify a value between 60 and 36000. The default value is 0.

Note

If you enable this feature, we recommend that you specify a value that corresponds exactly to a whole number of minutes (for example, 60, 120, and 180). If you don't do this, the value is rounded to the nearest minute. For example, if you specify a value of 70, users are disconnected after 1 minute of inactivity. If you specify a value that is at the midpoint between two different minutes, the value is rounded up. For example, if you specify a value of 90, users are disconnected after 2 minutes of inactivity.

Type: Integer

Required: No

ImageArn

The ARN of the public, private, or shared image to use.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/_+=, @.\s-]{0,1023}$`

Required: No

ImageName

The name of the image used to create the fleet.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: No

InstanceType

The instance type to use when launching fleet instances. The following instance types are available:

- stream.standard.small
- stream.standard.medium
- stream.standard.large
- stream.standard.xlarge
- stream.standard.2xlarge
- stream.compute.large
- stream.compute.xlarge
- stream.compute.2xlarge
- stream.compute.4xlarge
- stream.compute.8xlarge
- stream.memory.large

- `stream.memory.xlarge`
- `stream.memory.2xlarge`
- `stream.memory.4xlarge`
- `stream.memory.8xlarge`
- `stream.memory.z1d.large`
- `stream.memory.z1d.xlarge`
- `stream.memory.z1d.2xlarge`
- `stream.memory.z1d.3xlarge`
- `stream.memory.z1d.6xlarge`
- `stream.memory.z1d.12xlarge`
- `stream.graphics-design.large`
- `stream.graphics-design.xlarge`
- `stream.graphics-design.2xlarge`
- `stream.graphics-design.4xlarge`
- `stream.graphics-desktop.2xlarge`
- `stream.graphics.g4dn.xlarge`
- `stream.graphics.g4dn.2xlarge`
- `stream.graphics.g4dn.4xlarge`
- `stream.graphics.g4dn.8xlarge`
- `stream.graphics.g4dn.12xlarge`
- `stream.graphics.g4dn.16xlarge`
- `stream.graphics.g5.xlarge`
- `stream.graphics.g5.2xlarge`
- `stream.graphics.g5.4xlarge`
- `stream.graphics.g5.8xlarge`
- `stream.graphics.g5.12xlarge`
- `stream.graphics.g5.16xlarge`
- `stream.graphics.g5.24xlarge`
- `stream.graphics-pro.4xlarge`
- `stream.graphics-pro.8xlarge`

- `stream.graphics-pro.16xlarge`
- `stream.graphics.g6.xlarge`
- `stream.graphics.g6.2xlarge`
- `stream.graphics.g6.4xlarge`
- `stream.graphics.g6.8xlarge`
- `stream.graphics.g6.16xlarge`
- `stream.graphics.g6.12xlarge`
- `stream.graphics.g6.24xlarge`
- `stream.graphics.gr6.4xlarge`
- `stream.graphics.gr6.8xlarge`

The following instance types are available for Elastic fleets:

- `stream.standard.small`
- `stream.standard.medium`
- `stream.standard.large`
- `stream.standard.xlarge`
- `stream.standard.2xlarge`

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

MaxConcurrentSessions

The maximum concurrent sessions of the Elastic fleet. This is required for Elastic fleets, and not allowed for other fleet types.

Type: Integer

Required: No

MaxSessionsPerInstance

The maximum number of user sessions on an instance. This only applies to multi-session fleets.

Type: Integer

Required: No

MaxUserDurationInSeconds

The maximum amount of time that a streaming session can remain active, in seconds. If users are still connected to a streaming instance five minutes before this limit is reached, they are prompted to save any open documents before being disconnected. After this time elapses, the instance is terminated and replaced by a new instance.

Specify a value between 600 and 432000.

Type: Integer

Required: No

Name

A unique name for the fleet.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Platform

The fleet platform. WINDOWS_SERVER_2019 and AMAZON_LINUX2 are supported for Elastic fleets.

Type: String

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 | WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: No

SessionScriptS3Location

The S3 location of the session scripts configuration zip file. This only applies to Elastic fleets.

Type: [S3Location](#) object

Required: No

StreamView

The AppStream 2.0 view that is displayed to your users when they stream from the fleet. When APP is specified, only the windows of applications opened by users display. When DESKTOP is specified, the standard desktop that is provided by the operating system displays.

The default value is APP.

Type: String

Valid Values: APP | DESKTOP

Required: No

Tags

The tags to associate with the fleet. A tag is a key-value pair, and the value is optional. For example, Environment=Test. If you do not specify a value, Environment=.

If you do not specify a value, the value is set to an empty string.

Generally allowed characters are: letters, numbers, and spaces representable in UTF-8, and the following special characters:

`_ . : / = + \ - @`

For more information, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(!aws:)\p{L}\p{Z}\p{N}_./=+\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^( [\p{L}\p{Z}\p{N}_./=+\-@]*)$`

Required: No

UsbDeviceFilterStrings

The USB device filter strings that specify which USB devices a user can redirect to the fleet streaming session, when using the Windows native client. This is allowed but not required for Elastic fleets.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `^((\\w*)\\s*(\\w*)\\s*\\,\\s*(\\w*)\\s*\\,\\s*\\*?(\\w*)\\s*\\,\\s*\\*?(\\w*)\\s*\\,\\s*\\*?\\d*\\s*\\,\\s*\\*?\\d*\\s*\\,\\s*[0-1]\\s*\\,\\s*[0-1]\\s*)$`

Required: No

VpcConfig

The VPC configuration for the fleet. This is required for Elastic fleets, but not required for other fleet types. Elastic fleets require that you specify at least two subnets in different availability zones.

Type: [VpcConfig](#) object

Required: No

Response Syntax

```
{
  "Fleet": {
    "Arn": "string",
    "ComputeCapacityStatus": {
      "ActiveUserSessions": number,
      "ActualUserSessions": number,
      "Available": number,
      "AvailableUserSessions": number,
      "Desired": number,
      "DesiredUserSessions": number,
      "InUse": number,
      "Running": number
    },
    "CreatedTime": number,
    "Description": "string",
```

```

    "DisconnectTimeoutInSeconds": number,
    "DisplayName": "string",
    "DomainJoinInfo": {
        "DirectoryName": "string",
        "OrganizationalUnitDistinguishedName": "string"
    },
    "EnableDefaultInternetAccess": boolean,
    "FleetErrors": [
        {
            "ErrorCode": "string",
            "ErrorMessage": "string"
        }
    ],
    "FleetType": "string",
    "IamRoleArn": "string",
    "IdleDisconnectTimeoutInSeconds": number,
    "ImageArn": "string",
    "ImageName": "string",
    "InstanceType": "string",
    "MaxConcurrentSessions": number,
    "MaxSessionsPerInstance": number,
    "MaxUserDurationInSeconds": number,
    "Name": "string",
    "Platform": "string",
    "SessionScriptS3Location": {
        "S3Bucket": "string",
        "S3Key": "string"
    },
    "State": "string",
    "StreamView": "string",
    "UsbDeviceFilterStrings": [ "string" ],
    "VpcConfig": {
        "SecurityGroupIds": [ "string" ],
        "SubnetIds": [ "string" ]
    }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Fleet

Information about the fleet.

Type: [Fleet](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

RequestLimitExceededException

AppStream 2.0 can't process the request right now because the Describe calls from your AWS account are being throttled by Amazon EC2. Try again later.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateImageBuilder

Creates an image builder. An image builder is a virtual machine that is used to create an image.

The initial state of the builder is PENDING. When it is ready, the state is RUNNING.

Request Syntax

```
{
  "AccessEndpoints": [
    {
      "EndpointType": "string",
      "VpceId": "string"
    }
  ],
  "AppstreamAgentVersion": "string",
  "Description": "string",
  "DisplayName": "string",
  "DomainJoinInfo": {
    "DirectoryName": "string",
    "OrganizationalUnitDistinguishedName": "string"
  },
  "EnableDefaultInternetAccess": boolean,
  "IamRoleArn": "string",
  "ImageArn": "string",
  "ImageName": "string",
  "InstanceType": "string",
  "Name": "string",
  "Tags": {
    "string" : "string"
  },
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AccessEndpoints

The list of interface VPC endpoint (interface endpoint) objects. Administrators can connect to the image builder only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

AppstreamAgentVersion

The version of the AppStream 2.0 agent to use for this image builder. To use the latest version of the AppStream 2.0 agent, specify [LATEST].

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

Description

The description to display.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

The image builder name to display.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DomainJoinInfo

The name of the directory and organizational unit (OU) to use to join the image builder to a Microsoft Active Directory domain.

Type: [DomainJoinInfo](#) object

Required: No

[EnableDefaultInternetAccess](#)

Enables or disables default internet access for the image builder.

Type: Boolean

Required: No

[IamRoleArn](#)

The Amazon Resource Name (ARN) of the IAM role to apply to the image builder. To assume a role, the image builder calls the AWS Security Token Service (STS) AssumeRole API operation and passes the ARN of the role to use. The operation creates a new session with temporary credentials. AppStream 2.0 retrieves the temporary credentials and creates the **appstream_machine_role** credential profile on the instance.

For more information, see [Using an IAM Role to Grant Permissions to Applications and Scripts Running on AppStream 2.0 Streaming Instances](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: No

[ImageArn](#)

The ARN of the public, private, or shared image to use.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: No

ImageName

The name of the image used to create the image builder.

Type: String

Length Constraints: Minimum length of 1.

Required: No

InstanceType

The instance type to use when launching the image builder. The following instance types are available:

- stream.standard.small
- stream.standard.medium
- stream.standard.large
- stream.compute.large
- stream.compute.xlarge
- stream.compute.2xlarge
- stream.compute.4xlarge
- stream.compute.8xlarge
- stream.memory.large
- stream.memory.xlarge
- stream.memory.2xlarge
- stream.memory.4xlarge
- stream.memory.8xlarge
- stream.memory.z1d.large
- stream.memory.z1d.xlarge
- stream.memory.z1d.2xlarge
- stream.memory.z1d.3xlarge
- stream.memory.z1d.6xlarge
- stream.memory.z1d.12xlarge

- `stream.graphics-design.large`
- `stream.graphics-design.xlarge`
- `stream.graphics-design.2xlarge`
- `stream.graphics-design.4xlarge`
- `stream.graphics-desktop.2xlarge`
- `stream.graphics.g4dn.xlarge`
- `stream.graphics.g4dn.2xlarge`
- `stream.graphics.g4dn.4xlarge`
- `stream.graphics.g4dn.8xlarge`
- `stream.graphics.g4dn.12xlarge`
- `stream.graphics.g4dn.16xlarge`
- `stream.graphics-pro.4xlarge`
- `stream.graphics-pro.8xlarge`
- `stream.graphics-pro.16xlarge`
- `stream.graphics.g5.xlarge`
- `stream.graphics.g5.2xlarge`
- `stream.graphics.g5.4xlarge`
- `stream.graphics.g5.8xlarge`
- `stream.graphics.g5.16xlarge`
- `stream.graphics.g5.12xlarge`
- `stream.graphics.g5.24xlarge`
- `stream.graphics.g6.xlarge`
- `stream.graphics.g6.2xlarge`
- `stream.graphics.g6.4xlarge`
- `stream.graphics.g6.8xlarge`
- `stream.graphics.g6.16xlarge`
- `stream.graphics.g6.12xlarge`
- `stream.graphics.g6.24xlarge`
- `stream.graphics.gr6.4xlarge`

- `stream.graphics.gr6.8xlarge`

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Name

A unique name for the image builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Tags

The tags to associate with the image builder. A tag is a key-value pair, and the value is optional. For example, `Environment=Test`. If you do not specify a value, `Environment=`.

Generally allowed characters are: letters, numbers, and spaces representable in UTF-8, and the following special characters:

`_ . : / = + \ - @`

If you do not specify a value, the value is set to an empty string.

For more information about tags, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(?!aws:)\p{L}\p{Z}\p{N}_./=+\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^( [\p{L}\p{Z}\p{N}_./=+\-@]*)$`

Required: No

VpcConfig

The VPC configuration for the image builder. You can specify only one subnet.

Type: VpcConfig object

Required: No

Response Syntax

```
{
  "ImageBuilder": {
    "AccessEndpoints": [
      {
        "EndpointType": "string",
        "VpceId": "string"
      }
    ],
    "AppstreamAgentVersion": "string",
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "DomainJoinInfo": {
      "DirectoryName": "string",
      "OrganizationalUnitDistinguishedName": "string"
    },
    "EnableDefaultInternetAccess": boolean,
    "IamRoleArn": "string",
    "ImageArn": "string",
    "ImageBuilderErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
      }
    ],
    "InstanceType": "string",
    "LatestAppstreamAgentVersion": "string",
    "Name": "string",
    "NetworkAccessConfiguration": {
```

```
    "EniId": "string",
    "EniPrivateIpAddress": "string"
  },
  "Platform": "string",
  "State": "string",
  "StateChangeReason": {
    "Code": "string",
    "Message": "string"
  },
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageBuilder

Information about the image builder.

Type: [ImageBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

RequestLimitExceededException

AppStream 2.0 can't process the request right now because the Describe calls from your AWS account are being throttled by Amazon EC2. Try again later.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateImageBuilderStreamingURL

Creates a URL to start an image builder streaming session.

Request Syntax

```
{  
  "Name": "string",  
  "Validity": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the image builder.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Validity

The time that the streaming URL will be valid, in seconds. Specify a value between 1 and 604800 seconds. The default is 3600 seconds.

Type: Long

Required: No

Response Syntax

```
{  
  "Expires": number,  
  "StreamingURL": "string"  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Expires

The elapsed time, in seconds after the Unix epoch, when this URL expires.

Type: Timestamp

StreamingURL

The URL to start the AppStream 2.0 streaming session.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateStack

Creates a stack to start streaming applications to users. A stack consists of an associated fleet, user access policies, and storage configurations.

Request Syntax

```
{
  "AccessEndpoints": [
    {
      "EndpointType": "string",
      "VpceId": "string"
    }
  ],
  "ApplicationSettings": {
    "Enabled": boolean,
    "SettingsGroup": "string"
  },
  "Description": "string",
  "DisplayName": "string",
  "EmbedHostDomains": [ "string" ],
  "FeedbackURL": "string",
  "Name": "string",
  "RedirectURL": "string",
  "StorageConnectors": [
    {
      "ConnectorType": "string",
      "Domains": [ "string" ],
      "DomainsRequireAdminConsent": [ "string" ],
      "ResourceIdentifier": "string"
    }
  ],
  "StreamingExperienceSettings": {
    "PreferredProtocol": "string"
  },
  "Tags": {
    "string" : "string"
  },
  "UserSettings": [
    {
      "Action": "string",
      "MaximumLength": number,
      "Permission": "string"
    }
  ]
}
```

```
}  
]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AccessEndpoints](#)

The list of interface VPC endpoint (interface endpoint) objects. Users of the stack can connect to AppStream 2.0 only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

[ApplicationSettings](#)

The persistent application settings for users of a stack. When these settings are enabled, changes that users make to applications and Windows settings are automatically saved after each session and applied to the next session.

Type: [ApplicationSettings](#) object

Required: No

[Description](#)

The description to display.

Type: String

Length Constraints: Maximum length of 256.

Required: No

[DisplayName](#)

The stack name to display.

Type: String

Length Constraints: Maximum length of 100.

Required: No

EmbedHostDomains

The domains where AppStream 2.0 streaming sessions can be embedded in an iframe. You must approve the domains that you want to host embedded AppStream 2.0 streaming sessions.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Maximum length of 128.

Pattern: `(?:[a-z0-9](?:[a-z0-9-]{0,61}[a-z0-9])?\.\.)+[a-z0-9][a-z0-9-]{0,61}[a-z0-9]`

Required: No

FeedbackURL

The URL that users are redirected to after they click the Send Feedback link. If no URL is specified, no Send Feedback link is displayed.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

Name

The name of the stack.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

RedirectURL

The URL that users are redirected to after their streaming session ends.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

StorageConnectors

The storage connectors to enable.

Type: Array of [StorageConnector](#) objects

Required: No

StreamingExperienceSettings

The streaming protocol you want your stack to prefer. This can be UDP or TCP. Currently, UDP is only supported in the Windows native client.

Type: [StreamingExperienceSettings](#) object

Required: No

Tags

The tags to associate with the stack. A tag is a key-value pair, and the value is optional. For example, Environment=Test. If you do not specify a value, Environment=.

If you do not specify a value, the value is set to an empty string.

Generally allowed characters are: letters, numbers, and spaces representable in UTF-8, and the following special characters:

`_ . : / = + \ - @`

For more information about tags, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(?!aws:).[\p{L}\p{Z}\p{N}_.: / = + \ - @]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^([\p{L}\p{Z}\p{N}_.: /+=\ -@]*)$`

Required: No

UserSettings

The actions that are enabled or disabled for users during their streaming sessions. By default, these actions are enabled.

Type: Array of [UserSetting](#) objects

Array Members: Minimum number of 1 item.

Required: No

Response Syntax

```
{
  "Stack": {
    "AccessEndpoints": [
      {
        "EndpointType": "string",
        "VpceId": "string"
      }
    ],
    "ApplicationSettings": {
      "Enabled": boolean,
      "S3BucketName": "string",
      "SettingsGroup": "string"
    },
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "EmbedHostDomains": [ "string" ],
    "FeedbackURL": "string",
    "Name": "string",
    "RedirectURL": "string",
    "StackErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string"
      }
    ]
  }
}
```

```
    ],  
    "StorageConnectors": [  
      {  
        "ConnectorType": "string",  
        "Domains": [ "string" ],  
        "DomainsRequireAdminConsent": [ "string" ],  
        "ResourceIdentifier": "string"  
      }  
    ],  
    "StreamingExperienceSettings": {  
      "PreferredProtocol": "string"  
    },  
    "UserSettings": [  
      {  
        "Action": "string",  
        "MaxLength": number,  
        "Permission": "string"  
      }  
    ]  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Stack

Information about the stack.

Type: [Stack](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateStreamingURL

Creates a temporary URL to start an AppStream 2.0 streaming session for the specified user. A streaming URL enables application streaming to be tested without user setup.

Request Syntax

```
{  
  "ApplicationId": "string",  
  "FleetName": "string",  
  "SessionContext": "string",  
  "StackName": "string",  
  "UserId": "string",  
  "Validity": number  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationId

The name of the application to launch after the session starts. This is the name that you specified as **Name** in the Image Assistant. If your fleet is enabled for the **Desktop** stream view, you can also choose to launch directly to the operating system desktop. To do so, specify **Desktop**.

Type: String

Length Constraints: Minimum length of 1.

Required: No

FleetName

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

SessionContext

The session context. For more information, see [Session Context](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Length Constraints: Minimum length of 1.

Required: No

StackName

The name of the stack.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

UserId

The identifier of the user.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 32.

Pattern: `[\w+=, .@-]*`

Required: Yes

Validity

The time that the streaming URL will be valid, in seconds. Specify a value between 1 and 604800 seconds. The default is 60 seconds.

Type: Long

Required: No

Response Syntax

```
{  
  "Expires": number,  
  "StreamingURL": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Expires](#)

The elapsed time, in seconds after the Unix epoch, when this URL expires.

Type: Timestamp

[StreamingURL](#)

The URL to start the AppStream 2.0 streaming session.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateThemeForStack

Creates custom branding that customizes the appearance of the streaming application catalog page.

Request Syntax

```
{
  "FaviconS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "FooterLinks": [
    {
      "DisplayName": "string",
      "FooterLinkURL": "string"
    }
  ],
  "OrganizationLogoS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "StackName": "string",
  "ThemeStyling": "string",
  "TitleText": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

FaviconS3Location

The S3 location of the favicon. The favicon enables users to recognize their application streaming site in a browser full of tabs or bookmarks. It is displayed at the top of the browser tab for the application streaming site during users' streaming sessions.

Type: [S3Location](#) object

Required: Yes

FooterLinks

The links that are displayed in the footer of the streaming application catalog page. These links are helpful resources for users, such as the organization's IT support and product marketing sites.

Type: Array of [ThemeFooterLink](#) objects

Required: No

OrganizationLogoS3Location

The organization logo that appears on the streaming application catalog page.

Type: [S3Location](#) object

Required: Yes

StackName

The name of the stack for the theme.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

ThemeStyling

The color theme that is applied to website links, text, and buttons. These colors are also applied as accents in the background for the streaming application catalog page.

Type: String

Valid Values: LIGHT_BLUE | BLUE | PINK | RED

Required: Yes

TitleText

The title that is displayed at the top of the browser tab during users' application streaming sessions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `^[-@./#&+\w\s]*$`

Required: Yes

Response Syntax

```
{
  "Theme": {
    "CreatedTime": number,
    "StackName": "string",
    "State": "string",
    "ThemeFaviconURL": "string",
    "ThemeFooterLinks": [
      {
        "DisplayName": "string",
        "FooterLinkURL": "string"
      }
    ],
    "ThemeOrganizationLogoURL": "string",
    "ThemeStyling": "string",
    "ThemeTitleText": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Theme

The theme object that contains the metadata of the custom branding.

Type: [Theme](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUpdatedImage

Creates a new image with the latest Windows operating system updates, driver updates, and AppStream 2.0 agent software.

For more information, see the "Update an Image by Using Managed AppStream 2.0 Image Updates" section in [Administer Your AppStream 2.0 Images](#), in the *Amazon AppStream 2.0 Administration Guide*.

Request Syntax

```
{
  "dryRun": boolean,
  "existingImageName": "string",
  "newImageDescription": "string",
  "newImageDisplayName": "string",
  "newImageName": "string",
  "newImageTags": {
    "string" : "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

dryRun

Indicates whether to display the status of image update availability before AppStream 2.0 initiates the process of creating a new updated image. If this value is set to `true`, AppStream 2.0 displays whether image updates are available. If this value is set to `false`, AppStream 2.0 initiates the process of creating a new updated image without displaying whether image updates are available.

Type: Boolean

Required: No

existingImageName

The name of the image to update.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

newImageDescription

The description to display for the new image.

Type: String

Length Constraints: Maximum length of 256.

Required: No

newImageDisplayName

The name to display for the new image.

Type: String

Length Constraints: Maximum length of 100.

Required: No

newImageName

The name of the new image. The name must be unique within the AWS account and Region.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

newImageTags

The tags to associate with the new image. A tag is a key-value pair, and the value is optional. For example, Environment=Test. If you do not specify a value, Environment=.

Generally allowed characters are: letters, numbers, and spaces representable in UTF-8, and the following special characters:

`_ . : / = + \ - @`

If you do not specify a value, the value is set to an empty string.

For more information about tags, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(!aws:)\p{L}\p{Z}\p{N}_:/=+\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^( [\p{L}\p{Z}\p{N}_:/=+\-@]*)$`

Required: No

Response Syntax

```
{
  "canUpdateImage": boolean,
  "image": {
    "Applications": [
      {
        "AppBlockArn": "string",
        "Arn": "string",
        "CreatedTime": number,
        "Description": "string",
        "DisplayName": "string",
        "Enabled": boolean,
        "IconS3Location": {
          "S3Bucket": "string",
          "S3Key": "string"
        },
        "IconURL": "string",
        "InstanceFamilies": [ "string" ],
        "LaunchParameters": "string",
        "LaunchPath": "string",
        "Metadata": {
          "string" : "string"
        },
      },
    ],
  },
}
```

```

        "Name": "string",
        "Platforms": [ "string" ],
        "WorkingDirectory": "string"
    }
],
"AppstreamAgentVersion": "string",
"Arn": "string",
"BaseImageArn": "string",
"CreatedTime": number,
"Description": "string",
"DisplayName": "string",
"DynamicAppProvidersEnabled": "string",
"ImageBuilderName": "string",
"ImageBuilderSupported": boolean,
"ImageErrors": [
    {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
    }
],
"ImagePermissions": {
    "allowFleet": boolean,
    "allowImageBuilder": boolean
},
"ImageSharedWithOthers": "string",
"LatestAppstreamAgentVersion": "string",
"Name": "string",
"Platform": "string",
"PublicBaseImageReleasedDate": number,
"State": "string",
"StateChangeReason": {
    "Code": "string",
    "Message": "string"
},
"SupportedInstanceFamilies": [ "string" ],
"Visibility": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

canUpdateImage

Indicates whether a new image can be created.

Type: Boolean

image

Describes an image.

Type: [Image](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUsageReportSubscription

Creates a usage report subscription. Usage reports are generated daily.

Response Syntax

```
{
  "S3BucketName": "string",
  "Schedule": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[S3BucketName](#)

The Amazon S3 bucket where generated reports are stored.

If you enabled on-instance session scripts and Amazon S3 logging for your session script configuration, AppStream 2.0 created an S3 bucket to store the script output. The bucket is unique to your account and Region. When you enable usage reporting in this case, AppStream 2.0 uses the same bucket to store your usage reports. If you haven't already enabled on-instance session scripts, when you enable usage reports, AppStream 2.0 creates a new S3 bucket.

Type: String

Length Constraints: Minimum length of 1.

[Schedule](#)

The schedule for generating usage reports.

Type: String

Valid Values: DAILY

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUser

Creates a new user in the user pool.

Request Syntax

```
{  
  "AuthenticationType": "string",  
  "FirstName": "string",  
  "LastName": "string",  
  "MessageAction": "string",  
  "UserName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AuthenticationType

The authentication type for the user. You must specify USERPOOL.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: Yes

FirstName

The first name, or given name, of the user.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[A-Za-z0-9_\-\\s]+$`

Required: No

LastName

The last name, or surname, of the user.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[A-Za-z0-9_\-\\s]+$`

Required: No

MessageAction

The action to take for the welcome email that is sent to a user after the user is created in the user pool. If you specify `SUPPRESS`, no email is sent. If you specify `RESEND`, do not specify the first name or last name of the user. If the value is null, the email is sent.

Note

The temporary password in the welcome email is valid for only 7 days. If users don't set their passwords within 7 days, you must send them a new welcome email.

Type: String

Valid Values: `SUPPRESS` | `RESEND`

Required: No

UserName

The email address of the user.

Note

Users' email addresses are case-sensitive. During login, if they specify an email address that doesn't use the same capitalization as the email address specified when their user pool account was created, a "user does not exist" error message displays.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{M}\p{S}\p{N}\p{P}]`+

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceAlreadyExistsException

The specified resource already exists.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAppBlock

Deletes an app block.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the app block.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAppBlockBuilder

Deletes an app block builder.

An app block builder can only be deleted when it has no association with an app block.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteApplication

Deletes an application.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the application.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDirectoryConfig

Deletes the specified Directory Config object from AppStream 2.0. This object includes the information required to join streaming instances to an Active Directory domain.

Request Syntax

```
{  
  "DirectoryName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DirectoryName

The name of the directory configuration.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEntitlement

Deletes the specified entitlement.

Request Syntax

```
{  
  "Name": "string",  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

StackName

The name of the stack with which the entitlement is associated.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

EntitlementNotFoundException

The entitlement can't be found.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteFleet

Deletes the specified fleet.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteImage

Deletes the specified image. You cannot delete an image when it is in use. After you delete an image, you cannot provision new capacity using the image.

Request Syntax

```
{
  "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the image.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Syntax

```
{
  "Image": {
    "Applications": [
      {
        "AppBlockArn": "string",
        "Arn": "string",
        "CreatedTime": number,
        "Description": "string",
        "DisplayName": "string",
        "Enabled": boolean,
        "IconS3Location": {
          "S3Bucket": "string",
          "S3Key": "string"
        }
      }
    ]
  }
}
```

```

    },
    "IconURL": "string",
    "InstanceFamilies": [ "string" ],
    "LaunchParameters": "string",
    "LaunchPath": "string",
    "Metadata": {
        "string" : "string"
    },
    "Name": "string",
    "Platforms": [ "string" ],
    "WorkingDirectory": "string"
}
],
"AppstreamAgentVersion": "string",
"Arn": "string",
"BaseImageArn": "string",
"CreatedTime": number,
"Description": "string",
"DisplayName": "string",
"DynamicAppProvidersEnabled": "string",
"ImageBuilderName": "string",
"ImageBuilderSupported": boolean,
"ImageErrors": [
    {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
    }
],
"ImagePermissions": {
    "allowFleet": boolean,
    "allowImageBuilder": boolean
},
"ImageSharedWithOthers": "string",
"LatestAppstreamAgentVersion": "string",
"Name": "string",
"Platform": "string",
"PublicBaseImageReleasedDate": number,
"State": "string",
"StateChangeReason": {
    "Code": "string",
    "Message": "string"
},
"SupportedInstanceFamilies": [ "string" ],

```

```
    "Visibility": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Image

Information about the image.

Type: Image object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteImageBuilder

Deletes the specified image builder and releases the capacity.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the image builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Syntax

```
{  
  "ImageBuilder": {  
    "AccessEndpoints": [  
      {  
        "EndpointType": "string",  
        "VpceId": "string"  
      }  
    ],  
    "AppstreamAgentVersion": "string",  
    "Arn": "string",  
    "CreatedTime": number,  
    "Description": "string",  
    "DisplayName": "string",
```

```

    "DomainJoinInfo": {
      "DirectoryName": "string",
      "OrganizationalUnitDistinguishedName": "string"
    },
    "EnableDefaultInternetAccess": boolean,
    "IamRoleArn": "string",
    "ImageArn": "string",
    "ImageBuilderErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
      }
    ],
    "InstanceType": "string",
    "LatestAppstreamAgentVersion": "string",
    "Name": "string",
    "NetworkAccessConfiguration": {
      "EniId": "string",
      "EniPrivateIpAddress": "string"
    },
    "Platform": "string",
    "State": "string",
    "StateChangeReason": {
      "Code": "string",
      "Message": "string"
    },
    "VpcConfig": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
    }
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageBuilder

Information about the image builder.

Type: [ImageBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteImagePermissions

Deletes permissions for the specified private image. After you delete permissions for an image, AWS accounts to which you previously granted these permissions can no longer use the image.

Request Syntax

```
{  
  "Name": "string",  
  "SharedAccountId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the private image.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

SharedAccountId

The 12-digit identifier of the AWS account for which to delete image permissions.

Type: String

Pattern: `^\d+$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteStack

Deletes the specified stack. After the stack is deleted, the application streaming environment provided by the stack is no longer available to users. Also, any reservations made for application streaming sessions for the stack are released.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the stack.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteThemeForStack

Deletes custom branding that customizes the appearance of the streaming application catalog page.

Request Syntax

```
{  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

StackName

The name of the stack for the theme.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteUsageReportSubscription

Disables usage report generation.

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteUser

Deletes a user from the user pool.

Request Syntax

```
{  
  "AuthenticationType": "string",  
  "UserName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AuthenticationType](#)

The authentication type for the user. You must specify USERPOOL.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: Yes

[UserName](#)

The email address of the user.

Note

Users' email addresses are case-sensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{M}\p{S}\p{N}\p{P}]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAppBlockBuilderAppBlockAssociations

Retrieves a list that describes one or more app block builder associations.

Request Syntax

```
{  
  "AppBlockArn": "string",  
  "AppBlockBuilderName": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppBlockArn

The ARN of the app block.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_+=, @.\-]{0,1023}$`

Required: No

AppBlockBuilderName

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: No

MaxResults

The maximum size of each page of results.

Type: Integer

Required: No

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "AppBlockBuilderAppBlockAssociations": [
    {
      "AppBlockArn": "string",
      "AppBlockBuilderName": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppBlockBuilderAppBlockAssociations

This list of app block builders associated with app blocks.

Type: Array of [AppBlockBuilderAppBlockAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAppBlockBuilders

Retrieves a list that describes one or more app block builders.

Request Syntax

```
{  
  "MaxResults": number,  
  "Names": [ "string" ],  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum size of each page of results. The maximum value is 25.

Type: Integer

Required: No

[Names](#)

The names of the app block builders.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: No

[NextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "AppBlockBuilders": [
    {
      "AccessEndpoints": [
        {
          "EndpointType": "string",
          "VpceId": "string"
        }
      ],
      "AppBlockBuilderErrors": [
        {
          "ErrorCode": "string",
          "ErrorMessage": "string",
          "ErrorTimestamp": number
        }
      ],
      "Arn": "string",
      "CreatedTime": number,
      "Description": "string",
      "DisplayName": "string",
      "EnableDefaultInternetAccess": boolean,
      "IamRoleArn": "string",
      "InstanceType": "string",
      "Name": "string",
      "Platform": "string",
      "State": "string",
      "StateChangeReason": {
        "Code": "string",
        "Message": "string"
      },
      "VpcConfig": {
        "SecurityGroupIds": [ "string" ],
        "SubnetIds": [ "string" ]
      }
    }
  ],
  "NextToken": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AppBlockBuilders](#)

The list that describes one or more app block builders.

Type: Array of [AppBlockBuilder](#) objects

[NextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAppBlocks

Retrieves a list that describes one or more app blocks.

Request Syntax

```
{  
  "Arns": [ "string" ],  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Arns

The ARNs of the app blocks.

Type: Array of strings

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: No

MaxResults

The maximum size of each page of results.

Type: Integer

Required: No

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "AppBlocks": [
    {
      "AppBlockErrors": [
        {
          "ErrorCode": "string",
          "ErrorMessage": "string"
        }
      ],
      "Arn": "string",
      "CreatedTime": number,
      "Description": "string",
      "DisplayName": "string",
      "Name": "string",
      "PackagingType": "string",
      "PostSetupScriptDetails": {
        "ExecutableParameters": "string",
        "ExecutablePath": "string",
        "ScriptS3Location": {
          "S3Bucket": "string",
          "S3Key": "string"
        }
      },
      "TimeoutInSeconds": number
    },
    "SetupScriptDetails": {
      "ExecutableParameters": "string",
      "ExecutablePath": "string",
      "ScriptS3Location": {
        "S3Bucket": "string",
        "S3Key": "string"
      }
    },
    "TimeoutInSeconds": number
  },
  "SourceS3Location": {
    "S3Bucket": "string",
```

```
        "S3Key": "string"
      },
      "State": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppBlocks

The app blocks in the list.

Type: Array of [AppBlock](#) objects

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeApplicationFleetAssociations

Retrieves a list that describes one or more application fleet associations. Either ApplicationArn or FleetName must be specified.

Request Syntax

```
{
  "ApplicationArn": "string",
  "FleetName": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

The ARN of the application.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: No

[FleetName](#)

The name of the fleet.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: No

MaxResults

The maximum size of each page of results.

Type: Integer

Required: No

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "ApplicationFleetAssociations": [
    {
      "ApplicationArn": "string",
      "FleetName": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ApplicationFleetAssociations

The application fleet associations in the list.

Type: Array of [ApplicationFleetAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "Applications": [
    {
      "AppBlockArn": "string",
      "Arn": "string",
      "CreatedTime": number,
      "Description": "string",
      "DisplayName": "string",
      "Enabled": boolean,
      "IconS3Location": {
        "S3Bucket": "string",
        "S3Key": "string"
      },
      "IconURL": "string",
      "InstanceFamilies": [ "string" ],
      "LaunchParameters": "string",
      "LaunchPath": "string",
      "Metadata": {
        "string" : "string"
      },
      "Name": "string",
      "Platforms": [ "string" ],
      "WorkingDirectory": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Applications](#)

The applications in the list.

Type: Array of [Application](#) objects

[NextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDirectoryConfigs

Retrieves a list that describes one or more specified Directory Config objects for AppStream 2.0, if the names for these objects are provided. Otherwise, all Directory Config objects in the account are described. These objects include the configuration information required to join fleets and image builders to Microsoft Active Directory domains.

Although the response syntax in this topic includes the account password, this password is not returned in the actual response.

Request Syntax

```
{  
  "DirectoryNames": [ "string" ],  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

DirectoryNames

The directory names.

Type: Array of strings

Required: No

MaxResults

The maximum size of each page of results.

Type: Integer

Required: No

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "DirectoryConfigs": [
    {
      "CertificateBasedAuthProperties": {
        "CertificateAuthorityArn": "string",
        "Status": "string"
      },
      "CreatedTime": number,
      "DirectoryName": "string",
      "OrganizationalUnitDistinguishedNames": [ "string" ],
      "ServiceAccountCredentials": {
        "AccountName": "string",
        "AccountPassword": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DirectoryConfigs

Information about the directory configurations. Note that although the response syntax in this topic includes the account password, this password is not returned in the actual response.

Type: Array of [DirectoryConfig](#) objects

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeEntitlements

Retrieves a list that describes one or more entitlements.

Request Syntax

```
{  
  "MaxResults": number,  
  "Name": "string",  
  "NextToken": "string",  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum size of each page of results.

Type: Integer

Required: No

[Name](#)

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: No

[NextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Required: No

StackName

The name of the stack with which the entitlement is associated.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Syntax

```
{
  "Entitlements": [
    {
      "AppVisibility": "string",
      "Attributes": [
        {
          "Name": "string",
          "Value": "string"
        }
      ],
      "CreatedTime": number,
      "Description": "string",
      "LastModifiedTime": number,
      "Name": "string",
      "StackName": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entitlements

The entitlements.

Type: Array of [Entitlement](#) objects

[NextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntitlementNotFoundException

The entitlement can't be found.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)


```

{
  "Arn": "string",
  "ComputeCapacityStatus": {
    "ActiveUserSessions": number,
    "ActualUserSessions": number,
    "Available": number,
    "AvailableUserSessions": number,
    "Desired": number,
    "DesiredUserSessions": number,
    "InUse": number,
    "Running": number
  },
  "CreatedTime": number,
  "Description": "string",
  "DisconnectTimeoutInSeconds": number,
  "DisplayName": "string",
  "DomainJoinInfo": {
    "DirectoryName": "string",
    "OrganizationalUnitDistinguishedName": "string"
  },
  "EnableDefaultInternetAccess": boolean,
  "FleetErrors": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string"
    }
  ],
  "FleetType": "string",
  "IamRoleArn": "string",
  "IdleDisconnectTimeoutInSeconds": number,
  "ImageArn": "string",
  "ImageName": "string",
  "InstanceType": "string",
  "MaxConcurrentSessions": number,
  "MaxSessionsPerInstance": number,
  "MaxUserDurationInSeconds": number,
  "Name": "string",
  "Platform": "string",
  "SessionScriptS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "State": "string",
  "StreamView": "string",

```



```
    "UsbDeviceFilterStrings": [ "string" ],
    "VpcConfig": {
        "SecurityGroupIds": [ "string" ],
        "SubnetIds": [ "string" ]
    }
},
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Fleets

Information about the fleets.

Type: Array of [Fleet](#) objects

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeImageBuilders

Retrieves a list that describes one or more specified image builders, if the image builder names are provided. Otherwise, all image builders in the account are described.

Request Syntax

```
{  
  "MaxResults": number,  
  "Names": [ "string" ],  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[MaxResults](#)

The maximum size of each page of results.

Type: Integer

Required: No

[Names](#)

The names of the image builders to describe.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: No

[NextToken](#)

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "ImageBuilders": [
    {
      "AccessEndpoints": [
        {
          "EndpointType": "string",
          "VpceId": "string"
        }
      ],
      "AppstreamAgentVersion": "string",
      "Arn": "string",
      "CreatedTime": number,
      "Description": "string",
      "DisplayName": "string",
      "DomainJoinInfo": {
        "DirectoryName": "string",
        "OrganizationalUnitDistinguishedName": "string"
      },
      "EnableDefaultInternetAccess": boolean,
      "IamRoleArn": "string",
      "ImageArn": "string",
      "ImageBuilderErrors": [
        {
          "ErrorCode": "string",
          "ErrorMessage": "string",
          "ErrorTimestamp": number
        }
      ],
      "InstanceType": "string",
      "LatestAppstreamAgentVersion": "string",
      "Name": "string",
      "NetworkAccessConfiguration": {
        "EniId": "string",
        "EniPrivateIpAddress": "string"
      }
    }
  ]
}
```

```
    "Platform": "string",
    "State": "string",
    "StateChangeReason": {
      "Code": "string",
      "Message": "string"
    },
    "VpcConfig": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
    }
  },
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ImageBuilders](#)

Information about the image builders.

Type: Array of [ImageBuilder](#) objects

[NextToken](#)

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeImagePermissions

Retrieves a list that describes the permissions for shared AWS account IDs on a private image that you own.

Request Syntax

```
{
  "MaxResults": number,
  "Name": "string",
  "NextToken": "string",
  "SharedAwsAccountIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

MaxResults

The maximum size of each page of results.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 500.

Required: No

Name

The name of the private image for which to describe permissions. The image must be one that you own.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

SharedAwsAccountIds

The 12-digit identifier of one or more AWS accounts with which the image is shared.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Pattern: `^\d+$`

Required: No

Response Syntax

```
{
  "Name": "string",
  "NextToken": "string",
  "SharedImagePermissionsList": [
    {
      "imagePermissions": {
        "allowFleet": boolean,
        "allowImageBuilder": boolean
      },
      "sharedAccountId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Name

The name of the private image.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

SharedImagePermissionsList

The permissions for a private image that you own.

Type: Array of [SharedImagePermissions](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeImages

Retrieves a list that describes one or more specified images, if the image names or image ARNs are provided. Otherwise, all images in the account are described.

Request Syntax

```
{  
  "Arns": [ "string" ],  
  "MaxResults": number,  
  "Names": [ "string" ],  
  "NextToken": "string",  
  "Type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Arns

The ARNs of the public, private, and shared images to describe.

Type: Array of strings

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\s|-b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.\s-]{0,1023}$`

Required: No

MaxResults

The maximum size of each page of results.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 25.

Required: No

Names

The names of the public or private images to describe.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: No

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Type

The type of image (public, private, or shared) to describe.

Type: String

Valid Values: PUBLIC | PRIVATE | SHARED

Required: No

Response Syntax

```
{
  "Images": [
    {
      "Applications": [
        {
          "AppBlockArn": "string",
          "Arn": "string",
          "CreatedTime": number,
          "Description": "string",
          "DisplayName": "string",
          "Enabled": boolean,
          "IconS3Location": {
```

```

        "S3Bucket": "string",
        "S3Key": "string"
    },
    "IconURL": "string",
    "InstanceFamilies": [ "string" ],
    "LaunchParameters": "string",
    "LaunchPath": "string",
    "Metadata": {
        "string" : "string"
    },
    "Name": "string",
    "Platforms": [ "string" ],
    "WorkingDirectory": "string"
}
],
"AppstreamAgentVersion": "string",
"Arn": "string",
"BaseImageArn": "string",
"CreatedTime": number,
"Description": "string",
"DisplayName": "string",
"DynamicAppProvidersEnabled": "string",
"ImageBuilderName": "string",
"ImageBuilderSupported": boolean,
"ImageErrors": [
    {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
    }
],
"ImagePermissions": {
    "allowFleet": boolean,
    "allowImageBuilder": boolean
},
"ImageSharedWithOthers": "string",
"LatestAppstreamAgentVersion": "string",
"Name": "string",
"Platform": "string",
"PublicBaseImageReleasedDate": number,
"State": "string",
"StateChangeReason": {
    "Code": "string",
    "Message": "string"
}

```

```
    },  
    "SupportedInstanceFamilies": [ "string" ],  
    "Visibility": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Images

Information about the images.

Type: Array of [Image](#) objects

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeSessions

Retrieves a list that describes the streaming sessions for a specified stack and fleet. If a `UserId` is provided for the stack and fleet, only streaming sessions for that user are described. If an authentication type is not provided, the default is to authenticate users using a streaming URL.

Request Syntax

```
{  
  "AuthenticationType": "string",  
  "FleetName": "string",  
  "InstanceId": "string",  
  "Limit": number,  
  "NextToken": "string",  
  "StackName": "string",  
  "UserId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AuthenticationType

The authentication method. Specify API for a user authenticated using a streaming URL or SAML for a SAML federated user. The default is to authenticate users using a streaming URL.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: No

FleetName

The name of the fleet. This value is case-sensitive.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

InstanceId

The identifier for the instance hosting the session.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Limit

The size of each page of results. The default value is 20 and the maximum value is 50.

Type: Integer

Required: No

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

StackName

The name of the stack. This value is case-sensitive.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

UserId

The user identifier (ID). If you specify a user ID, you must also specify the authentication type.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "Sessions": [
    {
      "AuthenticationType": "string",
      "ConnectionState": "string",
      "FleetName": "string",
      "Id": "string",
      "InstanceId": "string",
      "MaxExpirationTime": number,
      "NetworkAccessConfiguration": {
        "EniId": "string",
        "EniPrivateIpAddress": "string"
      },
      "StackName": "string",
      "StartTime": number,
      "State": "string",
      "UserId": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

[Sessions](#)

Information about the streaming sessions.

Type: Array of [Session](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeStacks

Retrieves a list that describes one or more specified stacks, if the stack names are provided. Otherwise, all stacks in the account are described.

Request Syntax

```
{  
  "Names": [ "string" ],  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Names

The names of the stacks to describe.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: No

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{  
  "NextToken": "string",  
}
```

```
"Stacks": [
  {
    "AccessEndpoints": [
      {
        "EndpointType": "string",
        "VpceId": "string"
      }
    ],
    "ApplicationSettings": {
      "Enabled": boolean,
      "S3BucketName": "string",
      "SettingsGroup": "string"
    },
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "EmbedHostDomains": [ "string" ],
    "FeedbackURL": "string",
    "Name": "string",
    "RedirectURL": "string",
    "StackErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string"
      }
    ],
    "StorageConnectors": [
      {
        "ConnectorType": "string",
        "Domains": [ "string" ],
        "DomainsRequireAdminConsent": [ "string" ],
        "ResourceIdentifier": "string"
      }
    ],
    "StreamingExperienceSettings": {
      "PreferredProtocol": "string"
    },
    "UserSettings": [
      {
        "Action": "string",
        "MaxLength": number,
        "Permission": "string"
      }
    ]
  }
]
```

```
    ]  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Stacks

Information about the stacks.

Type: Array of [Stack](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeThemeForStack

Retrieves a list that describes the theme for a specified stack. A theme is custom branding that customizes the appearance of the streaming application catalog page.

Request Syntax

```
{  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

StackName

The name of the stack for the theme.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Syntax

```
{  
  "Theme": {  
    "CreatedTime": number,  
    "StackName": "string",  
    "State": "string",  
    "ThemeFaviconURL": "string",  
    "ThemeFooterLinks": [  
      {  
        "DisplayName": "string",  
        "FooterLinkURL": "string"  
      }  
    ]  
  }  
}
```



```
    ],  
    "ThemeOrganizationLogoURL": "string",  
    "ThemeStyling": "string",  
    "ThemeTitleText": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Theme

The theme object that contains the metadata of the custom branding.

Type: [Theme](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)


```
{
  "LastGeneratedReportDate": number,
  "S3BucketName": "string",
  "Schedule": "string",
  "SubscriptionErrors": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

UsageReportSubscriptions

Information about the usage report subscription.

Type: Array of [UsageReportSubscription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeUsers

Retrieves a list that describes one or more specified users in the user pool.

Request Syntax

```
{
  "AuthenticationType": "string",
  "MaxResults": number,
  "NextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AuthenticationType

The authentication type for the users in the user pool to describe. You must specify USERPOOL.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: Yes

MaxResults

The maximum size of each page of results.

Type: Integer

Required: No

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "NextToken": "string",
  "Users": [
    {
      "Arn": "string",
      "AuthenticationType": "string",
      "CreatedTime": number,
      "Enabled": boolean,
      "FirstName": "string",
      "LastName": "string",
      "Status": "string",
      "UserName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Users

Information about users in the user pool.

Type: Array of [User](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeUserStackAssociations

Retrieves a list that describes the UserStackAssociation objects. You must specify either or both of the following:

- The stack name
- The user name (email address of the user associated with the stack) and the authentication type for the user

Request Syntax

```
{  
  "AuthenticationType": "string",  
  "MaxResults": number,  
  "NextToken": "string",  
  "StackName": "string",  
  "UserName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AuthenticationType

The authentication type for the user who is associated with the stack. You must specify USERPOOL.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: No

MaxResults

The maximum size of each page of results.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 500.

Required: No

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

StackName

The name of the stack that is associated with the user.

Type: String

Length Constraints: Minimum length of 1.

Required: No

UserName

The email address of the user who is associated with the stack.

Note

Users' email addresses are case-sensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{M}\p{S}\p{N}\p{P}]+`

Required: No

Response Syntax

```
{
```

```
"NextToken": "string",
"UserStackAssociations": [
  {
    "AuthenticationType": "string",
    "SendEmailNotification": boolean,
    "StackName": "string",
    "UserName": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

UserStackAssociations

The UserStackAssociation objects.

Type: Array of [UserStackAssociation](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisableUser

Disables the specified user in the user pool. Users can't sign in to AppStream 2.0 until they are re-enabled. This action does not delete the user.

Request Syntax

```
{
  "AuthenticationType": "string",
  "UserName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AuthenticationType

The authentication type for the user. You must specify USERPOOL.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: Yes

UserName

The email address of the user.

Note

Users' email addresses are case-sensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{M}\p{S}\p{N}\p{P}]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateAppBlockBuilderAppBlock

Disassociates a specified app block builder from a specified app block.

Request Syntax

```
{  
  "AppBlockArn": "string",  
  "AppBlockBuilderName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppBlockArn

The ARN of the app block.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: Yes

AppBlockBuilderName

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateApplicationFleet

Disassociates the specified application from the fleet.

Request Syntax

```
{  
  "ApplicationArn": "string",  
  "FleetName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ApplicationArn](#)

The ARN of the application.

Type: String

Pattern: `^arn:aws(?:\s-cn|\s-iso\b|\s-iso|\s-us\s-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: Yes

[FleetName](#)

The name of the fleet.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateApplicationFromEntitlement

Deletes the specified application from the specified entitlement.

Request Syntax

```
{  
  "ApplicationIdentifier": "string",  
  "EntitlementName": "string",  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ApplicationIdentifier

The identifier of the application to remove from the entitlement.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

EntitlementName

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

StackName

The name of the stack with which the entitlement is associated.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntitlementNotFoundException

The entitlement can't be found.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateFleet

Disassociates the specified fleet from the specified stack.

Request Syntax

```
{  
  "FleetName": "string",  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

FleetName

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

StackName

The name of the stack.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

EnableUser

Enables a user in the user pool. After being enabled, users can sign in to AppStream 2.0 and open applications from the stacks to which they are assigned.

Request Syntax

```
{  
  "AuthenticationType": "string",  
  "UserName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AuthenticationType

The authentication type for the user. You must specify USERPOOL.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: Yes

UserName

The email address of the user.

Note

Users' email addresses are case-sensitive. During login, if they specify an email address that doesn't use the same capitalization as the email address specified when their user pool account was created, a "user does not exist" error message displays.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{M}\p{S}\p{N}\p{P}]+`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ExpireSession

Immediately stops the specified streaming session.

Request Syntax

```
{  
  "SessionId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[SessionId](#)

The identifier of the streaming session.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssociatedFleets

Retrieves the name of the fleet that is associated with the specified stack.

Request Syntax

```
{  
  "NextToken": "string",  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

StackName

The name of the stack.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
{
```

```
"Names": [ "string" ],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Names

The name of the fleet.

Type: Array of strings

Length Constraints: Minimum length of 1.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAssociatedStacks

Retrieves the name of the stack with which the specified fleet is associated.

Request Syntax

```
{  
  "FleetName": "string",  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

FleetName

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

NextToken

The pagination token to use to retrieve the next page of results for this operation. If this value is null, it retrieves the first page.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
```

```
"Names": [ "string" ],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Names

The name of the stack.

Type: Array of strings

Length Constraints: Minimum length of 1.

NextToken

The pagination token to use to retrieve the next page of results for this operation. If there are no more pages, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEntitledApplications

Retrieves a list of entitled applications.

Request Syntax

```
{  
  "EntitlementName": "string",  
  "MaxResults": number,  
  "NextToken": "string",  
  "StackName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

EntitlementName

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

MaxResults

The maximum size of each page of results.

Type: Integer

Required: No

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Required: No

StackName

The name of the stack with which the entitlement is associated.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Syntax

```
{
  "EntitledApplications": [
    {
      "ApplicationIdentifier": "string"
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EntitledApplications

The entitled applications.

Type: Array of [EntitledApplication](#) objects

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

EntitlementNotFoundException

The entitlement can't be found.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Retrieves a list of all tags for the specified AppStream 2.0 resource. You can tag AppStream 2.0 image builders, images, fleets, and stacks.

For more information about tags, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Request Syntax

```
{  
  "ResourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the resource.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=\,@.\-]{0,1023}$`

Required: Yes

Response Syntax

```
{  
  "Tags": {  
    "string" : "string"  
  }  
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Tags

The information about the tags.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(!aws:)\p{L}\p{Z}\p{N}_:/+=\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^( [\p{L}\p{Z}\p{N}_:/+=\-@]*)$`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartAppBlockBuilder

Starts an app block builder.

An app block builder can only be started when it's associated with an app block.

Starting an app block builder starts a new instance, which is equivalent to an elastic fleet instance with application builder assistance functionality.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Response Syntax

```
{  
  "AppBlockBuilder": {  
    "AccessEndpoints": [  
      {  
        "EndpointType": "string",  
        "VpceId": "string"  
      }  
    ],  
    "AppBlockBuilderErrors": [  
      {  
        "Code": "string",  
        "Message": "string"  
      }  
    ]  
  }  
}
```

```

    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "ErrorTimestamp": number
    }
  ],
  "Arn": "string",
  "CreatedTime": number,
  "Description": "string",
  "DisplayName": "string",
  "EnableDefaultInternetAccess": boolean,
  "IamRoleArn": "string",
  "InstanceType": "string",
  "Name": "string",
  "Platform": "string",
  "State": "string",
  "StateChangeReason": {
    "Code": "string",
    "Message": "string"
  },
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppBlockBuilder

Describes an app block builder.

Type: [AppBlockBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

RequestLimitExceededException

AppStream 2.0 can't process the request right now because the Describe calls from your AWS account are being throttled by Amazon EC2. Try again later.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartFleet

Starts the specified fleet.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

RequestLimitExceededException

AppStream 2.0 can't process the request right now because the Describe calls from your AWS account are being throttled by Amazon EC2. Try again later.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartImageBuilder

Starts the specified image builder.

Request Syntax

```
{  
  "AppstreamAgentVersion": "string",  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppstreamAgentVersion

The version of the AppStream 2.0 agent to use for this image builder. To use the latest version of the AppStream 2.0 agent, specify [LATEST].

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

Name

The name of the image builder.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
{  
  "ImageBuilder": {  
    "AccessEndpoints": [  

```

```

    {
      "EndpointType": "string",
      "VpceId": "string"
    }
  ],
  "AppstreamAgentVersion": "string",
  "Arn": "string",
  "CreatedTime": number,
  "Description": "string",
  "DisplayName": "string",
  "DomainJoinInfo": {
    "DirectoryName": "string",
    "OrganizationalUnitDistinguishedName": "string"
  },
  "EnableDefaultInternetAccess": boolean,
  "IamRoleArn": "string",
  "ImageArn": "string",
  "ImageBuilderErrors": [
    {
      "ErrorCode": "string",
      "ErrorMessage": "string",
      "ErrorTimestamp": number
    }
  ],
  "InstanceType": "string",
  "LatestAppstreamAgentVersion": "string",
  "Name": "string",
  "NetworkAccessConfiguration": {
    "EniId": "string",
    "EniPrivateIpAddress": "string"
  },
  "Platform": "string",
  "State": "string",
  "StateChangeReason": {
    "Code": "string",
    "Message": "string"
  },
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageBuilder

Information about the image builder.

Type: [ImageBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopAppBlockBuilder

Stops an app block builder.

Stopping an app block builder terminates the instance, and the instance state is not persisted.

Request Syntax

```
{
  "Name": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Syntax

```
{
  "AppBlockBuilder": {
    "AccessEndpoints": [
      {
        "EndpointType": "string",
        "VpceId": "string"
      }
    ],
    "AppBlockBuilderErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string",

```

```
        "ErrorTimestamp": number
      }
    ],
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "EnableDefaultInternetAccess": boolean,
    "IamRoleArn": "string",
    "InstanceType": "string",
    "Name": "string",
    "Platform": "string",
    "State": "string",
    "StateChangeReason": {
      "Code": "string",
      "Message": "string"
    },
    "VpcConfig": {
      "SecurityGroupIds": [ "string " ],
      "SubnetIds": [ "string " ]
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppBlockBuilder

Describes an app block builder.

Type: [AppBlockBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopFleet

Stops the specified fleet.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StopImageBuilder

Stops the specified image builder.

Request Syntax

```
{  
  "Name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

Name

The name of the image builder.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Response Syntax

```
{  
  "ImageBuilder": {  
    "AccessEndpoints": [  
      {  
        "EndpointType": "string",  
        "VpceId": "string"  
      }  
    ],  
    "AppstreamAgentVersion": "string",  
    "Arn": "string",  
    "CreatedTime": number,  
    "Description": "string",  
    "DisplayName": "string",
```

```

    "DomainJoinInfo": {
      "DirectoryName": "string",
      "OrganizationalUnitDistinguishedName": "string"
    },
    "EnableDefaultInternetAccess": boolean,
    "IamRoleArn": "string",
    "ImageArn": "string",
    "ImageBuilderErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
      }
    ],
    "InstanceType": "string",
    "LatestAppstreamAgentVersion": "string",
    "Name": "string",
    "NetworkAccessConfiguration": {
      "EniId": "string",
      "EniPrivateIpAddress": "string"
    },
    "Platform": "string",
    "State": "string",
    "StateChangeReason": {
      "Code": "string",
      "Message": "string"
    },
    "VpcConfig": {
      "SecurityGroupIds": [ "string" ],
      "SubnetIds": [ "string" ]
    }
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ImageBuilder

Information about the image builder.

Type: [ImageBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds or overwrites one or more tags for the specified AppStream 2.0 resource. You can tag AppStream 2.0 image builders, images, fleets, and stacks.

Each tag consists of a key and an optional value. If a resource already has a tag with the same key, this operation updates its value.

To list the current tags for your resources, use [ListTagsForResource](#). To disassociate tags from your resources, use [UntagResource](#).

For more information about tags, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Request Syntax

```
{
  "ResourceArn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the resource.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+.=, @.\s|-]{0,1023}$`

Required: Yes

Tags

The tags to associate. A tag is a key-value pair, and the value is optional. For example, Environment=Test. If you do not specify a value, Environment=.

If you do not specify a value, the value is set to an empty string.

Generally allowed characters are: letters, numbers, and spaces representable in UTF-8, and the following special characters:

`_ . : / = + \ - @`

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Key Pattern: `^(^(!aws:)\p{L}\p{Z}\p{N}_:/=+\-@]*)$`

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Value Pattern: `^( [\p{L}\p{Z}\p{N}_:/=+\-@]*)$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Disassociates one or more specified tags from the specified AppStream 2.0 resource.

To list the current tags for your resources, use [ListTagsForResource](#).

For more information about tags, see [Tagging Your Resources](#) in the *Amazon AppStream 2.0 Administration Guide*.

Request Syntax

```
{  
  "ResourceArn": "string",  
  "TagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[ResourceArn](#)

The Amazon Resource Name (ARN) of the resource.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+@.\s-]{0,1023}$`

Required: Yes

[TagKeys](#)

The tag keys for the tags to disassociate.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^(^(?!aws:)\p{L}\p{Z}\p{N}_.:/+\\-@]*)$`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAppBlockBuilder

Updates an app block builder.

If the app block builder is in the STARTING or STOPPING state, you can't update it. If the app block builder is in the RUNNING state, you can only update the DisplayName and Description. If the app block builder is in the STOPPED state, you can update any attribute except the Name.

Request Syntax

```
{
  "AccessEndpoints": [
    {
      "EndpointType": "string",
      "VpceId": "string"
    }
  ],
  "AttributesToDelete": [ "string" ],
  "Description": "string",
  "DisplayName": "string",
  "EnableDefaultInternetAccess": boolean,
  "IamRoleArn": "string",
  "InstanceType": "string",
  "Name": "string",
  "Platform": "string",
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AccessEndpoints

The list of interface VPC endpoint (interface endpoint) objects. Administrators can connect to the app block builder only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

AttributesToDelete

The attributes to delete from the app block builder.

Type: Array of strings

Valid Values: IAM_ROLE_ARN | ACCESS_ENDPOINTS |
VPC_CONFIGURATION_SECURITY_GROUP_IDS

Required: No

Description

The description of the app block builder.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

The display name of the app block builder.

Type: String

Length Constraints: Maximum length of 100.

Required: No

EnableDefaultInternetAccess

Enables or disables default internet access for the app block builder.

Type: Boolean

Required: No

IamRoleArn

The Amazon Resource Name (ARN) of the IAM role to apply to the app block builder. To assume a role, the app block builder calls the AWS Security Token Service (STS) AssumeRole API operation and passes the ARN of the role to use. The operation creates a new session with temporary credentials. AppStream 2.0 retrieves the temporary credentials and creates the **appstream_machine_role** credential profile on the instance.

For more information, see [Using an IAM Role to Grant Permissions to Applications and Scripts Running on AppStream 2.0 Streaming Instances](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso|-b|\s|-iso|\s|-us|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: No

InstanceType

The instance type to use when launching the app block builder. The following instance types are available:

- stream.standard.small
- stream.standard.medium
- stream.standard.large
- stream.standard.xlarge
- stream.standard.2xlarge

Type: String

Length Constraints: Minimum length of 1.

Required: No

Name

The unique name for the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

Platform

The platform of the app block builder.

WINDOWS_SERVER_2019 is the only valid value.

Type: String

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 |
WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: No

VpcConfig

The VPC configuration for the app block builder.

App block builders require that you specify at least two subnets in different availability zones.

Type: [VpcConfig](#) object

Required: No

Response Syntax

```
{
  "AppBlockBuilder": {
    "AccessEndpoints": [
      {
        "EndpointType": "string",
        "VpceId": "string"
      }
    ],
    "AppBlockBuilderErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string",
        "ErrorTimestamp": number
      }
    ]
  },
}
```

```
{
  "Arn": "string",
  "CreatedTime": number,
  "Description": "string",
  "DisplayName": "string",
  "EnableDefaultInternetAccess": boolean,
  "IamRoleArn": "string",
  "InstanceType": "string",
  "Name": "string",
  "Platform": "string",
  "State": "string",
  "StateChangeReason": {
    "Code": "string",
    "Message": "string"
  },
  "VpcConfig": {
    "SecurityGroupIds": [ "string" ],
    "SubnetIds": [ "string" ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AppBlockBuilder

Describes an app block builder.

Type: [AppBlockBuilder](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

RequestLimitExceededException

AppStream 2.0 can't process the request right now because the Describe calls from your AWS account are being throttled by Amazon EC2. Try again later.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateApplication

Updates the specified application.

Request Syntax

```
{
  "AppBlockArn": "string",
  "AttributesToDelete": [ "string" ],
  "Description": "string",
  "DisplayName": "string",
  "IconS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "LaunchParameters": "string",
  "LaunchPath": "string",
  "Name": "string",
  "WorkingDirectory": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppBlockArn

The ARN of the app block.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\s|-b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: No

AttributesToDelete

The attributes to delete for an application.

Type: Array of strings

Array Members: Maximum number of 2 items.

Valid Values: LAUNCH_PARAMETERS | WORKING_DIRECTORY

Required: No

Description

The description of the application.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

The display name of the application. This name is visible to users in the application catalog.

Type: String

Length Constraints: Maximum length of 100.

Required: No

IconS3Location

The icon S3 location of the application.

Type: [S3Location](#) object

Required: No

LaunchParameters

The launch parameters of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

LaunchPath

The launch path of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Name

The name of the application. This name is visible to users when display name is not specified.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

WorkingDirectory

The working directory of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
  "Application": {
    "AppBlockArn": "string",
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "Enabled": boolean,
    "IconS3Location": {
      "S3Bucket": "string",
      "S3Key": "string"
    }
  },
}
```

```
    "IconURL": "string",
    "InstanceFamilies": [ "string" ],
    "LaunchParameters": "string",
    "LaunchPath": "string",
    "Metadata": {
        "string" : "string"
    },
    "Name": "string",
    "Platforms": [ "string" ],
    "WorkingDirectory": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Application](#)

Describes an application in the application catalog.

Type: [Application](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDirectoryConfig

Updates the specified Directory Config object in AppStream 2.0. This object includes the configuration information required to join fleets and image builders to Microsoft Active Directory domains.

Request Syntax

```
{
  "CertificateBasedAuthProperties": {
    "CertificateAuthorityArn": "string",
    "Status": "string"
  },
  "DirectoryName": "string",
  "OrganizationalUnitDistinguishedNames": [ "string" ],
  "ServiceAccountCredentials": {
    "AccountName": "string",
    "AccountPassword": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[CertificateBasedAuthProperties](#)

The certificate-based authentication properties used to authenticate SAML 2.0 Identity Provider (IdP) user identities to Active Directory domain-joined streaming instances. Fallback is turned on by default when certificate-based authentication is **Enabled**. Fallback allows users to log in using their AD domain password if certificate-based authentication is unsuccessful, or to unlock a desktop lock screen. **Enabled_no_directory_login_fallback** enables certificate-based authentication, but does not allow users to log in using their AD domain password. Users will be disconnected to re-authenticate using certificates.

Type: [CertificateBasedAuthProperties](#) object

Required: No

DirectoryName

The name of the Directory Config object.

Type: String

Required: Yes

OrganizationalUnitDistinguishedNames

The distinguished names of the organizational units for computer accounts.

Type: Array of strings

Length Constraints: Maximum length of 2000.

Required: No

ServiceAccountCredentials

The credentials for the service account used by the fleet or image builder to connect to the directory.

Type: [ServiceAccountCredentials](#) object

Required: No

Response Syntax

```
{
  "DirectoryName": {
    "CertificateBasedAuthProperties": {
      "CertificateAuthorityArn": "string",
      "Status": "string"
    },
    "CreatedTime": number,
    "DirectoryName": "string",
    "OrganizationalUnitDistinguishedNames": [ "string" ],
    "ServiceAccountCredentials": {
      "AccountName": "string",
      "AccountPassword": "string"
    }
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[DirectoryConfig](#)

Information about the Directory Config object.

Type: [DirectoryConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEntitlement

Updates the specified entitlement.

Request Syntax

```
{
  "AppVisibility": "string",
  "Attributes": [
    {
      "Name": "string",
      "Value": "string"
    }
  ],
  "Description": "string",
  "Name": "string",
  "StackName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AppVisibility

Specifies whether all or only selected apps are entitled.

Type: String

Valid Values: ALL | ASSOCIATED

Required: No

Attributes

The attributes of the entitlement.

Type: Array of [EntitlementAttribute](#) objects

Array Members: Minimum number of 1 item.

Required: No

Description

The description of the entitlement.

Type: String

Length Constraints: Maximum length of 256.

Required: No

Name

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

StackName

The name of the stack with which the entitlement is associated.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

Response Syntax

```
{
  "Entitlement": {
    "AppVisibility": "string",
    "Attributes": [
      {
        "Name": "string",
        "Value": "string"
      }
    ],
    "CreatedTime": number,
```

```
"Description": "string",  
"LastModifiedTime": number,  
"Name": "string",  
"StackName": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Entitlement

The entitlement.

Type: [Entitlement](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

EntitlementNotFoundException

The entitlement can't be found.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateFleet

Updates the specified fleet.

If the fleet is in the STOPPED state, you can update any attribute except the fleet name.

If the fleet is in the RUNNING state, you can update the following based on the fleet type:

- Always-On and On-Demand fleet types

You can update the `DisplayName`, `ComputeCapacity`, `ImageARN`, `ImageName`, `IdleDisconnectTimeoutInSeconds`, and `DisconnectTimeoutInSeconds` attributes.

- Elastic fleet type

You can update the `DisplayName`, `IdleDisconnectTimeoutInSeconds`, `DisconnectTimeoutInSeconds`, `MaxConcurrentSessions`, `SessionScriptS3Location` and `UsbDeviceFilterStrings` attributes.

If the fleet is in the STARTING or STOPPED state, you can't update it.

Request Syntax

```
{
  "AttributesToDelete": [ "string" ],
  "ComputeCapacity": {
    "DesiredInstances": number,
    "DesiredSessions": number
  },
  "DeleteVpcConfig": boolean,
  "Description": "string",
  "DisconnectTimeoutInSeconds": number,
  "DisplayName": "string",
  "DomainJoinInfo": {
    "DirectoryName": "string",
    "OrganizationalUnitDistinguishedName": "string"
  },
  "EnableDefaultInternetAccess": boolean,
  "IamRoleArn": "string",
  "IdleDisconnectTimeoutInSeconds": number,
  "ImageArn": "string",
  "ImageName": "string",
```



```
"InstanceType": "string",
"MaxConcurrentSessions": number,
"MaxSessionsPerInstance": number,
"MaxUserDurationInSeconds": number,
"Name": "string",
"Platform": "string",
"SessionScriptS3Location": {
  "S3Bucket": "string",
  "S3Key": "string"
},
"StreamView": "string",
"UsbDeviceFilterStrings": [ "string" ],
"VpcConfig": {
  "SecurityGroupIds": [ "string" ],
  "SubnetIds": [ "string" ]
}
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AttributesToDelete](#)

The fleet attributes to delete.

Type: Array of strings

Valid Values: VPC_CONFIGURATION | VPC_CONFIGURATION_SECURITY_GROUP_IDS
| DOMAIN_JOIN_INFO | IAM_ROLE_ARN | USB_DEVICE_FILTER_STRINGS |
SESSION_SCRIPT_S3_LOCATION | MAX_SESSIONS_PER_INSTANCE

Required: No

[ComputeCapacity](#)

The desired capacity for the fleet. This is not allowed for Elastic fleets.

Type: [ComputeCapacity](#) object

Required: No

DeleteVpcConfig

This parameter has been deprecated.

Deletes the VPC association for the specified fleet.

Type: Boolean

Required: No

Description

The description to display.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisconnectTimeoutInSeconds

The amount of time that a streaming session remains active after users disconnect. If users try to reconnect to the streaming session after a disconnection or network interruption within this time interval, they are connected to their previous session. Otherwise, they are connected to a new session with a new streaming instance.

Specify a value between 60 and 36000.

Type: Integer

Required: No

DisplayName

The fleet name to display.

Type: String

Length Constraints: Maximum length of 100.

Required: No

DomainJoinInfo

The name of the directory and organizational unit (OU) to use to join the fleet to a Microsoft Active Directory domain.

Type: [DomainJoinInfo](#) object

Required: No

[EnableDefaultInternetAccess](#)

Enables or disables default internet access for the fleet.

Type: Boolean

Required: No

[IamRoleArn](#)

The Amazon Resource Name (ARN) of the IAM role to apply to the fleet. To assume a role, a fleet instance calls the AWS Security Token Service (STS) AssumeRole API operation and passes the ARN of the role to use. The operation creates a new session with temporary credentials. AppStream 2.0 retrieves the temporary credentials and creates the **appstream_machine_role** credential profile on the instance.

For more information, see [Using an IAM Role to Grant Permissions to Applications and Scripts Running on AppStream 2.0 Streaming Instances](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s|-]{0,1023}$`

Required: No

[IdleDisconnectTimeoutInSeconds](#)

The amount of time that users can be idle (inactive) before they are disconnected from their streaming session and the `DisconnectTimeoutInSeconds` time interval begins. Users are notified before they are disconnected due to inactivity. If users try to reconnect to the streaming session before the time interval specified in `DisconnectTimeoutInSeconds` elapses, they are connected to their previous session. Users are considered idle when they stop providing keyboard or mouse input during their streaming session. File uploads and downloads, audio in, audio out, and pixels changing do not qualify as user activity. If users continue to be idle after the time interval in `IdleDisconnectTimeoutInSeconds` elapses, they are disconnected.

To prevent users from being disconnected due to inactivity, specify a value of 0. Otherwise, specify a value between 60 and 36000. The default value is 0.

Note

If you enable this feature, we recommend that you specify a value that corresponds exactly to a whole number of minutes (for example, 60, 120, and 180). If you don't do this, the value is rounded to the nearest minute. For example, if you specify a value of 70, users are disconnected after 1 minute of inactivity. If you specify a value that is at the midpoint between two different minutes, the value is rounded up. For example, if you specify a value of 90, users are disconnected after 2 minutes of inactivity.

Type: Integer

Required: No

ImageArn

The ARN of the public, private, or shared image to use.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-\gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=\,@.\-]{0,1023}$`

Required: No

ImageName

The name of the image used to create the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: No

InstanceType

The instance type to use when launching fleet instances. The following instance types are available:

- `stream.standard.small`

- `stream.standard.medium`
- `stream.standard.large`
- `stream.standard.xlarge`
- `stream.standard.2xlarge`
- `stream.compute.large`
- `stream.compute.xlarge`
- `stream.compute.2xlarge`
- `stream.compute.4xlarge`
- `stream.compute.8xlarge`
- `stream.memory.large`
- `stream.memory.xlarge`
- `stream.memory.2xlarge`
- `stream.memory.4xlarge`
- `stream.memory.8xlarge`
- `stream.memory.z1d.large`
- `stream.memory.z1d.xlarge`
- `stream.memory.z1d.2xlarge`
- `stream.memory.z1d.3xlarge`
- `stream.memory.z1d.6xlarge`
- `stream.memory.z1d.12xlarge`
- `stream.graphics-design.large`
- `stream.graphics-design.xlarge`
- `stream.graphics-design.2xlarge`
- `stream.graphics-design.4xlarge`
- `stream.graphics-desktop.2xlarge`
- `stream.graphics.g4dn.xlarge`
- `stream.graphics.g4dn.2xlarge`
- `stream.graphics.g4dn.4xlarge`
- `stream.graphics.g4dn.8xlarge`
- `stream.graphics.g4dn.12xlarge`

- `stream.graphics.g4dn.16xlarge`
- `stream.graphics-pro.4xlarge`
- `stream.graphics-pro.8xlarge`
- `stream.graphics-pro.16xlarge`

The following instance types are available for Elastic fleets:

- `stream.standard.small`
- `stream.standard.medium`
- `stream.standard.large`
- `stream.standard.xlarge`
- `stream.standard.2xlarge`

Type: String

Length Constraints: Minimum length of 1.

Required: No

[MaxConcurrentSessions](#)

The maximum number of concurrent sessions for a fleet.

Type: Integer

Required: No

[MaxSessionsPerInstance](#)

The maximum number of user sessions on an instance. This only applies to multi-session fleets.

Type: Integer

Required: No

[MaxUserDurationInSeconds](#)

The maximum amount of time that a streaming session can remain active, in seconds. If users are still connected to a streaming instance five minutes before this limit is reached, they are prompted to save any open documents before being disconnected. After this time elapses, the instance is terminated and replaced by a new instance.

Specify a value between 600 and 432000.

Type: Integer

Required: No

Name

A unique name for the fleet.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: No

Platform

The platform of the fleet. WINDOWS_SERVER_2019 and AMAZON_LINUX2 are supported for Elastic fleets.

Type: String

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 |
WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: No

SessionScriptS3Location

The S3 location of the session scripts configuration zip file. This only applies to Elastic fleets.

Type: [S3Location](#) object

Required: No

StreamView

The AppStream 2.0 view that is displayed to your users when they stream from the fleet. When APP is specified, only the windows of applications opened by users display. When DESKTOP is specified, the standard desktop that is provided by the operating system displays.

The default value is APP.

Type: String

Valid Values: APP | DESKTOP

Required: No

UsbDeviceFilterStrings

The USB device filter strings that specify which USB devices a user can redirect to the fleet streaming session, when using the Windows native client. This is allowed but not required for Elastic fleets.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `^((\\w*)\\s*(\\w*)\\s*\\,\\s*(\\w*)\\s*\\,\\s*\\*?(\\w*)\\s*\\,\\s*\\*?(\\w*)\\s*\\,\\s*\\*?\\d*\\s*\\,\\s*\\*?\\d*\\s*\\,\\s*[0-1]\\s*\\,\\s*[0-1]\\s*)$`

Required: No

VpcConfig

The VPC configuration for the fleet. This is required for Elastic fleets, but not required for other fleet types. Elastic fleets require that you specify at least two subnets in different availability zones.

Type: [VpcConfig](#) object

Required: No

Response Syntax

```
{
  "Fleet": {
    "Arn": "string",
    "ComputeCapacityStatus": {
      "ActiveUserSessions": number,
      "ActualUserSessions": number,
      "Available": number,
      "AvailableUserSessions": number,
      "Desired": number,
      "DesiredUserSessions": number,
      "InUse": number,
      "Running": number
    },
    "CreatedTime": number,
    "Description": "string",
```



```

    "DisconnectTimeoutInSeconds": number,
    "DisplayName": "string",
    "DomainJoinInfo": {
        "DirectoryName": "string",
        "OrganizationalUnitDistinguishedName": "string"
    },
    "EnableDefaultInternetAccess": boolean,
    "FleetErrors": [
        {
            "ErrorCode": "string",
            "ErrorMessage": "string"
        }
    ],
    "FleetType": "string",
    "IamRoleArn": "string",
    "IdleDisconnectTimeoutInSeconds": number,
    "ImageArn": "string",
    "ImageName": "string",
    "InstanceType": "string",
    "MaxConcurrentSessions": number,
    "MaxSessionsPerInstance": number,
    "MaxUserDurationInSeconds": number,
    "Name": "string",
    "Platform": "string",
    "SessionScriptS3Location": {
        "S3Bucket": "string",
        "S3Key": "string"
    },
    "State": "string",
    "StreamView": "string",
    "UsbDeviceFilterStrings": [ "string" ],
    "VpcConfig": {
        "SecurityGroupIds": [ "string" ],
        "SubnetIds": [ "string" ]
    }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Fleet

Information about the fleet.

Type: [Fleet](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

RequestLimitExceededException

AppStream 2.0 can't process the request right now because the Describe calls from your AWS account are being throttled by Amazon EC2. Try again later.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateImagePermissions

Adds or updates permissions for the specified private image.

Request Syntax

```
{  
  "ImagePermissions": {  
    "allowFleet": boolean,  
    "allowImageBuilder": boolean  
  },  
  "Name": "string",  
  "SharedAccountId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ImagePermissions

The permissions for the image.

Type: [ImagePermissions](#) object

Required: Yes

Name

The name of the private image.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

SharedAccountId

The 12-digit identifier of the AWS account for which you want add or update image permissions.

Type: String

Pattern: ^\d+\$

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

ResourceNotAvailableException

The specified resource exists and is not in use, but isn't available.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateStack

Updates the specified fields for the specified stack.

Request Syntax

```
{
  "AccessEndpoints": [
    {
      "EndpointType": "string",
      "VpceId": "string"
    }
  ],
  "ApplicationSettings": {
    "Enabled": boolean,
    "SettingsGroup": "string"
  },
  "AttributesToDelete": [ "string" ],
  "DeleteStorageConnectors": boolean,
  "Description": "string",
  "DisplayName": "string",
  "EmbedHostDomains": [ "string" ],
  "FeedbackURL": "string",
  "Name": "string",
  "RedirectURL": "string",
  "StorageConnectors": [
    {
      "ConnectorType": "string",
      "Domains": [ "string" ],
      "DomainsRequireAdminConsent": [ "string" ],
      "ResourceIdentifier": "string"
    }
  ],
  "StreamingExperienceSettings": {
    "PreferredProtocol": "string"
  },
  "UserSettings": [
    {
      "Action": "string",
      "MaxLength": number,
      "Permission": "string"
    }
  ]
}
```



```
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[AccessEndpoints](#)

The list of interface VPC endpoint (interface endpoint) objects. Users of the stack can connect to AppStream 2.0 only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

[ApplicationSettings](#)

The persistent application settings for users of a stack. When these settings are enabled, changes that users make to applications and Windows settings are automatically saved after each session and applied to the next session.

Type: [ApplicationSettings](#) object

Required: No

[AttributesToDelete](#)

The stack attributes to delete.

Type: Array of strings

Valid Values: STORAGE_CONNECTORS | STORAGE_CONNECTOR_HOMEFOLDERS | STORAGE_CONNECTOR_GOOGLE_DRIVE | STORAGE_CONNECTOR_ONE_DRIVE | REDIRECT_URL | FEEDBACK_URL | THEME_NAME | USER_SETTINGS | EMBED_HOST_DOMAINS | IAM_ROLE_ARN | ACCESS_ENDPOINTS | STREAMING_EXPERIENCE_SETTINGS

Required: No

DeleteStorageConnectors

This parameter has been deprecated.

Deletes the storage connectors currently enabled for the stack.

Type: Boolean

Required: No

Description

The description to display.

Type: String

Length Constraints: Maximum length of 256.

Required: No

DisplayName

The stack name to display.

Type: String

Length Constraints: Maximum length of 100.

Required: No

EmbedHostDomains

The domains where AppStream 2.0 streaming sessions can be embedded in an iframe. You must approve the domains that you want to host embedded AppStream 2.0 streaming sessions.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Maximum length of 128.

Pattern: `(?:[a-z0-9](?:[a-z0-9-]{0,61}[a-z0-9])?\.\.)+[a-z0-9][a-z0-9-]{0,61}[a-z0-9]`

Required: No

FeedbackURL

The URL that users are redirected to after they choose the Send Feedback link. If no URL is specified, no Send Feedback link is displayed.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

Name

The name of the stack.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

RedirectURL

The URL that users are redirected to after their streaming session ends.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

StorageConnectors

The storage connectors to enable.

Type: Array of [StorageConnector](#) objects

Required: No

StreamingExperienceSettings

The streaming protocol you want your stack to prefer. This can be UDP or TCP. Currently, UDP is only supported in the Windows native client.

Type: [StreamingExperienceSettings](#) object

Required: No

[UserSettings](#)

The actions that are enabled or disabled for users during their streaming sessions. By default, these actions are enabled.

Type: Array of [UserSetting](#) objects

Array Members: Minimum number of 1 item.

Required: No

Response Syntax

```
{
  "Stack": {
    "AccessEndpoints": [
      {
        "EndpointType": "string",
        "VpceId": "string"
      }
    ],
    "ApplicationSettings": {
      "Enabled": boolean,
      "S3BucketName": "string",
      "SettingsGroup": "string"
    },
    "Arn": "string",
    "CreatedTime": number,
    "Description": "string",
    "DisplayName": "string",
    "EmbedHostDomains": [ "string" ],
    "FeedbackURL": "string",
    "Name": "string",
    "RedirectURL": "string",
    "StackErrors": [
      {
        "ErrorCode": "string",
        "ErrorMessage": "string"
      }
    ]
  }
}
```

```
],
  "StorageConnectors": [
    {
      "ConnectorType": "string",
      "Domains": [ "string" ],
      "DomainsRequireAdminConsent": [ "string" ],
      "ResourceIdentifier": "string"
    }
  ],
  "StreamingExperienceSettings": {
    "PreferredProtocol": "string"
  },
  "UserSettings": [
    {
      "Action": "string",
      "MaximumLength": number,
      "Permission": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Stack

Information about the stack.

Type: [Stack](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

IncompatibleImageException

The image can't be updated because it's not compatible for updates.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

InvalidRoleException

The specified role is invalid.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

The specified resource is in use.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateThemeForStack

Updates custom branding that customizes the appearance of the streaming application catalog page.

Request Syntax

```
{
  "AttributesToDelete": [ "string" ],
  "FaviconS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "FooterLinks": [
    {
      "DisplayName": "string",
      "FooterLinkURL": "string"
    }
  ],
  "OrganizationLogoS3Location": {
    "S3Bucket": "string",
    "S3Key": "string"
  },
  "StackName": "string",
  "State": "string",
  "ThemeStyling": "string",
  "TitleText": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

AttributesToDelete

The attributes to delete.

Type: Array of strings

Valid Values: FOOTER_LINKS

Required: No

FaviconS3Location

The S3 location of the favicon. The favicon enables users to recognize their application streaming site in a browser full of tabs or bookmarks. It is displayed at the top of the browser tab for the application streaming site during users' streaming sessions.

Type: [S3Location](#) object

Required: No

FooterLinks

The links that are displayed in the footer of the streaming application catalog page. These links are helpful resources for users, such as the organization's IT support and product marketing sites.

Type: Array of [ThemeFooterLink](#) objects

Required: No

OrganizationLogoS3Location

The organization logo that appears on the streaming application catalog page.

Type: [S3Location](#) object

Required: No

StackName

The name of the stack for the theme.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

State

Specifies whether custom branding should be applied to catalog page or not.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

ThemeStyling

The color theme that is applied to website links, text, and buttons. These colors are also applied as accents in the background for the streaming application catalog page.

Type: String

Valid Values: LIGHT_BLUE | BLUE | PINK | RED

Required: No

TitleText

The title that is displayed at the top of the browser tab during users' application streaming sessions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: ^[-@./#&+\w\s]*\$

Required: No

Response Syntax

```
{
  "Theme": {
    "CreatedTime": number,
    "StackName": "string",
    "State": "string",
    "ThemeFaviconURL": "string",
    "ThemeFooterLinks": [
      {
        "DisplayName": "string",
        "FooterLinkURL": "string"
      }
    ],
    "ThemeOrganizationLogoURL": "string",
    "ThemeStyling": "string",
    "ThemeTitleText": "string"
  }
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Theme](#)

The theme object that contains the metadata of the custom branding.

Type: [Theme](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConcurrentModificationException

An API error occurred. Wait a few minutes and try again.

HTTP Status Code: 400

InvalidAccountStatusException

The resource cannot be created because your AWS account is suspended. For assistance, contact AWS Support.

HTTP Status Code: 400

InvalidParameterCombinationException

Indicates an incorrect combination of parameters, or a missing parameter.

HTTP Status Code: 400

LimitExceededException

The requested limit exceeds the permitted limit for an account.

HTTP Status Code: 400

OperationNotPermittedException

The attempted operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified resource was not found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon AppStream 2.0 API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessEndpoint](#)
- [AppBlock](#)
- [AppBlockBuilder](#)
- [AppBlockBuilderAppBlockAssociation](#)
- [AppBlockBuilderStateChangeReason](#)
- [Application](#)
- [ApplicationFleetAssociation](#)
- [ApplicationSettings](#)
- [ApplicationSettingsResponse](#)
- [CertificateBasedAuthProperties](#)
- [ComputeCapacity](#)
- [ComputeCapacityStatus](#)
- [DirectoryConfig](#)
- [DomainJoinInfo](#)
- [EntitledApplication](#)
- [Entitlement](#)
- [EntitlementAttribute](#)
- [ErrorDetails](#)
- [Fleet](#)
- [FleetError](#)

- [Image](#)
- [ImageBuilder](#)
- [ImageBuilderStateChangeReason](#)
- [ImagePermissions](#)
- [ImageStateChangeReason](#)
- [LastReportGenerationExecutionError](#)
- [NetworkAccessConfiguration](#)
- [ResourceError](#)
- [S3Location](#)
- [ScriptDetails](#)
- [ServiceAccountCredentials](#)
- [Session](#)
- [SharedImagePermissions](#)
- [Stack](#)
- [StackError](#)
- [StorageConnector](#)
- [StreamingExperienceSettings](#)
- [Theme](#)
- [ThemeFooterLink](#)
- [UsageReportSubscription](#)
- [User](#)
- [UserSetting](#)
- [UserStackAssociation](#)
- [UserStackAssociationError](#)
- [VpcConfig](#)

AccessEndpoint

Describes an interface VPC endpoint (interface endpoint) that lets you create a private connection between the virtual private cloud (VPC) that you specify and AppStream 2.0. When you specify an interface endpoint for a stack, users of the stack can connect to AppStream 2.0 only through that endpoint. When you specify an interface endpoint for an image builder, administrators can connect to the image builder only through that endpoint.

Contents

EndpointType

The type of interface endpoint.

Type: String

Valid Values: STREAMING

Required: Yes

VpcId

The identifier (ID) of the VPC in which the interface endpoint is used.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AppBlock

Describes an app block.

App blocks are an Amazon AppStream 2.0 resource that stores the details about the virtual hard disk in an S3 bucket. It also stores the setup script with details about how to mount the virtual hard disk. The virtual hard disk includes the application binaries and other files necessary to launch your applications. Multiple applications can be assigned to a single app block.

This is only supported for Elastic fleets.

Contents

Arn

The ARN of the app block.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9_/_+=, @.\-]{0,1023}$`

Required: Yes

Name

The name of the app block.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

AppBlockErrors

The errors of the app block.

Type: Array of [ErrorDetails](#) objects

Required: No

CreatedTime

The created time of the app block.

Type: Timestamp

Required: No

Description

The description of the app block.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DisplayName

The display name of the app block.

Type: String

Length Constraints: Minimum length of 1.

Required: No

PackagingType

The packaging type of the app block.

Type: String

Valid Values: CUSTOM | APPSTREAM2

Required: No

PostSetupScriptDetails

The post setup script details of the app block.

This only applies to app blocks with PackagingType APPSTREAM2.

Type: [ScriptDetails](#) object

Required: No

SetupScriptDetails

The setup script details of the app block.

This only applies to app blocks with PackagingType CUSTOM.

Type: [ScriptDetails](#) object

Required: No

SourceS3Location

The source S3 location of the app block.

Type: [S3Location](#) object

Required: No

State

The state of the app block.

An app block with AppStream 2.0 packaging will be in the INACTIVE state if no application package (VHD) is assigned to it. After an application package (VHD) is created by an app block builder for an app block, it becomes ACTIVE.

Custom app blocks are always in the ACTIVE state and no action is required to use them.

Type: String

Valid Values: INACTIVE | ACTIVE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AppBlockBuilder

Describes an app block builder.

Contents

Arn

The ARN of the app block builder.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: Yes

InstanceType

The instance type of the app block builder.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Name

The name of the app block builder.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Platform

The platform of the app block builder.

WINDOWS_SERVER_2019 is the only valid value.

Type: String

Valid Values: WINDOWS_SERVER_2019

Required: Yes

State

The state of the app block builder.

Type: String

Valid Values: STARTING | RUNNING | STOPPING | STOPPED

Required: Yes

VpcConfig

The VPC configuration for the app block builder.

Type: [VpcConfig](#) object

Required: Yes

AccessEndpoints

The list of interface VPC endpoint (interface endpoint) objects. Administrators can connect to the app block builder only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

AppBlockBuilderErrors

The app block builder errors.

Type: Array of [ResourceError](#) objects

Required: No

CreatedTime

The creation time of the app block builder.

Type: Timestamp

Required: No

Description

The description of the app block builder.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DisplayName

The display name of the app block builder.

Type: String

Length Constraints: Minimum length of 1.

Required: No

EnableDefaultInternetAccess

Indicates whether default internet access is enabled for the app block builder.

Type: Boolean

Required: No

IamRoleArn

The ARN of the IAM role that is applied to the app block builder.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: No

StateChangeReason

The state change reason.

Type: [AppBlockBuilderStateChangeReason](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AppBlockBuilderAppBlockAssociation

Describes an association between an app block builder and app block.

Contents

AppBlockArn

The ARN of the app block.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: Yes

AppBlockBuilderName

The name of the app block builder.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-.]{0,100}$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AppBlockBuilderStateChangeReason

Describes the reason why the last app block builder state change occurred.

Contents

Code

The state change reason code.

Type: String

Valid Values: INTERNAL_ERROR

Required: No

Message

The state change reason message.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Application

Describes an application in the application catalog.

Contents

AppBlockArn

The app block ARN of the application.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: No

Arn

The ARN of the application.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\-]{0,1023}$`

Required: No

CreatedTime

The time at which the application was created within the app block.

Type: Timestamp

Required: No

Description

The description of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DisplayName

The application name to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Enabled

If there is a problem, the application can be disabled after image creation.

Type: Boolean

Required: No

IconS3Location

The S3 location of the application icon.

Type: [S3Location](#) object

Required: No

IconURL

The URL for the application icon. This URL might be time-limited.

Type: String

Length Constraints: Minimum length of 1.

Required: No

InstanceFamilies

The instance families for the application.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: No

LaunchParameters

The arguments that are passed to the application at launch.

Type: String

Length Constraints: Minimum length of 1.

Required: No

LaunchPath

The path to the application executable in the instance.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Metadata

Additional attributes that describe the application.

Type: String to string map

Key Length Constraints: Minimum length of 1.

Value Length Constraints: Minimum length of 1.

Required: No

Name

The name of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Platforms

The platforms on which the application can run.

Type: Array of strings

Array Members: Maximum number of 4 items.

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 |
WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: No

WorkingDirectory

The working directory for the application.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ApplicationFleetAssociation

Describes the application fleet association.

Contents

ApplicationArn

The ARN of the application associated with the fleet.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/_+=, @.\-]{0,1023}$`

Required: Yes

FleetName

The name of the fleet associated with the application.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ApplicationSettings

The persistent application settings for users of a stack.

Contents

Enabled

Enables or disables persistent application settings for users during their streaming sessions.

Type: Boolean

Required: Yes

SettingsGroup

The path prefix for the S3 bucket where users' persistent application settings are stored. You can allow the same persistent application settings to be used across multiple stacks by specifying the same settings group for each stack.

Type: String

Length Constraints: Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ApplicationSettingsResponse

Describes the persistent application settings for users of a stack.

Contents

Enabled

Specifies whether persistent application settings are enabled for users during their streaming sessions.

Type: Boolean

Required: No

S3BucketName

The S3 bucket where users' persistent application settings are stored. When persistent application settings are enabled for the first time for an account in an AWS Region, an S3 bucket is created. The bucket is unique to the AWS account and the Region.

Type: String

Length Constraints: Minimum length of 1.

Required: No

SettingsGroup

The path prefix for the S3 bucket where users' persistent application settings are stored.

Type: String

Length Constraints: Maximum length of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CertificateBasedAuthProperties

The certificate-based authentication properties used to authenticate SAML 2.0 Identity Provider (IdP) user identities to Active Directory domain-joined streaming instances. Fallback is turned on by default when certificate-based authentication is **Enabled** . Fallback allows users to log in using their AD domain password if certificate-based authentication is unsuccessful, or to unlock a desktop lock screen. **Enabled_no_directory_login_fallback** enables certificate-based authentication, but does not allow users to log in using their AD domain password. Users will be disconnected to re-authenticate using certificates.

Contents

CertificateAuthorityArn

The ARN of the AWS Certificate Manager Private CA resource.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=@.\s-]{0,1023}$`

Required: No

Status

The status of the certificate-based authentication properties.

Type: String

Valid Values: `DISABLED` | `ENABLED` | `ENABLED_NO_DIRECTORY_LOGIN_FALLBACK`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeCapacity

Describes the capacity for a fleet.

Contents

DesiredInstances

The desired number of streaming instances.

Type: Integer

Required: No

DesiredSessions

The desired number of user sessions for a multi-session fleet. This is not allowed for single-session fleets.

When you create a fleet, you must set either the DesiredSessions or DesiredInstances attribute, based on the type of fleet you create. You can't define both attributes or leave both attributes blank.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeCapacityStatus

Describes the capacity status for a fleet.

Contents

Desired

The desired number of streaming instances.

Type: Integer

Required: Yes

ActiveUserSessions

The number of user sessions currently being used for streaming sessions. This only applies to multi-session fleets.

Type: Integer

Required: No

ActualUserSessions

The total number of session slots that are available for streaming or are currently streaming.

$\text{ActualUserSessionCapacity} = \text{AvailableUserSessionCapacity} + \text{ActiveUserSessions}$

This only applies to multi-session fleets.

Type: Integer

Required: No

Available

The number of currently available instances that can be used to stream sessions.

Type: Integer

Required: No

AvailableUserSessions

The number of idle session slots currently available for user sessions.

$\text{AvailableUserSessionCapacity} = \text{ActualUserSessionCapacity} - \text{ActiveUserSessions}$

This only applies to multi-session fleets.

Type: Integer

Required: No

DesiredUserSessions

The total number of sessions slots that are either running or pending. This represents the total number of concurrent streaming sessions your fleet can support in a steady state.

$\text{DesiredUserSessionCapacity} = \text{ActualUserSessionCapacity} + \text{PendingUserSessionCapacity}$

This only applies to multi-session fleets.

Type: Integer

Required: No

InUse

The number of instances in use for streaming.

Type: Integer

Required: No

Running

The total number of simultaneous streaming instances that are running.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

DirectoryConfig

Describes the configuration information required to join fleets and image builders to Microsoft Active Directory domains.

Contents

DirectoryName

The fully qualified name of the directory (for example, corp.example.com).

Type: String

Required: Yes

CertificateBasedAuthProperties

The certificate-based authentication properties used to authenticate SAML 2.0 Identity Provider (IdP) user identities to Active Directory domain-joined streaming instances. Fallback is turned on by default when certificate-based authentication is **Enabled** . Fallback allows users to log in using their AD domain password if certificate-based authentication is unsuccessful, or to unlock a desktop lock screen. **Enabled_no_directory_login_fallback** enables certificate-based authentication, but does not allow users to log in using their AD domain password. Users will be disconnected to re-authenticate using certificates.

Type: [CertificateBasedAuthProperties](#) object

Required: No

CreatedTime

The time the directory configuration was created.

Type: Timestamp

Required: No

OrganizationalUnitDistinguishedNames

The distinguished names of the organizational units for computer accounts.

Type: Array of strings

Length Constraints: Maximum length of 2000.

Required: No

ServiceAccountCredentials

The credentials for the service account used by the fleet or image builder to connect to the directory.

Type: [ServiceAccountCredentials](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DomainJoinInfo

Describes the configuration information required to join fleets and image builders to Microsoft Active Directory domains.

Contents

DirectoryName

The fully qualified name of the directory (for example, corp.example.com).

Type: String

Required: No

OrganizationalUnitDistinguishedName

The distinguished name of the organizational unit for computer accounts.

Type: String

Length Constraints: Maximum length of 2000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EntitledApplication

The application associated to an entitlement. Access is controlled based on user attributes.

Contents

ApplicationIdentifier

The identifier of the application.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Entitlement

Specifies an entitlement. Entitlements control access to specific applications within a stack, based on user attributes. Entitlements apply to SAML 2.0 federated user identities. Amazon AppStream 2.0 user pool and streaming URL users are entitled to all applications in a stack. Entitlements don't apply to the desktop stream view application, or to applications managed by a dynamic app provider using the Dynamic Application Framework.

Contents

AppVisibility

Specifies whether all or selected apps are entitled.

Type: String

Valid Values: ALL | ASSOCIATED

Required: Yes

Attributes

The attributes of the entitlement.

Type: Array of [EntitlementAttribute](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

Name

The name of the entitlement.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

StackName

The name of the stack with which the entitlement is associated.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: Yes

CreatedTime

The time when the entitlement was created.

Type: Timestamp

Required: No

Description

The description of the entitlement.

Type: String

Length Constraints: Maximum length of 256.

Required: No

LastModifiedTime

The time when the entitlement was last modified.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EntitlementAttribute

An attribute associated with an entitlement. Application entitlements work by matching a supported SAML 2.0 attribute name to a value when a user identity federates to an Amazon AppStream 2.0 SAML application.

Contents

Name

A supported AWS IAM SAML `PrincipalTag` attribute that is matched to the associated value when a user identity federates into an Amazon AppStream 2.0 SAML application.

The following are valid values:

- roles
- department
- organization
- groups
- title
- costCenter
- userType

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Value

A value that is matched to a supported SAML attribute name when a user identity federates into an Amazon AppStream 2.0 SAML application.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ErrorDetails

The error details.

Contents

ErrorCode

The error code.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ErrorMessage

The error message.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Fleet

Describes a fleet.

Contents

Arn

The Amazon Resource Name (ARN) for the fleet.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_+=,@.\s-]{0,1023}$`

Required: Yes

ComputeCapacityStatus

The capacity status for the fleet.

Type: [ComputeCapacityStatus](#) object

Required: Yes

InstanceType

The instance type to use when launching fleet instances. The following instance types are available:

- stream.standard.small
- stream.standard.medium
- stream.standard.large
- stream.compute.large
- stream.compute.xlarge
- stream.compute.2xlarge
- stream.compute.4xlarge
- stream.compute.8xlarge
- stream.memory.large

- `stream.memory.xlarge`
- `stream.memory.2xlarge`
- `stream.memory.4xlarge`
- `stream.memory.8xlarge`
- `stream.memory.z1d.large`
- `stream.memory.z1d.xlarge`
- `stream.memory.z1d.2xlarge`
- `stream.memory.z1d.3xlarge`
- `stream.memory.z1d.6xlarge`
- `stream.memory.z1d.12xlarge`
- `stream.graphics-design.large`
- `stream.graphics-design.xlarge`
- `stream.graphics-design.2xlarge`
- `stream.graphics-design.4xlarge`
- `stream.graphics-desktop.2xlarge`
- `stream.graphics.g4dn.xlarge`
- `stream.graphics.g4dn.2xlarge`
- `stream.graphics.g4dn.4xlarge`
- `stream.graphics.g4dn.8xlarge`
- `stream.graphics.g4dn.12xlarge`
- `stream.graphics.g4dn.16xlarge`
- `stream.graphics-pro.4xlarge`
- `stream.graphics-pro.8xlarge`
- `stream.graphics-pro.16xlarge`
- `stream.graphics.g5.xlarge`
- `stream.graphics.g5.2xlarge`
- `stream.graphics.g5.4xlarge`
- `stream.graphics.g5.8xlarge`
- `stream.graphics.g5.16xlarge`
- `stream.graphics.g5.12xlarge`

- `stream.graphics.g5.24xlarge`
- `stream.graphics.g6.xlarge`
- `stream.graphics.g6.2xlarge`
- `stream.graphics.g6.4xlarge`
- `stream.graphics.g6.8xlarge`
- `stream.graphics.g6.16xlarge`
- `stream.graphics.g6.12xlarge`
- `stream.graphics.g6.24xlarge`
- `stream.graphics.gr6.4xlarge`
- `stream.graphics.gr6.8xlarge`

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Name

The name of the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

State

The current state for the fleet.

Type: String

Valid Values: `STARTING` | `RUNNING` | `STOPPING` | `STOPPED`

Required: Yes

CreatedTime

The time the fleet was created.

Type: Timestamp

Required: No

Description

The description to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DisconnectTimeoutInSeconds

The amount of time that a streaming session remains active after users disconnect. If they try to reconnect to the streaming session after a disconnection or network interruption within this time interval, they are connected to their previous session. Otherwise, they are connected to a new session with a new streaming instance.

Specify a value between 60 and 36000.

Type: Integer

Required: No

DisplayName

The fleet name to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DomainJoinInfo

The name of the directory and organizational unit (OU) to use to join the fleet to a Microsoft Active Directory domain.

Type: [DomainJoinInfo](#) object

Required: No

EnableDefaultInternetAccess

Indicates whether default internet access is enabled for the fleet.

Type: Boolean

Required: No

FleetErrors

The fleet errors.

Type: Array of [FleetError](#) objects

Required: No

FleetType

The fleet type.

ALWAYS_ON

Provides users with instant-on access to their apps. You are charged for all running instances in your fleet, even if no users are streaming apps.

ON_DEMAND

Provide users with access to applications after they connect, which takes one to two minutes. You are charged for instance streaming when users are connected and a small hourly fee for instances that are not streaming apps.

Type: String

Valid Values: ALWAYS_ON | ON_DEMAND | ELASTIC

Required: No

IamRoleArn

The ARN of the IAM role that is applied to the fleet. To assume a role, the fleet instance calls the AWS Security Token Service (STS) AssumeRole API operation and passes the ARN of the role to use. The operation creates a new session with temporary credentials. AppStream 2.0 retrieves the temporary credentials and creates the **appstream_machine_role** credential profile on the instance.

For more information, see [Using an IAM Role to Grant Permissions to Applications and Scripts Running on AppStream 2.0 Streaming Instances](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_+=,@.\-]{0,1023}$`

Required: No

IdleDisconnectTimeoutInSeconds

The amount of time that users can be idle (inactive) before they are disconnected from their streaming session and the `DisconnectTimeoutInSeconds` time interval begins. Users are notified before they are disconnected due to inactivity. If users try to reconnect to the streaming session before the time interval specified in `DisconnectTimeoutInSeconds` elapses, they are connected to their previous session. Users are considered idle when they stop providing keyboard or mouse input during their streaming session. File uploads and downloads, audio in, audio out, and pixels changing do not qualify as user activity. If users continue to be idle after the time interval in `IdleDisconnectTimeoutInSeconds` elapses, they are disconnected.

To prevent users from being disconnected due to inactivity, specify a value of 0. Otherwise, specify a value between 60 and 36000. The default value is 0.

Note

If you enable this feature, we recommend that you specify a value that corresponds exactly to a whole number of minutes (for example, 60, 120, and 180). If you don't do this, the value is rounded to the nearest minute. For example, if you specify a value of 70, users are disconnected after 1 minute of inactivity. If you specify a value that is at the midpoint between two different minutes, the value is rounded up. For example, if you specify a value of 90, users are disconnected after 2 minutes of inactivity.

Type: Integer

Required: No

ImageArn

The ARN for the public, private, or shared image.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:._/+=@.\-]{0,1023}$`

Required: No

ImageName

The name of the image used to create the fleet.

Type: String

Length Constraints: Minimum length of 1.

Required: No

MaxConcurrentSessions

The maximum number of concurrent sessions for the fleet.

Type: Integer

Required: No

MaxSessionsPerInstance

The maximum number of user sessions on an instance. This only applies to multi-session fleets.

Type: Integer

Required: No

MaxUserDurationInSeconds

The maximum amount of time that a streaming session can remain active, in seconds. If users are still connected to a streaming instance five minutes before this limit is reached, they are prompted to save any open documents before being disconnected. After this time elapses, the instance is terminated and replaced by a new instance.

Specify a value between 600 and 360000.

Type: Integer

Required: No

Platform

The platform of the fleet.

Type: String

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 |
WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: No

SessionScriptS3Location

The S3 location of the session scripts configuration zip file. This only applies to Elastic fleets.

Type: [S3Location](#) object

Required: No

StreamView

The AppStream 2.0 view that is displayed to your users when they stream from the fleet. When APP is specified, only the windows of applications opened by users display. When DESKTOP is specified, the standard desktop that is provided by the operating system displays.

The default value is APP.

Type: String

Valid Values: APP | DESKTOP

Required: No

UsbDeviceFilterStrings

The USB device filter strings associated with the fleet.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `^((\w*)\s*(\w*)\s*\, \s*(\w*)\s*\, \s*\*?(\w*)\s*\, \s*\*?(\w*)\s*\, \s*\*?\d*\s*\, \s*\*?\d*\s*\, \s*[0-1]\s*\, \s*[0-1]\s*)$`

Required: No

VpcConfig

The VPC configuration for the fleet.

Type: [VpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FleetError

Describes a fleet error.

Contents

ErrorCode

The error code.

Type: String

Valid Values: IAM_SERVICE_ROLE_MISSING_ENI_DESCRIBE_ACTION
| IAM_SERVICE_ROLE_MISSING_ENI_CREATE_ACTION |
IAM_SERVICE_ROLE_MISSING_ENI_DELETE_ACTION |
NETWORK_INTERFACE_LIMIT_EXCEEDED | INTERNAL_SERVICE_ERROR
| IAM_SERVICE_ROLE_IS_MISSING | MACHINE_ROLE_IS_MISSING |
STS_DISABLED_IN_REGION | SUBNET_HAS_INSUFFICIENT_IP_ADDRESSES
| IAM_SERVICE_ROLE_MISSING_DESCRIBE_SUBNET_ACTION |
SUBNET_NOT_FOUND | IMAGE_NOT_FOUND | INVALID_SUBNET_CONFIGURATION
| SECURITY_GROUPS_NOT_FOUND | IGW_NOT_ATTACHED |
IAM_SERVICE_ROLE_MISSING_DESCRIBE_SECURITY_GROUPS_ACTION | FLEET_STOPPED
| FLEET_INSTANCE_PROVISIONING_FAILURE | DOMAIN_JOIN_ERROR_FILE_NOT_FOUND
| DOMAIN_JOIN_ERROR_ACCESS_DENIED | DOMAIN_JOIN_ERROR_LOGON_FAILURE
| DOMAIN_JOIN_ERROR_INVALID_PARAMETER | DOMAIN_JOIN_ERROR_MORE_DATA |
DOMAIN_JOIN_ERROR_NO_SUCH_DOMAIN | DOMAIN_JOIN_ERROR_NOT_SUPPORTED |
DOMAIN_JOIN_NERR_INVALID_WORKGROUP_NAME |
DOMAIN_JOIN_NERR_WORKSTATION_NOT_STARTED |
DOMAIN_JOIN_ERROR_DS_MACHINE_ACCOUNT_QUOTA_EXCEEDED |
DOMAIN_JOIN_NERR_PASSWORD_EXPIRED | DOMAIN_JOIN_INTERNAL_SERVICE_ERROR

Required: No

ErrorMessage

The error message.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Image

Describes an image.

Contents

Name

The name of the image.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Applications

The applications associated with the image.

Type: Array of [Application](#) objects

Required: No

AppstreamAgentVersion

The version of the AppStream 2.0 agent to use for instances that are launched from this image.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

Arn

The ARN of the image.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\s|-b|\s|-iso|\s|-us\s|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+ =, @. \-]{0,1023}$`

Required: No

BaseImageArn

The ARN of the image from which this image was created.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_+=, @.\-]{0,1023}$`

Required: No

CreatedTime

The time the image was created.

Type: Timestamp

Required: No

Description

The description to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DisplayName

The image name to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DynamicAppProvidersEnabled

Indicates whether dynamic app providers are enabled within an AppStream 2.0 image or not.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

ImageBuilderName

The name of the image builder that was used to create the private image. If the image is shared, copied, or updated by using Managed Image Updates, this value is null.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ImageBuilderSupported

Indicates whether an image builder can be launched from this image.

Type: Boolean

Required: No

ImageErrors

Describes the errors that are returned when a new image can't be created.

Type: Array of [ResourceError](#) objects

Required: No

ImagePermissions

The permissions to provide to the destination AWS account for the specified image.

Type: [ImagePermissions](#) object

Required: No

ImageSharedWithOthers

Indicates whether the image is shared with another account ID.

Type: String

Valid Values: TRUE | FALSE

Required: No

LatestAppstreamAgentVersion

Indicates whether the image is using the latest AppStream 2.0 agent version or not.

Type: String

Valid Values: TRUE | FALSE

Required: No

Platform

The operating system platform of the image.

Type: String

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 |
WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: No

PublicBaseImageReleasedDate

The release date of the public base image. For private images, this date is the release date of the base image from which the image was created.

Type: Timestamp

Required: No

State

The image starts in the PENDING state. If image creation succeeds, the state is AVAILABLE. If image creation fails, the state is FAILED.

Type: String

Valid Values: PENDING | AVAILABLE | FAILED | COPYING | DELETING | CREATING |
IMPORTING

Required: No

StateChangeReason

The reason why the last state change occurred.

Type: [ImageStateChangeReason](#) object

Required: No

SupportedInstanceFamilies

The supported instances families that determine which image a customer can use when the customer launches a fleet or image builder. The following instances families are supported:

- General Purpose
- Compute Optimized
- Memory Optimized
- Graphics
- Graphics Design
- Graphics Pro
- Graphics G4
- Graphics G5

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: No

Visibility

Indicates whether the image is public or private.

Type: String

Valid Values: PUBLIC | PRIVATE | SHARED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

ImageBuilder

Describes a virtual machine that is used to create an image.

Contents

Name

The name of the image builder.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

AccessEndpoints

The list of virtual private cloud (VPC) interface endpoint objects. Administrators can connect to the image builder only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

AppstreamAgentVersion

The version of the AppStream 2.0 agent that is currently being used by the image builder.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

Arn

The ARN for the image builder.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\b|\-iso|\-us\gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=\,@.\-]{0,1023}$`

Required: No

CreatedTime

The time stamp when the image builder was created.

Type: Timestamp

Required: No

Description

The description to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DisplayName

The image builder name to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DomainJoinInfo

The name of the directory and organizational unit (OU) to use to join the image builder to a Microsoft Active Directory domain.

Type: [DomainJoinInfo](#) object

Required: No

EnableDefaultInternetAccess

Enables or disables default internet access for the image builder.

Type: Boolean

Required: No

IamRoleArn

The ARN of the IAM role that is applied to the image builder. To assume a role, the image builder calls the AWS Security Token Service (STS) AssumeRole API operation and passes the ARN of the role to use. The operation creates a new session with temporary credentials. AppStream 2.0 retrieves the temporary credentials and creates the **appstream_machine_role** credential profile on the instance.

For more information, see [Using an IAM Role to Grant Permissions to Applications and Scripts Running on AppStream 2.0 Streaming Instances](#) in the *Amazon AppStream 2.0 Administration Guide*.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_+=, @.\s-]{0,1023}$`

Required: No

ImageArn

The ARN of the image from which this builder was created.

Type: String

Pattern: `^arn:aws(?:\s|-cn|\s|-iso\b|\s|-iso|\s|-us|-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_+=, @.\s-]{0,1023}$`

Required: No

ImageBuilderErrors

The image builder errors.

Type: Array of [ResourceError](#) objects

Required: No

InstanceType

The instance type for the image builder. The following instance types are available:

- `stream.standard.small`
- `stream.standard.medium`
- `stream.standard.large`
- `stream.compute.large`
- `stream.compute.xlarge`
- `stream.compute.2xlarge`
- `stream.compute.4xlarge`
- `stream.compute.8xlarge`
- `stream.memory.large`
- `stream.memory.xlarge`
- `stream.memory.2xlarge`
- `stream.memory.4xlarge`
- `stream.memory.8xlarge`
- `stream.memory.z1d.large`
- `stream.memory.z1d.xlarge`
- `stream.memory.z1d.2xlarge`
- `stream.memory.z1d.3xlarge`
- `stream.memory.z1d.6xlarge`
- `stream.memory.z1d.12xlarge`
- `stream.graphics-design.large`
- `stream.graphics-design.xlarge`
- `stream.graphics-design.2xlarge`
- `stream.graphics-design.4xlarge`
- `stream.graphics-desktop.2xlarge`
- `stream.graphics.g4dn.xlarge`
- `stream.graphics.g4dn.2xlarge`
- `stream.graphics.g4dn.4xlarge`
- `stream.graphics.g4dn.8xlarge`
- `stream.graphics.g4dn.12xlarge`
- `stream.graphics.g4dn.16xlarge`

- stream.graphics-pro.4xlarge
- stream.graphics-pro.8xlarge
- stream.graphics-pro.16xlarge
- stream.graphics.g5.xlarge
- stream.graphics.g5.2xlarge
- stream.graphics.g5.4xlarge
- stream.graphics.g5.8xlarge
- stream.graphics.g5.16xlarge
- stream.graphics.g5.12xlarge
- stream.graphics.g5.24xlarge
- stream.graphics.g6.xlarge
- stream.graphics.g6.2xlarge
- stream.graphics.g6.4xlarge
- stream.graphics.g6.8xlarge
- stream.graphics.g6.16xlarge
- stream.graphics.g6.12xlarge
- stream.graphics.g6.24xlarge
- stream.graphics.gr6.4xlarge
- stream.graphics.gr6.8xlarge

Type: String

Length Constraints: Minimum length of 1.

Required: No

LatestAppstreamAgentVersion

Indicates whether the image builder is using the latest AppStream 2.0 agent version or not.

Type: String

Valid Values: TRUE | FALSE

Required: No

NetworkAccessConfiguration

Describes the network details of the fleet or image builder instance.

Type: [NetworkAccessConfiguration](#) object

Required: No

Platform

The operating system platform of the image builder.

Type: String

Valid Values: WINDOWS | WINDOWS_SERVER_2016 | WINDOWS_SERVER_2019 |
WINDOWS_SERVER_2022 | AMAZON_LINUX2 | RHEL8 | ROCKY_LINUX8

Required: No

State

The state of the image builder.

Type: String

Valid Values: PENDING | UPDATING_AGENT | RUNNING | STOPPING | STOPPED
| REBOOTING | SNAPSHOTTING | DELETING | FAILED | UPDATING |
PENDING_QUALIFICATION

Required: No

StateChangeReason

The reason why the last state change occurred.

Type: [ImageBuilderStateChangeReason](#) object

Required: No

VpcConfig

The VPC configuration of the image builder.

Type: [VpcConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageBuilderStateChangeReason

Describes the reason why the last image builder state change occurred.

Contents

Code

The state change reason code.

Type: String

Valid Values: INTERNAL_ERROR | IMAGE_UNAVAILABLE

Required: No

Message

The state change reason message.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImagePermissions

Describes the permissions for an image.

Contents

allowFleet

Indicates whether the image can be used for a fleet.

Type: Boolean

Required: No

allowImageBuilder

Indicates whether the image can be used for an image builder.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImageStateChangeReason

Describes the reason why the last image state change occurred.

Contents

Code

The state change reason code.

Type: String

Valid Values: INTERNAL_ERROR | IMAGE_BUILDER_NOT_AVAILABLE | IMAGE_COPY_FAILURE

Required: No

Message

The state change reason message.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LastReportGenerationExecutionError

Describes the error that is returned when a usage report can't be generated.

Contents

ErrorCode

The error code for the error that is returned when a usage report can't be generated.

Type: String

Valid Values: RESOURCE_NOT_FOUND | ACCESS_DENIED | INTERNAL_SERVICE_ERROR

Required: No

ErrorMessage

The error message for the error that is returned when a usage report can't be generated.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkAccessConfiguration

Describes the network details of the fleet or image builder instance.

Contents

EniId

The resource identifier of the elastic network interface that is attached to instances in your VPC. All network interfaces have the eni-xxxxxxx resource identifier.

Type: String

Length Constraints: Minimum length of 1.

Required: No

EniPrivateIpAddress

The private IP address of the elastic network interface that is attached to instances in your VPC.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceError

Describes a resource error.

Contents

ErrorCode

The error code.

Type: String

Valid Values: IAM_SERVICE_ROLE_MISSING_ENI_DESCRIBE_ACTION
| IAM_SERVICE_ROLE_MISSING_ENI_CREATE_ACTION |
IAM_SERVICE_ROLE_MISSING_ENI_DELETE_ACTION |
NETWORK_INTERFACE_LIMIT_EXCEEDED | INTERNAL_SERVICE_ERROR
| IAM_SERVICE_ROLE_IS_MISSING | MACHINE_ROLE_IS_MISSING |
STS_DISABLED_IN_REGION | SUBNET_HAS_INSUFFICIENT_IP_ADDRESSES
| IAM_SERVICE_ROLE_MISSING_DESCRIBE_SUBNET_ACTION |
SUBNET_NOT_FOUND | IMAGE_NOT_FOUND | INVALID_SUBNET_CONFIGURATION
| SECURITY_GROUPS_NOT_FOUND | IGW_NOT_ATTACHED |
IAM_SERVICE_ROLE_MISSING_DESCRIBE_SECURITY_GROUPS_ACTION | FLEET_STOPPED
| FLEET_INSTANCE_PROVISIONING_FAILURE | DOMAIN_JOIN_ERROR_FILE_NOT_FOUND
| DOMAIN_JOIN_ERROR_ACCESS_DENIED | DOMAIN_JOIN_ERROR_LOGON_FAILURE
| DOMAIN_JOIN_ERROR_INVALID_PARAMETER | DOMAIN_JOIN_ERROR_MORE_DATA |
DOMAIN_JOIN_ERROR_NO_SUCH_DOMAIN | DOMAIN_JOIN_ERROR_NOT_SUPPORTED |
DOMAIN_JOIN_NERR_INVALID_WORKGROUP_NAME |
DOMAIN_JOIN_NERR_WORKSTATION_NOT_STARTED |
DOMAIN_JOIN_ERROR_DS_MACHINE_ACCOUNT_QUOTA_EXCEEDED |
DOMAIN_JOIN_NERR_PASSWORD_EXPIRED | DOMAIN_JOIN_INTERNAL_SERVICE_ERROR

Required: No

ErrorMessage

The error message.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ErrorTimestamp

The time the error occurred.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3Location

Describes the S3 location.

Contents

S3Bucket

The S3 bucket of the S3 object.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[0-9a-z\.\-]*(?<!\. )$`

Required: Yes

S3Key

The S3 key of the S3 object.

This is required when used for the following:

- IconS3Location (Actions: CreateApplication and UpdateApplication)
- SessionScriptS3Location (Actions: CreateFleet and UpdateFleet)
- ScriptDetails (Actions: CreateAppBlock)
- SourceS3Location when creating an app block with CUSTOM PackagingType (Actions: CreateAppBlock)
- SourceS3Location when creating an app block with APPSTREAM2 PackagingType, and using an existing application package (VHD file). In this case, S3Key refers to the VHD file. If a new application package is required, then S3Key is not required. (Actions: CreateAppBlock)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScriptDetails

Describes the details of the script.

Contents

ExecutablePath

The run path for the script.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

ScriptS3Location

The S3 object location for the script.

Type: [S3Location](#) object

Required: Yes

TimeoutInSeconds

The run timeout, in seconds, for the script.

Type: Integer

Required: Yes

ExecutableParameters

The runtime parameters passed to the run path for the script.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceAccountCredentials

Describes the credentials for the service account used by the fleet or image builder to connect to the directory.

Contents

AccountName

The user name of the account. This account must have the following privileges: create computer objects, join computers to the domain, and change/reset the password on descendant computer objects for the organizational units specified.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

AccountPassword

The password for the account.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 127.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Session

Describes a streaming session.

Contents

FleetName

The name of the fleet for the streaming session.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

Id

The identifier of the streaming session.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

StackName

The name of the stack for the streaming session.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

State

The current state of the streaming session.

Type: String

Valid Values: ACTIVE | PENDING | EXPIRED

Required: Yes

UserId

The identifier of the user for whom the session was created.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 128.

Required: Yes

AuthenticationType

The authentication method. The user is authenticated using a streaming URL (API) or SAML 2.0 federation (SAML).

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: No

ConnectionState

Specifies whether a user is connected to the streaming session.

Type: String

Valid Values: CONNECTED | NOT_CONNECTED

Required: No

InstanceId

The identifier for the instance hosting the session.

Type: String

Length Constraints: Minimum length of 1.

Required: No

MaxExpirationTime

The time when the streaming session is set to expire. This time is based on the `MaxUserDurationInSeconds` value, which determines the maximum length of time that a streaming session can run. A streaming session might end earlier than the time specified in

`SessionMaxExpirationTime`, when the `DisconnectTimeoutInSeconds` elapses or the user chooses to end his or her session. If the `DisconnectTimeoutInSeconds` elapses, or the user chooses to end his or her session, the streaming instance is terminated and the streaming session ends.

Type: Timestamp

Required: No

NetworkAccessConfiguration

The network details for the streaming session.

Type: [NetworkAccessConfiguration](#) object

Required: No

StartTime

The time when a streaming instance is dedicated for the user.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SharedImagePermissions

Describes the permissions that are available to the specified AWS account for a shared image.

Contents

imagePermissions

Describes the permissions for a shared image.

Type: [ImagePermissions](#) object

Required: Yes

sharedAccountId

The 12-digit identifier of the AWS account with which the image is shared.

Type: String

Pattern: `^\d+$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Stack

Describes a stack.

Contents

Name

The name of the stack.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

AccessEndpoints

The list of virtual private cloud (VPC) interface endpoint objects. Users of the stack can connect to AppStream 2.0 only through the specified endpoints.

Type: Array of [AccessEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Required: No

ApplicationSettings

The persistent application settings for users of the stack.

Type: [ApplicationSettingsResponse](#) object

Required: No

Arn

The ARN of the stack.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9:_/+=\,@.\-]{0,1023}$`

Required: No

CreatedTime

The time the stack was created.

Type: Timestamp

Required: No

Description

The description to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DisplayName

The stack name to display.

Type: String

Length Constraints: Minimum length of 1.

Required: No

EmbedHostDomains

The domains where AppStream 2.0 streaming sessions can be embedded in an iframe. You must approve the domains that you want to host embedded AppStream 2.0 streaming sessions.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 20 items.

Length Constraints: Maximum length of 128.

Pattern: `(?:[a-z0-9](?:[a-z0-9-]{0,61}[a-z0-9])?\.)+[a-z0-9][a-z0-9-]{0,61}[a-z0-9]`

Required: No

FeedbackURL

The URL that users are redirected to after they click the Send Feedback link. If no URL is specified, no Send Feedback link is displayed.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

RedirectURL

The URL that users are redirected to after their streaming session ends.

Type: String

Length Constraints: Maximum length of 1000.

Required: No

StackErrors

The errors for the stack.

Type: Array of [StackError](#) objects

Required: No

StorageConnectors

The storage connectors to enable.

Type: Array of [StorageConnector](#) objects

Required: No

StreamingExperienceSettings

The streaming protocol you want your stack to prefer. This can be UDP or TCP. Currently, UDP is only supported in the Windows native client.

Type: [StreamingExperienceSettings](#) object

Required: No

UserSettings

The actions that are enabled or disabled for users during their streaming sessions. By default these actions are enabled.

Type: Array of [UserSetting](#) objects

Array Members: Minimum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StackError

Describes a stack error.

Contents

ErrorCode

The error code.

Type: String

Valid Values: STORAGE_CONNECTOR_ERROR | INTERNAL_SERVICE_ERROR

Required: No

ErrorMessage

The error message.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StorageConnector

Describes a connector that enables persistent storage for users.

Contents

ConnectorType

The type of storage connector.

Type: String

Valid Values: HOMEFOLDERS | GOOGLE_DRIVE | ONE_DRIVE

Required: Yes

Domains

The names of the domains for the account.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

DomainsRequireAdminConsent

The OneDrive for Business domains where you require admin consent when users try to link their OneDrive account to AppStream 2.0. The attribute can only be specified when ConnectorType=ONE_DRIVE.

Type: Array of strings

Array Members: Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

ResourceIdentifier

The ARN of the storage connector.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StreamingExperienceSettings

The streaming protocol you want your stack to prefer. This can be UDP or TCP. Currently, UDP is only supported in the Windows native client.

Contents

PreferredProtocol

The preferred protocol that you want to use while streaming your application.

Type: String

Valid Values: TCP | UDP

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Theme

The custom branding theme, which might include a custom logo, website links, and other branding to display to users.

Contents

CreatedTime

The time the theme was created.

Type: Timestamp

Required: No

StackName

The stack that has the custom branding theme.

Type: String

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_.-]{0,100}$`

Required: No

State

The state of the theme.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

ThemeFaviconURL

The URL of the icon that displays at the top of a user's browser tab during streaming sessions.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ThemeFooterLinks

The website links that display in the catalog page footer.

Type: Array of [ThemeFooterLink](#) objects

Required: No

ThemeOrganizationLogoURL

The URL of the logo that displays in the catalog page header.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ThemeStyling

The color that is used for the website links, text, buttons, and catalog page background.

Type: String

Valid Values: LIGHT_BLUE | BLUE | PINK | RED

Required: No

ThemeTitleText

The browser tab page title.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: ^[-@./#&+\w\s]*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ThemeFooterLink

The website links that display in the catalog page footer.

Contents

DisplayName

The name of the websites that display in the catalog page footer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Pattern: `^[-@./#&+\w\s]*$`

Required: No

FooterLinkURL

The URL of the websites that display in the catalog page footer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UsageReportSubscription

Describes information about the usage report subscription.

Contents

LastGeneratedReportDate

The time when the last usage report was generated.

Type: Timestamp

Required: No

S3BucketName

The Amazon S3 bucket where generated reports are stored.

If you enabled on-instance session scripts and Amazon S3 logging for your session script configuration, AppStream 2.0 created an S3 bucket to store the script output. The bucket is unique to your account and Region. When you enable usage reporting in this case, AppStream 2.0 uses the same bucket to store your usage reports. If you haven't already enabled on-instance session scripts, when you enable usage reports, AppStream 2.0 creates a new S3 bucket.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Schedule

The schedule for generating usage reports.

Type: String

Valid Values: DAILY

Required: No

SubscriptionErrors

The errors that were returned if usage reports couldn't be generated.

Type: Array of [LastReportGenerationExecutionError](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

User

Describes a user in the user pool.

Contents

AuthenticationType

The authentication type for the user.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: Yes

Arn

The ARN of the user.

Type: String

Pattern: `^arn:aws(?:\-cn|\-iso\-b|\-iso|\-us\-gov)?:[A-Za-z0-9][A-Za-z0-9_/.-]{0,62}:[A-Za-z0-9_/.-]{0,63}:[A-Za-z0-9][A-Za-z0-9_/_+=, @.\-]{0,1023}$`

Required: No

CreatedTime

The date and time the user was created in the user pool.

Type: Timestamp

Required: No

Enabled

Specifies whether the user in the user pool is enabled.

Type: Boolean

Required: No

FirstName

The first name, or given name, of the user.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[A-Za-z0-9_-\s]+$`

Required: No

LastName

The last name, or surname, of the user.

Type: String

Length Constraints: Maximum length of 2048.

Pattern: `^[A-Za-z0-9_-\s]+$`

Required: No

Status

The status of the user in the user pool. The status can be one of the following:

- UNCONFIRMED – The user is created but not confirmed.
- CONFIRMED – The user is confirmed.
- ARCHIVED – The user is no longer active.
- COMPROMISED – The user is disabled because of a potential security threat.
- UNKNOWN – The user status is not known.

Type: String

Length Constraints: Minimum length of 1.

Required: No

UserName

The email address of the user.

Note

Users' email addresses are case-sensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{M}\p{S}\p{N}\p{P}]`+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserSetting

Describes an action and whether the action is enabled or disabled for users during their streaming sessions.

Contents

Action

The action that is enabled or disabled.

Type: String

Valid Values: CLIPBOARD_COPY_FROM_LOCAL_DEVICE |
CLIPBOARD_COPY_TO_LOCAL_DEVICE | FILE_UPLOAD | FILE_DOWNLOAD
| PRINTING_TO_LOCAL_DEVICE | DOMAIN_PASSWORD_SIGNIN |
DOMAIN_SMART_CARD_SIGNIN | AUTO_TIME_ZONE_REDIRECTION

Required: Yes

Permission

Indicates whether the action is enabled or disabled.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

MaxLength

Specifies the number of characters that can be copied by end users from the local device to the remote session, and to the local device from the remote session.

This can be specified only for the CLIPBOARD_COPY_FROM_LOCAL_DEVICE and CLIPBOARD_COPY_TO_LOCAL_DEVICE actions.

This defaults to 20,971,520 (20 MB) when unspecified and the permission is ENABLED. This can't be specified when the permission is DISABLED.

The value can be between 1 and 20,971,520 (20 MB).

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserStackAssociation

Describes a user in the user pool and the associated stack.

Contents

AuthenticationType

The authentication type for the user.

Type: String

Valid Values: API | SAML | USERPOOL | AWS_AD

Required: Yes

StackName

The name of the stack that is associated with the user.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

UserName

The email address of the user who is associated with the stack.

Note

Users' email addresses are case-sensitive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{M}\p{S}\p{N}\p{P}]+`

Required: Yes

SendEmailNotification

Specifies whether a welcome email is sent to a user after the user is created in the user pool.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserStackAssociationError

Describes the error that is returned when a user can't be associated with or disassociated from a stack.

Contents

ErrorCode

The error code for the error that is returned when a user can't be associated with or disassociated from a stack.

Type: String

Valid Values: STACK_NOT_FOUND | USER_NAME_NOT_FOUND | DIRECTORY_NOT_FOUND | INTERNAL_ERROR

Required: No

ErrorMessage

The error message for the error that is returned when a user can't be associated with or disassociated from a stack.

Type: String

Length Constraints: Minimum length of 1.

Required: No

UserStackAssociation

Information about the user and associated stack.

Type: [UserStackAssociation](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcConfig

Describes VPC configuration information for fleets and image builders.

Contents

SecurityGroupIds

The identifiers of the security groups for the fleet or image builder.

Type: Array of strings

Array Members: Maximum number of 5 items.

Length Constraints: Minimum length of 1.

Required: No

SubnetIds

The identifiers of the subnets to which a network interface is attached from the fleet instance or image builder instance. Fleet instances use one or more subnets. Image builder instances use one subnet.

Type: Array of strings

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400