



API Reference

AWS Support



API Version 2013-04-15

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Support: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	3
AddAttachmentsToSet	4
Request Syntax	4
Request Parameters	4
Response Syntax	5
Response Elements	5
Errors	6
See Also	6
AddCommunicationToCase	8
Request Syntax	8
Request Parameters	8
Response Syntax	9
Response Elements	9
Errors	10
See Also	10
CreateCase	12
Request Syntax	12
Request Parameters	13
Response Syntax	15
Response Elements	15
Errors	15
See Also	16
DescribeAttachment	17
Request Syntax	17
Request Parameters	17
Response Syntax	18
Response Elements	18
Errors	18
See Also	19
DescribeCases	20
Request Syntax	20
Request Parameters	21
Response Syntax	22

Response Elements	23
Errors	23
See Also	24
DescribeCommunications	25
Request Syntax	25
Request Parameters	25
Response Syntax	26
Response Elements	27
Errors	27
See Also	28
DescribeCreateCaseOptions	29
Request Syntax	29
Request Parameters	29
Response Syntax	30
Response Elements	31
Errors	31
See Also	32
DescribeServices	33
Request Syntax	33
Request Parameters	33
Response Syntax	34
Response Elements	34
Errors	34
See Also	35
DescribeSeverityLevels	36
Request Syntax	36
Request Parameters	36
Response Syntax	36
Response Elements	37
Errors	37
See Also	37
DescribeSupportedLanguages	39
Request Syntax	39
Request Parameters	39
Response Syntax	40
Response Elements	40

Errors	40
See Also	41
DescribeTrustedAdvisorCheckRefreshStatuses	42
Request Syntax	42
Request Parameters	42
Response Syntax	43
Response Elements	43
Errors	43
See Also	44
DescribeTrustedAdvisorCheckResult	45
Request Syntax	45
Request Parameters	46
Response Syntax	46
Response Elements	47
Errors	47
See Also	48
DescribeTrustedAdvisorChecks	49
Request Syntax	49
Request Parameters	49
Response Syntax	50
Response Elements	50
Errors	51
See Also	51
DescribeTrustedAdvisorCheckSummaries	52
Request Syntax	52
Request Parameters	52
Response Syntax	53
Response Elements	53
Errors	53
See Also	54
RefreshTrustedAdvisorCheck	55
Request Syntax	55
Request Parameters	55
Response Syntax	56
Response Elements	56
Errors	56

See Also	57
ResolveCase	58
Request Syntax	58
Request Parameters	58
Response Syntax	58
Response Elements	59
Errors	59
See Also	59
Data Types	61
Attachment	63
Contents	63
See Also	63
AttachmentDetails	64
Contents	64
See Also	64
CaseDetails	65
Contents	66
See Also	68
Category	69
Contents	69
See Also	69
Communication	70
Contents	70
See Also	71
CommunicationTypeOptions	72
Contents	72
See Also	72
DateInterval	74
Contents	74
See Also	74
RecentCaseCommunications	75
Contents	75
See Also	75
Service	76
Contents	76
See Also	76

SeverityLevel	77
Contents	77
See Also	78
SupportedHour	79
Contents	79
See Also	79
SupportedLanguage	80
Contents	80
See Also	80
TrustedAdvisorCategorySpecificSummary	81
Contents	81
See Also	81
TrustedAdvisorCheckDescription	82
Contents	82
See Also	82
TrustedAdvisorCheckRefreshStatus	84
Contents	84
See Also	84
TrustedAdvisorCheckResult	85
Contents	85
See Also	86
TrustedAdvisorCheckSummary	87
Contents	87
See Also	88
TrustedAdvisorCostOptimizingSummary	89
Contents	89
See Also	89
TrustedAdvisorResourceDetail	90
Contents	90
See Also	90
TrustedAdvisorResourcesSummary	92
Contents	92
See Also	92
Common Parameters	93
Common Errors	96

Welcome

The *AWS Support API Reference* is intended for programmers who need detailed information about the AWS Support operations and data types. You can use the API to manage your support cases programmatically. The AWS Support API uses HTTP methods that return results in JSON format.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

You can also use the AWS Support API to access features for [AWS Trusted Advisor](#). You can return a list of checks and their descriptions, get check results, specify checks to refresh, and get the refresh status of checks.

You can manage your support cases with the following AWS Support API operations:

- The [CreateCase](#), [DescribeCases](#), [DescribeAttachment](#), and [ResolveCase](#) operations create AWS Support cases, retrieve information about cases, and resolve cases.
- The [DescribeCommunications](#), [AddCommunicationToCase](#), and [AddAttachmentsToSet](#) operations retrieve and add communications and attachments to AWS Support cases.
- The [DescribeServices](#) and [DescribeSeverityLevels](#) operations return AWS service names, service codes, service categories, and problem severity levels. You use these values when you call the [CreateCase](#) operation.

You can also use the AWS Support API to call the Trusted Advisor operations. For more information, see [AWS Trusted Advisor](#) in the *AWS Support User Guide*.

For authentication of requests, AWS Support uses [Signature Version 4 Signing Process](#).

For more information about this service and the endpoints to use, see [About the AWS Support API](#) in the *AWS Support User Guide*.

This document was last published on March 20, 2024.

Actions

The following actions are supported:

- [AddAttachmentsToSet](#)
- [AddCommunicationToCase](#)
- [CreateCase](#)
- [DescribeAttachment](#)
- [DescribeCases](#)
- [DescribeCommunications](#)
- [DescribeCreateCaseOptions](#)
- [DescribeServices](#)
- [DescribeSeverityLevels](#)
- [DescribeSupportedLanguages](#)
- [DescribeTrustedAdvisorCheckRefreshStatuses](#)
- [DescribeTrustedAdvisorCheckResult](#)
- [DescribeTrustedAdvisorChecks](#)
- [DescribeTrustedAdvisorCheckSummaries](#)
- [RefreshTrustedAdvisorCheck](#)
- [ResolveCase](#)

AddAttachmentsToSet

Adds one or more attachments to an attachment set.

An attachment set is a temporary container for attachments that you add to a case or case communication. The set is available for 1 hour after it's created. The `expiryTime` returned in the response is when the set expires.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "attachments": [  
    {  
      "data": blob,  
      "fileName": "string"  
    }  
  ],  
  "attachmentSetId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attachments

One or more attachments to add to the set. You can add up to three attachments per set. The size limit is 5 MB per attachment.

In the Attachment object, use the data parameter to specify the contents of the attachment file. In the previous request syntax, the value for data appear as blob, which is represented as a base64-encoded string. The value for fileName is the name of the attachment, such as troubleshoot-screenshot.png.

Type: Array of [Attachment](#) objects

attachmentSetId

The ID of the attachment set. If an attachmentSetId is not specified, a new attachment set is created, and the ID of the set is returned in the response. If an attachmentSetId is specified, the attachments are added to the specified set, if it exists.

Type: String

Response Syntax

```
{  
    "attachmentSetId": "string",  
    "expiryTime": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

attachmentSetId

The ID of the attachment set. If an attachmentSetId was not specified, a new attachment set is created, and the ID of the set is returned in the response. If an attachmentSetId was specified, the attachments are added to the specified set, if it exists.

Type: String

expiryTime

The time and date when the attachment set expires.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AttachmentLimitExceeded

The limit for the number of attachment sets created in a short period of time has been exceeded.

HTTP Status Code: 400

AttachmentSetExpired

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

AttachmentSetIdNotFound

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

AttachmentSetSizeLimitExceeded

A limit for the size of an attachment set has been exceeded. The limits are three attachments and 5 MB per attachment.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AddCommunicationToCase

Adds additional customer communication to an AWS Support case. Use the `caseId` parameter to identify the case to which to add communication. You can list a set of email addresses to copy on the communication by using the `ccEmailAddresses` parameter. The `communicationBody` value contains the text of the communication.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "attachmentSetId": "string",  
  "caseId": "string",  
  "ccEmailAddresses": [ "string" ],  
  "communicationBody": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[attachmentSetId](#)

The ID of a set of one or more attachments for the communication to add to the case. Create the set by calling [AddAttachmentsToSet](#)

Type: String

caseId

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

ccEmailAddresses

The email addresses in the CC line of an email to be added to the support case.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

communicationBody

The body of an email communication to add to the support case.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

Response Syntax

```
{  
  "result": boolean  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

result

True if [AddCommunicationToCase](#) succeeds. Otherwise, returns an error.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AttachmentSetExpired

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

AttachmentSetIdNotFound

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

CaseIdNotFound

The requested caseId couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

CreateCase

Creates a case in the AWS Support Center. This operation is similar to how you create a case in the AWS Support Center [Create Case](#) page.

The AWS Support API doesn't support requesting service limit increases. You can submit a service limit increase in the following ways:

- Submit a request from the AWS Support Center [Create Case](#) page.
- Use the Service Quotas [RequestServiceQuotaIncrease](#) operation.

A successful CreateCase request returns an AWS Support case number. You can use the [DescribeCases](#) operation and specify the case number to get existing AWS Support cases. After you create a case, use the [AddCommunicationToCase](#) operation to add additional communication or attachments to an existing case.

The caseId is separate from the displayId that appears in the [AWS Support Center](#). Use the [DescribeCases](#) operation to get the displayId.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the SubscriptionRequiredException error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "attachmentSetId": "string",  
  "categoryCode": "string",  
  "ccEmailAddresses": [ "string" ],  
  "communicationBody": "string",  
  "issueType": "string",  
  "language": "string",  
}
```

```
"serviceCode": "string",
"severityCode": "string",
"subject": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[attachmentSetId](#)

The ID of a set of one or more attachments for the case. Create the set by using the [AddAttachmentsToSet](#) operation.

Type: String

[categoryCode](#)

The category of problem for the support case. You also use the [DescribeServices](#) operation to get the category code for a service. Each AWS service defines its own set of category codes.

Type: String

[ccEmailAddresses](#)

A list of email addresses that AWS Support copies on case correspondence. AWS Support identifies the account that creates the case when you specify your AWS credentials in an HTTP POST method or use the [AWS SDKs](#).

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

[communicationBody](#)

The communication body text that describes the issue. This text appears in the **Description** field on the AWS Support Center [Create Case](#) page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

issueType

The type of issue for the case. You can specify customer-service or technical. If you don't specify a value, the default is technical.

Type: String

language

The language in which AWS Support handles the case. AWS Support currently supports Chinese ("zh"), English ("en"), Japanese ("ja") and Korean ("ko"). You must specify the ISO 639-1 code for the language parameter if you want support in that language.

Type: String

serviceCode

The code for the AWS service. You can use the [DescribeServices](#) operation to get the possible serviceCode values.

Type: String

severityCode

A value that indicates the urgency of the case. This value determines the response time according to your service level agreement with AWS Support. You can use the [DescribeSeverityLevels](#) operation to get the possible values for severityCode.

For more information, see [SeverityLevel](#) and [Choosing a Severity](#) in the *AWS Support User Guide*.

 **Note**

The availability of severity levels depends on the support plan for the AWS account.

Type: String

subject

The title of the support case. The title appears in the **Subject** field on the AWS Support Center [Create Case](#) page.

Type: String

Response Syntax

```
{  
    "caseId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[caseld](#)

The support case ID requested or returned in the call. The case ID is an alphanumeric string in the following format: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AttachmentSetExpired

The expiration time of the attachment set has passed. The set expires 1 hour after it is created.

HTTP Status Code: 400

AttachmentSetIdNotFound

An attachment set with the specified ID could not be found.

HTTP Status Code: 400

CaseCreationLimitExceeded

The case creation limit for the account has been exceeded.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAttachment

Returns the attachment that has the specified ID. Attachments can include screenshots, error logs, or other files that describe your issue. Attachment IDs are generated by the case management system when you add an attachment to a case or case communication. Attachment IDs are returned in the [AttachmentDetails](#) objects that are returned by the [DescribeCommunications](#) operation.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "attachmentId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

attachmentId

The ID of the attachment to return. Attachment IDs are returned by the [DescribeCommunications](#) operation.

Type: String

Response Syntax

```
{  
  "attachment": {  
    "data": blob,  
    "fileName": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

attachment

This object includes the attachment content and file name.

In the previous response syntax, the value for the data parameter appears as *blob*, which is represented as a base64-encoded string. The value for *fileName* is the name of the attachment, such as troubleshoot-screenshot.png.

Type: [Attachment](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AttachmentIdNotFound

An attachment with the specified ID could not be found.

HTTP Status Code: 400

DescribeAttachmentLimitExceeded

The limit for the number of [DescribeAttachment](#) requests in a short period of time has been exceeded.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCases

Returns a list of cases that you specify by passing one or more case IDs. You can use the `afterTime` and `beforeTime` parameters to filter the cases by date. You can set values for the `includeResolvedCases` and `includeCommunications` parameters to specify how much information to return.

The response returns the following in JSON format:

- One or more [CaseDetails](#) data types.
- One or more `nextToken` values, which specify where to paginate the returned records represented by the `CaseDetails` objects.

Case data is available for 12 months after creation. If a case was created more than 12 months ago, a request might return an error.

 **Note**

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
    "afterTime": "string",  
    "beforeTime": "string",  
    "caseIdList": [ "string" ],  
    "displayId": "string",  
    "includeCommunications": boolean,  
    "includeResolvedCases": boolean,  
    "language": "string",  
    "maxResults": number,  
    "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

afterTime

The start date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

beforeTime

The end date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

caseIdList

A list of ID numbers of the support cases you want returned. The maximum number of cases is 100.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

displayId

The ID displayed for a case in the AWS Support Center user interface.

Type: String

includeCommunications

Specifies whether to include communications in the `DescribeCases` response. By default, communications are included.

Type: Boolean

includeResolvedCases

Specifies whether to include resolved support cases in the `DescribeCases` response. By default, resolved cases aren't included.

Type: Boolean

language

The language in which AWS Support handles the case. AWS Support currently supports Chinese ("zh"), English ("en"), Japanese ("ja") and Korean ("ko"). You must specify the ISO 639-1 code for the language parameter if you want support in that language.

Type: String

maxResults

The maximum number of results to return before paginating.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

nextToken

A resumption point for pagination.

Type: String

Response Syntax

```
{  
  "cases": [  
    {  
      "caseId": "string",  
      "categoryCode": "string",  
      "ccEmailAddresses": [ "string" ],  
      "displayId": "string",  
      "language": "string",  
      "recentCommunications": {  
        "communications": [  
          {  
            "attachmentSet": [  
              {  
                "attachmentId": "string",  
                "fileName": "string"  
              }  
            ],  
            "body": "string",  
            "displayId": "string",  
            "language": "string",  
            "recipients": [ "string" ]  
          }  
        ]  
      }  
    }  
  ]  
}
```

```
        "caseId": "string",
        "submittedBy": "string",
        "timeCreated": "string"
    }
],
"nextToken": "string"
},
"serviceCode": "string",
"severityCode": "string",
"status": "string",
"subject": "string",
"submittedBy": "string",
"timeCreated": "string"
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[cases](#)

The details for the cases that match the request.

Type: Array of [CaseDetails](#) objects

[nextToken](#)

A resumption point for pagination.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CASEIDNOTFOUND

The requested caseId couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCommunications

Returns communications and attachments for one or more support cases. Use the `afterTime` and `beforeTime` parameters to filter by date. You can use the `caseId` parameter to restrict the results to a specific case.

Case data is available for 12 months after creation. If a case was created more than 12 months ago, a request for data might cause an error.

You can use the `maxResults` and `nextToken` parameters to control the pagination of the results. Set `maxResults` to the number of cases that you want to display on each page, and use `nextToken` to specify the resumption of pagination.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "afterTime": "string",  
  "beforeTime": "string",  
  "caseId": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

afterTime

The start date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

beforeTime

The end date for a filtered date search on support case communications. Case communications are available for 12 months after creation.

Type: String

caseId

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

maxResults

The maximum number of results to return before paginating.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

nextToken

A resumption point for pagination.

Type: String

Response Syntax

```
{  
  "communications": [  
    {  
      "attachmentSet": [  
        {  
          "attachmentId": "string",  
          "fileName": "string"  
        }  
      ]  
    }  
  ]  
}
```

```
        ],
        "body": "string",
        "caseId": "string",
        "submittedBy": "string",
        "timeCreated": "string"
    }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[communications](#)

The communications for the case.

Type: Array of [Communication](#) objects

[nextToken](#)

A resumption point for pagination.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CaseIdNotFound

The requested caseId couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCreateCaseOptions

Returns a list of CreateCaseOption types along with the corresponding supported hours and language availability. You can specify the `language`, `categoryCode`, `issueType` and `serviceCode` used to retrieve the CreateCaseOptions.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
    "categoryCode": "string",  
    "issueType": "string",  
    "language": "string",  
    "serviceCode": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[categoryCode](#)

The category of problem for the support case. You also use the [DescribeServices](#) operation to get the category code for a service. Each AWS service defines its own set of category codes.

Type: String

issueType

The type of issue for the case. You can specify customer-service or technical. If you don't specify a value, the default is technical.

Type: String

language

The language in which AWS Support handles the case. AWS Support currently supports Chinese ("zh"), English ("en"), Japanese ("ja") and Korean ("ko"). You must specify the ISO 639-1 code for the language parameter if you want support in that language.

Type: String

serviceCode

The code for the AWS service. You can use the [DescribeServices](#) operation to get the possible serviceCode values.

Type: String

Response Syntax

```
{
  "communicationTypes": [
    {
      "datesWithoutSupport": [
        {
          "endDateTime": "string",
          "startDateTime": "string"
        }
      ],
      "supportedHours": [
        {
          "endTime": "string",
          "startTime": "string"
        }
      ],
      "type": "string"
    }
  ],
  "languageAvailability": "string"
```

{}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[communicationTypes](#)

A JSON-formatted array that contains the available communication type options, along with the available support timeframes for the given inputs.

Type: Array of [CommunicationTypeOptions](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

[languageAvailability](#)

Language availability can be any of the following:

- available
- best_effort
- unavailable

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

ThrottlingException

You have exceeded the maximum allowed TPS (Transactions Per Second) for the operations.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeServices

Returns the current list of AWS services and a list of service categories for each service. You then use service names and categories in your [CreateCase](#) requests. Each AWS service has its own set of categories.

The service codes and category codes correspond to the values that appear in the **Service** and **Category** lists on the AWS Support Center [Create Case](#) page. The values in those fields don't necessarily match the service codes and categories returned by the `DescribeServices` operation. Always use the service codes and categories that the `DescribeServices` operation returns, so that you have the most recent set of service and category codes.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "language": "string",  
  "serviceCodeList": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[language](#)

The language in which AWS Support handles the case. AWS Support currently supports Chinese ("zh"), English ("en"), Japanese ("ja") and Korean ("ko"). You must specify the ISO 639-1 code for the `language` parameter if you want support in that language.

Type: String

serviceCodeList

A JSON-formatted list of service codes available for AWS services.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Response Syntax

```
{  
  "services": [  
    {  
      "categories": [  
        {  
          "code": "string",  
          "name": "string"  
        }  
      ],  
      "code": "string",  
      "name": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

services

A JSON-formatted list of AWS services.

Type: Array of [Service](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeSeverityLevels

Returns the list of severity levels that you can assign to a support case. The severity level for a case is also a field in the [CaseDetails](#) data type that you include for a [CreateCase](#) request.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
    "language": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[language](#)

The language in which AWS Support handles the case. AWS Support currently supports Chinese ("zh"), English ("en"), Japanese ("ja") and Korean ("ko"). You must specify the ISO 639-1 code for the `language` parameter if you want support in that language.

Type: String

Response Syntax

```
{  
    "severityLevels": [  
        "string"  
    ]  
}
```

```
{  
    "code": "string",  
    "name": "string"  
}  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[severityLevels](#)

The available severity levels for the support case. Available severity levels are defined by your service level agreement with AWS.

Type: Array of [SeverityLevel](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeSupportedLanguages

Returns a list of supported languages for a specified `categoryCode`, `issueType` and `serviceCode`. The returned supported languages will include a ISO 639-1 code for the language, and the language display name.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
    "categoryCode": "string",  
    "issueType": "string",  
    "serviceCode": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

categoryCode

The category of problem for the support case. You also use the [DescribeServices](#) operation to get the category code for a service. Each AWS service defines its own set of category codes.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

issueType

The type of issue for the case. You can specify `customer-service` or `technical`.

Type: String

Length Constraints: Minimum length of 9. Maximum length of 22.

serviceCode

The code for the AWS service. You can use the [DescribeServices](#) operation to get the possible serviceCode values.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Response Syntax

```
{  
    "supportedLanguages": [  
        {  
            "code": "string",  
            "display": "string",  
            "language": "string"  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

supportedLanguages

A JSON-formatted array that contains the available ISO 639-1 language codes.

Type: Array of [SupportedLanguage](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

ThrottlingException

You have exceeded the maximum allowed TPS (Transactions Per Second) for the operations.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorCheckRefreshStatuses

Returns the refresh status of the AWS Trusted Advisor checks that have the specified check IDs. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) operation.

Some checks are refreshed automatically, and you can't return their refresh statuses by using the `DescribeTrustedAdvisorCheckRefreshStatuses` operation. If you call this operation for these checks, you might see an `InvalidParameterValue` error.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

To call the AWS Trusted Advisor operations in the AWS Support API, you must use the US East (N. Virginia) endpoint. Currently, the US West (Oregon) and Europe (Ireland) endpoints don't support the Trusted Advisor operations. For more information, see [About the AWS Support API](#) in the [AWS Support User Guide](#).

Request Syntax

```
{  
    "checkIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

checkIds

The IDs of the Trusted Advisor checks to get the status.

Note

If you specify the check ID of a check that is automatically refreshed, you might see an `InvalidParameterValue` error.

Type: Array of strings

Response Syntax

```
{  
  "statuses": [  
    {  
      "checkId": "string",  
      "millisUntilNextRefreshable": number,  
      "status": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

statuses

The refresh status of the specified Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckRefreshStatus](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

ThrottlingException

You have exceeded the maximum allowed TPS (Transactions Per Second) for the operations.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorCheckResult

Returns the results of the AWS Trusted Advisor check that has the specified check ID. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) operation.

The response contains a [TrustedAdvisorCheckResult](#) object, which contains these three objects:

- [TrustedAdvisorCategorySpecificSummary](#)
- [TrustedAdvisorResourceDetail](#)
- [TrustedAdvisorResourcesSummary](#)

In addition, the response contains these fields:

- **status** - The alert status of the check can be ok (green), warning (yellow), error (red), or not_available.
- **timestamp** - The time of the last refresh of the check.
- **checkId** - The unique identifier for the check.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the SubscriptionRequiredException error message appears. For information about changing your support plan, see [AWS Support](#).

To call the AWS Trusted Advisor operations in the AWS Support API, you must use the US East (N. Virginia) endpoint. Currently, the US West (Oregon) and Europe (Ireland) endpoints don't support the Trusted Advisor operations. For more information, see [About the AWS Support API](#) in the [AWS Support User Guide](#).

Request Syntax

```
{  
  "checkId": "string",
```

```
    "language": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[checkId](#)

The unique identifier for the Trusted Advisor check.

Type: String

[language](#)

The ISO 639-1 code for the language that you want your check results to appear in.

The AWS Support API currently supports the following languages for Trusted Advisor:

- Chinese, Simplified - zh
- Chinese, Traditional - zh_TW
- English - en
- French - fr
- German - de
- Indonesian - id
- Italian - it
- Japanese - ja
- Korean - ko
- Portuguese, Brazilian - pt_BR
- Spanish - es

Type: String

Response Syntax

```
{  
    "result": {
```

```
"categorySpecificSummary": {  
    "costOptimizing": {  
        "estimatedMonthlySavings": number,  
        "estimatedPercentMonthlySavings": number  
    }  
},  
"checkId": "string",  
"flaggedResources": [  
    {  
        "isSuppressed": boolean,  
        "metadata": [ "string" ],  
        "region": "string",  
        "resourceId": "string",  
        "status": "string"  
    }  
],  
"resourcesSummary": {  
    "resourcesFlagged": number,  
    "resourcesIgnored": number,  
    "resourcesProcessed": number,  
    "resourcesSuppressed": number  
},  
"status": "string",  
"timestamp": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

result

The detailed results of the Trusted Advisor check.

Type: [TrustedAdvisorCheckResult](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

ThrottlingException

You have exceeded the maximum allowed TPS (Transactions Per Second) for the operations.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorChecks

Returns information about all available AWS Trusted Advisor checks, including the name, ID, category, description, and metadata. You must specify a language code.

The response contains a [TrustedAdvisorCheckDescription](#) object for each check. You must set the AWS Region to us-east-1.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).
- The names and descriptions for Trusted Advisor checks are subject to change. We recommend that you specify the check ID in your code to uniquely identify a check.

To call the AWS Trusted Advisor operations in the AWS Support API, you must use the US East (N. Virginia) endpoint. Currently, the US West (Oregon) and Europe (Ireland) endpoints don't support the Trusted Advisor operations. For more information, see [About the AWS Support API](#) in the [AWS Support User Guide](#).

Request Syntax

```
{  
    "language": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

language

The ISO 639-1 code for the language that you want your checks to appear in.

The AWS Support API currently supports the following languages for Trusted Advisor:

- Chinese, Simplified - zh
- Chinese, Traditional - zh_TW
- English - en
- French - fr
- German - de
- Indonesian - id
- Italian - it
- Japanese - ja
- Korean - ko
- Portuguese, Brazilian - pt_BR
- Spanish - es

Type: String

Response Syntax

```
{  
  "checks": [  
    {  
      "category": "string",  
      "description": "string",  
      "id": "string",  
      "metadata": [ "string" ],  
      "name": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[checks](#)

Information about all available Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckDescription](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

ThrottlingException

You have exceeded the maximum allowed TPS (Transactions Per Second) for the operations.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeTrustedAdvisorCheckSummaries

Returns the results for the AWS Trusted Advisor check summaries for the check IDs that you specified. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) operation.

The response contains an array of [TrustedAdvisorCheckSummary](#) objects.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

To call the AWS Trusted Advisor operations in the AWS Support API, you must use the US East (N. Virginia) endpoint. Currently, the US West (Oregon) and Europe (Ireland) endpoints don't support the Trusted Advisor operations. For more information, see [About the AWS Support API](#) in the [AWS Support User Guide](#).

Request Syntax

```
{  
    "checkIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

checkIds

The IDs of the Trusted Advisor checks.

Type: Array of strings

Response Syntax

```
{  
  "summaries": [  
    {  
      "categorySpecificSummary": {  
        "costOptimizing": {  
          "estimatedMonthlySavings": number,  
          "estimatedPercentMonthlySavings": number  
        }  
      },  
      "checkId": "string",  
      "hasFlaggedResources": boolean,  
      "resourcesSummary": {  
        "resourcesFlagged": number,  
        "resourcesIgnored": number,  
        "resourcesProcessed": number,  
        "resourcesSuppressed": number  
      },  
      "status": "string",  
      "timestamp": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

summaries

The summary information for the requested Trusted Advisor checks.

Type: Array of [TrustedAdvisorCheckSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

ThrottlingException

You have exceeded the maximum allowed TPS (Transactions Per Second) for the operations.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RefreshTrustedAdvisorCheck

Refreshes the AWS Trusted Advisor check that you specify using the check ID. You can get the check IDs by calling the [DescribeTrustedAdvisorChecks](#) operation.

Some checks are refreshed automatically. If you call the RefreshTrustedAdvisorCheck operation to refresh them, you might see the InvalidParameterValue error.

The response contains a [TrustedAdvisorCheckRefreshStatus](#) object.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the SubscriptionRequiredException error message appears. For information about changing your support plan, see [AWS Support](#).

To call the AWS Trusted Advisor operations in the AWS Support API, you must use the US East (N. Virginia) endpoint. Currently, the US West (Oregon) and Europe (Ireland) endpoints don't support the Trusted Advisor operations. For more information, see [About the AWS Support API](#) in the *AWS Support User Guide*.

Request Syntax

```
{  
    "checkId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[checkId](#)

The unique identifier for the Trusted Advisor check to refresh.

Note

Specifying the check ID of a check that is automatically refreshed causes an `InvalidParameterValue` error.

Type: String

Response Syntax

```
{  
  "status": {  
    "checkId": "string",  
    "millisUntilNextRefreshable": number,  
    "status": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

status

The current refresh status for a check, including the amount of time until the check is eligible for refresh.

Type: [TrustedAdvisorCheckRefreshStatus](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResolveCase

Resolves a support case. This operation takes a `caseId` and returns the initial and final state of the case.

Note

- You must have a Business, Enterprise On-Ramp, or Enterprise Support plan to use the AWS Support API.
- If you call the AWS Support API from an account that doesn't have a Business, Enterprise On-Ramp, or Enterprise Support plan, the `SubscriptionRequiredException` error message appears. For information about changing your support plan, see [AWS Support](#).

Request Syntax

```
{  
  "caseId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

caseId

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: `case-12345678910-2013-c4c1d2bf33c5cf47`

Type: String

Response Syntax

```
{  
  "finalCaseStatus": "string",  
  "initialCaseStatus": "string"
```

{}

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[finalCaseStatus](#)

The status of the case after the [ResolveCase](#) request was processed.

Type: String

[initialCaseStatus](#)

The status of the case when the [ResolveCase](#) request was sent.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

CaseIdNotFound

The requested caseId couldn't be located.

HTTP Status Code: 400

InternalServerError

An internal server error occurred.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Support API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Attachment](#)
- [AttachmentDetails](#)
- [CaseDetails](#)
- [Category](#)
- [Communication](#)
- [CommunicationTypeOptions](#)
- [DateInterval](#)
- [RecentCaseCommunications](#)
- [Service](#)
- [SeverityLevel](#)
- [SupportedHour](#)
- [SupportedLanguage](#)
- [TrustedAdvisorCategorySpecificSummary](#)
- [TrustedAdvisorCheckDescription](#)
- [TrustedAdvisorCheckRefreshStatus](#)
- [TrustedAdvisorCheckResult](#)
- [TrustedAdvisorCheckSummary](#)
- [TrustedAdvisorCostOptimizingSummary](#)
- [TrustedAdvisorResourceDetail](#)
- [TrustedAdvisorResourcesSummary](#)

Attachment

An attachment to a case communication. The attachment consists of the file name and the content of the file. Each attachment file size should not exceed 5 MB. File types that are supported include the following: pdf, jpeg,.doc, .log, .text

Contents

data

The content of the attachment file.

Type: Base64-encoded binary data object

fileName

The name of the attachment file.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AttachmentDetails

The file name and ID of an attachment to a case communication. You can use the ID to retrieve the attachment with the [DescribeAttachment](#) operation.

Contents

attachmentId

The ID of the attachment.

Type: String

fileName

The file name of the attachment.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CaseDetails

A JSON-formatted object that contains the metadata for a support case. It is contained in the response from a [DescribeCases](#) request. **CaseDetails** contains the following fields:

- **caseId** - The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: case-12345678910-2013-c4c1d2bf33c5cf47.
- **categoryCode** - The category of problem for the support case. Corresponds to the CategoryCode values returned by a call to [DescribeServices](#).
- **displayId** - The identifier for the case on pages in the AWS Support Center.
- **language** - The language in which AWS Support handles the case. AWS Support currently supports Chinese ("zh"), English ("en"), Japanese ("ja") and Korean ("ko"). You must specify the ISO 639-1 code for the language parameter if you want support in that language.
- **nextToken** - A resumption point for pagination.
- **recentCommunications** - One or more [Communication](#) objects. Fields of these objects are attachments, body, caseId, submittedBy, and timeCreated.
- **serviceCode** - The identifier for the AWS service that corresponds to the service code defined in the call to [DescribeServices](#).
- **severityCode** - The severity code assigned to the case. Contains one of the values returned by the call to [DescribeSeverityLevels](#). The possible values are: low, normal, high, urgent, and critical.
- **status** - The status of the case in the AWS Support Center. Valid values:
 - opened
 - pending-customer-action
 - reopened
 - resolved
 - unassigned
 - work-in-progress
- **subject** - The subject line of the case.
- **submittedBy** - The email address of the account that submitted the case.
- **timeCreated** - The time the case was created, in ISO-8601 format.

Contents

caseId

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

categoryCode

The category of problem for the support case.

Type: String

ccEmailAddresses

The email addresses that receive copies of communication about the case.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 10 items.

displayId

The ID displayed for the case in the AWS Support Center. This is a numeric string.

Type: String

language

The language in which AWS Support handles the case. AWS Support currently supports Chinese ("zh"), English ("en"), Japanese ("ja") and Korean ("ko"). You must specify the ISO 639-1 code for the language parameter if you want support in that language.

Type: String

recentCommunications

The five most recent communications between you and AWS Support Center, including the IDs of any attachments to the communications. Also includes a nextToken that you can use to retrieve earlier communications.

Type: [RecentCaseCommunications](#) object

serviceCode

The code for the AWS service. You can get a list of codes and the corresponding service names by calling [DescribeServices](#).

Type: String

severityCode

The code for the severity level returned by the call to [DescribeSeverityLevels](#).

Type: String

status

The status of the case.

Valid values:

- opened
- pending-customer-action
- reopened
- resolved
- unassigned
- work-in-progress

Type: String

subject

The subject line for the case in the AWS Support Center.

Type: String

submittedBy

The email address of the account that submitted the case.

Type: String

timeCreated

The time that the case was created in the AWS Support Center.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Category

A JSON-formatted name/value pair that represents the category name and category code of the problem, selected from the [DescribeServices](#) response for each AWS service.

Contents

code

The category code for the support case.

Type: String

name

The category name for the support case.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Communication

A communication associated with a support case. The communication consists of the case ID, the message body, attachment information, the submitter of the communication, and the date and time of the communication.

Contents

attachmentSet

Information about the attachments to the case communication.

Type: Array of [AttachmentDetails](#) objects

body

The text of the communication between the customer and AWS Support.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

caseId

The support case ID requested or returned in the call. The case ID is an alphanumeric string formatted as shown in this example: case-12345678910-2013-c4c1d2bf33c5cf47

Type: String

submittedBy

The identity of the account that submitted, or responded to, the support case. Customer entries include the IAM role as well as the email address (for example, "AdminRole (Role) <janedoe@example.com>"). Entries from the AWS Support team display "Amazon Web Services," and don't show an email address.

Type: String

timeCreated

The time the communication was created.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommunicationTypeOptions

A JSON-formatted object that contains the CommunicationTypeOptions for creating a case for a certain communication channel. It is contained in the response from a [DescribeCreateCaseOptions](#) request. **CommunicationTypeOptions** contains the following fields:

- **datesWithoutSupport** - A JSON-formatted list containing date and time ranges for periods without support in UTC time. Date and time format is RFC 3339 : 'yyyy-MM-dd'T'HH:mm:ss.SSSZZ'.
- **supportedHours** - A JSON-formatted list containing time ranges when support are available. Time format is RFC 3339 : 'HH:mm:ss.SSS'.
- **type** - A string value indicating the communication type that the aforementioned rules apply to. At the moment the type value can assume one of 3 values at the moment chat, web and call.

Contents

datesWithoutSupport

A JSON-formatted list containing date and time ranges for periods without support

Type: Array of [DateInterval](#) objects

supportedHours

A JSON-formatted list containing time ranges when support is available.

Type: Array of [SupportedHour](#) objects

type

A string value indicating the communication type. At the moment the type value can assume one of 3 values at the moment chat, web and call.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DateInterval

Date and time (UTC) format in RFC 3339 : 'yyyy-MM-dd'T'HH:mm:ss.SSSZZ'.

Contents

endDateTime

End Date Time (UTC). RFC 3339 format : 'yyyy-MM-dd'T'HH:mm:ss.SSSZZ'.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 30.

startDateTime

A JSON object containing start and date time (UTC). Date and time format is RFC 3339 : 'yyyy-MM-dd'T'HH:mm:ss.SSSZZ'.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 30.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RecentCaseCommunications

The five most recent communications associated with the case.

Contents

communications

The five most recent communications associated with the case.

Type: Array of [Communication](#) objects

nextToken

A resumption point for pagination.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service

Information about an AWS service returned by the [DescribeServices](#) operation.

Contents

categories

A list of categories that describe the type of support issue a case describes. Categories consist of a category name and a category code. Category names and codes are passed to AWS Support when you call [CreateCase](#).

Type: Array of [Category](#) objects

code

The code for an AWS service returned by the [DescribeServices](#) response. The name element contains the corresponding friendly name.

Type: String

name

The friendly name for an AWS service. The code element contains the corresponding code.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SeverityLevel

A code and name pair that represents the severity level of a support case. The available values depend on the support plan for the account. For more information, see [Choosing a severity](#) in the *AWS Support User Guide*.

Contents

code

The code for case severity level.

Valid values: `low | normal | high | urgent | critical`

Type: String

name

The name of the severity level that corresponds to the severity level code.

Note

The values returned by the API are different from the values that appear in the AWS Support Center. For example, the API uses the code `low`, but the name appears as General guidance in Support Center.

The following are the API code names and how they appear in the console:

- `low` - General guidance
- `normal` - System impaired
- `high` - Production system impaired
- `urgent` - Production system down
- `critical` - Business-critical system down

For more information, see [Choosing a severity](#) in the *AWS Support User Guide*.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SupportedHour

Time range object with startTime and endTime range in RFC 3339 format. 'HH:mm:ss.SSS'.

Contents

endTime

End Time. RFC 3339 format 'HH:mm:ss.SSS'.

Type: String

startTime

Start Time. RFC 3339 format 'HH:mm:ss.SSS'.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SupportedLanguage

A JSON-formatted object that contains the available ISO 639-1 language code, language name and language display value. The language code is what should be used in the [CreateCase](#) call.

Contents

code

2 digit ISO 639-1 code. e.g. en

Type: String

display

Language display value e.g. ENGLISH

Type: String

language

Full language description e.g. ENGLISH

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCategorySpecificSummary

The container for summary information that relates to the category of the Trusted Advisor check.

Contents

costOptimizing

The summary information about cost savings for a Trusted Advisor check that is in the Cost Optimizing category.

Type: [TrustedAdvisorCostOptimizingSummary](#) object

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckDescription

The description and metadata for a Trusted Advisor check.

Contents

category

The category of the Trusted Advisor check.

Type: String

description

The description of the Trusted Advisor check, which includes the alert criteria and recommended operations (contains HTML markup).

Type: String

id

The unique identifier for the Trusted Advisor check.

Type: String

metadata

The column headings for the data returned by the Trusted Advisor check. The order of the headings corresponds to the order of the data in the **Metadata** element of the [TrustedAdvisorResourceDetail](#) for the check. **Metadata** contains all the data that is shown in the Excel download, even in those cases where the UI shows just summary data.

Type: Array of strings

name

The display name for the Trusted Advisor check.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckRefreshStatus

The refresh status of a Trusted Advisor check.

Contents

checkId

The unique identifier for the Trusted Advisor check.

Type: String

millisUntilNextRefreshable

The amount of time, in milliseconds, until the Trusted Advisor check is eligible for refresh.

Type: Long

status

The status of the Trusted Advisor check for which a refresh has been requested:

- none - The check is not refreshed or the non-success status exceeds the timeout
- queued - The check refresh requests has entered the refresh queue
- processing - The check refresh request is picked up by the rule processing engine
- success - The check is successfully refreshed
- abandoned - The check refresh has failed

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckResult

The results of a Trusted Advisor check returned by [DescribeTrustedAdvisorCheckResult](#).

Contents

categorySpecificSummary

Summary information that relates to the category of the check. Cost Optimizing is the only category that is currently supported.

Type: [TrustedAdvisorCategorySpecificSummary](#) object

checkId

The unique identifier for the Trusted Advisor check.

Type: String

flaggedResources

The details about each resource listed in the check result.

Type: Array of [TrustedAdvisorResourceDetail](#) objects

resourcesSummary

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries](#).

Type: [TrustedAdvisorResourcesSummary](#) object

status

The alert status of the check: "ok" (green), "warning" (yellow), "error" (red), or "not_available".

Type: String

timestamp

The time of the last refresh of the check.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCheckSummary

A summary of a Trusted Advisor check result, including the alert status, last refresh, and number of resources examined.

Contents

categorySpecificSummary

Summary information that relates to the category of the check. Cost Optimizing is the only category that is currently supported.

Type: [TrustedAdvisorCategorySpecificSummary](#) object

checkId

The unique identifier for the Trusted Advisor check.

Type: String

resourcesSummary

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries](#).

Type: [TrustedAdvisorResourcesSummary](#) object

status

The alert status of the check: "ok" (green), "warning" (yellow), "error" (red), or "not_available".

Type: String

timestamp

The time of the last refresh of the check.

Type: String

hasFlaggedResources

Specifies whether the Trusted Advisor check has flagged resources.

Type: Boolean

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorCostOptimizingSummary

The estimated cost savings that might be realized if the recommended operations are taken.

Contents

estimatedMonthlySavings

The estimated monthly savings that might be realized if the recommended operations are taken.

Type: Double

estimatedPercentMonthlySavings

The estimated percentage of savings that might be realized if the recommended operations are taken.

Type: Double

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorResourceDetail

Contains information about a resource identified by a Trusted Advisor check.

Contents

metadata

Additional information about the identified resource. The exact metadata and its order can be obtained by inspecting the [TrustedAdvisorCheckDescription](#) object returned by the call to [DescribeTrustedAdvisorChecks](#). **Metadata** contains all the data that is shown in the Excel download, even in those cases where the UI shows just summary data.

Type: Array of strings

resourceId

The unique identifier for the identified resource.

Type: String

status

The status code for the resource identified in the Trusted Advisor check.

Type: String

isSuppressed

Specifies whether the AWS resource was ignored by Trusted Advisor because it was marked as suppressed by the user.

Type: Boolean

region

The AWS Region in which the identified resource is located.

Type: String

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustedAdvisorResourcesSummary

Details about AWS resources that were analyzed in a call to Trusted Advisor [DescribeTrustedAdvisorCheckSummaries](#).

Contents

resourcesFlagged

The number of AWS resources that were flagged (listed) by the Trusted Advisor check.

Type: Long

resourcesIgnored

The number of AWS resources ignored by Trusted Advisor because information was unavailable.

Type: Long

resourcesProcessed

The number of AWS resources that were analyzed by the Trusted Advisor check.

Type: Long

resourcesSuppressed

The number of AWS resources ignored by Trusted Advisor because they were marked as suppressed by the user.

Type: Long

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400