API Reference

AWS Clean Rooms

API Version 2022-02-17

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Clean Rooms: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome **1**
Actions **2**
BatchGetCollaborationAnalysisTemplate 6
Request Syntax 6
URI Request Parameters 6
Request Body 6
Response Syntax 7
Response Elements 8
Errors 9
See Also 9
BatchGetSchema 11
Request Syntax 11
URI Request Parameters 11
Request Body 11
Response Syntax 12
Response Elements 13
Errors 13
See Also 14
BatchGetSchemaAnalysisRule 16
Request Syntax 16
URI Request Parameters 16
Request Body 16
Response Syntax 17
Response Elements 17
Errors 18
See Also 19
CreateAnalysisTemplate 20
Request Syntax 20
URI Request Parameters 20
Request Body 21
Response Syntax 23
Response Elements 24
Errors 24
See Also 25

CreateCollaboration ... 26
Request Syntax ... 26
URI Request Parameters ... 27
Request Body ... 27
Response Syntax ... 31
Response Elements ... 31
Errors ... 32
See Also ... 32
CreateCollaborationChangeRequest ... 34
Request Syntax ... 34
URI Request Parameters ... 34
Request Body ... 34
Response Syntax ... 35
Response Elements ... 35
Errors ... 36
See Also ... 37
CreateConfiguredAudienceModelAssociation ... 38
Request Syntax ... 38
URI Request Parameters ... 38
Request Body ... 38
Response Syntax ... 40
Response Elements ... 41
Errors ... 41
See Also ... 42
CreateConfiguredTable ... 43
Request Syntax ... 43
URI Request Parameters ... 43
Request Body ... 43
Response Syntax ... 45
Response Elements ... 46
Errors ... 46
See Also ... 47
CreateConfiguredTableAnalysisRule ... 48
Request Syntax ... 48
URI Request Parameters ... 48
Request Body ... 48

Response Syntax ... 49
Response Elements ... 49
Errors ... 50
See Also ... 51
CreateConfiguredTableAssociation ... 52
Request Syntax ... 52
URI Request Parameters ... 52
Request Body ... 52
Response Syntax ... 54
Response Elements ... 55
Errors ... 55
See Also ... 56
CreateConfiguredTableAssociationAnalysisRule ... 57
Request Syntax ... 57
URI Request Parameters ... 57
Request Body ... 58
Response Syntax ... 58
Response Elements ... 59
Errors ... 59
See Also ... 60
CreateIdMappingTable ... 61
Request Syntax ... 61
URI Request Parameters ... 61
Request Body ... 61
Response Syntax ... 63
Response Elements ... 64
Errors ... 64
See Also ... 65
CreateIdNamespaceAssociation ... 66
Request Syntax ... 66
URI Request Parameters ... 66
Request Body ... 66
Response Syntax ... 68
Response Elements ... 68
Errors ... 69
See Also ... 70

CreateMembership ... 71
Request Syntax ... 71
URI Request Parameters ... 72
Request Body ... 72
Response Syntax ... 74
Response Elements ... 75
Errors ... 75
See Also ... 76
CreatePrivacyBudgetTemplate ... 77
Request Syntax ... 77
URI Request Parameters ... 77
Request Body ... 77
Response Syntax ... 79
Response Elements ... 79
Errors ... 80
See Also ... 80
DeleteAnalysisTemplate ... 82
Request Syntax ... 82
URI Request Parameters ... 82
Request Body ... 82
Response Syntax ... 82
Response Elements ... 83
Errors ... 83
See Also ... 83
DeleteCollaboration ... 85
Request Syntax ... 85
URI Request Parameters ... 85
Request Body ... 85
Response Syntax ... 85
Response Elements ... 85
Errors ... 85
See Also ... 86
DeleteConfiguredAudienceModelAssociation ... 87
Request Syntax ... 87
URI Request Parameters ... 87
Request Body ... 87

Response Syntax ... 87
Response Elements ... 88
Errors ... 88
See Also ... 88
DeleteConfiguredTable ... 90
Request Syntax ... 90
URI Request Parameters ... 90
Request Body ... 90
Response Syntax ... 90
Response Elements ... 90
Errors ... 90
See Also ... 91
DeleteConfiguredTableAnalysisRule ... 93
Request Syntax ... 93
URI Request Parameters ... 93
Request Body ... 93
Response Syntax ... 93
Response Elements ... 94
Errors ... 94
See Also ... 95
DeleteConfiguredTableAssociation ... 96
Request Syntax ... 96
URI Request Parameters ... 96
Request Body ... 96
Response Syntax ... 96
Response Elements ... 97
Errors ... 97
See Also ... 98
DeleteConfiguredTableAssociationAnalysisRule ... 99
Request Syntax ... 99
URI Request Parameters ... 99
Request Body ... 100
Response Syntax ... 100
Response Elements ... 100
Errors ... 100
See Also ... 101

DeleteIdMappingTable ... 102
Request Syntax ... 102
URI Request Parameters ... 102
Request Body ... 102
Response Syntax ... 102
Response Elements ... 103
Errors ... 103
See Also ... 103
DeleteIdNamespaceAssociation ... 105
Request Syntax ... 105
URI Request Parameters ... 105
Request Body ... 105
Response Syntax ... 105
Response Elements ... 106
Errors ... 106
See Also ... 106
DeleteMember ... 108
Request Syntax ... 108
URI Request Parameters ... 108
Request Body ... 108
Response Syntax ... 108
Response Elements ... 109
Errors ... 109
See Also ... 110
DeleteMembership ... 111
Request Syntax ... 111
URI Request Parameters ... 111
Request Body ... 111
Response Syntax ... 111
Response Elements ... 111
Errors ... 111
See Also ... 112
DeletePrivacyBudgetTemplate ... 114
Request Syntax ... 114
URI Request Parameters ... 114
Request Body ... 114

Response Syntax 114
Response Elements 115
Errors 115
See Also 115
GetAnalysisTemplate 117
Request Syntax 117
URI Request Parameters 117
Request Body 117
Response Syntax 117
Response Elements 119
Errors 119
See Also 120
GetCollaboration 121
Request Syntax 121
URI Request Parameters 121
Request Body 121
Response Syntax 121
Response Elements 122
Errors 122
See Also 123
GetCollaborationAnalysisTemplate 124
Request Syntax 124
URI Request Parameters 124
Request Body 124
Response Syntax 124
Response Elements 126
Errors 126
See Also 127
GetCollaborationChangeRequest 128
Request Syntax 128
URI Request Parameters 128
Request Body 128
Response Syntax 128
Response Elements 129
Errors 129
See Also 130

GetCollaborationConfiguredAudienceModelAssociation 131
Request Syntax 131
URI Request Parameters 131
Request Body 131
Response Syntax 131
Response Elements 132
Errors 132
See Also 133
GetCollaborationIdNamespaceAssociation 134
Request Syntax 134
URI Request Parameters 134
Request Body 134
Response Syntax 134
Response Elements 135
Errors 135
See Also 136
GetCollaborationPrivacyBudgetTemplate 138
Request Syntax 138
URI Request Parameters 138
Request Body 138
Response Syntax 138
Response Elements 139
Errors 139
See Also 140
GetConfiguredAudienceModelAssociation 141
Request Syntax 141
URI Request Parameters 141
Request Body 141
Response Syntax 141
Response Elements 142
Errors 142
See Also 143
GetConfiguredTable 144
Request Syntax 144
URI Request Parameters 144
Request Body 144

Response Syntax ... 144
Response Elements ... 145
Errors ... 145
See Also ... 146
GetConfiguredTableAnalysisRule ... 147
Request Syntax ... 147
URI Request Parameters ... 147
Request Body ... 147
Response Syntax ... 147
Response Elements ... 148
Errors ... 148
See Also ... 149
GetConfiguredTableAssociation ... 150
Request Syntax ... 150
URI Request Parameters ... 150
Request Body ... 150
Response Syntax ... 150
Response Elements ... 151
Errors ... 151
See Also ... 152
GetConfiguredTableAssociationAnalysisRule ... 153
Request Syntax ... 153
URI Request Parameters ... 153
Request Body ... 154
Response Syntax ... 154
Response Elements ... 154
Errors ... 154
See Also ... 155
GetIdMappingTable ... 157
Request Syntax ... 157
URI Request Parameters ... 157
Request Body ... 157
Response Syntax ... 157
Response Elements ... 158
Errors ... 158
See Also ... 159

GetIdNamespaceAssociation 161
Request Syntax 161
URI Request Parameters 161
Request Body 161
Response Syntax 161
Response Elements 162
Errors 162
See Also 163
GetMembership 165
Request Syntax 165
URI Request Parameters 165
Request Body 165
Response Syntax 165
Response Elements 166
Errors 167
See Also 167
GetPrivacyBudgetTemplate 169
Request Syntax 169
URI Request Parameters 169
Request Body 169
Response Syntax 169
Response Elements 170
Errors 170
See Also 171
GetProtectedJob 172
Request Syntax 172
URI Request Parameters 172
Request Body 172
Response Syntax 172
Response Elements 173
Errors 174
See Also 174
GetProtectedQuery 176
Request Syntax 176
URI Request Parameters 176
Request Body 176

Response Syntax ... 176
Response Elements ... 178
Errors ... 178
See Also ... 179
GetSchema ... 180
Request Syntax ... 180
URI Request Parameters ... 180
Request Body ... 180
Response Syntax ... 180
Response Elements ... 182
Errors ... 182
See Also ... 183
GetSchemaAnalysisRule ... 184
Request Syntax ... 184
URI Request Parameters ... 184
Request Body ... 185
Response Syntax ... 185
Response Elements ... 185
Errors ... 185
See Also ... 186
ListAnalysisTemplates ... 188
Request Syntax ... 188
URI Request Parameters ... 188
Request Body ... 188
Response Syntax ... 189
Response Elements ... 189
Errors ... 190
See Also ... 190
ListCollaborationAnalysisTemplates ... 192
Request Syntax ... 192
URI Request Parameters ... 192
Request Body ... 192
Response Syntax ... 193
Response Elements ... 193
Errors ... 194
See Also ... 194

ListCollaborationChangeRequests ... 196
Request Syntax ... 196
URI Request Parameters ... 196
Request Body ... 197
Response Syntax ... 197
Response Elements ... 197
Errors ... 198
See Also ... 198
ListCollaborationConfiguredAudienceModelAssociations ... 200
Request Syntax ... 200
URI Request Parameters ... 200
Request Body ... 200
Response Syntax ... 201
Response Elements ... 201
Errors ... 202
See Also ... 202
ListCollaborationIdNamespaceAssociations ... 204
Request Syntax ... 204
URI Request Parameters ... 204
Request Body ... 204
Response Syntax ... 205
Response Elements ... 205
Errors ... 206
See Also ... 206
ListCollaborationPrivacyBudgets ... 208
Request Syntax ... 208
URI Request Parameters ... 208
Request Body ... 209
Response Syntax ... 209
Response Elements ... 209
Errors ... 210
See Also ... 210
ListCollaborationPrivacyBudgetTemplates ... 212
Request Syntax ... 212
URI Request Parameters ... 212
Request Body ... 212

Response Syntax ... 213
Response Elements ... 213
Errors ... 214
See Also ... 214
ListCollaborations ... 216
Request Syntax ... 216
URI Request Parameters ... 216
Request Body ... 216
Response Syntax ... 216
Response Elements ... 217
Errors ... 217
See Also ... 218
ListConfiguredAudienceModelAssociations ... 219
Request Syntax ... 219
URI Request Parameters ... 219
Request Body ... 219
Response Syntax ... 220
Response Elements ... 220
Errors ... 221
See Also ... 221
ListConfiguredTableAssociations ... 223
Request Syntax ... 223
URI Request Parameters ... 223
Request Body ... 223
Response Syntax ... 224
Response Elements ... 224
Errors ... 225
See Also ... 225
ListConfiguredTables ... 227
Request Syntax ... 227
URI Request Parameters ... 227
Request Body ... 227
Response Syntax ... 227
Response Elements ... 228
Errors ... 228
See Also ... 229

ListIdMappingTables 230
Request Syntax 230
URI Request Parameters 230
Request Body 230
Response Syntax 231
Response Elements 231
Errors 232
See Also 232
ListIdNamespaceAssociations 234
Request Syntax 234
URI Request Parameters 234
Request Body 234
Response Syntax 235
Response Elements 235
Errors 236
See Also 236
ListMembers 238
Request Syntax 238
URI Request Parameters 238
Request Body 238
Response Syntax 239
Response Elements 239
Errors 240
See Also 241
ListMemberships 242
Request Syntax 242
URI Request Parameters 242
Request Body 242
Response Syntax 242
Response Elements 243
Errors 244
See Also 244
ListPrivacyBudgets 246
Request Syntax 246
URI Request Parameters 246
Request Body 247

Response Syntax ... 247
Response Elements ... 247
Errors ... 248
See Also ... 249
ListPrivacyBudgetTemplates ... 250
Request Syntax ... 250
URI Request Parameters ... 250
Request Body ... 250
Response Syntax ... 251
Response Elements ... 251
Errors ... 252
See Also ... 252
ListProtectedJobs ... 254
Request Syntax ... 254
URI Request Parameters ... 254
Request Body ... 255
Response Syntax ... 255
Response Elements ... 255
Errors ... 256
See Also ... 256
ListProtectedQueries ... 258
Request Syntax ... 258
URI Request Parameters ... 258
Request Body ... 259
Response Syntax ... 259
Response Elements ... 259
Errors ... 260
See Also ... 260
ListSchemas ... 262
Request Syntax ... 262
URI Request Parameters ... 262
Request Body ... 263
Response Syntax ... 263
Response Elements ... 263
Errors ... 264
See Also ... 264

ListTagsForResource 266
Request Syntax 266
URI Request Parameters 266
Request Body 266
Response Syntax 266
Response Elements 266
Errors 267
See Also 267
PopulateIdMappingTable 269
Request Syntax 269
URI Request Parameters 269
Request Body 269
Response Syntax 269
Response Elements 270
Errors 270
See Also 271
PreviewPrivacyImpact 272
Request Syntax 272
URI Request Parameters 272
Request Body 272
Response Syntax 273
Response Elements 273
Errors 273
See Also 274
StartProtectedJob 275
Request Syntax 275
URI Request Parameters 275
Request Body 275
Response Syntax 276
Response Elements 277
Errors 277
See Also 278
StartProtectedQuery 280
Request Syntax 280
URI Request Parameters 280
Request Body 280

Response Syntax 281
Response Elements 282
Errors 283
See Also 284
TagResource 285
Request Syntax 285
URI Request Parameters 285
Request Body 285
Response Syntax 286
Response Elements 286
Errors 286
See Also 286
UntagResource 288
Request Syntax 288
URI Request Parameters 288
Request Body 288
Response Syntax 288
Response Elements 289
Errors 289
See Also 289
UpdateAnalysisTemplate 290
Request Syntax 290
URI Request Parameters 290
Request Body 290
Response Syntax 291
Response Elements 292
Errors 292
See Also 293
UpdateCollaboration 294
Request Syntax 294
URI Request Parameters 294
Request Body 294
Response Syntax 295
Response Elements 296
Errors 296
See Also 297

UpdateConfiguredAudienceModelAssociation ... 298
Request Syntax ... 298
URI Request Parameters ... 298
Request Body ... 299
Response Syntax ... 299
Response Elements ... 300
Errors ... 300
See Also ... 301
UpdateConfiguredTable ... 302
Request Syntax ... 302
URI Request Parameters ... 302
Request Body ... 302
Response Syntax ... 304
Response Elements ... 305
Errors ... 305
See Also ... 306
UpdateConfiguredTableAnalysisRule ... 307
Request Syntax ... 307
URI Request Parameters ... 307
Request Body ... 307
Response Syntax ... 308
Response Elements ... 308
Errors ... 308
See Also ... 309
UpdateConfiguredTableAssociation ... 311
Request Syntax ... 311
URI Request Parameters ... 311
Request Body ... 311
Response Syntax ... 312
Response Elements ... 313
Errors ... 313
See Also ... 314
UpdateConfiguredTableAssociationAnalysisRule ... 315
Request Syntax ... 315
URI Request Parameters ... 315
Request Body ... 316

Response Syntax ... 316
Response Elements ... 316
Errors ... 317
See Also ... 318
UpdateIdMappingTable ... 319
Request Syntax ... 319
URI Request Parameters ... 319
Request Body ... 319
Response Syntax ... 320
Response Elements ... 321
Errors ... 321
See Also ... 322
UpdateIdNamespaceAssociation ... 323
Request Syntax ... 323
URI Request Parameters ... 323
Request Body ... 324
Response Syntax ... 324
Response Elements ... 325
Errors ... 325
See Also ... 326
UpdateMembership ... 328
Request Syntax ... 328
URI Request Parameters ... 328
Request Body ... 328
Response Syntax ... 329
Response Elements ... 331
Errors ... 331
See Also ... 332
UpdatePrivacyBudgetTemplate ... 333
Request Syntax ... 333
URI Request Parameters ... 333
Request Body ... 334
Response Syntax ... 334
Response Elements ... 335
Errors ... 335
See Also ... 336

UpdateProtectedJob ... 337
Request Syntax ... 337
URI Request Parameters ... 337
Request Body ... 337
Response Syntax ... 338
Response Elements ... 339
Errors ... 339
See Also ... 340
UpdateProtectedQuery ... 341
Request Syntax ... 341
URI Request Parameters ... 341
Request Body ... 341
Response Syntax ... 342
Response Elements ... 343
Errors ... 343
See Also ... 344
Data Types ... 345
AggregateColumn ... 352
Contents ... 352
See Also ... 352
AggregationConstraint ... 353
Contents ... 353
See Also ... 354
AnalysisParameter ... 355
Contents ... 355
See Also ... 356
AnalysisRule ... 357
Contents ... 357
See Also ... 358
AnalysisRuleAggregation ... 360
Contents ... 360
See Also ... 362
AnalysisRuleCustom ... 363
Contents ... 363
See Also ... 364
AnalysisRuleIdMappingTable ... 365

Contents ... 365
See Also ... 366
AnalysisRuleList ... 367
Contents ... 367
See Also ... 368
AnalysisRulePolicy ... 369
Contents ... 369
See Also ... 369
AnalysisRulePolicyV1 ... 370
Contents ... 370
See Also ... 371
AnalysisSchema ... 372
Contents ... 372
See Also ... 372
AnalysisSource ... 373
Contents ... 373
See Also ... 373
AnalysisSourceMetadata ... 374
Contents ... 374
See Also ... 374
AnalysisTemplate ... 375
Contents ... 375
See Also ... 379
AnalysisTemplateArtifact ... 380
Contents ... 380
See Also ... 380
AnalysisTemplateArtifactMetadata ... 381
Contents ... 381
See Also ... 381
AnalysisTemplateArtifacts ... 382
Contents ... 382
See Also ... 382
AnalysisTemplateSummary ... 384
Contents ... 384
See Also ... 386
AnalysisTemplateValidationStatusDetail ... 387

Contents ... 387
See Also ... 388
AnalysisTemplateValidationStatusReason ... 389
Contents ... 389
See Also ... 389
AthenaTableReference ... 390
Contents ... 390
See Also ... 391
BatchGetCollaborationAnalysisTemplateError ... 392
Contents ... 392
See Also ... 392
BatchGetSchemaAnalysisRuleError ... 394
Contents ... 394
See Also ... 395
BatchGetSchemaError ... 396
Contents ... 396
See Also ... 396
BilledJobResourceUtilization ... 398
Contents ... 398
See Also ... 398
BilledResourceUtilization ... 399
Contents ... 399
See Also ... 399
Change ... 400
Contents ... 400
See Also ... 400
ChangeInput ... 402
Contents ... 402
See Also ... 402
ChangeSpecification ... 403
Contents ... 403
See Also ... 403
Collaboration ... 404
Contents ... 404
See Also ... 408
CollaborationAnalysisTemplate ... 409

Contents ... 409
See Also ... 412
CollaborationAnalysisTemplateSummary ... 414
Contents ... 414
See Also ... 416
CollaborationChangeRequest ... 417
Contents ... 417
See Also ... 418
CollaborationChangeRequestSummary ... 419
Contents ... 419
See Also ... 420
CollaborationConfiguredAudienceModelAssociation ... 421
Contents ... 421
See Also ... 423
CollaborationConfiguredAudienceModelAssociationSummary ... 424
Contents ... 424
See Also ... 426
CollaborationIdNamespaceAssociation ... 427
Contents ... 427
See Also ... 429
CollaborationIdNamespaceAssociationSummary ... 431
Contents ... 431
See Also ... 433
CollaborationPrivacyBudgetSummary ... 435
Contents ... 435
See Also ... 437
CollaborationPrivacyBudgetTemplate ... 438
Contents ... 438
See Also ... 440
CollaborationPrivacyBudgetTemplateSummary ... 441
Contents ... 441
See Also ... 443
CollaborationSummary ... 444
Contents ... 444
See Also ... 446
Column ... 448

Contents ... 448
See Also ... 448
ComputeConfiguration ... 449
Contents ... 449
See Also ... 449
ConfigurationDetails ... 450
Contents ... 450
See Also ... 450
ConfiguredAudienceModelAssociation ... 451
Contents ... 451
See Also ... 454
ConfiguredAudienceModelAssociationSummary ... 455
Contents ... 455
See Also ... 458
ConfiguredTable ... 459
Contents ... 459
See Also ... 461
ConfiguredTableAnalysisRule ... 463
Contents ... 463
See Also ... 464
ConfiguredTableAnalysisRulePolicy ... 465
Contents ... 465
See Also ... 465
ConfiguredTableAnalysisRulePolicyV1 ... 466
Contents ... 466
See Also ... 466
ConfiguredTableAssociation ... 468
Contents ... 468
See Also ... 471
ConfiguredTableAssociationAnalysisRule ... 472
Contents ... 472
See Also ... 473
ConfiguredTableAssociationAnalysisRuleAggregation ... 475
Contents ... 475
See Also ... 476
ConfiguredTableAssociationAnalysisRuleCustom ... 477

Contents ... 477
See Also ... 477
ConfiguredTableAssociationAnalysisRuleList ... 479
Contents ... 479
See Also ... 479
ConfiguredTableAssociationAnalysisRulePolicy ... 481
Contents ... 481
See Also ... 481
ConfiguredTableAssociationAnalysisRulePolicyV1 ... 482
Contents ... 482
See Also ... 482
ConfiguredTableAssociationSummary ... 484
Contents ... 484
See Also ... 486
ConfiguredTableSummary ... 487
Contents ... 487
See Also ... 489
ConsolidatedPolicy ... 490
Contents ... 490
See Also ... 490
ConsolidatedPolicyAggregation ... 491
Contents ... 491
See Also ... 493
ConsolidatedPolicyCustom ... 494
Contents ... 494
See Also ... 496
ConsolidatedPolicyList ... 497
Contents ... 497
See Also ... 498
ConsolidatedPolicyV1 ... 500
Contents ... 500
See Also ... 500
DataEncryptionMetadata ... 502
Contents ... 502
See Also ... 503
DifferentialPrivacyColumn ... 504

Contents ... 504
See Also ... 504
DifferentialPrivacyConfiguration ... 505
Contents ... 505
See Also ... 505
DifferentialPrivacyParameters ... 506
Contents ... 506
See Also ... 506
DifferentialPrivacyPreviewAggregation ... 507
Contents ... 507
See Also ... 507
DifferentialPrivacyPreviewParametersInput ... 508
Contents ... 508
See Also ... 508
DifferentialPrivacyPrivacyBudget ... 509
Contents ... 509
See Also ... 509
DifferentialPrivacyPrivacyBudgetAggregation ... 510
Contents ... 510
See Also ... 510
DifferentialPrivacyPrivacyImpact ... 512
Contents ... 512
See Also ... 512
DifferentialPrivacySensitivityParameters ... 513
Contents ... 513
See Also ... 514
DifferentialPrivacyTemplateParametersInput ... 515
Contents ... 515
See Also ... 515
DifferentialPrivacyTemplateParametersOutput ... 516
Contents ... 516
See Also ... 516
DifferentialPrivacyTemplateUpdateParameters ... 517
Contents ... 517
See Also ... 517
DirectAnalysisConfigurationDetails ... 518

Contents ... 518
See Also ... 518
ErrorMessageConfiguration ... 519
Contents ... 519
See Also ... 519
GlueTableReference ... 520
Contents ... 520
See Also ... 520
Hash ... 521
Contents ... 521
See Also ... 521
IdMappingConfig ... 522
Contents ... 522
See Also ... 522
IdMappingTable ... 523
Contents ... 523
See Also ... 526
IdMappingTableInputReferenceConfig ... 527
Contents ... 527
See Also ... 527
IdMappingTableInputReferenceProperties ... 528
Contents ... 528
See Also ... 528
IdMappingTableInputSource ... 529
Contents ... 529
See Also ... 529
IdMappingTableSchemaTypeProperties ... 530
Contents ... 530
See Also ... 530
IdMappingTableSummary ... 531
Contents ... 531
See Also ... 533
IdNamespaceAssociation ... 535
Contents ... 535
See Also ... 538
IdNamespaceAssociationInputReferenceConfig ... 539

Contents ... 539
See Also ... 539
IdNamespaceAssociationInputReferenceProperties ... 541
Contents ... 541
See Also ... 541
IdNamespaceAssociationInputReferencePropertiesSummary ... 542
Contents ... 542
See Also ... 542
IdNamespaceAssociationSummary ... 543
Contents ... 543
See Also ... 546
JobComputePaymentConfig ... 547
Contents ... 547
See Also ... 547
MemberChangeSpecification ... 548
Contents ... 548
See Also ... 549
Membership ... 550
Contents ... 550
See Also ... 554
MembershipJobComputePaymentConfig ... 555
Contents ... 555
See Also ... 555
MembershipMLPaymentConfig ... 556
Contents ... 556
See Also ... 556
MembershipModelInferencePaymentConfig ... 557
Contents ... 557
See Also ... 557
MembershipModelTrainingPaymentConfig ... 558
Contents ... 558
See Also ... 558
MembershipPaymentConfiguration ... 559
Contents ... 559
See Also ... 559
MembershipProtectedJobOutputConfiguration ... 560

Contents ... 560
See Also ... 560
MembershipProtectedJobResultConfiguration ... 561
Contents ... 561
See Also ... 561
MembershipProtectedQueryOutputConfiguration ... 562
Contents ... 562
See Also ... 562
MembershipProtectedQueryResultConfiguration ... 563
Contents ... 563
See Also ... 563
MembershipQueryComputePaymentConfig ... 564
Contents ... 564
See Also ... 564
MembershipSummary ... 565
Contents ... 565
See Also ... 568
MemberSpecification ... 569
Contents ... 569
See Also ... 570
MemberSummary ... 571
Contents ... 571
See Also ... 573
MLMemberAbilities ... 574
Contents ... 574
See Also ... 574
MLPaymentConfig ... 575
Contents ... 575
See Also ... 575
ModelInferencePaymentConfig ... 576
Contents ... 576
See Also ... 576
ModelTrainingPaymentConfig ... 577
Contents ... 577
See Also ... 577
PaymentConfiguration ... 578

Contents ... 578
See Also ... 578
PreviewPrivacyImpactParametersInput ... 580
Contents ... 580
See Also ... 580
PrivacyBudget ... 581
Contents ... 581
See Also ... 581
PrivacyBudgetSummary ... 582
Contents ... 582
See Also ... 584
PrivacyBudgetTemplate ... 586
Contents ... 586
See Also ... 589
PrivacyBudgetTemplateParametersInput ... 590
Contents ... 590
See Also ... 590
PrivacyBudgetTemplateParametersOutput ... 591
Contents ... 591
See Also ... 591
PrivacyBudgetTemplateSummary ... 592
Contents ... 592
See Also ... 594
PrivacyBudgetTemplateUpdateParameters ... 595
Contents ... 595
See Also ... 595
PrivacyImpact ... 596
Contents ... 596
See Also ... 596
ProtectedJob ... 597
Contents ... 597
See Also ... 599
ProtectedJobComputeConfiguration ... 600
Contents ... 600
See Also ... 600
ProtectedJobConfigurationDetails ... 601

Contents 601
See Also 601
ProtectedJobDirectAnalysisConfigurationDetails 602
Contents 602
See Also 602
ProtectedJobError 603
Contents 603
See Also 603
ProtectedJobMemberOutputConfigurationInput 604
Contents 604
See Also 604
ProtectedJobMemberOutputConfigurationOutput 605
Contents 605
See Also 605
ProtectedJobOutput 606
Contents 606
See Also 606
ProtectedJobOutputConfigurationInput 607
Contents 607
See Also 607
ProtectedJobOutputConfigurationOutput 608
Contents 608
See Also 608
ProtectedJobParameters 609
Contents 609
See Also 609
ProtectedJobReceiverConfiguration 610
Contents 610
See Also 610
ProtectedJobResult 611
Contents 611
See Also 611
ProtectedJobResultConfigurationInput 612
Contents 612
See Also 612
ProtectedJobResultConfigurationOutput 613

Contents ... 613
See Also ... 613
ProtectedJobS3Output ... 614
Contents ... 614
See Also ... 614
ProtectedJobS3OutputConfigurationInput ... 615
Contents ... 615
See Also ... 615
ProtectedJobS3OutputConfigurationOutput ... 616
Contents ... 616
See Also ... 616
ProtectedJobSingleMemberOutput ... 617
Contents ... 617
See Also ... 617
ProtectedJobStatistics ... 618
Contents ... 618
See Also ... 618
ProtectedJobSummary ... 619
Contents ... 619
See Also ... 620
ProtectedJobWorkerComputeConfiguration ... 621
Contents ... 621
See Also ... 621
ProtectedQuery ... 622
Contents ... 622
See Also ... 624
ProtectedQueryDistributeOutput ... 625
Contents ... 625
See Also ... 625
ProtectedQueryDistributeOutputConfiguration ... 626
Contents ... 626
See Also ... 626
ProtectedQueryDistributeOutputConfigurationLocation ... 627
Contents ... 627
See Also ... 627
ProtectedQueryError ... 628

Contents 628
See Also 628
ProtectedQueryMemberOutputConfiguration 629
Contents 629
See Also 629
ProtectedQueryOutput 630
Contents 630
See Also 631
ProtectedQueryOutputConfiguration 632
Contents 632
See Also 632
ProtectedQueryResult 634
Contents 634
See Also 634
ProtectedQueryResultConfiguration 635
Contents 635
See Also 635
ProtectedQueryS3Output 636
Contents 636
See Also 636
ProtectedQueryS3OutputConfiguration 637
Contents 637
See Also 638
ProtectedQuerySingleMemberOutput 639
Contents 639
See Also 639
ProtectedQuerySQLParameters 640
Contents 640
See Also 641
ProtectedQueryStatistics 642
Contents 642
See Also 642
ProtectedQuerySummary 643
Contents 643
See Also 644
QueryComputePaymentConfig 645

Contents ... 645
See Also ... 645
QueryConstraint ... 646
Contents ... 646
See Also ... 646
QueryConstraintRequireOverlap ... 647
Contents ... 647
See Also ... 647
ReceiverConfiguration ... 648
Contents ... 648
See Also ... 648
S3Location ... 649
Contents ... 649
See Also ... 649
Schema ... 650
Contents ... 650
See Also ... 653
SchemaAnalysisRuleRequest ... 654
Contents ... 654
See Also ... 654
SchemaStatusDetail ... 655
Contents ... 655
See Also ... 656
SchemaStatusReason ... 657
Contents ... 657
See Also ... 657
SchemaSummary ... 658
Contents ... 658
See Also ... 660
SchemaTypeProperties ... 661
Contents ... 661
See Also ... 661
SnowflakeTableReference ... 662
Contents ... 662
See Also ... 663
SnowflakeTableSchema ... 664

Contents 664
See Also 664
SnowflakeTableSchemaV1 665
Contents 665
See Also 665
TableReference 667
Contents 667
See Also 667
ValidationExceptionField 669
Contents 669
See Also 669
WorkerComputeConfiguration 670
Contents 670
See Also 670
Common Parameters 671
Common Errors 674

Welcome

Welcome to the *AWS Clean Rooms API Reference*.

AWS Clean Rooms is an AWS service that helps multiple parties to join their data together in a secure collaboration workspace. In the collaboration, members who can run queries and jobs and receive results can get insights into the collective datasets without either party getting access to the other party's raw data.

To learn more about AWS Clean Rooms concepts, procedures, and best practices, see the AWS Clean Rooms User Guide.

To learn more about SQL commands, functions, and conditions supported in AWS Clean Rooms, see the AWS Clean Rooms SQL Reference.

This document was last published on September 4, 2025.

Actions

The following actions are supported:

- BatchGetCollaborationAnalysisTemplate
- BatchGetSchema
- BatchGetSchemaAnalysisRule
- CreateAnalysisTemplate
- CreateCollaboration
- CreateCollaborationChangeRequest
- CreateConfiguredAudienceModelAssociation
- CreateConfiguredTable
- CreateConfiguredTableAnalysisRule
- CreateConfiguredTableAssociation
- CreateConfiguredTableAssociationAnalysisRule
- CreateIdMappingTable
- CreateIdNamespaceAssociation
- CreateMembership
- CreatePrivacyBudgetTemplate
- DeleteAnalysisTemplate
- DeleteCollaboration
- DeleteConfiguredAudienceModelAssociation
- DeleteConfiguredTable
- DeleteConfiguredTableAnalysisRule
- DeleteConfiguredTableAssociation
- DeleteConfiguredTableAssociationAnalysisRule
- DeleteIdMappingTable
- DeleteIdNamespaceAssociation
- DeleteMember
- DeleteMembership
- DeletePrivacyBudgetTemplate

- GetAnalysisTemplate
- GetCollaboration
- GetCollaborationAnalysisTemplate
- GetCollaborationChangeRequest
- GetCollaborationConfiguredAudienceModelAssociation
- GetCollaborationIdNamespaceAssociation
- GetCollaborationPrivacyBudgetTemplate
- GetConfiguredAudienceModelAssociation
- GetConfiguredTable
- GetConfiguredTableAnalysisRule
- GetConfiguredTableAssociation
- GetConfiguredTableAssociationAnalysisRule
- GetIdMappingTable
- GetIdNamespaceAssociation
- GetMembership
- GetPrivacyBudgetTemplate
- GetProtectedJob
- GetProtectedQuery
- GetSchema
- GetSchemaAnalysisRule
- ListAnalysisTemplates
- ListCollaborationAnalysisTemplates
- ListCollaborationChangeRequests
- ListCollaborationConfiguredAudienceModelAssociations
- ListCollaborationIdNamespaceAssociations
- ListCollaborationPrivacyBudgets
- ListCollaborationPrivacyBudgetTemplates
- ListCollaborations
- ListConfiguredAudienceModelAssociations
- ListConfiguredTableAssociations

- ListConfiguredTables
- ListIdMappingTables
- ListIdNamespaceAssociations
- ListMembers
- ListMemberships
- ListPrivacyBudgets
- ListPrivacyBudgetTemplates
- ListProtectedJobs
- ListProtectedQueries
- ListSchemas
- ListTagsForResource
- PopulateIdMappingTable
- PreviewPrivacyImpact
- StartProtectedJob
- StartProtectedQuery
- TagResource
- UntagResource
- UpdateAnalysisTemplate
- UpdateCollaboration
- UpdateConfiguredAudienceModelAssociation
- UpdateConfiguredTable
- UpdateConfiguredTableAnalysisRule
- UpdateConfiguredTableAssociation
- UpdateConfiguredTableAssociationAnalysisRule
- UpdateIdMappingTable
- UpdateIdNamespaceAssociation
- UpdateMembership
- UpdatePrivacyBudgetTemplate
- UpdateProtectedJob
- UpdateProtectedQuery

BatchGetCollaborationAnalysisTemplate

Retrieves multiple analysis templates within a collaboration by their Amazon Resource Names (ARNs).

Request Syntax

```
POST /collaborations/collaborationIdentifier/batch-analysistemplates HTTP/1.1
Content-type: application/json

{
   "analysisTemplateArns": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the analysis templates belong to. Currently accepts collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

analysisTemplateArns

The Amazon Resource Name (ARN) associated with the analysis template within a collaboration.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationAnalysisTemplates": [
      {
         "analysisParameters": [
            {
               "defaultValue": "string",
               "name": "string",
               "type": "string"
            }
         ],
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "description": "string",
         "errorMessageConfiguration": {
            "type": "string"
         },
         "format": "string",
         "id": "string",
         "name": "string",
         "schema": {
            "referencedTables": [ "string" ]
         },
         "source": { ... },
         "sourceMetadata": { ... },
         "updateTime": number,
         "validations": [
            {
```

```
                "reasons": [
                   {
                      "message": "string"
                   }
                ],
                "status": "string",
                "type": "string"
             }
          ]
       }
    ],
    "errors": [
       {
          "arn": "string",
          "code": "string",
          "message": "string"
       }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationAnalysisTemplates

The retrieved list of analysis templates within a collaboration.

Type: Array of CollaborationAnalysisTemplate objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

errors

Error reasons for collaboration analysis templates that could not be retrieved. One error is returned for every collaboration analysis template that could not be retrieved.

Type: Array of BatchGetCollaborationAnalysisTemplateError objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

BatchGetSchema

Retrieves multiple schemas by their identifiers.

Request Syntax

```
POST /collaborations/collaborationIdentifier/batch-schema HTTP/1.1
Content-type: application/json

{
   "names": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the schemas belong to. Currently accepts collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

names

The names for the schema objects to retrieve.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "errors": [
      {
         "code": "string",
         "message": "string",
         "name": "string"
      }
   ],
   "schemas": [
      {
         "analysisMethod": "string",
         "analysisRuleTypes": [ "string" ],
         "collaborationArn": "string",
         "collaborationId": "string",
         "columns": [
            {
               "name": "string",
               "type": "string"
            }
         ],
         "createTime": number,
         "creatorAccountId": "string",
         "description": "string",
         "name": "string",
         "partitionKeys": [
            {
               "name": "string",
               "type": "string"
            }
         ],
         "schemaStatusDetails": [
            {
               "analysisRuleType": "string",
               "analysisType": "string",
```

```
                "configurations": [ "string" ],
                "reasons": [
                   {
                      "code": "string",
                      "message": "string"
                   }
                ],
                "status": "string"
             }
          ],
          "schemaTypeProperties": { ... },
          "selectedAnalysisMethods": [ "string" ],
          "type": "string",
          "updateTime": number
       }
    ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

errors

Error reasons for schemas that could not be retrieved. One error is returned for every schema that could not be retrieved.

Type: Array of BatchGetSchemaError objects

Array Members: Minimum number of 0 items. Maximum number of 25 items.

schemas

The retrieved list of schemas.

Type: Array of Schema objects

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

BatchGetSchemaAnalysisRule

Retrieves multiple analysis rule schemas.

Request Syntax

```
POST /collaborations/collaborationIdentifier/batch-schema-analysis-rule HTTP/1.1
Content-type: application/json

{
   "schemaAnalysisRuleRequests": [
      {
         "name": "string",
         "type": "string"
      }
   ]
}
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The unique identifier of the collaboration that contains the schema analysis rule.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

schemaAnalysisRuleRequests

The information that's necessary to retrieve a schema analysis rule.

Type: Array of SchemaAnalysisRuleRequest objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisRules": [
      {
         "collaborationId": "string",
         "collaborationPolicy": { ... },
         "consolidatedPolicy": { ... },
         "createTime": number,
         "name": "string",
         "policy": { ... },
         "type": "string",
         "updateTime": number
      }
   ],
   "errors": [
      {
         "code": "string",
         "message": "string",
         "name": "string",
         "type": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRules

The retrieved list of analysis rules.

Type: Array of AnalysisRule objects

Array Members: Minimum number of 0 items. Maximum number of 25 items.

errors

Error reasons for schemas that could not be retrieved. One error is returned for every schema that could not be retrieved.

Type: Array of BatchGetSchemaAnalysisRuleError objects

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateAnalysisTemplate

Creates a new analysis template.

Request Syntax

```
POST /memberships/membershipIdentifier/analysistemplates HTTP/1.1
Content-type: application/json

{
   "analysisParameters": [
      {
         "defaultValue": "string",
         "name": "string",
         "type": "string"
      }
   ],
   "description": "string",
   "errorMessageConfiguration": {
      "type": "string"
   },
   "format": "string",
   "name": "string",
   "schema": {
      "referencedTables": [ "string" ]
   },
   "source": { ... },
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The identifier for a membership resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

analysisParameters

The parameters of the analysis template.

Type: Array of AnalysisParameter objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

description

The description of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

errorMessageConfiguration

The configuration that specifies the level of detail in error messages returned by analyses using this template. When set to `DETAILED`, error messages include more information to help troubleshoot issues with PySpark jobs. Detailed error messages may expose underlying data, including sensitive information. Recommended for faster troubleshooting in development and testing environments.

Type: ErrorMessageConfiguration object

Required: No

format

The format of the analysis template.

Type: String

Valid Values: `SQL` | `PYSPARK_1_0`

Required: Yes

name

The name of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

schema

A relation within an analysis.

Type: AnalysisSchema object

Required: No

source

The information in the analysis template.

Type: AnalysisSource object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisTemplate": {
      "analysisParameters": [
         {
            "defaultValue": "string",
            "name": "string",
            "type": "string"
         }
      ],
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "description": "string",
      "errorMessageConfiguration": {
         "type": "string"
      },
      "format": "string",
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "schema": {
         "referencedTables": [ "string" ]
      },
      "source": { ... },
      "sourceMetadata": { ... },
      "updateTime": number,
      "validations": [
         {
            "reasons": [
               {
```

```
                    "message": "string"
                }
            ],
            "status": "string",
            "type": "string"
        }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisTemplate

The analysis template.

Type: AnalysisTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateCollaboration

Creates a new collaboration.

Request Syntax

```
POST /collaborations HTTP/1.1
Content-type: application/json

{
   "analyticsEngine": "string",
   "autoApprovedChangeRequestTypes": [ "string" ],
   "creatorDisplayName": "string",
   "creatorMemberAbilities": [ "string" ],
   "creatorMLMemberAbilities": {
      "customMLMemberAbilities": [ "string" ]
   },
   "creatorPaymentConfiguration": {
      "jobCompute": {
         "isResponsible": boolean
      },
      "machineLearning": {
         "modelInference": {
            "isResponsible": boolean
         },
         "modelTraining": {
            "isResponsible": boolean
         }
      },
      "queryCompute": {
         "isResponsible": boolean
      }
   },
   "dataEncryptionMetadata": {
      "allowCleartext": boolean,
      "allowDuplicates": boolean,
      "allowJoinsOnColumnsWithDifferentNames": boolean,
      "preserveNulls": boolean
   },
   "description": "string",
   "jobLogStatus": "string",
   "members": [
      {
```

```
            "accountId": "string",
            "displayName": "string",
            "memberAbilities": [ "string" ],
            "mlMemberAbilities": {
               "customMLMemberAbilities": [ "string" ]
            },
            "paymentConfiguration": {
               "jobCompute": {
                  "isResponsible": boolean
               },
               "machineLearning": {
                  "modelInference": {
                     "isResponsible": boolean
                  },
                  "modelTraining": {
                     "isResponsible": boolean
                  }
               },
               "queryCompute": {
                  "isResponsible": boolean
               }
            }
         }
      ],
      "name": "string",
      "queryLogStatus": "string",
      "tags": {
         "string" : "string"
      }
   }
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

analyticsEngine

The analytics engine.

> **Note**
>
> After July 16, 2025, the `CLEAN_ROOMS_SQL` parameter will no longer be available.

Type: String

Valid Values: `SPARK | CLEAN_ROOMS_SQL`

Required: No

autoApprovedChangeRequestTypes

The types of change requests that are automatically approved for this collaboration.

Type: Array of strings

Valid Values: `ADD_MEMBER`

Required: No

creatorDisplayName

The display name of the collaboration creator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

creatorMemberAbilities

The abilities granted to the collaboration creator.

Type: Array of strings

Valid Values: `CAN_QUERY | CAN_RECEIVE_RESULTS | CAN_RUN_JOB`

Required: Yes

creatorMLMemberAbilities

The ML abilities granted to the collaboration creator.

Type: MLMemberAbilities object

Required: No

creatorPaymentConfiguration

The collaboration creator's payment responsibilities set by the collaboration creator.

If the collaboration creator hasn't specified anyone as the member paying for query compute costs, then the member who can query is the default payer.

Type: PaymentConfiguration object

Required: No

dataEncryptionMetadata

The settings for client-side encryption with Cryptographic Computing for Clean Rooms.

Type: DataEncryptionMetadata object

Required: No

description

A description of the collaboration provided by the collaboration owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: Yes

jobLogStatus

Specifies whether job logs are enabled for this collaboration.

When `ENABLED`, AWS Clean Rooms logs details about jobs run within this collaboration; those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: No

members

A list of initial members, not including the creator. This list is immutable.

Type: Array of MemberSpecification objects

Array Members: Minimum number of 0 items. Maximum number of 9 items.

Required: Yes

name

The display name for a collaboration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

queryLogStatus

An indicator as to whether query logging has been enabled or disabled for the collaboration.

When `ENABLED`, AWS Clean Rooms logs details about queries run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaboration": {
      "analyticsEngine": "string",
      "arn": "string",
      "autoApprovedChangeTypes": [ "string" ],
      "createTime": number,
      "creatorAccountId": "string",
      "creatorDisplayName": "string",
      "dataEncryptionMetadata": {
         "allowCleartext": boolean,
         "allowDuplicates": boolean,
         "allowJoinsOnColumnsWithDifferentNames": boolean,
         "preserveNulls": boolean
      },
      "description": "string",
      "id": "string",
      "jobLogStatus": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "memberStatus": "string",
      "name": "string",
      "queryLogStatus": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaboration

The collaboration.

Type: Collaboration object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateCollaborationChangeRequest

Creates a new change request to modify an existing collaboration. This enables post-creation modifications to collaborations through a structured API-driven approach.

Request Syntax

```
POST /collaborations/collaborationIdentifier/changeRequests HTTP/1.1
Content-type: application/json

{
   "changes": [
      {
         "specification": { ... },
         "specificationType": "string"
      }
   ]
}
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The identifier of the collaboration that the change request is made against.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

changes

The list of changes to apply to the collaboration. Each change specifies the type of modification and the details of what should be changed.

Type: Array of ChangeInput objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationChangeRequest": {
      "changes": [
         {
            "specification": { ... },
            "specificationType": "string",
            "types": [ "string" ]
         }
      ],
      "collaborationId": "string",
      "createTime": number,
      "id": "string",
      "isAutoApproved": boolean,
      "status": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationChangeRequest

Represents a request to modify a collaboration. Change requests enable structured modifications to collaborations after they have been created.

Type: CollaborationChangeRequest object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateConfiguredAudienceModelAssociation

Provides the details necessary to create a configured audience model association.

Request Syntax

```
POST /memberships/membershipIdentifier/configuredaudiencemodelassociations HTTP/1.1
Content-type: application/json

{
   "configuredAudienceModelArn": "string",
   "configuredAudienceModelAssociationName": "string",
   "description": "string",
   "manageResourcePolicies": boolean,
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The configured audience model is associated to the collaboration that this membership belongs to. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

configuredAudienceModelArn

A unique identifier for the configured audience model that you want to associate.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:[0-9]{12}:configured-audience-model/[-a-zA-Z0-9_/.]+`

Required: Yes

configuredAudienceModelAssociationName

The name of the configured audience model association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

description

A description of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

manageResourcePolicies

When `TRUE`, indicates that the resource policy for the configured audience model resource being associated is configured for AWS Clean Rooms to manage permissions related to the given collaboration. When `FALSE`, indicates that the configured audience model resource owner will manage permissions related to the given collaboration.

Setting this to `TRUE` requires you to have permissions to create, update, and delete the resource policy for the `cleanrooms-ml` resource when you call the DeleteConfiguredAudienceModelAssociation resource. In addition, if you are the collaboration

creator and specify TRUE, you must have the same permissions when you call the DeleteMember and DeleteCollaboration APIs.

Type: Boolean

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredAudienceModelAssociation": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "configuredAudienceModelArn": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "manageResourcePolicies": boolean,
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "updateTime": number
   }
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredAudienceModelAssociation

Information about the configured audience model association.

Type: ConfiguredAudienceModelAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateConfiguredTable

Creates a new configured table resource.

Request Syntax

```
POST /configuredTables HTTP/1.1
Content-type: application/json

{
   "allowedColumns": [ "string" ],
   "analysisMethod": "string",
   "description": "string",
   "name": "string",
   "selectedAnalysisMethods": [ "string" ],
   "tableReference": { ... },
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

allowedColumns

The columns of the underlying table that can be used by collaborations or analysis rules.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

analysisMethod

The analysis method allowed for the configured tables.

`DIRECT_QUERY` allows SQL queries to be run directly on this table.

`DIRECT_JOB` allows PySpark jobs to be run directly on this table.

`MULTIPLE` allows both SQL queries and PySpark jobs to be run directly on this table.

Type: String

Valid Values: `DIRECT_QUERY | DIRECT_JOB | MULTIPLE`

Required: Yes

description

A description for the configured table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

name

The name of the configured table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

selectedAnalysisMethods

The analysis methods to enable for the configured table. When configured, you must specify at least two analysis methods.

Type: Array of strings

Valid Values: `DIRECT_QUERY | DIRECT_JOB`

Required: No

tableReference

A reference to the table being configured.

Type: TableReference object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredTable": {
      "allowedColumns": [ "string" ],
      "analysisMethod": "string",
      "analysisRuleTypes": [ "string" ],
      "arn": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
```

```
        "name": "string",
        "selectedAnalysisMethods": [ "string" ],
        "tableReference": { ... },
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTable

The created configured table.

Type: ConfiguredTable object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateConfiguredTableAnalysisRule

Creates a new analysis rule for a configured table. Currently, only one analysis rule can be created for a given configured table.

Request Syntax

```
POST /configuredTables/configuredTableIdentifier/analysisRule HTTP/1.1
Content-type: application/json

{
   "analysisRulePolicy": { ... },
   "analysisRuleType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableIdentifier

The identifier for the configured table to create the analysis rule for. Currently accepts the configured table ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

analysisRulePolicy

The analysis rule policy that was created for the configured table.

Type: ConfiguredTableAnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

analysisRuleType

The type of analysis rule.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisRule": {
      "configuredTableArn": "string",
      "configuredTableId": "string",
      "createTime": number,
      "policy": { ... },
      "type": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRule

The analysis rule that was created for the configured table.

Type: ConfiguredTableAnalysisRule object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateConfiguredTableAssociation

Creates a configured table association. A configured table association links a configured table with a collaboration.

Request Syntax

```
POST /memberships/membershipIdentifier/configuredTableAssociations HTTP/1.1
Content-type: application/json

{
   "configuredTableIdentifier": "string",
   "description": "string",
   "name": "string",
   "roleArn": "string",
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The configured table is associated to the collaboration that this membership belongs to. Currently accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

configuredTableIdentifier

A unique identifier for the configured table to be associated to. Currently accepts a configured table ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

description

A description for the configured table association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

name

The name of the configured table association. This name is used to query the underlying configured table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

roleArn

The service will assume this role to access catalog metadata and query the table.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 512.

Pattern: `arn:aws:iam::[\w]+:role/[\w+=./@-]+`

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredTableAssociation": {
      "analysisRuleTypes": [ "string" ],
      "arn": "string",
      "configuredTableArn": "string",
      "configuredTableId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "roleArn": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTableAssociation

The configured table association.

Type: ConfiguredTableAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateConfiguredTableAssociationAnalysisRule

Creates a new analysis rule for an associated configured table.

Request Syntax

```
POST /memberships/membershipIdentifier/
configuredTableAssociations/configuredTableAssociationIdentifier/analysisRule HTTP/1.1
Content-type: application/json

{
   "analysisRulePolicy": { ... },
   "analysisRuleType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableAssociationIdentifier

The unique ID for the configured table association. Currently accepts the configured table association ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier for the membership that the configured table association belongs to. Currently accepts the membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

analysisRulePolicy

The analysis rule policy that was created for the configured table association.

Type: ConfiguredTableAssociationAnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

analysisRuleType

The type of analysis rule.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisRule": {
      "configuredTableAssociationArn": "string",
      "configuredTableAssociationId": "string",
      "createTime": number,
      "membershipIdentifier": "string",
      "policy": { ... },
      "type": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRule

The analysis rule for the configured table association. In the console, the `ConfiguredTableAssociationAnalysisRule` is referred to as the *collaboration analysis rule*.

Type: ConfiguredTableAssociationAnalysisRule object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateIdMappingTable

Creates an ID mapping table.

Request Syntax

```
POST /memberships/membershipIdentifier/idmappingtables HTTP/1.1
Content-type: application/json

{
   "description": "string",
   "inputReferenceConfig": {
      "inputReferenceArn": "string",
      "manageResourcePolicies": boolean
   },
   "kmsKeyArn": "string",
   "name": "string",
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The unique identifier of the membership that contains the ID mapping table.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

A description of the ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

inputReferenceConfig

The input reference configuration needed to create the ID mapping table.

Type: IdMappingTableInputReferenceConfig object

Required: Yes

kmsKeyArn

The Amazon Resource Name (ARN) of the AWS KMS key. This value is used to encrypt the mapping table data that is stored by AWS Clean Rooms.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:kms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:key/[a-zA-Z0-9-]+`

Required: No

name

A name for the ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "idMappingTable": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "inputReferenceConfig": {
         "inputReferenceArn": "string",
         "manageResourcePolicies": boolean
      },
      "inputReferenceProperties": {
         "idMappingTableInputSource": [
            {
               "idNamespaceAssociationId": "string",
               "type": "string"
            }
         ]
      },
      "kmsKeyArn": "string",
```

```
        "membershipArn": "string",
        "membershipId": "string",
        "name": "string",
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idMappingTable

The ID mapping table that was created.

Type: IdMappingTable object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateIdNamespaceAssociation

Creates an ID namespace association.

Request Syntax

```
POST /memberships/membershipIdentifier/idnamespaceassociations HTTP/1.1
Content-type: application/json

{
   "description": "string",
   "idMappingConfig": {
      "allowUseAsDimensionColumn": boolean
   },
   "inputReferenceConfig": {
      "inputReferenceArn": "string",
      "manageResourcePolicies": boolean
   },
   "name": "string",
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The unique identifier of the membership that contains the ID namespace association.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

The description of the ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

idMappingConfig

The configuration settings for the ID mapping table.

Type: IdMappingConfig object

Required: No

inputReferenceConfig

The input reference configuration needed to create the ID namespace association.

Type: IdNamespaceAssociationInputReferenceConfig object

Required: Yes

name

The name for the ID namespace association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "idNamespaceAssociation": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "idMappingConfig": {
         "allowUseAsDimensionColumn": boolean
      },
      "inputReferenceConfig": {
         "inputReferenceArn": "string",
         "manageResourcePolicies": boolean
      },
      "inputReferenceProperties": {
         "idMappingWorkflowsSupported": [ JSON value ],
         "idNamespaceType": "string"
      },
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idNamespaceAssociation

The ID namespace association that was created.

Type: IdNamespaceAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreateMembership

Creates a membership for a specific collaboration identifier and joins the collaboration.

Request Syntax

```
POST /memberships HTTP/1.1
Content-type: application/json

{
   "collaborationIdentifier": "string",
   "defaultJobResultConfiguration": {
      "outputConfiguration": { ... },
      "roleArn": "string"
   },
   "defaultResultConfiguration": {
      "outputConfiguration": { ... },
      "roleArn": "string"
   },
   "jobLogStatus": "string",
   "paymentConfiguration": {
      "jobCompute": {
         "isResponsible": boolean
      },
      "machineLearning": {
         "modelInference": {
            "isResponsible": boolean
         },
         "modelTraining": {
            "isResponsible": boolean
         }
      },
      "queryCompute": {
         "isResponsible": boolean
      }
   },
   "queryLogStatus": "string",
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

collaborationIdentifier

The unique ID for the associated collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

defaultJobResultConfiguration

The default job result configuration that determines how job results are protected and managed within this membership. This configuration applies to all jobs.

Type: MembershipProtectedJobResultConfiguration object

Required: No

defaultResultConfiguration

The default protected query result configuration as specified by the member who can receive results.

Type: MembershipProtectedQueryResultConfiguration object

Required: No

jobLogStatus

An indicator as to whether job logging has been enabled or disabled for the collaboration.

When `ENABLED`, AWS Clean Rooms logs details about jobs run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: No

paymentConfiguration

The payment responsibilities accepted by the collaboration member.

Not required if the collaboration member has the member ability to run queries.

Required if the collaboration member doesn't have the member ability to run queries but is configured as a payer by the collaboration creator.

Type: MembershipPaymentConfiguration object

Required: No

queryLogStatus

An indicator as to whether query logging has been enabled or disabled for the membership.

When `ENABLED`, AWS Clean Rooms logs details about queries run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "membership": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationCreatorAccountId": "string",
      "collaborationCreatorDisplayName": "string",
      "collaborationId": "string",
      "collaborationName": "string",
      "createTime": number,
      "defaultJobResultConfiguration": {
         "outputConfiguration": { ... },
         "roleArn": "string"
      },
      "defaultResultConfiguration": {
         "outputConfiguration": { ... },
         "roleArn": "string"
      },
      "id": "string",
      "jobLogStatus": "string",
      "memberAbilities": [ "string" ],
      "mlMemberAbilities": {
         "customMLMemberAbilities": [ "string" ]
      },
      "paymentConfiguration": {
         "jobCompute": {
            "isResponsible": boolean
         },
         "machineLearning": {
            "modelInference": {
               "isResponsible": boolean
            },
            "modelTraining": {
               "isResponsible": boolean
            }
```

```
            },
            "queryCompute": {
               "isResponsible": boolean
            }
         },
         "queryLogStatus": "string",
         "status": "string",
         "updateTime": number
      }
   }
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

membership

The membership that was created.

Type: Membership object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

CreatePrivacyBudgetTemplate

Creates a privacy budget template for a specified collaboration. Each collaboration can have only one privacy budget template. If you need to change the privacy budget template, use the UpdatePrivacyBudgetTemplate operation.

Request Syntax

```
POST /memberships/membershipIdentifier/privacybudgettemplates HTTP/1.1
Content-type: application/json

{
   "autoRefresh": "string",
   "parameters": { ... },
   "privacyBudgetType": "string",
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The privacy budget template is created in the collaboration that this membership belongs to. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

autoRefresh

How often the privacy budget refreshes.

> **Important**
>
> If you plan to regularly bring new data into the collaboration, you can use `CALENDAR_MONTH` to automatically get a new privacy budget for the collaboration every calendar month. Choosing this option allows arbitrary amounts of information to be revealed about rows of the data when repeatedly queries across refreshes. Avoid choosing this if the same rows will be repeatedly queried between privacy budget refreshes.

Type: String

Valid Values: `CALENDAR_MONTH | NONE`

Required: Yes

parameters

Specifies your parameters for the privacy budget template.

Type: PrivacyBudgetTemplateParametersInput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

privacyBudgetType

Specifies the type of the privacy budget template.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

tags

An optional label that you can assign to a resource when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to this resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "privacyBudgetTemplate": {
      "arn": "string",
      "autoRefresh": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "parameters": { ... },
      "privacyBudgetType": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

privacyBudgetTemplate

A summary of the elements in the privacy budget template.

Type: PrivacyBudgetTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteAnalysisTemplate

Deletes an analysis template.

Request Syntax

```
DELETE /memberships/membershipIdentifier/analysistemplates/analysisTemplateIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analysisTemplateIdentifier

The identifier for the analysis template resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The identifier for a membership resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteCollaboration

Deletes a collaboration. It can only be called by the collaboration owner.

Request Syntax

```
DELETE /collaborations/collaborationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The identifier for the collaboration.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteConfiguredAudienceModelAssociation

Provides the information necessary to delete a configured audience model association.

Request Syntax

```
DELETE /memberships/membershipIdentifier/
configuredaudiencemodelassociations/configuredAudienceModelAssociationIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

configuredAudienceModelAssociationIdentifier

A unique identifier of the configured audience model association that you want to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier of the membership that contains the audience model association that you want to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteConfiguredTable

Deletes a configured table.

Request Syntax

```
DELETE /configuredTables/configuredTableIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableIdentifier

The unique ID for the configured table to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteConfiguredTableAnalysisRule

Deletes a configured table analysis rule.

Request Syntax

```
DELETE /configuredTables/configuredTableIdentifier/analysisRule/analysisRuleType
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analysisRuleType

The analysis rule type to be deleted. Configured table analysis rules are uniquely identified by their configured table identifier and analysis rule type.

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

configuredTableIdentifier

The unique identifier for the configured table that the analysis rule applies to. Currently accepts the configured table ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteConfiguredTableAssociation

Deletes a configured table association.

Request Syntax

```
DELETE /memberships/membershipIdentifier/
configuredTableAssociations/configuredTableAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableAssociationIdentifier

The unique ID for the configured table association to be deleted. Currently accepts the configured table ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier for the membership that the configured table association belongs to. Currently accepts the membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteConfiguredTableAssociationAnalysisRule

Deletes an analysis rule for a configured table association.

Request Syntax

```
DELETE /memberships/membershipIdentifier/
configuredTableAssociations/configuredTableAssociationIdentifier/
analysisRule/analysisRuleType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analysisRuleType

The type of the analysis rule that you want to delete.

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

configuredTableAssociationIdentifier

The identifier for the configured table association that's related to the analysis rule that you want to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier for the membership that the configured table association belongs to. Currently accepts the membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteIdMappingTable

Deletes an ID mapping table.

Request Syntax

```
DELETE /memberships/membershipIdentifier/idmappingtables/idMappingTableIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

idMappingTableIdentifier

The unique identifier of the ID mapping table that you want to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique identifier of the membership that contains the ID mapping table that you want to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteIdNamespaceAssociation

Deletes an ID namespace association.

Request Syntax

```
DELETE /memberships/membershipIdentifier/
idnamespaceassociations/idNamespaceAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

idNamespaceAssociationIdentifier

The unique identifier of the ID namespace association that you want to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique identifier of the membership that contains the ID namespace association that you want to delete.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteMember

Removes the specified member from a collaboration. The removed member is placed in the Removed status and can't interact with the collaboration. The removed member's data is inaccessible to active members of the collaboration.

Request Syntax

```
DELETE /collaborations/collaborationIdentifier/member/accountId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

accountId

The account ID of the member to remove.

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

collaborationIdentifier

The unique identifier for the associated collaboration.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeleteMembership

Deletes a specified membership. All resources under a membership must be deleted.

Request Syntax

```
DELETE /memberships/membershipIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The identifier for a membership resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

DeletePrivacyBudgetTemplate

Deletes a privacy budget template for a specified collaboration.

Request Syntax

```
DELETE /memberships/membershipIdentifier/
privacybudgettemplates/privacyBudgetTemplateIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The privacy budget template is deleted from the collaboration that this membership belongs to. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetTemplateIdentifier

A unique identifier for your privacy budget template.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetAnalysisTemplate

Retrieves an analysis template.

Request Syntax

```
GET /memberships/membershipIdentifier/analysistemplates/analysisTemplateIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analysisTemplateIdentifier

The identifier for the analysis template resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The identifier for a membership resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
    "analysisTemplate": {
       "analysisParameters": [
          {
             "defaultValue": "string",
             "name": "string",
             "type": "string"
          }
       ],
       "arn": "string",
       "collaborationArn": "string",
       "collaborationId": "string",
       "createTime": number,
       "description": "string",
       "errorMessageConfiguration": {
          "type": "string"
       },
       "format": "string",
       "id": "string",
       "membershipArn": "string",
       "membershipId": "string",
       "name": "string",
       "schema": {
          "referencedTables": [ "string" ]
       },
       "source": { ... },
       "sourceMetadata": { ... },
       "updateTime": number,
       "validations": [
          {
             "reasons": [
                {
                   "message": "string"
                }
             ],
             "status": "string",
             "type": "string"
          }
       ]
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisTemplate

The analysis template.

Type: AnalysisTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetCollaboration

Returns metadata about a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The identifier for the collaboration.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaboration": {
      "analyticsEngine": "string",
      "arn": "string",
      "autoApprovedChangeTypes": [ "string" ],
      "createTime": number,
      "creatorAccountId": "string",
      "creatorDisplayName": "string",
      "dataEncryptionMetadata": {
         "allowCleartext": boolean,
```

```
            "allowDuplicates": boolean,
            "allowJoinsOnColumnsWithDifferentNames": boolean,
            "preserveNulls": boolean
        },
        "description": "string",
        "id": "string",
        "jobLogStatus": "string",
        "membershipArn": "string",
        "membershipId": "string",
        "memberStatus": "string",
        "name": "string",
        "queryLogStatus": "string",
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaboration

The entire collaboration for this identifier.

Type: Collaboration object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetCollaborationAnalysisTemplate

Retrieves an analysis template within a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/analysistemplates/analysisTemplateArn
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analysisTemplateArn

The Amazon Resource Name (ARN) associated with the analysis template within a collaboration.

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: Yes

collaborationIdentifier

A unique identifier for the collaboration that the analysis templates belong to. Currently accepts collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "collaborationAnalysisTemplate": {
      "analysisParameters": [
         {
            "defaultValue": "string",
            "name": "string",
            "type": "string"
         }
      ],
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "creatorAccountId": "string",
      "description": "string",
      "errorMessageConfiguration": {
         "type": "string"
      },
      "format": "string",
      "id": "string",
      "name": "string",
      "schema": {
         "referencedTables": [ "string" ]
      },
      "source": { ... },
      "sourceMetadata": { ... },
      "updateTime": number,
      "validations": [
         {
            "reasons": [
               {
                  "message": "string"
               }
            ],
            "status": "string",
            "type": "string"
         }
      ]
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationAnalysisTemplate

The analysis template within a collaboration.

Type: CollaborationAnalysisTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetCollaborationChangeRequest

Retrieves detailed information about a specific collaboration change request.

Request Syntax

```
GET /collaborations/collaborationIdentifier/changeRequests/changeRequestIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

changeRequestIdentifier

A unique identifier for the change request to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

collaborationIdentifier

The identifier of the collaboration that the change request is made against.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "collaborationChangeRequest": {
      "changes": [
         {
            "specification": { ... },
            "specificationType": "string",
            "types": [ "string" ]
         }
      ],
      "collaborationId": "string",
      "createTime": number,
      "id": "string",
      "isAutoApproved": boolean,
      "status": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationChangeRequest

The collaboration change request that was requested.

Type: CollaborationChangeRequest object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetCollaborationConfiguredAudienceModelAssociation

Retrieves a configured audience model association within a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/
configuredaudiencemodelassociations/configuredAudienceModelAssociationIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the configured audience model association belongs to. Accepts a collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

configuredAudienceModelAssociationIdentifier

A unique identifier for the configured audience model association that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "collaborationConfiguredAudienceModelAssociation": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "configuredAudienceModelArn": "string",
      "createTime": number,
      "creatorAccountId": "string",
      "description": "string",
      "id": "string",
      "name": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationConfiguredAudienceModelAssociation

The metadata of the configured audience model association.

Type: CollaborationConfiguredAudienceModelAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetCollaborationIdNamespaceAssociation

Retrieves an ID namespace association from a specific collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/
idnamespaceassociations/idNamespaceAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The unique identifier of the collaboration that contains the ID namespace association that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

idNamespaceAssociationIdentifier

The unique identifier of the ID namespace association that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "collaborationIdNamespaceAssociation": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "creatorAccountId": "string",
      "description": "string",
      "id": "string",
      "idMappingConfig": {
         "allowUseAsDimensionColumn": boolean
      },
      "inputReferenceConfig": {
         "inputReferenceArn": "string",
         "manageResourcePolicies": boolean
      },
      "inputReferenceProperties": {
         "idMappingWorkflowsSupported": [ JSON value ],
         "idNamespaceType": "string"
      },
      "name": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationIdNamespaceAssociation

The ID namespace association that you requested.

Type: CollaborationIdNamespaceAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetCollaborationPrivacyBudgetTemplate

Returns details about a specified privacy budget template.

Request Syntax

```
GET /collaborations/collaborationIdentifier/
privacybudgettemplates/privacyBudgetTemplateIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for one of your collaborations.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetTemplateIdentifier

A unique identifier for one of your privacy budget templates.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "collaborationPrivacyBudgetTemplate": {
      "arn": "string",
      "autoRefresh": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "creatorAccountId": "string",
      "id": "string",
      "parameters": { ... },
      "privacyBudgetType": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationPrivacyBudgetTemplate

Returns the details of the privacy budget template that you requested.

Type: CollaborationPrivacyBudgetTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetConfiguredAudienceModelAssociation

Returns information about a configured audience model association.

Request Syntax

```
GET /memberships/membershipIdentifier/
configuredaudiencemodelassociations/configuredAudienceModelAssociationIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

configuredAudienceModelAssociationIdentifier

A unique identifier for the configured audience model association that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier for the membership that contains the configured audience model association that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "configuredAudienceModelAssociation": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "configuredAudienceModelArn": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "manageResourcePolicies": boolean,
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredAudienceModelAssociation

Information about the configured audience model association that you requested.

Type: ConfiguredAudienceModelAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetConfiguredTable

Retrieves a configured table.

Request Syntax

```
GET /configuredTables/configuredTableIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableIdentifier

The unique ID for the configured table to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredTable": {
      "allowedColumns": [ "string" ],
      "analysisMethod": "string",
      "analysisRuleTypes": [ "string" ],
      "arn": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
```

```
        "name": "string",
        "selectedAnalysisMethods": [ "string" ],
        "tableReference": { ... },
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTable

The retrieved configured table.

Type: ConfiguredTable object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetConfiguredTableAnalysisRule

Retrieves a configured table analysis rule.

Request Syntax

```
GET /configuredTables/configuredTableIdentifier/analysisRule/analysisRuleType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analysisRuleType

The analysis rule to be retrieved. Configured table analysis rules are uniquely identified by their configured table identifier and analysis rule type.

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

configuredTableIdentifier

The unique identifier for the configured table to retrieve. Currently accepts the configured table ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "analysisRule": {
      "configuredTableArn": "string",
      "configuredTableId": "string",
      "createTime": number,
      "policy": { ... },
      "type": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRule

The entire analysis rule output.

Type: ConfiguredTableAnalysisRule object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetConfiguredTableAssociation

Retrieves a configured table association.

Request Syntax

```
GET /memberships/membershipIdentifier/
configuredTableAssociations/configuredTableAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableAssociationIdentifier

The unique ID for the configured table association to retrieve. Currently accepts the configured table ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier for the membership that the configured table association belongs to. Currently accepts the membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "configuredTableAssociation": {
      "analysisRuleTypes": [ "string" ],
      "arn": "string",
      "configuredTableArn": "string",
      "configuredTableId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "roleArn": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTableAssociation

The entire configured table association object.

Type: ConfiguredTableAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetConfiguredTableAssociationAnalysisRule

Retrieves the analysis rule for a configured table association.

Request Syntax

```
GET /memberships/membershipIdentifier/
configuredTableAssociations/configuredTableAssociationIdentifier/
analysisRule/analysisRuleType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

analysisRuleType

The type of analysis rule that you want to retrieve.

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

configuredTableAssociationIdentifier

The identifier for the configured table association that's related to the analysis rule.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier for the membership that the configured table association belongs to. Currently accepts the membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisRule": {
      "configuredTableAssociationArn": "string",
      "configuredTableAssociationId": "string",
      "createTime": number,
      "membershipIdentifier": "string",
      "policy": { ... },
      "type": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRule

The analysis rule for the configured table association. In the console, the `ConfiguredTableAssociationAnalysisRule` is referred to as the *collaboration analysis rule*.

Type: ConfiguredTableAssociationAnalysisRule object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetIdMappingTable

Retrieves an ID mapping table.

Request Syntax

```
GET /memberships/membershipIdentifier/idmappingtables/idMappingTableIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

idMappingTableIdentifier

The unique identifier of the ID mapping table identifier that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique identifier of the membership that contains the ID mapping table that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "idMappingTable": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "inputReferenceConfig": {
         "inputReferenceArn": "string",
         "manageResourcePolicies": boolean
      },
      "inputReferenceProperties": {
         "idMappingTableInputSource": [
            {
               "idNamespaceAssociationId": "string",
               "type": "string"
            }
         ]
      },
      "kmsKeyArn": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idMappingTable

The ID mapping table that you requested.

Type: IdMappingTable object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetIdNamespaceAssociation

Retrieves an ID namespace association.

Request Syntax

```
GET /memberships/membershipIdentifier/
idnamespaceassociations/idNamespaceAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

idNamespaceAssociationIdentifier

The unique identifier of the ID namespace association that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique identifier of the membership that contains the ID namespace association that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "idNamespaceAssociation": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "idMappingConfig": {
         "allowUseAsDimensionColumn": boolean
      },
      "inputReferenceConfig": {
         "inputReferenceArn": "string",
         "manageResourcePolicies": boolean
      },
      "inputReferenceProperties": {
         "idMappingWorkflowsSupported": [ JSON value ],
         "idNamespaceType": "string"
      },
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idNamespaceAssociation

The ID namespace association that you requested.

Type: IdNamespaceAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin

- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetMembership

Retrieves a specified membership for an identifier.

Request Syntax

```
GET /memberships/membershipIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The identifier for a membership resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "membership": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationCreatorAccountId": "string",
      "collaborationCreatorDisplayName": "string",
      "collaborationId": "string",
      "collaborationName": "string",
      "createTime": number,
      "defaultJobResultConfiguration": {
```

```
            "outputConfiguration": { ... },
            "roleArn": "string"
        },
        "defaultResultConfiguration": {
            "outputConfiguration": { ... },
            "roleArn": "string"
        },
        "id": "string",
        "jobLogStatus": "string",
        "memberAbilities": [ "string" ],
        "mlMemberAbilities": {
            "customMLMemberAbilities": [ "string" ]
        },
        "paymentConfiguration": {
            "jobCompute": {
                "isResponsible": boolean
            },
            "machineLearning": {
                "modelInference": {
                    "isResponsible": boolean
                },
                "modelTraining": {
                    "isResponsible": boolean
                }
            },
            "queryCompute": {
                "isResponsible": boolean
            }
        },
        "queryLogStatus": "string",
        "status": "string",
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

membership

The membership retrieved for the provided identifier.

Type: Membership object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetPrivacyBudgetTemplate

Returns details for a specified privacy budget template.

Request Syntax

```
GET /memberships/membershipIdentifier/
privacybudgettemplates/privacyBudgetTemplateIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The privacy budget template is retrieved from the collaboration that this membership belongs to. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetTemplateIdentifier

A unique identifier for your privacy budget template.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "privacyBudgetTemplate": {
      "arn": "string",
      "autoRefresh": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "parameters": { ... },
      "privacyBudgetType": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

privacyBudgetTemplate

Returns the details of the privacy budget template that you requested.

Type: PrivacyBudgetTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetProtectedJob

Returns job processing metadata.

Request Syntax

```
GET /memberships/membershipIdentifier/protectedJobs/protectedJobIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The identifier for a membership in a protected job instance.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

protectedJobIdentifier

The identifier for the protected job instance.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "protectedJob": {
      "computeConfiguration": { ... },
      "createTime": number,
      "error": {
         "code": "string",
         "message": "string"
      },
      "id": "string",
      "jobParameters": {
         "analysisTemplateArn": "string"
      },
      "membershipArn": "string",
      "membershipId": "string",
      "result": {
         "output": { ... }
      },
      "resultConfiguration": {
         "outputConfiguration": { ... }
      },
      "statistics": {
         "billedResourceUtilization": {
            "units": number
         },
         "totalDurationInMillis": number
      },
      "status": "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

protectedJob

The protected job metadata.

Type: ProtectedJob object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetProtectedQuery

Returns query processing metadata.

Request Syntax

```
GET /memberships/membershipIdentifier/protectedQueries/protectedQueryIdentifier
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The identifier for a membership in a protected query instance.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

protectedQueryIdentifier

The identifier for a protected query instance.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
    "protectedQuery": {
       "computeConfiguration": { ... },
       "createTime": number,
       "differentialPrivacy": {
          "sensitivityParameters": [
             {
                "aggregationExpression": "string",
                "aggregationType": "string",
                "maxColumnValue": number,
                "minColumnValue": number,
                "userContributionLimit": number
             }
          ]
       },
       "error": {
          "code": "string",
          "message": "string"
       },
       "id": "string",
       "membershipArn": "string",
       "membershipId": "string",
       "result": {
          "output": { ... }
       },
       "resultConfiguration": {
          "outputConfiguration": { ... }
       },
       "sqlParameters": {
          "analysisTemplateArn": "string",
          "parameters": {
             "string" : "string"
          },
          "queryString": "string"
       },
       "statistics": {
          "billedResourceUtilization": {
             "units": number
          },
          "totalDurationInMillis": number
       },
       "status": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

protectedQuery

The query processing metadata.

Type: ProtectedQuery object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetSchema

Retrieves the schema for a relation within a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/schemas/name HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the schema belongs to. Currently accepts a collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the relation to retrieve the schema for.

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
    "schema": {
       "analysisMethod": "string",
       "analysisRuleTypes": [ "string" ],
       "collaborationArn": "string",
       "collaborationId": "string",
       "columns": [
          {
             "name": "string",
             "type": "string"
          }
       ],
       "createTime": number,
       "creatorAccountId": "string",
       "description": "string",
       "name": "string",
       "partitionKeys": [
          {
             "name": "string",
             "type": "string"
          }
       ],
       "schemaStatusDetails": [
          {
             "analysisRuleType": "string",
             "analysisType": "string",
             "configurations": [ "string" ],
             "reasons": [
                {
                   "code": "string",
                   "message": "string"
                }
             ],
             "status": "string"
          }
       ],
       "schemaTypeProperties": { ... },
       "selectedAnalysisMethods": [ "string" ],
       "type": "string",
       "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

schema

The entire schema object.

Type: Schema object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

GetSchemaAnalysisRule

Retrieves a schema analysis rule.

Request Syntax

```
GET /collaborations/collaborationIdentifier/schemas/name/analysisRule/type HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the schema belongs to. Currently accepts a collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the schema to retrieve the analysis rule for.

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

type

The type of the schema analysis rule to retrieve. Schema analysis rules are uniquely identified by a combination of the collaboration, the schema name, and their type.

Valid Values: `AGGREGATION | LIST | CUSTOM | ID_MAPPING_TABLE`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisRule": {
      "collaborationId": "string",
      "collaborationPolicy": { ... },
      "consolidatedPolicy": { ... },
      "createTime": number,
      "name": "string",
      "policy": { ... },
      "type": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRule

A specification about how data from the configured table can be used.

Type: AnalysisRule object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListAnalysisTemplates

Lists analysis templates that the caller owns.

Request Syntax

```
GET /memberships/membershipIdentifier/analysistemplates?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

The identifier for a membership resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisTemplateSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "description": "string",
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisTemplateSummaries

Lists analysis template metadata.

Type: Array of AnalysisTemplateSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCollaborationAnalysisTemplates

Lists analysis templates within a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/analysistemplates?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the analysis templates belong to. Currently accepts collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationAnalysisTemplateSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "description": "string",
         "id": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationAnalysisTemplateSummaries

The metadata of the analysis template within a collaboration.

Type: Array of CollaborationAnalysisTemplateSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCollaborationChangeRequests

Lists all change requests for a collaboration with pagination support. Returns change requests sorted by creation time.

Request Syntax

```
GET /collaborations/collaborationIdentifier/changeRequests?
maxResults=maxResults&nextToken=nextToken&status=status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The identifier of the collaboration that the change request is made against.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum number of results that are returned for an API request call.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

status

A filter to only return change requests with the specified status.

Valid Values: `PENDING | APPROVED | CANCELLED | DENIED | COMMITTED`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationChangeRequestSummaries": [
      {
         "changes": [
            {
               "specification": { ... },
               "specificationType": "string",
               "types": [ "string" ]
            }
         ],
         "collaborationId": "string",
         "createTime": number,
         "id": "string",
         "isAutoApproved": boolean,
         "status": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationChangeRequestSummaries

The list of collaboration change request summaries.

Type: Array of CollaborationChangeRequestSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCollaborationConfiguredAudienceModelAssociations

Lists configured audience model associations within a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/configuredaudiencemodelassociations?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the configured audience model association belongs to. Accepts a collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationConfiguredAudienceModelAssociationSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "description": "string",
         "id": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationConfiguredAudienceModelAssociationSummaries

The metadata of the configured audience model association within a collaboration.

Type: Array of CollaborationConfiguredAudienceModelAssociationSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCollaborationIdNamespaceAssociations

Returns a list of the ID namespace associations in a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/idnamespaceassociations?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The unique identifier of the collaboration that contains the ID namespace associations that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum size of the results that is returned per call. Service chooses a default if it has not been set. Service may return a nextToken even if the maximum results has not been met.>

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationIdNamespaceAssociationSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "description": "string",
         "id": "string",
         "inputReferenceConfig": {
            "inputReferenceArn": "string",
            "manageResourcePolicies": boolean
         },
         "inputReferenceProperties": {
            "idNamespaceType": "string"
         },
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationIdNamespaceAssociationSummaries

The summary information of the collaboration ID namespace associations that you requested.

Type: Array of CollaborationIdNamespaceAssociationSummary objects

nextToken

The token value provided to access the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCollaborationPrivacyBudgets

Returns an array that summarizes each privacy budget in a specified collaboration. The summary includes the collaboration ARN, creation time, creating account, and privacy budget details.

Request Syntax

```
GET /collaborations/collaborationIdentifier/privacybudgets?
maxResults=maxResults&nextToken=nextToken&privacyBudgetType=privacyBudgetType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for one of your collaborations.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

privacyBudgetType

Specifies the type of the privacy budget.

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationPrivacyBudgetSummaries": [
      {
         "budget": { ... },
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "id": "string",
         "privacyBudgetTemplateArn": "string",
         "privacyBudgetTemplateId": "string",
         "type": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationPrivacyBudgetSummaries

Summaries of the collaboration privacy budgets.

Type: Array of CollaborationPrivacyBudgetSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface

- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCollaborationPrivacyBudgetTemplates

Returns an array that summarizes each privacy budget template in a specified collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/privacybudgettemplates?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for one of your collaborations.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaborationPrivacyBudgetTemplateSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "id": "string",
         "privacyBudgetType": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationPrivacyBudgetTemplateSummaries

An array that summarizes the collaboration privacy budget templates. The summary includes collaboration information, creation information, the privacy budget type.

Type: Array of CollaborationPrivacyBudgetTemplateSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListCollaborations

Lists collaborations the caller owns, is active in, or has been invited to.

Request Syntax

```
GET /collaborations?maxResults=maxResults&memberStatus=memberStatus&nextToken=nextToken
 HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

memberStatus

The caller's status in a collaboration.

Valid Values: `INVITED | ACTIVE`

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "collaborationList": [
      {
         "analyticsEngine": "string",
         "arn": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "creatorDisplayName": "string",
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "memberStatus": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaborationList

The list of collaborations.

Type: Array of CollaborationSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListConfiguredAudienceModelAssociations

Lists information about requested configured audience model associations.

Request Syntax

```
GET /memberships/membershipIdentifier/configuredaudiencemodelassociations?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

A unique identifier for a membership that contains the configured audience model associations that you want to retrieve.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredAudienceModelAssociationSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "configuredAudienceModelArn": "string",
         "createTime": number,
         "description": "string",
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredAudienceModelAssociationSummaries

Summaries of the configured audience model associations that you requested.

Type: Array of ConfiguredAudienceModelAssociationSummary objects

nextToken

The token value provided to access the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListConfiguredTableAssociations

Lists configured table associations for a membership.

Request Syntax

```
GET /memberships/membershipIdentifier/configuredTableAssociations?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

A unique identifier for the membership to list configured table associations for. Currently accepts the membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredTableAssociationSummaries": [
      {
         "analysisRuleTypes": [ "string" ],
         "arn": "string",
         "configuredTableId": "string",
         "createTime": number,
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTableAssociationSummaries

The retrieved list of configured table associations.

Type: Array of ConfiguredTableAssociationSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListConfiguredTables

Lists configured tables.

Request Syntax

```
GET /configuredTables?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredTableSummaries": [
      {
         "analysisMethod": "string",
         "analysisRuleTypes": [ "string" ],
```

```
            "arn": "string",
            "createTime": number,
            "id": "string",
            "name": "string",
            "selectedAnalysisMethods": [ "string" ],
            "updateTime": number
        }
    ],
    "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTableSummaries

The configured tables listed by the request.

Type: Array of ConfiguredTableSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListIdMappingTables

Returns a list of ID mapping tables.

Request Syntax

```
GET /memberships/membershipIdentifier/idmappingtables?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum size of the results that is returned per call. Service chooses a default if it has not been set. Service may return a nextToken even if the maximum results has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

The unique identifier of the membership that contains the ID mapping tables that you want to view.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "idMappingTableSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "description": "string",
         "id": "string",
         "inputReferenceConfig": {
            "inputReferenceArn": "string",
            "manageResourcePolicies": boolean
         },
         "membershipArn": "string",
         "membershipId": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idMappingTableSummaries

The summary information of the ID mapping tables that you requested.

Type: Array of IdMappingTableSummary objects

nextToken

The token value provided to access the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET

- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListIdNamespaceAssociations

Returns a list of ID namespace associations.

Request Syntax

```
GET /memberships/membershipIdentifier/idnamespaceassociations?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum size of the results that is returned per call. Service chooses a default if it has not been set. Service may return a nextToken even if the maximum results has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

The unique identifier of the membership that contains the ID namespace association that you want to view.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "idNamespaceAssociationSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "description": "string",
         "id": "string",
         "inputReferenceConfig": {
            "inputReferenceArn": "string",
            "manageResourcePolicies": boolean
         },
         "inputReferenceProperties": {
            "idNamespaceType": "string"
         },
         "membershipArn": "string",
         "membershipId": "string",
         "name": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idNamespaceAssociationSummaries

The summary information of the ID namespace associations that you requested.

Type: Array of IdNamespaceAssociationSummary objects

nextToken

The token value provided to access the next page of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListMembers

Lists all members within a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/members?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The identifier of the collaboration in which the members are listed.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "memberSummaries": [
      {
         "abilities": [ "string" ],
         "accountId": "string",
         "createTime": number,
         "displayName": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "mlAbilities": {
            "customMLMemberAbilities": [ "string" ]
         },
         "paymentConfiguration": {
            "jobCompute": {
               "isResponsible": boolean
            },
            "machineLearning": {
               "modelInference": {
                  "isResponsible": boolean
               },
               "modelTraining": {
                  "isResponsible": boolean
               }
            },
            "queryCompute": {
               "isResponsible": boolean
            }
         },
         "status": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

memberSummaries

The list of members returned by the ListMembers operation.

Type: Array of MemberSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListMemberships

Lists all memberships resources within the caller's account.

Request Syntax

```
GET /memberships?maxResults=maxResults&nextToken=nextToken&status=status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

status

A filter which will return only memberships in the specified status.

Valid Values: `ACTIVE | REMOVED | COLLABORATION_DELETED`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
   "membershipSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationCreatorAccountId": "string",
         "collaborationCreatorDisplayName": "string",
         "collaborationId": "string",
         "collaborationName": "string",
         "createTime": number,
         "id": "string",
         "memberAbilities": [ "string" ],
         "mlMemberAbilities": {
            "customMLMemberAbilities": [ "string" ]
         },
         "paymentConfiguration": {
            "jobCompute": {
               "isResponsible": boolean
            },
            "machineLearning": {
               "modelInference": {
                  "isResponsible": boolean
               },
               "modelTraining": {
                  "isResponsible": boolean
               }
            },
            "queryCompute": {
               "isResponsible": boolean
            }
         },
         "status": "string",
         "updateTime": number
      }
   ],
   "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

membershipSummaries

The list of memberships returned from the ListMemberships operation.

Type: Array of MembershipSummary objects

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListPrivacyBudgets

Returns detailed information about the privacy budgets in a specified membership.

Request Syntax

```
GET /memberships/membershipIdentifier/privacybudgets?
maxResults=maxResults&nextToken=nextToken&privacyBudgetType=privacyBudgetType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The privacy budget is retrieved from the collaboration that this membership belongs to. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

privacyBudgetType

The privacy budget type.

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "nextToken": "string",
   "privacyBudgetSummaries": [
      {
         "budget": { ... },
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "privacyBudgetTemplateArn": "string",
         "privacyBudgetTemplateId": "string",
         "type": "string",
         "updateTime": number
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

privacyBudgetSummaries

An array that summarizes the privacy budgets. The summary includes collaboration information, membership information, privacy budget template information, and privacy budget details.

Type: Array of PrivacyBudgetSummary objects

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListPrivacyBudgetTemplates

Returns detailed information about the privacy budget templates in a specified membership.

Request Syntax

```
GET /memberships/membershipIdentifier/privacybudgettemplates?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The privacy budget templates are retrieved from the collaboration that this membership belongs to. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "nextToken": "string",
   "privacyBudgetTemplateSummaries": [
      {
         "arn": "string",
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "privacyBudgetType": "string",
         "updateTime": number
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

privacyBudgetTemplateSummaries

An array that summarizes the privacy budget templates. The summary includes collaboration information, creation information, and privacy budget type.

Type: Array of PrivacyBudgetTemplateSummary objects

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListProtectedJobs

Lists protected jobs, sorted by most recent job.

Request Syntax

```
GET /memberships/membershipIdentifier/protectedJobs?
maxResults=maxResults&nextToken=nextToken&status=status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

The identifier for the membership in the collaboration.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

status

A filter on the status of the protected job.

Valid Values: `SUBMITTED | STARTED | CANCELLED | CANCELLING | FAILED | SUCCESS`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "nextToken": "string",
   "protectedJobs": [
      {
         "createTime": number,
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "receiverConfigurations": [
            {
               "analysisType": "string",
               "configurationDetails": { ... }
            }
         ],
         "status": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

protectedJobs

A list of protected job summaries.

Type: Array of ProtectedJobSummary objects

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListProtectedQueries

Lists protected queries, sorted by the most recent query.

Request Syntax

```
GET /memberships/membershipIdentifier/protectedQueries?
maxResults=maxResults&nextToken=nextToken&status=status HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

membershipIdentifier

The identifier for the membership in the collaboration.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

status

A filter on the status of the protected query.

Valid Values: `SUBMITTED | STARTED | CANCELLED | CANCELLING | FAILED | SUCCESS | TIMED_OUT`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "nextToken": "string",
   "protectedQueries": [
      {
         "createTime": number,
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "receiverConfigurations": [
            {
               "analysisType": "string",
               "configurationDetails": { ... }
            }
         ],
         "status": "string"
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

protectedQueries

A list of protected queries.

Type: Array of ProtectedQuerySummary objects

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListSchemas

Lists the schemas for relations within a collaboration.

Request Syntax

```
GET /collaborations/collaborationIdentifier/schemas?
maxResults=maxResults&nextToken=nextToken&schemaType=schemaType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

A unique identifier for the collaboration that the schema belongs to. Currently accepts a collaboration ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

maxResults

The maximum number of results that are returned for an API request call. The service chooses a default number if you don't set one. The service might return a `nextToken` even if the `maxResults` value has not been met.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

The pagination token that's used to fetch the next set of results.

Length Constraints: Minimum length of 0. Maximum length of 10240.

schemaType

If present, filter schemas by schema type.

Valid Values: `TABLE | ID_MAPPING_TABLE`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "nextToken": "string",
   "schemaSummaries": [
      {
         "analysisMethod": "string",
         "analysisRuleTypes": [ "string" ],
         "collaborationArn": "string",
         "collaborationId": "string",
         "createTime": number,
         "creatorAccountId": "string",
         "name": "string",
         "selectedAnalysisMethods": [ "string" ],
         "type": "string",
         "updateTime": number
      }
   ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The pagination token that's used to fetch the next set of results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10240.

schemaSummaries

The retrieved list of schemas.

Type: Array of SchemaSummary objects

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

ListTagsForResource

Lists all of the tags that have been added to a resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) associated with the resource you want to list tags on.

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:[\d\w/-]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "tags": {
      "string" : "string"
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A map of objects specifying each key name and value.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see Common Errors.

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2

- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

PopulateIdMappingTable

Defines the information that's necessary to populate an ID mapping table.

Request Syntax

```
POST /memberships/membershipIdentifier/idmappingtables/idMappingTableIdentifier/
populate HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

idMappingTableIdentifier

The unique identifier of the ID mapping table that you want to populate.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique identifier of the membership that contains the ID mapping table that you want to populate.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "idMappingJobId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idMappingJobId

The unique identifier of the mapping job that will populate the ID mapping table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

PreviewPrivacyImpact

An estimate of the number of aggregation functions that the member who can query can run given epsilon and noise parameters.

Request Syntax

```
POST /memberships/membershipIdentifier/previewprivacyimpact HTTP/1.1
Content-type: application/json

{
   "parameters": { ... }
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

parameters

Specifies the desired epsilon and noise parameters to preview.

Type: PreviewPrivacyImpactParametersInput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "privacyImpact": { ... }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

privacyImpact

An estimate of the number of aggregation functions that the member who can query can run given the epsilon and noise parameters. This does not change the privacy budget.

Type: PrivacyImpact object

Note: This object is a Union. Only one member of this object can be specified or returned.

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartProtectedJob

Creates a protected job that is started by AWS Clean Rooms.

Request Syntax

```
POST /memberships/membershipIdentifier/protectedJobs HTTP/1.1
Content-type: application/json

{
   "computeConfiguration": { ... },
   "jobParameters": {
      "analysisTemplateArn": "string"
   },
   "resultConfiguration": {
      "outputConfiguration": { ... }
   },
   "type": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for the membership to run this job against. Currently accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

computeConfiguration

The compute configuration for the protected job.

Type: ProtectedJobComputeConfiguration object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

jobParameters

The job parameters.

Type: ProtectedJobParameters object

Required: Yes

resultConfiguration

The details needed to write the job results.

Type: ProtectedJobResultConfigurationInput object

Required: No

type

The type of protected job to start.

Type: String

Valid Values: PYSPARK

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "protectedJob": {
      "computeConfiguration": { ... },
      "createTime": number,
      "error": {
         "code": "string",
         "message": "string"
```

```
        },
        "id": "string",
        "jobParameters": {
           "analysisTemplateArn": "string"
        },
        "membershipArn": "string",
        "membershipId": "string",
        "result": {
           "output": { ... }
        },
        "resultConfiguration": {
           "outputConfiguration": { ... }
        },
        "statistics": {
           "billedResourceUtilization": {
              "units": number
           },
           "totalDurationInMillis": number
        },
        "status": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

protectedJob

The protected job.

Type: ProtectedJob object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3

- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

StartProtectedQuery

Creates a protected query that is started by AWS Clean Rooms.

Request Syntax

```
POST /memberships/membershipIdentifier/protectedQueries HTTP/1.1
Content-type: application/json

{
   "computeConfiguration": { ... },
   "resultConfiguration": {
      "outputConfiguration": { ... }
   },
   "sqlParameters": {
      "analysisTemplateArn": "string",
      "parameters": {
         "string" : "string"
      },
      "queryString": "string"
   },
   "type": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for the membership to run this query against. Currently accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

computeConfiguration

The compute configuration for the protected query.

Type: ComputeConfiguration object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

resultConfiguration

The details needed to write the query results.

Type: ProtectedQueryResultConfiguration object

Required: No

sqlParameters

The protected SQL query parameters.

Type: ProtectedQuerySQLParameters object

Required: Yes

type

The type of the protected query to be started.

Type: String

Valid Values: SQL

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "protectedQuery": {
      "computeConfiguration": { ... },
      "createTime": number,
      "differentialPrivacy": {
```

```
            "sensitivityParameters": [
               {
                  "aggregationExpression": "string",
                  "aggregationType": "string",
                  "maxColumnValue": number,
                  "minColumnValue": number,
                  "userContributionLimit": number
               }
            ]
         },
         "error": {
            "code": "string",
            "message": "string"
         },
         "id": "string",
         "membershipArn": "string",
         "membershipId": "string",
         "result": {
            "output": { ... }
         },
         "resultConfiguration": {
            "outputConfiguration": { ... }
         },
         "sqlParameters": {
            "analysisTemplateArn": "string",
            "parameters": {
               "string" : "string"
            },
            "queryString": "string"
         },
         "statistics": {
            "billedResourceUtilization": {
               "units": number
            },
            "totalDurationInMillis": number
         },
         "status": "string"
      }
   }
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

protectedQuery

The protected query.

Type: ProtectedQuery object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

TagResource

Tags a resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
   "tags": {
      "string" : "string"
   }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) associated with the resource you want to tag.

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:[\d\w/-]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

A map of objects specifying each key name and value.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2

- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UntagResource

Removes a tag or list of tags from a resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) associated with the resource you want to remove the tag from.

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:[\d\w/-]+`

Required: Yes

tagKeys

A list of key names of tags to be removed.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see Common Errors.

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateAnalysisTemplate

Updates the analysis template metadata.

Request Syntax

```
PATCH /memberships/membershipIdentifier/analysistemplates/analysisTemplateIdentifier
 HTTP/1.1
Content-type: application/json

{
   "description": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

analysisTemplateIdentifier

The identifier for the analysis template resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The identifier for a membership resource.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

A new description for the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisTemplate": {
      "analysisParameters": [
         {
            "defaultValue": "string",
            "name": "string",
            "type": "string"
         }
      ],
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "description": "string",
      "errorMessageConfiguration": {
         "type": "string"
      },
      "format": "string",
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "schema": {
         "referencedTables": [ "string" ]
      },
      "source": { ... },
```

```
        "sourceMetadata": { ... },
        "updateTime": number,
        "validations": [
           {
              "reasons": [
                 {
                    "message": "string"
                 }
              ],
              "status": "string",
              "type": "string"
           }
        ]
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisTemplate

The analysis template.

Type: AnalysisTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateCollaboration

Updates collaboration metadata and can only be called by the collaboration owner.

Request Syntax

```
PATCH /collaborations/collaborationIdentifier HTTP/1.1
Content-type: application/json

{
   "analyticsEngine": "string",
   "description": "string",
   "name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

collaborationIdentifier

The identifier for the collaboration.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

analyticsEngine

The analytics engine.

> **Note**
>
> After July 16, 2025, the `CLEAN_ROOMS_SQL` parameter will no longer be available.

Type: String

Valid Values: `SPARK | CLEAN_ROOMS_SQL`

Required: No

description

A description of the collaboration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

name

A human-readable identifier provided by the collaboration owner. Display names are not unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "collaboration": {
      "analyticsEngine": "string",
      "arn": "string",
      "autoApprovedChangeTypes": [ "string" ],
```

```
        "createTime": number,
        "creatorAccountId": "string",
        "creatorDisplayName": "string",
        "dataEncryptionMetadata": {
           "allowCleartext": boolean,
           "allowDuplicates": boolean,
           "allowJoinsOnColumnsWithDifferentNames": boolean,
           "preserveNulls": boolean
        },
        "description": "string",
        "id": "string",
        "jobLogStatus": "string",
        "membershipArn": "string",
        "membershipId": "string",
        "memberStatus": "string",
        "name": "string",
        "queryLogStatus": "string",
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collaboration

The entire collaboration that has been updated.

Type: Collaboration object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateConfiguredAudienceModelAssociation

Provides the details necessary to update a configured audience model association.

Request Syntax

```
PATCH /memberships/membershipIdentifier/
configuredaudiencemodelassociations/configuredAudienceModelAssociationIdentifier
 HTTP/1.1
Content-type: application/json

{
   "description": "string",
   "name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

configuredAudienceModelAssociationIdentifier

A unique identifier for the configured audience model association that you want to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier of the membership that contains the configured audience model association that you want to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

A new description for the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

name

A new name for the configured audience model association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredAudienceModelAssociation": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "configuredAudienceModelArn": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "manageResourcePolicies": boolean,
```

```
        "membershipArn": "string",
        "membershipId": "string",
        "name": "string",
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredAudienceModelAssociation

Details about the configured audience model association that you updated.

Type: ConfiguredAudienceModelAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateConfiguredTable

Updates a configured table.

Request Syntax

```
PATCH /configuredTables/configuredTableIdentifier HTTP/1.1
Content-type: application/json

{
   "allowedColumns": [ "string" ],
   "analysisMethod": "string",
   "description": "string",
   "name": "string",
   "selectedAnalysisMethods": [ "string" ],
   "tableReference": { ... }
}
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableIdentifier

The identifier for the configured table to update. Currently accepts the configured table ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

allowedColumns

The columns of the underlying table that can be used by collaborations or analysis rules.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: No

analysisMethod

The analysis method for the configured table.

`DIRECT_QUERY` allows SQL queries to be run directly on this table.

`DIRECT_JOB` allows PySpark jobs to be run directly on this table.

`MULTIPLE` allows both SQL queries and PySpark jobs to be run directly on this table.

Type: String

Valid Values: `DIRECT_QUERY | DIRECT_JOB | MULTIPLE`

Required: No

description

A new description for the configured table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

name

A new name for the configured table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: No

selectedAnalysisMethods

The selected analysis methods for the table configuration update.

Type: Array of strings

Valid Values: `DIRECT_QUERY | DIRECT_JOB`

Required: No

tableReference

A pointer to the dataset that underlies this table.

Type: TableReference object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredTable": {
      "allowedColumns": [ "string" ],
      "analysisMethod": "string",
      "analysisRuleTypes": [ "string" ],
      "arn": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "name": "string",
      "selectedAnalysisMethods": [ "string" ],
      "tableReference": { ... },
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTable

The updated configured table.

Type: ConfiguredTable object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

Request denied because service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateConfiguredTableAnalysisRule

Updates a configured table analysis rule.

Request Syntax

```
PATCH /configuredTables/configuredTableIdentifier/analysisRule/analysisRuleType
 HTTP/1.1
Content-type: application/json

{
   "analysisRulePolicy": { ... }
}
```

URI Request Parameters

The request uses the following URI parameters.

analysisRuleType

The analysis rule type to be updated. Configured table analysis rules are uniquely identified by their configured table identifier and analysis rule type.

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

configuredTableIdentifier

The unique identifier for the configured table that the analysis rule applies to. Currently accepts the configured table ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

analysisRulePolicy

The new analysis rule policy for the configured table analysis rule.

Type: ConfiguredTableAnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisRule": {
      "configuredTableArn": "string",
      "configuredTableId": "string",
      "createTime": number,
      "policy": { ... },
      "type": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRule

The entire updated analysis rule.

Type: ConfiguredTableAnalysisRule object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++

- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateConfiguredTableAssociation

Updates a configured table association.

Request Syntax

```
PATCH /memberships/membershipIdentifier/
configuredTableAssociations/configuredTableAssociationIdentifier HTTP/1.1
Content-type: application/json

{
   "description": "string",
   "roleArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

configuredTableAssociationIdentifier

The unique identifier for the configured table association to update. Currently accepts the configured table association ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique ID for the membership that the configured table association belongs to.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

A new description for the configured table association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

roleArn

The service will assume this role to access catalog metadata and query the table.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 512.

Pattern: `arn:aws:iam::[\w]+:role/[\w+=./@-]+`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "configuredTableAssociation": {
      "analysisRuleTypes": [ "string" ],
      "arn": "string",
      "configuredTableArn": "string",
      "configuredTableId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "name": "string",
      "roleArn": "string",
      "updateTime": number
   }
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configuredTableAssociation

The entire updated configured table association.

Type: ConfiguredTableAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateConfiguredTableAssociationAnalysisRule

Updates the analysis rule for a configured table association.

Request Syntax

```
PATCH /memberships/membershipIdentifier/
configuredTableAssociations/configuredTableAssociationIdentifier/
analysisRule/analysisRuleType HTTP/1.1
Content-type: application/json

{
   "analysisRulePolicy": { ... }
}
```

URI Request Parameters

The request uses the following URI parameters.

analysisRuleType

The analysis rule type that you want to update.

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

configuredTableAssociationIdentifier

The identifier for the configured table association to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

A unique identifier for the membership that the configured table association belongs to. Currently accepts the membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

analysisRulePolicy

The updated analysis rule policy for the configured table association.

Type: ConfiguredTableAssociationAnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "analysisRule": {
      "configuredTableAssociationArn": "string",
      "configuredTableAssociationId": "string",
      "createTime": number,
      "membershipIdentifier": "string",
      "policy": { ... },
      "type": "string",
      "updateTime": number
   }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

analysisRule

The updated analysis rule for the configured table association. In the console, the `ConfiguredTableAssociationAnalysisRule` is referred to as the *collaboration analysis rule*.

Type: ConfiguredTableAssociationAnalysisRule object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateIdMappingTable

Provides the details that are necessary to update an ID mapping table.

Request Syntax

```
PATCH /memberships/membershipIdentifier/idmappingtables/idMappingTableIdentifier
 HTTP/1.1
Content-type: application/json

{
   "description": "string",
   "kmsKeyArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

idMappingTableIdentifier

The unique identifier of the ID mapping table that you want to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique identifier of the membership that contains the ID mapping table that you want to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

A new description for the ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

kmsKeyArn

The Amazon Resource Name (ARN) of the AWS KMS key.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:kms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:key/[a-zA-Z0-9-]+`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "idMappingTable": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "description": "string",
      "id": "string",
      "inputReferenceConfig": {
         "inputReferenceArn": "string",
         "manageResourcePolicies": boolean
      },
      "inputReferenceProperties": {
         "idMappingTableInputSource": [
            {
```

```
                "idNamespaceAssociationId": "string",
                "type": "string"
            }
        ]
    },
    "kmsKeyArn": "string",
    "membershipArn": "string",
    "membershipId": "string",
    "name": "string",
    "updateTime": number
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idMappingTable

The updated ID mapping table.

Type: IdMappingTable object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateIdNamespaceAssociation

Provides the details that are necessary to update an ID namespace association.

Request Syntax

```
PATCH /memberships/membershipIdentifier/
idnamespaceassociations/idNamespaceAssociationIdentifier HTTP/1.1
Content-type: application/json

{
   "description": "string",
   "idMappingConfig": {
      "allowUseAsDimensionColumn": boolean
   },
   "name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

idNamespaceAssociationIdentifier

The unique identifier of the ID namespace association that you want to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipIdentifier

The unique identifier of the membership that contains the ID namespace association that you want to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

description

A new description for the ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

idMappingConfig

The configuration settings for the ID mapping table.

Type: IdMappingConfig object

Required: No

name

A new name for the ID namespace association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "idNamespaceAssociation": {
      "arn": "string",
```

```
        "collaborationArn": "string",
        "collaborationId": "string",
        "createTime": number,
        "description": "string",
        "id": "string",
        "idMappingConfig": {
           "allowUseAsDimensionColumn": boolean
        },
        "inputReferenceConfig": {
           "inputReferenceArn": "string",
           "manageResourcePolicies": boolean
        },
        "inputReferenceProperties": {
           "idMappingWorkflowsSupported": [ JSON value ],
           "idNamespaceType": "string"
        },
        "membershipArn": "string",
        "membershipId": "string",
        "name": "string",
        "updateTime": number
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

idNamespaceAssociation

The updated ID namespace association.

Type: IdNamespaceAssociation object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateMembership

Updates a membership.

Request Syntax

```
PATCH /memberships/membershipIdentifier HTTP/1.1
Content-type: application/json

{
   "defaultJobResultConfiguration": {
      "outputConfiguration": { ... },
      "roleArn": "string"
   },
   "defaultResultConfiguration": {
      "outputConfiguration": { ... },
      "roleArn": "string"
   },
   "jobLogStatus": "string",
   "queryLogStatus": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The unique identifier of the membership.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

defaultJobResultConfiguration

The default job result configuration.

Type: MembershipProtectedJobResultConfiguration object

Required: No

defaultResultConfiguration

The default protected query result configuration as specified by the member who can receive results.

Type: MembershipProtectedQueryResultConfiguration object

Required: No

jobLogStatus

An indicator as to whether job logging has been enabled or disabled for the collaboration.

When `ENABLED`, AWS Clean Rooms logs details about jobs run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: No

queryLogStatus

An indicator as to whether query logging has been enabled or disabled for the membership.

When `ENABLED`, AWS Clean Rooms logs details about queries run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
   "membership": {
      "arn": "string",
      "collaborationArn": "string",
      "collaborationCreatorAccountId": "string",
      "collaborationCreatorDisplayName": "string",
      "collaborationId": "string",
      "collaborationName": "string",
      "createTime": number,
      "defaultJobResultConfiguration": {
         "outputConfiguration": { ... },
         "roleArn": "string"
      },
      "defaultResultConfiguration": {
         "outputConfiguration": { ... },
         "roleArn": "string"
      },
      "id": "string",
      "jobLogStatus": "string",
      "memberAbilities": [ "string" ],
      "mlMemberAbilities": {
         "customMLMemberAbilities": [ "string" ]
      },
      "paymentConfiguration": {
         "jobCompute": {
            "isResponsible": boolean
         },
         "machineLearning": {
            "modelInference": {
               "isResponsible": boolean
            },
            "modelTraining": {
               "isResponsible": boolean
            }
         },
         "queryCompute": {
            "isResponsible": boolean
         }
      },
      "queryLogStatus": "string",
      "status": "string",
      "updateTime": number
```

```
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

membership

The membership object.

Type: Membership object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdatePrivacyBudgetTemplate

Updates the privacy budget template for the specified collaboration.

Request Syntax

```
PATCH /memberships/membershipIdentifier/
privacybudgettemplates/privacyBudgetTemplateIdentifier HTTP/1.1
Content-type: application/json

{
   "parameters": { ... },
   "privacyBudgetType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

A unique identifier for one of your memberships for a collaboration. The privacy budget template is updated in the collaboration that this membership belongs to. Accepts a membership ID.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetTemplateIdentifier

A unique identifier for your privacy budget template that you want to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

parameters

Specifies the epsilon and noise parameters for the privacy budget template.

Type: PrivacyBudgetTemplateUpdateParameters object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

privacyBudgetType

Specifies the type of the privacy budget template.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "privacyBudgetTemplate": {
      "arn": "string",
      "autoRefresh": "string",
      "collaborationArn": "string",
      "collaborationId": "string",
      "createTime": number,
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "parameters": { ... },
      "privacyBudgetType": "string",
      "updateTime": number
   }
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

privacyBudgetTemplate

Summary of the privacy budget template.

Type: PrivacyBudgetTemplate object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateProtectedJob

Updates the processing of a currently running job.

Request Syntax

```
PATCH /memberships/membershipIdentifier/protectedJobs/protectedJobIdentifier HTTP/1.1
Content-type: application/json

{
   "targetStatus": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The identifier for a member of a protected job instance.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

protectedJobIdentifier

The identifier of the protected job to update.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

targetStatus

The target status of a protected job. Used to update the execution status of a currently running job.

Type: String

Valid Values: CANCELLED

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "protectedJob": {
      "computeConfiguration": { ... },
      "createTime": number,
      "error": {
         "code": "string",
         "message": "string"
      },
      "id": "string",
      "jobParameters": {
         "analysisTemplateArn": "string"
      },
      "membershipArn": "string",
      "membershipId": "string",
      "result": {
         "output": { ... }
      },
      "resultConfiguration": {
         "outputConfiguration": { ... }
      },
      "statistics": {
         "billedResourceUtilization": {
            "units": number
         },
         "totalDurationInMillis": number
      },
```

```
        "status": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

protectedJob

The protected job output.

Type: ProtectedJob object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

UpdateProtectedQuery

Updates the processing of a currently running query.

Request Syntax

```
PATCH /memberships/membershipIdentifier/protectedQueries/protectedQueryIdentifier
 HTTP/1.1
Content-type: application/json

{
   "targetStatus": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

membershipIdentifier

The identifier for a member of a protected query instance.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

protectedQueryIdentifier

The identifier for a protected query instance.

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

targetStatus

The target status of a query. Used to update the execution status of a currently running query.

Type: String

Valid Values: `CANCELLED`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
   "protectedQuery": {
      "computeConfiguration": { ... },
      "createTime": number,
      "differentialPrivacy": {
         "sensitivityParameters": [
            {
               "aggregationExpression": "string",
               "aggregationType": "string",
               "maxColumnValue": number,
               "minColumnValue": number,
               "userContributionLimit": number
            }
         ]
      },
      "error": {
         "code": "string",
         "message": "string"
      },
      "id": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "result": {
         "output": { ... }
      },
      "resultConfiguration": {
         "outputConfiguration": { ... }
      },
```

```
        "sqlParameters": {
           "analysisTemplateArn": "string",
           "parameters": {
              "string" : "string"
           },
           "queryString": "string"
        },
        "statistics": {
           "billedResourceUtilization": {
              "units": number
           },
           "totalDurationInMillis": number
        },
        "status": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

protectedQuery

The protected query output.

Type: ProtectedQuery object

Errors

For information about the errors that are common to all actions, see Common Errors.

AccessDeniedException

Caller does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Unexpected error during processing of request.

HTTP Status Code: 500

ResourceNotFoundException

Request references a resource which does not exist.

HTTP Status Code: 404

ThrottlingException

Request was denied due to request throttling.

HTTP Status Code: 429

ValidationException

The input fails to satisfy the specified constraints.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS Command Line Interface
- AWS SDK for .NET
- AWS SDK for C++
- AWS SDK for Go v2
- AWS SDK for Java V2
- AWS SDK for JavaScript V3
- AWS SDK for Kotlin
- AWS SDK for PHP V3
- AWS SDK for Python
- AWS SDK for Ruby V3

Data Types

The AWS Clean Rooms Service API contains several data types that various actions use. This section describes each data type in detail.

> **Note**
>
> The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- AggregateColumn
- AggregationConstraint
- AnalysisParameter
- AnalysisRule
- AnalysisRuleAggregation
- AnalysisRuleCustom
- AnalysisRuleIdMappingTable
- AnalysisRuleList
- AnalysisRulePolicy
- AnalysisRulePolicyV1
- AnalysisSchema
- AnalysisSource
- AnalysisSourceMetadata
- AnalysisTemplate
- AnalysisTemplateArtifact
- AnalysisTemplateArtifactMetadata
- AnalysisTemplateArtifacts
- AnalysisTemplateSummary
- AnalysisTemplateValidationStatusDetail
- AnalysisTemplateValidationStatusReason

- AthenaTableReference
- BatchGetCollaborationAnalysisTemplateError
- BatchGetSchemaAnalysisRuleError
- BatchGetSchemaError
- BilledJobResourceUtilization
- BilledResourceUtilization
- Change
- ChangeInput
- ChangeSpecification
- Collaboration
- CollaborationAnalysisTemplate
- CollaborationAnalysisTemplateSummary
- CollaborationChangeRequest
- CollaborationChangeRequestSummary
- CollaborationConfiguredAudienceModelAssociation
- CollaborationConfiguredAudienceModelAssociationSummary
- CollaborationIdNamespaceAssociation
- CollaborationIdNamespaceAssociationSummary
- CollaborationPrivacyBudgetSummary
- CollaborationPrivacyBudgetTemplate
- CollaborationPrivacyBudgetTemplateSummary
- CollaborationSummary
- Column
- ComputeConfiguration
- ConfigurationDetails
- ConfiguredAudienceModelAssociation
- ConfiguredAudienceModelAssociationSummary
- ConfiguredTable
- ConfiguredTableAnalysisRule
- ConfiguredTableAnalysisRulePolicy

- ConfiguredTableAnalysisRulePolicyV1
- ConfiguredTableAssociation
- ConfiguredTableAssociationAnalysisRule
- ConfiguredTableAssociationAnalysisRuleAggregation
- ConfiguredTableAssociationAnalysisRuleCustom
- ConfiguredTableAssociationAnalysisRuleList
- ConfiguredTableAssociationAnalysisRulePolicy
- ConfiguredTableAssociationAnalysisRulePolicyV1
- ConfiguredTableAssociationSummary
- ConfiguredTableSummary
- ConsolidatedPolicy
- ConsolidatedPolicyAggregation
- ConsolidatedPolicyCustom
- ConsolidatedPolicyList
- ConsolidatedPolicyV1
- DataEncryptionMetadata
- DifferentialPrivacyColumn
- DifferentialPrivacyConfiguration
- DifferentialPrivacyParameters
- DifferentialPrivacyPreviewAggregation
- DifferentialPrivacyPreviewParametersInput
- DifferentialPrivacyPrivacyBudget
- DifferentialPrivacyPrivacyBudgetAggregation
- DifferentialPrivacyPrivacyImpact
- DifferentialPrivacySensitivityParameters
- DifferentialPrivacyTemplateParametersInput
- DifferentialPrivacyTemplateParametersOutput
- DifferentialPrivacyTemplateUpdateParameters
- DirectAnalysisConfigurationDetails
- ErrorMessageConfiguration

- GlueTableReference
- Hash
- IdMappingConfig
- IdMappingTable
- IdMappingTableInputReferenceConfig
- IdMappingTableInputReferenceProperties
- IdMappingTableInputSource
- IdMappingTableSchemaTypeProperties
- IdMappingTableSummary
- IdNamespaceAssociation
- IdNamespaceAssociationInputReferenceConfig
- IdNamespaceAssociationInputReferenceProperties
- IdNamespaceAssociationInputReferencePropertiesSummary
- IdNamespaceAssociationSummary
- JobComputePaymentConfig
- MemberChangeSpecification
- Membership
- MembershipJobComputePaymentConfig
- MembershipMLPaymentConfig
- MembershipModelInferencePaymentConfig
- MembershipModelTrainingPaymentConfig
- MembershipPaymentConfiguration
- MembershipProtectedJobOutputConfiguration
- MembershipProtectedJobResultConfiguration
- MembershipProtectedQueryOutputConfiguration
- MembershipProtectedQueryResultConfiguration
- MembershipQueryComputePaymentConfig
- MembershipSummary
- MemberSpecification
- MemberSummary

- MLMemberAbilities
- MLPaymentConfig
- ModelInferencePaymentConfig
- ModelTrainingPaymentConfig
- PaymentConfiguration
- PreviewPrivacyImpactParametersInput
- PrivacyBudget
- PrivacyBudgetSummary
- PrivacyBudgetTemplate
- PrivacyBudgetTemplateParametersInput
- PrivacyBudgetTemplateParametersOutput
- PrivacyBudgetTemplateSummary
- PrivacyBudgetTemplateUpdateParameters
- PrivacyImpact
- ProtectedJob
- ProtectedJobComputeConfiguration
- ProtectedJobConfigurationDetails
- ProtectedJobDirectAnalysisConfigurationDetails
- ProtectedJobError
- ProtectedJobMemberOutputConfigurationInput
- ProtectedJobMemberOutputConfigurationOutput
- ProtectedJobOutput
- ProtectedJobOutputConfigurationInput
- ProtectedJobOutputConfigurationOutput
- ProtectedJobParameters
- ProtectedJobReceiverConfiguration
- ProtectedJobResult
- ProtectedJobResultConfigurationInput
- ProtectedJobResultConfigurationOutput
- ProtectedJobS3Output

- ProtectedJobS3OutputConfigurationInput
- ProtectedJobS3OutputConfigurationOutput
- ProtectedJobSingleMemberOutput
- ProtectedJobStatistics
- ProtectedJobSummary
- ProtectedJobWorkerComputeConfiguration
- ProtectedQuery
- ProtectedQueryDistributeOutput
- ProtectedQueryDistributeOutputConfiguration
- ProtectedQueryDistributeOutputConfigurationLocation
- ProtectedQueryError
- ProtectedQueryMemberOutputConfiguration
- ProtectedQueryOutput
- ProtectedQueryOutputConfiguration
- ProtectedQueryResult
- ProtectedQueryResultConfiguration
- ProtectedQueryS3Output
- ProtectedQueryS3OutputConfiguration
- ProtectedQuerySingleMemberOutput
- ProtectedQuerySQLParameters
- ProtectedQueryStatistics
- ProtectedQuerySummary
- QueryComputePaymentConfig
- QueryConstraint
- QueryConstraintRequireOverlap
- ReceiverConfiguration
- S3Location
- Schema
- SchemaAnalysisRuleRequest
- SchemaStatusDetail

- SchemaStatusReason
- SchemaSummary
- SchemaTypeProperties
- SnowflakeTableReference
- SnowflakeTableSchema
- SnowflakeTableSchemaV1
- TableReference
- ValidationExceptionField
- WorkerComputeConfiguration

AggregateColumn

Column in configured table that can be used in aggregate function in query.

Contents

columnNames

Column names in configured table of aggregate columns.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

function

Aggregation function that can be applied to aggregate column in query.

Type: String

Valid Values: `SUM | SUM_DISTINCT | COUNT | COUNT_DISTINCT | AVG`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AggregationConstraint

Constraint on query output removing output rows that do not meet a minimum number of distinct values of a specified column.

Contents

columnName

Column in aggregation constraint for which there must be a minimum number of distinct values in an output row for it to be in the query output.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

minimum

The minimum number of distinct values that an output row must be an aggregation of. Minimum threshold of distinct values for a specified column that must exist in an output row for it to be in the query output.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 100000.

Required: Yes

type

The type of aggregation the constraint allows. The only valid value is currently `COUNT_DISTINCT`.

Type: String

Valid Values: `COUNT_DISTINCT`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisParameter

Optional. The member who can query can provide this placeholder for a literal data value in an analysis template.

Contents

name

The name of the parameter. The name must use only alphanumeric, underscore (_), or hyphen (-) characters but cannot start or end with a hyphen.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `[0-9a-zA-Z_]+`

Required: Yes

type

The type of parameter.

Type: String

Valid Values: `SMALLINT | INTEGER | BIGINT | DECIMAL | REAL | DOUBLE_PRECISION | BOOLEAN | CHAR | VARCHAR | DATE | TIMESTAMP | TIMESTAMPTZ | TIME | TIMETZ | VARBYTE | BINARY | BYTE | CHARACTER | DOUBLE | FLOAT | INT | LONG | NUMERIC | SHORT | STRING | TIMESTAMP_LTZ | TIMESTAMP_NTZ | TINYINT`

Required: Yes

defaultValue

Optional. The default value that is applied in the analysis template. The member who can query can override this value in the query editor.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisRule

A specification about how data from the configured table can be used in a query.

Contents

collaborationId

The unique ID for the associated collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time the analysis rule was created.

Type: Timestamp

Required: Yes

name

The name for the analysis rule.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

policy

A policy that describes the associated data usage limitations.

Type: AnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

type

The type of analysis rule.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM | ID_MAPPING_TABLE`

Required: Yes

updateTime

The time the analysis rule was last updated.

Type: Timestamp

Required: Yes

collaborationPolicy

Controls on the query specifications that can be run on an associated configured table.

Type: ConfiguredTableAssociationAnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

consolidatedPolicy

The consolidated policy for the analysis rule.

Type: ConsolidatedPolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisRuleAggregation

A type of analysis rule that enables query structure and specified queries that produce aggregate statistics.

Contents

aggregateColumns

The columns that query runners are allowed to use in aggregation queries.

Type: Array of AggregateColumn objects

Array Members: Minimum number of 1 item.

Required: Yes

dimensionColumns

The columns that query runners are allowed to select, group by, or filter by.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

joinColumns

Columns in configured table that can be used in join statements and/or as aggregate columns. They can never be outputted directly.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

outputConstraints

Columns that must meet a specific threshold value (after an aggregation function is applied to it) for each output row to be returned.

Type: Array of AggregationConstraint objects

Array Members: Minimum number of 1 item.

Required: Yes

scalarFunctions

Set of scalar functions that are allowed to be used on dimension columns and the output of aggregation of metrics.

Type: Array of strings

Valid Values: `ABS | CAST | CEILING | COALESCE | CONVERT | CURRENT_DATE | DATEADD | EXTRACT | FLOOR | GETDATE | LN | LOG | LOWER | ROUND | RTRIM | SQRT | SUBSTRING | TO_CHAR | TO_DATE | TO_NUMBER | TO_TIMESTAMP | TRIM | TRUNC | UPPER`

Required: Yes

additionalAnalyses

An indicator as to whether additional analyses (such as AWS Clean Rooms ML) can be applied to the output of the direct query.

The `additionalAnalyses` parameter is currently supported for the list analysis rule (`AnalysisRuleList`) and the custom analysis rule (`AnalysisRuleCustom`).

Type: String

Valid Values: `ALLOWED | REQUIRED | NOT_ALLOWED`

Required: No

allowedJoinOperators

Which logical operators (if any) are to be used in an INNER JOIN match condition. Default is `AND`.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Valid Values: `OR | AND`

Required: No

joinRequired

Control that requires member who runs query to do a join with their configured table and/or other configured table in query.

Type: String

Valid Values: `QUERY_RUNNER`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisRuleCustom

A type of analysis rule that enables the table owner to approve custom SQL queries on their configured tables. It supports differential privacy.

Contents

allowedAnalyses

The ARN of the analysis templates that are allowed by the custom analysis rule.

Type: Array of strings

Array Members: Minimum number of 0 items.

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `(ANY_QUERY|ANY_JOB|arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+)`

Required: Yes

additionalAnalyses

An indicator as to whether additional analyses (such as AWS Clean Rooms ML) can be applied to the output of the direct query.

Type: String

Valid Values: `ALLOWED | REQUIRED | NOT_ALLOWED`

Required: No

allowedAnalysisProviders

The IDs of the AWS accounts that are allowed to query by the custom analysis rule. Required when `allowedAnalyses` is `ANY_QUERY`.

Type: Array of strings

Array Members: Minimum number of 0 items.

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: No

differentialPrivacy

The differential privacy configuration.

Type: DifferentialPrivacyConfiguration object

Required: No

disallowedOutputColumns

A list of columns that aren't allowed to be shown in the query output.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisRuleIdMappingTable

Defines details for the analysis rule ID mapping table.

Contents

joinColumns

The columns that query runners are allowed to use in an INNER JOIN statement.

Type: Array of strings

Array Members: Fixed number of 2 items.

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

queryConstraints

The query constraints of the analysis rule ID mapping table.

Type: Array of QueryConstraint objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: Yes

dimensionColumns

The columns that query runners are allowed to select, group by, or filter by.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisRuleList

A type of analysis rule that enables row-level analysis.

Contents

joinColumns

Columns that can be used to join a configured table with the table of the member who can query and other members' configured tables.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

listColumns

Columns that can be listed in the output.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

additionalAnalyses

An indicator as to whether additional analyses (such as AWS Clean Rooms ML) can be applied to the output of the direct query.

Type: String

Valid Values: `ALLOWED | REQUIRED | NOT_ALLOWED`

Required: No

allowedJoinOperators

The logical operators (if any) that are to be used in an INNER JOIN match condition. Default is `AND`.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Valid Values: `OR` | `AND`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisRulePolicy

Controls on the query specifications that can be run on configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

v1

Controls on the query specifications that can be run on configured table.

Type: AnalysisRulePolicyV1 object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisRulePolicyV1

Controls on the query specifications that can be run on configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

aggregation

Analysis rule type that enables only aggregation queries on a configured table.

Type: AnalysisRuleAggregation object

Required: No

custom

Analysis rule type that enables custom SQL queries on a configured table.

Type: AnalysisRuleCustom object

Required: No

idMappingTable

The ID mapping table.

Type: AnalysisRuleIdMappingTable object

Required: No

list

Analysis rule type that enables only list queries on a configured table.

Type: AnalysisRuleList object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisSchema

A relation within an analysis.

Contents

referencedTables

The tables referenced in the analysis schema.

Type: Array of strings

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisSource

The structure that defines the body of the analysis template.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

artifacts

The artifacts of the analysis source.

Type: AnalysisTemplateArtifacts object

Required: No

text

The query text.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 90000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisSourceMetadata

The analysis source metadata.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

artifacts

The artifacts of the analysis source metadata.

Type: AnalysisTemplateArtifactMetadata object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisTemplate

The analysis template.

Contents

arn

The Amazon Resource Name (ARN) of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the analysis template's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique ID for the associated collaboration of the analysis template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time that the analysis template was created.

Type: Timestamp

Required: Yes

format

The format of the analysis template.

Type: String

Valid Values: `SQL | PYSPARK_1_0`

Required: Yes

id

The identifier for the analysis template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the member who created the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The identifier of a member who created the analysis template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

schema

The entire schema object.

Type: AnalysisSchema object

Required: Yes

source

The source of the analysis template.

Type: AnalysisSource object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

updateTime

The time that the analysis template was last updated.

Type: Timestamp

Required: Yes

analysisParameters

The parameters of the analysis template.

Type: Array of AnalysisParameter objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

description

The description of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

errorMessageConfiguration

The configuration that specifies the level of detail in error messages returned by analyses using this template. When set to `DETAILED`, error messages include more information to help troubleshoot issues with PySpark jobs. Detailed error messages may expose underlying data, including sensitive information. Recommended for faster troubleshooting in development and testing environments.

Type: ErrorMessageConfiguration object

Required: No

sourceMetadata

The source metadata for the analysis template.

Type: AnalysisSourceMetadata object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

validations

Information about the validations performed on the analysis template.

Type: Array of AnalysisTemplateValidationStatusDetail objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisTemplateArtifact

The analysis template artifact.

Contents

location

The artifact location.

Type: S3Location object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisTemplateArtifactMetadata

The analysis template artifact metadata.

Contents

entryPointHash

The hash of the entry point for the analysis template artifact metadata.

Type: Hash object

Required: Yes

additionalArtifactHashes

Additional artifact hashes for the analysis template.

Type: Array of Hash objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisTemplateArtifacts

The analysis template artifacts.

Contents

entryPoint

The entry point for the analysis template artifacts.

Type: AnalysisTemplateArtifact object

Required: Yes

roleArn

The role ARN for the analysis template artifacts.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 512.

Pattern: `arn:aws:iam::[\w]+:role/[\w+=./@-]+`

Required: Yes

additionalArtifacts

Additional artifacts for the analysis template.

Type: Array of AnalysisTemplateArtifact objects

Array Members: Fixed number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2

- AWS SDK for Ruby V3

AnalysisTemplateSummary

The metadata of the analysis template.

Contents

arn

The Amazon Resource Name (ARN) of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the analysis template summary's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

A unique identifier for the collaboration that the analysis template summary belongs to. Currently accepts collaboration ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time that the analysis template summary was created.

Type: Timestamp

Required: Yes

id

The identifier of the analysis template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the member who created the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The identifier for a membership resource.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

updateTime

The time that the analysis template summary was last updated.

Type: Timestamp

Required: Yes

description

The description of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisTemplateValidationStatusDetail

The status details of the analysis template validation. AWS Clean Rooms Differential Privacy uses a general-purpose query structure to support complex SQL queries and validates whether an analysis template fits that general-purpose query structure. Validation is performed when analysis templates are created and fetched. Because analysis templates are immutable by design, we recommend that you create analysis templates after you associate the configured tables with their analysis rule to your collaboration.

For more information, see https://docs.aws.amazon.com/clean-rooms/latest/userguide/analysis-rules-custom.html#custom-diff-privacy.

Contents

status

The status of the validation.

Type: String

Valid Values: `VALID | INVALID | UNABLE_TO_VALIDATE`

Required: Yes

type

The type of validation that was performed.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

reasons

The reasons for the validation results.

Type: Array of AnalysisTemplateValidationStatusReason objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AnalysisTemplateValidationStatusReason

The reasons for the validation results.

Contents

message

The validation message.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

AthenaTableReference

A reference to a table within Athena.

Contents

databaseName

The database name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_]+-)*([a-zA-Z0-9_]+))?`

Required: Yes

tableName

The table reference.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_]+)*([a-zA-Z0-9_]+))?`

Required: Yes

workGroup

The workgroup of the Athena table reference.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `([a-zA-Z0-9._-])*`

Required: Yes

outputLocation

The output location for the Athena table.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 1024.

Pattern: `s3://[a-z0-9.-]{3,63}(.*)`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

BatchGetCollaborationAnalysisTemplateError

Details of errors thrown by the call to retrieve multiple analysis templates within a collaboration by their identifiers.

Contents

arn

The Amazon Resource Name (ARN) of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: Yes

code

An error code for the error.

Type: String

Required: Yes

message

A description of why the call failed.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

BatchGetSchemaAnalysisRuleError

An error that describes why a schema could not be fetched.

Contents

code

An error code for the error.

Type: String

Required: Yes

message

A description of why the call failed.

Type: String

Required: Yes

name

An error name for the error.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

type

The analysis rule type.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM | ID_MAPPING_TABLE`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

BatchGetSchemaError

An error describing why a schema could not be fetched.

Contents

code

An error code for the error.

Type: String

Required: Yes

message

An error message for the error.

Type: String

Required: Yes

name

An error name for the error.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

BilledJobResourceUtilization

Information related to the utilization of resources that have been billed or charged for in a given context, such as a protected job.

Contents

units

The number of Clean Rooms Processing Unit (CRPU) hours that have been billed.

Type: Double

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

BilledResourceUtilization

Information related to the utilization of resources that have been billed or charged for in a given context, such as a protected query.

Contents

units

The number of Clean Rooms Processing Unit (CRPU) hours that have been billed.

Type: Double

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Change

Represents a single change within a collaboration change request, containing the change identifier and specification.

Contents

specification

The specification details for this change.

Type: ChangeSpecification object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

specificationType

The type of specification for this change.

Type: String

Valid Values: `MEMBER`

Required: Yes

types

The list of change types that were applied.

Type: Array of strings

Array Members: Minimum number of 1 item.

Valid Values: `ADD_MEMBER`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ChangeInput

Specifies a change to apply to a collaboration.

Contents

specification

The specification details for the change. The structure depends on the specification type.

Type: ChangeSpecification object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

specificationType

The type of specification for the change. Currently supports `MEMBER` for member-related changes.

Type: String

Valid Values: `MEMBER`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ChangeSpecification

A union that contains the specification details for different types of changes.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

member

The member change specification when the change type is `MEMBER`.

Type: MemberChangeSpecification object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Collaboration

The multi-party data share environment. The collaboration contains metadata about its purpose and participants.

Contents

arn

The unique ARN for the collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d \w-]+`

Required: Yes

createTime

The time when the collaboration was created.

Type: Timestamp

Required: Yes

creatorAccountId

The identifier used to reference members of the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

creatorDisplayName

A display name of the collaboration creator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

id

The unique ID for the collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

memberStatus

The status of a member in a collaboration.

Type: String

Valid Values: `INVITED | ACTIVE | LEFT | REMOVED`

Required: Yes

name

A human-readable identifier provided by the collaboration owner. Display names are not unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

queryLogStatus

An indicator as to whether query logging has been enabled or disabled for the collaboration.

When ENABLED, AWS Clean Rooms logs details about queries run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is DISABLED.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

updateTime

The time the collaboration metadata was last updated.

Type: Timestamp

Required: Yes

analyticsEngine

The analytics engine for the collaboration.

> **Note**
>
> After July 16, 2025, the CLEAN_ROOMS_SQL parameter will no longer be available.

Type: String

Valid Values: SPARK | CLEAN_ROOMS_SQL

Required: No

autoApprovedChangeTypes

The types of change requests that are automatically approved for this collaboration.

Type: Array of strings

Valid Values: ADD_MEMBER

Required: No

dataEncryptionMetadata

The settings for client-side encryption for cryptographic computing.

Type: DataEncryptionMetadata object

Required: No

description

A description of the collaboration provided by the collaboration owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

jobLogStatus

An indicator as to whether job logging has been enabled or disabled for the collaboration.

When `ENABLED`, AWS Clean Rooms logs details about jobs run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: No

membershipArn

The unique ARN for your membership within the collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: No

membershipId

The unique ID for your membership within the collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationAnalysisTemplate

The analysis template within a collaboration.

Contents

arn

The Amazon Resource Name (ARN) of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the analysis template's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

A unique identifier for the collaboration that the analysis templates belong to. Currently accepts collaboration ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time that the analysis template within a collaboration was created.

Type: Timestamp

Required: Yes

creatorAccountId

The identifier used to reference members of the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

format

The format of the analysis template in the collaboration.

Type: String

Valid Values: `SQL | PYSPARK_1_0`

Required: Yes

id

The identifier of the analysis template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

schema

The entire schema object.

Type: AnalysisSchema object

Required: Yes

updateTime

The time that the analysis template in the collaboration was last updated.

Type: Timestamp

Required: Yes

analysisParameters

The analysis parameters that have been specified in the analysis template.

Type: Array of AnalysisParameter objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

description

The description of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

errorMessageConfiguration

The configuration that specifies the level of detail in error messages returned by analyses using this template. When set to `DETAILED`, error messages include more information to help troubleshoot issues with PySpark jobs. Detailed error messages may expose underlying data, including sensitive information. Recommended for faster troubleshooting in development and testing environments.

Type: ErrorMessageConfiguration object

Required: No

source

The source of the analysis template within a collaboration.

Type: AnalysisSource object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

sourceMetadata

The source metadata for the collaboration analysis template.

Type: AnalysisSourceMetadata object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

validations

The validations that were performed.

Type: Array of AnalysisTemplateValidationStatusDetail objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationAnalysisTemplateSummary

The metadata of the analysis template within a collaboration.

Contents

arn

The Amazon Resource Name (ARN) of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the analysis template's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

A unique identifier for the collaboration that the analysis templates belong to. Currently accepts collaboration ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time that the summary of the analysis template in a collaboration was created.

Type: Timestamp

Required: Yes

creatorAccountId

The identifier used to reference members of the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

id

The identifier of the analysis template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

updateTime

The time that the summary of the analysis template in the collaboration was last updated.

Type: Timestamp

Required: Yes

description

The description of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationChangeRequest

Represents a request to modify a collaboration. Change requests enable structured modifications to collaborations after they have been created.

Contents

changes

The list of changes specified in this change request.

Type: Array of Change objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

collaborationId

The unique identifier for the collaboration being modified.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time when the change request was created.

Type: Timestamp

Required: Yes

id

The unique identifier for the change request.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

isAutoApproved

Whether the change request was automatically approved based on the collaboration's auto-approval settings.

Type: Boolean

Required: Yes

status

The current status of the change request. Valid values are `PENDING`, `APPROVED`, `DENIED`, `COMMITTED`, and `CANCELLED`.

Type: String

Valid Values: `PENDING | APPROVED | CANCELLED | DENIED | COMMITTED`

Required: Yes

updateTime

The time when the change request was last updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationChangeRequestSummary

Summary information about a collaboration change request.

Contents

changes

Summary of the changes in this change request.

Type: Array of Change objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

collaborationId

The unique identifier for the collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time when the change request was created.

Type: Timestamp

Required: Yes

id

The unique identifier for the change request.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

isAutoApproved

Whether the change request was automatically approved.

Type: Boolean

Required: Yes

status

The current status of the change request.

Type: String

Valid Values: `PENDING | APPROVED | CANCELLED | DENIED | COMMITTED`

Required: Yes

updateTime

The time when the change request was last updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationConfiguredAudienceModelAssociation

The configured audience model association within a collaboration.

Contents

arn

The Amazon Resource Name (ARN) of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/configuredaudiencemodelassociation/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the configured audience model's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

A unique identifier for the collaboration that the configured audience model associations belong to. Accepts collaboration ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

configuredAudienceModelArn

The Amazon Resource Name (ARN) of the configure audience model.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:[0-9]{12}:configured-audience-model/[-a-zA-Z0-9_/.]+`

Required: Yes

createTime

The time at which the configured audience model association was created.

Type: Timestamp

Required: Yes

creatorAccountId

The identifier used to reference members of the collaboration. Only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

id

The identifier of the configured audience model association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the configured audience model association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which the configured audience model association was updated.

Type: Timestamp

Required: Yes

description

The description of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationConfiguredAudienceModelAssociationSummary

A summary of the configured audience model association in the collaboration.

Contents

arn

The Amazon Resource Name (ARN) of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/configuredaudiencemodelassociation/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the configured audience model's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

A unique identifier for the collaboration that the configured audience model associations belong to. Accepts collaboration ID.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the configured audience model association was created.

Type: Timestamp

Required: Yes

creatorAccountId

The identifier used to reference members of the collaboration. Only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

id

The identifier of the configured audience model association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the configured audience model association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which the configured audience model association was updated.

Type: Timestamp

Required: Yes

description

The description of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationIdNamespaceAssociation

Defines details for the collaboration ID namespace association.

Contents

arn

The Amazon Resource Name (ARN) of the collaboration ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/idnamespaceassociation/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains the collaboration ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains the collaboration ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the collaboration ID namespace association was created.

Type: Timestamp

Required: Yes

creatorAccountId

The unique identifier of the AWS account that created the collaboration ID namespace association.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

id

The unique identifier of the collaboration ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

inputReferenceConfig

The input reference configuration that's necessary to create the collaboration ID namespace association.

Type: IdNamespaceAssociationInputReferenceConfig object

Required: Yes

inputReferenceProperties

The input reference properties that are needed to create the collaboration ID namespace association.

Type: IdNamespaceAssociationInputReferenceProperties object

Required: Yes

name

The name of the collaboration ID namespace association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which the collaboration ID namespace was updated.

Type: Timestamp

Required: Yes

description

The description of the collaboration ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

idMappingConfig

The configuration settings for the ID mapping table.

Type: IdMappingConfig object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationIdNamespaceAssociationSummary

Provides summary information about the collaboration ID namespace association.

Contents

arn

The Amazon Resource Name (ARN) of the collaboration ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/idnamespaceassociation/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains this collaboration ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains this collaboration ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the collaboration ID namespace association was created.

Type: Timestamp

Required: Yes

creatorAccountId

The AWS account that created this collaboration ID namespace association.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

id

The unique identifier of the collaboration ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

inputReferenceConfig

The input reference configuration that's used to create the collaboration ID namespace association.

Type: IdNamespaceAssociationInputReferenceConfig object

Required: Yes

inputReferenceProperties

The input reference properties that are used to create the collaboration ID namespace association.

Type: IdNamespaceAssociationInputReferencePropertiesSummary object

Required: Yes

name

The name of the collaboration ID namespace association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which the collaboration ID namespace association was updated.

Type: Timestamp

Required: Yes

description

The description of the collaboration ID namepsace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationPrivacyBudgetSummary

A summary of the collaboration privacy budgets. This summary includes the collaboration information, creation information, epsilon provided, and utility in terms of aggregations.

Contents

budget

The includes epsilon provided and utility in terms of aggregations.

Type: PrivacyBudget object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

collaborationArn

The ARN of the collaboration that includes this privacy budget.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that includes this privacy budget.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the privacy budget was created.

Type: Timestamp

Required: Yes

creatorAccountId

The unique identifier of the account that created this privacy budget.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

id

The unique identifier of the collaboration privacy budget.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetTemplateArn

The ARN of the collaboration privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:privacybudgettemplate/[\d\w-]+`

Required: Yes

privacyBudgetTemplateId

The unique identifier of the collaboration privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

type

The type of privacy budget template.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

updateTime

The most recent time at which the privacy budget was updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationPrivacyBudgetTemplate

An array that specifies the information for a collaboration's privacy budget template.

Contents

arn

The ARN of the collaboration privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:privacybudgettemplate/[\d\w-]+`

Required: Yes

autoRefresh

How often the privacy budget refreshes.

> **Important**
>
> If you plan to regularly bring new data into the collaboration, use `CALENDAR_MONTH` to automatically get a new privacy budget for the collaboration every calendar month. Choosing this option allows arbitrary amounts of information to be revealed about rows of the data when repeatedly queried across refreshes. Avoid choosing this if the same rows will be repeatedly queried between privacy budget refreshes.

Type: String

Valid Values: `CALENDAR_MONTH | NONE`

Required: Yes

collaborationArn

The ARN of the collaboration that includes this collaboration privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that includes this collaboration privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the collaboration privacy budget template was created.

Type: Timestamp

Required: Yes

creatorAccountId

The unique identifier of the account that created this collaboration privacy budget template.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

id

The unique identifier of the collaboration privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

parameters

Specifies the epsilon and noise parameters for the privacy budget template.

Type: PrivacyBudgetTemplateParametersOutput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

privacyBudgetType

The type of privacy budget template.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

updateTime

The most recent time at which the collaboration privacy budget template was updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationPrivacyBudgetTemplateSummary

A summary of the collaboration's privacy budget template. This summary includes information about who created the privacy budget template and what collaborations it belongs to.

Contents

arn

The ARN of the collaboration privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:privacybudgettemplate/[\d\w-]+`

Required: Yes

collaborationArn

The ARN of the collaboration that contains this collaboration privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains this collaboration privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the collaboration privacy budget template was created.

Type: Timestamp

Required: Yes

creatorAccountId

The unique identifier of the account that created this collaboration privacy budget template.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

id

The unique identifier of the collaboration privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetType

The type of the privacy budget template.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

updateTime

The most recent time at which the collaboration privacy budget template was updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

CollaborationSummary

The metadata of the collaboration.

Contents

arn

The ARN of the collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d \w-]+`

Required: Yes

createTime

The time when the collaboration was created.

Type: Timestamp

Required: Yes

creatorAccountId

The identifier used to reference members of the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

creatorDisplayName

The display name of the collaboration creator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

id

The identifier for the collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

memberStatus

The status of a member in a collaboration.

Type: String

Valid Values: `INVITED | ACTIVE | LEFT | REMOVED`

Required: Yes

name

A human-readable identifier provided by the collaboration owner. Display names are not unique.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The time the collaboration metadata was last updated.

Type: Timestamp

Required: Yes

analyticsEngine

The analytics engine.

> **Note**
>
> After July 16, 2025, the `CLEAN_ROOMS_SQL` parameter will no longer be available.

Type: String

Valid Values: `SPARK` | `CLEAN_ROOMS_SQL`

Required: No

membershipArn

The ARN of a member in a collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: No

membershipId

The identifier of a member in a collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Column

A column within a schema relation, derived from the underlying table.

Contents

name

The name of the column.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

type

The type of the column.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ComputeConfiguration

The configuration of the compute resources for an analysis with the Spark analytics engine.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

worker

The worker configuration for the compute environment.

Type: WorkerComputeConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfigurationDetails

The configuration details.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

directAnalysisConfigurationDetails

The direct analysis configuration details.

Type: DirectAnalysisConfigurationDetails object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredAudienceModelAssociation

Details about the configured audience model association.

Contents

arn

The Amazon Resource Name (ARN) of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/configuredaudiencemodelassociation/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains this configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

A unique identifier of the collaboration that contains this configured audience model association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

configuredAudienceModelArn

The Amazon Resource Name (ARN) of the configured audience model that was used for this configured audience model association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:[0-9]{12}:configured-audience-model/[-a-zA-Z0-9_/.]+`

Required: Yes

createTime

The time at which the configured audience model association was created.

Type: Timestamp

Required: Yes

id

A unique identifier of the configured audience model association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

manageResourcePolicies

When `TRUE`, indicates that the resource policy for the configured audience model resource being associated is configured for AWS Clean Rooms to manage permissions related to the given collaboration. When `FALSE`, indicates that the configured audience model resource owner will manage permissions related to the given collaboration.

Type: Boolean

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the membership that contains this configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

A unique identifier for the membership that contains this configured audience model association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the configured audience model association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which the configured audience model association was updated.

Type: Timestamp

Required: Yes

description

The description of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredAudienceModelAssociationSummary

A summary of the configured audience model association.

Contents

arn

The Amazon Resource Name (ARN) of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/configuredaudiencemodelassociation/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

A unique identifier of the collaboration that configured audience model is associated with.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

configuredAudienceModelArn

The Amazon Resource Name (ARN) of the configured audience model that was used for this configured audience model association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:[0-9]{12}:configured-audience-model/[-a-zA-Z0-9_/.]+`

Required: Yes

createTime

The time at which the configured audience model association was created.

Type: Timestamp

Required: Yes

id

A unique identifier of the configured audience model association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the membership that contains the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

A unique identifier of the membership that contains the configured audience model association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the configured audience model association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which the configured audience model association was updated.

Type: Timestamp

Required: Yes

description

The description of the configured audience model association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTable

A table that has been configured for use in a collaboration.

Contents

allowedColumns

The columns within the underlying AWS Glue table that can be utilized within collaborations.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

analysisMethod

The analysis method for the configured table.

`DIRECT_QUERY` allows SQL queries to be run directly on this table.

`DIRECT_JOB` allows PySpark jobs to be run directly on this table.

`MULTIPLE` allows both SQL queries and PySpark jobs to be run directly on this table.

Type: String

Valid Values: `DIRECT_QUERY | DIRECT_JOB | MULTIPLE`

Required: Yes

analysisRuleTypes

The types of analysis rules associated with this configured table. Currently, only one analysis rule may be associated with a configured table.

Type: Array of strings

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

arn

The unique ARN for the configured table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:configuredtable/[\d\w-]+`

Required: Yes

createTime

The time the configured table was created.

Type: Timestamp

Required: Yes

id

The unique ID for the configured table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

A name for the configured table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

tableReference

The table that this configured table represents.

Type: TableReference object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

updateTime

The time the configured table was last updated

Type: Timestamp

Required: Yes

description

A description for the configured table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

selectedAnalysisMethods

The selected analysis methods for the configured table.

Type: Array of strings

Valid Values: `DIRECT_QUERY | DIRECT_JOB`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAnalysisRule

A configured table analysis rule, which limits how data for this table can be used.

Contents

configuredTableArn

The unique ARN for the configured table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:configuredtable/[\d\w-]+`

Required: Yes

configuredTableId

The unique ID for the configured table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time the configured table analysis rule was created.

Type: Timestamp

Required: Yes

policy

The policy that controls SQL query rules.

Type: ConfiguredTableAnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

type

The type of configured table analysis rule.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

updateTime

The time the configured table analysis rule was last updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAnalysisRulePolicy

Controls on the query specifications that can be run on a configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

v1

Controls on the query specifications that can be run on a configured table.

Type: ConfiguredTableAnalysisRulePolicyV1 object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAnalysisRulePolicyV1

Controls on the query specifications that can be run on a configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

aggregation

Analysis rule type that enables only aggregation queries on a configured table.

Type: AnalysisRuleAggregation object

Required: No

custom

A type of analysis rule that enables the table owner to approve custom SQL queries on their configured tables. It supports differential privacy.

Type: AnalysisRuleCustom object

Required: No

list

Analysis rule type that enables only list queries on a configured table.

Type: AnalysisRuleList object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociation

A configured table association links a configured table to a collaboration.

Contents

arn

The unique ARN for the configured table association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:configuredtableassociation/[\d\w-]+/[\d\w-]+`

Required: Yes

configuredTableArn

The unique ARN for the configured table that the association refers to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:configuredtable/[\d\w-]+`

Required: Yes

configuredTableId

The unique ID for the configured table that the association refers to.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time the configured table association was created.

Type: Timestamp

Required: Yes

id

The unique ID for the configured table association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The unique ARN for the membership this configured table association belongs to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique ID for the membership this configured table association belongs to.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the configured table association, in lowercase. The table is identified by this name when running protected queries against the underlying data.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

roleArn

The service will assume this role to access catalog metadata and query the table.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 512.

Pattern: `arn:aws:iam::[\w]+:role/[\w+=./@-]+`

Required: Yes

updateTime

The time the configured table association was last updated.

Type: Timestamp

Required: Yes

analysisRuleTypes

The analysis rule types for the configured table association.

Type: Array of strings

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: No

description

A description of the configured table association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociationAnalysisRule

An analysis rule for a configured table association. This analysis rule specifies how data from the table can be used within its associated collaboration. In the console, the `ConfiguredTableAssociationAnalysisRule` is referred to as the *collaboration analysis rule*.

Contents

configuredTableAssociationArn

The Amazon Resource Name (ARN) of the configured table association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:configuredtableassociation/[\d\w-]+/[\d\w-]+`

Required: Yes

configuredTableAssociationId

The unique identifier for the configured table association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The creation time of the configured table association analysis rule.

Type: Timestamp

Required: Yes

membershipIdentifier

The membership identifier for the configured table association analysis rule.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

policy

The policy of the configured table association analysis rule.

Type: ConfiguredTableAssociationAnalysisRulePolicy object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

type

The type of the configured table association analysis rule.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

updateTime

The update time of the configured table association analysis rule.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociationAnalysisRuleAggregation

The configured table association analysis rule applied to a configured table with the aggregation analysis rule.

Contents

allowedAdditionalAnalyses

The list of resources or wildcards (ARNs) that are allowed to perform additional analysis on query output.

The `allowedAdditionalAnalyses` parameter is currently supported for the list analysis rule (`AnalysisRuleList`) and the custom analysis rule (`AnalysisRuleCustom`).

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:([\d]{12}|\*):membership\/[\*\d\w-]+\/configuredaudiencemodelassociation\/[\*\d\w-]+$|^arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:([0-9]{12}|\*):membership\/[\*\d\w-]+\/configured-model-algorithm-association\/([-a-zA-Z0-9_\/.]+|\*)`

Required: No

allowedResultReceivers

The list of collaboration members who are allowed to receive results of queries run with this configured table.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociationAnalysisRuleCustom

The configured table association analysis rule applied to a configured table with the custom analysis rule.

Contents

allowedAdditionalAnalyses

The list of resources or wildcards (ARNs) that are allowed to perform additional analysis on query output.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:([\d]{12}|\*):membership\/[\*\d\w-]+\/configuredaudiencemodelassociation\/[\*\d\w-]+$|^arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:([0-9]{12}|\*):membership\/[\*\d\w-]+\/configured-model-algorithm-association\/([-a-zA-Z0-9_\/.]+|\*)`

Required: No

allowedResultReceivers

The list of collaboration members who are allowed to receive results of queries run with this configured table.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociationAnalysisRuleList

The configured table association analysis rule applied to a configured table with the list analysis rule.

Contents

allowedAdditionalAnalyses

The list of resources or wildcards (ARNs) that are allowed to perform additional analysis on query output.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:([\d]{12}|\*):membership\/[\*\d\w-]+\/configuredaudiencemodelassociation\/[\*\d\w-]+$|^arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:([0-9]{12}|\*):membership\/[\*\d\w-]+\/configured-model-algorithm-association\/([-a-zA-Z0-9_\/.]+|\*)`

Required: No

allowedResultReceivers

The list of collaboration members who are allowed to receive results of queries run with this configured table.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociationAnalysisRulePolicy

Controls on the query specifications that can be run on an associated configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

v1

The policy for the configured table association analysis rule.

Type: ConfiguredTableAssociationAnalysisRulePolicyV1 object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociationAnalysisRulePolicyV1

Controls on the query specifications that can be run on an associated configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

aggregation

Analysis rule type that enables only aggregation queries on a configured table.

Type: ConfiguredTableAssociationAnalysisRuleAggregation object

Required: No

custom

Analysis rule type that enables the table owner to approve custom SQL queries on their configured tables. It supports differential privacy.

Type: ConfiguredTableAssociationAnalysisRuleCustom object

Required: No

list

Analysis rule type that enables only list queries on a configured table.

Type: ConfiguredTableAssociationAnalysisRuleList object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableAssociationSummary

The configured table association summary for the objects listed by the request.

Contents

arn

The unique ARN for the configured table association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:configuredtableassociation/[\d\w-]+/[\d\w-]+`

Required: Yes

configuredTableId

The unique configured table ID that this configured table association refers to.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time the configured table association was created.

Type: Timestamp

Required: Yes

id

The unique ID for the configured table association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The unique ARN for the membership that the configured table association belongs to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique ID for the membership that the configured table association belongs to.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the configured table association. The table is identified by this name when running Protected Queries against the underlying data.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

updateTime

The time the configured table association was last updated.

Type: Timestamp

Required: Yes

analysisRuleTypes

The analysis rule types that are associated with the configured table associations in this summary.

Type: Array of strings

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConfiguredTableSummary

The configured table summary for the objects listed by the request.

Contents

analysisMethod

The analysis method for the configured tables.

`DIRECT_QUERY` allows SQL queries to be run directly on this table.

`DIRECT_JOB` allows PySpark jobs to be run directly on this table.

`MULTIPLE` allows both SQL queries and PySpark jobs to be run directly on this table.

Type: String

Valid Values: `DIRECT_QUERY | DIRECT_JOB | MULTIPLE`

Required: Yes

analysisRuleTypes

The types of analysis rules associated with this configured table.

Type: Array of strings

Valid Values: `AGGREGATION | LIST | CUSTOM`

Required: Yes

arn

The unique ARN of the configured table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:configuredtable/[\d\w-]+`

Required: Yes

createTime

The time the configured table was created.

Type: Timestamp

Required: Yes

id

The unique ID of the configured table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the configured table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The time the configured table was last updated.

Type: Timestamp

Required: Yes

selectedAnalysisMethods

The selected analysis methods for the configured table summary.

Type: Array of strings

Valid Values: `DIRECT_QUERY | DIRECT_JOB`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConsolidatedPolicy

Controls on the analysis specifications that can be run on a configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

v1

The consolidated policy version 1.

Type: ConsolidatedPolicyV1 object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConsolidatedPolicyAggregation

Controls on the analysis specifications that can be run on a configured table.

Contents

aggregateColumns

Aggregate columns in consolidated policy aggregation.

Type: Array of AggregateColumn objects

Array Members: Minimum number of 1 item.

Required: Yes

dimensionColumns

The dimension columns of the consolidated policy aggregation.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

joinColumns

The columns to join on.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

outputConstraints

The output constraints of the consolidated policy aggregation.

Type: Array of AggregationConstraint objects

Array Members: Minimum number of 1 item.

Required: Yes

scalarFunctions

The scalar functions.

Type: Array of strings

Valid Values: `ABS | CAST | CEILING | COALESCE | CONVERT | CURRENT_DATE | DATEADD | EXTRACT | FLOOR | GETDATE | LN | LOG | LOWER | ROUND | RTRIM | SQRT | SUBSTRING | TO_CHAR | TO_DATE | TO_NUMBER | TO_TIMESTAMP | TRIM | TRUNC | UPPER`

Required: Yes

additionalAnalyses

Additional analyses for the consolidated policy aggregation.

Type: String

Valid Values: `ALLOWED | REQUIRED | NOT_ALLOWED`

Required: No

allowedAdditionalAnalyses

The additional analyses allowed by the consolidated policy aggregation.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:([\d]{12}|\*):membership\/[\*\d\w-]+\/configuredaudiencemodelassociation\/[\*\d\w-]+$|^arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:([0-9]{12}|\*):membership\/[\*\d\w-]+\/configured-model-algorithm-association\/([-a-zA-Z0-9_\/.]+|\*)`

Required: No

allowedJoinOperators

The allowed join operators.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Valid Values: `OR | AND`

Required: No

allowedResultReceivers

The allowed result receivers.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: No

joinRequired

Join required

Type: String

Valid Values: `QUERY_RUNNER`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConsolidatedPolicyCustom

Controls on the analysis specifications that can be run on a configured table.

Contents

allowedAnalyses

The allowed analyses.

Type: Array of strings

Array Members: Minimum number of 0 items.

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `(ANY_QUERY|ANY_JOB|arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+)`

Required: Yes

additionalAnalyses

Additional analyses for the consolidated policy.

Type: String

Valid Values: `ALLOWED | REQUIRED | NOT_ALLOWED`

Required: No

allowedAdditionalAnalyses

The additional analyses allowed by the consolidated policy.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:([\d]{12}|\*):membership\/[\*\d\w-]+\/configuredaudiencemodelassociation\/[\*\d\w-]+$|^arn:aws[-`

```
a-z]*:cleanrooms-ml:[-a-z0-9]+:([0-9]{12}|\*):membership\/[\*\d\w-]+\/
configured-model-algorithm-association\/([-a-zA-Z0-9_\/.]+|\*)
```

Required: No

allowedAnalysisProviders

The allowed analysis providers.

Type: Array of strings

Array Members: Minimum number of 0 items.

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: No

allowedResultReceivers

The allowed result receivers.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: No

differentialPrivacy

Specifies the unique identifier for your users.

Type: DifferentialPrivacyConfiguration object

Required: No

disallowedOutputColumns

Disallowed output columns

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConsolidatedPolicyList

Controls on the analysis specifications that can be run on a configured table.

Contents

joinColumns

The columns to join on.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

listColumns

The columns in the consolidated policy list.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

additionalAnalyses

Additional analyses for the consolidated policy list.

Type: String

Valid Values: `ALLOWED | REQUIRED | NOT_ALLOWED`

Required: No

allowedAdditionalAnalyses

The additional analyses allowed by the consolidated policy list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:([\d]{12}|\*):membership\/[\*\d\w-]+\/configuredaudiencemodelassociation\/[\*\d\w-]+$|^arn:aws[-a-z]*:cleanrooms-ml:[-a-z0-9]+:([0-9]{12}|\*):membership\/[\*\d\w-]+\/configured-model-algorithm-association\/([-a-zA-Z0-9_\/.]+|\*)`

Required: No

allowedJoinOperators

The allowed join operators in the consolidated policy list.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 2 items.

Valid Values: `OR` | `AND`

Required: No

allowedResultReceivers

The allowed result receivers.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

ConsolidatedPolicyV1

Controls on the analysis specifications that can be run on a configured table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

aggregation

The aggregation setting for the consolidated policy.

Type: ConsolidatedPolicyAggregation object

Required: No

custom

Custom policy

Type: ConsolidatedPolicyCustom object

Required: No

list

The list of consolidated policies.

Type: ConsolidatedPolicyList object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

DataEncryptionMetadata

The settings for client-side encryption for cryptographic computing.

Contents

allowCleartext

Indicates whether encrypted tables can contain cleartext data (TRUE) or are to cryptographically process every column (FALSE).

Type: Boolean

Required: Yes

allowDuplicates

Indicates whether Fingerprint columns can contain duplicate entries (TRUE) or are to contain only non-repeated values (FALSE).

Type: Boolean

Required: Yes

allowJoinsOnColumnsWithDifferentNames

Indicates whether Fingerprint columns can be joined on any other Fingerprint column with a different name (TRUE) or can only be joined on Fingerprint columns of the same name (FALSE).

Type: Boolean

Required: Yes

preserveNulls

Indicates whether NULL values are to be copied as NULL to encrypted tables (TRUE) or cryptographically processed (FALSE).

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyColumn

Specifies the name of the column that contains the unique identifier of your users, whose privacy you want to protect.

Contents

name

The name of the column, such as user_id, that contains the unique identifier of your users, whose privacy you want to protect. If you want to turn on differential privacy for two or more tables in a collaboration, you must configure the same column as the user identifier column in both analysis rules.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyConfiguration

Specifies the unique identifier for your users.

Contents

columns

The name of the column (such as user_id) that contains the unique identifier of your users whose privacy you want to protect. If you want to turn on differential privacy for two or more tables in a collaboration, you must configure the same column as the user identifier column in both analysis rules.

Type: Array of DifferentialPrivacyColumn objects

Array Members: Fixed number of 1 item.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyParameters

An array that contains the sensitivity parameters.

Contents

sensitivityParameters

Provides the sensitivity parameters that you can use to better understand the total amount of noise in query results.

Type: Array of DifferentialPrivacySensitivityParameters objects

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyPreviewAggregation

Provides an estimate of the number of aggregation functions that the member who can query can run given the epsilon and noise parameters.

Contents

maxCount

The maximum number of aggregations that the member who can query can run given the epsilon and noise parameters.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

type

The type of aggregation function.

Type: String

Valid Values: `AVG | COUNT | COUNT_DISTINCT | SUM | STDDEV`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyPreviewParametersInput

The epsilon and noise parameters that you want to preview.

Contents

epsilon

The epsilon value that you want to preview.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: Yes

usersNoisePerQuery

Noise added per query is measured in terms of the number of users whose contributions you want to obscure. This value governs the rate at which the privacy budget is depleted.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyPrivacyBudget

Specifies the configured epsilon value and the utility in terms of total aggregations, as well as the remaining aggregations available.

Contents

aggregations

This information includes the configured epsilon value and the utility in terms of total aggregations, as well as the remaining aggregations.

Type: Array of DifferentialPrivacyPrivacyBudgetAggregation objects

Required: Yes

epsilon

The epsilon value that you configured.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyPrivacyBudgetAggregation

Information about the total number of aggregations, as well as the remaining aggregations.

Contents

maxCount

The maximum number of aggregation functions that you can perform with the given privacy budget.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

remainingCount

The remaining number of aggregation functions that can be run with the available privacy budget.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

type

The different types of aggregation functions that you can perform.

Type: String

Valid Values: `AVG | COUNT | COUNT_DISTINCT | SUM | STDDEV`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyPrivacyImpact

Information about the number of aggregation functions that the member who can query can run given the epsilon and noise parameters.

Contents

aggregations

The number of aggregation functions that you can perform.

Type: Array of DifferentialPrivacyPreviewAggregation objects

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacySensitivityParameters

Provides the sensitivity parameters.

Contents

aggregationExpression

The aggregation expression that was run.

Type: String

Length Constraints: Minimum length of 1.

Required: Yes

aggregationType

The type of aggregation function that was run.

Type: String

Valid Values: `AVG | COUNT | COUNT_DISTINCT | SUM | STDDEV`

Required: Yes

userContributionLimit

The maximum number of rows contributed by a user in a SQL query.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

maxColumnValue

The upper bound of the aggregation expression.

Type: Float

Required: No

minColumnValue

The lower bound of the aggregation expression.

Type: Float

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyTemplateParametersInput

The epsilon and noise parameter values that you want to use for the differential privacy template.

Contents

epsilon

The epsilon value that you want to use.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: Yes

usersNoisePerQuery

Noise added per query is measured in terms of the number of users whose contributions you want to obscure. This value governs the rate at which the privacy budget is depleted.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyTemplateParametersOutput

The epsilon and noise parameter values that were used for the differential privacy template.

Contents

epsilon

The epsilon value that you specified.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: Yes

usersNoisePerQuery

Noise added per query is measured in terms of the number of users whose contributions you want to obscure. This value governs the rate at which the privacy budget is depleted.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DifferentialPrivacyTemplateUpdateParameters

The epsilon and noise parameter values that you want to update in the differential privacy template.

Contents

epsilon

The updated epsilon value that you want to use.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 20.

Required: No

usersNoisePerQuery

The updated value of noise added per query. It is measured in terms of the number of users whose contributions you want to obscure. This value governs the rate at which the privacy budget is depleted.

Type: Integer

Valid Range: Minimum value of 10. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

DirectAnalysisConfigurationDetails

The direct analysis configuration details.

Contents

receiverAccountIds

The account IDs for the member who received the results of a protected query.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ErrorMessageConfiguration

A structure that defines the level of detail included in error messages returned by PySpark jobs. This configuration allows you to control the verbosity of error messages to help with troubleshooting PySpark jobs while maintaining appropriate security controls.

Contents

type

The level of detail for error messages returned by the PySpark job. When set to DETAILED, error messages include more information to help troubleshoot issues with your PySpark job.

Because this setting may expose sensitive data, it is recommended for development and testing environments.

Type: String

Valid Values: `DETAILED`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

GlueTableReference

A reference to a table within an AWS Glue data catalog.

Contents

databaseName

The name of the database the AWS Glue table belongs to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_]+-)*([a-zA-Z0-9_]+))?`

Required: Yes

tableName

The name of the AWS Glue table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Hash

Hash

Contents

sha256

The SHA-256 hash value.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdMappingConfig

The configuration settings for the ID mapping table.

Contents

allowUseAsDimensionColumn

An indicator as to whether you can use your column as a dimension column in the ID mapping table (TRUE) or not (FALSE).

Default is FALSE.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdMappingTable

Describes information about the ID mapping table.

Contents

arn

The Amazon Resource Name (ARN) of the ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/idmappingtable/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains this ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains this ID mapping table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the ID mapping table was created.

Type: Timestamp

Required: Yes

id

The unique identifier of the ID mapping table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

inputReferenceConfig

The input reference configuration for the ID mapping table.

Type: IdMappingTableInputReferenceConfig object

Required: Yes

inputReferenceProperties

The input reference properties for the ID mapping table.

Type: IdMappingTableInputReferenceProperties object

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the membership resource for the ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique identifier of the membership resource for the ID mapping table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

updateTime

The most recent time at which the ID mapping table was updated.

Type: Timestamp

Required: Yes

description

The description of the ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

kmsKeyArn

The Amazon Resource Name (ARN) of the AWS KMS key.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:kms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:key/[a-zA-Z0-9-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdMappingTableInputReferenceConfig

Provides the input reference configuration for the ID mapping table.

Contents

inputReferenceArn

The Amazon Resource Name (ARN) of the referenced resource in AWS Entity Resolution. Valid values are ID mapping workflow ARNs.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:(aws|aws-us-gov|aws-cn):entityresolution:.*:[0-9]+:(idmappingworkflow/.*)`

Required: Yes

manageResourcePolicies

When `TRUE`, AWS Clean Rooms manages permissions for the ID mapping table resource.

When `FALSE`, the resource owner manages permissions for the ID mapping table resource.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdMappingTableInputReferenceProperties

The input reference properties for the ID mapping table.

Contents

idMappingTableInputSource

The input source of the ID mapping table.

Type: Array of IdMappingTableInputSource objects

Array Members: Fixed number of 2 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdMappingTableInputSource

The input source of the ID mapping table.

Contents

idNamespaceAssociationId

The unique identifier of the ID namespace association.

Type: String

Required: Yes

type

The type of the input source of the ID mapping table.

Type: String

Valid Values: `SOURCE` | `TARGET`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdMappingTableSchemaTypeProperties

Additional properties that are specific to the type of the associated schema.

Contents

idMappingTableInputSource

Defines which ID namespace associations are used to create the ID mapping table.

Type: Array of IdMappingTableInputSource objects

Array Members: Fixed number of 2 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdMappingTableSummary

Detailed information about the ID mapping table.

Contents

arn

The Amazon Resource Name (ARN) of this ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/idmappingtable/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains this ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains this ID mapping table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which this ID mapping table was created.

Type: Timestamp

Required: Yes

id

The unique identifier of this ID mapping table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

inputReferenceConfig

The input reference configuration for the ID mapping table.

Type: IdMappingTableInputReferenceConfig object

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the membership resource for this ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique identifier of the membership resource for this ID mapping table.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of this ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

updateTime

The most recent time at which this ID mapping table was updated.

Type: Timestamp

Required: Yes

description

The description of this ID mapping table.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdNamespaceAssociation

Provides information to create the ID namespace association.

Contents

arn

The Amazon Resource Name (ARN) of the ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/idnamespaceassociation/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains this ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains this ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the ID namespace association was created.

Type: Timestamp

Required: Yes

id

The unique identifier for this ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

inputReferenceConfig

The input reference configuration for the ID namespace association.

Type: IdNamespaceAssociationInputReferenceConfig object

Required: Yes

inputReferenceProperties

The input reference properties for the ID namespace association.

Type: IdNamespaceAssociationInputReferenceProperties object

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the membership resource for this ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique identifier of the membership resource for this ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of this ID namespace association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which the ID namespace association was updated.

Type: Timestamp

Required: Yes

description

The description of the ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

idMappingConfig

The configuration settings for the ID mapping table.

Type: IdMappingConfig object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdNamespaceAssociationInputReferenceConfig

Provides the information for the ID namespace association input reference configuration.

Contents

inputReferenceArn

The Amazon Resource Name (ARN) of the AWS Entity Resolution resource that is being associated to the collaboration. Valid resource ARNs are from the ID namespaces that you own.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:entityresolution:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:idnamespace/[\d\w-]+`

Required: Yes

manageResourcePolicies

When TRUE, AWS Clean Rooms manages permissions for the ID namespace association resource.

When FALSE, the resource owner manages permissions for the ID namespace association resource.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdNamespaceAssociationInputReferenceProperties

Provides the information for the ID namespace association input reference properties.

Contents

idMappingWorkflowsSupported

Defines how ID mapping workflows are supported for this ID namespace association.

Type: Array of JSON values

Required: Yes

idNamespaceType

The ID namespace type for this ID namespace association.

Type: String

Valid Values: `SOURCE | TARGET`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdNamespaceAssociationInputReferencePropertiesSummary

Detailed information about the ID namespace association input reference properties.

Contents

idNamespaceType

The ID namespace type for this ID namespace association.

Type: String

Valid Values: `SOURCE` | `TARGET`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

IdNamespaceAssociationSummary

Detailed information about the ID namespace association.

Contents

arn

The Amazon Resource Name (ARN) of this ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/idnamespaceassociation/[\d\w-]+`

Required: Yes

collaborationArn

The Amazon Resource Name (ARN) of the collaboration that contains this ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains this ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which this ID namespace association was created.

Type: Timestamp

Required: Yes

id

The unique identifier of this ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

inputReferenceConfig

The input reference configuration details for this ID namespace association.

Type: IdNamespaceAssociationInputReferenceConfig object

Required: Yes

inputReferenceProperties

The input reference properties for this ID namespace association.

Type: IdNamespaceAssociationInputReferencePropertiesSummary object

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the membership resource for this ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique identifier of the membership resource for this ID namespace association.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

name

The name of the ID namespace association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

updateTime

The most recent time at which this ID namespace association has been updated.

Type: Timestamp

Required: Yes

description

The description of the ID namespace association.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

JobComputePaymentConfig

An object representing the collaboration member's payment responsibilities set by the collaboration creator for query and job compute costs.

Contents

isResponsible

Indicates whether the collaboration creator has configured the collaboration member to pay for query and job compute costs (TRUE) or has not configured the collaboration member to pay for query and job compute costs (FALSE).

Exactly one member can be configured to pay for query and job compute costs. An error is returned if the collaboration creator sets a TRUE value for more than one member in the collaboration.

An error is returned if the collaboration creator sets a FALSE value for the member who can run queries and jobs.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MemberChangeSpecification

Specifies changes to collaboration membership, including adding new members with their abilities and display names.

Contents

accountId

The AWS account ID of the member to add to the collaboration.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

memberAbilities

The abilities granted to the collaboration member. These determine what actions the member can perform within the collaboration.

> **Note**
>
> The following values are currently not supported: `CAN_QUERY`, `CAN_RECEIVE_RESULTS`, and `CAN_RUN_JOB`.
> Set the value of `memberAbilities` to `[]` to allow a member to contribute data.

Type: Array of strings

Valid Values: `CAN_QUERY | CAN_RECEIVE_RESULTS | CAN_RUN_JOB`

Required: Yes

displayName

Specifies the display name that will be shown for this member in the collaboration. While this field is required when inviting new members, it becomes optional when modifying abilities of existing collaboration members.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Membership

The membership object.

Contents

arn

The unique ARN for the membership.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the membership's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationCreatorAccountId

The identifier used to reference members of the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

collaborationCreatorDisplayName

The display name of the collaboration creator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

collaborationId

The unique ID for the membership's collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

collaborationName

The name of the membership's collaboration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

createTime

The time when the membership was created.

Type: Timestamp

Required: Yes

id

The unique ID of the membership.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

memberAbilities

The abilities granted to the collaboration member.

Type: Array of strings

Valid Values: `CAN_QUERY | CAN_RECEIVE_RESULTS | CAN_RUN_JOB`

Required: Yes

paymentConfiguration

The payment responsibilities accepted by the collaboration member.

Type: MembershipPaymentConfiguration object

Required: Yes

queryLogStatus

An indicator as to whether query logging has been enabled or disabled for the membership.

When `ENABLED`, AWS Clean Rooms logs details about queries run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: Yes

status

The status of the membership.

Type: String

Valid Values: `ACTIVE | REMOVED | COLLABORATION_DELETED`

Required: Yes

updateTime

The time the membership metadata was last updated.

Type: Timestamp

Required: Yes

defaultJobResultConfiguration

The default job result configuration for the membership.

Type: MembershipProtectedJobResultConfiguration object

Required: No

defaultResultConfiguration

The default protected query result configuration as specified by the member who can receive results.

Type: MembershipProtectedQueryResultConfiguration object

Required: No

jobLogStatus

An indicator as to whether job logging has been enabled or disabled for the collaboration.

When `ENABLED`, AWS Clean Rooms logs details about jobs run within this collaboration and those logs can be viewed in Amazon CloudWatch Logs. The default value is `DISABLED`.

Type: String

Valid Values: `ENABLED | DISABLED`

Required: No

mlMemberAbilities

Specifies the ML member abilities that are granted to a collaboration member.

Type: MLMemberAbilities object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipJobComputePaymentConfig

An object representing the payment responsibilities accepted by the collaboration member for query and job compute costs.

Contents

isResponsible

Indicates whether the collaboration member has accepted to pay for job compute costs (TRUE) or has not accepted to pay for query and job compute costs (FALSE).

There is only one member who pays for queries and jobs.

An error message is returned for the following reasons:

- If you set the value to FALSE but you are responsible to pay for query and job compute costs.
- If you set the value to TRUE but you are not responsible to pay for query and job compute costs.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipMLPaymentConfig

An object representing the collaboration member's machine learning payment responsibilities set by the collaboration creator.

Contents

modelInference

The payment responsibilities accepted by the member for model inference.

Type: MembershipModelInferencePaymentConfig object

Required: No

modelTraining

The payment responsibilities accepted by the member for model training.

Type: MembershipModelTrainingPaymentConfig object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipModelInferencePaymentConfig

An object representing the collaboration member's model inference payment responsibilities set by the collaboration creator.

Contents

isResponsible

Indicates whether the collaboration member has accepted to pay for model inference costs (TRUE) or has not accepted to pay for model inference costs (FALSE).

If the collaboration creator has not specified anyone to pay for model inference costs, then the member who can query is the default payer.

An error message is returned for the following reasons:

- If you set the value to FALSE but you are responsible to pay for model inference costs.
- If you set the value to TRUE but you are not responsible to pay for model inference costs.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipModelTrainingPaymentConfig

An object representing the collaboration member's model training payment responsibilities set by the collaboration creator.

Contents

isResponsible

Indicates whether the collaboration member has accepted to pay for model training costs (TRUE) or has not accepted to pay for model training costs (FALSE).

If the collaboration creator has not specified anyone to pay for model training costs, then the member who can query is the default payer.

An error message is returned for the following reasons:

- If you set the value to FALSE but you are responsible to pay for model training costs.
- If you set the value to TRUE but you are not responsible to pay for model training costs.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipPaymentConfiguration

An object representing the payment responsibilities accepted by the collaboration member.

Contents

queryCompute

The payment responsibilities accepted by the collaboration member for query compute costs.

Type: MembershipQueryComputePaymentConfig object

Required: Yes

jobCompute

The payment responsibilities accepted by the collaboration member for job compute costs.

Type: MembershipJobComputePaymentConfig object

Required: No

machineLearning

The payment responsibilities accepted by the collaboration member for machine learning costs.

Type: MembershipMLPaymentConfig object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipProtectedJobOutputConfiguration

Contains configurations for protected job results.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

s3

Contains the configuration to write the job results to S3.

Type: ProtectedJobS3OutputConfigurationInput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipProtectedJobResultConfiguration

Contains configurations for protected job results.

Contents

outputConfiguration

The output configuration for a protected job result.

Type: MembershipProtectedJobOutputConfiguration object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

roleArn

The unique ARN for an IAM role that is used by AWS Clean Rooms to write protected job results to the result location, given by the member who can receive results.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 512.

Pattern: `arn:aws:iam::[\w]+:role/[\w+=./@-]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipProtectedQueryOutputConfiguration

Contains configurations for protected query results.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

s3

Contains the configuration to write the query results to S3.

Type: ProtectedQueryS3OutputConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipProtectedQueryResultConfiguration

Contains configurations for protected query results.

Contents

outputConfiguration

Configuration for protected query results.

Type: MembershipProtectedQueryOutputConfiguration object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

roleArn

The unique ARN for an IAM role that is used by AWS Clean Rooms to write protected query results to the result location, given by the member who can receive results.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 512.

Pattern: `arn:aws:iam::[\w]+:role/[\w+=./@-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipQueryComputePaymentConfig

An object representing the payment responsibilities accepted by the collaboration member for query compute costs.

Contents

isResponsible

Indicates whether the collaboration member has accepted to pay for query compute costs (TRUE) or has not accepted to pay for query compute costs (FALSE).

If the collaboration creator has not specified anyone to pay for query compute costs, then the member who can query is the default payer.

An error message is returned for the following reasons:

- If you set the value to FALSE but you are responsible to pay for query compute costs.
- If you set the value to TRUE but you are not responsible to pay for query compute costs.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MembershipSummary

The membership object listed by the request.

Contents

arn

The unique ARN for the membership.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

collaborationArn

The unique ARN for the membership's associated collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationCreatorAccountId

The identifier of the AWS principal that created the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

collaborationCreatorDisplayName

The display name of the collaboration creator.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

collaborationId

The unique ID for the membership's collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

collaborationName

The name for the membership's collaboration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

createTime

The time when the membership was created.

Type: Timestamp

Required: Yes

id

The unique ID for the membership's collaboration.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

memberAbilities

The abilities granted to the collaboration member.

Type: Array of strings

Valid Values: `CAN_QUERY | CAN_RECEIVE_RESULTS | CAN_RUN_JOB`

Required: Yes

paymentConfiguration

The payment responsibilities accepted by the collaboration member.

Type: MembershipPaymentConfiguration object

Required: Yes

status

The status of the membership.

Type: String

Valid Values: `ACTIVE | REMOVED | COLLABORATION_DELETED`

Required: Yes

updateTime

The time the membership metadata was last updated.

Type: Timestamp

Required: Yes

mlMemberAbilities

Provides a summary of the ML abilities for the collaboration member.

Type: MLMemberAbilities object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MemberSpecification

Basic metadata used to construct a new member.

Contents

accountId

The identifier used to reference members of the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

displayName

The member's display name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

memberAbilities

The abilities granted to the collaboration member.

Type: Array of strings

Valid Values: `CAN_QUERY | CAN_RECEIVE_RESULTS | CAN_RUN_JOB`

Required: Yes

mlMemberAbilities

The ML abilities granted to the collaboration member.

Type: MLMemberAbilities object

Required: No

paymentConfiguration

The collaboration member's payment responsibilities set by the collaboration creator.

If the collaboration creator hasn't specified anyone as the member paying for query compute costs, then the member who can query is the default payer.

Type: PaymentConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MemberSummary

The member object listed by the request.

Contents

abilities

The abilities granted to the collaboration member.

Type: Array of strings

Valid Values: `CAN_QUERY | CAN_RECEIVE_RESULTS | CAN_RUN_JOB`

Required: Yes

accountId

The identifier used to reference members of the collaboration. Currently only supports AWS account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

createTime

The time when the member was created.

Type: Timestamp

Required: Yes

displayName

The member's display name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `(?!\s*$)[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

paymentConfiguration

The collaboration member's payment responsibilities set by the collaboration creator.

Type: PaymentConfiguration object

Required: Yes

status

The status of the member.

Type: String

Valid Values: `INVITED | ACTIVE | LEFT | REMOVED`

Required: Yes

updateTime

The time the member metadata was last updated.

Type: Timestamp

Required: Yes

membershipArn

The unique ARN for the member's associated membership, if present.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: No

membershipId

The unique ID for the member's associated membership, if present.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

mlAbilities

Provides a summary of the ML abilities for the collaboration member.

Type: MLMemberAbilities object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MLMemberAbilities

The ML member abilities for a collaboration member.

Contents

customMLMemberAbilities

The custom ML member abilities for a collaboration member.

Type: Array of strings

Array Members: Minimum number of 1 item.

Valid Values: `CAN_RECEIVE_MODEL_OUTPUT | CAN_RECEIVE_INFERENCE_OUTPUT`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

MLPaymentConfig

An object representing the collaboration member's machine learning payment responsibilities set by the collaboration creator.

Contents

modelInference

The payment responsibilities accepted by the member for model inference.

Type: ModelInferencePaymentConfig object

Required: No

modelTraining

The payment responsibilities accepted by the member for model training.

Type: ModelTrainingPaymentConfig object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ModelInferencePaymentConfig

An object representing the collaboration member's model inference payment responsibilities set by the collaboration creator.

Contents

isResponsible

Indicates whether the collaboration creator has configured the collaboration member to pay for model inference costs (`TRUE`) or has not configured the collaboration member to pay for model inference costs (`FALSE`).

Exactly one member can be configured to pay for model inference costs. An error is returned if the collaboration creator sets a `TRUE` value for more than one member in the collaboration.

If the collaboration creator hasn't specified anyone as the member paying for model inference costs, then the member who can query is the default payer. An error is returned if the collaboration creator sets a `FALSE` value for the member who can query.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ModelTrainingPaymentConfig

An object representing the collaboration member's model training payment responsibilities set by the collaboration creator.

Contents

isResponsible

Indicates whether the collaboration creator has configured the collaboration member to pay for model training costs (TRUE) or has not configured the collaboration member to pay for model training costs (FALSE).

Exactly one member can be configured to pay for model training costs. An error is returned if the collaboration creator sets a TRUE value for more than one member in the collaboration.

If the collaboration creator hasn't specified anyone as the member paying for model training costs, then the member who can query is the default payer. An error is returned if the collaboration creator sets a FALSE value for the member who can query.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PaymentConfiguration

An object representing the collaboration member's payment responsibilities set by the collaboration creator.

Contents

queryCompute

The collaboration member's payment responsibilities set by the collaboration creator for query compute costs.

Type: QueryComputePaymentConfig object

Required: Yes

jobCompute

The compute configuration for the job.

Type: JobComputePaymentConfig object

Required: No

machineLearning

An object representing the collaboration member's machine learning payment responsibilities set by the collaboration creator.

Type: MLPaymentConfig object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PreviewPrivacyImpactParametersInput

Specifies the updated epsilon and noise parameters to preview. The preview allows you to see how the maximum number of each type of aggregation function would change with the new parameters.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

differentialPrivacy

An array that specifies the epsilon and noise parameters.

Type: DifferentialPrivacyPreviewParametersInput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyBudget

The epsilon parameter value and number of each aggregation function that you can perform.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

differentialPrivacy

An object that specifies the epsilon parameter and the utility in terms of total aggregations, as well as the remaining aggregations available.

Type: DifferentialPrivacyPrivacyBudget object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyBudgetSummary

An array that summaries the specified privacy budget. This summary includes collaboration information, creation information, membership information, and privacy budget information.

Contents

budget

The provided privacy budget.

Type: PrivacyBudget object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

collaborationArn

The ARN of the collaboration that contains this privacy budget.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique identifier of the collaboration that contains this privacy budget.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the privacy budget was created.

Type: Timestamp

Required: Yes

id

The unique identifier of the privacy budget.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the member who created the privacy budget summary.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The identifier for a membership resource.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetTemplateArn

The ARN of the privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:privacybudgettemplate/[\d\w-]+`

Required: Yes

privacyBudgetTemplateId

The unique identifier of the privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

type

Specifies the type of the privacy budget.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

updateTime

The most recent time at which the privacy budget was updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyBudgetTemplate

An object that defines the privacy budget template.

Contents

arn

The ARN of the privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:privacybudgettemplate/[\d\w-]+`

Required: Yes

autoRefresh

How often the privacy budget refreshes.

> **Important**
>
> If you plan to regularly bring new data into the collaboration, use `CALENDAR_MONTH` to automatically get a new privacy budget for the collaboration every calendar month. Choosing this option allows arbitrary amounts of information to be revealed about rows of the data when repeatedly queried across refreshes. Avoid choosing this if the same rows will be repeatedly queried between privacy budget refreshes.

Type: String

Valid Values: `CALENDAR_MONTH | NONE`

Required: Yes

collaborationArn

The ARN of the collaboration that contains this privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique ID of the collaboration that contains this privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the privacy budget template was created.

Type: Timestamp

Required: Yes

id

The unique identifier of the privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the member who created the privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The identifier for a membership resource.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

parameters

Specifies the epsilon and noise parameters for the privacy budget template.

Type: PrivacyBudgetTemplateParametersOutput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

privacyBudgetType

Specifies the type of the privacy budget template.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

updateTime

The most recent time at which the privacy budget template was updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyBudgetTemplateParametersInput

The epsilon and noise parameters that you want to use for the privacy budget template.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

differentialPrivacy

An object that specifies the epsilon and noise parameters.

Type: DifferentialPrivacyTemplateParametersInput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyBudgetTemplateParametersOutput

The epsilon and noise parameters that were used in the privacy budget template.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

differentialPrivacy

The epsilon and noise parameters.

Type: DifferentialPrivacyTemplateParametersOutput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyBudgetTemplateSummary

A summary of the privacy budget template. The summary includes membership information, collaboration information, and creation information.

Contents

arn

The ARN of the privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:privacybudgettemplate/[\d\w-]+`

Required: Yes

collaborationArn

The ARN of the collaboration that contains this privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique ID of the collaboration that contains this privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time at which the privacy budget template was created.

Type: Timestamp

Required: Yes

id

The unique identifier of the privacy budget template.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The Amazon Resource Name (ARN) of the member who created the privacy budget template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The identifier for a membership resource.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

privacyBudgetType

The type of the privacy budget template.

Type: String

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: Yes

updateTime

The most recent time at which the privacy budget template was updated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyBudgetTemplateUpdateParameters

The epsilon and noise parameters that you want to update in the privacy budget template.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

differentialPrivacy

An object that specifies the new values for the epsilon and noise parameters.

Type: DifferentialPrivacyTemplateUpdateParameters object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

PrivacyImpact

Provides an estimate of the number of aggregation functions that the member who can query can run given the epsilon and noise parameters.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

differentialPrivacy

An object that lists the number and type of aggregation functions you can perform.

Type: DifferentialPrivacyPrivacyImpact object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJob

The parameters for an AWS Clean Rooms protected job.

Contents

createTime

The creation time of the protected job.

Type: Timestamp

Required: Yes

id

The identifier for a protected job instance.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The ARN of the membership.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

he identifier for the membership.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

status

The status of the protected job.

Type: String

Valid Values: `SUBMITTED | STARTED | CANCELLED | CANCELLING | FAILED | SUCCESS`

Required: Yes

computeConfiguration

The compute configuration for the protected job.

Type: ProtectedJobComputeConfiguration object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

error

The error from the protected job.

Type: ProtectedJobError object

Required: No

jobParameters

The job parameters for the protected job.

Type: ProtectedJobParameters object

Required: No

result

The result of the protected job.

Type: ProtectedJobResult object

Required: No

resultConfiguration

Contains any details needed to write the job results.

Type: ProtectedJobResultConfigurationOutput object

Required: No

statistics

The statistics of the protected job.

Type: ProtectedJobStatistics object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobComputeConfiguration

The configuration of the compute resources for a PySpark job.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

worker

The worker configuration for the compute environment.

Type: ProtectedJobWorkerComputeConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobConfigurationDetails

The protected job configuration details.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

directAnalysisConfigurationDetails

The details needed to configure the direct analysis.

Type: ProtectedJobDirectAnalysisConfigurationDetails object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobDirectAnalysisConfigurationDetails

The protected job direct analysis configuration details.

Contents

receiverAccountIds

The receiver account IDs.

Type: Array of strings

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobError

The protected job error.

Contents

code

The error code for the protected job.

Type: String

Required: Yes

message

The message for the protected job error.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobMemberOutputConfigurationInput

The protected job member output configuration input.

Contents

accountId

The account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobMemberOutputConfigurationOutput

The protected job member output configuration output.

Contents

accountId

The account ID.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobOutput

Contains details about the protected job output.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

memberList

The list of member AWS account(s) that received the results of the job.

Type: Array of ProtectedJobSingleMemberOutput objects

Required: No

s3

If present, the output for a protected job with an `S3` output type.

Type: ProtectedJobS3Output object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobOutputConfigurationInput

The protected job output configuration input.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

member

The member of the protected job output configuration input.

Type: ProtectedJobMemberOutputConfigurationInput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobOutputConfigurationOutput

The protected job output configuration output.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

member

The member output configuration for a protected job.

Type: ProtectedJobMemberOutputConfigurationOutput object

Required: No

s3

If present, the output for a protected job with an `S3` output type.

Type: ProtectedJobS3OutputConfigurationOutput object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobParameters

The parameters for the protected job.

Contents

analysisTemplateArn

The ARN of the analysis template.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobReceiverConfiguration

The protected job receiver configuration.

Contents

analysisType

The analysis type for the protected job receiver configuration.

Type: String

Valid Values: `DIRECT_ANALYSIS`

Required: Yes

configurationDetails

The configuration details for the protected job receiver.

Type: ProtectedJobConfigurationDetails object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobResult

Details about the job results.

Contents

output

The output of the protected job.

Type: ProtectedJobOutput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobResultConfigurationInput

The protected job result configuration input.

Contents

outputConfiguration

The output configuration for a protected job result.

Type: ProtectedJobOutputConfigurationInput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobResultConfigurationOutput

The output configuration for a protected job result.

Contents

outputConfiguration

The output configuration.

Type: ProtectedJobOutputConfigurationOutput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobS3Output

Contains output information for protected jobs with an S3 output type.

Contents

location

The S3 location for the protected job output.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobS3OutputConfigurationInput

Contains input information for protected jobs with an S3 output type.

Contents

bucket

The S3 bucket for job output.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `.*(?!^(\d+\.)+\d+$)(^(([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])\.)*([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])$).*`

Required: Yes

keyPrefix

The S3 prefix to unload the protected job results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `[\w!.=*/-]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobS3OutputConfigurationOutput

The output configuration for a protected job's S3 output.

Contents

bucket

The S3 bucket for job output.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `.*(?!^(\d+\.)+\d+$)(^(([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])\.)*([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])$).*`

Required: Yes

keyPrefix

The S3 prefix to unload the protected job results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `[\w!.=*/-]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobSingleMemberOutput

Details about the member who received the job result.

Contents

accountId

The AWS account ID of the member in the collaboration who can receive results from analyses.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobStatistics

Contains statistics about the execution of the protected job.

Contents

billedResourceUtilization

The billed resource utilization for the protected job.

Type: BilledJobResourceUtilization object

Required: No

totalDurationInMillis

The duration of the protected job, from creation until job completion, in milliseconds.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobSummary

The protected job summary for the objects listed by the request.

Contents

createTime

The time the protected job was created.

Type: Timestamp

Required: Yes

id

The ID of the protected job.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The unique ARN for the membership that initiated the protected job.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique ID for the membership that initiated the protected job.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

receiverConfigurations

The receiver configurations for the protected job.

Type: Array of ProtectedJobReceiverConfiguration objects

Required: Yes

status

The status of the protected job.

Type: String

Valid Values: `SUBMITTED | STARTED | CANCELLED | CANCELLING | FAILED | SUCCESS`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedJobWorkerComputeConfiguration

The configuration of the compute resources for a PySpark job.

Contents

number

The number of workers for a PySpark job.

Type: Integer

Valid Range: Minimum value of 4. Maximum value of 128.

Required: Yes

type

The worker compute configuration type.

Type: String

Valid Values: `CR.1X | CR.4X`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQuery

The parameters for an AWS Clean Rooms protected query.

Contents

createTime

The time at which the protected query was created.

Type: Timestamp

Required: Yes

id

The identifier for a protected query instance.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The ARN of the membership.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The identifier for the membership.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

status

The status of the query.

Type: String

Valid Values: `SUBMITTED | STARTED | CANCELLED | CANCELLING | FAILED | SUCCESS | TIMED_OUT`

Required: Yes

computeConfiguration

The compute configuration for the protected query.

Type: ComputeConfiguration object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

differentialPrivacy

The sensitivity parameters of the differential privacy results of the protected query.

Type: DifferentialPrivacyParameters object

Required: No

error

An error thrown by the protected query.

Type: ProtectedQueryError object

Required: No

result

The result of the protected query.

Type: ProtectedQueryResult object

Required: No

resultConfiguration

Contains any details needed to write the query results.

Type: ProtectedQueryResultConfiguration object

Required: No

sqlParameters

The protected query SQL parameters.

Type: ProtectedQuerySQLParameters object

Required: No

statistics

Statistics about protected query execution.

Type: ProtectedQueryStatistics object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryDistributeOutput

Contains the output information for a protected query with a distribute output configuration.

This output type allows query results to be distributed to multiple receivers, including S3 and collaboration members. It is only available for queries using the Spark analytics engine.

Contents

memberList

Contains the output results for each member location specified in the distribute output configuration. Each entry provides details about the result distribution to a specific collaboration member.

Type: Array of ProtectedQuerySingleMemberOutput objects

Required: No

s3

Contains output information for protected queries with an S3 output type.

Type: ProtectedQueryS3Output object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryDistributeOutputConfiguration

Specifies the configuration for distributing protected query results to multiple receivers, including S3 and collaboration members.

Contents

locations

A list of locations where you want to distribute the protected query results. Each location must specify either an S3 destination or a collaboration member destination.

> **Important**
>
> You can't specify more than one S3 location.
> You can't specify the query runner's account as a member location.
> You must include either an S3 or member output configuration for each location, but not both.

Type: Array of ProtectedQueryDistributeOutputConfigurationLocation objects

Array Members: Minimum number of 1 item.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryDistributeOutputConfigurationLocation

Specifies where you'll distribute the results of your protected query. You must configure either an S3 destination or a collaboration member destination.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

member

Contains configuration details for the protected query member output.

Type: ProtectedQueryMemberOutputConfiguration object

Required: No

s3

Contains the configuration to write the query results to S3.

Type: ProtectedQueryS3OutputConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryError

Details of errors thrown by the protected query.

Contents

code

An error code for the error.

Type: String

Required: Yes

message

A description of why the query failed.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryMemberOutputConfiguration

Contains configuration details for the protected query member output.

Contents

accountId

The unique identifier for the account.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryOutput

Contains details about the protected query output.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

distribute

Contains output information for protected queries that use a `distribute` output type. This output type lets you send query results to multiple locations - either to S3 or to collaboration members.

> **Note**
>
> You can only use the `distribute` output type with the Spark analytics engine.

Type: ProtectedQueryDistributeOutput object

Required: No

memberList

The list of member AWS account(s) that received the results of the query.

Type: Array of ProtectedQuerySingleMemberOutput objects

Required: No

s3

If present, the output for a protected query with an S3 output type.

Type: ProtectedQueryS3Output object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryOutputConfiguration

Contains configuration details for protected query output.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

distribute

Required configuration for a protected query with a `distribute` output type.

Type: ProtectedQueryDistributeOutputConfiguration object

Required: No

member

Required configuration for a protected query with a `member` output type.

Type: ProtectedQueryMemberOutputConfiguration object

Required: No

s3

Required configuration for a protected query with an `s3` output type.

Type: ProtectedQueryS3OutputConfiguration object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryResult

Details about the query results.

Contents

output

The output of the protected query.

Type: ProtectedQueryOutput object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryResultConfiguration

Contains configurations for protected query results.

Contents

outputConfiguration

Configuration for protected query results.

Type: ProtectedQueryOutputConfiguration object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryS3Output

Contains output information for protected queries with an S3 output type.

Contents

location

The S3 location of the result.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryS3OutputConfiguration

Contains the configuration to write the query results to S3.

Contents

bucket

The S3 bucket to unload the protected query results.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `.*(?!^(\d+\.)+\d+$)(^(([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])\.)*([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])$).*`

Required: Yes

resultFormat

Intended file format of the result.

Type: String

Valid Values: `CSV | PARQUET`

Required: Yes

keyPrefix

The S3 prefix to unload the protected query results.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 512.

Pattern: `[\w!.=*/-]*`

Required: No

singleFileOutput

Indicates whether files should be output as a single file (`TRUE`) or output as multiple files (`FALSE`). This parameter is only supported for analyses with the Spark analytics engine.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQuerySingleMemberOutput

Details about the member who received the query result.

Contents

accountId

The AWS account ID of the member in the collaboration who can receive results for the query.

Type: String

Length Constraints: Fixed length of 12.

Pattern: \d+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQuerySQLParameters

The parameters for the SQL type Protected Query.

Contents

analysisTemplateArn

The Amazon Resource Name (ARN) associated with the analysis template within a collaboration.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 200.

Pattern: `arn:aws:cleanrooms:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+/analysistemplate/[\d\w-]+`

Required: No

parameters

The protected query SQL parameters.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 100.

Key Pattern: `[0-9a-zA-Z_]+`

Value Length Constraints: Minimum length of 0. Maximum length of 250.

Required: No

queryString

The query string to be submitted.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQueryStatistics

Contains statistics about the execution of the protected query.

Contents

billedResourceUtilization

The billed resource utilization.

Type: BilledResourceUtilization object

Required: No

totalDurationInMillis

The duration of the protected query, from creation until query completion, in milliseconds.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ProtectedQuerySummary

The protected query summary for the objects listed by the request.

Contents

createTime

The time the protected query was created.

Type: Timestamp

Required: Yes

id

The unique ID of the protected query.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

membershipArn

The unique ARN for the membership that initiated the protected query.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:membership/[\d\w-]+`

Required: Yes

membershipId

The unique ID for the membership that initiated the protected query.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

receiverConfigurations

The receiver configuration.

Type: Array of ReceiverConfiguration objects

Required: Yes

status

The status of the protected query.

Type: String

Valid Values: `SUBMITTED | STARTED | CANCELLED | CANCELLING | FAILED | SUCCESS | TIMED_OUT`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

QueryComputePaymentConfig

An object representing the collaboration member's payment responsibilities set by the collaboration creator for query compute costs.

Contents

isResponsible

Indicates whether the collaboration creator has configured the collaboration member to pay for query compute costs (TRUE) or has not configured the collaboration member to pay for query compute costs (FALSE).

Exactly one member can be configured to pay for query compute costs. An error is returned if the collaboration creator sets a TRUE value for more than one member in the collaboration.

If the collaboration creator hasn't specified anyone as the member paying for query compute costs, then the member who can query is the default payer. An error is returned if the collaboration creator sets a FALSE value for the member who can query.

Type: Boolean

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

QueryConstraint

Provides any necessary query constraint information.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

requireOverlap

An array of column names that specifies which columns are required in the JOIN statement.

Type: QueryConstraintRequireOverlap object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

QueryConstraintRequireOverlap

Provides the name of the columns that are required to overlap.

Contents

columns

The columns that are required to overlap.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 127.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

ReceiverConfiguration

The receiver configuration for a protected query.

Contents

analysisType

The type of analysis for the protected query. The results of the query can be analyzed directly (`DIRECT_ANALYSIS`) or used as input into additional analyses (`ADDITIONAL_ANALYSIS`), such as a query that is a seed for a lookalike ML model.

Type: String

Valid Values: `DIRECT_ANALYSIS | ADDITIONAL_ANALYSIS`

Required: Yes

configurationDetails

The configuration details of the receiver configuration.

Type: ConfigurationDetails object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

S3Location

The S3 location.

Contents

bucket

The bucket name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `.*(?!^(\d+\.)+\d+$)(^(([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])\.)*([a-z0-9]|[a-z0-9][a-z0-9\-]*[a-z0-9])$).*`

Required: Yes

key

The object key.

Type: String

Pattern: `[a-zA-Z0-9!_.*'()-/]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Schema

A schema is a relation within a collaboration.

Contents

analysisRuleTypes

The analysis rule types that are associated with the schema. Currently, only one entry is present.

Type: Array of strings

Valid Values: `AGGREGATION | LIST | CUSTOM | ID_MAPPING_TABLE`

Required: Yes

collaborationArn

The unique Amazon Resource Name (ARN) for the collaboration that the schema belongs to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d \w-]+`

Required: Yes

collaborationId

The unique ID for the collaboration that the schema belongs to.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

columns

The columns for the relation that this schema represents.

Type: Array of Column objects

Required: Yes

createTime

The time at which the schema was created.

Type: Timestamp

Required: Yes

creatorAccountId

The unique account ID for the AWS account that owns the schema.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

description

A description for the schema.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t\r\n]*`

Required: Yes

name

A name for the schema. The schema relation is referred to by this name when queried by a protected query.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

partitionKeys

The partition keys for the dataset underlying this schema.

Type: Array of Column objects

Required: Yes

schemaStatusDetails

Details about the status of the schema. Currently, only one entry is present.

Type: Array of SchemaStatusDetail objects

Required: Yes

type

The type of schema.

Type: String

Valid Values: `TABLE | ID_MAPPING_TABLE`

Required: Yes

updateTime

The most recent time at which the schema was updated.

Type: Timestamp

Required: Yes

analysisMethod

The analysis method for the schema.

`DIRECT_QUERY` allows SQL queries to be run directly on this table.

`DIRECT_JOB` allows PySpark jobs to be run directly on this table.

`MULTIPLE` allows both SQL queries and PySpark jobs to be run directly on this table.

Type: String

Valid Values: `DIRECT_QUERY | DIRECT_JOB | MULTIPLE`

Required: No

schemaTypeProperties

The schema type properties.

Type: SchemaTypeProperties object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

selectedAnalysisMethods

The selected analysis methods for the schema.

Type: Array of strings

Valid Values: `DIRECT_QUERY | DIRECT_JOB`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SchemaAnalysisRuleRequest

Defines the information that's necessary to retrieve an analysis rule schema. Schema analysis rules are uniquely identified by a combination of the schema name and the analysis rule type for a given collaboration.

Contents

name

The name of the analysis rule schema that you are requesting.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

type

The type of analysis rule schema that you are requesting.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM | ID_MAPPING_TABLE`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SchemaStatusDetail

Information about the schema status.

A status of `READY` means that based on the schema analysis rule, queries of the given analysis rule type are properly configured to run queries on this schema.

Contents

analysisType

The type of analysis that can be performed on the schema.

A schema can have an `analysisType` of `DIRECT_ANALYSIS`, `ADDITIONAL_ANALYSIS_FOR_AUDIENCE_GENERATION`, or both.

Type: String

Valid Values: `DIRECT_ANALYSIS | ADDITIONAL_ANALYSIS`

Required: Yes

status

The status of the schema, indicating if it is ready to query.

Type: String

Valid Values: `READY | NOT_READY`

Required: Yes

analysisRuleType

The analysis rule type for which the schema status has been evaluated.

Type: String

Valid Values: `AGGREGATION | LIST | CUSTOM | ID_MAPPING_TABLE`

Required: No

configurations

The configuration details of the schema analysis rule for the given type.

Type: Array of strings

Valid Values: `DIFFERENTIAL_PRIVACY`

Required: No

reasons

The reasons why the schema status is set to its current state.

Type: Array of SchemaStatusReason objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SchemaStatusReason

A reason why the schema status is set to its current value.

Contents

code

The schema status reason code.

Type: String

Valid Values: `ANALYSIS_RULE_MISSING | ANALYSIS_TEMPLATES_NOT_CONFIGURED | ANALYSIS_PROVIDERS_NOT_CONFIGURED | DIFFERENTIAL_PRIVACY_POLICY_NOT_CONFIGURED | ID_MAPPING_TABLE_NOT_POPULATED | COLLABORATION_ANALYSIS_RULE_NOT_CONFIGURED | ADDITIONAL_ANALYSES_NOT_CONFIGURED | RESULT_RECEIVERS_NOT_CONFIGURED | ADDITIONAL_ANALYSES_NOT_ALLOWED | RESULT_RECEIVERS_NOT_ALLOWED | ANALYSIS_RULE_TYPES_NOT_COMPATIBLE`

Required: Yes

message

An explanation of the schema status reason code.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SchemaSummary

The schema summary for the objects listed by the request.

Contents

analysisRuleTypes

The types of analysis rules that are associated with this schema object.

Type: Array of strings

Valid Values: `AGGREGATION | LIST | CUSTOM | ID_MAPPING_TABLE`

Required: Yes

collaborationArn

The unique ARN for the collaboration that the schema belongs to.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 100.

Pattern: `arn:aws:[\w]+:[\w]{2}-[\w]{4,9}-[\d]:[\d]{12}:collaboration/[\d\w-]+`

Required: Yes

collaborationId

The unique ID for the collaboration that the schema belongs to.

Type: String

Length Constraints: Fixed length of 36.

Pattern: `[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

createTime

The time the schema object was created.

Type: Timestamp

Required: Yes

creatorAccountId

The unique account ID for the AWS account that owns the schema.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d+`

Required: Yes

name

The name for the schema object.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-zA-Z0-9_](([a-zA-Z0-9_ ]+-)*([a-zA-Z0-9_ ]+))?`

Required: Yes

type

The type of schema object.

Type: String

Valid Values: `TABLE | ID_MAPPING_TABLE`

Required: Yes

updateTime

The time the schema object was last updated.

Type: Timestamp

Required: Yes

analysisMethod

The analysis method for the associated schema.

`DIRECT_QUERY` allows SQL queries to be run directly on this table.

`DIRECT_JOB` allows PySpark jobs to be run directly on this table.

`MULTIPLE` allows both SQL queries and PySpark jobs to be run directly on this table.

Type: String

Valid Values: `DIRECT_QUERY | DIRECT_JOB | MULTIPLE`

Required: No

selectedAnalysisMethods

The selected analysis methods for the schema.

Type: Array of strings

Valid Values: `DIRECT_QUERY | DIRECT_JOB`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SchemaTypeProperties

Information about the schema type properties.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

idMappingTable

The ID mapping table for the schema type properties.

Type: IdMappingTableSchemaTypeProperties object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SnowflakeTableReference

A reference to a table within Snowflake.

Contents

accountIdentifier

The account identifier for the Snowflake table reference.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 256.

Pattern: `[\p{L}\p{M}\p{N}\p{Pc}\p{Pd}\p{Zs}.]+`

Required: Yes

databaseName

The name of the database the Snowflake table belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\p{L}\p{M}\p{N}\p{Pc}\p{Pd}\p{Zs}]+`

Required: Yes

schemaName

The schema name of the Snowflake table reference.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\p{L}\p{M}\p{N}\p{Pc}\p{Pd}\p{Zs}]+`

Required: Yes

secretArn

The secret ARN of the Snowflake table reference.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `arn:aws:secretsmanager:[a-z]{2}-[a-z]+-[0-9]:\d{12}:secret:.*`

Required: Yes

tableName

The name of the Snowflake table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\p{L}\p{M}\p{N}\p{Pc}\p{Pd}\p{Zs}]+`

Required: Yes

tableSchema

The schema of the Snowflake table.

Type: SnowflakeTableSchema object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SnowflakeTableSchema

The schema of a Snowflake table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

v1

The schema of a Snowflake table.

Type: Array of SnowflakeTableSchemaV1 objects

Array Members: Minimum number of 1 item. Maximum number of 250 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

SnowflakeTableSchemaV1

The Snowflake table schema.

Contents

columnName

The column name.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 128.

Pattern: `[a-z0-9_](([a-z0-9_ ]+-)*([a-z0-9_ ]+))?`

Required: Yes

columnType

The column's data type. Supported data types: `ARRAY`, `BIGINT`, `BOOLEAN`, `CHAR`, `DATE`, `DECIMAL`, `DOUBLE`, `DOUBLE PRECISION`, `FLOAT`, `FLOAT4`, `INT`, `INTEGER`, `MAP`, `NUMERIC`, `NUMBER`, `REAL`, `SMALLINT`, `STRING`, `TIMESTAMP`, `TIMESTAMP_LTZ`, `TIMESTAMP_NTZ`, `DATETIME`, `TINYINT`, `VARCHAR`, `TEXT`, `CHARACTER`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 255.

Pattern: `[\u0020-\uD7FF\uE000-\uFFFD\uD800\uDBFF-\uDC00\uDFFF\t]*`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

TableReference

A pointer to the dataset that underlies this table.

Contents

> **Important**
>
> This data type is a UNION, so only one of the following members can be specified when used or returned.

athena

If present, a reference to the Athena table referred to by this table reference.

Type: AthenaTableReference object

Required: No

glue

If present, a reference to the AWS Glue table referred to by this table reference.

Type: GlueTableReference object

Required: No

snowflake

If present, a reference to the Snowflake table referred to by this table reference.

Type: SnowflakeTableReference object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++

- AWS SDK for Java V2
- AWS SDK for Ruby V3

ValidationExceptionField

Describes validation errors for specific input parameters.

Contents

message

A message for the input validation error.

Type: String

Required: Yes

name

The name of the input parameter.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

WorkerComputeConfiguration

The configuration of the compute resources for workers running an analysis with the AWS Clean Rooms SQL analytics engine.

Contents

number

The number of workers.

SQL queries support a minimum value of 2 and a maximum value of 400.

PySpark jobs support a minimum value of 4 and a maximum value of 128.

Type: Integer

Valid Range: Minimum value of 2. Maximum value of 400.

Required: No

type

The worker compute configuration type.

Type: String

Valid Values: `CR.1X | CR.4X`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- AWS SDK for C++
- AWS SDK for Java V2
- AWS SDK for Ruby V3

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see Signing AWS API requests in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key*/*YYYYMMDD*/*region*/*service*/aws4_request.

For more information, see Create a signed AWS API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see Elements of an AWS API request signature in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see AWS services that work with IAM in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see Create a signed AWS API request in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400