aws

Hands-on tutorials

Connect to Private Amazon RDS PostgreSQL Database Using AWS CloudShell

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Connect to Private Amazon RDS PostgreSQL Database Using AWS CloudShell: Hands-on tutorials

Copyright © 2026 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Connect to Private Amazon RDS PostgreSQL Database Using AWS CloudShell 1
Introduction 1
Prerequisites 1
Tasks 2
Implementation 2
Conclusion 12

Connect to Private Amazon RDS PostgreSQL Database Using AWS CloudShell

AWS experience	Beginner
Time to complete	30 minutes
Cost to complete	Less than $1 when completed in 1 hour
Services used	AWS CloudShell and Amazon RDS for PostgreSQL
Last updated	February 23, 2026

Introduction

Following AWS best practices, databases should be hosted in private subnets within an Amazon Virtual Private Cloud (Amazon VPC) for enhanced security. When an Amazon RDS PostgreSQL database is hosted in private subnets without public access, you must create another instance in a public subnet and then connect to the database instance. Alternatively, you can establish a connection by creating an AWS Client VPN; however, both options incur additional costs.

A simpler and more cost-effective alternative is to use AWS CloudShell. AWS CloudShell is a browser-based, pre-authenticated shell that you can launch directly from the AWS Management Console. The AWS CloudShell VPC feature allows you to create a CloudShell environment within your VPC. For each VPC environment, you can specify a VPC, add a subnet, and associate up to five security groups. CloudShell inherits the network configuration of the VPC, enabling you to use CloudShell securely within the same subnet as other resources in the VPC and connect to them.

There is no additional charge for AWS CloudShell. You only pay for other AWS resources you use with CloudShell to create and run your applications.

Prerequisites

Before starting this tutorial, you will need:

- An AWS account: If you don't already have one, follow the Setting Up Your AWS Environment getting started guide for a quick overview.

Tasks

This tutorial is divided into the following short tasks. You must complete each task before moving on to the next one.

1. Create a custom Amazon Virtual Private Cloud with public and private subnets (5 Minutes)
2. Create an Amazon RDS PostgreSQL database hosted in private subnets within an Amazon VPC. (10 Minutes)
3. Set up an AWS CloudShell Virtual Private Cloud environment and test connectivity (10 Minutes)
4. Clean up resources (5 Minutes)

Implementation

Task 1: Create a custom Amazon Virtual Private Cloud with public and private subnets

In this task, you will use an AWS CloudFormation template to create a custom Amazon VPC with public and private subnets.

1. Open AWS CloudShell
2. Copy and paste the following commands into CloudShell:

```
git clone https://github.com/aws-samples/sample-Amazon-Q-Developer-Cookbook.git
cd sample-Amazon-Q-Developer-Cookbook/dev-vpc-with-private-subnet/example-result/
custom-vpc
chmod 700 deploy.sh
./deploy.sh
```

3. Choose **Paste**.

   The commands performed the following actions:

   - Deployed an AWS CloudFormation template in a VPC with a pair of public and private subnets spread across two Availability Zones.

- Deployed an internet gateway with a default route on the public subnets.
- Deployed a NAT gateway and default routes for the NAT gateway in the private subnets.

4. Open AWS CloudFormation and wait for the Status column of the **custom-vpc** stack to show CREATE_COMPLETE.
5. Open Amazon VPC.
6. Select **Your VPCs** from the left menu.
7. Select **CustomVPC**, and then select the **Resource map tab** to review the layout of the subnets and route tables.



Task 2: Create an Amazon RDS PostgreSQL database hosted in private subnets within an Amazon VPC

In this task, you will create an Amazon RDS PostgreSQL database hosted in private subnets within an Amazon VPC you've created in the previous task.

1. Open the Amazon RDS console, and select **Create a database**.



2. For Engine options, select **PostgreSQL** Engine type.



3. For Engine version, select **PostgreSQL 16.8-R2**.



4. Select the **Dev/Test** template with the **Single-AZ DB instance deployment** option.



5. Name your DB instance identifier.

   a. For example, **postgresql-demo**



6. Under Instance Configuration, select **Burstable classes**.
7. Select **db.t3.medium** for DB instance class, and set Allocated Storage to **20GB**.



8. Under **Connectivity**:
   - Select the **CustomVPC** you created in previous task.
   - Confirm that the **Public access** setting is set to **No**.
   - Select the **default security group**.



9. Leave all other options as their default settings, and choose **Create database**.

10. After the database instance successfully creates, select **View connection Details**.



11. Copy the hostname of the instance, and select **Manage Credentials**.



12. Retrieve the password by selecting **Retrieve secret value**.

> **Important**
>
> Take note of the **username**, **Endpoint**, and **password**. You will need these values for your VPC environment in the next task.



Task 3: Set up an AWS CloudShell Virtual Private Cloud environment and test connectivity

In this task, you will set up an AWS CloudShell VPC environment and test connectivity.

1. Open AWS CloudShell, and select the **+** button to bring up an option for **Create VPC environment**.



2. Name the VPC environment.
   a. For example, **cloudshell-vpc-demo**.
3. Select **CustomVPC**, any **Private subnet,** and the **default security group**.
4. Choose **Create**.


CloudShell us-west-2
Create a VPC environment
After creating a VPC environment, a new tab linked to this environment is added to CloudShell. You can access your VPC environment by selecting this tab.
Name
A unique VPC environment name used to identify it within AWS CloudShell.
cloudshell-vpc-demo
Must contain up to 28 alphanumeric characters, hyphens, and no spaces. The first character must be a letter or a number.
Virtual private cloud (VPC)
vpc-0e715a73793ea2ad6
Subnet
subnet-0bc6651cd55aa3539
Security group
sg-07eb8f116a4d6a3de
default - default VPC security group
Maximum of 5.
After 30 minutes of inactivity, the shell session will terminate and the home directory of the VPC environment will be deleted.
Cancel
Create

> **Note**
>
> Public IP addresses are not allocated to CloudShell VPC environments by default. VPC environments created in public subnets with routing tables configured to route all traffic to Internet Gateway will not have access to public internet, but private subnets configured with Network Address Translation (NAT) have access to public internet. VPC environments created in such private subnets will have access to public internet.

5. Once the environment is set up, install version 16 of PostgreSQL by copying and pasting these commands.
6. Choose **Paste**.

> **Note**
>
> It is possible that your PostgreSQL version may be outdated compared to your Amazon RDS PostgreSQL database. These commands remove the older version and installs PostgreSQL version 16.

```
psql --version
sudo dnf remove postgresql15* -y
sudo dnf clean all
```

7. After that completes, copy and paste the following command to install version 16 of PostgreSQL.
8. Choose **Paste**.

```
sudo dnf install postgresql16 -y
```

9. In your AWS CloudShell VPC environment, run the following PostgreSQL command:

> **Note**
>
> These are the values at the end of Task 2.

```
psql -h <HOSTNAME> -U <USERNAME>
```

Note

<HOSTNAME> is your database endpoint

<USERNAME> is your database administrator username

10Enter your **password** to finish establishing a connection to your database.



11Validate your setup by running this test command:

```
CREATE DATABASE demodb;
```



Task 4: Clean up resources

To avoid unexpected charges, follow these clean-up steps:

1. Open AWS CloudShell, and select **Delete**.

> **Note**
>
> VPC environments do not have persistent storage. The $HOME directory is deleted when your VPC environment times out (after 20-30 minutes of inactivity), or when you delete or restart your environment.



2. Enter **delete**, and choose **Delete** to confirm the deletion of the VPC environment.
3. Open Amazon RDS, and select **Databases**.
4. Select **postgresql-demo**.

5. Select **Actions**, and select **Delete.**



6. Enter **delete me** to remove the PostgreSQL database instance.
7. Open AWS CloudFormation, and select **custom-vpc**.
8. Select **Delete.**



9. Choose **Delete** to remove the CloudFormation stack.

Conclusion

You have learned how to connect to an Amazon RDS PostgreSQL instance in private subnets within Amazon VPC using AWS CloudShell.