



Welcome

Managed integrations



API Version 2025-03-03

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Managed integrations: Welcome

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateCredentialLocker	5
Request Syntax	5
URI Request Parameters	5
Request Body	5
Response Syntax	6
Response Elements	6
Errors	7
See Also	8
CreateDestination	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	11
Response Elements	11
Errors	12
See Also	12
CreateEventLogConfiguration	14
Request Syntax	14
URI Request Parameters	14
Request Body	14
Response Syntax	15
Response Elements	15
Errors	16
See Also	17
CreateManagedThing	18
Request Syntax	18
URI Request Parameters	19
Request Body	19
Response Syntax	23
Response Elements	23
Errors	24
See Also	25

CreateNotificationConfiguration	27
Request Syntax	27
URI Request Parameters	27
Request Body	27
Response Syntax	28
Response Elements	29
Errors	29
See Also	30
CreateOtaTask	31
Request Syntax	31
URI Request Parameters	32
Request Body	32
Response Syntax	34
Response Elements	35
Errors	36
See Also	36
CreateOtaTaskConfiguration	38
Request Syntax	38
URI Request Parameters	39
Request Body	39
Response Syntax	40
Response Elements	40
Errors	40
See Also	41
CreateProvisioningProfile	43
Request Syntax	43
URI Request Parameters	43
Request Body	43
Response Syntax	45
Response Elements	45
Errors	46
See Also	47
DeleteCredentialLocker	49
Request Syntax	49
URI Request Parameters	49
Request Body	49

Response Syntax	49
Response Elements	49
Errors	50
See Also	50
DeleteDestination	52
Request Syntax	52
URI Request Parameters	52
Request Body	52
Response Syntax	52
Response Elements	52
Errors	52
See Also	53
DeleteEventLogConfiguration	55
Request Syntax	55
URI Request Parameters	55
Request Body	55
Response Syntax	55
Response Elements	55
Errors	55
See Also	56
DeleteManagedThing	58
Request Syntax	58
URI Request Parameters	58
Request Body	58
Response Syntax	58
Response Elements	58
Errors	59
See Also	60
DeleteNotificationConfiguration	61
Request Syntax	61
URI Request Parameters	61
Request Body	61
Response Syntax	61
Response Elements	61
Errors	61
See Also	62

DeleteOtaTask	64
Request Syntax	64
URI Request Parameters	64
Request Body	64
Response Syntax	64
Response Elements	64
Errors	64
See Also	65
DeleteOtaTaskConfiguration	67
Request Syntax	67
URI Request Parameters	67
Request Body	67
Response Syntax	67
Response Elements	67
Errors	67
See Also	68
DeleteProvisioningProfile	70
Request Syntax	70
URI Request Parameters	70
Request Body	70
Response Syntax	70
Response Elements	70
Errors	70
See Also	71
GetCredentialLocker	73
Request Syntax	73
URI Request Parameters	73
Request Body	73
Response Syntax	73
Response Elements	74
Errors	75
See Also	76
GetCustomEndpoint	77
Request Syntax	77
URI Request Parameters	77
Request Body	77

Response Syntax	77
Response Elements	77
Errors	78
See Also	79
GetDefaultEncryptionConfiguration	80
Request Syntax	80
URI Request Parameters	80
Request Body	80
Response Syntax	80
Response Elements	80
Errors	81
See Also	82
GetDestination	84
Request Syntax	84
URI Request Parameters	84
Request Body	84
Response Syntax	84
Response Elements	85
Errors	86
See Also	87
GetDeviceDiscovery	89
Request Syntax	89
URI Request Parameters	89
Request Body	89
Response Syntax	89
Response Elements	90
Errors	92
See Also	93
GetEventLogConfiguration	94
Request Syntax	94
URI Request Parameters	94
Request Body	94
Response Syntax	94
Response Elements	94
Errors	95
See Also	96

GitHubConfiguration	98
Request Syntax	98
URI Request Parameters	98
Request Body	98
Response Syntax	98
Response Elements	98
Errors	99
See Also	100
GetManagedThing	101
Request Syntax	101
URI Request Parameters	101
Request Body	101
Response Syntax	101
Response Elements	102
Errors	108
See Also	109
GetManagedThingCapabilities	110
Request Syntax	110
URI Request Parameters	110
Request Body	110
Response Syntax	110
Response Elements	111
Errors	112
See Also	113
GetManagedThingConnectivityData	114
Request Syntax	114
URI Request Parameters	114
Request Body	114
Response Syntax	114
Response Elements	114
Errors	115
See Also	116
GetManagedThingMetaData	118
Request Syntax	118
URI Request Parameters	118
Request Body	118

Response Syntax	118
Response Elements	119
Errors	119
See Also	120
GetManagedThingState	122
Request Syntax	122
URI Request Parameters	122
Request Body	122
Response Syntax	122
Response Elements	123
Errors	123
See Also	124
GetNotificationConfiguration	125
Request Syntax	125
URI Request Parameters	125
Request Body	125
Response Syntax	125
Response Elements	126
Errors	127
See Also	127
GetOtaTask	129
Request Syntax	129
URI Request Parameters	129
Request Body	129
Response Syntax	129
Response Elements	130
Errors	133
See Also	134
GetOtaTaskConfiguration	135
Request Syntax	135
URI Request Parameters	135
Request Body	135
Response Syntax	135
Response Elements	136
Errors	137
See Also	138

GetProvisioningProfile	139
Request Syntax	139
URI Request Parameters	139
Request Body	139
Response Syntax	139
Response Elements	140
Errors	141
See Also	142
GetRuntimeLogConfiguration	143
Request Syntax	143
URI Request Parameters	143
Request Body	143
Response Syntax	143
Response Elements	144
Errors	144
See Also	145
GetSchemaVersion	146
Request Syntax	146
URI Request Parameters	146
Request Body	146
Response Syntax	146
Response Elements	147
Errors	148
See Also	149
ListCredentialLockers	151
Request Syntax	151
URI Request Parameters	151
Request Body	151
Response Syntax	151
Response Elements	152
Errors	152
See Also	153
ListDestinations	154
Request Syntax	154
URI Request Parameters	154
Request Body	154

Response Syntax	154
Response Elements	155
Errors	155
See Also	156
ListEventLogConfigurations	157
Request Syntax	157
URI Request Parameters	157
Request Body	157
Response Syntax	157
Response Elements	158
Errors	158
See Also	159
ListManagedThings	160
Request Syntax	160
URI Request Parameters	160
Request Body	161
Response Syntax	161
Response Elements	162
Errors	163
See Also	164
ListManagedThingSchemas	165
Request Syntax	165
URI Request Parameters	165
Request Body	166
Response Syntax	166
Response Elements	166
Errors	167
See Also	168
ListNotificationConfigurations	169
Request Syntax	169
URI Request Parameters	169
Request Body	169
Response Syntax	169
Response Elements	170
Errors	170
See Also	171

ListOtaTaskConfigurations	172
Request Syntax	172
URI Request Parameters	172
Request Body	172
Response Syntax	172
Response Elements	173
Errors	173
See Also	174
ListOtaTaskExecutions	175
Request Syntax	175
URI Request Parameters	175
Request Body	175
Response Syntax	175
Response Elements	176
Errors	176
See Also	177
ListOtaTasks	179
Request Syntax	179
URI Request Parameters	179
Request Body	179
Response Syntax	179
Response Elements	180
Errors	180
See Also	181
ListProvisioningProfiles	182
Request Syntax	182
URI Request Parameters	182
Request Body	182
Response Syntax	182
Response Elements	183
Errors	183
See Also	184
ListSchemaVersions	186
Request Syntax	186
URI Request Parameters	186
Request Body	187

Response Syntax	187
Response Elements	188
Errors	188
See Also	189
PutDefaultEncryptionConfiguration	190
Request Syntax	190
URI Request Parameters	190
Request Body	190
Response Syntax	191
Response Elements	191
Errors	192
See Also	193
PutHubConfiguration	194
Request Syntax	194
URI Request Parameters	194
Request Body	194
Response Syntax	194
Response Elements	195
Errors	195
See Also	196
PutRuntimeLogConfiguration	197
Request Syntax	197
URI Request Parameters	197
Request Body	197
Response Syntax	198
Response Elements	198
Errors	198
See Also	199
RegisterCustomEndpoint	200
Request Syntax	200
URI Request Parameters	200
Request Body	200
Response Syntax	200
Response Elements	200
Errors	201
See Also	202

ResetRuntimeLogConfiguration	203
Request Syntax	203
URI Request Parameters	203
Request Body	203
Response Syntax	203
Response Elements	203
Errors	203
See Also	204
SendManagedThingCommand	206
Request Syntax	206
URI Request Parameters	206
Request Body	207
Response Syntax	207
Response Elements	207
Errors	208
See Also	209
StartDeviceDiscovery	210
Request Syntax	210
URI Request Parameters	210
Request Body	210
Response Syntax	212
Response Elements	212
Errors	213
See Also	214
UpdateDestination	215
Request Syntax	215
URI Request Parameters	215
Request Body	215
Response Syntax	216
Response Elements	216
Errors	217
See Also	217
UpdateEventLogConfiguration	219
Request Syntax	219
URI Request Parameters	219
Request Body	219

Response Syntax	220
Response Elements	220
Errors	220
See Also	221
UpdateManagedThing	222
Request Syntax	222
URI Request Parameters	223
Request Body	223
Response Syntax	226
Response Elements	226
Errors	226
See Also	227
UpdateNotificationConfiguration	229
Request Syntax	229
URI Request Parameters	229
Request Body	229
Response Syntax	230
Response Elements	230
Errors	230
See Also	231
UpdateOtaTask	232
Request Syntax	232
URI Request Parameters	232
Request Body	232
Response Syntax	233
Response Elements	233
Errors	233
See Also	234
Data Types	235
AbortConfigCriteria	237
Contents	237
See Also	238
CapabilityAction	239
Contents	239
See Also	240
CapabilityReport	241

Contents	241
See Also	241
CapabilityReportCapability	243
Contents	243
See Also	244
CapabilityReportEndpoint	246
Contents	246
See Also	247
CommandCapability	248
Contents	248
See Also	249
CommandEndpoint	250
Contents	250
See Also	250
ConfigurationError	251
Contents	251
See Also	251
ConfigurationStatus	252
Contents	252
See Also	252
CredentialLockerSummary	253
Contents	253
See Also	254
DestinationSummary	255
Contents	255
See Also	256
EventLogConfigurationSummary	257
Contents	257
See Also	258
ExponentialRolloutRate	259
Contents	259
See Also	259
ManagedThingSchemaListItem	261
Contents	261
See Also	261
ManagedThingSummary	263

Contents	263
See Also	267
NotificationConfigurationSummary	269
Contents	269
See Also	269
OtaTaskAbortConfig	270
Contents	270
See Also	270
OtaTaskConfigurationSummary	271
Contents	271
See Also	271
OtaTaskExecutionRetryConfig	273
Contents	273
See Also	273
OtaTaskExecutionRolloutConfig	274
Contents	274
See Also	274
OtaTaskExecutionSummaries	275
Contents	275
See Also	275
OtaTaskExecutionSummary	276
Contents	276
See Also	277
OtaTaskSchedulingConfig	278
Contents	278
See Also	278
OtaTaskSummary	280
Contents	280
See Also	281
OtaTaskTimeoutConfig	282
Contents	282
See Also	282
ProvisioningProfileSummary	283
Contents	283
See Also	284
PushConfig	285

Contents	285
See Also	285
RetryConfigCriteria	286
Contents	286
See Also	286
RolloutRateIncreaseCriteria	287
Contents	287
See Also	287
RuntimeLogConfigurations	288
Contents	288
See Also	289
ScheduleMaintenanceWindow	290
Contents	290
See Also	290
SchemaVersionListItem	291
Contents	291
See Also	292
StateCapability	293
Contents	293
See Also	294
StateEndpoint	295
Contents	295
See Also	295
TaskProcessingDetails	296
Contents	296
See Also	297
Common Parameters	298
Common Errors	301

Welcome

Managed integrations is a feature of AWS IoT Device Management that enables developers to quickly build innovative IoT solutions. Customers can use managed integrations to automate device setup workflows and support interoperability across many devices, regardless of device vendor or connectivity protocol. This allows developers to use a single user-interface to control, manage, and operate a range of devices.

IoT managed integrations is in preview release and is subject to change.

This document was last published on May 22, 2025.

Actions

The following actions are supported:

- [CreateCredentialLocker](#)
- [CreateDestination](#)
- [CreateEventLogConfiguration](#)
- [CreateManagedThing](#)
- [CreateNotificationConfiguration](#)
- [CreateOtaTask](#)
- [CreateOtaTaskConfiguration](#)
- [CreateProvisioningProfile](#)
- [DeleteCredentialLocker](#)
- [DeleteDestination](#)
- [DeleteEventLogConfiguration](#)
- [DeleteManagedThing](#)
- [DeleteNotificationConfiguration](#)
- [DeleteOtaTask](#)
- [DeleteOtaTaskConfiguration](#)
- [DeleteProvisioningProfile](#)
- [GetCredentialLocker](#)
- [GetCustomEndpoint](#)
- [GetDefaultEncryptionConfiguration](#)
- [GetDestination](#)
- [GetDeviceDiscovery](#)
- [GetEventLogConfiguration](#)
- [GetHubConfiguration](#)
- [GetManagedThing](#)
- [GetManagedThingCapabilities](#)
- [GetManagedThingConnectivityData](#)
- [GetManagedThingMetaData](#)

- [GetManagedThingState](#)
- [GetNotificationConfiguration](#)
- [GetOtaTask](#)
- [GetOtaTaskConfiguration](#)
- [GetProvisioningProfile](#)
- [GetRuntimeLogConfiguration](#)
- [GetSchemaVersion](#)
- [ListCredentialLockers](#)
- [ListDestinations](#)
- [ListEventLogConfigurations](#)
- [ListManagedThings](#)
- [ListManagedThingSchemas](#)
- [ListNotificationConfigurations](#)
- [ListOtaTaskConfigurations](#)
- [ListOtaTaskExecutions](#)
- [ListOtaTasks](#)
- [ListProvisioningProfiles](#)
- [ListSchemaVersions](#)
- [PutDefaultEncryptionConfiguration](#)
- [PutHubConfiguration](#)
- [PutRuntimeLogConfiguration](#)
- [RegisterCustomEndpoint](#)
- [ResetRuntimeLogConfiguration](#)
- [SendManagedThingCommand](#)
- [StartDeviceDiscovery](#)
- [UpdateDestination](#)
- [UpdateEventLogConfiguration](#)
- [UpdateManagedThing](#)
- [UpdateNotificationConfiguration](#)
- [UpdateOtaTask](#)

CreateCredentialLocker

Create a product credential locker. This operation will trigger the creation of all the manufacturing resources including the Wi-Fi setup key pair and device certificate.

Request Syntax

```
POST /credential-lockers HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Name

The name of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Tags

A set of key/value pairs that are used to manage the credential locker.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "Arn": "string",
  "CreatedAt": number,
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the credential locker.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:credential-locker/[0-9a-zA-Z-]+`

CreatedAt

The timestamp value of when the credential locker request occurred.

Type: Timestamp

Id

The identifier of the credential locker creation request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded for this request.

HTTP Status Code: 402

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDestination

Create a destination. IoT managed integrations uses the destination to determine where to deliver notifications for a device.

Request Syntax

```
POST /destinations HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "DeliveryDestinationArn": "string",
  "DeliveryDestinationType": "string",
  "Description": "string",
  "Name": "string",
  "RoleArn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z. _-]+`

Required: Yes

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Required: Yes

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-\]+`

Required: No

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _-]+`

Required: Yes

RoleArn

The Amazon Resource Name (ARN) of the delivery destination role.

Type: String

Required: Yes

Tags

A set of key/value pairs that are used to manage the destination.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEventLogConfiguration

Set the event log configuration for the account, resource type, or specific resource.

Request Syntax

```
POST /event-log-configurations HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "EventLogLevel": "string",
  "ResourceId": "string",
  "ResourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

EventLogLevel

The logging level for the event log configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: Yes

ResourceId

The identifier of the resource for the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [a-zA-Z0-9+]*

Required: No

ResourceType

The type of resource for the event log configuration.

Type: String

Pattern: [*]\${}^(managed-thing|credential-locker|provisioning-profile|ota-task)

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Id

The identifier of the event log configuration request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded for this request.

HTTP Status Code: 402

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateManagedThing

Creates a managed thing. A managed thing contains the device identifier, protocol supported, and capabilities of the device in a protocol-specific format.

Request Syntax

```
POST /managed-things HTTP/1.1
Content-type: application/json
```

```
{
  "AuthenticationMaterial": "string",
  "AuthenticationMaterialType": "string",
  "Brand": "string",
  "Capabilities": "string",
  "CapabilityReport": {
    "endpoints": [
      {
        "capabilities": [
          {
            "actions": [ "string" ],
            "events": [ "string" ],
            "id": "string",
            "name": "string",
            "properties": [ "string" ],
            "version": "string"
          }
        ],
        "deviceTypes": [ "string" ],
        "id": "string"
      }
    ],
    "nodeId": "string",
    "version": "string"
  },
  "Classification": "string",
  "ClientToken": "string",
  "CredentialLockerId": "string",
  "MetaData": {
    "string" : "string"
  },
  "Model": "string",
  "Name": "string",
```

```
"Owner": "string",
"Role": "string",
"SerialNumber": "string",
"Tags": {
  "string" : "string"
}
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AuthenticationMaterial

The authentication material defining the device connectivity setup requests. The authentication materials used are the device bar code.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Pattern: [0-9A-Za-z!#\$%&()*\+\-;<=>?@^_`{|}~\/:]+

Required: Yes

AuthenticationMaterialType

The type of authentication material used for device connectivity setup requests.

Type: String

Valid Values: WIFI_SETUP_QR_BAR_CODE | ZWAVE_QR_BAR_CODE | ZIGBEE_QR_BAR_CODE

Required: Yes

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

Capabilities

The capabilities of the device such as light bulb.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9\s'\x{0022}, . : \\ \\/ { \$ } \ [\] = _ \ - \ +]+

Required: No

CapabilityReport

A report of the capabilities for the managed thing.

Type: [CapabilityReport](#) object

Required: No

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

CredentialLockerId

The identifier of the credential for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

MetaData

The metadata for the managed thing.

Note

The managedThing metadata parameter is used for associating attributes with a managedThing that can be used for grouping over-the-air (OTA) tasks. Name value pairs in metadata can be used in the OtaTargetQueryString parameter for the CreateOtaTask API operation.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: .*[a-zA-Z0-9_.,@/:#-]+.*

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: .*[a-zA-Z0-9_.,@/:#-]*.*

Required: No

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\p{L}\p{N} ._-]+

Required: No

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.,@-]+

Required: No

Role

The type of device used. This will be the hub controller, cloud device, or AWS IoT device.

Type: String

Valid Values: CONTROLLER | DEVICE

Required: Yes

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Tags

A set of key/value pairs that are used to manage the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "Arn": "string",
  "CreatedAt": number,
  "Id": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the managed thing.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:managed-thing/([0-9a-zA-Z:_-])+`

CreatedAt

The timestamp value of when the device creation request occurred.

Type: Timestamp

Id

The id of the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateNotificationConfiguration

Creates a notification configuration. A configuration is a connection between an event type and a destination that you have already created.

Request Syntax

```
POST /notification-configurations HTTP/1.1
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "DestinationName": "string",
  "EventType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: Yes

EventType

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: `DEVICE_COMMAND | DEVICE_COMMAND_REQUEST | DEVICE_EVENT | DEVICE_LIFE_CYCLE | DEVICE_STATE | DEVICE_OTA | CONNECTOR_ASSOCIATION | CONNECTOR_ERROR_REPORT`

Required: Yes

Tags

A set of key/value pairs that are used to manage the notification configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{  
  "EventType": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

EventType

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST | DEVICE_EVENT |
DEVICE_LIFE_CYCLE | DEVICE_STATE | DEVICE_OTA | CONNECTOR_ASSOCIATION |
CONNECTOR_ERROR_REPORT

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOtaTask

Create an over-the-air (OTA) task to update a device.

Request Syntax

```
POST /ota-tasks HTTP/1.1
Content-type: application/json

{
  "ClientToken": "string",
  "Description": "string",
  "OtaMechanism": "string",
  "OtaSchedulingConfig": {
    "EndBehavior": "string",
    "EndTime": "string",
    "MaintenanceWindows": [
      {
        "DurationInMinutes": number,
        "StartTime": "string"
      }
    ],
    "StartTime": "string"
  },
  "OtaTargetQueryString": "string",
  "OtaTaskExecutionRetryConfig": {
    "RetryConfigCriteria": [
      {
        "FailureType": "string",
        "MinNumberOfRetries": number
      }
    ]
  },
  "OtaType": "string",
  "Protocol": "string",
  "S3Url": "string",
  "Tags": {
    "string" : "string"
  },
  "Target": [ "string" ],
  "TaskConfigurationId": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Description

The description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

OtaMechanism

The deployment mechanism for the over-the-air (OTA) task.

Type: String

Valid Values: PUSH

Required: No

OtaSchedulingConfig

Over-the-air (OTA) task scheduling config.

Type: [OtaTaskSchedulingConfig](#) object

Required: No

OtaTargetQueryString

The query string to add things to the thing group.

Type: String

Required: No

OtaTaskExecutionRetryConfig

Over-the-air (OTA) task retry config.

Type: [OtaTaskExecutionRetryConfig](#) object

Required: No

OtaType

The frequency type for the over-the-air (OTA) task.

Type: String

Valid Values: ONE_TIME | CONTINUOUS

Required: Yes

Protocol

The connection protocol the over-the-air (OTA) task uses to update the device.

Type: String

Valid Values: HTTP

Required: No

S3Url

The URL to the Amazon S3 bucket where the over-the-air (OTA) task is stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: Yes

Tags

A set of key/value pairs that are used to manage the over-the-air (OTA) task.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Target

The device targeted for the over-the-air (OTA) task.

Type: Array of strings

Required: No

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

Response Syntax

```
HTTP/1.1 201
```

```
Content-type: application/json
```

```
{  
  "Description": "string",  
  "TaskArn": "string",  
  "TaskId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Description

A description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

TaskArn

The Amazon Resource Name (ARN) of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1011.

Pattern: arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:ota-task/
[0-9a-zA-Z-]+

TaskId

The identifier of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOtaTaskConfiguration

Create a configuration for the over-the-air (OTA) task.

Request Syntax

```
POST /ota-task-configurations HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "Description": "string",
  "Name": "string",
  "PushConfig": {
    "AbortConfig": {
      "AbortConfigCriteriaList": [
        {
          "Action": "string",
          "FailureType": "string",
          "MinNumberOfExecutedThings": number,
          "ThresholdPercentage": number
        }
      ]
    },
    "RolloutConfig": {
      "ExponentialRolloutRate": {
        "BaseRatePerMinute": number,
        "IncrementFactor": number,
        "RateIncreaseCriteria": {
          "numberOfNotifiedThings": number,
          "numberOfSucceededThings": number
        }
      },
      "MaximumPerMinute": number
    },
    "TimeoutConfig": {
      "InProgressTimeoutInMinutes": number
    }
  }
}
```


URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Description

A description of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

Required: No

Name

The name of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

PushConfig

Describes the type of configuration used for the over-the-air (OTA) task.

Type: [PushConfig](#) object

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "TaskConfigurationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

TaskConfigurationId

The identifier of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

CreateProvisioningProfile

Create a provisioning profile for a device to execute the provisioning flows using a provisioning template. The provisioning template is a document that defines the set of resources and policies applied to a device during the provisioning process.

Request Syntax

```
POST /provisioning-profiles HTTP/1.1
Content-type: application/json

{
  "CaCertificate": "string",
  "ClientToken": "string",
  "Name": "string",
  "ProvisioningType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

CaCertificate

The id of the certificate authority (CA) certificate.

Type: String

Pattern: -----BEGIN CERTIFICATE-----.*(\.|\n)*-----END CERTIFICATE-----\n?

Required: No

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

Name

The name of the provisioning template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [0-9A-Za-z_-]+

Required: No

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: FLEET_PROVISIONING | JITR

Required: Yes

Tags

A set of key/value pairs that are used to manage the provisioning profile.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Arn": "string",
  "ClaimCertificate": "string",
  "ClaimCertificatePrivateKey": "string",
  "Id": "string",
  "Name": "string",
  "ProvisioningType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the provisioning template used in the provisioning profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 64.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:provisioning-profile/[0-9a-zA-Z-]+`

ClaimCertificate

The id of the claim certificate.

Type: String

ClaimCertificatePrivateKey

The private key of the claim certificate. This is stored securely on the device for validating the connection endpoint with IoT managed integrations using the public key.

Type: String

Id

The identifier of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Name

The name of the provisioning template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: [0-9A-Za-z_-]+

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: FLEET_PROVISIONING | JITR

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCredentialLocker

Delete a credential locker.

Note

This operation can't be undone and any existing device won't be able to use IoT managed integrations.

Request Syntax

```
DELETE /credential-lockers/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the credential locker.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDestination

Deletes a customer-managed destination specified by id.

Request Syntax

```
DELETE /destinations/Name HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Name

The id of the customer-managed destination.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEventLogConfiguration

Delete an event log configuration.

Request Syntax

```
DELETE /event-log-configurations/Id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Id

The identifier of the event log configuration.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteManagedThing

Delete a managed thing. If a controller is deleted, all of the devices connected to it will have their status changed to PENDING. It is not possible to remove a cloud device.

Request Syntax

```
DELETE /managed-things/Identifier?Force=Force HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Force

When set to TRUE, a forceful deletion of the managed thing will occur. When set to FALSE, a non-forceful deletion of the managed thing will occur.

Identifier

The id of the managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteNotificationConfiguration

Deletes a notification configuration.

Request Syntax

```
DELETE /notification-configurations/EventType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

EventType

The type of event triggering a device notification to the customer-managed destination.

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST | DEVICE_EVENT | DEVICE_LIFE_CYCLE | DEVICE_STATE | DEVICE_OTA | CONNECTOR_ASSOCIATION | CONNECTOR_ERROR_REPORT

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOtaTask

Delete the over-the-air (OTA) task.

Request Syntax

```
DELETE /ota-tasks/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the over-the-air (OTA) task.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOtaTaskConfiguration

Delete the over-the-air (OTA) task configuration.

Request Syntax

```
DELETE /ota-task-configurations/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the over-the-air (OTA) task configuration.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteProvisioningProfile

Delete a provisioning profile.

Request Syntax

```
DELETE /provisioning-profiles/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The name of the provisioning template.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCredentialLocker

Get information on an existing credential locker

Request Syntax

```
GET /credential-lockers/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of the credential locker.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```
{  
  "Arn": "string",  
  "CreatedAt": number,  
  "Id": "string",  
  "Name": "string",  
  "Tags": {  
    "string" : "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the credential locker.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:credential-locker/[0-9a-zA-Z-]+`

CreatedAt

The timestamp value of when the credential locker request occurred.

Type: Timestamp

Id

The identifier of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Name

The name of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9- _]+`

Tags

A set of key/value pairs that are used to manage the credential locker.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCustomEndpoint

Returns the IoT managed integrations custom endpoint.

Request Syntax

```
GET /custom-endpoint HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "EndpointAddress": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[EndpointAddress](#)

The IoT managed integrations dedicated, custom endpoint for the device to route traffic through.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._@-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDefaultEncryptionConfiguration

Retrieves information about the default encryption configuration for the AWS account in the default or specified region. For more information, see [Key management](#) in the *AWS IoT SiteWise User Guide*.

Request Syntax

```
GET /configuration/account/encryption HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "configurationStatus": {
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configurationStatus

Provides the status of the default encryption configuration for an AWS account.

Type: [ConfigurationStatus](#) object

encryptionType

The type of encryption used for the encryption configuration.

Type: String

Valid Values: MANAGED_INTEGRATIONS_DEFAULT_ENCRYPTION | CUSTOMER_KEY_ENCRYPTION

kmsKeyArn

The Key Amazon Resource Name (ARN) of the AWS AWS KMS key used for AWS KMS encryption if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:aws:kms:[0-9a-zA-Z-]+:[0-9]+:key/[0-9a-zA-Z-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalFailureException

An unexpected error has occurred.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDestination

Gets a destination by ID.

Request Syntax

```
GET /destinations/Name HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Name

The name of the customer-managed destination.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CreatedAt": number,
  "DeliveryDestinationArn": "string",
  "DeliveryDestinationType": "string",
  "Description": "string",
  "Name": "string",
  "RoleArn": "string",
  "Tags": {
    "string" : "string"
  }
}
```

```
},  
  "UpdatedAt": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the destination creation request occurred.

Type: Timestamp

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z._-]+`

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-]+`

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

RoleArn

The Amazon Resource Name (ARN) of the delivery destination role.

Type: String

Tags

A set of key/value pairs that are used to manage the customer-managed destination.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

UpdatedAt

The timestamp value of when the destination update request occurred.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDeviceDiscovery

Get the current state of a device discovery.

Request Syntax

```
GET /device-discoveries/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the device discovery job request.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ConnectorAssociationId": "string",
  "ControllerId": "string",
  "DiscoveryType": "string",
  "FinishedAt": number,
  "Id": "string",
  "StartedAt": number,
  "Status": "string",
```

```
"Tags": {  
  "string" : "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the device discovery job request.

Type: String

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:device-discovery/[0-9a-zA-Z-]+`

ConnectorAssociationId

The ID tracking the current discovery process for one connector association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z-]+`

ControllerId

The id of the end-user's IoT hub.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

DiscoveryType

The discovery type supporting the type of device to be discovered in the device discovery job request.

Type: String

Valid Values: ZWAVE | ZIGBEE | CLOUD

FinishedAt

The timestamp value for the completion time of the device discovery.

Type: Timestamp

Id

The id of the device discovery job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

StartedAt

The timestamp value for the start time of the device discovery.

Type: Timestamp

Status

The status of the device discovery job request.

Type: String

Valid Values: RUNNING | SUCCEEDED | FAILED | TIMED_OUT

Tags

A set of key/value pairs that are used to manage the device discovery request.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEventLogConfiguration

Get an event log configuration.

Request Syntax

```
GET /event-log-configurations/Id HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Id

The identifier of the event log configuration.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "EventLogLevel": "string",
  "Id": "string",
  "ResourceId": "string",
  "ResourceType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventLogLevel

The logging level for the event log configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Id

The identifier of the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

ResourceId

The identifier of the resource for the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [a-zA-Z0-9+]*

ResourceType

The type of resource for the event log configuration.

Type: String

Pattern: [*]\$|^ (managed-thing|credential-locker|provisioning-profile|ota-task)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetHubConfiguration

Get a hub configuration.

Request Syntax

```
GET /hub-configuration HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "HubTokenTimerExpirySettingInSeconds": number,
  "UpdatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[HubTokenTimerExpirySettingInSeconds](#)

A user-defined integer value that represents the hub token timer expiry setting in seconds.

Type: Long

Valid Range: Minimum value of 1.

UpdatedAt

The timestamp value of when the hub configuration was updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetManagedThing

Get the attributes and capabilities associated with a managed thing.

Request Syntax

```
GET /managed-things/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9: _-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ActivatedAt": number,
  "AdvertisedProductId": "string",
  "Arn": "string",
  "Brand": "string",
  "Classification": "string",
  "ConnectorDeviceId": "string",
  "ConnectorPolicyId": "string",
  "CreatedAt": number,
```

```
"CredentialLockerId": "string",
"DeviceSpecificKey": "string",
"HubNetworkMode": "string",
"Id": "string",
"InternationalArticleNumber": "string",
"MacAddress": "string",
"MetaData": {
  "string" : "string"
},
"Model": "string",
"Name": "string",
"Owner": "string",
"ParentControllerId": "string",
"ProvisioningStatus": "string",
"Role": "string",
"SerialNumber": "string",
"Tags": {
  "string" : "string"
},
"UniversalProductCode": "string",
"UpdatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ActivatedAt

The timestamp value of when the device was activated.

Type: Timestamp

AdvertisedProductId

The id of the advertised product.

Type: String

Length Constraints: Fixed length of 5.

Pattern: ([A-Za-z0-9!#\$%&()*\+\-\;<=>?@^_`{|}~])+

Arn

The Amazon Resource Name (ARN) of the managed thing.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:managed-thing/([0-9a-zA-Z:_-])+`

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_]+`

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

ConnectorDeviceId

The third-party device id as defined by the connector. This device id must not contain personal identifiable information (PII).

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[a-zA-Z0-9_.,@-]+`

ConnectorPolicyId

The id of the connector policy.

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

CreatedAt

The timestamp value of when the device creation request occurred.

Type: Timestamp

CredentialLockerId

The identifier of the credential locker for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

DeviceSpecificKey

A Zwave device-specific key used during device activation.

Note

This parameter is used for Zwave devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9=_.\@+\-]+

HubNetworkMode

The network mode for the hub-connected device.

Type: String

Valid Values: STANDARD | NETWORK_WIDE_EXCLUSION

Id

The id of the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

InternationalArticleNumber

The unique 13 digit number that identifies the managed thing.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 13.

Pattern: [0-9]+

MacAddress

The media access control (MAC) address for the device represented by the managed thing.

Note

This parameter is used for Zigbee devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

MetaData

The metadata for the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: `.*[a-zA-Z0-9_.,@/:#-]+.*`

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: `.*[a-zA-Z0-9_.,@/:#-]*.*`

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9- _]+`

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} . _-]+`

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.,@-]+`

ParentControllerId

Id of the controller device used for the discovery job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9]+

ProvisioningStatus

The provisioning status of the device in the provisioning workflow for onboarding to IoT managed integrations.

Type: String

Valid Values: UNASSOCIATED | PRE_ASSOCIATED | DISCOVERED | ACTIVATED | DELETION_FAILED | DELETE_IN_PROGRESS | ISOLATED | DELETED

Role

The type of device used. This will be the AWS hub controller, cloud device, or AWS IoT device.

Type: String

Valid Values: CONTROLLER | DEVICE

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Tags

A set of key/value pairs that are used to manage the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

UniversalProductCode

The universal product code (UPC) of the device model. The UPC is typically used in the United States of America and Canada.

Type: String

Length Constraints: Fixed length of 12.

Pattern: [0-9]+

UpdatedAt

The timestamp value of when the managed thing was last updated at.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingCapabilities

Get the capabilities for a managed thing using the device ID.

Request Syntax

```
GET /managed-things-capabilities/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9: _-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Capabilities": "string",
  "CapabilityReport": {
    "endpoints": [
      {
        "capabilities": [
          {
            "actions": [ "string" ],
            "events": [ "string" ],
```



```
        "id": "string",
        "name": "string",
        "properties": [ "string" ],
        "version": "string"
    }
],
    "deviceTypes": [ "string" ],
    "id": "string"
}
],
    "nodeId": "string",
    "version": "string"
},
    "ManagedThingId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Capabilities

The capabilities of the device such as light bulb.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9\s'\x{0022}, . : \\ \\/ { \$ } \ [\] = _ \ - \ +] +

CapabilityReport

A report of the capabilities for the managed thing.

Type: [CapabilityReport](#) object

ManagedThingId

The id of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingConnectivityData

Get the connectivity status of a managed thing.

Request Syntax

```
POST /managed-things-connectivity-data/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The identifier of a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Connected": boolean,
  "DisconnectReason": "string",
  "ManagedThingId": "string",
  "Timestamp": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Connected

The connectivity status for a managed thing.

Type: Boolean

DisconnectReason

The reason for the connectivity disconnect with the managed thing.

Type: String

Valid Values: AUTH_ERROR | CLIENT_INITIATED_DISCONNECT | CLIENT_ERROR
| CONNECTION_LOST | DUPLICATE_CLIENTID | FORBIDDEN_ACCESS |
MQTT_KEEP_ALIVE_TIMEOUT | SERVER_ERROR | SERVER_INITIATED_DISCONNECT
| THROTTLED | WEBSOCKET_TTL_EXPIRATION | CUSTOMAUTH_TTL_EXPIRATION |
UNKNOWN | NONE

ManagedThingId

The id of a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Timestamp

The timestamp value of when the connectivity status for a managed thing was last taken.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingMetaData

Get the metadata information for a managed thing.

Note

The managedThing metadata parameter is used for associating attributes with a managedThing that can be used for grouping over-the-air (OTA) tasks. Name value pairs in metadata can be used in the OtaTargetQueryString parameter for the CreateOtaTask API operation.

Request Syntax

```
GET /managed-things-metadata/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The managed thing id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```



```
{
  "ManagedThingId": "string",
  "MetaData": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ManagedThingId

The managed thing id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

MetaData

The metadata for the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: .*[a-zA-Z0-9_.,@/:#-]+.*

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: .*[a-zA-Z0-9_.,@/:#-]*.*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetManagedThingState

Returns the managed thing state for the given device Id.

Request Syntax

```
GET /managed-thing-states/ManagedThingId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id of the device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Endpoints": [
    {
      "capabilities": [
        {
          "id": "string",
          "name": "string",
          "properties": JSON value,
          "version": "string"
        }
      ]
    }
  ]
}
```

```
    ],  
    "endpointId": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Endpoints

The device endpoint.

Type: Array of [StateEndpoint](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalFailureException

An unexpected error has occurred.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNotificationConfiguration

Get a notification configuration.

Request Syntax

```
GET /notification-configurations/EventType HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[EventType](#)

The type of event triggering a device notification to the customer-managed destination.

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST | DEVICE_EVENT | DEVICE_LIFE_CYCLE | DEVICE_STATE | DEVICE_OTA | CONNECTOR_ASSOCIATION | CONNECTOR_ERROR_REPORT

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CreatedAt": number,
  "DestinationName": "string",
  "EventType": "string",
  "Tags": {
    "string" : "string"
  },
  "UpdatedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the notification configuration was created.

Type: Timestamp

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

EventType

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: `DEVICE_COMMAND | DEVICE_COMMAND_REQUEST | DEVICE_EVENT | DEVICE_LIFE_CYCLE | DEVICE_STATE | DEVICE_OTA | CONNECTOR_ASSOCIATION | CONNECTOR_ERROR_REPORT`

Tags

A set of key/value pairs that are used to manage the notification configuration.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

UpdatedAt

The timestamp value of when the notification configuration was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOtaTask

Get the over-the-air (OTA) task.

Request Syntax

```
GET /ota-tasks/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CreatedAt": number,
  "Description": "string",
  "LastUpdatedAt": number,
  "OtaMechanism": "string",
  "OtaSchedulingConfig": {
    "EndBehavior": "string",
    "EndTime": "string",
```

```

    "MaintenanceWindows": [
      {
        "DurationInMinutes": number,
        "StartTime": "string"
      }
    ],
    "StartTime": "string"
  },
  "OtaTargetQueryString": "string",
  "OtaTaskExecutionRetryConfig": {
    "RetryConfigCriteria": [
      {
        "FailureType": "string",
        "MinNumberOfRetries": number
      }
    ]
  },
  "OtaType": "string",
  "Protocol": "string",
  "S3Url": "string",
  "Status": "string",
  "Target": [ "string" ],
  "TaskArn": "string",
  "TaskConfigurationId": "string",
  "TaskId": "string",
  "TaskProcessingDetails": {
    "NumberOfCanceledThings": number,
    "NumberOfFailedThings": number,
    "NumberOfInProgressThings": number,
    "numberOfQueuedThings": number,
    "numberOfRejectedThings": number,
    "numberOfRemovedThings": number,
    "numberOfSucceededThings": number,
    "numberOfTimedOutThings": number,
    "processingTargets": [ "string" ]
  }
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the over-the-air (OTA) task was created.

Type: Timestamp

Description

The description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-]+

LastUpdatedAt

The timestamp value of when the over-the-air (OTA) task was last updated at.

Type: Timestamp

OtaMechanism

The deployment mechanism for the over-the-air (OTA) task.

Type: String

Valid Values: PUSH

OtaSchedulingConfig

Over-the-air (OTA) task scheduling config.

Type: [OtaTaskSchedulingConfig](#) object

OtaTargetQueryString

The query string to add things to the thing group.

Type: String

OtaTaskExecutionRetryConfig

Over-the-air (OTA) task retry config.

Type: [OtaTaskExecutionRetryConfig](#) object

OtaType

The frequency type for the over-the-air (OTA) task.

Type: String

Valid Values: ONE_TIME | CONTINUOUS

Protocol

The connection protocol the over-the-air (OTA) task uses to update the device.

Type: String

Valid Values: HTTP

S3Url

The URL to the Amazon S3 bucket where the over-the-air (OTA) task is stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Status

The status of the over-the-air (OTA) task.

Type: String

Valid Values: IN_PROGRESS | CANCELED | COMPLETED | DELETION_IN_PROGRESS | SCHEDULED

Target

The device targeted for the over-the-air (OTA) task.

Type: Array of strings

TaskArn

The Amazon Resource Name (ARN) of the over-the-air (OTA) task

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:ota-task/[0-9a-zA-Z-]+`

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

TaskId

The id of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `[A-Za-z0-9]+`

TaskProcessingDetails

The processing details of all over-the-air (OTA) tasks.

Type: [TaskProcessingDetails](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOtaTaskConfiguration

Get a configuraiton for the over-the-air (OTA) task.

Request Syntax

```
GET /ota-task-configurations/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task configuration id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CreatedAt": number,
  "Description": "string",
  "Name": "string",
  "PushConfig": {
    "AbortConfig": {
      "AbortConfigCriteriaList": [
        {
          "Action": "string",
          "FailureType": "string",
```

```
        "MinNumberOfExecutedThings": number,
        "ThresholdPercentage": number
    }
]
},
"RolloutConfig": {
    "ExponentialRolloutRate": {
        "BaseRatePerMinute": number,
        "IncrementFactor": number,
        "RateIncreaseCriteria": {
            "numberOfNotifiedThings": number,
            "numberOfSucceededThings": number
        }
    },
    "MaximumPerMinute": number
},
"TimeoutConfig": {
    "InProgressTimeoutInMinutes": number
}
},
"TaskConfigurationId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CreatedAt

The timestamp value of when the over-the-air (OTA) task configuration was created at.

Type: Timestamp

Description

A description of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

Name

The name of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

PushConfig

Describes the type of configuration used for the over-the-air (OTA) task.

Type: [PushConfig](#) object

TaskConfigurationId

The over-the-air (OTA) task configuration id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetProvisioningProfile

Get a provisioning profile by template name.

Request Syntax

```
GET /provisioning-profiles/Identifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The provisioning template the device uses for the provisioning process.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ClaimCertificate": "string",
  "Id": "string",
  "Name": "string",
  "ProvisioningType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the provisioning template used in the provisioning profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 64.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:provisioning-profile/[0-9a-zA-Z-]+`

ClaimCertificate

The id of the claim certificate.

Type: String

Id

The provisioning profile id..

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9-_]+`

Name

The name of the provisioning template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[0-9A-Za-z_-]+`

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: FLEET_PROVISIONING | JITR

Tags

A set of key/value pairs that are used to manage the provisioning profile.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRuntimeLogConfiguration

Get the runtime log configuration for a specific managed thing or for all managed things as a group.

Request Syntax

```
GET /runtime-log-configurations/ManagedThingId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ManagedThingId": "string",
  "RuntimeLogConfigurations": {
    "DeleteLocalStoreAfterUpload": boolean,
    "LocalStoreFileRotationMaxBytes": number,
    "LocalStoreFileRotationMaxFiles": number,
    "LocalStoreLocation": "string",
    "LogFlushLevel": "string",
```

```
"LogLevel": "string",  
"UploadLog": boolean,  
"UploadPeriodMinutes": number  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ManagedThingId

The id for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

RuntimeLogConfigurations

The runtime log configuration for a managed thing.

Type: [RuntimeLogConfigurations](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSchemaVersion

Gets a schema version with the provided information.

Request Syntax

```
GET /schema-versions/Type/SchemaVersionedId?Format=Format HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Format

The format of the schema version.

Valid Values: AWS | ZCL | CONNECTOR

SchemaVersionedId

Schema id with a version specified. If the version is missing, it defaults to latest version.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9.\-\/]+(@(\d+\.\d+|\$latest))?`

Required: Yes

Type

The type of schema version.

Valid Values: capability | definition

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "Description": "string",
  "Namespace": "string",
  "Schema": JSON value,
  "SchemaId": "string",
  "SemanticVersion": "string",
  "Type": "string",
  "Visibility": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Description

The description of the schema version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9.,]+

Namespace

The name of the schema version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-z]+

Schema

The schema of the schema version.

Type: JSON value

SchemaId

The id of the schema version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9./]+

SemanticVersion

The schema version. If this is left blank, it defaults to the latest version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: (\d+\.\d+|\\$latest)

Type

The type of schema version.

Type: String

Valid Values: capability | definition

Visibility

The visibility of the schema version.

Type: String

Valid Values: PUBLIC | PRIVATE

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCredentialLockers

List information on an existing credential locker.

Request Syntax

```
GET /credential-lockers?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "Arn": "string",
      "CreatedAt": number,
```

```
    "Id": "string",  
    "Name": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of credential lockers.

Type: Array of [CredentialLockerSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDestinations

List all destination names under one AWS account.

Request Syntax

```
GET /destinations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DestinationList": [
    {
      "DeliveryDestinationArn": "string",
      "DeliveryDestinationType": "string",
      "Description": "string",
```

```
    "Name": "string",  
    "RoleArn": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DestinationList

The list of destinations.

Type: Array of [DestinationSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEventLogConfigurations

List all event log configurations for an account.

Request Syntax

```
GET /event-log-configurations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "EventLogConfigurationList": [
    {
      "EventLogLevel": "string",
      "Id": "string",
```

```
    "ResourceId": "string",
    "ResourceType": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventLogConfigurationList

A list of each event log configuration and pertinent information.

Type: Array of [EventLogConfigurationSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListManagedThings

Listing all managed things with provision for filters.

Request Syntax

```
GET /managed-things?  
ConnectorPolicyIdFilter=ConnectorPolicyIdFilter&CredentialLockerFilter=CredentialLockerFilter&M  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ConnectorPolicyIdFilter

Filter on a connector policy id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9-_]+

CredentialLockerFilter

Filter on a credential locker for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=-_]+

OwnerFilter

Filter on device owners when listing managed things.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9_.,@-]+

ParentControllerIdentifierFilter

Filter on a parent controller id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9]+

ProvisioningStatusFilter

Filter on the status of the device.

Valid Values: UNASSOCIATED | PRE_ASSOCIATED | DISCOVERED | ACTIVATED | DELETION_FAILED | DELETE_IN_PROGRESS | ISOLATED | DELETED

RoleFilter

Filter on the type of device used. This will be the AWS hub controller, cloud device, or AWS IoT device.

Valid Values: CONTROLLER | DEVICE

SerialNumberFilter

Filter on the serial number of the device.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Items": [
    {
      "ActivatedAt": number,
      "AdvertisedProductId": "string",
      "Arn": "string",
      "Brand": "string",
      "Classification": "string",
      "ConnectorDeviceId": "string",
      "ConnectorPolicyId": "string",
      "CreatedAt": number,
      "CredentialLockerId": "string",
      "Id": "string",
      "Model": "string",
      "Name": "string",
      "Owner": "string",
      "ParentControllerId": "string",
      "ProvisioningStatus": "string",
      "Role": "string",
      "SerialNumber": "string",
      "UpdatedAt": number
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of managed things.

Type: Array of [ManagedThingSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListManagedThingSchemas

List schemas associated with a managed thing.

Request Syntax

```
GET /managed-thing-schemas/Identifier?  
CapabilityIdFilter=CapabilityIdFilter&EndpointIdFilter=EndpointIdFilter&MaxResults=MaxResults&N  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

CapabilityIdFilter

Filter on a capability id.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9./]+(@\d+\. \d+)?`

EndpointIdFilter

Filter on an endpoint id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Identifier

The managed thing id.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9:_-]*`

Required: Yes

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "CapabilityId": "string",
      "EndpointId": "string",
      "Schema": JSON value
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of managed thing schemas.

Type: Array of [ManagedThingSchemaListItem](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNotificationConfigurations

List all notification configurations.

Request Syntax

```
GET /notification-configurations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "NotificationConfigurationList": [
    {
      "DestinationName": "string",
```

```
    "EventType": "string"  
  }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

NotificationConfigurationList

The list of notification configurations.

Type: Array of [NotificationConfigurationSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOtaTaskConfigurations

List all of the over-the-air (OTA) task configurations.

Request Syntax

```
GET /ota-task-configurations?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: `[a-zA-Z0-9=_-]+`

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "CreatedAt": number,
      "Name": "string",
      "TaskConfigurationId": "string"
    }
  ]
}
```

```
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of the over-the-air (OTA) task configurations.

Type: Array of [OtaTaskConfigurationSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOtaTaskExecutions

List all of the over-the-air (OTA) task executions.

Request Syntax

```
GET /ota-tasks/Identifier/devices?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "ExecutionSummaries": [
    {
      "ManagedThingId": "string",
      "TaskExecutionSummary": {
        "ExecutionNumber": number,
        "LastUpdatedAt": number,
        "QueuedAt": number,
        "RetryAttempt": number,
        "StartedAt": number,
        "Status": "string"
      }
    }
  ],
  "NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExecutionSummaries

A list of all of the over-the-air (OTA) task executions.

Type: Array of [OtaTaskExecutionSummaries](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOtaTasks

List all of the over-the-air (OTA) tasks.

Request Syntax

```
GET /ota-tasks?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "NextToken": "string",
  "Tasks": [
    {
      "CreatedAt": number,
      "LastUpdatedAt": number,

```

```
    "Status": "string",
    "TaskArn": "string",
    "TaskConfigurationId": "string",
    "TaskId": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_+/-]+

Tasks

A list of all of the over-the-air (OTA) tasks.

Type: Array of [OtaTaskSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListProvisioningProfiles

List the provisioning profiles within the AWS account.

Request Syntax

```
GET /provisioning-profiles?MaxResults=MaxResults&NextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "Arn": "string",
      "Id": "string",
```



```
    "Name": "string",  
    "ProvisioningType": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of provisioning profiles.

Type: Array of [ProvisioningProfileSummary](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSchemaVersions

Lists schema versions with the provided information.

Request Syntax

```
GET /schema-versions/Type?  
MaxResults=MaxResults&NamespaceFilter=Namespace&NextToken=NextToken&SchemaIdFilter=SchemaId&Sem  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return at one time.

Valid Range: Minimum value of 1. Maximum value of 1000.

Namespace

Filter on the name of the schema version.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-z]+

NextToken

A token that can be used to retrieve the next set of results.

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

SchemaId

Filter on the id of the schema version.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9./]+

SemanticVersion

The schema version. If this is left blank, it defaults to the latest version.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: (\d+\.\d+|\\$latest)

Type

Filter on the type of schema version.

Valid Values: capability | definition

Required: Yes

Visibility

The visibility of the schema version.

Valid Values: PUBLIC | PRIVATE

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "Description": "string",
      "Namespace": "string",
      "SchemaId": "string",
      "SemanticVersion": "string",
      "Type": "string",
      "Visibility": "string"
    }
  ],
  "NextToken": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The list of schema versions.

Type: Array of [SchemaVersionListItem](#) objects

NextToken

A token that can be used to retrieve the next set of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9=_-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutDefaultEncryptionConfiguration

Sets the default encryption configuration for the AWS account. For more information, see [Key management](#) in the AWS IoT SiteWise User Guide.

Request Syntax

```
POST /configuration/account/encryption HTTP/1.1
Content-type: application/json

{
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[encryptionType](#)

The type of encryption used for the encryption configuration.

Type: String

Valid Values: MANAGED_INTEGRATIONS_DEFAULT_ENCRYPTION | CUSTOMER_KEY_ENCRYPTION

Required: Yes

[kmsKeyArn](#)

The Key Amazon Resource Name (ARN) of the AWS KMS key used for AWS KMS encryption if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:aws:kms:[0-9a-zA-Z-]+:[0-9]+:key/[0-9a-zA-Z-]+

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "configurationStatus": {
    "error": {
      "code": "string",
      "message": "string"
    },
    "state": "string"
  },
  "encryptionType": "string",
  "kmsKeyArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

configurationStatus

Provides the status of the default encryption configuration for an AWS account.

Type: [ConfigurationStatus](#) object

encryptionType

The type of encryption used for the encryption configuration.

Type: String

Valid Values: MANAGED_INTEGRATIONS_DEFAULT_ENCRYPTION |
CUSTOMER_KEY_ENCRYPTION

kmsKeyArn

The Key Amazon Resource Name (ARN) of the AWS KMS key used for AWS KMS encryption if you use KMS_BASED_ENCRYPTION.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: arn:aws:kms:[0-9a-zA-Z-]+:[0-9]+:key/[0-9a-zA-Z-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalFailureException

An unexpected error has occurred.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutHubConfiguration

Update a hub configuration.

Request Syntax

```
PUT /hub-configuration HTTP/1.1
Content-type: application/json

{
  "HubTokenTimerExpirySettingInSeconds": number
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[HubTokenTimerExpirySettingInSeconds](#)

A user-defined integer value that represents the hub token timer expiry setting in seconds.

Type: Long

Valid Range: Minimum value of 1.

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "HubTokenTimerExpirySettingInSeconds": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

HubTokenTimerExpirySettingInSeconds

A user-defined integer value that represents the hub token timer expiry setting in seconds.

Type: Long

Valid Range: Minimum value of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutRuntimeLogConfiguration

Set the runtime log configuration for a specific managed thing or for all managed things as a group.

Request Syntax

```
PUT /runtime-log-configurations/ManagedThingId HTTP/1.1
Content-type: application/json
```

```
{
  "RuntimeLogConfigurations": {
    "DeleteLocalStoreAfterUpload": boolean,
    "LocalStoreFileRotationMaxBytes": number,
    "LocalStoreFileRotationMaxFiles": number,
    "LocalStoreLocation": "string",
    "LogFlushLevel": "string",
    "LogLevel": "string",
    "UploadLog": boolean,
    "UploadPeriodMinutes": number
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id for a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9: _-]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

RuntimeLogConfigurations

The runtime log configuration for a managed thing.

Type: [RuntimeLogConfigurations](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterCustomEndpoint

Customers can request IoT managed integrations to manage the server trust for them or bring their own external server trusts for the custom domain. Returns an IoT managed integrations endpoint.

Request Syntax

```
POST /custom-endpoint HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "EndpointAddress": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[EndpointAddress](#)

The IoT managed integrations dedicated, custom endpoint for the device to route traffic through.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [A-Za-z0-9._@-]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResetRuntimeLogConfiguration

Reset a runtime log configuration for a specific managed thing or for all managed things as a group.

Request Syntax

```
DELETE /runtime-log-configurations/ManagedThingId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id of a managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SendManagedThingCommand

Send the command to the device represented by the managed thing.

Request Syntax

```
POST /managed-things-command/ManagedThingId HTTP/1.1  
Content-type: application/json
```

```
{  
  "ConnectorAssociationId": "string",  
  "Endpoints": [  
    {  
      "capabilities": [  
        {  
          "actions": [  
            {  
              "actionTraceId": "string",  
              "name": "string",  
              "parameters": JSON value,  
              "ref": "string"  
            }  
          ],  
          "id": "string",  
          "name": "string",  
          "version": "string"  
        }  
      ],  
      "endpointId": "string"  
    }  
  ]  
}
```

URI Request Parameters

The request uses the following URI parameters.

ManagedThingId

The id of the device.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: Yes

Request Body

The request accepts the following data in JSON format.

ConnectorAssociationId

The ID tracking the current discovery process for one connector association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: No

Endpoints

The device endpoint.

Type: Array of [CommandEndpoint](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

Response Syntax

```
HTTP/1.1 202
Content-type: application/json

{
  "TraceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response.

The following data is returned in JSON format by the service.

TraceId

The trace request identifier. This is specified by the device owner, but will be generated by IoT managed integrations if not provided by the device owner.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9:=-_]+

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartDeviceDiscovery

During user-guided setup, this is used to start device discovery. The authentication material (install code) is passed as a message to the controller telling it to start the discovery.

Request Syntax

```
POST /device-discoveries HTTP/1.1
Content-type: application/json

{
  "AuthenticationMaterial": "string",
  "AuthenticationMaterialType": "string",
  "ClientToken": "string",
  "ConnectorAssociationIdentifier": "string",
  "ControllerIdentifier": "string",
  "DiscoveryType": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AuthenticationMaterial

The authentication material required to start the local device discovery job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9A-Za-z_-\+=\/:;]+

Required: No

AuthenticationMaterialType

The type of authentication material used for device discovery jobs.

Type: String

Valid Values: ZWAVE_INSTALL_CODE

Required: No

ClientToken

An idempotency token. If you retry a request that completed successfully initially using the same client token and parameters, then the retry attempt will succeed without performing any further actions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_-]+

Required: No

ConnectorAssociationIdentifier

The id of the connector association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [0-9a-zA-Z]+

Required: No

ControllerIdentifier

The id of the end-user's IoT hub.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: No

DiscoveryType

The discovery type supporting the type of device to be discovered in the device discovery job request.

Type: String

Valid Values: ZWAVE | ZIGBEE | CLOUD

Required: Yes

Tags

A set of key/value pairs that are used to manage the device discovery request.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Id": "string",
  "StartedAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Id

The id of the device discovery job request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

StartedAt

The timestamp value for the start time of the device discovery.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDestination

Update a destination specified by id.

Request Syntax

```
PUT /destinations/Name HTTP/1.1
Content-type: application/json

{
  "DeliveryDestinationArn": "string",
  "DeliveryDestinationType": "string",
  "Description": "string",
  "RoleArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Name

The name of the customer-managed destination.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: Yes

Request Body

The request accepts the following data in JSON format.

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z._-]+`

Required: No

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Required: No

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-\]+`

Required: No

RoleArn

The Amazon Resource Name (ARN) of the delivery destination role.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 201
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerErrorException

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEventLogConfiguration

Update an event log configuration by log configuration ID.

Request Syntax

```
PATCH /event-log-configurations/Id HTTP/1.1
Content-type: application/json

{
  "EventLogLevel": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Id

The log configuration id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

EventLogLevel

The log level for the event in terms of severity.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateManagedThing

Update the attributes and capabilities associated with a managed thing.

Request Syntax

```
PUT /managed-things/Identifier HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "Brand": "string",
  "Capabilities": "string",
  "CapabilityReport": {
    "endpoints": [
      {
        "capabilities": [
          {
            "actions": [ "string" ],
            "events": [ "string" ],
            "id": "string",
            "name": "string",
            "properties": [ "string" ],
            "version": "string"
          }
        ],
        "deviceTypes": [ "string" ],
        "id": "string"
      }
    ],
    "nodeId": "string",
    "version": "string"
  },
  "Classification": "string",
  "CredentialLockerId": "string",
  "HubNetworkMode": "string",
  "MetaData": {
    "string" : "string"
  },
  "Model": "string",
  "Name": "string",
  "Owner": "string",
  "SerialNumber": "string"
}
```



```
}
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The id of the managed thing.

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9: _-]*`

Required: Yes

Request Body

The request accepts the following data in JSON format.

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_]+`

Required: No

Capabilities

The capabilities of the device such as light bulb.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: `[a-zA-Z0-9\s'\x{0022}, . : \\ \\/ { $ } \ [\] = _ \ - \ +] +`

Required: No

CapabilityReport

A report of the capabilities for the managed thing.

Type: [CapabilityReport](#) object

Required: No

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

CredentialLockerId

The identifier of the credential for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

HubNetworkMode

The network mode for the hub-connected device.

Type: String

Valid Values: STANDARD | NETWORK_WIDE_EXCLUSION

Required: No

MetaData

The metadata for the managed thing.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 0. Maximum length of 128.

Key Pattern: `.*[a-zA-Z0-9_.,@/:#-]+.*`

Value Length Constraints: Minimum length of 0. Maximum length of 800.

Value Pattern: `.*[a-zA-Z0-9_.,@/:#-]*.*`

Required: No

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[A-Za-z0-9-_]+`

Required: No

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: No

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.,@-]+`

Required: No

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

ConflictException

There is a conflict with the request.

HTTP Status Code: 409

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

UnauthorizedException

You are not authorized to perform this operation.

HTTP Status Code: 401

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNotificationConfiguration

Update a notification configuration.

Request Syntax

```
PUT /notification-configurations/EventType HTTP/1.1
Content-type: application/json

{
  "DestinationName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

EventType

The type of event triggering a device notification to the customer-managed destination.

Valid Values: DEVICE_COMMAND | DEVICE_COMMAND_REQUEST | DEVICE_EVENT | DEVICE_LIFE_CYCLE | DEVICE_STATE | DEVICE_OTA | CONNECTOR_ASSOCIATION | CONNECTOR_ERROR_REPORT

Required: Yes

Request Body

The request accepts the following data in JSON format.

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: Yes

Response Syntax

```
HTTP/1.1 201
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateOtaTask

Update an over-the-air (OTA) task.

Request Syntax

```
PUT /ota-tasks/Identifier HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "TaskConfigurationId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

Identifier

The over-the-air (OTA) task id.

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9A-Za-z_\-\]+

Required: No

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

User is not authorized.

HTTP Status Code: 403

InternalServerError

Internal error from the service that indicates an unexpected error or that the service is unavailable.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource does not exist.

HTTP Status Code: 404

ThrottlingException

The rate exceeds the limit.

HTTP Status Code: 429

ValidationException

A validation error occurred when performing the API request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Managed integrations for AWS IoT Device Management API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AbortConfigCriteria](#)
- [CapabilityAction](#)
- [CapabilityReport](#)
- [CapabilityReportCapability](#)
- [CapabilityReportEndpoint](#)
- [CommandCapability](#)
- [CommandEndpoint](#)
- [ConfigurationError](#)
- [ConfigurationStatus](#)
- [CredentialLockerSummary](#)
- [DestinationSummary](#)
- [EventLogConfigurationSummary](#)
- [ExponentialRolloutRate](#)
- [ManagedThingSchemaListItem](#)
- [ManagedThingSummary](#)
- [NotificationConfigurationSummary](#)
- [OtaTaskAbortConfig](#)
- [OtaTaskConfigurationSummary](#)
- [OtaTaskExecutionRetryConfig](#)
- [OtaTaskExecutionRolloutConfig](#)

- [OtaTaskExecutionSummaries](#)
- [OtaTaskExecutionSummary](#)
- [OtaTaskSchedulingConfig](#)
- [OtaTaskSummary](#)
- [OtaTaskTimeoutConfig](#)
- [ProvisioningProfileSummary](#)
- [PushConfig](#)
- [RetryConfigCriteria](#)
- [RolloutRateIncreaseCriteria](#)
- [RuntimeLogConfigurations](#)
- [ScheduleMaintenanceWindow](#)
- [SchemaVersionListItem](#)
- [StateCapability](#)
- [StateEndpoint](#)
- [TaskProcessingDetails](#)

AbortConfigCriteria

Structure representing one abort config criteria.

Contents

Action

The action taken by the abort configuration.

Type: String

Valid Values: CANCEL

Required: No

FailureType

Over-the-air (OTA) task abort criteria failure type.

Type: String

Valid Values: FAILED | REJECTED | TIMED_OUT | ALL

Required: No

MinNumberOfExecutedThings

The minimum number of things that must receive task execution notifications before the task can be aborted.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

ThresholdPercentage

The minimum percentage of over-the-air (OTA) task execution failures that must occur to initiate the last abort.

Type: Double

Valid Range: Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityAction

Action for an AWS capability, containing the action parameters for control.

Contents

name

Describe a capability action with a name.

Type: String

Pattern: [/a-zA-Z]+

Required: Yes

actionTraceId

Describe a capability action with an `actionTraceId` for a response command.

Type: String

Length Constraints: Minimum length of 16. Maximum length of 20.

Pattern: [a-zA-Z0-9]+(?:_[0-9]+)?

Required: No

parameters

Describe a capability action with a capability property.

Type: JSON value

Required: No

ref

Describe a capability action with an reference.

Type: String

Pattern: [a-zA-Z.]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityReport

Report of all capabilities supported by the device.

Contents

endpoints

The endpoints used in the capability report.

Type: Array of [CapabilityReportEndpoint](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

version

The version of the capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10.

Pattern: 1\.\0\.\0

Required: Yes

nodeId

The numeric identifier of the node.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9=_.,@+\-/+]

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityReportCapability

The capability used in capability report.

Contents

actions

The capability actions used in the capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._]+`

Required: Yes

events

The capability events used in the capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._]+`

Required: Yes

id

The id of the schema version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9.\v/]+(@(\d+\.\d+|\$latest))?`

Required: Yes

name

The name of the capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._]+`

Required: Yes

properties

The capability properties used in the capability report.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._]+`

Required: Yes

version

The version of the capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `(0|[1-9][0-9]*)`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapabilityReportEndpoint

The endpoint used in the capability report.

Contents

capabilities

The capabilities used in the capability report.

Type: Array of [CapabilityReportCapability](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

deviceTypes

The type of device.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `[a-zA-Z0-9=_.,@+\-/+]`

Required: Yes

id

The id of the endpoint used in the capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommandCapability

The command capabilities added for the managed thing

Contents

actions

Describe the command capability with the actions it supports.

Type: Array of [CapabilityAction](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

id

Describe the capability with an id.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9.\v/]+(@(\d+\.\d+|\$latest))?`

Required: Yes

name

Describe the capability with an name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._]+`

Required: Yes

version

Describe the capability with a version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: (\emptyset | [1-9][0-9]*)

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CommandEndpoint

The endpoint for a managed thing when sending a command.

Contents

capabilities

Describe the endpoint with an id, a name, and the relevant capabilities for sending commands.

Type: Array of [CommandCapability](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

endpointId

The id of the endpoint for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConfigurationError

Provides the default encryption configuration error update details.

Contents

code

The error code returned when the default encryption configuration update fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

message

The error message returned when the default encryption configuration update fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 65535.

Pattern: [a-zA-Z0-9\-._,]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ConfigurationStatus

Provides the status of the default encryption configuration for an AWS account.

Contents

state

The status state describing the default encryption configuration update.

Type: String

Valid Values: ENABLED | UPDATE_IN_PROGRESS | UPDATE_FAILED

Required: Yes

error

The error details describing a failed default encryption configuration update.

Type: [ConfigurationError](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CredentialLockerSummary

Structure describing one Credential Locker.

Contents

Arn

The Amazon Resource Name (ARN) of the credential locker.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:credential-locker/[0-9a-zA-Z-]+`

Required: No

CreatedAt

The timestamp value of when the credential locker was created at.

Type: Timestamp

Required: No

Id

The id of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9]*`

Required: No

Name

The name of the credential locker.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DestinationSummary

Structure describing a destination for IoT managed integrations to deliver notifications for a device.

Contents

DeliveryDestinationArn

The Amazon Resource Name (ARN) of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:aws:[0-9a-zA-Z]+:[0-9a-zA-Z-]+:[0-9]+:[0-9a-zA-Z]+/[0-9a-zA-Z._-]+`

Required: No

DeliveryDestinationType

The destination type for the customer-managed destination.

Type: String

Valid Values: KINESIS

Required: No

Description

The description of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[0-9A-Za-z_\-\]+`

Required: No

Name

The name of the customer-managed destination.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: No

RoleArn

The Amazon Resource Name (ARN) of the delivery destination.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventLogConfigurationSummary

List of event log configurations.

Contents

EventLogLevel

The logging level for the event log configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: No

Id

The identifier of the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: No

ResourceId

The identifier of the resource for the event log configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [a-zA-Z0-9+]*

Required: No

ResourceType

The type of resource for the event log configuration.

Type: String

Pattern: [*]\$|^^(managed-thing|credential-locker|provisioning-profile|ota-task)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExponentialRolloutRate

Structure representing exponential rate of rollout for an over-the-air (OTA) task.

Contents

BaseRatePerMinute

The base rate per minute for the rollout of an over-the-air (OTA) task.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

IncrementFactor

The incremental factor for increasing the rollout rate of an over-the-air (OTA) task.

Type: Double

Valid Range: Minimum value of 1.1. Maximum value of 5.

Required: No

RateIncreaseCriteria

The criteria for increasing the rollout rate of an over-the-air (OTA) task.

Type: [RolloutRateIncreaseCriteria](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedThingSchemaListItem

Structure representing one schema item associated with a managed thing.

Contents

CapabilityId

The id of the capability for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9./]+(@\d+\. \d+)?`

Required: No

EndpointId

The id of the endpoint for a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: No

Schema

The validation schema for one schema item associated with a managed thing.

Type: JSON value

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ManagedThingSummary

Structure representing one managed thing.

Contents

ActivatedAt

The timestamp value of when the managed thing was activated at.

Type: Timestamp

Required: No

AdvertisedProductId

The id of the advertised product.

Type: String

Length Constraints: Fixed length of 5.

Pattern: (`[A-Za-z0-9!#$%&()*\+\-; <=>?@^_`{|}~]`)+

Required: No

Arn

The Amazon Resource Name (ARN) of the managed thing.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:managed-thing/([0-9a-zA-Z:_-])+`

Required: No

Brand

The brand of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

Classification

The classification of the managed thing such as light bulb or thermostat.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

ConnectorDeviceId

The third-party device id as defined by the connector. This device id must not contain personal identifiable information (PII).

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_.,@-]+

Required: No

ConnectorPolicyId

The id of the connector policy.

Note

This parameter is used for cloud-to-cloud devices only.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [A-Za-z0-9- _]+

Required: No

CreatedAt

The timestamp value of when the device creation request occurred.

Type: Timestamp

Required: No

CredentialLockerId

The identifier of the credential locker for the managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

Id

The id of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9: _-]*

Required: No

Model

The model of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

Name

The name of the managed thing representing the physical device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: No

Owner

Owner of the device, usually an indication of whom the device belongs to. This value should not contain personal identifiable information.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[a-zA-Z0-9_.,@-]+`

Required: No

ParentControllerId

Id of the controller device used for the discovery job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9]+`

Required: No

ProvisioningStatus

The provisioning status of the device in the provisioning workflow for onboarding to IoT managed integrations.

Type: String

Valid Values: UNASSOCIATED | PRE_ASSOCIATED | DISCOVERED | ACTIVATED | DELETION_FAILED | DELETE_IN_PROGRESS | ISOLATED | DELETED

Required: No

Role

The type of device used. This will be the AWS hub controller, cloud device, or AWS IoT device.

Type: String

Valid Values: CONTROLLER | DEVICE

Required: No

SerialNumber

The serial number of the device.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9-_]+

Required: No

UpdatedAt

The timestamp value of when the managed thing was last updated at.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NotificationConfigurationSummary

Structure describing a notification configuration.

Contents

DestinationName

The name of the destination for the notification configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\p{L}\p{N} ._-]+`

Required: No

EventType

The type of event triggering a device notification to the customer-managed destination.

Type: String

Valid Values: `DEVICE_COMMAND | DEVICE_COMMAND_REQUEST | DEVICE_EVENT | DEVICE_LIFE_CYCLE | DEVICE_STATE | DEVICE_OTA | CONNECTOR_ASSOCIATION | CONNECTOR_ERROR_REPORT`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskAbortConfig

Over-the-air (OTA) task abort config.

Contents

AbortConfigCriteriaList

The list of criteria for the abort config.

Type: Array of [AbortConfigCriteria](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskConfigurationSummary

Structure representing one over-the-air (OTA) task configuration.

Contents

CreatedAt

The timestamp value of when the over-the-air (OTA) task configuration was created at.

Type: Timestamp

Required: No

Name

The name of the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [A-Za-z0-9- _]+

Required: No

TaskConfigurationId

The id of the over-the-air (OTA) task configuration

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionRetryConfig

Over-the-air (OTA) task retry config.

Contents

RetryConfigCriteria

The list of retry config criteria.

Type: Array of [RetryConfigCriteria](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionRolloutConfig

Over-the-air (OTA) task rollout config.

Contents

ExponentialRolloutRate

Structure representing exponential rate of rollout for an over-the-air (OTA) task.

Type: [ExponentialRolloutRate](#) object

Required: No

MaximumPerMinute

The maximum number of things that will be notified of a pending task, per minute.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionSummaries

Structure representing one execution summary.

Contents

ManagedThingId

The id of a managed thing.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9:_-]*

Required: No

TaskExecutionSummary

Structure representing one over-the-air (OTA) task execution summary

Type: [OtaTaskExecutionSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskExecutionSummary

Structure representing one over-the-air (OTA) task execution summary.

Contents

ExecutionNumber

The execution number of the over-the-air (OTA) task execution summary.

Type: Long

Required: No

LastUpdatedAt

The timestamp value of when the over-the-air (OTA) task execution summary was last updated.

Type: Timestamp

Required: No

QueuedAt

The timestamp value of when the over-the-air (OTA) task execution summary is targeted to start.

Type: Timestamp

Required: No

RetryAttempt

The number of retry attempts for starting the over-the-air (OTA) task execution summary after a failed attempt.

Type: Integer

Required: No

StartedAt

The timestamp value of when the over-the-air (OTA) task execution summary started.

Type: Timestamp

Required: No

Status

The status of the over-the-air (OTA) task execution summary.

Type: String

Valid Values: QUEUED | IN_PROGRESS | SUCCEEDED | FAILED | TIMED_OUT | REJECTED | REMOVED | CANCELED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskSchedulingConfig

Over-the-air (OTA) task scheduling config.

Contents

EndBehavior

Specifies the end behavior for all task executions after a task reaches the selected `endTime`. If `endTime` is not selected when creating the task, then `endBehavior` does not apply.

Type: String

Valid Values: STOP_ROLLOUT | CANCEL | FORCE_CANCEL

Required: No

EndTime

The time an over-the-air (OTA) task will stop.

Type: String

Required: No

MaintenanceWindows

Maintenance window list for over-the-air (OTA) task scheduling config.

Type: Array of [ScheduleMaintenanceWindow](#) objects

Required: No

StartTime

The time an over-the-air (OTA) task will start.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskSummary

Structure representing one over-the-air (OTA) task.

Contents

CreatedAt

The timestamp value of when the over-the-air (OTA) task was created at.

Type: Timestamp

Required: No

LastUpdatedAt

The timestamp value of when the over-the-air (OTA) task was last updated at.

Type: Timestamp

Required: No

Status

The status of the over-the-air (OTA) task summary.

Type: String

Valid Values: IN_PROGRESS | CANCELED | COMPLETED | DELETION_IN_PROGRESS | SCHEDULED

Required: No

TaskArn

The Amazon Resource Name (ARN) of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1011.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:ota-task/[0-9a-zA-Z-]+`

Required: No

TaskConfigurationId

The identifier for the over-the-air (OTA) task configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: [a-zA-Z0-9]*

Required: No

TaskId

The id of the over-the-air (OTA) task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: [A-Za-z0-9]+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OtaTaskTimeoutConfig

Over-the-air (OTA) task timeout config.

Contents

InProgressTimeoutInMinutes

Specifies the amount of time the device has to finish execution of this task. The timeout interval can be anywhere between 1 minute and 7 days.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 10080.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ProvisioningProfileSummary

Structure describing a provisioning profile.

Contents

Arn

The Amazon Resource Name (ARN) of the provisioning template used in the provisioning profile.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 64.

Pattern: `arn:aws:iotmanagedintegrations:[0-9a-zA-Z-]+:[0-9]+:provisioning-profile/[0-9a-zA-Z-]+`

Required: No

Id

The identifier of the provisioning profile.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z0-9-_]+`

Required: No

Name

The name of the provisioning template.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[0-9A-Za-z_-]+`

Required: No

ProvisioningType

The type of provisioning workflow the device uses for onboarding to IoT managed integrations.

Type: String

Valid Values: FLEET_PROVISIONING | JITR

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PushConfig

Structure representing a push config.

Contents

AbortConfig

Structure representing one abort config.

Type: [OtaTaskAbortConfig](#) object

Required: No

RolloutConfig

Structure representing one rollout config.

Type: [OtaTaskExecutionRolloutConfig](#) object

Required: No

TimeoutConfig

Structure representing one timeout config.

Type: [OtaTaskTimeoutConfig](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RetryConfigCriteria

Structure representing one retry config criteria.

Contents

FailureType

Over-the-air (OTA) retry criteria failure type.

Type: String

Valid Values: FAILED | TIMED_OUT | ALL

Required: No

MinNumberOfRetries

The number of retries allowed for a failure type for the over-the-air (OTA) task.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RolloutRateIncreaseCriteria

Structure representing rollout config criteria.

Contents

numberOfNotifiedThings

The threshold for number of notified things that will initiate the increase in rate of rollout.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

numberOfSucceededThings

The threshold for number of succeeded things that will initiate the increase in rate of rollout.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuntimeLogConfigurations

The different configurations for runtime logs.

Contents

DeleteLocalStoreAfterUpload

Configuration to enable or disable deleting of runtime logs in the device once uploaded to the cloud.

Type: Boolean

Required: No

LocalStoreFileRotationMaxBytes

Configuration to set the maximum bytes of runtime logs that can be stored on the device before the oldest logs are deleted or overwritten.

Type: Integer

Required: No

LocalStoreFileRotationMaxFiles

Configuration to set the maximum number of runtime log files that can be stored on the device before the oldest files are deleted or overwritten.

Type: Integer

Required: No

LocalStoreLocation

Configuration of where to store runtime logs in the device.

Type: String

Required: No

LogFlushLevel

The different log levels available for configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: No

LogLevel

The different log levels available for configuration.

Type: String

Valid Values: DEBUG | ERROR | INFO | WARN

Required: No

UploadLog

Configuration to enable or disable uploading of runtime logs to the cloud.

Type: Boolean

Required: No

UploadPeriodMinutes

Configuration to set the time interval in minutes between each batch of runtime logs that the device uploads to the cloud.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScheduleMaintenanceWindow

Structure representing scheduling maintenance window.

Contents

DurationInMinutes

Displays the duration of the next maintenance window.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1430.

Required: No

StartTime

Displays the start time of the next maintenance window.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SchemaVersionListItem

List item describing a schema version.

Contents

Description

A description of the schema version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9.,]+

Required: No

Namespace

The name of the schema version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-z]+

Required: No

SchemaId

The identifier of the schema version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [a-zA-Z0-9./]+

Required: No

SemanticVersion

The schema version. If this is left blank, it defaults to the latest version.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: (\d+\.\d+|\\$latest)

Required: No

Type

The type of schema version.

Type: String

Valid Values: capability | definition

Required: No

Visibility

The visibility of the schema version.

Type: String

Valid Values: PUBLIC | PRIVATE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StateCapability

State capabilities added for the managed thing.

Contents

id

The id of the managed thing in the capability report.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[a-zA-Z0-9.\v/]+(@(\d+\.\d+|\$latest))?`

Required: Yes

name

Name for the AWS capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[/a-zA-Z0-9\._]+`

Required: Yes

version

Version for the AWS capability.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `(0|[1-9][0-9]*)`

Required: Yes

properties

Describe the command capability with the properties it supports.

Type: JSON value

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StateEndpoint

Describe the endpoint with an Id, a name, and the relevant capabilities for reporting state

Contents

capabilities

Describe the endpoint with an id, a name, and the relevant capabilities for the reporting state.

Type: Array of [StateCapability](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

endpointId

Numeric identifier of the endpoint

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[0-9a-zA-Z]+`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TaskProcessingDetails

Details about the over-the-air (OTA) task process.

Contents

NumberOfCanceledThings

The number of canceled things in an over-the-air (OTA) task.

Type: Integer

Required: No

NumberOfFailedThings

The number of failed things in an over-the-air (OTA) task.

Type: Integer

Required: No

NumberOfInProgressThings

The number of in progress things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfQueuedThings

The number of queued things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfRejectedThings

The number of rejected things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfRemovedThings

The number of removed things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfSucceededThings

The number of succeeded things in an over-the-air (OTA) task.

Type: Integer

Required: No

numberOfTimedOutThings

The number of timed out things in an over-the-air (OTA) task.

Type: Integer

Required: No

processingTargets

The targets of the over-the-air (OTA) task.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400