



API Reference

AWS IoT Analytics



API Version 2017-11-27

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS IoT Analytics: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchPutMessage	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	5
Response Elements	6
Errors	6
See Also	7
CancelPipelineReprocessing	8
Request Syntax	8
URI Request Parameters	8
Request Body	8
Response Syntax	9
Response Elements	9
Errors	9
See Also	10
CreateChannel	11
Request Syntax	11
URI Request Parameters	12
Request Body	12
Response Syntax	13
Response Elements	13
Errors	14
See Also	14
CreateDataset	16
Request Syntax	16
URI Request Parameters	18
Request Body	18
Response Syntax	20
Response Elements	21
Errors	21
See Also	22

CreateDatasetContent	24
Request Syntax	24
URI Request Parameters	24
Request Body	24
Response Syntax	25
Response Elements	25
Errors	25
See Also	26
CreateDatastore	28
Request Syntax	28
URI Request Parameters	29
Request Body	29
Response Syntax	31
Response Elements	31
Errors	32
See Also	33
CreatePipeline	34
Request Syntax	34
URI Request Parameters	36
Request Body	36
Response Syntax	37
Response Elements	37
Errors	38
See Also	38
DeleteChannel	40
Request Syntax	40
URI Request Parameters	40
Request Body	40
Response Syntax	40
Response Elements	41
Errors	41
See Also	41
DeleteDataset	43
Request Syntax	43
URI Request Parameters	43
Request Body	43

Response Syntax	43
Response Elements	44
Errors	44
See Also	44
DeleteDatasetContent	46
Request Syntax	46
URI Request Parameters	46
Request Body	46
Response Syntax	47
Response Elements	47
Errors	47
See Also	48
DeleteDatastore	49
Request Syntax	49
URI Request Parameters	49
Request Body	49
Response Syntax	49
Response Elements	50
Errors	50
See Also	50
DeletePipeline	52
Request Syntax	52
URI Request Parameters	52
Request Body	52
Response Syntax	52
Response Elements	53
Errors	53
See Also	53
DescribeChannel	55
Request Syntax	55
URI Request Parameters	55
Request Body	55
Response Syntax	56
Response Elements	56
Errors	57
See Also	58

DescribeDataset	59
Request Syntax	59
URI Request Parameters	59
Request Body	59
Response Syntax	59
Response Elements	62
Errors	62
See Also	63
DescribeDatastore	64
Request Syntax	64
URI Request Parameters	64
Request Body	64
Response Syntax	65
Response Elements	66
Errors	67
See Also	67
DescribeLoggingOptions	69
Request Syntax	69
URI Request Parameters	69
Request Body	69
Response Syntax	69
Response Elements	69
Errors	70
See Also	70
DescribePipeline	72
Request Syntax	72
URI Request Parameters	72
Request Body	72
Response Syntax	72
Response Elements	74
Errors	75
See Also	75
GetDatasetContent	77
Request Syntax	77
URI Request Parameters	77
Request Body	77

Response Syntax	78
Response Elements	78
Errors	79
See Also	79
ListChannels	81
Request Syntax	81
URI Request Parameters	81
Request Body	81
Response Syntax	81
Response Elements	82
Errors	82
See Also	83
ListDatasetContents	84
Request Syntax	84
URI Request Parameters	84
Request Body	85
Response Syntax	85
Response Elements	85
Errors	86
See Also	87
ListDatasets	88
Request Syntax	88
URI Request Parameters	88
Request Body	88
Response Syntax	88
Response Elements	89
Errors	90
See Also	90
ListDatastores	92
Request Syntax	92
URI Request Parameters	92
Request Body	92
Response Syntax	92
Response Elements	94
Errors	94
See Also	95

ListPipelines	96
Request Syntax	96
URI Request Parameters	96
Request Body	96
Response Syntax	96
Response Elements	97
Errors	97
See Also	98
ListTagsForResource	99
Request Syntax	99
URI Request Parameters	99
Request Body	99
Response Syntax	99
Response Elements	100
Errors	100
See Also	101
PutLoggingOptions	102
Request Syntax	102
URI Request Parameters	102
Request Body	102
Response Syntax	103
Response Elements	103
Errors	103
See Also	103
RunPipelineActivity	105
Request Syntax	105
URI Request Parameters	106
Request Body	107
Response Syntax	107
Response Elements	107
Errors	108
See Also	109
SampleChannelData	110
Request Syntax	110
URI Request Parameters	110
Request Body	111

Response Syntax	111
Response Elements	111
Errors	111
See Also	112
StartPipelineReprocessing	113
Request Syntax	113
URI Request Parameters	113
Request Body	114
Response Syntax	114
Response Elements	115
Errors	115
See Also	116
TagResource	117
Request Syntax	117
URI Request Parameters	117
Request Body	118
Response Syntax	118
Response Elements	118
Errors	118
See Also	119
UntagResource	120
Request Syntax	120
URI Request Parameters	120
Request Body	120
Response Syntax	121
Response Elements	121
Errors	121
See Also	122
UpdateChannel	123
Request Syntax	123
URI Request Parameters	123
Request Body	124
Response Syntax	124
Response Elements	124
Errors	124
See Also	125

UpdateDataset	127
Request Syntax	127
URI Request Parameters	129
Request Body	129
Response Syntax	131
Response Elements	131
Errors	131
See Also	132
UpdateDatastore	133
Request Syntax	133
URI Request Parameters	134
Request Body	134
Response Syntax	135
Response Elements	135
Errors	135
See Also	136
UpdatePipeline	137
Request Syntax	137
URI Request Parameters	139
Request Body	139
Response Syntax	139
Response Elements	140
Errors	140
See Also	141
Data Types	142
AddAttributesActivity	145
Contents	145
See Also	146
BatchPutMessageErrorEntry	147
Contents	147
See Also	147
Channel	149
Contents	149
See Also	150
ChannelActivity	152
Contents	152

See Also	152
ChannelMessages	154
Contents	154
See Also	154
ChannelStatistics	155
Contents	155
See Also	155
ChannelStorage	156
Contents	156
See Also	156
ChannelStorageSummary	157
Contents	157
See Also	157
ChannelSummary	158
Contents	158
See Also	159
Column	160
Contents	160
See Also	160
ContainerDatasetAction	161
Contents	161
See Also	162
CustomerManagedChannelS3Storage	163
Contents	163
See Also	164
CustomerManagedChannelS3StorageSummary	165
Contents	165
See Also	166
CustomerManagedDatastoreS3Storage	167
Contents	167
See Also	168
CustomerManagedDatastoreS3StorageSummary	169
Contents	169
See Also	170
Dataset	171
Contents	171

See Also	173
DatasetAction	174
Contents	174
See Also	174
DatasetActionSummary	176
Contents	176
See Also	176
DatasetContentDeliveryDestination	177
Contents	177
See Also	177
DatasetContentDeliveryRule	178
Contents	178
See Also	178
DatasetContentStatus	179
Contents	179
See Also	179
DatasetContentSummary	180
Contents	180
See Also	181
DatasetContentVersionValue	182
Contents	182
See Also	182
DatasetEntry	183
Contents	183
See Also	183
DatasetSummary	184
Contents	184
See Also	185
DatasetTrigger	186
Contents	186
See Also	186
Datastore	187
Contents	187
See Also	189
DatastoreActivity	190
Contents	190

See Also	190
DatastorelotSiteWiseMultiLayerStorage	191
Contents	191
See Also	191
DatastorelotSiteWiseMultiLayerStorageSummary	192
Contents	192
See Also	192
DatastorePartition	193
Contents	193
See Also	193
DatastorePartitions	194
Contents	194
See Also	194
DatastoreStatistics	195
Contents	195
See Also	195
DatastoreStorage	196
Contents	196
See Also	196
DatastoreStorageSummary	198
Contents	198
See Also	198
DatastoreSummary	199
Contents	199
See Also	200
DeltaTime	202
Contents	202
See Also	202
DeltaTimeSessionWindowConfiguration	203
Contents	203
See Also	203
DeviceRegistryEnrichActivity	204
Contents	204
See Also	205
DeviceShadowEnrichActivity	206
Contents	206

See Also	207
EstimatedResourceSize	208
Contents	208
See Also	208
FileFormatConfiguration	209
Contents	209
See Also	209
FilterActivity	210
Contents	210
See Also	210
GlueConfiguration	212
Contents	212
See Also	212
IoTEventsDestinationConfiguration	214
Contents	214
See Also	214
IoTSiteWiseCustomerManagedDatastoreS3Storage	215
Contents	215
See Also	215
IoTSiteWiseCustomerManagedDatastoreS3StorageSummary	217
Contents	217
See Also	217
JsonConfiguration	219
Contents	219
See Also	219
LambdaActivity	220
Contents	220
See Also	221
LateDataRule	222
Contents	222
See Also	222
LateDataRuleConfiguration	223
Contents	223
See Also	223
LoggingOptions	224
Contents	224

See Also	224
MathActivity	226
Contents	226
See Also	227
Message	228
Contents	228
See Also	228
OutputFileUriValue	229
Contents	229
See Also	229
ParquetConfiguration	230
Contents	230
See Also	230
Partition	231
Contents	231
See Also	231
Pipeline	232
Contents	232
See Also	233
PipelineActivity	234
Contents	234
See Also	235
PipelineSummary	237
Contents	237
See Also	237
QueryFilter	239
Contents	239
See Also	239
RemoveAttributesActivity	240
Contents	240
See Also	240
ReprocessingSummary	242
Contents	242
See Also	242
ResourceConfiguration	243
Contents	243

See Also	243
RetentionPeriod	244
Contents	244
See Also	244
S3DestinationConfiguration	245
Contents	245
See Also	246
Schedule	247
Contents	247
See Also	247
SchemaDefinition	248
Contents	248
See Also	248
SelectAttributesActivity	249
Contents	249
See Also	249
ServiceManagedChannelS3Storage	251
Contents	251
See Also	251
ServiceManagedChannelS3StorageSummary	252
Contents	252
See Also	252
ServiceManagedDatastoreS3Storage	253
Contents	253
See Also	253
ServiceManagedDatastoreS3StorageSummary	254
Contents	254
See Also	254
SqlQueryDatasetAction	255
Contents	255
See Also	255
Tag	256
Contents	256
See Also	256
TimestampPartition	257
Contents	257

See Also	257
TriggeringDataset	258
Contents	258
See Also	258
Variable	259
Contents	259
See Also	260
VersioningConfiguration	261
Contents	261
See Also	261
Common Parameters	262
Common Errors	265

Welcome

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics.

After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

AWS IoT Analytics allows you to collect large amounts of device data, process messages, and store them. You can then query the data and run sophisticated analytics on it. AWS IoT Analytics enables advanced data exploration through integration with Jupyter Notebooks and data visualization through integration with Amazon QuickSight.

Traditional analytics and business intelligence tools are designed to process structured data. IoT data often comes from devices that record noisy processes (such as temperature, motion, or sound). As a result the data from these devices can have significant gaps, corrupted messages, and false readings that must be cleaned up before analysis can occur. Also, IoT data is often only meaningful in the context of other data from external sources.

AWS IoT Analytics automates the steps required to analyze data from IoT devices. AWS IoT Analytics filters, transforms, and enriches IoT data before storing it in a time-series data store for analysis. You can set up the service to collect only the data you need from your devices, apply mathematical transforms to process the data, and enrich the data with device-specific metadata such as device type and location before storing it. Then, you can analyze your data by running queries using the built-in SQL query engine, or perform more complex analytics and machine learning inference. AWS IoT Analytics includes pre-built models for common IoT use cases so you can answer questions like which devices are about to fail or which customers are at risk of abandoning their wearable devices.

This document was last published on September 4, 2025.

Actions

The following actions are supported:

- [BatchPutMessage](#)
- [CancelPipelineReprocessing](#)
- [CreateChannel](#)
- [CreateDataset](#)
- [CreateDatasetContent](#)
- [CreateDatastore](#)
- [CreatePipeline](#)
- [DeleteChannel](#)
- [DeleteDataset](#)
- [DeleteDatasetContent](#)
- [DeleteDatastore](#)
- [DeletePipeline](#)
- [DescribeChannel](#)
- [DescribeDataset](#)
- [DescribeDatastore](#)
- [DescribeLoggingOptions](#)
- [DescribePipeline](#)
- [GetDatasetContent](#)
- [ListChannels](#)
- [ListDatasetContents](#)
- [ListDatasets](#)
- [ListDatastores](#)
- [ListPipelines](#)
- [ListTagsForResource](#)
- [PutLoggingOptions](#)
- [RunPipelineActivity](#)
- [SampleChannelData](#)

- [StartPipelineReprocessing](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateChannel](#)
- [UpdateDataset](#)
- [UpdateDatastore](#)
- [UpdatePipeline](#)

BatchPutMessage

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Sends messages to a channel.

Request Syntax

```
POST /messages/batch HTTP/1.1
Content-type: application/json

{
  "channelNamemessagesmessageIdpayload
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

channelName

The name of the channel where the messages are sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\\$)

Required: Yes

messages

The list of messages to be sent. Each message has the format: { "messageId": "string", "payload": "string"}.

The field names of message payloads (data) that you send to AWS IoT Analytics:

- Must contain only alphanumeric characters and underscores (_). No other special characters are allowed.
- Must begin with an alphabetic character or single underscore (_).
- Cannot contain hyphens (-).
- In regular expression terms: "^[A-Za-z_][A-Za-z0-9]*[A-Za-z0-9][A-Za-z0-9_]*\$".
- Cannot be more than 255 characters.
- Are case insensitive. (Fields named foo and FOO in the same payload are considered duplicates.)

For example, {"temp_01": 29} or {"_temp_01": 29} are valid, but {"temp-01": 29}, {"01_temp": 29} or {"__temp_01": 29} are invalid in message payloads.

Type: Array of [Message](#) objects

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "batchPutMessageErrorEntries": [
    {
      "errorCodeerrorMessagemessageId
```

```
    }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[batchPutMessageErrorEntries](#)

A list of any errors encountered when sending the messages to the channel.

Type: Array of [BatchPutMessageErrorEntry](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelPipelineReprocessing

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Cancels the reprocessing of data through the pipeline.

Request Syntax

```
DELETE /pipelines/pipelineName/reprocessing/reprocessingId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[pipelineName](#)

The name of pipeline for which data reprocessing is canceled.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

[reprocessingId](#)

The ID of the reprocessing task (returned by [StartPipelineReprocessing](#)).

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateChannel

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Used to create a channel. A channel collects data from an MQTT topic and archives the raw, unprocessed messages before publishing the data to a pipeline.

Request Syntax

```
POST /channels HTTP/1.1
Content-type: application/json

{
  "channelName": "string",
  "channelStorage": {
    "customerManagedS3": {
      "bucket": "string",
      "keyPrefix": "string",
      "roleArn": "string"
    },
    "serviceManagedS3": {
    }
  },
  "retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  },
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

channelName

The name of the channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

channelStorage

Where channel data is stored. You can choose one of serviceManagedS3 or customerManagedS3 storage. If not specified, the default is serviceManagedS3. You can't change this storage option after the channel is created.

Type: [ChannelStorage](#) object

Required: No

retentionPeriod

How long, in days, message data is kept for the channel. When customerManagedS3 storage is selected, this parameter is ignored.

Type: [RetentionPeriod](#) object

Required: No

tags

Metadata which can be used to manage the channel.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "channelArn": "string",
  "channelName": "string",
  "retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[channelArn](#)

The ARN of the channel.

Type: String

[channelName](#)

The name of the channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))([a-zA-Z0-9_]+\$)

[retentionPeriod](#)

How long, in days, message data is kept for the channel.

Type: [RetentionPeriod](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceAlreadyExistsException

A resource with the same name already exists.

HTTP Status Code: 409

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDataset

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Used to create a dataset. A dataset stores data retrieved from a data store by applying a queryAction (a SQL query) or a containerAction (executing a containerized application). This operation creates the skeleton of a dataset. The dataset can be populated manually by calling CreateDatasetContent or automatically according to a trigger you specify.

Request Syntax

```
POST /datasets HTTP/1.1
Content-type: application/json

{
  "actions": [
    {
      "actionName": "string",
      "containerAction": {
        "executionRoleArn": "string",
        "image": "string",
        "resourceConfiguration": {
          "computeType": "string",
          "volumeSizeInGB": number
        },
        "variables": [
          {
            "datasetContentVersionValue": {
              "datasetName": "string"
            },
            "doubleValue": number,
            "name": "string",
            "outputFileUriValue": {
              "fileName": "string"
            }
          }
        ]
      }
    }
  ]
}
```

```
        "stringValue": "string"
    }
]
},
"queryAction": {
    "filters": [
        {
            "deltaTime": {
                "offsetSeconds": number,
                "timeExpression": "string"
            }
        }
    ],
    "sqlQuery": "string"
}
},
"contentDeliveryRules": [
{
    "destination": {
        "iotEventsDestinationConfiguration": {
            "inputName": "string",
            "roleArn": "string"
        },
        "s3DestinationConfiguration": {
            "bucket": "string",
            "glueConfiguration": {
                "databaseName": "string",
                "tableName": "string"
            },
            "key": "string",
            "roleArn": "string"
        }
    },
    "entryName": "string"
}
],
"datasetName": "string",
"lateDataRules": [
{
    "ruleConfiguration": {
        "deltaTimeSessionWindowConfiguration": {
            "timeoutInMinutes": number
        }
    }
}
```

```
        },
        "ruleName": "string"
    }
],
"retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
},
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
"triggers": [
    {
        "dataset": {
            "name": "string"
        },
        "schedule": {
            "expression": "string"
        }
    }
],
"versioningConfiguration": {
    "maxVersions": number,
    "unlimited": boolean
}
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

actions

A list of actions that create the dataset contents.

Type: Array of [DatasetAction](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

[contentDeliveryRules](#)

When dataset contents are created, they are delivered to destinations specified here.

Type: Array of [DatasetContentDeliveryRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

[datasetName](#)

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(!_{2}))(^[a-zA-Z0-9_]+$)`

Required: Yes

[lateDataRules](#)

A list of data rules that send notifications to CloudWatch, when data arrives late. To specify `lateDataRules`, the dataset must use a [DeltaTimer](#) filter.

Type: Array of [LateDataRule](#) objects

Array Members: Fixed number of 1 item.

Required: No

[retentionPeriod](#)

Optional. How long, in days, versions of dataset contents are kept for the dataset.

If not specified or set to null, versions of dataset contents are retained for at most 90 days. The number of versions of dataset contents retained is determined by the `versioningConfiguration` parameter. For more information, see [Keeping Multiple Versions of AWS IoT Analytics datasets](#) in the *AWS IoT Analytics User Guide*.

Type: [RetentionPeriod](#) object

Required: No

tags

Metadata which can be used to manage the dataset.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

triggers

A list of triggers. A trigger causes dataset contents to be populated at a specified time interval or when another dataset's contents are created. The list of triggers can be empty or contain up to five [DataSetTrigger](#) objects.

Type: Array of [DatasetTrigger](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

versioningConfiguration

Optional. How many versions of dataset contents are kept. If not specified or set to null, only the latest version plus the latest succeeded version (if they are different) are kept for the time period specified by the [retentionPeriod](#) parameter. For more information, see [Keeping Multiple Versions of AWS IoT Analytics datasets](#) in the [AWS IoT Analytics User Guide](#).

Type: [VersioningConfiguration](#) object

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "datasetArn": "string",
  "datasetName": "string",
```

```
"retentionPeriod": {  
    "numberOfDaysnumber,  
    "unlimited": boolean  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

datasetArn

The ARN of the dataset.

Type: String

datasetName

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

retentionPeriod

How long, in days, dataset contents are kept for the dataset.

Type: [RetentionPeriod](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceAlreadyExistsException

A resource with the same name already exists.

HTTP Status Code: 409

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDatasetContent

A Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Creates the content of a dataset by applying a queryAction (a SQL query) or a containerAction (executing a containerized application).

Request Syntax

```
POST /datasets/datasetName/content HTTP/1.1
Content-type: application/json

{
    "versionIdstring"
}
```

URI Request Parameters

The request uses the following URI parameters.

datasetName

The name of the dataset.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request accepts the following data in JSON format.

versionId

The version ID of the dataset content. To specify `versionId` for a dataset content, the dataset must use a [DeltaTimer](#) filter.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 36.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "versionId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

versionId

The version ID of the dataset contents that are being created.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 36.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDatastore

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Creates a data store, which is a repository for messages.

Request Syntax

```
POST /datastores HTTP/1.1
Content-type: application/json

{
  "datastoreName": "string",
  "datastorePartitions": {
    "partitions": [
      {
        "attributePartition": {
          "attributeName": "string"
        },
        "timestampPartition": {
          "attributeName": "string",
          "timestampFormat": "string"
        }
      }
    ]
  },
  "datastoreStorage": {
    "customerManagedS3": {
      "bucket": "string",
      "keyPrefix": "string",
      "roleArn": "string"
    },
    "iotSiteWiseMultiLayerStorage": {
      "customerManagedS3Storage": {
        "bucket": "string",
        "prefix": "string"
      }
    }
  }
}
```

```
        "keyPrefix": "string"
    }
},
"serviceManagedS3": {
}
},
"fileFormatConfiguration": {
    "jsonConfiguration": {
    },
    "parquetConfiguration": {
        "schemaDefinition": {
            "columns": [
                {
                    "name": "string",
                    "type": "string"
                }
            ]
        }
    }
},
"retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
},
"tags": [
    {
        "key": "string",
        "value": "string"
    }
]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[datastoreName](#)

The name of the data store.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))([a-zA-Z0-9_]+\$)

Required: Yes

[datastorePartitions](#)

Contains information about the partition dimensions in a data store.

Type: [DatastorePartitions](#) object

Required: No

[datastoreStorage](#)

Where data in a data store is stored.. You can choose serviceManagedS3 storage, customerManagedS3 storage, or iotSiteWiseMultiLayerStorage storage. The default is serviceManagedS3. You can't change the choice of Amazon S3 storage after your data store is created.

Type: [DatastoreStorage](#) object

Required: No

[fileFormatConfiguration](#)

Contains the configuration information of file formats. AWS IoT Analytics data stores support JSON and [Parquet](#).

The default file format is JSON. You can specify only one format.

You can't change the file format after you create the data store.

Type: [FileFormatConfiguration](#) object

Required: No

[retentionPeriod](#)

How long, in days, message data is kept for the data store. When customerManagedS3 storage is selected, this parameter is ignored.

Type: [RetentionPeriod](#) object

Required: No

tags

Metadata which can be used to manage the data store.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "datastoreArn": "string",
  "datastoreNameretentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[datastoreArn](#)

The ARN of the data store.

Type: String

[datastoreName](#)

The name of the data store.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

retentionPeriod

How long, in days, message data is kept for the data store.

Type: [RetentionPeriod](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceAlreadyExistsException

A resource with the same name already exists.

HTTP Status Code: 409

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePipeline

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Creates a pipeline. A pipeline consumes messages from a channel and allows you to process the messages before storing them in a data store. You must specify both a channel and a datastore activity and, optionally, as many as 23 additional activities in the pipelineActivities array.

Request Syntax

```
POST /pipelines HTTP/1.1
Content-type: application/json

{
  "pipelineActivities": [
    {
      "addAttributes": {
        "attributes": {
          "string" : "string"
        },
        "name": "string",
        "next": "string"
      },
      "channel": {
        "channelName": "string",
        "name": "string",
        "next": "string"
      },
      "datastore": {
        "datastoreName": "string",
        "name": "string"
      },
      "deviceRegistryEnrich": {
        "attribute": "string",
        "name": "string",
      }
    }
  ]
}
```

```
        "next": "string",
        "roleArn": "string",
        "thingName": "string"
    },
    "deviceShadowEnrich": {
        "attribute": "string",
        "name": "string",
        "next": "string",
        "roleArn": "string",
        "thingName": "string"
    },
    "filter": {
        "filter": "string",
        "name": "string",
        "next": "string"
    },
    "lambda": {
        "batchSize": number,
        "lambdaName": "string",
        "name": "string",
        "next": "string"
    },
    "math": {
        "attribute": "string",
        "math": "string",
        "name": "string",
        "next": "string"
    },
    "removeAttributes": {
        "attributes": [ "string" ],
        "name": "string",
        "next": "string"
    },
    "selectAttributes": {
        "attributes": [ "string" ],
        "name": "string",
        "next": "string"
    }
}
],
"pipelineName": "string",
"tags": [
{
    "key": "string",

```

```
        "value": "string"
    }
]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[pipelineActivities](#)

A list of PipelineActivity objects. Activities perform transformations on your messages, such as removing, renaming or adding message attributes; filtering messages based on attribute values; invoking your Lambda functions on messages for advanced processing; or performing mathematical transformations to normalize device data.

The list can be 2-25 PipelineActivity objects and must contain both a channel and a datastore activity. Each entry in the list must contain only one activity. For example:

```
pipelineActivities = [ { "channel": { ... } }, { "lambda": { ... } }, ... ]
```

Type: Array of [PipelineActivity](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

[pipelineName](#)

The name of the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: $(^(!_{2}))([a-zA-Z0-9_]+\$)$

Required: Yes

tags

Metadata which can be used to manage the pipeline.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "pipelineArn": "string",
  "pipelineName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[pipelineArn](#)

The ARN of the pipeline.

Type: String

[pipelineName](#)

The name of the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))([a-zA-Z0-9_]+\$)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceAlreadyExistsException

A resource with the same name already exists.

HTTP Status Code: 409

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteChannel

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Deletes the specified channel.

Request Syntax

```
DELETE /channels/channelName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

channelName

The name of the channel to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDataset

A Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Deletes the specified dataset.

You do not have to delete the content of the dataset before you perform this operation.

Request Syntax

```
DELETE /datasets/datasetName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datasetName](#)

The name of the dataset to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDatasetContent

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Deletes the content of the specified dataset.

Request Syntax

```
DELETE /datasets/datasetName/content?versionId=versionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datasetName

The name of the dataset whose content is deleted.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

versionId

The version of the dataset whose content is deleted. You can also use the strings "\$LATEST" or "\$LATEST_SUCCEEDED" to delete the latest or latest successfully completed data set. If not specified, "\$LATEST_SUCCEEDED" is the default.

Length Constraints: Minimum length of 7. Maximum length of 36.

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 204

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

The request was denied due to an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDatastore

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Deletes the specified data store.

Request Syntax

```
DELETE /datastores/datastoreName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datastoreName

The name of the data store to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePipeline

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Deletes the specified pipeline.

Request Syntax

```
DELETE /pipelines/pipelineName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[pipelineName](#)

The name of the pipeline to delete.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeChannel

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves information about a channel.

Request Syntax

```
GET /channels/channelName?includeStatistics=includeStatistics HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[channelName](#)

The name of the channel whose information is retrieved.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(!_{2}))([a-zA-Z0-9_]+$)`

Required: Yes

[includeStatistics](#)

If true, additional statistical information about the channel is included in the response. This feature can't be used with a channel whose S3 storage is customer-managed.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "channel": {
    "arn": "string",
    "creationTime": number,
    "lastMessageArrivalTime": number,
    "lastUpdateTime": number,
    "name": "string",
    "retentionPeriod": {
      "numberOfDays": number,
      "unlimited": boolean
    },
    "status": "string",
    "storage": {
      "customerManagedS3": {
        "bucket": "string",
        "keyPrefix": "string",
        "roleArn": "string"
      },
      "serviceManagedS3": {
      }
    }
  },
  "statistics": {
    "size": {
      "estimatedOn": number,
      "estimatedSizeInBytes": number
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

channel

An object that contains information about the channel.

Type: [Channel](#) object

statistics

Statistics about the channel. Included if the `includeStatistics` parameter is set to `true` in the request.

Type: [ChannelStatistics](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDataset

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves information about a dataset.

Request Syntax

```
GET /datasets/datasetName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datasetName

The name of the dataset whose information is retrieved.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))([a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"dataset": {  
    "actions": [  
        {  
            "actionName": "string",  
            "containerAction": {  
                "executionRoleArn": "string",  
                "image": "string",  
                "resourceConfiguration": {  
                    "computeType": "string",  
                    "volumeSizeInGB": number  
                },  
                "variables": [  
                    {  
                        "datasetContentVersionValue": {  
                            "datasetName": "string"  
                        },  
                        "doubleValue": number,  
                        "name": "string",  
                        "outputFileUriValue": {  
                            "fileName": "string"  
                        },  
                        "stringValue": "string"  
                    }  
                ]  
            },  
            "queryAction": {  
                "filters": [  
                    {  
                        "deltaTime": {  
                            "offsetSeconds": number,  
                            "timeExpression": "string"  
                        }  
                    }  
                ],  
                "sqlQuery": "string"  
            }  
        }  
    ],  
    "arn": "string",  
    "contentDeliveryRules": [  
        {  
            "destination": {  
                "iotEventsDestinationConfiguration": {  
                    "inputName": "string",  
                    "outputPath": "string"  
                }  
            }  
        }  
    ]  
}
```

```
        "roleArn": "string"
    },
    "s3DestinationConfiguration": {
        "bucket": "string",
        "glueConfiguration": {
            "databaseName": "string",
            "tableName": "string"
        },
        "key": "string",
        "roleArn": "string"
    }
},
"entryName": "string"
}
],
"creationTime": number,
"lastUpdateTime": number,
"lateDataRules": [
{
    "ruleConfiguration": {
        "deltaTimeSessionWindowConfiguration": {
            "timeoutInMinutes": number
        }
    },
    "ruleName": "string"
}
],
"name": "string",
"retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
},
"status": "string",
"triggers": [
{
    "dataset": {
        "name": "string"
    },
    "schedule": {
        "expression": "string"
    }
}
],
"versioningConfiguration": {
```

```
        "maxVersions": number,  
        "unlimited": boolean  
    }  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

dataset

An object that contains information about the dataset.

Type: [Dataset object](#)

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeDatastore

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves information about a data store.

Request Syntax

```
GET /datastores/datastoreName?includeStatistics=includeStatistics HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreName](#)

The name of the data store

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

[includeStatistics](#)

If true, additional statistical information about the data store is included in the response. This feature can't be used with a data store whose S3 storage is customer-managed.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datastore": {
    "arn": "string",
    "creationTime": number,
    "datastorePartitions": {
      "partitions": [
        {
          "attributePartition": {
            "attributeName": "string"
          },
          "timestampPartition": {
            "attributeName": "string",
            "timestampFormat": "string"
          }
        }
      ]
    },
    "fileFormatConfiguration": {
      "jsonConfiguration": {
      },
      "parquetConfiguration": {
        "schemaDefinition": {
          "columns": [
            {
              "name": "string",
              "type": "string"
            }
          ]
        }
      }
    },
    "lastMessageArrivalTime": number,
    "lastUpdateTime": number,
    "name": "string",
    "retentionPeriod": {
      "numberOfDays": number,
      "unlimited": boolean
    },
  }
}
```

```
"status": "string",
"storage": {
    "customerManagedS3": {
        "bucket": "string",
        "keyPrefix": "string",
        "roleArn": "string"
    },
    "iotSiteWiseMultiLayerStorage": {
        "customerManagedS3Storage": {
            "bucket": "string",
            "keyPrefix": "string"
        }
    },
    "serviceManagedS3": {
    }
},
},
"statistics": {
    "size": {
        "estimatedOn": number,
        "estimatedSizeInBytes": number
    }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastore](#)

Information about the data store.

Type: [Datastore](#) object

[statistics](#)

Additional statistical information about the data store. Included if the `includeStatistics` parameter is set to `true` in the request.

Type: [DatastoreStatistics](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeLoggingOptions

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves the current settings of the AWS IoT Analytics logging options.

Request Syntax

```
GET /logging HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "loggingOptions": {
    "enabled": boolean,
    "level": string,
    "roleArn": string
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

loggingOptions

The current settings of the AWS IoT Analytics logging options.

Type: [LoggingOptions](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribePipeline

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves information about a pipeline.

Request Syntax

```
GET /pipelines/pipelineName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[pipelineName](#)

The name of the pipeline whose information is retrieved.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"pipeline": {  
    "activities": [  
        {  
            "addAttributes": {  
                "attributes": {  
                    "string": "string"  
                },  
                "name": "string",  
                "next": "string"  
            },  
            "channel": {  
                "channelName": "string",  
                "name": "string",  
                "next": "string"  
            },  
            "datastore": {  
                "datastoreName": "string",  
                "name": "string"  
            },  
            "deviceRegistryEnrich": {  
                "attribute": "string",  
                "name": "string",  
                "next": "string",  
                "roleArn": "string",  
                "thingName": "string"  
            },  
            "deviceShadowEnrich": {  
                "attribute": "string",  
                "name": "string",  
                "next": "string",  
                "roleArn": "string",  
                "thingName": "string"  
            },  
            "filter": {  
                "filter": "string",  
                "name": "string",  
                "next": "string"  
            },  
            "lambda": {  
                "batchSize": number,  
                "lambdaName": "string",  
                "name": "string",  
                "next": "string"  
            },  
        ],  
        "end": "string"  
    ]  
}
```

```
"mathattributemathnamenextremoveAttributesattributesnamenextselectAttributesattributesnamenextarncreationTimelastUpdateTimenamereprocessingSummariescreationTimeidstatus
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[pipeline](#)

A Pipeline object that contains information about the pipeline.

Type: [Pipeline](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDatasetContent

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves the contents of a dataset as presigned URLs.

Request Syntax

```
GET /datasets/datasetName/content?versionId=versionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datasetName

The name of the dataset whose contents are retrieved.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

versionId

The version of the dataset whose contents are retrieved. You can also use the strings "\$LATEST" or "\$LATEST_SUCCEEDED" to retrieve the contents of the latest or latest successfully completed dataset. If not specified, "\$LATEST_SUCCEEDED" is the default.

Length Constraints: Minimum length of 7. Maximum length of 36.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "entriesdataURIentryNamestatusreasonstatetimestamp
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

entries

A list of [DatasetEntry](#) objects.

Type: Array of [DatasetEntry](#) objects

status

The status of the dataset content.

Type: [DatasetContentStatus](#) object

timestamp

The time when the request was made.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListChannels

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves a list of channels.

Request Syntax

```
GET /channels?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The maximum number of results to return in this request.

The default value is 100.

Valid Range: Minimum value of 1. Maximum value of 250.

[nextToken](#)

The token for the next set of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
    "channelSummaries": [  
        {  
            "channelName": "string",  
            "channelStorage": {  
                "customerManagedS3": {  
                    "bucket": "string",  
                    "keyPrefix": "string",  
                    "roleArn": "string"  
                },  
                "serviceManagedS3": {  
                }  
            },  
            "creationTime": number,  
            "lastMessageArrivalTime": number,  
            "lastUpdateTime": number,  
            "status": "string"  
        }  
    ],  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[channelSummaries](#)

A list of ChannelSummary objects.

Type: Array of [ChannelSummary](#) objects

[nextToken](#)

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDatasetContents

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics.

After December 15, 2025, you will no longer be able to access the AWS IoT Analytics

console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Lists information about dataset contents that have been created.

Request Syntax

```
GET /datasets/datasetName/contents?  
maxResults=maxResults&nextToken=nextToken&scheduledBefore=scheduledBefore&scheduledOnOrAfter=scheduledOnOrAfter  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

datasetName

The name of the dataset whose contents information you want to list.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

maxResults

The maximum number of results to return in this request.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token for the next set of results.

scheduledBefore

A filter to limit results to those dataset contents whose creation is scheduled before the given time. See the field `triggers.schedule` in the `CreateDataset` request. (timestamp)

scheduledOnOrAfter

A filter to limit results to those dataset contents whose creation is scheduled on or after the given time. See the field `triggers.schedule` in the `CreateDataset` request. (timestamp)

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "datasetContentSummaries": [
    {
      "completionTime": number,
      "creationTime": number,
      "scheduleTime": number,
      "status": {
        "reason": "string",
        "state": "string"
      },
      "version": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

datasetContentSummaries

Summary information about dataset contents that have been created.

Type: Array of [DatasetContentSummary](#) objects

nextToken

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDatasets

A Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves information about datasets.

Request Syntax

```
GET /datasets?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return in this request.

The default value is 100.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token for the next set of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
    "datasetSummaries": [  
        {  
            "actions": [  
                {  
                    "actionName": "string",  
                    "actionType": "string"  
                }  
            ],  
            "creationTime": number,  
            "datasetName": "string",  
            "lastUpdateTime": number,  
            "status": "string",  
            "triggers": [  
                {  
                    "dataset": {  
                        "name": "string"  
                    },  
                    "schedule": {  
                        "expression": "string"  
                    }  
                }  
            ]  
        }  
    ],  
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datasetSummaries](#)

A list of [DatasetSummary](#) objects.

Type: Array of [DatasetSummary](#) objects

[nextToken](#)

The token to retrieve the next set of results, or `null` if there are no more results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDatastores

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves a list of data stores.

Request Syntax

```
GET /datastores?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The maximum number of results to return in this request.

The default value is 100.

Valid Range: Minimum value of 1. Maximum value of 250.

[nextToken](#)

The token for the next set of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "datastoreSummaries": [  
    {  
      "creationTime": number,  
      "datastoreName": "string",  
      "datastorePartitions": {  
        "partitions": [  
          {  
            "attributePartition": {  
              "attributeName": "string"  
            },  
            "timestampPartition": {  
              "attributeName": "string",  
              "timestampFormat": "string"  
            }  
          }  
        ]  
      },  
      "datastoreStorage": {  
        "customerManagedS3": {  
          "bucket": "string",  
          "keyPrefix": "string",  
          "roleArn": "string"  
        },  
        "iotSiteWiseMultiLayerStorage": {  
          "customerManagedS3Storage": {  
            "bucket": "string",  
            "keyPrefix": "string"  
          }  
        },  
        "serviceManagedS3": {  
        }  
      },  
      "fileFormatType": "string",  
      "lastMessageArrivalTime": number,  
      "lastUpdateTime": number,  
      "status": "string"  
    }  
  ],  
  "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[datastoreSummaries](#)

A list of DatastoreSummary objects.

Type: Array of [DatastoreSummary](#) objects

[nextToken](#)

The token to retrieve the next set of results, or null if there are no more results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPipelines

A Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Retrieves a list of pipelines.

Request Syntax

```
GET /pipelines?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return in this request.

The default value is 100.

Valid Range: Minimum value of 1. Maximum value of 250.

nextToken

The token for the next set of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
    "nextToken": "string",  
    "pipelineSummaries": [  
        {  
            "creationTime": number,  
            "lastUpdateTime": number,  
            "pipelineName": "string",  
            "reprocessingSummaries": [  
                {  
                    "creationTime": number,  
                    "id": "string",  
                    "status": "string"  
                }  
            ]  
        }  
    ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The token to retrieve the next set of results, or null if there are no more results.

Type: String

[pipelineSummaries](#)

A list of PipelineSummary objects.

Type: Array of [PipelineSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Lists the tags (metadata) that you have assigned to the resource.

Request Syntax

```
GET /tags?resourceArn=resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[resourceArn](#)

The ARN of the resource whose tags you want to list.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"tags": [  
    {  
        "key        "value": "string"  
    }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

The tags (metadata) that you have assigned to the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutLoggingOptions

A Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Sets or updates the AWS IoT Analytics logging options.

If you update the value of any `loggingOptions` field, it takes up to one minute for the change to take effect. Also, if you change the policy attached to the role you specified in the `roleArn` field (for example, to correct an invalid policy), it takes up to five minutes for that change to take effect.

Request Syntax

```
PUT /logging HTTP/1.1
Content-type: application/json

{
  "loggingOptionsenabledboolean,
    "levelstring",
    "roleArnstring"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

loggingOptions

The new values of the AWS IoT Analytics logging options.

Type: [LoggingOptions](#) object

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RunPipelineActivity

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Simulates the results of running a pipeline activity on a message payload.

Request Syntax

```
POST /pipelineactivities/run HTTP/1.1
Content-type: application/json
```

```
{
  "payloadsblob ],
  "pipelineActivityaddAttributesattributesstring": "string"
      },
      "namestring",
      "nextstring"
    },
    "channelchannelNamestring",
      "namestring",
      "nextstring"
    },
    "datastoredatastoreNamestring",
      "namestring"
    },
    "deviceRegistryEnrichattributestring",
      "namestring",
      "nextstring",
      "roleArnstring",
    }
  }
}
```

```
        "thingName": "string"
    },
    "deviceShadowEnrich": {
        "attribute": "string",
        "name": "string",
        "next": "string",
        "roleArn": "string",
        "thingName": "string"
    },
    "filter": {
        "filter": "string",
        "name": "string",
        "next": "string"
    },
    "lambda": {
        "batchSize": number,
        "lambdaName": "string",
        "name": "string",
        "next": "string"
    },
    "math": {
        "attribute": "string",
        "math": "string",
        "name": "string",
        "next": "string"
    },
    "removeAttributes": {
        "attributes": [ "string" ],
        "name": "string",
        "next": "string"
    },
    "selectAttributes": {
        "attributes": [ "string" ],
        "name": "string",
        "next": "string"
    }
}
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[payloads](#)

The sample message payloads on which the pipeline activity is run.

Type: Array of Base64-encoded binary data objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

[pipelineActivity](#)

The pipeline activity that is run. This must not be a channel activity or a data store activity because these activities are used in a pipeline only to load the original message and to store the (possibly) transformed message. If a Lambda activity is specified, only short-running Lambda functions (those with a timeout of less than 30 seconds or less) can be used.

Type: [PipelineActivity](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "logResult": "string",
  "payloads": [ blob ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

logResult

In case the pipeline activity fails, the log message that is generated.

Type: String

payloads

The enriched or transformed sample message payloads as base64-encoded strings. (The results of running the pipeline activity on each input sample message payload, encoded in base64.)

Type: Array of Base64-encoded binary data objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SampleChannelData

Retrieves a sample of messages from the specified channel ingested during the specified timeframe. Up to 10 messages can be retrieved.

⚠ Important

The SampleChannelData operation in AWS IoT Analytics is no longer available to new customers. Existing customers of AWS IoT Analytics can continue to use the service as normal. [Learn more](#)

Request Syntax

```
GET /channels/channelName/sample?  
endTime=endTime&maxMessages=maxMessages&startTime=startTime HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[channelName](#)

The name of the channel whose message samples are retrieved.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

[endTime](#)

The end of the time window from which sample messages are retrieved.

[maxMessages](#)

The number of sample messages to be retrieved. The limit is 10. The default is also 10.

Valid Range: Minimum value of 1. Maximum value of 10.

startTime

The start of the time window from which sample messages are retrieved.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "payloads": [ blob ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

payloads

The list of message samples. Each sample message is returned as a base64-encoded string.

Type: Array of Base64-encoded binary data objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartPipelineReprocessing

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Starts the reprocessing of raw message data through the pipeline.

Request Syntax

```
POST /pipelines/pipelineName/reprocessing HTTP/1.1
Content-type: application/json

{
  "channelMessagess3Pathsstring" ]
  },
  "endTimenumber,
  "startTimenumber
}
```

URI Request Parameters

The request uses the following URI parameters.

[pipelineName](#)

The name of the pipeline on which to start reprocessing.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request accepts the following data in JSON format.

channelMessages

Specifies one or more sets of channel messages that you want to reprocess.

If you use the `channelMessages` object, you must not specify a value for `startTime` and `endTime`.

Type: [ChannelMessages](#) object

Required: No

endTime

The end time (exclusive) of raw message data that is reprocessed.

If you specify a value for the `endTime` parameter, you must not use the `channelMessages` object.

Type: Timestamp

Required: No

startTime

The start time (inclusive) of raw message data that is reprocessed.

If you specify a value for the `startTime` parameter, you must not use the `channelMessages` object.

Type: Timestamp

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
    "reprocessingId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[reprocessingId](#)

The ID of the pipeline reprocessing activity that was started.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceAlreadyExistsException

A resource with the same name already exists.

HTTP Status Code: 409

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Adds to or modifies the tags of the given resource. Tags are metadata that can be used to manage a resource.

Request Syntax

```
POST /tags?resourceArn=resourceArn HTTP/1.1
Content-type: application/json

{
  "tags": [
    {
      "keystring",
      "valuestring"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

[resourceArn](#)

The ARN of the resource whose tags you want to modify.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The new or modified tags for the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Required: Yes

Response Syntax

HTTP/1.1 204

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

A Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Removes the given tags (metadata) from the resource.

Request Syntax

```
DELETE /tags?resourceArn=resourceArn&tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource whose tags you want to remove.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

tagKeys

The keys of those tags which you want to remove.

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 204

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateChannel

Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Used to update the settings of a channel.

Request Syntax

```
PUT /channels/channelName HTTP/1.1
Content-type: application/json

{
  "channelStoragecustomerManagedS3bucketstring",
      "keyPrefixstring",
      "roleArnstring"
    },
    "serviceManagedS3retentionPeriodnumberOfDaysnumber,
    "unlimitedboolean
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

channelName

The name of the channel to be updated.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\\$)

Required: Yes

Request Body

The request accepts the following data in JSON format.

[channelStorage](#)

Where channel data is stored. You can choose one of serviceManagedS3 or customerManagedS3 storage. If not specified, the default is serviceManagedS3. You can't change this storage option after the channel is created.

Type: [ChannelStorage](#) object

Required: No

[retentionPeriod](#)

How long, in days, message data is kept for the channel. The retention period can't be updated if the channel's Amazon S3 storage is customer-managed.

Type: [RetentionPeriod](#) object

Required: No

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDataset

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Updates the settings of a dataset.

Request Syntax

```
PUT /datasets/datasetName HTTP/1.1
Content-type: application/json

{
  "actionsactionNamecontainerActionexecutionRoleArnimageresourceConfigurationcomputeTypevolumeSizeInGBvariablesdatasetContentVersionValuedatasetNamedoubleValuenameoutputFileUriValuefileNamestringValue
```

```
        },
        "queryAction": {
            "filters": [
                {
                    "deltaTime": {
                        "offsetSeconds": number,
                        "timeExpression": "string"
                    }
                }
            ],
            "sqlQuery": "string"
        }
    }
],
"contentDeliveryRules": [
{
    "destination": {
        "iotEventsDestinationConfiguration": {
            "inputName": "string",
            "roleArn": "string"
        },
        "s3DestinationConfiguration": {
            "bucket": "string",
            "glueConfiguration": {
                "databaseName": "string",
                "tableName": "string"
            },
            "key": "string",
            "roleArn": "string"
        }
    },
    "entryName": "string"
}
],
"lateDataRules": [
{
    "ruleConfiguration": {
        "deltaTimeSessionWindowConfiguration": {
            "timeoutInMinutes": number
        }
    },
    "ruleName": "string"
}
],
```

```
"retentionPeriod    "numberOfDaysnumber,  
    "unlimitedboolean  
},  
"triggers    {  
        "dataset            "namestring"  
        },  
        "schedule            "expressionstring"  
        }  
    }  
],  
"versioningConfiguration    "maxVersionsnumber,  
    "unlimitedboolean  
}  
}
```

URI Request Parameters

The request uses the following URI parameters.

datasetName

The name of the dataset to update.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request accepts the following data in JSON format.

actions

A list of DatasetAction objects.

Type: Array of [DatasetAction](#) objects

Array Members: Fixed number of 1 item.

Required: Yes

[contentDeliveryRules](#)

When dataset contents are created, they are delivered to destinations specified here.

Type: Array of [DatasetContentDeliveryRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

[lateDataRules](#)

A list of data rules that send notifications to CloudWatch, when data arrives late. To specify `lateDataRules`, the dataset must use a [DeltaTimer](#) filter.

Type: Array of [LateDataRule](#) objects

Array Members: Fixed number of 1 item.

Required: No

[retentionPeriod](#)

How long, in days, dataset contents are kept for the dataset.

Type: [RetentionPeriod](#) object

Required: No

[triggers](#)

A list of `DatasetTrigger` objects. The list can be empty or can contain up to five `DatasetTrigger` objects.

Type: Array of [DatasetTrigger](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

[versioningConfiguration](#)

Optional. How many versions of dataset contents are kept. If not specified or set to null, only the latest version plus the latest succeeded version (if they are different) are kept for the time

period specified by the `retentionPeriod` parameter. For more information, see [Keeping Multiple Versions of AWS IoT Analytics datasets](#) in the *AWS IoT Analytics User Guide*.

Type: [VersioningConfiguration](#) object

Required: No

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDatastore

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Used to update the settings of a data store.

Request Syntax

```
PUT /datastores/datastoreName HTTP/1.1
Content-type: application/json

{
  "datastoreStoragecustomerManagedS3bucketkeyPrefixroleArniotSiteWiseMultiLayerStoragecustomerManagedS3StoragebucketkeyPrefixserviceManagedS3fileFormatConfigurationjsonConfigurationparquetConfigurationschemaDefinitioncolumnsname
```

```
        "type": "string"
    }
]
}
},
"retentionPeriod": {
    "numberOfDays": number,
    "unlimited": boolean
}
}
```

URI Request Parameters

The request uses the following URI parameters.

[datastoreName](#)

The name of the data store to be updated.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request accepts the following data in JSON format.

[datastoreStorage](#)

Where data in a data store is stored.. You can choose serviceManagedS3 storage, customerManagedS3 storage, or iotSiteWiseMultiLayerStorage storage. The default is serviceManagedS3. You can't change the choice of Amazon S3 storage after your data store is created.

Type: [DatastoreStorage](#) object

Required: No

fileFormatConfiguration

Contains the configuration information of file formats. AWS IoT Analytics data stores support JSON and [Parquet](#).

The default file format is JSON. You can specify only one format.

You can't change the file format after you create the data store.

Type: [FileFormatConfiguration](#) object

Required: No

retentionPeriod

How long, in days, message data is kept for the data store. The retention period can't be updated if the data store's Amazon S3 storage is customer-managed.

Type: [RetentionPeriod](#) object

Required: No

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePipeline

⚠ Important

End of support notice: On December 15, 2025, AWS will end support for AWS IoT Analytics. After December 15, 2025, you will no longer be able to access the AWS IoT Analytics console or AWS IoT Analytics resources. For more information, see [AWS IoT Analytics end of support](#).

Updates the settings of a pipeline. You must specify both a channel and a datastore activity and, optionally, as many as 23 additional activities in the `pipelineActivities` array.

Request Syntax

```
PUT /pipelines/pipelineName HTTP/1.1
Content-type: application/json

{
  "pipelineActivities": [
    {
      "addAttributesattributes": {
          "string": "string"
        },
        "name": "string",
        "next": "string"
      },
      "channel": {
        "channelName": "string",
        "name": "string",
        "next": "string"
      },
      "datastore": {
        "datastoreName": "string",
        "name": "string"
      },
      "deviceRegistryEnrich": {
        "attribute": "string",
        "name": "string",
        "next": "string",
      }
    }
  ]
}
```

```
        "roleArn": "string",
        "thingName": "string"
    },
    "deviceShadowEnrich": {
        "attribute": "string",
        "name": "string",
        "next": "string",
        "roleArn": "string",
        "thingName": "string"
    },
    "filter": {
        "filter": "string",
        "name": "string",
        "next": "string"
    },
    "lambda": {
        "batchSize": number,
        "lambdaName": "string",
        "name": "string",
        "next": "string"
    },
    "math": {
        "attribute": "string",
        "math": "string",
        "name": "string",
        "next": "string"
    },
    "removeAttributes": {
        "attributes": [ "string" ],
        "name": "string",
        "next": "string"
    },
    "selectAttributes": {
        "attributes": [ "string" ],
        "name": "string",
        "next": "string"
    }
}
]
}
```

URI Request Parameters

The request uses the following URI parameters.

[pipelineName](#)

The name of the pipeline to update.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(!_{2}))([a-zA-Z0-9_]+\$)

Required: Yes

Request Body

The request accepts the following data in JSON format.

[pipelineActivities](#)

A list of PipelineActivity objects. Activities perform transformations on your messages, such as removing, renaming or adding message attributes; filtering messages based on attribute values; invoking your Lambda functions on messages for advanced processing; or performing mathematical transformations to normalize device data.

The list can be 2-25 PipelineActivity objects and must contain both a channel and a datastore activity. Each entry in the list must contain only one activity. For example:

```
pipelineActivities = [ { "channel": { ... } }, { "lambda": { ... } }, ... ]
```

Type: Array of [PipelineActivity](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalFailureException

There was an internal failure.

HTTP Status Code: 500

InvalidRequestException

The request was not valid.

HTTP Status Code: 400

LimitExceededException

The command caused an internal limit to be exceeded.

HTTP Status Code: 410

ResourceNotFoundException

A resource with the specified name could not be found.

HTTP Status Code: 404

ServiceUnavailableException

The service is temporarily unavailable.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS IoT Analytics API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AddAttributesActivity](#)
- [BatchPutMessageErrorEntry](#)
- [Channel](#)
- [ChannelActivity](#)
- [ChannelMessages](#)
- [ChannelStatistics](#)
- [ChannelStorage](#)
- [ChannelStorageSummary](#)
- [ChannelSummary](#)
- [Column](#)
- [ContainerDatasetAction](#)
- [CustomerManagedChannelS3Storage](#)
- [CustomerManagedChannelS3StorageSummary](#)
- [CustomerManagedDatastoreS3Storage](#)
- [CustomerManagedDatastoreS3StorageSummary](#)
- [Dataset](#)
- [DatasetAction](#)
- [DatasetActionSummary](#)
- [DatasetContentDeliveryDestination](#)
- [DatasetContentDeliveryRule](#)

- [DatasetContentStatus](#)
- [DatasetContentSummary](#)
- [DatasetContentVersionValue](#)
- [DatasetEntry](#)
- [DatasetSummary](#)
- [DatasetTrigger](#)
- [Datastore](#)
- [DatastoreActivity](#)
- [DatastorelotSiteWiseMultiLayerStorage](#)
- [DatastorelotSiteWiseMultiLayerStorageSummary](#)
- [DatastorePartition](#)
- [DatastorePartitions](#)
- [DatastoreStatistics](#)
- [DatastoreStorage](#)
- [DatastoreStorageSummary](#)
- [DatastoreSummary](#)
- [DeltaTime](#)
- [DeltaTimeSessionWindowConfiguration](#)
- [DeviceRegistryEnrichActivity](#)
- [DeviceShadowEnrichActivity](#)
- [EstimatedResourceSize](#)
- [FileFormatConfiguration](#)
- [FilterActivity](#)
- [GlueConfiguration](#)
- [IoEventsDestinationConfiguration](#)
- [IoSiteWiseCustomerManagedDatastoreS3Storage](#)
- [IoSiteWiseCustomerManagedDatastoreS3StorageSummary](#)
- [JsonConfiguration](#)
- [LambdaActivity](#)
- [LateDataRule](#)

- [LateDataRuleConfiguration](#)
- [LoggingOptions](#)
- [MathActivity](#)
- [Message](#)
- [OutputFileUriValue](#)
- [ParquetConfiguration](#)
- [Partition](#)
- [Pipeline](#)
- [PipelineActivity](#)
- [PipelineSummary](#)
- [QueryFilter](#)
- [RemoveAttributesActivity](#)
- [ReprocessingSummary](#)
- [ResourceConfiguration](#)
- [RetentionPeriod](#)
- [S3DestinationConfiguration](#)
- [Schedule](#)
- [SchemaDefinition](#)
- [SelectAttributesActivity](#)
- [ServiceManagedChannelS3Storage](#)
- [ServiceManagedChannelS3StorageSummary](#)
- [ServiceManagedDatastoreS3Storage](#)
- [ServiceManagedDatastoreS3StorageSummary](#)
- [SqlQueryDatasetAction](#)
- [Tag](#)
- [TimestampPartition](#)
- [TriggeringDataset](#)
- [Variable](#)
- [VersioningConfiguration](#)

AddAttributesActivity

An activity that adds other attributes based on existing attributes in the message.

Contents

attributes

A list of 1-50 AttributeNameMapping objects that map an existing attribute to a new attribute.

 **Note**

The existing attributes remain in the message, so if you want to remove the originals, use RemoveAttributeActivity.

Type: String to string map

Map Entries: Maximum number of 50 items.

Key Length Constraints: Minimum length of 1. Maximum length of 256.

Value Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

name

The name of the addAttributes activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BatchPutMessageErrorEntry

Contains informations about errors.

Contents

errorCode

The code associated with the error.

Type: String

Required: No

errorMessage

The message associated with the error.

Type: String

Required: No

messageId

The ID of the message that caused the error. See the value corresponding to the messageId key in the message object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Channel

A collection of data from an MQTT topic. Channels archive the raw, unprocessed messages before publishing the data to a pipeline.

Contents

arn

The ARN of the channel.

Type: String

Required: No

creationTime

When the channel was created.

Type: Timestamp

Required: No

lastMessageArrivalTime

The last time when a new message arrived in the channel.

AWS IoT Analytics updates this value at most once per minute for one channel. Hence, the lastMessageArrivalTime value is an approximation.

This feature only applies to messages that arrived in the data store after October 23, 2020.

Type: Timestamp

Required: No

lastUpdateTime

When the channel was last updated.

Type: Timestamp

Required: No

name

The name of the channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))([a-zA-Z0-9_]+\$)

Required: No

retentionPeriod

How long, in days, message data is kept for the channel.

Type: [RetentionPeriod](#) object

Required: No

status

The status of the channel.

Type: String

Valid Values: CREATING | ACTIVE | DELETING

Required: No

storage

Where channel data is stored. You can choose one of serviceManagedS3 or customerManagedS3 storage. If not specified, the default is serviceManagedS3. You can't change this storage option after the channel is created.

Type: [ChannelStorage](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelActivity

The activity that determines the source of the messages to be processed.

Contents

channelName

The name of the channel from which the messages are processed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(?!_{2}))(^[\wedge-zA-Z0-9_]+\$)`

Required: Yes

name

The name of the channel activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelMessages

Specifies one or more sets of channel messages.

Contents

s3Paths

Specifies one or more keys that identify the Amazon Simple Storage Service (Amazon S3) objects that save your channel messages.

You must use the full path for the key.

Example path: channel/mychannel/__dt=2020-02-29
00:00:00/1582940490000_1582940520000_123456789012_mychannel_0_2118.0.json.gz

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: ^[a-zA-Z0-9/_!()'{}{}*\s\.\-\=\:\:]+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelStatistics

Statistics information about the channel.

Contents

size

The estimated size of the channel.

Type: [EstimatedResourceSize object](#)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelStorage

Where channel data is stored. You may choose one of `serviceManagedS3`, `customerManagedS3` storage. If not specified, the default is `serviceManagedS3`. This can't be changed after creation of the channel.

Contents

customerManagedS3

Used to store channel data in an S3 bucket that you manage. If customer managed storage is selected, the `retentionPeriod` parameter is ignored. You can't change the choice of S3 storage after the data store is created.

Type: [CustomerManagedChannelS3Storage](#) object

Required: No

serviceManagedS3

Used to store channel data in an S3 bucket managed by AWS IoT Analytics. You can't change the choice of S3 storage after the data store is created.

Type: [ServiceManagedChannelS3Storage](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelStorageSummary

Where channel data is stored.

Contents

customerManagedS3

Used to store channel data in an S3 bucket that you manage.

Type: [CustomerManagedChannelS3StorageSummary](#) object

Required: No

serviceManagedS3

Used to store channel data in an S3 bucket managed by AWS IoT Analytics.

Type: [ServiceManagedChannelS3StorageSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelSummary

A summary of information about a channel.

Contents

channelName

The name of the channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(!_{2}))([a-zA-Z0-9_]+$)`

Required: No

channelStorage

Where channel data is stored.

Type: [ChannelStorageSummary](#) object

Required: No

creationTime

When the channel was created.

Type: Timestamp

Required: No

lastMessageArrivalTime

The last time when a new message arrived in the channel.

AWS IoT Analytics updates this value at most once per minute for one channel. Hence, the `lastMessageArrivalTime` value is an approximation.

This feature only applies to messages that arrived in the data store after October 23, 2020.

Type: Timestamp

Required: No

lastUpdateTime

The last time the channel was updated.

Type: Timestamp

Required: No

status

The status of the channel.

Type: String

Valid Values: CREATING | ACTIVE | DELETING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Column

Contains information about a column that stores your data.

Contents

name

The name of the column.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[A-Za-z_]([A-Za-z0-9]* | [A-Za-z0-9][A-Za-z0-9_]*)\$

Required: Yes

type

The type of data. For more information about the supported data types, see [Common data types](#) in the *AWS Glue Developer Guide*.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 131072.

Pattern: ^[\u0020-\uD7FF\uE000-\uFFFF\uD800\uDC00-\uDBFF\uDFFF\t]*\$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ContainerDatasetAction

Information required to run the containerAction to produce dataset contents.

Contents

executionRoleArn

The ARN of the role that gives permission to the system to access required resources to run the containerAction. This includes, at minimum, permission to retrieve the dataset contents that are the input to the containerized application.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

image

The ARN of the Docker container stored in your account. The Docker container contains an application and required support libraries and is used to generate dataset contents.

Type: String

Length Constraints: Maximum length of 255.

Required: Yes

resourceConfiguration

Configuration of the resource that executes the containerAction.

Type: [ResourceConfiguration](#) object

Required: Yes

variables

The values of variables used in the context of the execution of the containerized application (basically, parameters passed to the application). Each variable must have a name and a value given by one of stringValue, datasetContentVersionValue, or outputFileUriValue.

Type: Array of [Variable](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomerManagedChannelS3Storage

Used to store channel data in an S3 bucket that you manage. If customer-managed storage is selected, the `retentionPeriod` parameter is ignored. You can't change the choice of S3 storage after the data store is created.

Contents

bucket

The name of the S3 bucket in which channel data is stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: ^[a-zA-Z0-9.\-_]*\$

Required: Yes

roleArn

The ARN of the role that grants AWS IoT Analytics permission to interact with your Amazon S3 resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

keyPrefix

(Optional) The prefix used to create the keys of the channel data objects. Each object in an S3 bucket has a key that is its unique identifier in the bucket. Each object in a bucket has exactly one key. The prefix must end with a forward slash (/).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9!_.*'()'{}:-]*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomerManagedChannelS3StorageSummary

Used to store channel data in an S3 bucket that you manage.

Contents

bucket

The name of the S3 bucket in which channel data is stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: ^[a-zA-Z0-9.\-_]*\$

Required: No

keyPrefix

(Optional) The prefix used to create the keys of the channel data objects. Each object in an S3 bucket has a key that is its unique identifier within the bucket (each object in a bucket has exactly one key). The prefix must end with a forward slash (/).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9!_.*'()'{}:-]*\$

Required: No

roleArn

The ARN of the role that grants AWS IoT Analytics permission to interact with your Amazon S3 resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomerManagedDatastoreS3Storage

S3-customer-managed; When you choose customer-managed storage, the `retentionPeriod` parameter is ignored. You can't change the choice of Amazon S3 storage after your data store is created.

Contents

bucket

The name of the Amazon S3 bucket where your data is stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: `^[a-zA-Z0-9.\-_]*$`

Required: Yes

roleArn

The ARN of the role that grants AWS IoT Analytics permission to interact with your Amazon S3 resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

keyPrefix

(Optional) The prefix used to create the keys of the data store data objects. Each object in an Amazon S3 bucket has a key that is its unique identifier in the bucket. Each object in a bucket has exactly one key. The prefix must end with a forward slash (/).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `^[a-zA-Z0-9!_.*'()/{}:;-]*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomerManagedDatastoreS3StorageSummary

Contains information about the data store that you manage.

Contents

bucket

The name of the Amazon S3 bucket where your data is stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: ^[a-zA-Z0-9.\-_]*\$

Required: No

keyPrefix

(Optional) The prefix used to create the keys of the data store data objects. Each object in an Amazon S3 bucket has a key that is its unique identifier in the bucket. Each object in a bucket has exactly one key. The prefix must end with a forward slash (/).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9!_.*'()'{}:-]*\$

Required: No

roleArn

The ARN of the role that grants AWS IoT Analytics permission to interact with your Amazon S3 resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Dataset

Information about a dataset.

Contents

actions

The DatasetAction objects that automatically create the dataset contents.

Type: Array of [DatasetAction](#) objects

Array Members: Fixed number of 1 item.

Required: No

arn

The ARN of the dataset.

Type: String

Required: No

contentDeliveryRules

When dataset contents are created they are delivered to destinations specified here.

Type: Array of [DatasetContentDeliveryRule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

creationTime

When the dataset was created.

Type: Timestamp

Required: No

lastUpdateTime

The last time the dataset was updated.

Type: Timestamp

Required: No

lateDataRules

A list of data rules that send notifications to CloudWatch, when data arrives late. To specify lateDataRules, the dataset must use a [DeltaTimer](#) filter.

Type: Array of [LateDataRule](#) objects

Array Members: Fixed number of 1 item.

Required: No

name

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(!_{2}))([a-zA-Z0-9_]+$)`

Required: No

retentionPeriod

Optional. How long, in days, message data is kept for the dataset.

Type: [RetentionPeriod](#) object

Required: No

status

The status of the dataset.

Type: String

Valid Values: CREATING | ACTIVE | DELETING

Required: No

triggers

The DatasetTrigger objects that specify when the dataset is automatically updated.

Type: Array of [DatasetTrigger](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

versioningConfiguration

Optional. How many versions of dataset contents are kept. If not specified or set to null, only the latest version plus the latest succeeded version (if they are different) are kept for the time period specified by the `retentionPeriod` parameter. For more information, see [Keeping Multiple Versions of AWS IoT Analytics datasets](#) in the *AWS IoT Analytics User Guide*.

Type: [VersioningConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetAction

A DatasetAction object that specifies how dataset contents are automatically created.

Contents

actionName

The name of the dataset action by which dataset contents are automatically created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_]+\$

Required: No

containerAction

Information that allows the system to run a containerized application to create the dataset contents. The application must be in a Docker container along with any required support libraries.

Type: [ContainerDatasetAction](#) object

Required: No

queryAction

An SqlQueryDatasetAction object that uses an SQL query to automatically create dataset contents.

Type: [SqlQueryDatasetAction](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetActionSummary

Information about the action that automatically creates the dataset's contents.

Contents

actionName

The name of the action that automatically creates the dataset's contents.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_]+\$

Required: No

actionType

The type of action by which the dataset's contents are automatically created.

Type: String

Valid Values: QUERY | CONTAINER

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetContentDeliveryDestination

The destination to which dataset contents are delivered.

Contents

iotEventsDestinationConfiguration

Configuration information for delivery of dataset contents to AWS IoT Events.

Type: [IoTEventsDestinationConfiguration](#) object

Required: No

s3DestinationConfiguration

Configuration information for delivery of dataset contents to Amazon S3.

Type: [S3DestinationConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetContentDeliveryRule

When dataset contents are created, they are delivered to destination specified here.

Contents

destination

The destination to which dataset contents are delivered.

Type: [DatasetContentDeliveryDestination](#) object

Required: Yes

entryName

The name of the dataset content delivery rules entry.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetContentStatus

The state of the dataset contents and the reason they are in this state.

Contents

reason

The reason the dataset contents are in this state.

Type: String

Required: No

state

The state of the dataset contents. Can be one of READY, CREATING, SUCCEEDED, or FAILED.

Type: String

Valid Values: CREATING | SUCCEEDED | FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetContentSummary

Summary information about dataset contents.

Contents

completionTime

The time the dataset content status was updated to SUCCEEDED or FAILED.

Type: Timestamp

Required: No

creationTime

The actual time the creation of the dataset contents was started.

Type: Timestamp

Required: No

scheduleTime

The time the creation of the dataset contents was scheduled to start.

Type: Timestamp

Required: No

status

The status of the dataset contents.

Type: [DatasetContentStatus](#) object

Required: No

version

The version of the dataset contents.

Type: String

Length Constraints: Minimum length of 7. Maximum length of 36.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetContentVersionValue

The dataset whose latest contents are used as input to the notebook or application.

Contents

datasetName

The name of the dataset whose latest contents are used as input to the notebook or application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(?!_{2}))(^[a-zA-Z0-9_]+$)`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetEntry

The reference to a dataset entry.

Contents

dataURI

The presigned URI of the dataset item.

Type: String

Required: No

entryName

The name of the dataset item.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetSummary

A summary of information about a dataset.

Contents

actions

A list of DataActionSummary objects.

Type: Array of [DatasetActionSummary](#) objects

Array Members: Fixed number of 1 item.

Required: No

creationTime

The time the dataset was created.

Type: Timestamp

Required: No

datasetName

The name of the dataset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: $(^(!\{2\}))(^[a-zA-Z0-9_]+\$)$

Required: No

lastUpdateTime

The last time the dataset was updated.

Type: Timestamp

Required: No

status

The status of the dataset.

Type: String

Valid Values: CREATING | ACTIVE | DELETING

Required: No

triggers

A list of triggers. A trigger causes dataset content to be populated at a specified time interval or when another dataset is populated. The list of triggers can be empty or contain up to five `DataSetTrigger` objects

Type: Array of [DatasetTrigger](#) objects

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatasetTrigger

The DatasetTrigger that specifies when the dataset is automatically updated.

Contents

dataset

The dataset whose content creation triggers the creation of this dataset's contents.

Type: [TriggeringDataset](#) object

Required: No

schedule

The Schedule when the trigger is initiated.

Type: [Schedule](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Datastore

Information about a data store.

Contents

arn

The ARN of the data store.

Type: String

Required: No

creationTime

When the data store was created.

Type: Timestamp

Required: No

datastorePartitions

Contains information about the partition dimensions in a data store.

Type: [DatastorePartitions](#) object

Required: No

fileFormatConfiguration

Contains the configuration information of file formats. AWS IoT Analytics data stores support JSON and [Parquet](#).

The default file format is JSON. You can specify only one format.

You can't change the file format after you create the data store.

Type: [FileFormatConfiguration](#) object

Required: No

lastMessageArrivalTime

The last time when a new message arrived in the data store.

AWS IoT Analytics updates this value at most once per minute for Amazon Simple Storage Service one data store. Hence, the `lastMessageArrivalTime` value is an approximation.

This feature only applies to messages that arrived in the data store after October 23, 2020.

Type: `Timestamp`

Required: No

lastUpdateTime

The last time the data store was updated.

Type: `Timestamp`

Required: No

name

The name of the data store.

Type: `String`

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(!_{2}))([a-zA-Z0-9_]+$)`

Required: No

retentionPeriod

How long, in days, message data is kept for the data store. When `customerManagedS3` storage is selected, this parameter is ignored.

Type: [RetentionPeriod](#) object

Required: No

status

The status of a data store:

`CREATING`

The data store is being created.

ACTIVE

The data store has been created and can be used.

DELETING

The data store is being deleted.

Type: String

Valid Values: CREATING | ACTIVE | DELETING

Required: No

storage

Where data in a data store is stored.. You can choose serviceManagedS3 storage, customerManagedS3 storage, or iotSiteWiseMultiLayerStorage storage. The default is serviceManagedS3. You can't change the choice of Amazon S3 storage after your data store is created.

Type: [DatastoreStorage](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreActivity

The datastore activity that specifies where to store the processed data.

Contents

datastoreName

The name of the data store where processed messages are stored.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(!_{2}))(^[a-zA-Z0-9_]+$)`

Required: Yes

name

The name of the datastore activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreIoTSiteWiseMultiLayerStorage

Used to store data used by AWS IoT SiteWise in an Amazon S3 bucket that you manage. You can't change the choice of Amazon S3 storage after your data store is created.

Contents

customerManagedS3Storage

Used to store data used by AWS IoT SiteWise in an Amazon S3 bucket that you manage.

Type: [IoTSiteWiseCustomerManagedDatastoreS3Storage](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreIoTSiteWiseMultiLayerStorageSummary

Contains information about the data store that you manage, which stores data used by AWS IoT SiteWise.

Contents

customerManagedS3Storage

Used to store data used by AWS IoT SiteWise in an Amazon S3 bucket that you manage.

Type: [IoTSiteWiseCustomerManagedDatastoreS3StorageSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastorePartition

A single dimension to partition a data store. The dimension must be an [AttributePartition](#) or a [TimestampPartition](#).

Contents

attributePartition

A partition dimension defined by an attributeName.

Type: [Partition](#) object

Required: No

timestampPartition

A partition dimension defined by a timestamp attribute.

Type: [TimestampPartition](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastorePartitions

Contains information about the partition dimensions in a data store.

Contents

partitions

A list of partition dimensions in a data store.

Type: Array of [DatastorePartition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 25 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreStatistics

Statistical information about the data store.

Contents

size

The estimated size of the data store.

Type: [EstimatedResourceSize](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreStorage

Where data in a data store is stored.. You can choose serviceManagedS3 storage, customerManagedS3 storage, or iotSiteWiseMultiLayerStorage storage. The default is serviceManagedS3. You can't change the choice of Amazon S3 storage after your data store is created.

Contents

customerManagedS3

S3-customer-managed; When you choose customer-managed storage, the retentionPeriod parameter is ignored. You can't change the choice of Amazon S3 storage after your data store is created.

Type: [CustomerManagedDatastoreS3Storage](#) object

Required: No

iotSiteWiseMultiLayerStorage

Used to store data used by AWS IoT SiteWise in an Amazon S3 bucket that you manage. You can't change the choice of Amazon S3 storage after your data store is created.

Type: [DatastoreiotSiteWiseMultiLayerStorage](#) object

Required: No

serviceManagedS3

Used to store data in an Amazon S3 bucket managed by AWS IoT Analytics. You can't change the choice of Amazon S3 storage after your data store is created.

Type: [ServiceManagedDatastoreS3Storage](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreStorageSummary

Contains information about your data store.

Contents

customerManagedS3

Used to store data in an Amazon S3 bucket managed by AWS IoT Analytics.

Type: [CustomerManagedDatastoreS3StorageSummary](#) object

Required: No

iotSiteWiseMultiLayerStorage

Used to store data used by AWS IoT SiteWise in an Amazon S3 bucket that you manage.

Type: [DatastoreIoTSiteWiseMultiLayerStorageSummary](#) object

Required: No

serviceManagedS3

Used to store data in an Amazon S3 bucket managed by AWS IoT Analytics.

Type: [ServiceManagedDatastoreS3StorageSummary](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatastoreSummary

A summary of information about a data store.

Contents

creationTime

When the data store was created.

Type: Timestamp

Required: No

datastoreName

The name of the data store.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: $(^(!_{\{2\}})(^{\text{[a-zA-Z0-9]}})+$)$

Required: No

datastorePartitions

Contains information about the partition dimensions in a data store.

Type: [DatastorePartitions](#) object

Required: No

datastoreStorage

Where data in a data store is stored.

Type: [DatastoreStorageSummary](#) object

Required: No

fileFormatType

The file format of the data in the data store.

Type: String

Valid Values: JSON | PARQUET

Required: No

lastMessageArrivalTime

The last time when a new message arrived in the data store.

AWS IoT Analytics updates this value at most once per minute for Amazon Simple Storage Service one data store. Hence, the `lastMessageArrivalTime` value is an approximation.

This feature only applies to messages that arrived in the data store after October 23, 2020.

Type: Timestamp

Required: No

lastUpdateTime

The last time the data store was updated.

Type: Timestamp

Required: No

status

The status of the data store.

Type: String

Valid Values: CREATING | ACTIVE | DELETING

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

DeltaTime

Used to limit data to that which has arrived since the last execution of the action.

Contents

offsetSeconds

The number of seconds of estimated in-flight lag time of message data. When you create dataset contents using message data from a specified timeframe, some message data might still be in flight when processing begins, and so do not arrive in time to be processed. Use this field to make allowances for the in flight time of your message data, so that data not processed from a previous timeframe is included with the next timeframe. Otherwise, missed message data would be excluded from processing during the next timeframe too, because its timestamp places it within the previous timeframe.

Type: Integer

Required: Yes

timeExpression

An expression by which the time of the message data might be determined. This can be the name of a timestamp field or a SQL expression that is used to derive the time the message data was generated.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeltaTimeSessionWindowConfiguration

A structure that contains the configuration information of a delta time session window.

[DeltaTime](#) specifies a time interval. You can use DeltaTime to create dataset contents with data that has arrived in the data store since the last execution. For an example of DeltaTime, see [Creating a SQL dataset with a delta window \(CLI\)](#) in the *AWS IoT Analytics User Guide*.

Contents

timeoutInMinutes

A time interval. You can use timeoutInMinutes so that AWS IoT Analytics can batch up late data notifications that have been generated since the last execution. AWS IoT Analytics sends one batch of notifications to Amazon CloudWatch Events at one time.

For more information about how to write a timestamp expression, see [Date and Time Functions and Operators](#), in the *Presto 0.172 Documentation*.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 60.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceRegistryEnrichActivity

An activity that adds data from the AWS IoT device registry to your message.

Contents

attribute

The name of the attribute that is added to the message.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

name

The name of the deviceRegistryEnrich activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

roleArn

The ARN of the role that allows access to the device's registry information.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

thingName

The name of the IoT device whose registry information is added to the message.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeviceShadowEnrichActivity

An activity that adds information from the AWS IoT Device Shadow service to a message.

Contents

attribute

The name of the attribute that is added to the message.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

name

The name of the deviceShadowEnrich activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

roleArn

The ARN of the role that allows access to the device's shadow.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

thingName

The name of the IoT device whose shadow information is added to the message.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EstimatedResourceSize

The estimated size of the resource.

Contents

estimatedOn

The time when the estimate of the size of the resource was made.

Type: Timestamp

Required: No

estimatedSizeInBytes

The estimated size of the resource, in bytes.

Type: Double

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FileFormatConfiguration

Contains the configuration information of file formats. AWS IoT Analytics data stores support JSON and [Parquet](#).

The default file format is JSON. You can specify only one format.

You can't change the file format after you create the data store.

Contents

jsonConfiguration

Contains the configuration information of the JSON format.

Type: [JsonConfiguration](#) object

Required: No

parquetConfiguration

Contains the configuration information of the Parquet format.

Type: [ParquetConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FilterActivity

An activity that filters a message based on its attributes.

Contents

filter

An expression that looks like a SQL WHERE clause that must return a Boolean value. Messages that satisfy the condition are passed to the next activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

name

The name of the filter activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GlueConfiguration

Configuration information for coordination with AWS Glue, a fully managed extract, transform and load (ETL) service.

Contents

databaseName

The name of the database in your AWS Glue Data Catalog in which the table is located. An AWS Glue Data Catalog database contains metadata tables.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*

Required: Yes

tableName

The name of the table in your AWS Glue Data Catalog that is used to perform the ETL operations. An AWS Glue Data Catalog table contains partitioned data and descriptions of data sources and targets.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 150.

Pattern: [\u0020-\uD7FF\uE000-\uFFFD\uD800\uDC00-\uDBFF\uDFFF\t]*

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

IoTEventsDestinationConfiguration

Configuration information for delivery of dataset contents to AWS IoT Events.

Contents

inputName

The name of the AWS IoT Events input to which dataset contents are delivered.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z][a-zA-Z0-9_]*\$

Required: Yes

roleArn

The ARN of the role that grants AWS IoT Analytics permission to deliver dataset contents to an AWS IoT Events input.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IoTSiteWiseCustomerManagedDatastoreS3Storage

Used to store data used by AWS IoT SiteWise in an Amazon S3 bucket that you manage. You can't change the choice of Amazon S3 storage after your data store is created.

Contents

bucket

The name of the Amazon S3 bucket where your data is stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: ^[a-zA-Z0-9.\-_]*\$

Required: Yes

keyPrefix

(Optional) The prefix used to create the keys of the data store data objects. Each object in an Amazon S3 bucket has a key that is its unique identifier in the bucket. Each object in a bucket has exactly one key. The prefix must end with a forward slash (/).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9!_.*'()'{}:-]*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IoTSiteWiseCustomerManagedDatastoreS3StorageSummary

Contains information about the data store that you manage, which stores data used by AWS IoT SiteWise.

Contents

bucket

The name of the Amazon S3 bucket where your data is stored.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: ^[a-zA-Z0-9.\-_]*\$

Required: No

keyPrefix

(Optional) The prefix used to create the keys of the data store data objects. Each object in an Amazon S3 bucket has a key that is its unique identifier in the bucket. Each object in a bucket has exactly one key. The prefix must end with a forward slash (/).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9!_.*'()'{}:-]*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JsonConfiguration

Contains the configuration information of the JSON format.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LambdaActivity

An activity that runs a Lambda function to modify the message.

Contents

batchSize

The number of messages passed to the Lambda function for processing.

The Lambda function must be able to process all of these messages within five minutes, which is the maximum timeout duration for Lambda functions.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: Yes

lambdaName

The name of the Lambda function that is run on the message.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^[a-zA-Z0-9_-]+\$

Required: Yes

name

The name of the lambda activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LateDataRule

A structure that contains the name and configuration information of a late data rule.

Contents

ruleConfiguration

The information needed to configure the late data rule.

Type: [LateDataRuleConfiguration](#) object

Required: Yes

ruleName

The name of the late data rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_]+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LateDataRuleConfiguration

The information needed to configure a delta time session window.

Contents

deltaTimeSessionWindowConfiguration

The information needed to configure a delta time session window.

Type: [DeltaTimeSessionWindowConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LoggingOptions

Information about logging options.

Contents

enabled

If true, logging is enabled for AWS IoT Analytics.

Type: Boolean

Required: Yes

level

The logging level. Currently, only ERROR is supported.

Type: String

Valid Values: ERROR

Required: Yes

roleArn

The ARN of the role that grants permission to AWS IoT Analytics to perform logging.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

MathActivity

An activity that computes an arithmetic expression using the message's attributes.

Contents

attribute

The name of the attribute that contains the result of the math operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

math

An expression that uses one or more existing attributes and must return an integer value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

name

The name of the math activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Message

Information about a message.

Contents

messageId

The ID you want to assign to the message. Each messageId must be unique within each batch sent.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

payload

The payload of the message. This can be a JSON string or a base64-encoded string representing binary data, in which case you must decode it by means of a pipeline activity.

Type: Base64-encoded binary data object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutputFileUriValue

The value of the variable as a structure that specifies an output file URI.

Contents

fileName

The URI of the location where dataset contents are stored, usually the URI of a file in an S3 bucket.

Type: String

Pattern: [\w\.-]{1,255}

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ParquetConfiguration

Contains the configuration information of the Parquet format.

Contents

schemaDefinition

Information needed to define a schema.

Type: [SchemaDefinition](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Partition

A partition dimension defined by an attribute.

Contents

attributeName

The name of the attribute that defines a partition dimension.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_]+\$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Pipeline

Contains information about a pipeline.

Contents

activities

The activities that perform transformations on the messages.

Type: Array of [PipelineActivity](#) objects

Array Members: Minimum number of 1 item. Maximum number of 25 items.

Required: No

arn

The ARN of the pipeline.

Type: String

Required: No

creationTime

When the pipeline was created.

Type: Timestamp

Required: No

lastUpdateTime

The last time the pipeline was updated.

Type: Timestamp

Required: No

name

The name of the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\\$)

Required: No

reprocessingSummaries

A summary of information about the pipeline reprocessing.

Type: Array of [ReprocessingSummary](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PipelineActivity

An activity that performs a transformation on a message.

Contents

addAttributes

Adds other attributes based on existing attributes in the message.

Type: [AddAttributesActivity](#) object

Required: No

channel

Determines the source of the messages to be processed.

Type: [ChannelActivity](#) object

Required: No

datastore

Specifies where to store the processed message data.

Type: [DatastoreActivity](#) object

Required: No

deviceRegistryEnrich

Adds data from the AWS IoT device registry to your message.

Type: [DeviceRegistryEnrichActivity](#) object

Required: No

deviceShadowEnrich

Adds information from the AWS IoT Device Shadow service to a message.

Type: [DeviceShadowEnrichActivity](#) object

Required: No

filter

Filters a message based on its attributes.

Type: [FilterActivity](#) object

Required: No

lambda

Runs a Lambda function to modify the message.

Type: [LambdaActivity](#) object

Required: No

math

Computes an arithmetic expression using the message's attributes and adds it to the message.

Type: [MathActivity](#) object

Required: No

removeAttributes

Removes attributes from a message.

Type: [RemoveAttributesActivity](#) object

Required: No

selectAttributes

Used to create a new message using only the specified attributes from the original message.

Type: [SelectAttributesActivity](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PipelineSummary

A summary of information about a pipeline.

Contents

creationTime

When the pipeline was created.

Type: Timestamp

Required: No

lastUpdateTime

When the pipeline was last updated.

Type: Timestamp

Required: No

pipelineName

The name of the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: (^(?!_{2}))(^[a-zA-Z0-9_]+\$)

Required: No

reprocessingSummaries

A summary of information about the pipeline reprocessing.

Type: Array of [ReprocessingSummary](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueryFilter

Information that is used to filter message data, to segregate it according to the timeframe in which it arrives.

Contents

deltaTime

Used to limit data to that which has arrived since the last execution of the action.

Type: [DeltaTime](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RemoveAttributesActivity

An activity that removes attributes from a message.

Contents

attributes

A list of 1-50 attributes to remove from the message.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

name

The name of the `removeAttributes` activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReprocessingSummary

Information about pipeline reprocessing.

Contents

creationTime

The time the pipeline reprocessing was created.

Type: Timestamp

Required: No

id

The reprocessingId returned by StartPipelineReprocessing.

Type: String

Required: No

status

The status of the pipeline reprocessing.

Type: String

Valid Values: RUNNING | SUCCEEDED | CANCELLED | FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceConfiguration

The configuration of the resource used to execute the containerAction.

Contents

computeType

The type of the compute resource used to execute the containerAction. Possible values are: ACU_1 (vCPU=4, memory=16 GiB) or ACU_2 (vCPU=8, memory=32 GiB).

Type: String

Valid Values: ACU_1 | ACU_2

Required: Yes

volumeSizeInGB

The size, in GB, of the persistent storage available to the resource instance used to execute the containerAction (min: 1, max: 50).

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RetentionPeriod

How long, in days, message data is kept.

Contents

numberOfDays

The number of days that message data is kept. The `unlimited` parameter must be false.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

unlimited

If true, message data is kept indefinitely.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3DestinationConfiguration

Configuration information for delivery of dataset contents to Amazon Simple Storage Service (Amazon S3).

Contents

bucket

The name of the S3 bucket to which dataset contents are delivered.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Pattern: ^[a-zA-Z0-9.\-_]*\$

Required: Yes

key

The key of the dataset contents object in an S3 bucket. Each object has a key that is a unique identifier. Each object has exactly one key.

You can create a unique key with the following options:

- Use !{iotanalytics:scheduleTime} to insert the time of a scheduled SQL query run.
- Use !{iotanalytics:versionId} to insert a unique hash that identifies a dataset content.
- Use !{iotanalytics:creationTime} to insert the creation time of a dataset content.

The following example creates a unique key for a CSV file: dataset/mydataset/!{iotanalytics:scheduleTime}/!{iotanalytics:versionId}.csv

Note

If you don't use !{iotanalytics:versionId} to specify the key, you might get duplicate keys. For example, you might have two dataset contents with the same scheduleTime but different versionIds. This means that one dataset content overwrites the other.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^[a-zA-Z0-9!_.*'(){}:-]*\$

Required: Yes

roleArn

The ARN of the role that grants AWS IoT Analytics permission to interact with your Amazon S3 and AWS Glue resources.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

glueConfiguration

Configuration information for coordination with AWS Glue, a fully managed extract, transform and load (ETL) service.

Type: [GlueConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Schedule

The schedule for when to trigger an update.

Contents

expression

The expression that defines when to trigger an update. For more information, see [Schedule Expressions for Rules in the Amazon CloudWatch Events User Guide](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SchemaDefinition

Information needed to define a schema.

Contents

columns

Specifies one or more columns that store your data.

Each schema can have up to 100 columns. Each column can have up to 100 nested types.

Type: Array of [Column](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SelectAttributesActivity

Used to create a new message using only the specified attributes from the original message.

Contents

attributes

A list of the attributes to select from the message.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

name

The name of the selectAttributes activity.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

next

The next activity in the pipeline.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceManagedChannelS3Storage

Used to store channel data in an S3 bucket managed by AWS IoT Analytics. You can't change the choice of S3 storage after the data store is created.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceManagedChannelS3StorageSummary

Used to store channel data in an S3 bucket managed by AWS IoT Analytics.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceManagedDatastoreS3Storage

Used to store data in an Amazon S3 bucket managed by AWS IoT Analytics. You can't change the choice of Amazon S3 storage after your data store is created.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceManagedDatastoreS3StorageSummary

Contains information about the data store that is managed by AWS IoT Analytics.

Contents

The members of this exception structure are context-dependent.

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SqlQueryDatasetAction

The SQL query to modify the message.

Contents

sqlQuery

A SQL query string.

Type: String

Required: Yes

filters

Prefilters applied to message data.

Type: Array of [QueryFilter](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1 item.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A set of key-value pairs that are used to manage the resource.

Contents

key

The tag's key.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

value

The tag's value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimestampPartition

A partition dimension defined by a timestamp attribute.

Contents

attributeName

The attribute name of the partition defined by a timestamp.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[a-zA-Z0-9_]+\$

Required: Yes

timestampFormat

The timestamp format of a partition defined by a timestamp. The default format is seconds since epoch (January 1, 1970 at midnight UTC time).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: ^[a-zA-Z0-9\s\[\\]_, . ' /:-]*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TriggeringDataset

Information about the dataset whose content generation triggers the new dataset content generation.

Contents

name

The name of the dataset whose content generation triggers the new dataset content generation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `(^(?!_{2}))(^[a-zA-Z0-9_]+\$)`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Variable

An instance of a variable to be passed to the containerAction execution. Each variable must have a name and a value given by one of stringValue, datasetContentVersionValue, or outputFileUriValue.

Contents

name

The name of the variable.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

datasetContentVersionValue

The value of the variable as a structure that specifies a dataset content version.

Type: [DatasetContentVersionValue](#) object

Required: No

doubleValue

The value of the variable as a double (numeric).

Type: Double

Required: No

outputFileUriValue

The value of the variable as a structure that specifies an output file URI.

Type: [OutputFileUriValue](#) object

Required: No

stringValue

The value of the variable as a string.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VersioningConfiguration

Information about the versioning of dataset contents.

Contents

maxVersions

How many versions of dataset contents are kept. The `unlimited` parameter must be `false`.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

unlimited

If true, unlimited versions of dataset contents are kept.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400