



API Reference

Amazon Keyspaces (for Apache Cassandra)



API Version 2022-02-10

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon Keyspaces (for Apache Cassandra): API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateKeyspace	3
Request Syntax	3
Request Parameters	3
Response Syntax	4
Response Elements	4
Errors	5
See Also	5
CreateTable	7
Request Syntax	7
Request Parameters	10
Response Syntax	14
Response Elements	15
Errors	15
See Also	16
CreateType	17
Request Syntax	17
Request Parameters	17
Response Syntax	18
Response Elements	18
Errors	19
See Also	20
DeleteKeyspace	21
Request Syntax	21
Request Parameters	21
Response Elements	21
Errors	21
See Also	22
DeleteTable	24
Request Syntax	24
Request Parameters	24
Response Elements	25
Errors	25

See Also	26
DeleteType	27
Request Syntax	27
Request Parameters	27
Response Syntax	28
Response Elements	28
Errors	28
See Also	29
GetKeyspace	31
Request Syntax	31
Request Parameters	31
Response Syntax	31
Response Elements	32
Errors	33
See Also	34
GetTable	35
Request Syntax	35
Request Parameters	35
Response Syntax	36
Response Elements	37
Errors	40
See Also	41
GetTableAutoScalingSettings	42
Request Syntax	42
Request Parameters	42
Response Syntax	43
Response Elements	45
Errors	46
See Also	46
GetType	48
Request Syntax	48
Request Parameters	48
Response Syntax	49
Response Elements	49
Errors	51
See Also	52

ListKeyspaces	53
Request Syntax	53
Request Parameters	53
Response Syntax	54
Response Elements	54
Errors	54
See Also	55
ListTables	57
Request Syntax	57
Request Parameters	57
Response Syntax	58
Response Elements	58
Errors	59
See Also	59
ListTagsForResource	61
Request Syntax	61
Request Parameters	61
Response Syntax	62
Response Elements	62
Errors	63
See Also	63
ListTypes	65
Request Syntax	65
Request Parameters	65
Response Syntax	66
Response Elements	66
Errors	67
See Also	67
RestoreTable	69
Request Syntax	70
Request Parameters	71
Response Syntax	75
Response Elements	75
Errors	75
See Also	76
TagResource	78

Request Syntax	78
Request Parameters	78
Response Elements	79
Errors	79
See Also	80
UntagResource	81
Request Syntax	81
Request Parameters	81
Response Elements	82
Errors	82
See Also	83
UpdateKeyspace	84
Request Syntax	85
Request Parameters	85
Response Syntax	86
Response Elements	86
Errors	87
See Also	88
UpdateTable	89
Request Syntax	89
Request Parameters	91
Response Syntax	94
Response Elements	95
Errors	95
See Also	96
Data Types	97
AutoScalingPolicy	99
Contents	99
See Also	99
AutoScalingSettings	100
Contents	101
See Also	102
AutoScalingSpecification	103
Contents	103
See Also	103
CapacitySpecification	104

Contents	104
See Also	105
CapacitySpecificationSummary	106
Contents	106
See Also	107
CdcSpecification	108
Contents	108
See Also	109
CdcSpecificationSummary	110
Contents	110
See Also	110
ClientSideTimestamps	112
Contents	112
See Also	112
ClusteringKey	113
Contents	113
See Also	113
ColumnDefinition	114
Contents	114
See Also	114
Comment	115
Contents	115
See Also	115
EncryptionSpecification	116
Contents	116
See Also	117
FieldDefinition	118
Contents	118
See Also	118
KeyspaceSummary	119
Contents	119
See Also	120
PartitionKey	121
Contents	121
See Also	121
PointInTimeRecovery	122

Contents	122
See Also	122
PointInTimeRecoverySummary	123
Contents	123
See Also	123
ReplicaAutoScalingSpecification	124
Contents	124
See Also	124
ReplicaSpecification	125
Contents	125
See Also	126
ReplicaSpecificationSummary	127
Contents	127
See Also	128
ReplicationGroupStatus	129
Contents	129
See Also	129
ReplicationSpecification	131
Contents	131
See Also	131
SchemaDefinition	133
Contents	133
See Also	134
StaticColumn	135
Contents	135
See Also	135
TableSummary	136
Contents	136
See Also	137
Tag	138
Contents	138
See Also	138
TargetTrackingScalingPolicyConfiguration	140
Contents	140
See Also	141
TimeToLive	142

Contents	142
See Also	142
Service-specific Errors	143
AccessDeniedException	144
Contents	144
See Also	144
ConflictException	145
Contents	145
See Also	145
InternalServerError	146
Contents	146
See Also	146
ResourceNotFoundException	147
Contents	147
See Also	147
ServiceQuotaExceededException	148
Contents	148
See Also	148
ValidationException	149
Contents	149
See Also	149
Common Parameters	150
Common Errors	153

Welcome

Amazon Keyspaces (for Apache Cassandra) is a scalable, highly available, and managed Apache Cassandra-compatible database service. Amazon Keyspaces makes it easy to migrate, run, and scale Cassandra workloads in the AWS Cloud. With just a few clicks on the AWS Management Console or a few lines of code, you can create keyspaces and tables in Amazon Keyspaces, without deploying any infrastructure or installing software.

In addition to supporting Cassandra Query Language (CQL) requests via open-source Cassandra drivers, Amazon Keyspaces supports data definition language (DDL) operations to manage keyspaces and tables using the AWS SDK and AWS CLI, as well as infrastructure as code (IaC) services and tools such as AWS CloudFormation and Terraform. This API reference describes the supported DDL operations in detail.

For the list of all supported CQL APIs, see [Supported Cassandra APIs, operations, and data types in Amazon Keyspaces](#) in the *Amazon Keyspaces Developer Guide*.

To learn how Amazon Keyspaces API actions are recorded with AWS CloudTrail, see [Amazon Keyspaces information in CloudTrail](#) in the *Amazon Keyspaces Developer Guide*.

For more information about AWS APIs, for example how to implement retry logic or how to sign AWS API requests, see [AWS APIs](#) in the *General Reference*.

This document was last published on September 3, 2025.

Actions

The following actions are supported:

- [CreateKeyspace](#)
- [CreateTable](#)
- [CreateType](#)
- [DeleteKeyspace](#)
- [DeleteTable](#)
- [DeleteType](#)
- [GetKeyspace](#)
- [GetTable](#)
- [GetTableAutoScalingSettings](#)
- [GetType](#)
- [ListKeyspaces](#)
- [ListTables](#)
- [ListTagsForResource](#)
- [ListTypes](#)
- [RestoreTable](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateKeyspace](#)
- [UpdateTable](#)

CreateKeyspace

The CreateKeyspace operation adds a new keyspace to your account. In an AWS account, keyspace names must be unique within each Region.

CreateKeyspace is an asynchronous operation. You can monitor the creation status of the new keyspace by using the GetKeyspace operation.

For more information, see [Create a keyspace](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{
  "keyspaceName": "string",
  "replicationSpecification": {
    "regionList": [ "string" ],
    "replicationStrategy": "string"
  },
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[keyspaceName](#)

The name of the keyspace to be created.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

replicationSpecification

The replication specification of the keyspace includes:

- `replicationStrategy` - the required value is `SINGLE_REGION` or `MULTI_REGION`.
- `regionList` - if the `replicationStrategy` is `MULTI_REGION`, the `regionList` requires the current Region and at least one additional AWS Region where the keyspace is going to be replicated in.

Type: [ReplicationSpecification](#) object

Required: No

tags

A list of key-value pair tags to be attached to the keyspace.

For more information, see [Adding tags and labels to Amazon Keyspaces resources](#) in the *Amazon Keyspaces Developer Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 60 items.

Required: No

Response Syntax

```
{
  "resourceArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

resourceArn

The unique identifier of the keyspace in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTable

The CreateTable operation adds a new table to the specified keyspace. Within a keyspace, table names must be unique.

CreateTable is an asynchronous operation. When the request is received, the status of the table is set to CREATING. You can monitor the creation status of the new table by using the GetTable operation, which returns the current status of the table. You can start using a table when the status is ACTIVE.

For more information, see [Create a table](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{
  "autoScalingSpecification": {
    "readCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    },
    "writeCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    }
  }
}
```



```

},
"capacitySpecification": {
  "readCapacityUnits": number,
  "throughputMode": "string",
  "writeCapacityUnits": number
},
"cdcSpecification": {
  "propagateTags": "string",
  "status": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "viewType": "string"
},
"clientSideTimestamps": {
  "status": "string"
},
"comment": {
  "message": "string"
},
"defaultTimeToLive": number,
"encryptionSpecification": {
  "kmsKeyIdentifier": "string",
  "type": "string"
},
"keyspaceName": "string",
"pointInTimeRecovery": {
  "status": "string"
},
"replicaSpecifications": [
  {
    "readCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    }
  }
]

```

```

        }
    }
},
    "readCapacityUnits": number,
    "region": "string"
}
],
"schemaDefinition": {
    "allColumns": [
        {
            "name": "string",
            "type": "string"
        }
    ],
    "clusteringKeys": [
        {
            "name": "string",
            "orderBy": "string"
        }
    ],
    "partitionKeys": [
        {
            "name": "string"
        }
    ],
    "staticColumns": [
        {
            "name": "string"
        }
    ]
},
"tableName": "string",
"tags": [
    {
        "key": "string",
        "value": "string"
    }
],
"ttl": {
    "status": "string"
}
}

```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[autoScalingSpecification](#)

The optional auto scaling settings for a table in provisioned capacity mode. Specifies if the service can manage throughput capacity automatically on your behalf.

Auto scaling helps you provision throughput capacity for variable workloads efficiently by increasing and decreasing your table's read and write capacity automatically in response to application traffic. For more information, see [Managing throughput capacity automatically with Amazon Keyspaces auto scaling](#) in the *Amazon Keyspaces Developer Guide*.

By default, auto scaling is disabled for a table.

Type: [AutoScalingSpecification](#) object

Required: No

[capacitySpecification](#)

Specifies the read/write throughput capacity mode for the table. The options are:

- `throughputMode:PAY_PER_REQUEST` and
- `throughputMode:PROVISIONED` - Provisioned capacity mode requires `readCapacityUnits` and `writeCapacityUnits` as input.

The default is `throughput_mode:PAY_PER_REQUEST`.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Type: [CapacitySpecification](#) object

Required: No

[cdcSpecification](#)

The CDC stream settings of the table.

Type: [CdcSpecification](#) object

Required: No

clientSideTimestamps

Enables client-side timestamps for the table. By default, the setting is disabled. You can enable client-side timestamps with the following option:

- `status: "enabled"`

Once client-side timestamps are enabled for a table, this setting cannot be disabled.

Type: [ClientSideTimestamps](#) object

Required: No

comment

This parameter allows to enter a description of the table.

Type: [Comment](#) object

Required: No

defaultTimeToLive

The default Time to Live setting in seconds for the table.

For more information, see [Setting the default TTL value for a table](#) in the *Amazon Keyspaces Developer Guide*.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 630720000.

Required: No

encryptionSpecification

Specifies how the encryption key for encryption at rest is managed for the table. You can choose one of the following KMS key (KMS key):

- `type: AWS_OWNED_KMS_KEY` - This key is owned by Amazon Keyspaces.
- `type: CUSTOMER_MANAGED_KMS_KEY` - This key is stored in your account and is created, owned, and managed by you. This option requires the `kms_key_identifier` of the KMS key in Amazon Resource Name (ARN) format as input.

The default is type :AWS_OWNED_KMS_KEY.

For more information, see [Encryption at rest](#) in the *Amazon Keyspaces Developer Guide*.

Type: [EncryptionSpecification](#) object

Required: No

[keyspaceName](#)

The name of the keyspace that the table is going to be created in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: [a-zA-Z0-9][a-zA-Z0-9_]{0,47}

Required: Yes

[pointInTimeRecovery](#)

Specifies if pointInTimeRecovery is enabled or disabled for the table. The options are:

- status=ENABLED
- status=DISABLED

If it's not specified, the default is status=DISABLED.

For more information, see [Point-in-time recovery](#) in the *Amazon Keyspaces Developer Guide*.

Type: [PointInTimeRecovery](#) object

Required: No

[replicaSpecifications](#)

The optional AWS Region specific settings of a multi-Region table. These settings overwrite the general settings of the table for the specified Region.

For a multi-Region table in provisioned capacity mode, you can configure the table's read capacity differently for each Region's replica. The write capacity, however, remains synchronized between all replicas to ensure that there's enough capacity to replicate writes across all Regions. To define the read capacity for a table replica in a specific Region, you can do so by configuring the following parameters.

- **region**: The Region where these settings are applied. (Required)
- **readCapacityUnits**: The provisioned read capacity units. (Optional)
- **readCapacityAutoScaling**: The read capacity auto scaling settings for the table. (Optional)

Type: Array of [ReplicaSpecification](#) objects

Array Members: Minimum number of 1 item.

Required: No

[schemaDefinition](#)

The `schemaDefinition` consists of the following parameters.

For each column to be created:

- **name** - The name of the column.
- **type** - An Amazon Keyspaces data type. For more information, see [Data types](#) in the *Amazon Keyspaces Developer Guide*.

The primary key of the table consists of the following columns:

- **partitionKeys** - The partition key can be a single column, or it can be a compound value composed of two or more columns. The partition key portion of the primary key is required and determines how Amazon Keyspaces stores your data.
- **name** - The name of each partition key column.
- **clusteringKeys** - The optional clustering column portion of your primary key determines how the data is clustered and sorted within each partition.
- **name** - The name of the clustering column.
- **orderBy** - Sets the ascendant (ASC) or descendant (DESC) order modifier.

To define a column as static use `staticColumns` - Static columns store values that are shared by all rows in the same partition:

- **name** - The name of the column.
- **type** - An Amazon Keyspaces data type.

Type: [SchemaDefinition](#) object

Required: Yes

tableName

The name of the table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

tags

A list of key-value pair tags to be attached to the resource.

For more information, see [Adding tags and labels to Amazon Keyspaces resources](#) in the *Amazon Keyspaces Developer Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 60 items.

Required: No

ttl

Enables Time to Live custom settings for the table. The options are:

- `status:enabled`
- `status:disabled`

The default is `status:disabled`. After `ttl` is enabled, you can't disable it for the table.

For more information, see [Expiring data by using Amazon Keyspaces Time to Live \(TTL\)](#) in the *Amazon Keyspaces Developer Guide*.

Type: [TimeToLive](#) object

Required: No

Response Syntax

```
{
```

```
"resourceArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[resourceArn](#)

The unique identifier of the table in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.+.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerError](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateType

The CreateType operation creates a new user-defined type in the specified keyspace.

To configure the required permissions, see [Permissions to create a UDT](#) in the *Amazon Keyspaces Developer Guide*.

For more information, see [User-defined types \(UDTs\)](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{
  "fieldDefinitions": [
    {
      "name": "string",
      "type": "string"
    }
  ],
  "keyspaceName": "string",
  "typeName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[fieldDefinitions](#)

The field definitions, consisting of names and types, that define this type.

Type: Array of [FieldDefinition](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

[keyspaceName](#)

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

typeName

The name of the user-defined type.

UDT names must contain 48 characters or less, must begin with an alphabetic character, and can only contain alpha-numeric characters and underscores. Amazon Keyspaces converts upper case characters automatically into lower case characters.

Alternatively, you can declare a UDT name in double quotes. When declaring a UDT name inside double quotes, Amazon Keyspaces preserves upper casing and allows special characters.

You can also use double quotes as part of the name when you create the UDT, but you must escape each double quote character with an additional double quote character.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Required: Yes

Response Syntax

```
{
  "keyspaceArn": "string",
  "typeName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

keyspaceArn

The unique identifier of the keyspace that contains the new type in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.+.*`

typeName

The formatted name of the user-defined type that was created. Note that Amazon Keyspaces requires the formatted name of the type for other operations, for example `GetType`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

ConflictException

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

InternalServerErrorException

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteKeyspace

The DeleteKeyspace operation deletes a keyspace and all of its tables.

Request Syntax

```
{  
  "keyspaceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace to be deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: [a-zA-Z0-9][a-zA-Z0-9_]{0,47}

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTable

The DeleteTable operation deletes a table and all of its data. After a DeleteTable request is received, the specified table is in the DELETING state until Amazon Keyspaces completes the deletion. If the table is in the ACTIVE state, you can delete it. If a table is either in the CREATING or UPDATING states, then Amazon Keyspaces returns a ResourceInUseException. If the specified table does not exist, Amazon Keyspaces returns a ResourceNotFoundException. If the table is already in the DELETING state, no error is returned.

Request Syntax

```
{
  "keyspaceName": "string",
  "tableName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace of the to be deleted table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

tableName

The name of the table to be deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerError](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteType

The DeleteType operation deletes a user-defined type (UDT). You can only delete a type that is not used in a table or another UDT.

To configure the required permissions, see [Permissions to delete a UDT](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{
  "keyspaceName": "string",
  "typeName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace of the to be deleted type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

typeName

The name of the type to be deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Required: Yes

Response Syntax

```
{
  "keyspaceArn": "string",
  "typeName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

keyspaceArn

The unique identifier of the keyspace from which the type was deleted in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*`

typeName

The name of the type that was deleted.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetKeyspace

Returns the name of the specified keyspace, the Amazon Resource Name (ARN), the replication strategy, the AWS Regions of a multi-Region keyspace, and the status of newly added Regions after an UpdateKeyspace operation.

Request Syntax

```
{  
  "keyspaceName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

Response Syntax

```
{  
  "keyspaceName": "string",  
  "replicationGroupStatuses": [  
    {  
      "keyspaceStatus": "string",  
      "region": "string",  
      "tablesReplicationProgress": "string"  
    }  
  ],  
}
```



```
"replicationRegions": [ "string" ],  
"replicationStrategy": "string",  
"resourceArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[keyspaceName](#)

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

[replicationGroupStatuses](#)

A list of all Regions the keyspace is replicated in after the update keyspace operation and their status.

Type: Array of [ReplicationGroupStatus](#) objects

Array Members: Minimum number of 2 items.

[replicationRegions](#)

If the `replicationStrategy` of the keyspace is `MULTI_REGION`, a list of replication Regions is returned.

Type: Array of strings

Array Members: Minimum number of 2 items.

Length Constraints: Minimum length of 2. Maximum length of 25.

[replicationStrategy](#)

Returns the replication strategy of the keyspace. The options are `SINGLE_REGION` or `MULTI_REGION`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Valid Values: SINGLE_REGION | MULTI_REGION

[resourceArn](#)

Returns the ARN of the keyspace.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTable

Returns information about the table, including the table's name and current status, the keyspace name, configuration settings, and metadata.

To read table metadata using `GetTable`, the IAM principal needs `Select` action permissions for the table and the system keyspace.

Request Syntax

```
{  
  "keyspaceName": "string",  
  "tableName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace that the table is stored in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

tableName

The name of the table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

Response Syntax

```
{
  "capacitySpecification": {
    "lastUpdateToPayPerRequestTimestamp": number,
    "readCapacityUnits": number,
    "throughputMode": "string",
    "writeCapacityUnits": number
  },
  "cdcSpecification": {
    "status": "string",
    "viewType": "string"
  },
  "clientSideTimestamps": {
    "status": "string"
  },
  "comment": {
    "message": "string"
  },
  "creationTimestamp": number,
  "defaultTimeToLive": number,
  "encryptionSpecification": {
    "kmsKeyIdentifier": "string",
    "type": "string"
  },
  "keyspaceName": "string",
  "latestStreamArn": "string",
  "pointInTimeRecovery": {
    "earliestRestorableTimestamp": number,
    "status": "string"
  },
  "replicaSpecifications": [
    {
      "capacitySpecification": {
        "lastUpdateToPayPerRequestTimestamp": number,
        "readCapacityUnits": number,
        "throughputMode": "string",
        "writeCapacityUnits": number
      },
      "region": "string",
      "status": "string"
    }
  ],
}
```

```
{
  "resourceArn": "string",
  "schemaDefinition": {
    "allColumns": [
      {
        "name": "string",
        "type": "string"
      }
    ],
    "clusteringKeys": [
      {
        "name": "string",
        "orderBy": "string"
      }
    ],
    "partitionKeys": [
      {
        "name": "string"
      }
    ],
    "staticColumns": [
      {
        "name": "string"
      }
    ]
  },
  "status": "string",
  "tableName": "string",
  "ttl": {
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

capacitySpecification

The read/write throughput capacity mode for a table. The options are:

- throughputMode:PAY_PER_REQUEST
- throughputMode:PROVISIONED

Type: [CapacitySpecificationSummary](#) object

cdcSpecification

The CDC stream settings of the table.

Type: [CdcSpecificationSummary](#) object

clientSideTimestamps

The client-side timestamps setting of the table.

Type: [ClientSideTimestamps](#) object

comment

The the description of the specified table.

Type: [Comment](#) object

creationTimestamp

The creation timestamp of the specified table.

Type: Timestamp

defaultTimeToLive

The default Time to Live settings in seconds of the specified table.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 630720000.

encryptionSpecification

The encryption settings of the specified table.

Type: [EncryptionSpecification](#) object

keyspaceName

The name of the keyspace that the specified table is stored in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

latestStreamArn

The Amazon Resource Name (ARN) of the stream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*.*`

pointInTimeRecovery

The point-in-time recovery status of the specified table.

Type: [PointInTimeRecoverySummary](#) object

replicaSpecifications

Returns the AWS Region specific settings of all Regions a multi-Region table is replicated in.

Type: Array of [ReplicaSpecificationSummary](#) objects

Array Members: Minimum number of 0 items.

resourceArn

The Amazon Resource Name (ARN) of the specified table.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*.*`

schemaDefinition

The schema definition of the specified table.

Type: [SchemaDefinition](#) object

status

The current status of the specified table.

Type: String

Valid Values: ACTIVE | CREATING | UPDATING | DELETING | DELETED | RESTORING
| INACCESSIBLE_ENCRYPTION_CREDENTIALS

tableName

The name of the specified table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: [a-zA-Z0-9][a-zA-Z0-9_]{0,47}

ttl

The custom Time to Live settings of the specified table.

Type: [TimeToLive](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

InternalServerError

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

ServiceQuotaExceededException

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTableAutoScalingSettings

Returns auto scaling related settings of the specified table in JSON format. If the table is a multi-Region table, the AWS Region specific auto scaling settings of the table are included.

Amazon Keyspaces auto scaling helps you provision throughput capacity for variable workloads efficiently by increasing and decreasing your table's read and write capacity automatically in response to application traffic. For more information, see [Managing throughput capacity automatically with Amazon Keyspaces auto scaling](#) in the *Amazon Keyspaces Developer Guide*.

Important

GetTableAutoScalingSettings can't be used as an action in an IAM policy.

To define permissions for GetTableAutoScalingSettings, you must allow the following two actions in the IAM policy statement's Action element:

- application-autoscaling:DescribeScalableTargets
- application-autoscaling:DescribeScalingPolicies

Request Syntax

```
{
  "keyspaceName": "string",
  "tableName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

tableName

The name of the table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

Response Syntax

```
{
  "autoScalingSpecification": {
    "readCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    },
    "writeCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,

```

```

        "targetValue": number
    }
}
},
"keyspaceName": "string",
"replicaSpecifications": [
{
    "autoScalingSpecification": {
        "readCapacityAutoScaling": {
            "autoScalingDisabled": boolean,
            "maximumUnits": number,
            "minimumUnits": number,
            "scalingPolicy": {
                "targetTrackingScalingPolicyConfiguration": {
                    "disableScaleIn": boolean,
                    "scaleInCooldown": number,
                    "scaleOutCooldown": number,
                    "targetValue": number
                }
            }
        },
        "writeCapacityAutoScaling": {
            "autoScalingDisabled": boolean,
            "maximumUnits": number,
            "minimumUnits": number,
            "scalingPolicy": {
                "targetTrackingScalingPolicyConfiguration": {
                    "disableScaleIn": boolean,
                    "scaleInCooldown": number,
                    "scaleOutCooldown": number,
                    "targetValue": number
                }
            }
        }
    },
    "region": "string"
}
],
"resourceArn": "string",
"tableName": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

autoScalingSpecification

The auto scaling settings of the table.

Type: [AutoScalingSpecification](#) object

keyspaceName

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

replicaSpecifications

The AWS Region specific settings of a multi-Region table. Returns the settings for all Regions the table is replicated in.

Type: Array of [ReplicaAutoScalingSpecification](#) objects

Array Members: Minimum number of 0 items.

resourceArn

The Amazon Resource Name (ARN) of the table.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.+.*`

tableName

The name of the table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetType

The GetType operation returns information about the type, for example the field definitions, the timestamp when the type was last modified, the level of nesting, the status, and details about if the type is used in other types and tables.

To read keyspace metadata using GetType, the IAM principal needs `Select` action permissions for the system keyspace. To configure the required permissions, see [Permissions to view a UDT](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{  
  "keyspaceName": "string",  
  "typeName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace that contains this type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

typeName

The formatted name of the type. For example, if the name of the type was created without double quotes, Amazon Keyspaces saved the name in lower-case characters. If the name was created in double quotes, you must use double quotes to specify the type name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Required: Yes

Response Syntax

```
{
  "directParentTypes": [ "string" ],
  "directReferringTables": [ "string" ],
  "fieldDefinitions": [
    {
      "name": "string",
      "type": "string"
    }
  ],
  "keyspaceArn": "string",
  "keyspaceName": "string",
  "lastModifiedTimestamp": number,
  "maxNestingDepth": number,
  "status": "string",
  "typeName": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

directParentTypes

The types that use this type.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 48.

directReferringTables

The tables that use this type.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

fieldDefinitions

The names and types that define this type.

Type: Array of [FieldDefinition](#) objects

Array Members: Minimum number of 1 item.

keyspaceArn

The unique identifier of the keyspace that contains this type in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*.*`

keyspaceName

The name of the keyspace that contains this type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

lastModifiedTimestamp

The timestamp that shows when this type was last modified.

Type: Timestamp

maxNestingDepth

The level of nesting implemented for this type.

Type: Integer

status

The status of this type.

Type: String

Valid Values: ACTIVE | CREATING | DELETING | RESTORING

typeName

The name of the type.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

InternalServerErrorException

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

ServiceQuotaExceededException

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

ValidationException

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListKeyspaces

The ListKeyspaces operation returns a list of keyspaces.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The total number of keyspaces to return in the output. If the total number of keyspaces available is more than the value specified, a NextToken is provided in the output. To resume pagination, provide the NextToken value as an argument of a subsequent API invocation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The pagination token. To resume pagination, provide the NextToken value as argument of a subsequent API invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{
  "keyspaces": [
    {
      "keyspaceName": "string",
      "replicationRegions": [ "string" ],
      "replicationStrategy": "string",
      "resourceArn": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[keyspaces](#)

A list of keyspaces.

Type: Array of [KeyspaceSummary](#) objects

[nextToken](#)

A token to specify where to start paginating. This is the NextToken from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTables

The ListTables operation returns a list of tables for a specified keyspace.

To read keyspace metadata using ListTables, the IAM principal needs Select action permissions for the system keyspace.

Request Syntax

```
{  
  "keyspaceName": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

maxResults

The total number of tables to return in the output. If the total number of tables available is more than the value specified, a NextToken is provided in the output. To resume pagination, provide the NextToken value as an argument of a subsequent API invocation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The pagination token. To resume pagination, provide the NextToken value as an argument of a subsequent API invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "tables": [
    {
      "keyspaceName": "string",
      "resourceArn": "string",
      "tableName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token to specify where to start paginating. This is the NextToken from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

tables

A list of tables.

Type: Array of [TableSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns a list of all tags associated with the specified Amazon Keyspaces resource.

To read keyspace metadata using `ListTagsForResource`, the IAM principal needs `Select` action permissions for the specified resource and the system keyspace.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

maxResults

The total number of tags to return in the output. If the total number of tags available is more than the value specified, a `NextToken` is provided in the output. To resume pagination, provide the `NextToken` value as an argument of a subsequent API invocation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

nextToken

The pagination token. To resume pagination, provide the `NextToken` value as argument of a subsequent API invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

resourceArn

The Amazon Resource Name (ARN) of the Amazon Keyspaces resource.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*`

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

A token to specify where to start paginating. This is the NextToken from a previously truncated response.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

tags

A list of tags.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 60 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[InternalServerException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTypes

The `ListTypes` operation returns a list of types for a specified keyspace.

To read keyspace metadata using `ListTypes`, the IAM principal needs `Select` action permissions for the system keyspace. To configure the required permissions, see [Permissions to view a UDT](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{  
  "keyspaceName": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

keyspaceName

The name of the keyspace that contains the listed types.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

maxResults

The total number of types to return in the output. If the total number of types available is more than the value specified, a `NextToken` is provided in the output. To resume pagination, provide the `NextToken` value as an argument of a subsequent API invocation.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

[nextToken](#)

The pagination token. To resume pagination, provide the NextToken value as an argument of a subsequent API invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "types": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The pagination token. To resume pagination, provide the NextToken value as an argument of a subsequent API invocation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

[types](#)

The list of types contained in the specified keyspace.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 48.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RestoreTable

Restores the table to the specified point in time within the `earliest_restorable_timestamp` and the current time. For more information about restore points, see [Time window for PITR continuous backups](#) in the *Amazon Keyspaces Developer Guide*.

Any number of users can execute up to 4 concurrent restores (any type of restore) in a given account.

When you restore using point in time recovery, Amazon Keyspaces restores your source table's schema and data to the state based on the selected timestamp (day:hour:minute:second) to a new table. The Time to Live (TTL) settings are also restored to the state based on the selected timestamp.

In addition to the table's schema, data, and TTL settings, `RestoreTable` restores the capacity mode, auto scaling settings, encryption settings, and point-in-time recovery settings from the source table. Unlike the table's schema data and TTL settings, which are restored based on the selected timestamp, these settings are always restored based on the table's settings as of the current time or when the table was deleted.

You can also overwrite these settings during restore:

- Read/write capacity mode
- Provisioned throughput capacity units
- Auto scaling settings
- Point-in-time (PITR) settings
- Tags

For more information, see [PITR restore settings](#) in the *Amazon Keyspaces Developer Guide*.

Note that the following settings are not restored, and you must configure them manually for the new table:

- AWS Identity and Access Management (IAM) policies
- Amazon CloudWatch metrics and alarms

Request Syntax

```
{
  "autoScalingSpecification": {
    "readCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    },
    "writeCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    }
  },
  "capacitySpecificationOverride": {
    "readCapacityUnits": number,
    "throughputMode": "string",
    "writeCapacityUnits": number
  },
  "encryptionSpecificationOverride": {
    "kmsKeyIdentifier": "string",
    "type": "string"
  },
  "pointInTimeRecoveryOverride": {
    "status": "string"
  },
}
```

```

"replicaSpecifications": [
  {
    "readCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    },
    "readCapacityUnits": number,
    "region": "string"
  }
],
"restoreTimestamp": number,
"sourceKeyspaceName": "string",
"sourceTableName": "string",
"tagsOverride": [
  {
    "key": "string",
    "value": "string"
  }
],
"targetKeyspaceName": "string",
"targetTableName": "string"
}

```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[autoScalingSpecification](#)

The optional auto scaling settings for the restored table in provisioned capacity mode. Specifies if the service can manage throughput capacity of a provisioned table automatically on your behalf. Amazon Keyspaces auto scaling helps you provision throughput capacity for

variable workloads efficiently by increasing and decreasing your table's read and write capacity automatically in response to application traffic.

For more information, see [Managing throughput capacity automatically with Amazon Keyspaces auto scaling](#) in the *Amazon Keyspaces Developer Guide*.

Type: [AutoScalingSpecification](#) object

Required: No

[capacitySpecificationOverride](#)

Specifies the read/write throughput capacity mode for the target table. The options are:

- `throughputMode:PAY_PER_REQUEST`
- `throughputMode:PROVISIONED` - Provisioned capacity mode requires `readCapacityUnits` and `writeCapacityUnits` as input.

The default is `throughput_mode:PAY_PER_REQUEST`.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Type: [CapacitySpecification](#) object

Required: No

[encryptionSpecificationOverride](#)

Specifies the encryption settings for the target table. You can choose one of the following KMS key (KMS key):

- `type:AWS_OWNED_KMS_KEY` - This key is owned by Amazon Keyspaces.
- `type:CUSTOMER_MANAGED_KMS_KEY` - This key is stored in your account and is created, owned, and managed by you. This option requires the `kms_key_identifier` of the KMS key in Amazon Resource Name (ARN) format as input.

The default is `type:AWS_OWNED_KMS_KEY`.

For more information, see [Encryption at rest](#) in the *Amazon Keyspaces Developer Guide*.

Type: [EncryptionSpecification](#) object

Required: No

pointInTimeRecoveryOverride

Specifies the `pointInTimeRecovery` settings for the target table. The options are:

- `status=ENABLED`
- `status=DISABLED`

If it's not specified, the default is `status=DISABLED`.

For more information, see [Point-in-time recovery](#) in the *Amazon Keyspaces Developer Guide*.

Type: [PointInTimeRecovery](#) object

Required: No

replicaSpecifications

The optional Region specific settings of a multi-Regional table.

Type: Array of [ReplicaSpecification](#) objects

Array Members: Minimum number of 1 item.

Required: No

restoreTimestamp

The restore timestamp in ISO 8601 format.

Type: Timestamp

Required: No

sourceKeyspaceName

The keyspace name of the source table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

sourceTableName

The name of the source table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

tagsOverride

A list of key-value pair tags to be attached to the restored table.

For more information, see [Adding tags and labels to Amazon Keyspaces resources](#) in the *Amazon Keyspaces Developer Guide*.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 60 items.

Required: No

targetKeyspaceName

The name of the target keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

targetTableName

The name of the target table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

Response Syntax

```
{
  "restoredTableARN": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[restoredTableARN](#)

The Amazon Resource Name (ARN) of the restored table.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

TagResource

Associates a set of tags with a Amazon Keyspaces resource. You can then activate these user-defined tags so that they appear on the Cost Management Console for cost allocation tracking. For more information, see [Adding tags and labels to Amazon Keyspaces resources](#) in the *Amazon Keyspaces Developer Guide*.

For IAM policy examples that show how to control access to Amazon Keyspaces resources based on tags, see [Amazon Keyspaces resource access based on tags](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the Amazon Keyspaces resource to which to add tags.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*.*`

Required: Yes

tags

The tags to be assigned to the Amazon Keyspaces resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 60 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

ConflictException

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

InternalServerErrorException

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes the association of tags from a Amazon Keyspaces resource.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[resourceArn](#)

The Amazon Keyspaces resource that the tags will be removed from. This value is an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*.*`

Required: Yes

[tags](#)

A list of existing tags to be removed from the Amazon Keyspaces resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 60 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerError](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateKeyspace

Adds a new AWS Region to the keyspace. You can add a new Region to a keyspace that is either a single or a multi-Region keyspace. Amazon Keyspaces is going to replicate all tables in the keyspace to the new Region. To successfully replicate all tables to the new Region, they must use client-side timestamps for conflict resolution. To enable client-side timestamps, specify `clientSideTimestamps.status = enabled` when invoking the API. For more information about client-side timestamps, see [Client-side timestamps in Amazon Keyspaces](#) in the *Amazon Keyspaces Developer Guide*.

To add a Region to a keyspace using the UpdateKeyspace API, the IAM principal needs permissions for the following IAM actions:

- `cassandra:Alter`
- `cassandra:AlterMultiRegionResource`
- `cassandra:Create`
- `cassandra:CreateMultiRegionResource`
- `cassandra:Select`
- `cassandra:SelectMultiRegionResource`
- `cassandra:Modify`
- `cassandra:ModifyMultiRegionResource`

If the keyspace contains a table that is configured in provisioned mode with auto scaling enabled, the following additional IAM actions need to be allowed.

- `application-autoscaling:RegisterScalableTarget`
- `application-autoscaling:DeregisterScalableTarget`
- `application-autoscaling:DescribeScalableTargets`
- `application-autoscaling:PutScalingPolicy`
- `application-autoscaling:DescribeScalingPolicies`

To use the UpdateKeyspace API, the IAM principal also needs permissions to create a service-linked role with the following elements:

- `iam:CreateServiceLinkedRole` - The **action** the principal can perform.

- `arn:aws:iam::*:role/aws-service-role/replication.cassandra.amazonaws.com/AWSServiceRoleForKeyspacesReplication` - The **resource** that the action can be performed on.
- `iam:AWSServiceName: replication.cassandra.amazonaws.com` - The only AWS service that this role can be attached to is Amazon Keyspaces.

For more information, see [Configure the IAM permissions required to add an AWS Region to a keyspace](#) in the *Amazon Keyspaces Developer Guide*.

Request Syntax

```
{
  "clientSideTimestamps": {
    "status": "string"
  },
  "keyspaceName": "string",
  "replicationSpecification": {
    "regionList": [ "string" ],
    "replicationStrategy": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientSideTimestamps](#)

The client-side timestamp setting of the table.

For more information, see [How it works: Amazon Keyspaces client-side timestamps](#) in the *Amazon Keyspaces Developer Guide*.

Type: [ClientSideTimestamps](#) object

Required: No

[keyspaceName](#)

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

[replicationSpecification](#)

The replication specification of the keyspace includes:

- `regionList` - the AWS Regions where the keyspace is replicated in.
- `replicationStrategy` - the required value is `SINGLE_REGION` or `MULTI_REGION`.

Type: [ReplicationSpecification](#) object

Required: Yes

Response Syntax

```
{
  "resourceArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[resourceArn](#)

The unique identifier of the keyspace in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerErrorException](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTable

Adds new columns to the table or updates one of the table's settings, for example capacity mode, auto scaling, encryption, point-in-time recovery, or ttl settings. Note that you can only update one specific table setting per update operation.

Request Syntax

```
{
  "addColumnns": [
    {
      "name": "string",
      "type": "string"
    }
  ],
  "autoScalingSpecification": {
    "readCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    },
    "writeCapacityAutoScaling": {
      "autoScalingDisabled": boolean,
      "maximumUnits": number,
      "minimumUnits": number,
      "scalingPolicy": {
        "targetTrackingScalingPolicyConfiguration": {
          "disableScaleIn": boolean,
          "scaleInCooldown": number,
          "scaleOutCooldown": number,
          "targetValue": number
        }
      }
    }
  }
}
```

```
{,
  "capacitySpecification": {
    "readCapacityUnits": number,
    "throughputMode": "string",
    "writeCapacityUnits": number
  },
  "cdcSpecification": {
    "propagateTags": "string",
    "status": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "viewType": "string"
  },
  "clientSideTimestamps": {
    "status": "string"
  },
  "defaultTimeToLive": number,
  "encryptionSpecification": {
    "kmsKeyIdentifier": "string",
    "type": "string"
  },
  "keyspaceName": "string",
  "pointInTimeRecovery": {
    "status": "string"
  },
  "replicaSpecifications": [
    {
      "readCapacityAutoScaling": {
        "autoScalingDisabled": boolean,
        "maximumUnits": number,
        "minimumUnits": number,
        "scalingPolicy": {
          "targetTrackingScalingPolicyConfiguration": {
            "disableScaleIn": boolean,
            "scaleInCooldown": number,
            "scaleOutCooldown": number,
            "targetValue": number
          }
        }
      }
    }
  ],
}
```

```
    "readCapacityUnits": number,
    "region": "string"
  }
],
"tableName": "string",
"ttl": {
  "status": "string"
}
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[addColumns](#)

For each column to be added to the specified table:

- name - The name of the column.
- type - An Amazon Keyspaces data type. For more information, see [Data types](#) in the *Amazon Keyspaces Developer Guide*.

Type: Array of [ColumnDefinition](#) objects

Array Members: Minimum number of 1 item.

Required: No

[autoScalingSpecification](#)

The optional auto scaling settings to update for a table in provisioned capacity mode. Specifies if the service can manage throughput capacity of a provisioned table automatically on your behalf. Amazon Keyspaces auto scaling helps you provision throughput capacity for variable workloads efficiently by increasing and decreasing your table's read and write capacity automatically in response to application traffic.

If auto scaling is already enabled for the table, you can use `UpdateTable` to update the minimum and maximum values or the auto scaling policy settings independently.

For more information, see [Managing throughput capacity automatically with Amazon Keyspaces auto scaling](#) in the *Amazon Keyspaces Developer Guide*.

Type: [AutoScalingSpecification](#) object

Required: No

[capacitySpecification](#)

Modifies the read/write throughput capacity mode for the table. The options are:

- `throughputMode:PAY_PER_REQUEST` and
- `throughputMode:PROVISIONED` - Provisioned capacity mode requires `readCapacityUnits` and `writeCapacityUnits` as input.

The default is `throughput_mode:PAY_PER_REQUEST`.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Type: [CapacitySpecification](#) object

Required: No

[cdcSpecification](#)

The CDC stream settings of the table.

Type: [CdcSpecification](#) object

Required: No

[clientSideTimestamps](#)

Enables client-side timestamps for the table. By default, the setting is disabled. You can enable client-side timestamps with the following option:

- `status: "enabled"`

Once client-side timestamps are enabled for a table, this setting cannot be disabled.

Type: [ClientSideTimestamps](#) object

Required: No

[defaultTimeToLive](#)

The default Time to Live setting in seconds for the table.

For more information, see [Setting the default TTL value for a table](#) in the *Amazon Keyspaces Developer Guide*.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 630720000.

Required: No

encryptionSpecification

Modifies the encryption settings of the table. You can choose one of the following KMS key (KMS key):

- `type:AWS_OWNED_KMS_KEY` - This key is owned by Amazon Keyspaces.
- `type:CUSTOMER_MANAGED_KMS_KEY` - This key is stored in your account and is created, owned, and managed by you. This option requires the `kms_key_identifier` of the KMS key in Amazon Resource Name (ARN) format as input.

The default is `AWS_OWNED_KMS_KEY`.

For more information, see [Encryption at rest](#) in the *Amazon Keyspaces Developer Guide*.

Type: [EncryptionSpecification](#) object

Required: No

keyspaceName

The name of the keyspace the specified table is stored in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

pointInTimeRecovery

Modifies the `pointInTimeRecovery` settings of the table. The options are:

- `status=ENABLED`
- `status=DISABLED`

If it's not specified, the default is `status=DISABLED`.

For more information, see [Point-in-time recovery](#) in the *Amazon Keyspaces Developer Guide*.

Type: [PointInTimeRecovery](#) object

Required: No

[replicaSpecifications](#)

The Region specific settings of a multi-Regional table.

Type: Array of [ReplicaSpecification](#) objects

Array Members: Minimum number of 1 item.

Required: No

[tableName](#)

The name of the table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

[ttl](#)

Modifies Time to Live custom settings for the table. The options are:

- `status:enabled`
- `status:disabled`

The default is `status:disabled`. After `ttl` is enabled, you can't disable it for the table.

For more information, see [Expiring data by using Amazon Keyspaces Time to Live \(TTL\)](#) in the *Amazon Keyspaces Developer Guide*.

Type: [TimeToLive](#) object

Required: No

Response Syntax

```
{
```

```
"resourceArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[resourceArn](#)

The Amazon Resource Name (ARN) of the modified table.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[AccessDeniedException](#)

You don't have sufficient access permissions to perform this action.

HTTP Status Code: 400

[ConflictException](#)

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code: 400

[InternalServerError](#)

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code: 500

[ResourceNotFoundException](#)

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code: 400

[ServiceQuotaExceededException](#)

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code: 400

[ValidationException](#)

The operation failed due to an invalid or malformed request.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Keyspaces API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AutoScalingPolicy](#)
- [AutoScalingSettings](#)
- [AutoScalingSpecification](#)
- [CapacitySpecification](#)
- [CapacitySpecificationSummary](#)
- [CdcSpecification](#)
- [CdcSpecificationSummary](#)
- [ClientSideTimestamps](#)
- [ClusteringKey](#)
- [ColumnDefinition](#)
- [Comment](#)
- [EncryptionSpecification](#)
- [FieldDefinition](#)
- [KeyspaceSummary](#)
- [PartitionKey](#)
- [PointInTimeRecovery](#)
- [PointInTimeRecoverySummary](#)
- [ReplicaAutoScalingSpecification](#)
- [ReplicaSpecification](#)
- [ReplicaSpecificationSummary](#)

- [ReplicationGroupStatus](#)
- [ReplicationSpecification](#)
- [SchemaDefinition](#)
- [StaticColumn](#)
- [TableSummary](#)
- [Tag](#)
- [TargetTrackingScalingPolicyConfiguration](#)
- [TimeToLive](#)

AutoScalingPolicy

Amazon Keyspaces supports the `target_tracking` auto scaling policy. With this policy, Amazon Keyspaces auto scaling ensures that the table's ratio of consumed to provisioned capacity stays at or near the target value that you specify. You define the target value as a percentage between 20 and 90.

Contents

`targetTrackingScalingPolicyConfiguration`

Auto scaling scales up capacity automatically when traffic exceeds this target utilization rate, and then back down when it falls below the target. A `double` between 20 and 90.

Type: [TargetTrackingScalingPolicyConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoScalingSettings

The optional auto scaling settings for a table with provisioned throughput capacity.

To turn on auto scaling for a table in `throughputMode:PROVISIONED`, you must specify the following parameters.

Configure the minimum and maximum capacity units. The auto scaling policy ensures that capacity never goes below the minimum or above the maximum range.

- **minimumUnits:** The minimum level of throughput the table should always be ready to support. The value must be between 1 and the max throughput per second quota for your account (40,000 by default).
- **maximumUnits:** The maximum level of throughput the table should always be ready to support. The value must be between 1 and the max throughput per second quota for your account (40,000 by default).
- **scalingPolicy:** Amazon Keyspaces supports the `target_tracking` scaling policy. The auto scaling target is the provisioned capacity of the table.
- **targetTrackingScalingPolicyConfiguration:** To define the target tracking policy, you must define the target value.
 - **targetValue:** The target utilization rate of the table. Amazon Keyspaces auto scaling ensures that the ratio of consumed capacity to provisioned capacity stays at or near this value. You define `targetValue` as a percentage. A double between 20 and 90. (Required)
 - **disableScaleIn:** A boolean that specifies if `scale-in` is disabled or enabled for the table. This parameter is disabled by default. To turn on `scale-in`, set the boolean value to `FALSE`. This means that capacity for a table can be automatically scaled down on your behalf. (Optional)
 - **scaleInCooldown:** A cooldown period in seconds between scaling activities that lets the table stabilize before another scale in activity starts. If no value is provided, the default is 0. (Optional)
 - **scaleOutCooldown:** A cooldown period in seconds between scaling activities that lets the table stabilize before another scale out activity starts. If no value is provided, the default is 0. (Optional)

For more information, see [Managing throughput capacity automatically with Amazon Keyspaces auto scaling](#) in the *Amazon Keyspaces Developer Guide*.

Contents

autoScalingDisabled

This optional parameter enables auto scaling for the table if set to `false`.

Type: Boolean

Required: No

maximumUnits

Manage costs by specifying the maximum amount of throughput to provision. The value must be between 1 and the max throughput per second quota for your account (40,000 by default).

Type: Long

Valid Range: Minimum value of 1.

Required: No

minimumUnits

The minimum level of throughput the table should always be ready to support. The value must be between 1 and the max throughput per second quota for your account (40,000 by default).

Type: Long

Valid Range: Minimum value of 1.

Required: No

scalingPolicy

Amazon Keyspaces supports the `target_tracking` auto scaling policy. With this policy, Amazon Keyspaces auto scaling ensures that the table's ratio of consumed to provisioned capacity stays at or near the target value that you specify. You define the target value as a percentage between 20 and 90.

Type: [AutoScalingPolicy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoScalingSpecification

The optional auto scaling capacity settings for a table in provisioned capacity mode.

Contents

readCapacityAutoScaling

The auto scaling settings for the table's read capacity.

Type: [AutoScalingSettings](#) object

Required: No

writeCapacityAutoScaling

The auto scaling settings for the table's write capacity.

Type: [AutoScalingSettings](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacitySpecification

Amazon Keyspaces has two read/write capacity modes for processing reads and writes on your tables:

- On-demand (default)
- Provisioned

The read/write capacity mode that you choose controls how you are charged for read and write throughput and how table throughput capacity is managed.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Contents

throughputMode

The read/write throughput capacity mode for a table. The options are:

- `throughputMode:PAY_PER_REQUEST` and
- `throughputMode:PROVISIONED` - Provisioned capacity mode requires `readCapacityUnits` and `writeCapacityUnits` as input.

The default is `throughput_mode:PAY_PER_REQUEST`.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Type: String

Valid Values: `PAY_PER_REQUEST` | `PROVISIONED`

Required: Yes

readCapacityUnits

The throughput capacity specified for read operations defined in `read capacity units` (RCUs).

Type: Long

Valid Range: Minimum value of 1.

Required: No

writeCapacityUnits

The throughput capacity specified for write operations defined in write capacity units (WCUs).

Type: Long

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacitySpecificationSummary

The read/write throughput capacity mode for a table. The options are:

- `throughputMode:PAY_PER_REQUEST` and
- `throughputMode:PROVISIONED`.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Contents

throughputMode

The read/write throughput capacity mode for a table. The options are:

- `throughputMode:PAY_PER_REQUEST` and
- `throughputMode:PROVISIONED` - Provisioned capacity mode requires `readCapacityUnits` and `writeCapacityUnits` as input.

The default is `throughput_mode:PAY_PER_REQUEST`.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Type: String

Valid Values: `PAY_PER_REQUEST` | `PROVISIONED`

Required: Yes

lastUpdateToPayPerRequestTimestamp

The timestamp of the last operation that changed the provisioned throughput capacity of a table.

Type: Timestamp

Required: No

readCapacityUnits

The throughput capacity specified for read operations defined in `read capacity units` (RCUs).

Type: Long

Valid Range: Minimum value of 1.

Required: No

writeCapacityUnits

The throughput capacity specified for write operations defined in write capacity units (WCUs).

Type: Long

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CdcSpecification

The settings for the CDC stream of a table. For more information about CDC streams, see [Working with change data capture \(CDC\) streams in Amazon Keyspaces](#) in the *Amazon Keyspaces Developer Guide*.

Contents

status

The status of the CDC stream. You can enable or disable a stream for a table.

Type: String

Valid Values: ENABLED | ENABLING | DISABLED | DISABLING

Required: Yes

propagateTags

Specifies that the stream inherits the tags from the table.

Type: String

Valid Values: TABLE | NONE

Required: No

tags

The tags (key-value pairs) that you want to apply to the stream.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 1 item. Maximum number of 60 items.

Required: No

viewType

The view type specifies the changes Amazon Keyspaces records for each changed row in the stream. After you create the stream, you can't make changes to this selection.

The options are:

- `NEW_AND_OLD_IMAGES` - both versions of the row, before and after the change. This is the default.
- `NEW_IMAGE` - the version of the row after the change.
- `OLD_IMAGE` - the version of the row before the change.
- `KEYS_ONLY` - the partition and clustering keys of the row that was changed.

Type: String

Valid Values: `NEW_IMAGE` | `OLD_IMAGE` | `KEYS_ONLY` | `NEW_AND_OLD_IMAGES`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CdcSpecificationSummary

The settings of the CDC stream of the table. For more information about CDC streams, see [Working with change data capture \(CDC\) streams in Amazon Keyspaces](#) in the *Amazon Keyspaces Developer Guide*.

Contents

status

The status of the CDC stream. Specifies if the table has a CDC stream.

Type: String

Valid Values: ENABLED | ENABLING | DISABLED | DISABLING

Required: Yes

viewType

The view type specifies the changes Amazon Keyspaces records for each changed row in the stream. This setting can't be changed, after the stream has been created.

The options are:

- NEW_AND_OLD_IMAGES - both versions of the row, before and after the change. This is the default.
- NEW_IMAGE - the version of the row after the change.
- OLD_IMAGE - the version of the row before the change.
- KEYS_ONLY - the partition and clustering keys of the row that was changed.

Type: String

Valid Values: NEW_IMAGE | OLD_IMAGE | KEYS_ONLY | NEW_AND_OLD_IMAGES

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClientSideTimestamps

The client-side timestamp setting of the table.

For more information, see [How it works: Amazon Keyspaces client-side timestamps](#) in the *Amazon Keyspaces Developer Guide*.

Contents

status

Shows how to enable client-side timestamps settings for the specified table.

Type: String

Valid Values: ENABLED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClusteringKey

The optional clustering column portion of your primary key determines how the data is clustered and sorted within each partition.

Contents

name

The name(s) of the clustering column(s).

Type: String

Required: Yes

orderBy

Sets the ascendant (ASC) or descendant (DESC) order modifier.

Type: String

Valid Values: ASC | DESC

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ColumnDefinition

The names and data types of regular columns.

Contents

name

The name of the column.

Type: String

Required: Yes

type

The data type of the column. For a list of available data types, see [Data types](#) in the *Amazon Keyspaces Developer Guide*.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Comment

An optional comment that describes the table.

Contents

message

An optional description of the table.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionSpecification

Amazon Keyspaces encrypts and decrypts the table data at rest transparently and integrates with AWS Key Management Service for storing and managing the encryption key. You can choose one of the following AWS KMS keys (KMS keys):

- **AWS owned key** - This is the default encryption type. The key is owned by Amazon Keyspaces (no additional charge).
- **Customer managed key** - This key is stored in your account and is created, owned, and managed by you. You have full control over the customer managed key (AWS KMS charges apply).

For more information about encryption at rest in Amazon Keyspaces, see [Encryption at rest](#) in the *Amazon Keyspaces Developer Guide*.

For more information about AWS KMS, see [AWS KMS management service concepts](#) in the *AWS Key Management Service Developer Guide*.

Contents

type

The encryption option specified for the table. You can choose one of the following KMS keys (KMS keys):

- `type:AWS_OWNED_KMS_KEY` - This key is owned by Amazon Keyspaces.
- `type:CUSTOMER_MANAGED_KMS_KEY` - This key is stored in your account and is created, owned, and managed by you. This option requires the `kms_key_identifier` of the KMS key in Amazon Resource Name (ARN) format as input.

The default is `type:AWS_OWNED_KMS_KEY`.

For more information, see [Encryption at rest](#) in the *Amazon Keyspaces Developer Guide*.

Type: String

Valid Values: `CUSTOMER_MANAGED_KMS_KEY` | `AWS_OWNED_KMS_KEY`

Required: Yes

kmsKeyIdentifier

The Amazon Resource Name (ARN) of the customer managed KMS key, for example `kms_key_identifier:ARN`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 5096.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FieldDefinition

A field definition consists out of a name and a type.

Contents

name

The identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

type

Any supported Cassandra data type, including collections and other user-defined types that are contained in the same keyspace.

For more information, see [Cassandra data type support](#) in the *Amazon Keyspaces Developer Guide*.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

KeyspaceSummary

Represents the properties of a keyspace.

Contents

keyspaceName

The name of the keyspace.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

replicationStrategy

This property specifies if a keyspace is a single Region keyspace or a multi-Region keyspace. The available values are `SINGLE_REGION` or `MULTI_REGION`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Valid Values: `SINGLE_REGION` | `MULTI_REGION`

Required: Yes

resourceArn

The unique identifier of the keyspace in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*`

Required: Yes

replicationRegions

If the `replicationStrategy` of the keyspace is `MULTI_REGION`, a list of replication Regions is returned.

Type: Array of strings

Array Members: Minimum number of 2 items.

Length Constraints: Minimum length of 2. Maximum length of 25.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PartitionKey

The partition key portion of the primary key is required and determines how Amazon Keyspaces stores the data. The partition key can be a single column, or it can be a compound value composed of two or more columns.

Contents

name

The name(s) of the partition key column(s).

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PointInTimeRecovery

Point-in-time recovery (PITR) helps protect your Amazon Keyspaces tables from accidental write or delete operations by providing you continuous backups of your table data.

For more information, see [Point-in-time recovery](#) in the *Amazon Keyspaces Developer Guide*.

Contents

status

The options are:

- status=ENABLED
- status=DISABLED

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PointInTimeRecoverySummary

The point-in-time recovery status of the specified table.

Contents

status

Shows if point-in-time recovery is enabled or disabled for the specified table.

Type: String

Valid Values: ENABLED | DISABLED

Required: Yes

earliestRestorableTimestamp

Specifies the earliest possible restore point of the table in ISO 8601 format.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicaAutoScalingSpecification

The auto scaling settings of a multi-Region table in the specified AWS Region.

Contents

autoScalingSpecification

The auto scaling settings for a multi-Region table in the specified AWS Region.

Type: [AutoScalingSpecification](#) object

Required: No

region

The AWS Region.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 25.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicaSpecification

The AWS Region specific settings of a multi-Region table.

For a multi-Region table, you can configure the table's read capacity differently per AWS Region. You can do this by configuring the following parameters.

- `region`: The Region where these settings are applied. (Required)
- `readCapacityUnits`: The provisioned read capacity units. (Optional)
- `readCapacityAutoScaling`: The read capacity auto scaling settings for the table. (Optional)

Contents

region

The AWS Region.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 25.

Required: Yes

readCapacityAutoScaling

The read capacity auto scaling settings for the multi-Region table in the specified AWS Region.

Type: [AutoScalingSettings](#) object

Required: No

readCapacityUnits

The provisioned read capacity units for the multi-Region table in the specified AWS Region.

Type: Long

Valid Range: Minimum value of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicaSpecificationSummary

The Region-specific settings of a multi-Region table in the specified AWS Region.

If the multi-Region table is using provisioned capacity and has optional auto scaling policies configured, note that the Region specific summary returns both read and write capacity settings. But only Region specific read capacity settings can be configured for a multi-Region table. In a multi-Region table, your write capacity units will be synced across all AWS Regions to ensure that there is enough capacity to replicate write events across Regions.

Contents

capacitySpecification

The read/write throughput capacity mode for a table. The options are:

- `throughputMode:PAY_PER_REQUEST` and
- `throughputMode:PROVISIONED`.

For more information, see [Read/write capacity modes](#) in the *Amazon Keyspaces Developer Guide*.

Type: [CapacitySpecificationSummary](#) object

Required: No

region

The AWS Region.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 25.

Required: No

status

The status of the multi-Region table in the specified AWS Region.

Type: String

Valid Values: ACTIVE | CREATING | UPDATING | DELETING | DELETED | RESTORING
| INACCESSIBLE_ENCRYPTION_CREDENTIALS

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicationGroupStatus

This shows the summary status of the keyspace after a new AWS Region was added.

Contents

keyspaceStatus

The status of the keyspace.

Type: String

Valid Values: ACTIVE | CREATING | UPDATING | DELETING

Required: Yes

region

The name of the Region that was added to the keyspace.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 25.

Required: Yes

tablesReplicationProgress

This shows the replication progress of tables in the keyspace. The value is expressed as a percentage of the newly replicated tables with status `Active` compared to the total number of tables in the keyspace.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 7.

Pattern: `[0-9]{1,3}(:[.][0-9]{1,2})?%`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplicationSpecification

The replication specification of the keyspace includes:

- `regionList` - the AWS Regions where the keyspace is replicated in.
- `replicationStrategy` - the required value is `SINGLE_REGION` or `MULTI_REGION`.

Contents

`replicationStrategy`

The `replicationStrategy` of a keyspace, the required value is `SINGLE_REGION` or `MULTI_REGION`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20.

Valid Values: `SINGLE_REGION` | `MULTI_REGION`

Required: Yes

`regionList`

The `regionList` contains the AWS Regions where the keyspace is replicated in.

Type: Array of strings

Array Members: Minimum number of 2 items.

Length Constraints: Minimum length of 2. Maximum length of 25.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

SchemaDefinition

Describes the schema of the table.

Contents

allColumns

The regular columns of the table.

Type: Array of [ColumnDefinition](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

partitionKeys

The columns that are part of the partition key of the table .

Type: Array of [PartitionKey](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

clusteringKeys

The columns that are part of the clustering key of the table.

Type: Array of [ClusteringKey](#) objects

Required: No

staticColumns

The columns that have been defined as STATIC. Static columns store values that are shared by all rows in the same partition.

Type: Array of [StaticColumn](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StaticColumn

The static columns of the table. Static columns store values that are shared by all rows in the same partition.

Contents

name

The name of the static column.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TableSummary

Returns the name of the specified table, the keyspace it is stored in, and the unique identifier in the format of an Amazon Resource Name (ARN).

Contents

keyspaceName

The name of the keyspace that the table is stored in.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

resourceArn

The unique identifier of the table in the format of an Amazon Resource Name (ARN).

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.+.*`

Required: Yes

tableName

The name of the table.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 48.

Pattern: `[a-zA-Z0-9][a-zA-Z0-9_]{0,47}`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

Describes a tag. A tag is a key-value pair. You can add up to 50 tags to a single Amazon Keyspaces resource.

AWS-assigned tag names and values are automatically assigned the `aws :` prefix, which the user cannot assign. AWS-assigned tag names do not count towards the tag limit of 50. User-assigned tag names have the prefix `user :` in the Cost Allocation Report. You cannot backdate the application of a tag.

For more information, see [Adding tags and labels to Amazon Keyspaces resources](#) in the *Amazon Keyspaces Developer Guide*.

Contents

key

The key of the tag. Tag keys are case sensitive. Each Amazon Keyspaces resource can only have up to one tag with the same key. If you try to add an existing tag (same key), the existing tag value will be updated to the new value.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value of the tag. Tag values are case-sensitive and can be null.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetTrackingScalingPolicyConfiguration

The auto scaling policy that scales a table based on the ratio of consumed to provisioned capacity.

Contents

targetValue

Specifies the target value for the target tracking auto scaling policy.

Amazon Keyspaces auto scaling scales up capacity automatically when traffic exceeds this target utilization rate, and then back down when it falls below the target. This ensures that the ratio of consumed capacity to provisioned capacity stays at or near this value. You define `targetValue` as a percentage. A double between 20 and 90.

Type: Double

Required: Yes

disableScaleIn

Specifies if `scale-in` is enabled.

When auto scaling automatically decreases capacity for a table, the table *scales in*. When scaling policies are set, they can't scale in the table lower than its minimum capacity.

Type: Boolean

Required: No

scaleInCooldown

Specifies a `scale-in` cool down period.

A cooldown period in seconds between scaling activities that lets the table stabilize before another scaling activity starts.

Type: Integer

Required: No

scaleOutCooldown

Specifies a scale out cool down period.

A cooldown period in seconds between scaling activities that lets the table stabilize before another scaling activity starts.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TimeToLive

Enable custom Time to Live (TTL) settings for rows and columns without setting a TTL default for the specified table.

For more information, see [Enabling TTL on tables](#) in the *Amazon Keyspaces Developer Guide*.

Contents

status

Shows how to enable custom Time to Live (TTL) settings for the specified table.

Type: String

Valid Values: ENABLED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Service-specific Errors

The Amazon Keyspaces API contains service-specific exceptions that various actions return. This section describes each exception in detail.

The following service-specific exceptions are returned:

- [AccessDeniedException](#)
- [ConflictException](#)
- [InternalServerException](#)
- [ResourceNotFoundException](#)
- [ServiceQuotaExceededException](#)
- [ValidationException](#)

AccessDeniedException

You don't have sufficient access permissions to perform this action.

HTTP Status Code returned: 400

Contents

message

You don't have the required permissions to perform this operation. Verify your IAM permissions and try again.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ConflictException

Amazon Keyspaces couldn't complete the requested action. This error may occur if you try to perform an action and the same or a different action is already in progress, or if you try to create a resource that already exists.

HTTP Status Code returned: 400

Contents

message

The requested operation conflicts with the current state of the resource or another concurrent operation.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

InternalServerErrorException

Amazon Keyspaces was unable to fully process this request because of an internal server error.

HTTP Status Code returned: 500

Contents

message

An internal service error occurred. Retry your request. If the problem persists, contact AWS Support.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ResourceNotFoundException

The operation tried to access a keyspace, table, or type that doesn't exist. The resource might not be specified correctly, or its status might not be ACTIVE.

HTTP Status Code returned: 400

Contents

message

The specified resource was not found. Verify the resource identifier and ensure the resource exists and is in an ACTIVE state.

Type: String

Required: No

resourceArn

The unique identifier in the format of Amazon Resource Name (ARN) for the resource couldn't be found.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1000.

Pattern: `arn:(aws[a-zA-Z0-9-]*):cassandra:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ServiceQuotaExceededException

The operation exceeded the service quota for this resource. For more information on service quotas, see [Quotas](#) in the *Amazon Keyspaces Developer Guide*.

HTTP Status Code returned: 400

Contents

message

The requested operation would exceed the service quota for this resource. Review the service quotas and adjust your request accordingly.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

ValidationException

The operation failed due to an invalid or malformed request.

HTTP Status Code returned: 400

Contents

message

The request parameters are invalid or malformed. Review the API documentation and correct the request format.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400