



Live API Reference

AWS Elemental MediaPackage V2 Live API



API Version 2022-12-25

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS Elemental MediaPackage V2 Live API: Live API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CancelHarvestJob	4
Request Syntax	4
URI Request Parameters	4
Request Body	5
Response Syntax	5
Response Elements	5
Errors	5
See Also	6
CreateChannel	8
Request Syntax	8
URI Request Parameters	8
Request Body	9
Response Syntax	11
Response Elements	11
Errors	13
See Also	15
CreateChannelGroup	16
Request Syntax	16
URI Request Parameters	16
Request Body	16
Response Syntax	17
Response Elements	18
Errors	19
See Also	20
CreateHarvestJob	22
Request Syntax	22
URI Request Parameters	23
Request Body	24
Response Syntax	25
Response Elements	26
Errors	28
See Also	30

CreateOriginEndpoint	31
Request Syntax	31
URI Request Parameters	35
Request Body	35
Response Syntax	38
Response Elements	42
Errors	45
See Also	46
DeleteChannel	47
Request Syntax	47
URI Request Parameters	47
Request Body	47
Response Syntax	47
Response Elements	48
Errors	48
See Also	49
DeleteChannelGroup	50
Request Syntax	50
URI Request Parameters	50
Request Body	50
Response Syntax	50
Response Elements	50
Errors	50
See Also	51
DeleteChannelPolicy	53
Request Syntax	53
URI Request Parameters	53
Request Body	53
Response Syntax	53
Response Elements	54
Errors	54
See Also	55
DeleteOriginEndpoint	56
Request Syntax	56
URI Request Parameters	56
Request Body	57

Response Syntax	57
Response Elements	57
Errors	57
See Also	58
DeleteOriginEndpointPolicy	59
Request Syntax	59
URI Request Parameters	59
Request Body	60
Response Syntax	60
Response Elements	60
Errors	60
See Also	61
GetChannel	62
Request Syntax	62
URI Request Parameters	62
Request Body	62
Response Syntax	62
Response Elements	63
Errors	66
See Also	66
GetChannelGroup	68
Request Syntax	68
URI Request Parameters	68
Request Body	68
Response Syntax	68
Response Elements	69
Errors	70
See Also	71
GetChannelPolicy	72
Request Syntax	72
URI Request Parameters	72
Request Body	72
Response Syntax	73
Response Elements	73
Errors	73
See Also	74

GetHarvestJob	76
Request Syntax	76
URI Request Parameters	76
Request Body	77
Response Syntax	77
Response Elements	78
Errors	81
See Also	81
GetOriginEndpoint	83
Request Syntax	83
URI Request Parameters	83
Request Body	84
Response Syntax	84
Response Elements	88
Errors	91
See Also	92
GetOriginEndpointPolicy	93
Request Syntax	93
URI Request Parameters	93
Request Body	94
Response Syntax	94
Response Elements	94
Errors	95
See Also	96
ListChannelGroups	98
Request Syntax	98
URI Request Parameters	98
Request Body	98
Response Syntax	98
Response Elements	99
Errors	99
See Also	100
ListChannels	101
Request Syntax	101
URI Request Parameters	101
Request Body	101

Response Syntax	101
Response Elements	102
Errors	102
See Also	103
ListHarvestJobs	105
Request Syntax	105
URI Request Parameters	105
Request Body	106
Response Syntax	106
Response Elements	107
Errors	108
See Also	109
ListOriginEndpoints	110
Request Syntax	110
URI Request Parameters	110
Request Body	111
Response Syntax	111
Response Elements	112
Errors	112
See Also	113
ListTagsForResource	115
Request Syntax	115
URI Request Parameters	115
Request Body	115
Response Syntax	115
Response Elements	115
Errors	116
See Also	116
PutChannelPolicy	117
Request Syntax	117
URI Request Parameters	117
Request Body	118
Response Syntax	118
Response Elements	118
Errors	118
See Also	119

PutOriginEndpointPolicy	121
Request Syntax	121
URI Request Parameters	121
Request Body	122
Response Syntax	122
Response Elements	123
Errors	123
See Also	124
ResetChannelState	125
Request Syntax	125
URI Request Parameters	125
Request Body	125
Response Syntax	126
Response Elements	126
Errors	126
See Also	127
ResetOriginEndpointState	129
Request Syntax	129
URI Request Parameters	129
Request Body	130
Response Syntax	130
Response Elements	130
Errors	131
See Also	132
TagResource	134
Request Syntax	134
URI Request Parameters	134
Request Body	134
Response Syntax	135
Response Elements	135
Errors	135
See Also	135
UntagResource	137
Request Syntax	137
URI Request Parameters	137
Request Body	137

Response Syntax	137
Response Elements	137
Errors	137
See Also	138
UpdateChannel	139
Request Syntax	139
URI Request Parameters	139
Request Body	140
Response Syntax	141
Response Elements	142
Errors	144
See Also	145
UpdateChannelGroup	146
Request Syntax	146
URI Request Parameters	146
Request Body	147
Response Syntax	147
Response Elements	147
Errors	149
See Also	150
UpdateOriginEndpoint	151
Request Syntax	151
URI Request Parameters	155
Request Body	156
Response Syntax	158
Response Elements	162
Errors	165
See Also	166
Data Types	167
CdnAuthConfiguration	169
Contents	169
See Also	169
ChannelGroupListConfiguration	170
Contents	170
See Also	171
ChannelListConfiguration	172

Contents	172
See Also	173
CreateDashManifestConfiguration	174
Contents	174
See Also	178
CreateHlsManifestConfiguration	179
Contents	179
See Also	181
CreateLowLatencyHlsManifestConfiguration	182
Contents	182
See Also	184
CreateMssManifestConfiguration	185
Contents	185
See Also	186
(baseUrl) DashBaseUrl	187
Contents	187
See Also	188
(baseUrl) DashDvbFontDownload	189
Contents	189
See Also	190
(baseUrl) DashDvbMetricsReporting	191
Contents	191
See Also	191
(baseUrl) DashDvbSettings	192
Contents	192
See Also	192
(baseUrl) DashProgramInformation	193
Contents	193
See Also	194
(baseUrl) DashSubtitleConfiguration	195
Contents	195
See Also	195
(baseUrl) DashTtmlConfiguration	196
Contents	196
See Also	196
(baseUrl) DashUtcTiming	197

Contents	197
See Also	197
Destination	198
Contents	198
See Also	198
Encryption	199
Contents	199
See Also	200
EncryptionContractConfiguration	201
Contents	201
See Also	202
EncryptionMethod	203
Contents	203
See Also	203
FilterConfiguration	205
Contents	205
See Also	206
ForceEndpointErrorConfiguration	207
Contents	207
See Also	207
GetDashManifestConfiguration	208
Contents	208
See Also	212
GetHlsManifestConfiguration	213
Contents	213
See Also	215
GetLowLatencyHlsManifestConfiguration	216
Contents	216
See Also	218
GetMssManifestConfiguration	219
Contents	219
See Also	220
HarvestedDashManifest	221
Contents	221
See Also	221
HarvestedHlsManifest	222

Contents	222
See Also	222
HarvestedLowLatencyHlsManifest	223
Contents	223
See Also	223
HarvestedManifests	224
Contents	224
See Also	224
HarvesterScheduleConfiguration	225
Contents	225
See Also	225
HarvestJob	226
Contents	226
See Also	229
IngestEndpoint	230
Contents	230
See Also	230
InputSwitchConfiguration	231
Contents	231
See Also	231
ListDashManifestConfiguration	232
Contents	232
See Also	232
ListHlsManifestConfiguration	233
Contents	233
See Also	234
ListLowLatencyHlsManifestConfiguration	235
Contents	235
See Also	236
ListMssManifestConfiguration	237
Contents	237
See Also	237
OriginEndpointListConfiguration	238
Contents	238
See Also	240
OutputHeaderConfiguration	242

Contents	242
See Also	242
S3DestinationConfig	243
Contents	243
See Also	243
Scte	244
Contents	244
See Also	244
ScteDash	245
Contents	245
See Also	245
ScteHls	246
Contents	246
See Also	246
Segment	247
Contents	247
See Also	248
SpekeKeyProvider	249
Contents	249
See Also	250
StartTag	251
Contents	251
See Also	251
Common Parameters	252
Common Errors	255

Welcome

Note

This guide is intended for creating AWS Elemental MediaPackage resources in MediaPackage Version 2 (v2) starting from May 2023. To get started with MediaPackage v2, create your MediaPackage resources. There isn't an automated process to migrate your resources from MediaPackage v1 to MediaPackage v2.

The names of the entities that you use to access this API, like URLs and ARNs, all have the versioning information added, like "v2", to distinguish from the prior version. If you used MediaPackage prior to this release, you can't use the MediaPackage v2 CLI or the MediaPackage v2 API to access any MediaPackage v1 resources.

If you created resources in MediaPackage v1, use video on demand (VOD) workflows, and aren't looking to migrate to MediaPackage v2 yet, see the [MediaPackage v1 Live API Reference](#).

This is the AWS Elemental MediaPackage v2 Live REST API Reference. It describes all the MediaPackage API operations for live content in detail, and provides sample requests, responses, and errors for the supported web services protocols.

We assume that you have the IAM permissions that you need to use MediaPackage via the REST API. We also assume that you are familiar with the features and operations of MediaPackage, as described in the AWS Elemental MediaPackage User Guide.

This document was last published on September 3, 2025.

Actions

The following actions are supported:

- [CancelHarvestJob](#)
- [CreateChannel](#)
- [CreateChannelGroup](#)
- [CreateHarvestJob](#)
- [CreateOriginEndpoint](#)
- [DeleteChannel](#)
- [DeleteChannelGroup](#)
- [DeleteChannelPolicy](#)
- [DeleteOriginEndpoint](#)
- [DeleteOriginEndpointPolicy](#)
- [GetChannel](#)
- [GetChannelGroup](#)
- [GetChannelPolicy](#)
- [GetHarvestJob](#)
- [GetOriginEndpoint](#)
- [GetOriginEndpointPolicy](#)
- [ListChannelGroups](#)
- [ListChannels](#)
- [ListHarvestJobs](#)
- [ListOriginEndpoints](#)
- [ListTagsForResource](#)
- [PutChannelPolicy](#)
- [PutOriginEndpointPolicy](#)
- [ResetChannelState](#)
- [ResetOriginEndpointState](#)
- [TagResource](#)
- [UntagResource](#)

- [UpdateChannel](#)
- [UpdateChannelGroup](#)
- [UpdateOriginEndpoint](#)

CancelHarvestJob

Cancels an in-progress harvest job.

Request Syntax

```
PUT /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName/harvestJob/HarvestJobName HTTP/1.1  
x-amzn-update-if-match: ETag
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name of the channel group containing the channel from which the harvest job is running.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name of the channel from which the harvest job is running.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ETag

The current Entity Tag (ETag) associated with the harvest job. Used for concurrency control.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

HarvestJobName

The name of the harvest job to cancel. This name must be unique within the channel and cannot be changed after the harvest job is submitted.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OriginEndpointName

The name of the origin endpoint that the harvest job is harvesting from. This cannot be changed after the harvest job is submitted.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is

making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateChannel

Create a channel to start receiving content streams. The channel represents the input to MediaPackage for incoming live content from an encoder such as AWS Elemental MediaLive. The channel receives content, and after packaging it, outputs it through an origin endpoint to downstream devices (such as video players or CDNs) that request the content. You can create only one channel with each request. We recommend that you spread out channels between channel groups, such as putting redundant channels in the same AWS Region in different channel groups.

Request Syntax

```
POST /channelGroup/ChannelGroupName/channel HTTP/1.1
x-amzn-client-token: ClientToken
Content-type: application/json

{
  "ChannelName": "string",
  "Description": "string",
  "InputSwitchConfiguration": {
    "MQCSInputSwitchingPreferredInput": number
  },
  "InputType": "string",
  "OutputHeaderConfiguration": {
    "PublishMQCS": boolean
  },
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[ClientToken](#)

A unique, case-sensitive token that you provide to ensure the idempotency of the request.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

Request Body

The request accepts the following data in JSON format.

[ChannelName](#)

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group. You can't change the name after you create the channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[Description](#)

Enter any descriptive text that helps you to identify the channel.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

[InputSwitchConfiguration](#)

The configuration for input switching based on the media quality confidence score (MQCS) as provided from AWS Elemental MediaLive. This setting is valid only when InputType is CMAF.

Type: [InputSwitchConfiguration](#) object

Required: No

[InputType](#)

The input type will be an immutable field which will be used to define whether the channel will allow CMAF ingest or HLS ingest. If unprovided, it will default to HLS to preserve current behavior.

The allowed values are:

- HLS - The HLS streaming specification (which defines M3U8 manifests and TS segments).
- CMAF - The DASH-IF CMAF Ingest specification (which defines CMAF segments with optional DASH manifests).

Type: String

Valid Values: HLS | CMAF

Required: No

[OutputHeaderConfiguration](#)

The settings for what common media server data (CMSD) headers AWS Elemental MediaPackage includes in responses to the CDN. This setting is valid only when InputType is CMAF.

Type: [OutputHeaderConfiguration](#) object

Required: No

[tags](#)

A comma-separated list of tag key:value pairs that you define. For example:

```
"Key1": "Value1",
```

```
"Key2": "Value2"
```

Type: String to string map

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ChannelGroupName": "string",
  "ChannelName": "string",
  "CreatedAt": number,
  "Description": "string",
  "ETag": "string",
  "IngestEndpoints": [
    {
      "Id": "string",
      "Url": "string"
    }
  ],
  "InputSwitchConfiguration": {
    "MQCSInputSwitching": boolean,
    "PreferredInput": number
  },
  "InputType": "string",
  "ModifiedAt": number,
  "OutputHeaderConfiguration": {
    "PublishMQCS": boolean
  },
  "Tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

CreatedAt

The date and time the channel was created.

Type: Timestamp

Description

The description for your channel.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

ETag

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

IngestEndpoints

The list of ingest endpoints.

Type: Array of [IngestEndpoint](#) objects

[InputSwitchConfiguration](#)

The configuration for input switching based on the media quality confidence score (MQCS) as provided from AWS Elemental MediaLive. This setting is valid only when InputType is CMAF.

Type: [InputSwitchConfiguration](#) object

[InputType](#)

The input type will be an immutable field which will be used to define whether the channel will allow CMAF ingest or HLS ingest. If unprovided, it will default to HLS to preserve current behavior.

The allowed values are:

- HLS - The HLS streaming specification (which defines M3U8 manifests and TS segments).
- CMAF - The DASH-IF CMAF Ingest specification (which defines CMAF segments with optional DASH manifests).

Type: String

Valid Values: HLS | CMAF

[ModifiedAt](#)

The date and time the channel was modified.

Type: Timestamp

[OutputHeaderConfiguration](#)

The settings for what common media server data (CMSD) headers AWS Elemental MediaPackage includes in responses to the CDN. This setting is valid only when InputType is CMAF.

Type: [OutputHeaderConfiguration](#) object

[Tags](#)

The comma-separated list of tag key:value pairs assigned to the channel.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateChannelGroup

Create a channel group to group your channels and origin endpoints. A channel group is the top-level resource that consists of channels and origin endpoints that are associated with it and that provides predictable URLs for stream delivery. All channels and origin endpoints within the channel group are guaranteed to share the DNS. You can create only one channel group with each request.

Request Syntax

```
POST /channelGroup HTTP/1.1
x-amzn-client-token: ClientToken
Content-type: application/json

{
  "ChannelGroupName": "string",
  "Description": "string",
  "tags": {
    "string": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ClientToken

A unique, case-sensitive token that you provide to ensure the idempotency of the request.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

Request Body

The request accepts the following data in JSON format.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region. You can't use spaces in the name. You can't change the name after you create the channel group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Description

Enter any descriptive text that helps you to identify the channel group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

tags

A comma-separated list of tag key:value pairs that you define. For example:

"Key1": "Value1",

"Key2": "Value2"

Type: String to string map

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
```

```
"Arn": "string",
"ChannelGroupName": "string",
"CreatedAt": number,
"Description": "string",
"EgressDomain": "string",
"ETag": "string",
"ModifiedAt": number,
"Tags": {
    "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

CreatedAt

The date and time the channel group was created.

Type: Timestamp

Description

The description for your channel group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

EgressDomain

The output domain where the source stream should be sent. Integrate the egress domain with a downstream CDN (such as Amazon CloudFront) or playback device.

Type: String

ETag

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

ModifiedAt

The date and time the channel group was modified.

Type: Timestamp

Tags

The comma-separated list of tag key:value pairs assigned to the channel group.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateHarvestJob

Creates a new harvest job to export content from a MediaPackage v2 channel to an S3 bucket.

Request Syntax

```
POST /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName/harvestJob HTTP/1.1  
x-amzn-client-token: ClientToken  
Content-type: application/json  
  
{  
    "Description": "string",  
    "Destination": {  
        "S3Destination": {  
            "BucketName": "string",  
            "DestinationPath": "string"  
        }  
    },  
    "HarvestedManifests": {  
        "DashManifests": [  
            {  
                "ManifestName": "string"  
            }  
        ],  
        "HlsManifests": [  
            {  
                "ManifestName": "string"  
            }  
        ],  
        "LowLatencyHlsManifests": [  
            {  
                "ManifestName": "string"  
            }  
        ]  
    },  
    "HarvestJobName": "string",  
    "ScheduleConfiguration": {  
        "EndTime": number,  
        "StartTime": number  
    },  
    "Tags": {  
        "string": "string"  
    }  
}
```

```
    }  
}
```

URI Request Parameters

The request uses the following URI parameters.

[ChannelGroupName](#)

The name of the channel group containing the channel from which to harvest content.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[ChannelName](#)

The name of the channel from which to harvest content.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[ClientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

[OriginEndpointName](#)

The name of the origin endpoint from which to harvest content.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

An optional description for the harvest job.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Destination

The S3 destination where the harvested content will be placed.

Type: [Destination](#) object

Required: Yes

HarvestedManifests

A list of manifests to be harvested.

Type: [HarvestedManifests](#) object

Required: Yes

HarvestJobName

A name for the harvest job. This name must be unique within the channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

ScheduleConfiguration

The configuration for when the harvest job should run, including start and end times.

Type: [HarvesterScheduleConfiguration](#) object

Required: Yes

Tags

A collection of tags associated with the harvest job.

Type: String to string map

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ChannelGroupName": "string",
  "ChannelName": "string",
  "CreatedAt": number,
  "Description": "string",
  "Destination": {
    "S3Destination": {
      "BucketName": "string",
      "DestinationPath": "string"
    }
  },
  "ErrorMessage": "string",
  "ETag": "string",
  "HarvestedManifests": [
    "DashManifests": [
      {
        "ManifestName": "string"
      }
    ],
    "HlsManifests": [
      {
        "ManifestName": "string"
      }
    ],
    "LowLatencyHlsManifests": [
      ...
    ]
  ]
}
```

```
{  
    "ManifestName": "string"  
}  
]  
,  
"HarvestJobName": "string",  
"ModifiedAt": number,  
"OriginEndpointName": "string",  
"ScheduleConfiguration": {  
    "EndTime": number,  
    "StartTime": number  
,  
    "Status": "string",  
    "Tags": {  
        "string" : "string"  
    }  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the created harvest job.

Type: String

ChannelGroupName

The name of the channel group containing the channel from which content is being harvested.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ChannelName

The name of the channel from which content is being harvested.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

CreatedAt

The date and time the harvest job was created.

Type: Timestamp

Description

The description of the harvest job, if provided.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Destination

The S3 destination where the harvested content will be placed.

Type: [Destination](#) object

ErrorMessage

An error message if the harvest job creation failed.

Type: String

ETag

The current version of the harvest job. Used for concurrency control.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

HarvestedManifests

A list of manifests that will be harvested.

Type: [HarvestedManifests](#) object

HarvestJobName

The name of the created harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ModifiedAt

The date and time the harvest job was last modified.

Type: Timestamp

OriginEndpointName

The name of the origin endpoint from which content is being harvested.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ScheduleConfiguration

The configuration for when the harvest job will run, including start and end times.

Type: [HarvesterScheduleConfiguration](#) object

Status

The current status of the harvest job (e.g., CREATED, IN_PROGRESS, ABORTED, COMPLETED, FAILED).

Type: String

Valid Values: QUEUED | IN_PROGRESS | CANCELLED | COMPLETED | FAILED

Tags

A collection of tags associated with the harvest job.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateOriginEndpoint

The endpoint is attached to a channel, and represents the output of the live content. You can associate multiple endpoints to a single channel. Each endpoint gives players and downstream CDNs (such as Amazon CloudFront) access to the content for playback. Content can't be served from a channel until it has an endpoint. You can create only one endpoint with each request.

Request Syntax

```
POST /channelGroup/ChannelGroupName/channel/ChannelName/originEndpoint HTTP/1.1
x-amzn-client-token: ClientToken
Content-type: application/json

{
  "ContainerTypeDashManifestsBaseUrlsDvbPriorityDvbWeightServiceLocationUrlCompactnessDrmSignalingDvbSettingsErrorMetricsProbabilityReportingUrlFontDownloadFontFamilyMimeTypeUrlFilterConfigurationClipStartTime
```

```
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "MinBufferTimeSeconds": number,
    "MinUpdatePeriodSeconds": number,
    "PeriodTriggers": [ "string" ],
    "Profiles": [ "string" ],
    "ProgramInformation": {
        "Copyright": "string",
        "LanguageCode": "string",
        "MoreInformationUrl": "string",
        "Source": "string",
        "Title": "string"
    },
    "ScteDash": {
        "AdMarkerDash": "string"
    },
    "SegmentTemplateFormat": "string",
    "SubtitleConfiguration": {
        "TtmlConfiguration": {
            "TtmlProfile": "string"
        }
    },
    "SuggestedPresentationDelaySeconds": number,
    "UtcTiming": {
        "TimingMode": "string",
        "TimingSource": "string"
    }
}
],
"Description": "string",
"ForceEndpointErrorConfiguration": {
    "EndpointErrorConditions": [ "string" ]
},
"HlsManifests": [
{
    "ChildManifestName": "string",
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number,
        "Start": number
    }
}
```

```
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "ProgramDateTimeIntervalSeconds": number,
    "ScteHls": {
        "AdMarkerHls": "string"
    },
    "StartTag": {
        "Precise": boolean,
        "TimeOffset": number
    },
    "UrlEncodeChildManifest": boolean
}
],
"LowLatencyHlsManifests": [
{
    "ChildManifestName": "string",
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "ProgramDateTimeIntervalSeconds": number,
    "ScteHls": {
        "AdMarkerHls": "string"
    },
    "StartTag": {
        "Precise": boolean,
        "TimeOffset": number
    },
    "UrlEncodeChildManifest": boolean
}
],
"MssManifests": [
{
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number
    }
}]
```

```
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestLayout": "string",
    "ManifestName": "string",
    "ManifestWindowSeconds": number
}
],
"OriginEndpointName": "string",
"Segment": {
    "Encryption": {
        "CmafExcludeSegmentDrmMetadata": boolean,
        "ConstantInitializationVector": "string",
        "EncryptionMethod": {
            "CmafEncryptionMethod": "string",
            "IsmEncryptionMethod": "string",
            "TsEncryptionMethod": "string"
        },
        "KeyRotationIntervalSeconds": number,
        "SpekeKeyProvider": {
            "DrmSystems": [ "string" ],
            "EncryptionContractConfiguration": {
                "PresetSpeke20Audio": "string",
                "PresetSpeke20Video": "string"
            },
            "ResourceId": "string",
            "RoleArn": "string",
            "Url": "string"
        }
    },
    "IncludeIframeOnlyStreams": boolean,
    "Scte": {
        "ScteFilter": [ "string" ]
    },
    "SegmentDurationSeconds": number,
    "SegmentName": "string",
    "TsIncludeDvbSubtitles": boolean,
    "TsUseAudioRenditionGroup": boolean
},
"StartoverWindowSeconds": number,
"Tags": {
    "string" : "string"
```

```
    }  
}
```

URI Request Parameters

The request uses the following URI parameters.

[ChannelGroupName](#)

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[ChannelName](#)

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[ClientToken](#)

A unique, case-sensitive token that you provide to ensure the idempotency of the request.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

Request Body

The request accepts the following data in JSON format.

ContainerType

The type of container to attach to this origin endpoint. A container type is a file format that encapsulates one or more media streams, such as audio and video, into a single file. You can't change the container type after you create the endpoint.

Type: String

Valid Values: TS | CMAF | ISM

Required: Yes

DashManifests

A DASH manifest configuration.

Type: Array of [CreateDashManifestConfiguration](#) objects

Required: No

Description

Enter any descriptive text that helps you to identify the origin endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ForceEndpointErrorConfiguration

The failover settings for the endpoint.

Type: [ForceEndpointErrorConfiguration](#) object

Required: No

HlsManifests

An HTTP live streaming (HLS) manifest configuration.

Type: Array of [CreateHlsManifestConfiguration](#) objects

Required: No

LowLatencyHlsManifests

A low-latency HLS manifest configuration.

Type: Array of [CreateLowLatencyHlsManifestConfiguration](#) objects

Required: No

MssManifests

A list of Microsoft Smooth Streaming (MSS) manifest configurations for the origin endpoint. You can configure multiple MSS manifests to provide different streaming experiences or to support different client requirements.

Type: Array of [CreateMssManifestConfiguration](#) objects

Required: No

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel. You can't use spaces in the name. You can't change the name after you create the endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Segment

The segment configuration, including the segment name, duration, and other configuration values.

Type: [Segment](#) object

Required: No

StartoverWindowSeconds

The size of the window (in seconds) to create a window of the live stream that's available for on-demand viewing. Viewers can start-over or catch-up on content that falls within the window. The maximum startover window is 1,209,600 seconds (14 days).

Type: Integer

Valid Range: Minimum value of 60. Maximum value of 1209600.

Required: No

Tags

A comma-separated list of tag key:value pairs that you define. For example:

```
"Key1": "Value1",
```

```
"Key2": "Value2"
```

Type: String to string map

Required: No

Response Syntax

HTTP/1.1 200
Content-type: application/json

```
{
  "ArnChannelGroupNameChannelNameContainerTypeCreatedAtDashManifestsBaseUrlsDvbPriorityDvbWeightServiceLocationUrlCompactnessDrmSignalingDvbSettingsErrorMetricsProbabilityReportingUrl
```

```
"FontDownload": {  
    "FontFamily": "string",  
    "MimeType": "string",  
    "Url": "string"  
},  
,  
"FilterConfiguration": {  
    "ClipStartTime": number,  
    "End": number,  
    "ManifestFilter": "string",  
    "Start": number,  
    "TimeDelaySeconds": number  
},  
"ManifestName": "string",  
"ManifestWindowSeconds": number,  
"MinBufferTimeSeconds": number,  
"MinUpdatePeriodSeconds": number,  
"PeriodTriggers": [ "string" ],  
"Profiles": [ "string" ],  
"ProgramInformation": {  
    "Copyright": "string",  
    "LanguageCode": "string",  
    "MoreInformationUrl": "string",  
    "Source": "string",  
    "Title": "string"  
},  
"ScteDash": {  
    "AdMarkerDash": "string"  
},  
"SegmentTemplateFormat": "string",  
"SubtitleConfiguration": {  
    "TtmlConfiguration": {  
        "TtmlProfile": "string"  
    }  
},  
"SuggestedPresentationDelaySeconds": number,  
"Url": "string",  
"UtcTiming": {  
    "TimingMode": "string",  
    "TimingSource": "string"  
}  
}  
],  
"Description": "string",
```

```
"ETag": "string",
"ForceEndpointErrorConfigurationEndpointErrorConditionsHlsManifestsChildManifestNameFilterConfigurationClipStartTimeEndManifestFilterStartTimeDelaySecondsManifestNameManifestWindowSecondsProgramDateTimeIntervalSecondsScteHlsAdMarkerHlsStartTagPreciseTimeOffsetUrlUrlEncodeChildManifestLowLatencyHlsManifestsChildManifestNameFilterConfigurationClipStartTimeEndManifestFilterStartTimeDelaySecondsManifestNameManifestWindowSecondsProgramDateTimeIntervalSecondsScteHlsAdMarkerHls
```

```
"StartTag": {  
    "Precise": boolean,  
    "TimeOffset": number  
},  
"Url": "string",  
"UrlEncodeChildManifest": boolean  
}  
],  
"ModifiedAt": number,  
"MssManifests": [  
    {  
        "FilterConfiguration": {  
            "ClipStartTime": number,  
            "End": number,  
            "ManifestFilter": "string",  
            "Start": number,  
            "TimeDelaySeconds": number  
        },  
        "ManifestLayout": "string",  
        "ManifestName": "string",  
        "ManifestWindowSeconds": number,  
        "Url": "string"  
    }  
],  
"OriginEndpointName": "string",  
"Segment": {  
    "Encryption": {  
        "CmafExcludeSegmentDrmMetadata": boolean,  
        "ConstantInitializationVector": "string",  
        "EncryptionMethod": {  
            "CmafEncryptionMethod": "string",  
            "IsmEncryptionMethod": "string",  
            "TsEncryptionMethod": "string"  
        },  
        "KeyRotationIntervalSeconds": number,  
        "SpekeKeyProvider": {  
            "DrmSystems": [ "string" ],  
            "EncryptionContractConfiguration": {  
                "PresetSpeke20Audio": "string",  
                "PresetSpeke20Video": "string"  
            },  
            "ResourceId": "string",  
            "RoleArn": "string",  
            "Url": "string"  
        }  
    }  
}
```

```
        },
      ],
      "IncludeIframeOnlyStreams": boolean,
      "ScteScteFilterstring" ]
      },
      "SegmentDurationSeconds": number,
      "SegmentName": "string",
      "TsIncludeDvbSubtitles": boolean,
      "TsUseAudioRenditionGroup": boolean
    },
    "StartoverWindowSeconds": number,
    "Tagsstring : "string"
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

[ContainerType](#)

The type of container attached to this origin endpoint.

Type: String

Valid Values: TS | CMAF | ISM

[CreatedAt](#)

The date and time the origin endpoint was created.

Type: Timestamp

[DashManifests](#)

A DASH manifest configuration.

Type: Array of [GetDashManifestConfiguration](#) objects

[Description](#)

The description for your origin endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

[ETag](#)

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

[ForceEndpointErrorConfiguration](#)

The failover settings for the endpoint.

Type: [ForceEndpointErrorConfiguration](#) object

HlsManifests

An HTTP live streaming (HLS) manifest configuration.

Type: Array of [GetHlsManifestConfiguration](#) objects

LowLatencyHlsManifests

A low-latency HLS manifest configuration.

Type: Array of [GetLowLatencyHlsManifestConfiguration](#) objects

ModifiedAt

The date and time the origin endpoint was modified.

Type: Timestamp

MssManifests

The Microsoft Smooth Streaming (MSS) manifest configurations that were created for this origin endpoint.

Type: Array of [GetMssManifestConfiguration](#) objects

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Segment

The segment configuration, including the segment name, duration, and other configuration values.

Type: [Segment](#) object

StartoverWindowSeconds

The size of the window (in seconds) to create a window of the live stream that's available for on-demand viewing. Viewers can start-over or catch-up on content that falls within the window.

Type: Integer

Tags

The comma-separated list of tag key:value pairs assigned to the origin endpoint.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteChannel

Delete a channel to stop AWS Elemental MediaPackage from receiving further content. You must delete the channel's origin endpoints before you can delete the channel.

Request Syntax

```
DELETE /channelGroup/ChannelGroupName/channel/ChannelName/ HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteChannelGroup

Delete a channel group. You must delete the channel group's channels and origin endpoints before you can delete the channel group. If you delete a channel group, you'll lose access to the egress domain and will have to create a new channel group to replace it.

Request Syntax

```
DELETE /channelGroup/ChannelGroupName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteChannelPolicy

Delete a channel policy.

Request Syntax

```
DELETE /channelGroup/ChannelGroupName/channel/ChannelName/policy HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOriginEndpoint

Origin endpoints can serve content until they're deleted. Delete the endpoint if it should no longer respond to playback requests. You must delete all endpoints from a channel before you can delete the channel.

Request Syntax

```
DELETE /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteOriginEndpointPolicy

Delete an origin endpoint policy.

Request Syntax

```
DELETE /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName/policy HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetChannel

Retrieves the specified channel that's configured in AWS Elemental MediaPackage.

Request Syntax

```
GET /channelGroup/ChannelGroupName/channel/ChannelName/ HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{  
  "Arn": "string",  
  "ChannelGroupName": "string",  
  "ChannelName": "string",  
  "CreatedAt": number,  
  "Description": "string",  
  "ETag": "string",  
  "IngestEndpoints": [  
    {  
      "Id": "string",  
      "Url": "string"  
    }  
  ],  
  "InputSwitchConfiguration": {  
    "MQCSInputSwitching": boolean,  
    "PreferredInput": number  
  },  
  "InputType": "string",  
  "ModifiedAt": number,  
  "OutputHeaderConfiguration": {  
    "PublishMQCS": boolean  
  },  
  "ResetAt": number,  
  "Tags": {  
    "string" : "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Arn](#)

The Amazon Resource Name (ARN) associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

CreatedAt

The date and time the channel was created.

Type: Timestamp

Description

The description for your channel.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

ETag

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

IngestEndpoints

The list of ingest endpoints.

Type: Array of [IngestEndpoint](#) objects

[InputSwitchConfiguration](#)

The configuration for input switching based on the media quality confidence score (MQCS) as provided from AWS Elemental MediaLive. This setting is valid only when InputType is CMAF.

Type: [InputSwitchConfiguration](#) object

[InputType](#)

The input type will be an immutable field which will be used to define whether the channel will allow CMAF ingest or HLS ingest. If unprovided, it will default to HLS to preserve current behavior.

The allowed values are:

- HLS - The HLS streaming specification (which defines M3U8 manifests and TS segments).
- CMAF - The DASH-IF CMAF Ingest specification (which defines CMAF segments with optional DASH manifests).

Type: String

Valid Values: HLS | CMAF

[ModifiedAt](#)

The date and time the channel was modified.

Type: Timestamp

[OutputHeaderConfiguration](#)

The settings for what common media server data (CMSD) headers AWS Elemental MediaPackage includes in responses to the CDN. This setting is valid only when InputType is CMAF.

Type: [OutputHeaderConfiguration](#) object

[ResetAt](#)

The time that the channel was last reset.

Type: Timestamp

[Tags](#)

The comma-separated list of tag key:value pairs assigned to the channel.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetChannelGroup

Retrieves the specified channel group that's configured in AWS Elemental MediaPackage.

Request Syntax

```
GET /channelGroup/ChannelGroupName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Arn": "string",
  "ChannelGroupName": "string",
  "CreatedAt": number,
  "Description": "string",
  "EgressDomain": "string",
  "ETag": "string",
  "ModifiedAt": number,
```

```
"tags": {  
    "string" : "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

CreatedAt

The date and time the channel group was created.

Type: Timestamp

Description

The description for your channel group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

EgressDomain

The output domain where the source stream should be sent. Integrate the domain with a downstream CDN (such as Amazon CloudFront) or playback device.

Type: String

ETag

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

ModifiedAt

The date and time the channel group was modified.

Type: Timestamp

tags

The comma-separated list of tag key:value pairs assigned to the channel group.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetChannelPolicy

Retrieves the specified channel policy that's configured in AWS Elemental MediaPackage. With policies, you can specify who has access to AWS resources and what actions they can perform on those resources.

Request Syntax

```
GET /channelGroup/ChannelGroupName/channel/ChannelName/policy HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ChannelGroupName": "string",
  "ChannelName": "string",
  "Policy": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[**ChannelGroupName**](#)

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

[**ChannelName**](#)

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

[**Policy**](#)

The policy assigned to the channel.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 6144.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetHarvestJob

Retrieves the details of a specific harvest job.

Request Syntax

```
GET /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName/harvestJob/HarvestJobName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name of the channel group containing the channel associated with the harvest job.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name of the channel associated with the harvest job.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

HarvestJobName

The name of the harvest job to retrieve.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[OriginEndpointName](#)

The name of the origin endpoint associated with the harvest job.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ChannelGroupName": "string",
  "ChannelName": "string",
  "CreatedAtDescription": "string",
  "Destination": {
    "S3Destination": {
      "BucketName": "string",
      "DestinationPath": "string"
    }
  },
  "ErrorMessage": "string",
  "ETag": "string",
  "HarvestedManifests": {
    "DashManifests": [
      {
        "ManifestName": "string"
      }
    ],
    "HlsManifests": [
      {
        "ManifestName": "string"
      }
    ]
  }
}
```

```
        ],
        "LowLatencyHlsManifests": [
            {
                "ManifestNameHarvestJobName": "string",
    "ModifiedAt": number,
    "OriginEndpointName": "string",
    "ScheduleConfiguration": {
        "EndTime": number,
        "StartTime": number
    },
    "Status": "string",
    "Tags": {
        "string" : "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) of the harvest job.

Type: String

ChannelGroupName

The name of the channel group containing the channel associated with the harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ChannelName

The name of the channel associated with the harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

CreatedAt

The date and time when the harvest job was created.

Type: Timestamp

Description

The description of the harvest job, if provided.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Destination

The S3 destination where the harvested content is being placed.

Type: [Destination](#) object

ErrorMessage

An error message if the harvest job encountered any issues.

Type: String

ETag

The current version of the harvest job. Used for concurrency control.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

HarvestedManifests

A list of manifests that are being or have been harvested.

Type: [HarvestedManifests](#) object

[HarvestJobName](#)

The name of the harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

[ModifiedAt](#)

The date and time when the harvest job was last modified.

Type: Timestamp

[OriginEndpointName](#)

The name of the origin endpoint associated with the harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

[ScheduleConfiguration](#)

The configuration for when the harvest job is scheduled to run, including start and end times.

Type: [HarvesterScheduleConfiguration](#) object

[Status](#)

The current status of the harvest job (e.g., QUEUED, IN_PROGRESS, CANCELLED, COMPLETED, FAILED).

Type: String

Valid Values: QUEUED | IN_PROGRESS | CANCELLED | COMPLETED | FAILED

[Tags](#)

A collection of tags associated with the harvest job.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOriginEndpoint

Retrieves the specified origin endpoint that's configured in AWS Elemental MediaPackage to obtain its playback URL and to view the packaging settings that it's currently using.

Request Syntax

```
GET /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[ChannelGroupName](#)

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[ChannelName](#)

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[OriginEndpointName](#)

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "ArnChannelGroupNameChannelNameContainerTypeCreatedAtDashManifestsBaseUrlsDvbPriorityDvbWeightServiceLocationUrlCompactnessDrmSignalingDvbSettingsErrorMetricsProbabilityReportingUrlFontDownloadFontFamilyMimeTypeUrl
```

```
"FilterConfiguration": {  
    "ClipStartTime": number,  
    "End": number,  
    "ManifestFilter": "string",  
    "Start": number,  
    "TimeDelaySeconds": number  
},  
"ManifestName": "string",  
"ManifestWindowSeconds": number,  
"MinBufferTimeSeconds": number,  
"MinUpdatePeriodSeconds": number,  

```

```
"ChildManifestName": "string",
"FilterConfiguration": {
    "ClipStartTime": number,
    "End": number,
    "ManifestFilter": "string",
    "Start": number,
    "TimeDelaySeconds": number
},
"ManifestName": "string",
"ManifestWindowSeconds": number,
"ProgramDateTimeIntervalSeconds": number,
"ScteHls": {
    "AdMarkerHls": "string"
},
"StartTag": {
    "Precise": boolean,
    "TimeOffset": number
},
"Url": "string",
"UrlEncodeChildManifest": boolean
},
],
"LowLatencyHlsManifests": [
{
    "ChildManifestName": "string",
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "ProgramDateTimeIntervalSeconds": number,
    "ScteHls": {
        "AdMarkerHls": "string"
    },
    "StartTag": {
        "Precise": boolean,
        "TimeOffset": number
    },
    "Url": "string",
    "UrlEncodeChildManifest": boolean
}
]
```

```
    },
],
"ModifiedAtnumber,
"MssManifestsFilterConfigurationClipStartTimenumber,
      "Endnumber,
      "ManifestFilterStartnumber,
      "TimeDelaySecondsnumber
    },
    "ManifestLayoutManifestNameManifestWindowSecondsnumber,
    "UrlOriginEndpointNameResetAtnumber,
"SegmentEncryptionCmafExcludeSegmentDrmMetadataboolean,
    "ConstantInitializationVectorEncryptionMethodCmafEncryptionMethodIsmEncryptionMethodTsEncryptionMethodKeyRotationIntervalSecondsnumber,
  "SpekeKeyProviderDrmSystemsEncryptionContractConfigurationPresetSpeke20AudioPresetSpeke20VideoResourceIdRoleArnUrlIncludeIframeOnlyStreamsboolean,
"ScteScteFilter
```

```
        },
        "SegmentDurationSeconds": number,
        "SegmentName": "string",
        "TsIncludeDvbSubtitles": boolean,
        "TsUseAudioRenditionGroup": boolean
    },
    "StartoverWindowSeconds": number,
    "Tags": {
        "string": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Arn](#)

The Amazon Resource Name (ARN) associated with the resource.

Type: String

[ChannelGroupName](#)

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

[ChannelName](#)

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

[ContainerType](#)

The type of container attached to this origin endpoint.

Type: String

Valid Values: TS | CMAF | ISM

[CreatedAt](#)

The date and time the origin endpoint was created.

Type: Timestamp

[DashManifests](#)

A DASH manifest configuration.

Type: Array of [GetDashManifestConfiguration](#) objects

[Description](#)

The description for your origin endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

[ETag](#)

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

[ForceEndpointErrorConfiguration](#)

The failover settings for the endpoint.

Type: [ForceEndpointErrorConfiguration](#) object

HlsManifests

An HTTP live streaming (HLS) manifest configuration.

Type: Array of [GetHlsManifestConfiguration](#) objects

LowLatencyHlsManifests

A low-latency HLS manifest configuration.

Type: Array of [GetLowLatencyHlsManifestConfiguration](#) objects

ModifiedAt

The date and time the origin endpoint was modified.

Type: Timestamp

MssManifests

The Microsoft Smooth Streaming (MSS) manifest configurations associated with this origin endpoint.

Type: Array of [GetMssManifestConfiguration](#) objects

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ResetAt

The time that the origin endpoint was last reset.

Type: Timestamp

Segment

The segment configuration, including the segment name, duration, and other configuration values.

Type: [Segment object](#)

[StartoverWindowSeconds](#)

The size of the window (in seconds) to create a window of the live stream that's available for on-demand viewing. Viewers can start-over or catch-up on content that falls within the window.

Type: Integer

[Tags](#)

The comma-separated list of tag key:value pairs assigned to the origin endpoint.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetOriginEndpointPolicy

Retrieves the specified origin endpoint policy that's configured in AWS Elemental MediaPackage.

Request Syntax

```
GET /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName/policy HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "CdnAuthConfigurationCdnIdentifierSecretArnsSecretsRoleArnChannelGroupNameChannelNameOriginEndpointNamePolicy
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CdnAuthConfiguration

The settings for using authorization headers between the MediaPackage endpoint and your CDN.

For information about CDN authorization, see [CDN authorization in AWS Elemental MediaPackage](#) in the MediaPackage user guide.

Type: [CdnAuthConfiguration](#) object

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Policy

The policy assigned to the origin endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 6144.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is

making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListChannelGroups

Retrieves all channel groups that are configured in AWS Elemental MediaPackage.

Request Syntax

```
GET /channelGroup?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results to return in the response.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The pagination token from the GET list request. Use the token to fetch the next page of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Items": [
    {
      "Arn": "string",
      "ChannelGroupName": "string",
      "CreatedAt": number,
      "Description": "string",
      "ModifiedAt": number
    }
  ]
}
```

```
],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The objects being returned.

Type: Array of [ChannelGroupListConfiguration](#) objects

NextToken

The pagination token from the GET list request. Use the token to fetch the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListChannels

Retrieves all channels in a specific channel group that are configured in AWS Elemental MediaPackage.

Request Syntax

```
GET /channelGroup/ChannelGroupName/channel?maxResults=MaxResults&nextToken=NextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

MaxResults

The maximum number of results to return in the response.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The pagination token from the GET list request. Use the token to fetch the next page of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{  
  "Items": [  
    {  
      "Arn": "string",  
      "ChannelGroupName": "string",  
      "ChannelName": "string",  
      "CreatedAt": number,  
      "Description": "string",  
      "InputType": "string",  
      "ModifiedAt": number  
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The objects being returned.

Type: Array of [ChannelListConfiguration](#) objects

NextToken

The pagination token from the GET list request.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is

making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListHarvestJobs

Retrieves a list of harvest jobs that match the specified criteria.

Request Syntax

```
GET /channelGroup/ChannelGroupName/harvestJob?
```

```
channelName=ChannelName&includeStatus=Status&maxResults=MaxResults&nextToken=NextToken&originEn
```

```
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name of the channel group to filter the harvest jobs by. If specified, only harvest jobs associated with channels in this group will be returned.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name of the channel to filter the harvest jobs by. If specified, only harvest jobs associated with this channel will be returned.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

MaxResults

The maximum number of harvest jobs to return in a single request. If not specified, a default value will be used.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

A token used for pagination. Provide this value in subsequent requests to retrieve the next set of results.

OriginEndpointName

The name of the origin endpoint to filter the harvest jobs by. If specified, only harvest jobs associated with this origin endpoint will be returned.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Status

The status to filter the harvest jobs by. If specified, only harvest jobs with this status will be returned.

Valid Values: QUEUED | IN_PROGRESS | CANCELLED | COMPLETED | FAILED

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ItemsArnChannelGroupNameChannelNameCreatedAtDescriptionDestinationS3DestinationBucketNameDestinationPath
```

```
        }
    },
    "ErrorMessage": "string",
    "ETag": "string",
    "HarvestedManifests": [
        "DashManifests": [
            {
                "ManifestName": "string"
            }
        ],
        "HlsManifests": [
            {
                "ManifestName": "string"
            }
        ],
        "LowLatencyHlsManifests": [
            {
                "ManifestName": "string"
            }
        ]
    ],
    "HarvestJobName": "string",
    "ModifiedAt": number,
    "OriginEndpointName": "string",
    "ScheduleConfiguration": {
        "EndTime": number,
        "StartTime": number
    },
    "Status": "string"
},
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

An array of harvest job objects that match the specified criteria.

Type: Array of [HarvestJob](#) objects

NextToken

A token used for pagination. Include this value in subsequent requests to retrieve the next set of results. If null, there are no more results to retrieve.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListOriginEndpoints

Retrieves all origin endpoints in a specific channel that are configured in AWS Elemental MediaPackage.

Request Syntax

```
GET /channelGroup/ChannelGroupName/channel/ChannelName/originEndpoint?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[ChannelGroupName](#)

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[ChannelName](#)

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

[MaxResults](#)

The maximum number of results to return in the response.

Valid Range: Minimum value of 1. Maximum value of 100.

NextToken

The pagination token from the GET list request. Use the token to fetch the next page of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ItemsArnChannelGroupNameChannelNameContainerTypeCreatedAtDashManifestsManifestNameUrlDescriptionForceEndpointErrorConfigurationEndpointErrorConditionsHlsManifestsChildManifestNameManifestNameUrlLowLatencyHlsManifestsChildManifestNameManifestName
```

```
        "Url": "string"
    },
],
"ModifiedAt": number,
"MssManifests": [
    {
        "ManifestName": "string",
        "Url": "string"
    }
],
"OriginEndpointName": "string"
},
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Items

The objects being returned.

Type: Array of [OriginEndpointListConfiguration](#) objects

NextToken

The pagination token from the GET list request. Use the token to fetch the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is

making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags assigned to a resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The ARN of the CloudWatch resource that you want to view tags for.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags" : {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[tags](#)

Contains a map of the key-value pairs for the resource tag or tags assigned to the resource.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutChannelPolicy

Attaches an IAM policy to the specified channel. With policies, you can specify who has access to AWS resources and what actions they can perform on those resources. You can attach only one policy with each request.

Request Syntax

```
PUT /channelGroup/ChannelGroupName/channel/ChannelName/policy HTTP/1.1
Content-type: application/json

{
    "Policy
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

Policy

The policy to attach to the specified channel.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 6144.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutOriginEndpointPolicy

Attaches an IAM policy to the specified origin endpoint. You can attach only one policy with each request.

Request Syntax

```
POST /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName/policy HTTP/1.1  
Content-type: application/json  
  
{  
    "CdnAuthConfiguration        "CdnIdentifierSecretArnsstring" ],  
        "SecretsRoleArnstring"  
    },  
    "Policystring"  
}
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

CdnAuthConfiguration

The settings for using authorization headers between the MediaPackage endpoint and your CDN.

For information about CDN authorization, see [CDN authorization in AWS Elemental MediaPackage](#) in the MediaPackage user guide.

Type: [CdnAuthConfiguration](#) object

Required: No

Policy

The policy to attach to the specified origin endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 6144.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResetChannelState

Resetting the channel can help to clear errors from misconfigurations in the encoder. A reset refreshes the ingest stream and removes previous content.

Be sure to stop the encoder before you reset the channel, and wait at least 30 seconds before you restart the encoder.

Request Syntax

```
POST /channelGroup/ChannelGroupName/channel/ChannelName/reset HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name of the channel group that contains the channel that you are resetting.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name of the channel that you are resetting.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ArnChannelGroupNameChannelNameResetAt
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Arn](#)

The Amazon Resource Name (ARN) associated with the channel that you just reset.

Type: String

[ChannelGroupName](#)

The name of the channel group that contains the channel that you just reset.

Type: String

[ChannelName](#)

The name of the channel that you just reset.

Type: String

[ResetAt](#)

The time that the channel was last reset.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ResetOriginEndpointState

Resetting the origin endpoint can help to resolve unexpected behavior and other content packaging issues. It also helps to preserve special events when you don't want the previous content to be available for viewing. A reset clears out all previous content from the origin endpoint.

MediaPackage might return old content from this endpoint in the first 30 seconds after the endpoint reset. For best results, when possible, wait 30 seconds from endpoint reset to send playback requests to this endpoint.

Request Syntax

```
POST /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName/reset HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name of the channel group that contains the channel with the origin endpoint that you are resetting.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name of the channel with the origin endpoint that you are resetting.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

OriginEndpointName

The name of the origin endpoint that you are resetting.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ChannelGroupName": "string",
  "ChannelName": "string",
  "OriginEndpointName": "string",
  "ResetAt": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) associated with the endpoint that you just reset.

Type: String

ChannelGroupName

The name of the channel group that contains the channel with the origin endpoint that you just reset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ChannelName

The name of the channel with the origin endpoint that you just reset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

OriginEndpointName

The name of the origin endpoint that you just reset.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ResetAt

The time that the origin endpoint was last reset.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Assigns one or more tags (key-value pairs) to the specified MediaPackage resource.

Tags can help you organize and categorize your resources. You can also use them to scope user permissions, by granting a user permission to access or change only resources with certain tag values. You can use the TagResource operation with a resource that already has tags. If you specify a new tag key for the resource, this tag is appended to the list of tags associated with the resource. If you specify a tag key that is already associated with the resource, the new tag value that you specify replaces the previous value for that tag.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json

{
  "tags": {
    "string": "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The ARN of the MediaPackage resource that you're adding tags to.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

Contains a map of the key-value pairs for the resource tag or tags assigned to the resource.

Type: String to string map

Required: Yes

Response Syntax

HTTP/1.1 204

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

UntagResource

Removes one or more tags from the specified resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

The ARN of the MediaPackage resource that you're removing tags from.

Required: Yes

TagKeys

The list of tag keys to remove from the resource.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateChannel

Update the specified channel. You can edit if MediaPackage sends ingest or egress access logs to the CloudWatch log group, if content will be encrypted, the description on a channel, and your channel's policy settings. You can't edit the name of the channel or CloudFront distribution details.

Any edits you make that impact the video output may not be reflected for a few minutes.

Request Syntax

```
PUT /channelGroup/ChannelGroupName/channel/ChannelName/ HTTP/1.1
x-amzn-update-if-match: ETag
Content-type: application/json

{
  "DescriptionInputSwitchConfigurationMQCSInputSwitchingPreferredInputOutputHeaderConfigurationPublishMQCS
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ETag

The expected current Entity Tag (ETag) for the resource. If the specified ETag does not match the resource's current entity tag, the update request will be rejected.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

Request Body

The request accepts the following data in JSON format.

Description

Any descriptive information that you want to add to the channel for future identification purposes.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

InputSwitchConfiguration

The configuration for input switching based on the media quality confidence score (MQCS) as provided from AWS Elemental MediaLive. This setting is valid only when InputType is CMAF.

Type: [InputSwitchConfiguration](#) object

Required: No

OutputHeaderConfiguration

The settings for what common media server data (CMSD) headers AWS Elemental MediaPackage includes in responses to the CDN. This setting is valid only when InputType is CMAF.

Type: [OutputHeaderConfiguration object](#)

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "Arn": "string",
    "ChannelGroupName": "string",
    "ChannelName": "string",
    "CreatedAt": number,
    "Description": "string",
    "ETag": "string",
    "IngestEndpoints": [
        {
            "Id": "string",
            "Url": "string"
        }
    ],
    "InputSwitchConfiguration": {
        "MQCSInputSwitching": boolean,
        "PreferredInput": number
    },
    "InputType": "string",
    "ModifiedAt": number,
    "OutputHeaderConfiguration": {
        "PublishMQCS": boolean
    },
    "tags": {
        "string" : "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

CreatedAt

The date and time the channel was created.

Type: Timestamp

Description

The description for your channel.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

ETag

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

IngestEndpoints

The list of ingest endpoints.

Type: Array of [IngestEndpoint](#) objects

InputSwitchConfiguration

The configuration for input switching based on the media quality confidence score (MQCS) as provided from AWS Elemental MediaLive. This setting is valid only when InputType is CMAF.

Type: [InputSwitchConfiguration](#) object

InputType

The input type will be an immutable field which will be used to define whether the channel will allow CMAF ingest or HLS ingest. If unprovided, it will default to HLS to preserve current behavior.

The allowed values are:

- HLS - The HLS streaming specification (which defines M3U8 manifests and TS segments).
- CMAF - The DASH-IF CMAF Ingest specification (which defines CMAF segments with optional DASH manifests).

Type: String

Valid Values: HLS | CMAF

ModifiedAt

The date and time the channel was modified.

Type: Timestamp

OutputHeaderConfiguration

The settings for what common media server data (CMDS) headers AWS Elemental MediaPackage includes in responses to the CDN. This setting is valid only when InputType is CMAF.

Type: [OutputHeaderConfiguration](#) object

[tags](#)

The comma-separated list of tag key:value pairs assigned to the channel.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateChannelGroup

Update the specified channel group. You can edit the description on a channel group for easier identification later from the AWS Elemental MediaPackage console. You can't edit the name of the channel group.

Any edits you make that impact the video output may not be reflected for a few minutes.

Request Syntax

```
PUT /channelGroup/ChannelGroupName HTTP/1.1
x-amzn-update-if-match: ETag
Content-type: application/json

{
    "Description
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ETag

The expected current Entity Tag (ETag) for the resource. If the specified ETag does not match the resource's current entity tag, the update request will be rejected.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

Request Body

The request accepts the following data in JSON format.

Description

Any descriptive information that you want to add to the channel group for future identification purposes.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "Arn": "string",
  "ChannelGroupName": "string",
  "CreatedAt": number,
  "Description": "string",
  "EgressDomain": "string",
  "ETag": "string",
  "ModifiedAt": number,
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

CreatedAt

The date and time the channel group was created.

Type: Timestamp

Description

The description for your channel group.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

EgressDomain

The output domain where the source stream is sent. Integrate the domain with a downstream CDN (such as Amazon CloudFront) or playback device.

Type: String

ETag

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

ModifiedAt

The date and time the channel group was modified.

Type: Timestamp

[tags](#)

The comma-separated list of tag key:value pairs assigned to the channel group.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateOriginEndpoint

Update the specified origin endpoint. Edit the packaging preferences on an endpoint to optimize the viewing experience. You can't edit the name of the endpoint.

Any edits you make that impact the video output may not be reflected for a few minutes.

Request Syntax

```
PUT /channelGroup/ChannelGroupName/channel/ChannelName/  
originEndpoint/OriginEndpointName HTTP/1.1  
x-amzn-update-if-match: ETag  
Content-type: application/json  
  
{  
    "ContainerType": "string",  
    "DashManifests": [  
        {  
            "BaseUrls": [  
                {  
                    "DvbPriority": number,  
                    "DvbWeight": number,  
                    "ServiceLocation": "string",  
                    "Url": "string"  
                }  
            ],  
            "Compactness": "string",  
            "DrmSignaling": "string",  
            "DvbSettings": {  
                "ErrorMetrics": [  
                    {  
                        "Probability": number,  
                        "ReportingUrl": "string"  
                    }  
                ],  
                "FontDownload": {  
                    "FontFamily": "string",  
                    "MimeType": "string",  
                    "Url": "string"  
                }  
            },  
            "FilterConfiguration": {  
                "ClipStartTime": number,
```

```
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "MinBufferTimeSeconds": number,
    "MinUpdatePeriodSeconds": number,
    "PeriodTriggers": [ "string" ],
    "Profiles": [ "string" ],
    "ProgramInformation": {
        "Copyright": "string",
        "LanguageCode": "string",
        "MoreInformationUrl": "string",
        "Source": "string",
        "Title": "string"
    },
    "ScteDash": {
        "AdMarkerDash": "string"
    },
    "SegmentTemplateFormat": "string",
    "SubtitleConfiguration": {
        "TtmlConfiguration": {
            "TtmlProfile": "string"
        }
    },
    "SuggestedPresentationDelaySeconds": number,
    "UtcTiming": {
        "TimingMode": "string",
        "TimingSource": "string"
    }
}
],
"Description": "string",
"ForceEndpointErrorConfiguration": {
    "EndpointErrorConditions": [ "string" ]
},
"HlsManifests": [
{
    "ChildManifestName": "string",
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number,
        "Start": number
    }
}
```

```
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "ProgramDateTimeIntervalSeconds": number,
    "ScteHls": {
        "AdMarkerHls": "string"
    },
    "StartTag": {
        "Precise": boolean,
        "TimeOffset": number
    },
    "UrlEncodeChildManifest": boolean
}
],
"LowLatencyHlsManifests": [
{
    "ChildManifestName": "string",
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "ProgramDateTimeIntervalSeconds": number,
    "ScteHls": {
        "AdMarkerHls": "string"
    },
    "StartTag": {
        "Precise": boolean,
        "TimeOffset": number
    },
    "UrlEncodeChildManifest": boolean
}
],
"MssManifests": [
{
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number
    }
}]
```

```
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestLayout": "string",
    "ManifestName": "string",
    "ManifestWindowSeconds": number
}
],
"Segment": {
    "Encryption": {
        "CmafExcludeSegmentDrmMetadata": boolean,
        "ConstantInitializationVector": "string",
        "EncryptionMethod": {
            "CmafEncryptionMethod": "string",
            "IsmEncryptionMethod": "string",
            "TsEncryptionMethod": "string"
        },
        "KeyRotationIntervalSeconds": number,
        "SpekeKeyProvider": {
            "DrmSystems": [ "string" ],
            "EncryptionContractConfiguration": {
                "PresetSpeke20Audio": "string",
                "PresetSpeke20Video": "string"
            },
            "ResourceId": "string",
            "RoleArn": "string",
            "Url": "string"
        }
    },
    "IncludeIframeOnlyStreams": boolean,
    "Scte": {
        "ScteFilter": [ "string" ]
    },
    "SegmentDurationSeconds": number,
    "SegmentName": "string",
    "TsIncludeDvbSubtitles": boolean,
    "TsUseAudioRenditionGroup": boolean
},
"StartoverWindowSeconds": number
}
```

URI Request Parameters

The request uses the following URI parameters.

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ETag

The expected current Entity Tag (ETag) for the resource. If the specified ETag does not match the resource's current entity tag, the update request will be rejected.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Request Body

The request accepts the following data in JSON format.

[ContainerType](#)

The type of container attached to this origin endpoint. A container type is a file format that encapsulates one or more media streams, such as audio and video, into a single file.

Type: String

Valid Values: TS | CMAF | ISM

Required: Yes

[DashManifests](#)

A DASH manifest configuration.

Type: Array of [CreateDashManifestConfiguration](#) objects

Required: No

[Description](#)

Any descriptive information that you want to add to the origin endpoint for future identification purposes.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

[ForceEndpointErrorConfiguration](#)

The failover settings for the endpoint.

Type: [ForceEndpointErrorConfiguration](#) object

Required: No

HlsManifests

An HTTP live streaming (HLS) manifest configuration.

Type: Array of [CreateHlsManifestConfiguration](#) objects

Required: No

LowLatencyHlsManifests

A low-latency HLS manifest configuration.

Type: Array of [CreateLowLatencyHlsManifestConfiguration](#) objects

Required: No

MssManifests

A list of Microsoft Smooth Streaming (MSS) manifest configurations to update for the origin endpoint. This replaces the existing MSS manifest configurations.

Type: Array of [CreateMssManifestConfiguration](#) objects

Required: No

Segment

The segment configuration, including the segment name, duration, and other configuration values.

Type: [Segment](#) object

Required: No

StartoverWindowSeconds

The size of the window (in seconds) to create a window of the live stream that's available for on-demand viewing. Viewers can start-over or catch-up on content that falls within the window. The maximum startover window is 1,209,600 seconds (14 days).

Type: Integer

Valid Range: Minimum value of 60. Maximum value of 1209600.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "ChannelGroupName": "string",
  "ChannelName": "string",
  "ContainerType": "string",
  "CreatedAt": number,
  "DashManifests": [
    {
      "BaseUrls": [
        {
          "DvbPriority": number,
          "DvbWeight": number,
          "ServiceLocation": "string",
          "Url": "string"
        }
      ],
      "Compactness": "string",
      "DrmSignaling": "string",
      "DvbSettings": {
        "ErrorMetrics": [
          {
            "Probability": number,
            "ReportingUrl": "string"
          }
        ],
        "FontDownload": {
          "FontFamily": "string",
          "MimeType": "string",
          "Url": "string"
        }
      },
      "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
      }
    }
  ]
}
```

```
"ManifestName": "string",
"ManifestWindowSeconds": number,
"MinBufferTimeSeconds": number,
"MinUpdatePeriodSeconds": number,
"PeriodTriggers": [ "string" ],
"Profiles": [ "string" ],
"ProgramInformation": {
    "Copyright": "string",
    "LanguageCode": "string",
    "MoreInformationUrl": "string",
    "Source": "string",
    "Title": "string"
},
"ScteDash": {
    "AdMarkerDash": "string"
},
"SegmentTemplateFormat": "string",
"SubtitleConfiguration": {
    "TtmlConfiguration": {
        "TtmlProfile": "string"
    }
},
"SuggestedPresentationDelaySeconds": number,
"Url": "string",
"UtcTiming": {
    "TimingMode": "string",
    "TimingSource": "string"
}
},
"Description": "string",
"ETag": "string",
"ForceEndpointErrorConfiguration": {
    "EndpointErrorConditions": [ "string" ]
},
"HlsManifests": [
{
    "ChildManifestName": "string",
    "FilterConfiguration": {
        "ClipStartTime": number,
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    }
}
```

```
        },
        "ManifestName": "string",
        "ManifestWindowSeconds": number,
        "ProgramDateTimeIntervalSeconds": number,
        "ScteHls": {
            "AdMarkerHls": "string"
        },
        "StartTag": {
            "Precise": boolean,
            "TimeOffset": number
        },
        "Url": "string",
        "UrlEncodeChildManifest": boolean
    }
],
"LowLatencyHlsManifests": [
    {
        "ChildManifestName": "string",
        "FilterConfiguration": {
            "ClipStartTime": number,
            "End": number,
            "ManifestFilter": "string",
            "Start": number,
            "TimeDelaySeconds": number
        },
        "ManifestName": "string",
        "ManifestWindowSeconds": number,
        "ProgramDateTimeIntervalSeconds": number,
        "ScteHls": {
            "AdMarkerHls": "string"
        },
        "StartTag": {
            "Precise": boolean,
            "TimeOffset": number
        },
        "Url": "string",
        "UrlEncodeChildManifest": boolean
    }
],
"ModifiedAt": number,
"MssManifests": [
    {
        "FilterConfiguration": {
            "ClipStartTime": number,
            "End": number,
            "ManifestFilter": "string",
            "Start": number
        }
    }
]
```

```
        "End": number,
        "ManifestFilter": "string",
        "Start": number,
        "TimeDelaySeconds": number
    },
    "ManifestLayout": "string",
    "ManifestName": "string",
    "ManifestWindowSeconds": number,
    "Url": "string"
},
],
"OriginEndpointName": "string",
"Segment": {
    "Encryption": {
        "CmafExcludeSegmentDrmMetadata": boolean,
        "ConstantInitializationVector": "string",
        "EncryptionMethod": {
            "CmafEncryptionMethod": "string",
            "IsmEncryptionMethod": "string",
            "TsEncryptionMethod": "string"
        },
        "KeyRotationIntervalSeconds": number,
        "SpekeKeyProvider": {
            "DrmSystems": [ "string" ],
            "EncryptionContractConfiguration": {
                "PresetSpeke20Audio": "string",
                "PresetSpeke20Video": "string"
            },
            "ResourceId": "string",
            "RoleArn": "string",
            "Url": "string"
        }
    },
    "IncludeIframeOnlyStreams": boolean,
    "Scte": {
        "ScteFilter": [ "string" ]
    },
    "SegmentDurationSeconds": number,
    "SegmentName": "string",
    "TsIncludeDvbSubtitles": boolean,
    "TsUseAudioRenditionGroup": boolean
},
"StartoverWindowSeconds": number,
"tags": {
```

```
    "string" : "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN associated with the resource.

Type: String

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

ContainerType

The type of container attached to this origin endpoint.

Type: String

Valid Values: TS | CMAF | ISM

CreatedAt

The date and time the origin endpoint was created.

Type: Timestamp

DashManifests

A DASH manifest configuration.

Type: Array of [GetDashManifestConfiguration](#) objects

Description

The description of the origin endpoint.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

ETag

The current Entity Tag (ETag) associated with this resource. The entity tag can be used to safely make concurrent updates to the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [\S]+

ForceEndpointErrorConfiguration

The failover settings for the endpoint.

Type: [ForceEndpointErrorConfiguration](#) object

HlsManifests

An HTTP live streaming (HLS) manifest configuration.

Type: Array of [GetHlsManifestConfiguration](#) objects

LowLatencyHlsManifests

A low-latency HLS manifest configuration.

Type: Array of [GetLowLatencyHlsManifestConfiguration](#) objects

ModifiedAt

The date and time the origin endpoint was modified.

Type: Timestamp

MssManifests

The updated Microsoft Smooth Streaming (MSS) manifest configurations for this origin endpoint.

Type: Array of [GetMssManifestConfiguration](#) objects

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Segment

The segment configuration, including the segment name, duration, and other configuration values.

Type: [Segment](#) object

StartoverWindowSeconds

The size of the window (in seconds) to create a window of the live stream that's available for on-demand viewing. Viewers can start-over or catch-up on content that falls within the window.

Type: Integer

tags

The comma-separated list of tag key:value pairs assigned to the origin endpoint.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied because either you don't have permissions to perform the requested operation or MediaPackage is getting throttling errors with CDN authorization. The user or role that is making the request must have at least one IAM permissions policy attached that grants the required permissions. For more information, see Access Management in the IAM User Guide. Or, if you're using CDN authorization, you will receive this exception if MediaPackage receives a throttling error from Secrets Manager.

HTTP Status Code: 403

ConflictException

Updating or deleting this resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerException

Indicates that an error from the service occurred while trying to process a request.

HTTP Status Code: 500

ResourceNotFoundException

The specified resource doesn't exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The request throughput limit was exceeded.

HTTP Status Code: 429

ValidationException

The input failed to meet the constraints specified by the AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Elemental MediaPackage v2 API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [CdnAuthConfiguration](#)
- [ChannelGroupListConfiguration](#)
- [ChannelListConfiguration](#)
- [CreateDashManifestConfiguration](#)
- [CreateHlsManifestConfiguration](#)
- [CreateLowLatencyHlsManifestConfiguration](#)
- [CreateMssManifestConfiguration](#)
- [DashBaseUrl](#)
- [DashDvbFontDownload](#)
- [DashDvbMetricsReporting](#)
- [DashDvbSettings](#)
- [DashProgramInformation](#)
- [DashSubtitleConfiguration](#)
- [DashTtmlConfiguration](#)
- [DashUtcTiming](#)
- [Destination](#)
- [Encryption](#)
- [EncryptionContractConfiguration](#)
- [EncryptionMethod](#)
- [FilterConfiguration](#)

- [ForceEndpointErrorConfiguration](#)
- [GetDashManifestConfiguration](#)
- [GetHlsManifestConfiguration](#)
- [GetLowLatencyHlsManifestConfiguration](#)
- [GetMssManifestConfiguration](#)
- [HarvestedDashManifest](#)
- [HarvestedHlsManifest](#)
- [HarvestedLowLatencyHlsManifest](#)
- [HarvestedManifests](#)
- [HarvesterScheduleConfiguration](#)
- [HarvestJob](#)
- [IngestEndpoint](#)
- [InputSwitchConfiguration](#)
- [ListDashManifestConfiguration](#)
- [ListHlsManifestConfiguration](#)
- [ListLowLatencyHlsManifestConfiguration](#)
- [ListMssManifestConfiguration](#)
- [OriginEndpointListConfiguration](#)
- [OutputHeaderConfiguration](#)
- [S3DestinationConfig](#)
- [Scte](#)
- [ScteDash](#)
- [ScteHls](#)
- [Segment](#)
- [SpekeKeyProvider](#)
- [StartTag](#)

CdnAuthConfiguration

The settings to enable CDN authorization headers in MediaPackage.

Contents

CdnIdentifierSecretArns

The ARN for the secret in Secrets Manager that your CDN uses for authorization to access the endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

SecretsRoleArn

The ARN for the IAM role that gives MediaPackage read access to Secrets Manager and AWS KMS for CDN authorization.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelGroupListConfiguration

The configuration of the channel group.

Contents

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

Required: Yes

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

Required: Yes

CreatedAt

The date and time the channel group was created.

Type: Timestamp

Required: Yes

ModifiedAt

The date and time the channel group was modified.

Type: Timestamp

Required: Yes

Description

Any descriptive information that you want to add to the channel group for future identification purposes.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ChannelListConfiguration

The configuration of the channel.

Contents

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

Required: Yes

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

Required: Yes

CreatedAt

The date and time the channel was created.

Type: Timestamp

Required: Yes

ModifiedAt

The date and time the channel was modified.

Type: Timestamp

Required: Yes

Description

Any descriptive information that you want to add to the channel for future identification purposes.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

InputType

The input type will be an immutable field which will be used to define whether the channel will allow CMAF ingest or HLS ingest. If unprovided, it will default to HLS to preserve current behavior.

The allowed values are:

- HLS - The HLS streaming specification (which defines M3U8 manifests and TS segments).
- CMAF - The DASH-IF CMAF Ingest specification (which defines CMAF segments with optional DASH manifests).

Type: String

Valid Values: HLS | CMAF

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateDashManifestConfiguration

Create a DASH manifest configuration.

Contents

ManifestName

A short string that's appended to the endpoint URL. The child manifest name creates a unique path to this endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9-]+

Required: Yes

BaseUrls

The base URLs to use for retrieving segments.

Type: Array of [DashBaseUrl](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Compactness

The layout of the DASH manifest that MediaPackage produces. STANDARD indicates a default manifest, which is compacted. NONE indicates a full manifest.

For information about compactness, see [DASH manifest compactness](#) in the *AWS Elemental MediaPackage v2 User Guide*.

Type: String

Valid Values: STANDARD | NONE

Required: No

DrmSignaling

Determines how the DASH manifest signals the DRM content.

Type: String

Valid Values: INDIVIDUAL | REFERENCED

Required: No

DvbSettings

For endpoints that use the DVB-DASH profile only. The font download and error reporting information that you want MediaPackage to pass through to the manifest.

Type: [DashDvbSettings](#) object

Required: No

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestWindowSeconds

The total duration (in seconds) of the manifest's content.

Type: Integer

Valid Range: Minimum value of 30.

Required: No

MinBufferTimeSeconds

Minimum amount of content (in seconds) that a player must keep available in the buffer.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 3600.

Required: No

MinUpdatePeriodSeconds

Minimum amount of time (in seconds) that the player should wait before requesting updates to the manifest.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 3600.

Required: No

PeriodTriggers

A list of triggers that controls when AWS Elemental MediaPackage separates the MPEG-DASH manifest into multiple periods. Type ADS to indicate that AWS Elemental MediaPackage must create periods in the output manifest that correspond to SCTE-35 ad markers in the input source. Leave this value empty to indicate that the manifest is contained all in one period. For more information about periods in the DASH manifest, see [Multi-period DASH in AWS Elemental MediaPackage](#).

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Valid Values: AVAILS | DRM_KEY_ROTATION | SOURCE_CHANGES | SOURCE_DISRUPTIONS | NONE

Required: No

Profiles

The profile that the output is compliant with.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Valid Values: DVB_DASH

Required: No

ProgramInformation

Details about the content that you want MediaPackage to pass through in the manifest to the playback device.

Type: [DashProgramInformation](#) object

Required: No

ScteDash

The SCTE configuration.

Type: [ScteDash](#) object

Required: No

SegmentTemplateFormat

Determines the type of variable used in the media URL of the SegmentTemplate tag in the manifest. Also specifies if segment timeline information is included in SegmentTimeline or SegmentTemplate.

Value description:

- NUMBER_WITH_TIMELINE - The \$Number\$ variable is used in the media URL. The value of this variable is the sequential number of the segment. A full SegmentTimeline object is presented in each SegmentTemplate.

Type: String

Valid Values: NUMBER_WITH_TIMELINE

Required: No

SubtitleConfiguration

The configuration for DASH subtitles.

Type: [DashSubtitleConfiguration](#) object

Required: No

SuggestedPresentationDelaySeconds

The amount of time (in seconds) that the player should be from the end of the manifest.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 3600.

Required: No

UtcTiming

Determines the type of UTC timing included in the DASH Media Presentation Description (MPD).

Type: [DashUtcTiming](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateHlsManifestConfiguration

Create an HTTP live streaming (HLS) manifest configuration.

Contents

ManifestName

A short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index. MediaPackage automatically inserts the format extension, such as .m3u8. You can't use the same manifest name if you use HLS manifest and low-latency HLS manifest. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9-]+

Required: Yes

ChildManifestName

A short string that's appended to the endpoint URL. The child manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index, with an added suffix to distinguish it from the manifest name. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9-]+

Required: No

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestWindowSeconds

The total duration (in seconds) of the manifest's content.

Type: Integer

Valid Range: Minimum value of 30.

Required: No

ProgramDateTimeIntervalSeconds

Inserts EXT-X-PROGRAM-DATE-TIME tags in the output manifest at the interval that you specify. If you don't enter an interval, EXT-X-PROGRAM-DATE-TIME tags aren't included in the manifest. The tags sync the stream to the wall clock so that viewers can seek to a specific time in the playback timeline on the player.

Irrespective of this parameter, if any ID3Timed metadata is in the HLS input, it is passed through to the HLS output.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1209600.

Required: No

ScteHls

The SCTE configuration.

Type: [ScteHls](#) object

Required: No

StartTag

To insert an EXT-X-START tag in your HLS playlist, specify a StartTag configuration object with a valid TimeOffset. When you do, you can also optionally specify whether to include a PRECISE value in the EXT-X-START tag.

Type: [StartTag](#) object

Required: No

UrlEncodeChildManifest

When enabled, MediaPackage URL-encodes the query string for API requests for HLS child manifests to comply with AWS Signature Version 4 (SigV4) signature signing protocol. For more information, see [AWS Signature Version 4 for API requests](#) in *AWS Identity and Access Management User Guide*.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateLowLatencyHlsManifestConfiguration

Create a low-latency HTTP live streaming (HLS) manifest configuration.

Contents

ManifestName

A short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index. MediaPackage automatically inserts the format extension, such as .m3u8. You can't use the same manifest name if you use HLS manifest and low-latency HLS manifest. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9-]+

Required: Yes

ChildManifestName

A short string that's appended to the endpoint URL. The child manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index, with an added suffix to distinguish it from the manifest name. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9-]+

Required: No

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestWindowSeconds

The total duration (in seconds) of the manifest's content.

Type: Integer

Valid Range: Minimum value of 30.

Required: No

ProgramDateTimeIntervalSeconds

Inserts EXT-X-PROGRAM-DATE-TIME tags in the output manifest at the interval that you specify. If you don't enter an interval, EXT-X-PROGRAM-DATE-TIME tags aren't included in the manifest. The tags sync the stream to the wall clock so that viewers can seek to a specific time in the playback timeline on the player.

Irrespective of this parameter, if any ID3Timed metadata is in the HLS input, it is passed through to the HLS output.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1209600.

Required: No

ScteHls

The SCTE configuration.

Type: [ScteHls](#) object

Required: No

StartTag

To insert an EXT-X-START tag in your HLS playlist, specify a StartTag configuration object with a valid TimeOffset. When you do, you can also optionally specify whether to include a PRECISE value in the EXT-X-START tag.

Type: [StartTag](#) object

Required: No

UrlEncodeChildManifest

When enabled, MediaPackage URL-encodes the query string for API requests for LL-HLS child manifests to comply with AWS Signature Version 4 (SigV4) signature signing protocol. For more information, see [AWS Signature Version 4 for API requests](#) in *AWS Identity and Access Management User Guide*.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateMssManifestConfiguration

Configuration parameters for creating a Microsoft Smooth Streaming (MSS) manifest. MSS is a streaming media format developed by Microsoft that delivers adaptive bitrate streaming content to compatible players and devices.

Contents

ManifestName

A short string that's appended to the endpoint URL to create a unique path to this MSS manifest. The manifest name must be unique within the origin endpoint and can contain letters, numbers, hyphens, and underscores.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9-]+

Required: Yes

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestLayout

Determines the layout format of the MSS manifest. This controls how the manifest is structured and presented to client players, affecting compatibility with different MSS-compatible devices and applications.

Type: String

Valid Values: FULL | COMPACT

Required: No

ManifestWindowSeconds

The total duration (in seconds) of the manifest window. This determines how much content is available in the manifest at any given time. The manifest window slides forward as new segments become available, maintaining a consistent duration of content. The minimum value is 30 seconds.

Type: Integer

Valid Range: Minimum value of 30.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashBaseUrl

The base URLs to use for retrieving segments. You can specify multiple locations and indicate the priority and weight for when each should be used, for use in multi-CDN workflows.

Contents

Url

A source location for segments.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

DvbPriority

For use with DVB-DASH profiles only. The priority of this location for serving segments. The lower the number, the higher the priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 15000.

Required: No

DvbWeight

For use with DVB-DASH profiles only. The weighting for source locations that have the same priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 15000.

Required: No

ServiceLocation

The name of the source location.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashDvbFontDownload

For use with DVB-DASH profiles only. The settings for font downloads that you want AWS Elemental MediaPackage to pass through to the manifest.

Contents

FontFamily

The `fontFamily` name for subtitles, as described in [EBU-TT-D Subtitling Distribution Format](#).

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: No

MimeType

The `mimeType` of the resource that's at the font download URL.

For information about font MIME types, see the [MPEG-DASH Profile for Transport of ISO BMFF Based DVB Services over IP Based Networks](#) document.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9][a-zA-Z0-9_-/-]*[a-zA-Z0-9]

Required: No

Url

The URL for downloading fonts for subtitles.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashDvbMetricsReporting

For use with DVB-DASH profiles only. The settings for error reporting from the playback device that you want AWS Elemental MediaPackage to pass through to the manifest.

Contents

ReportingUrl

The URL where playback devices send error reports.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Probability

The number of playback devices per 1000 that will send error reports to the reporting URL. This represents the probability that a playback device will be a reporting player for this session.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 1000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashDvbSettings

For endpoints that use the DVB-DASH profile only. The font download and error reporting information that you want MediaPackage to pass through to the manifest.

Contents

ErrorMetrics

Playback device error reporting settings.

Type: Array of [DashDvbMetricsReporting](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

FontDownload

Subtitle font settings.

Type: [DashDvbFontDownload](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashProgramInformation

Details about the content that you want MediaPackage to pass through in the manifest to the playback device.

Contents

Copyright

A copyright statement about the content.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

LanguageCode

The language code for this manifest.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 5.

Pattern: [a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]

Required: No

MoreInformationUrl

An absolute URL that contains more information about this content.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Source

Information about the content provider.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

Title

The title for the manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashSubtitleConfiguration

The configuration for DASH subtitles.

Contents

TtmlConfiguration

Settings for TTML subtitles.

Type: [DashTtmlConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashTtmlConfiguration

The settings for TTML subtitles.

Contents

TtmlProfile

The profile that MediaPackage uses when signaling subtitles in the manifest. IMSC is the default profile. EBU-TT-D produces subtitles that are compliant with the EBU-TT-D TTML profile. MediaPackage passes through subtitle styles to the manifest. For more information about EBU-TT-D subtitles, see [EBU-TT-D Subtitling Distribution Format](#).

Type: String

Valid Values: IMSC_1 | EBU_TT_D_101

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DashUtcTiming

Determines the type of UTC timing included in the DASH Media Presentation Description (MPD).

Contents

TimingMode

The UTC timing mode.

Type: String

Valid Values: HTTP_HEAD | HTTP_ISO | HTTP_XSDATE | UTC_DIRECT

Required: No

TimingSource

The method that the player uses to synchronize to coordinated universal time (UTC) wall clock time.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Destination

The configuration for the destination where the harvested content will be exported.

Contents

S3Destination

The configuration for exporting harvested content to an S3 bucket. This includes details such as the bucket name and destination path within the bucket.

Type: [S3DestinationConfig](#) object

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Encryption

The parameters for encrypting content.

Contents

EncryptionMethod

The encryption method to use.

Type: [EncryptionMethod](#) object

Required: Yes

SpekeKeyProvider

The parameters for the SPEKE key provider.

Type: [SpekeKeyProvider](#) object

Required: Yes

CmafExcludeSegmentDrmMetadata

Excludes SEIG and SGPD boxes from segment metadata in CMAF containers.

When set to true, MediaPackage omits these DRM metadata boxes from CMAF segments, which can improve compatibility with certain devices and players that don't support these boxes.

Important considerations:

- This setting only affects CMAF container formats
- Key rotation can still be handled through media playlist signaling
- PSSH and TENC boxes remain unaffected
- Default behavior is preserved when this setting is disabled

Valid values: true | false

Default: false

Type: Boolean

Required: No

ConstantInitializationVector

A 128-bit, 16-byte hex value represented by a 32-character string, used in conjunction with the key for encrypting content. If you don't specify a value, then MediaPackage creates the constant initialization vector (IV).

Type: String

Length Constraints: Fixed length of 32.

Pattern: [0-9a-fA-F]+

Required: No

KeyRotationIntervalSeconds

The frequency (in seconds) of key changes for live workflows, in which content is streamed real time. The service retrieves content keys before the live content begins streaming, and then retrieves them as needed over the lifetime of the workflow. By default, key rotation is set to 300 seconds (5 minutes), the minimum rotation interval, which is equivalent to setting it to 300. If you don't enter an interval, content keys aren't rotated.

The following example setting causes the service to rotate keys every thirty minutes: 1800

Type: Integer

Valid Range: Minimum value of 300. Maximum value of 31536000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionContractConfiguration

Configure one or more content encryption keys for your endpoints that use SPEKE Version 2.0. The encryption contract defines which content keys are used to encrypt the audio and video tracks in your stream. To configure the encryption contract, specify which audio and video encryption presets to use.

Contents

PresetSpeke20Audio

A collection of audio encryption presets.

Value description:

- PRESET-AUDIO-1 - Use one content key to encrypt all of the audio tracks in your stream.
- PRESET-AUDIO-2 - Use one content key to encrypt all of the stereo audio tracks and one content key to encrypt all of the multichannel audio tracks.
- PRESET-AUDIO-3 - Use one content key to encrypt all of the stereo audio tracks, one content key to encrypt all of the multichannel audio tracks with 3 to 6 channels, and one content key to encrypt all of the multichannel audio tracks with more than 6 channels.
- SHARED - Use the same content key for all of the audio and video tracks in your stream.
- UNENCRYPTED - Don't encrypt any of the audio tracks in your stream.

Type: String

Valid Values: PRESET_AUDIO_1 | PRESET_AUDIO_2 | PRESET_AUDIO_3 | SHARED | UNENCRYPTED

Required: Yes

PresetSpeke20Video

A collection of video encryption presets.

Value description:

- PRESET-VIDEO-1 - Use one content key to encrypt all of the video tracks in your stream.
- PRESET-VIDEO-2 - Use one content key to encrypt all of the SD video tracks and one content key for all HD and higher resolutions video tracks.

- PRESET-VIDEO-3 - Use one content key to encrypt all of the SD video tracks, one content key for HD video tracks and one content key for all UHD video tracks.
- PRESET-VIDEO-4 - Use one content key to encrypt all of the SD video tracks, one content key for HD video tracks, one content key for all UHD1 video tracks and one content key for all UHD2 video tracks.
- PRESET-VIDEO-5 - Use one content key to encrypt all of the SD video tracks, one content key for HD1 video tracks, one content key for HD2 video tracks, one content key for all UHD1 video tracks and one content key for all UHD2 video tracks.
- PRESET-VIDEO-6 - Use one content key to encrypt all of the SD video tracks, one content key for HD1 video tracks, one content key for HD2 video tracks and one content key for all UHD video tracks.
- PRESET-VIDEO-7 - Use one content key to encrypt all of the SD+HD1 video tracks, one content key for HD2 video tracks and one content key for all UHD video tracks.
- PRESET-VIDEO-8 - Use one content key to encrypt all of the SD+HD1 video tracks, one content key for HD2 video tracks, one content key for all UHD1 video tracks and one content key for all UHD2 video tracks.
- SHARED - Use the same content key for all of the video and audio tracks in your stream.
- UNENCRYPTED - Don't encrypt any of the video tracks in your stream.

Type: String

Valid Values: PRESET_VIDEO_1 | PRESET_VIDEO_2 | PRESET_VIDEO_3 |
PRESET_VIDEO_4 | PRESET_VIDEO_5 | PRESET_VIDEO_6 | PRESET_VIDEO_7 |
PRESET_VIDEO_8 | SHARED | UNENCRYPTED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EncryptionMethod

The encryption type.

Contents

CmafEncryptionMethod

The encryption method to use.

Type: String

Valid Values: CENC | CBCS

Required: No

IsmEncryptionMethod

The encryption method used for Microsoft Smooth Streaming (MSS) content. This specifies how the MSS segments are encrypted to protect the content during delivery to client players.

Type: String

Valid Values: CENC

Required: No

TsEncryptionMethod

The encryption method to use.

Type: String

Valid Values: AES_128 | SAMPLE_AES

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Contents

ClipStartTime

Optionally specify the clip start time for all of your manifest egress requests. When you include clip start time, note that you cannot use clip start time query parameters for this manifest's endpoint URL.

Type: Timestamp

Required: No

End

Optionally specify the end time for all of your manifest egress requests. When you include end time, note that you cannot use end time query parameters for this manifest's endpoint URL.

Type: Timestamp

Required: No

ManifestFilter

Optionally specify one or more manifest filters for all of your manifest egress requests. When you include a manifest filter, note that you cannot use an identical manifest filter query parameter for this manifest's endpoint URL.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: No

Start

Optionally specify the start time for all of your manifest egress requests. When you include start time, note that you cannot use start time query parameters for this manifest's endpoint URL.

Type: Timestamp

Required: No

TimeDelaySeconds

Optionally specify the time delay for all of your manifest egress requests. Enter a value that is smaller than your endpoint's startover window. When you include time delay, note that you cannot use time delay query parameters for this manifest's endpoint URL.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1209600.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ForceEndpointErrorConfiguration

The failover settings for the endpoint.

Contents

EndpointErrorConditions

The failover conditions for the endpoint. The options are:

- STALE_MANIFEST - The manifest stalled and there are no new segments or parts.
- INCOMPLETE_MANIFEST - There is a gap in the manifest.
- MISSING_DRM_KEY - Key rotation is enabled but we're unable to fetch the key for the current key period.
- SLATE_INPUT - The segments which contain slate content are considered to be missing content.

Type: Array of strings

Valid Values: STALE_MANIFEST | INCOMPLETE_MANIFEST | MISSING_DRM_KEY | SLATE_INPUT

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GetDashManifestConfiguration

Retrieve the DASH manifest configuration.

Contents

ManifestName

A short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Url

The egress domain URL for stream delivery from MediaPackage.

Type: String

Required: Yes

BaseUrls

The base URL to use for retrieving segments.

Type: Array of [DashBaseUrl](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Compactness

The layout of the DASH manifest that MediaPackage produces. STANDARD indicates a default manifest, which is compacted. NONE indicates a full manifest.

Type: String

Valid Values: STANDARD | NONE

Required: No

DrmSignaling

Determines how the DASH manifest signals the DRM content.

Type: String

Valid Values: INDIVIDUAL | REFERENCED

Required: No

DvbSettings

For endpoints that use the DVB-DASH profile only. The font download and error reporting information that you want MediaPackage to pass through to the manifest.

Type: [DashDvbSettings](#) object

Required: No

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestWindowSeconds

The total duration (in seconds) of the manifest's content.

Type: Integer

Required: No

MinBufferTimeSeconds

Minimum amount of content (in seconds) that a player must keep available in the buffer.

Type: Integer

Required: No

MinUpdatePeriodSeconds

Minimum amount of time (in seconds) that the player should wait before requesting updates to the manifest.

Type: Integer

Required: No

PeriodTriggers

A list of triggers that controls when AWS Elemental MediaPackage separates the MPEG-DASH manifest into multiple periods. Leave this value empty to indicate that the manifest is contained all in one period. For more information about periods in the DASH manifest, see [Multi-period DASH in AWS Elemental MediaPackage](#).

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Valid Values: AVAILS | DRM_KEY_ROTATION | SOURCE_CHANGES | SOURCE_DISRUPTIONS | NONE

Required: No

Profiles

The profile that the output is compliant with.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Valid Values: DVB_DASH

Required: No

ProgramInformation

Details about the content that you want MediaPackage to pass through in the manifest to the playback device.

Type: [DashProgramInformation](#) object

Required: No

ScteDash

The SCTE configuration.

Type: [ScteDash](#) object

Required: No

SegmentTemplateFormat

Determines the type of variable used in the media URL of the SegmentTemplate tag in the manifest. Also specifies if segment timeline information is included in SegmentTimeline or SegmentTemplate.

Value description:

- NUMBER_WITH_TIMELINE - The \$Number\$ variable is used in the media URL. The value of this variable is the sequential number of the segment. A full SegmentTimeline object is presented in each SegmentTemplate.

Type: String

Valid Values: NUMBER_WITH_TIMELINE

Required: No

SubtitleConfiguration

The configuration for DASH subtitles.

Type: [DashSubtitleConfiguration](#) object

Required: No

SuggestedPresentationDelaySeconds

The amount of time (in seconds) that the player should be from the end of the manifest.

Type: Integer

Required: No

UtcTiming

Determines the type of UTC timing included in the DASH Media Presentation Description (MPD).

Type: [DashUtcTiming object](#)

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GetHlsManifestConfiguration

Retrieve the HTTP live streaming (HLS) manifest configuration.

Contents

ManifestName

A short short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index. MediaPackage automatically inserts the format extension, such as .m3u8. You can't use the same manifest name if you use HLS manifest and low-latency HLS manifest. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Url

The egress domain URL for stream delivery from MediaPackage.

Type: String

Required: Yes

ChildManifestName

A short string that's appended to the endpoint URL. The child manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default child manifest name, index_1. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestWindowSeconds

The total duration (in seconds) of the manifest's content.

Type: Integer

Required: No

ProgramDateTimeIntervalSeconds

Inserts EXT-X-PROGRAM-DATE-TIME tags in the output manifest at the interval that you specify. If you don't enter an interval, EXT-X-PROGRAM-DATE-TIME tags aren't included in the manifest. The tags sync the stream to the wall clock so that viewers can seek to a specific time in the playback timeline on the player.

Irrespective of this parameter, if any ID3Timed metadata is in the HLS input, it is passed through to the HLS output.

Type: Integer

Required: No

ScteHls

The SCTE configuration.

Type: [ScteHls](#) object

Required: No

StartTag

To insert an EXT-X-START tag in your HLS playlist, specify a StartTag configuration object with a valid TimeOffset. When you do, you can also optionally specify whether to include a PRECISE value in the EXT-X-START tag.

Type: [StartTag](#) object

Required: No

UrlEncodeChildManifest

When enabled, MediaPackage URL-encodes the query string for API requests for HLS child manifests to comply with AWS Signature Version 4 (SigV4) signature signing protocol. For more information, see [AWS Signature Version 4 for API requests](#) in *AWS Identity and Access Management User Guide*.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GetLowLatencyHlsManifestConfiguration

Retrieve the low-latency HTTP live streaming (HLS) manifest configuration.

Contents

ManifestName

A short short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index. MediaPackage automatically inserts the format extension, such as .m3u8. You can't use the same manifest name if you use HLS manifest and low-latency HLS manifest. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Url

The egress domain URL for stream delivery from MediaPackage.

Type: String

Required: Yes

ChildManifestName

A short string that's appended to the endpoint URL. The child manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default child manifest name, index_1. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestWindowSeconds

The total duration (in seconds) of the manifest's content.

Type: Integer

Required: No

ProgramDateTimeIntervalSeconds

Inserts EXT-X-PROGRAM-DATE-TIME tags in the output manifest at the interval that you specify. If you don't enter an interval, EXT-X-PROGRAM-DATE-TIME tags aren't included in the manifest. The tags sync the stream to the wall clock so that viewers can seek to a specific time in the playback timeline on the player.

Irrespective of this parameter, if any ID3Timed metadata is in the HLS input, it is passed through to the HLS output.

Type: Integer

Required: No

ScteHls

The SCTE configuration.

Type: [ScteHls](#) object

Required: No

StartTag

To insert an EXT-X-START tag in your HLS playlist, specify a StartTag configuration object with a valid TimeOffset. When you do, you can also optionally specify whether to include a PRECISE value in the EXT-X-START tag.

Type: [StartTag](#) object

Required: No

UrlEncodeChildManifest

When enabled, MediaPackage URL-encodes the query string for API requests for LL-HLS child manifests to comply with AWS Signature Version 4 (SigV4) signature signing protocol. For more information, see [AWS Signature Version 4 for API requests](#) in *AWS Identity and Access Management User Guide*.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

GetMssManifestConfiguration

Configuration details for a Microsoft Smooth Streaming (MSS) manifest associated with an origin endpoint. This includes all the settings and properties that define how the MSS content is packaged and delivered.

Contents

ManifestName

The name of the MSS manifest. This name is appended to the origin endpoint URL to create the unique path for accessing this specific MSS manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9-]+

Required: Yes

Url

The complete URL for accessing the MSS manifest. Client players use this URL to retrieve the manifest and begin streaming the Microsoft Smooth Streaming content.

Type: String

Required: Yes

FilterConfiguration

Filter configuration includes settings for manifest filtering, start and end times, and time delay that apply to all of your egress requests for this manifest.

Type: [FilterConfiguration](#) object

Required: No

ManifestLayout

The layout format of the MSS manifest, which determines how the manifest is structured for client compatibility.

Type: String

Valid Values: FULL | COMPACT

Required: No

ManifestWindowSeconds

The duration (in seconds) of the manifest window. This represents the total amount of content available in the manifest at any given time.

Type: Integer

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HarvestedDashManifest

Information about a harvested DASH manifest.

Contents

ManifestName

The name of the harvested DASH manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HarvestedHlsManifest

Information about a harvested HLS manifest.

Contents

ManifestName

The name of the harvested HLS manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HarvestedLowLatencyHlsManifest

Information about a harvested Low-Latency HLS manifest.

Contents

ManifestName

The name of the harvested Low-Latency HLS manifest.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HarvestedManifests

A collection of harvested manifests of different types.

Contents

DashManifests

A list of harvested DASH manifests.

Type: Array of [HarvestedDashManifest](#) objects

Required: No

HlsManifests

A list of harvested HLS manifests.

Type: Array of [HarvestedHlsManifest](#) objects

Required: No

LowLatencyHlsManifests

A list of harvested Low-Latency HLS manifests.

Type: Array of [HarvestedLowLatencyHlsManifest](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HarvesterScheduleConfiguration

Defines the schedule configuration for a harvest job.

Contents

EndTime

The end time for the harvest job.

Type: Timestamp

Required: Yes

StartTime

The start time for the harvest job.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HarvestJob

Represents a harvest job resource in MediaPackage v2, which is used to export content from an origin endpoint to an S3 bucket.

Contents

Arn

The Amazon Resource Name (ARN) of the harvest job.

Type: String

Required: Yes

ChannelGroupName

The name of the channel group containing the channel associated with this harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name of the channel associated with this harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

CreatedAt

The date and time when the harvest job was created.

Type: Timestamp

Required: Yes

Destination

The S3 destination where the harvested content will be placed.

Type: [Destination](#) object

Required: Yes

HarvestedManifests

A list of manifests that are being or have been harvested.

Type: [HarvestedManifests](#) object

Required: Yes

HarvestJobName

The name of the harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ModifiedAt

The date and time when the harvest job was last modified.

Type: Timestamp

Required: Yes

OriginEndpointName

The name of the origin endpoint associated with this harvest job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ScheduleConfiguration

The configuration for when the harvest job is scheduled to run.

Type: [HarvesterScheduleConfiguration](#) object

Required: Yes

Status

The current status of the harvest job (e.g., QUEUED, IN_PROGRESS, CANCELLED, COMPLETED, FAILED).

Type: String

Valid Values: QUEUED | IN_PROGRESS | CANCELLED | COMPLETED | FAILED

Required: Yes

Description

An optional description of the harvest job.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ErrorMessage

An error message if the harvest job encountered any issues.

Type: String

Required: No

ETag

The current version of the harvest job. Used for concurrency control.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[\S]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IngestEndpoint

The ingest domain URL where the source stream should be sent.

Contents

Id

The system-generated unique identifier for the IngestEndpoint.

Type: String

Required: No

Url

The ingest domain URL where the source stream should be sent.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InputSwitchConfiguration

The configuration for input switching based on the media quality confidence score (MQCS) as provided from AWS Elemental MediaLive.

Contents

MQCSInputSwitching

When true, AWS Elemental MediaPackage performs input switching based on the MQCS.

Default is false. This setting is valid only when InputType is CMAF.

Type: Boolean

Required: No

PreferredInput

For CMAF inputs, indicates which input MediaPackage should prefer when both inputs have equal MQCS scores. Select 1 to prefer the first ingest endpoint, or 2 to prefer the second ingest endpoint. If you don't specify a preferred input, MediaPackage uses its default switching behavior when MQCS scores are equal.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListDashManifestConfiguration

List the DASH manifest configuration.

Contents

ManifestName

A short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Url

The egress domain URL for stream delivery from MediaPackage.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListHlsManifestConfiguration

List the HTTP live streaming (HLS) manifest configuration.

Contents

ManifestName

A short short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index. MediaPackage automatically inserts the format extension, such as .m3u8. You can't use the same manifest name if you use HLS manifest and low-latency HLS manifest. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChildManifestName

A short string that's appended to the endpoint URL. The child manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default child manifest name, index_1. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

Url

The egress domain URL for stream delivery from MediaPackage.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListLowLatencyHlsManifestConfiguration

List the low-latency HTTP live streaming (HLS) manifest configuration.

Contents

ManifestName

A short short string that's appended to the endpoint URL. The manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default manifest name, index. MediaPackage automatically inserts the format extension, such as .m3u8. You can't use the same manifest name if you use HLS manifest and low-latency HLS manifest. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChildManifestName

A short string that's appended to the endpoint URL. The child manifest name creates a unique path to this endpoint. If you don't enter a value, MediaPackage uses the default child manifest name, index_1. The manifestName on the HLSManifest object overrides the manifestName you provided on the originEndpoint object.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

Url

The egress domain URL for stream delivery from MediaPackage.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListMssManifestConfiguration

Summary information about a Microsoft Smooth Streaming (MSS) manifest configuration. This provides key details about the MSS manifest without including all configuration parameters.

Contents

ManifestName

The name of the MSS manifest configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

Url

The URL for accessing the MSS manifest.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OriginEndpointListConfiguration

The configuration of the origin endpoint.

Contents

Arn

The Amazon Resource Name (ARN) associated with the resource.

Type: String

Required: Yes

ChannelGroupName

The name that describes the channel group. The name is the primary identifier for the channel group, and must be unique for your account in the AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ChannelName

The name that describes the channel. The name is the primary identifier for the channel, and must be unique for your account in the AWS Region and channel group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

ContainerType

The type of container attached to this origin endpoint. A container type is a file format that encapsulates one or more media streams, such as audio and video, into a single file.

Type: String

Valid Values: TS | CMAF | ISM

Required: Yes

OriginEndpointName

The name that describes the origin endpoint. The name is the primary identifier for the origin endpoint, and must be unique for your account in the AWS Region and channel.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: Yes

CreatedAt

The date and time the origin endpoint was created.

Type: Timestamp

Required: No

DashManifests

A DASH manifest configuration.

Type: Array of [ListDashManifestConfiguration](#) objects

Required: No

Description

Any descriptive information that you want to add to the origin endpoint for future identification purposes.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1024.

Required: No

ForceEndpointErrorConfiguration

The failover settings for the endpoint.

Type: [ForceEndpointErrorConfiguration](#) object

Required: No

HlsManifests

An HTTP live streaming (HLS) manifest configuration.

Type: Array of [ListHlsManifestConfiguration](#) objects

Required: No

LowLatencyHlsManifests

A low-latency HLS manifest configuration.

Type: Array of [ListLowLatencyHlsManifestConfiguration](#) objects

Required: No

ModifiedAt

The date and time the origin endpoint was modified.

Type: Timestamp

Required: No

MssManifests

A list of Microsoft Smooth Streaming (MSS) manifest configurations associated with the origin endpoint. Each configuration represents a different MSS streaming option available from this endpoint.

Type: Array of [ListMssManifestConfiguration](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OutputHeaderConfiguration

The settings for what common media server data (CMSD) headers AWS Elemental MediaPackage includes in responses to the CDN.

Contents

PublishMQCS

When true, AWS Elemental MediaPackage includes the MQCS in responses to the CDN. This setting is valid only when InputType is CMAF.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3DestinationConfig

Configuration parameters for where in an S3 bucket to place the harvested content.

Contents

BucketName

The name of an S3 bucket within which harvested content will be exported.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Required: Yes

DestinationPath

The path within the specified S3 bucket where the harvested content will be placed.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: [\S]+

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Scte

The SCTE configuration.

Contents

ScteFilter

The SCTE-35 message types that you want to be treated as ad markers in the output.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Valid Values: SPLICE_INSERT | BREAK | PROVIDER_ADVERTISEMENT | DISTRIBUTOR_ADVERTISEMENT | PROVIDER_PLACEMENT OPPORTUNITY | DISTRIBUTOR_PLACEMENT OPPORTUNITY | PROVIDER_OVERLAY_PLACEMENT OPPORTUNITY | DISTRIBUTOR_OVERLAY_PLACEMENT OPPORTUNITY | PROGRAM

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScteDash

The SCTE configuration.

Contents

AdMarkerDash

Choose how ad markers are included in the packaged content. If you include ad markers in the content stream in your upstream encoders, then you need to inform MediaPackage what to do with the ad markers in the output.

Value description:

- Binary - The SCTE-35 marker is expressed as a hex-string (Base64 string) rather than full XML.
- XML - The SCTE marker is expressed fully in XML.

Type: String

Valid Values: BINARY | XML

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScteHls

The SCTE configuration.

Contents

AdMarkerHls

Ad markers indicate when ads should be inserted during playback. If you include ad markers in the content stream in your upstream encoders, then you need to inform MediaPackage what to do with the ad markers in the output. Choose what you want MediaPackage to do with the ad markers.

Value description:

- DATERANGE - Insert EXT-X-DATERANGE tags to signal ad and program transition events in TS and CMAF manifests. If you use DATERANGE, you must set a programDateTimeIntervalSeconds value of 1 or higher. To learn more about DATERANGE, see [SCTE-35 Ad Marker EXT-X-DATERANGE](#).

Type: String

Valid Values: DATERANGE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Segment

The segment configuration, including the segment name, duration, and other configuration values.

Contents

Encryption

The parameters for encrypting content.

Type: [Encryption](#) object

Required: No

IncludeIframeOnlyStreams

When selected, the stream set includes an additional I-frame only stream, along with the other tracks. If false, this extra stream is not included. MediaPackage generates an I-frame only stream from the first rendition in the manifest. The service inserts EXT-I-FRAMES-ONLY tags in the output manifest, and then generates and includes an I-frames only playlist in the stream. This playlist permits player functionality like fast forward and rewind.

Type: Boolean

Required: No

Scte

The SCTE configuration options in the segment settings.

Type: [Scte](#) object

Required: No

SegmentDurationSeconds

The duration (in seconds) of each segment. Enter a value equal to, or a multiple of, the input segment duration. If the value that you enter is different from the input segment duration, MediaPackage rounds segments to the nearest multiple of the input segment duration.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 30.

Required: No

SegmentName

The name that describes the segment. The name is the base name of the segment used in all content manifests inside of the endpoint. You can't use spaces in the name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [a-zA-Z0-9_-]+

Required: No

TsIncludeDvbSubtitles

By default, MediaPackage excludes all digital video broadcasting (DVB) subtitles from the output. When selected, MediaPackage passes through DVB subtitles into the output.

Type: Boolean

Required: No

TsUseAudioRenditionGroup

When selected, MediaPackage bundles all audio tracks in a rendition group. All other tracks in the stream can be used with any audio rendition from the group.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SpekeKeyProvider

The parameters for the SPEKE key provider.

Contents

DrmSystems

The DRM solution provider you're using to protect your content during distribution.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 4 items.

Valid Values: CLEAR_KEY_AES_128 | FAIRPLAY | PLAYREADY | WIDEVINE | IRDETO

Required: Yes

EncryptionContractConfiguration

Configure one or more content encryption keys for your endpoints that use SPEKE Version 2.0. The encryption contract defines which content keys are used to encrypt the audio and video tracks in your stream. To configure the encryption contract, specify which audio and video encryption presets to use.

Type: [EncryptionContractConfiguration](#) object

Required: Yes

ResourceId

The unique identifier for the content. The service sends this to the key server to identify the current endpoint. How unique you make this depends on how fine-grained you want access controls to be. The service does not permit you to use the same ID for two simultaneous encryption processes. The resource ID is also known as the content ID.

The following example shows a resource ID: MovieNight20171126093045

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [0-9a-zA-Z_-]+

Required: Yes

RoleArn

The ARN for the IAM role granted by the key provider that provides access to the key provider API. This role must have a trust policy that allows MediaPackage to assume the role, and it must have a sufficient permissions policy to allow access to the specific key retrieval URL. Get this from your DRM solution provider.

Valid format: `arn:aws:iam::{accountID}:role/{name}`. The following example shows a role ARN: `arn:aws:iam::44445556666:role/SpekeAccess`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

Url

The URL of the API Gateway proxy that you set up to talk to your key server. The API Gateway proxy must reside in the same AWS Region as MediaPackage and must start with `https://`.

The following example shows a URL: `https://1wm2dx1f33.execute-api.us-west-2.amazonaws.com/SpekeSample/copyProtection`

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

StartTag

To insert an EXT-X-START tag in your HLS playlist, specify a StartTag configuration object with a valid TimeOffset. When you do, you can also optionally specify whether to include a PRECISE value in the EXT-X-START tag.

Contents

TimeOffset

Specify the value for TIME-OFFSET within your EXT-X-START tag. Enter a signed floating point value which, if positive, must be less than the configured manifest duration minus three times the configured segment target duration. If negative, the absolute value must be larger than three times the configured segment target duration, and the absolute value must be smaller than the configured manifest duration.

Type: Float

Required: Yes

Precise

Specify the value for PRECISE within your EXT-X-START tag. Leave blank, or choose false, to use the default value NO. Choose yes to use the value YES.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests in the IAM User Guide](#).

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationException

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400