



API Reference

Amazon OpenSearch Serverless



API Version 2021-11-01

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon OpenSearch Serverless: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchGetCollection	4
Request Syntax	4
Request Parameters	4
Response Syntax	5
Response Elements	5
Errors	6
Examples	6
See Also	8
BatchGetEffectiveLifecyclePolicy	9
Request Syntax	9
Request Parameters	9
Response Syntax	9
Response Elements	10
Errors	10
See Also	11
BatchGetLifecyclePolicy	12
Request Syntax	12
Request Parameters	12
Response Syntax	12
Response Elements	13
Errors	13
See Also	14
BatchGetVpcEndpoint	15
Request Syntax	15
Request Parameters	15
Response Syntax	15
Response Elements	16
Errors	16
See Also	17
CreateAccessPolicy	18
Request Syntax	18
Request Parameters	18

Response Syntax	19
Response Elements	20
Errors	20
See Also	21
CreateCollection	22
Request Syntax	22
Request Parameters	22
Response Syntax	24
Response Elements	24
Errors	24
Examples	25
See Also	26
CreateIndex	28
Request Syntax	28
Request Parameters	28
Response Elements	29
Errors	29
See Also	30
CreateLifecyclePolicy	31
Request Syntax	31
Request Parameters	31
Response Syntax	32
Response Elements	33
Errors	33
See Also	34
CreateSecurityConfig	35
Request Syntax	35
Request Parameters	35
Response Syntax	37
Response Elements	38
Errors	38
See Also	39
CreateSecurityPolicy	40
Request Syntax	40
Request Parameters	40
Response Syntax	41

Response Elements	42
Errors	42
See Also	43
CreateVpcEndpoint	44
Request Syntax	44
Request Parameters	44
Response Syntax	45
Response Elements	46
Errors	46
See Also	47
DeleteAccessPolicy	48
Request Syntax	48
Request Parameters	48
Response Elements	49
Errors	49
See Also	49
DeleteCollection	51
Request Syntax	51
Request Parameters	51
Response Syntax	52
Response Elements	52
Errors	52
Examples	53
See Also	54
DeleteIndex	55
Request Syntax	55
Request Parameters	55
Response Elements	55
Errors	56
See Also	56
DeleteLifecyclePolicy	57
Request Syntax	57
Request Parameters	57
Response Elements	58
Errors	58
See Also	58

DeleteSecurityConfig	60
Request Syntax	60
Request Parameters	60
Response Elements	60
Errors	61
See Also	61
DeleteSecurityPolicy	63
Request Syntax	63
Request Parameters	63
Response Elements	64
Errors	64
See Also	64
DeleteVpcEndpoint	66
Request Syntax	66
Request Parameters	66
Response Syntax	66
Response Elements	67
Errors	67
See Also	68
GetAccessPolicy	69
Request Syntax	69
Request Parameters	69
Response Syntax	69
Response Elements	70
Errors	70
See Also	71
GetAccountSettings	72
Response Syntax	72
Response Elements	72
Errors	72
See Also	73
GetIndex	74
Request Syntax	74
Request Parameters	74
Response Syntax	74
Response Elements	75

Errors	75
See Also	75
GetPoliciesStats	77
Response Syntax	77
Response Elements	77
Errors	78
See Also	78
GetSecurityConfig	80
Request Syntax	80
Request Parameters	80
Response Syntax	80
Response Elements	81
Errors	81
See Also	82
GetSecurityPolicy	83
Request Syntax	83
Request Parameters	83
Response Syntax	84
Response Elements	84
Errors	84
See Also	85
ListAccessPolicies	86
Request Syntax	86
Request Parameters	86
Response Syntax	87
Response Elements	87
Errors	88
See Also	88
ListCollections	90
Request Syntax	90
Request Parameters	90
Response Syntax	91
Response Elements	91
Errors	92
Examples	92
See Also	95

ListLifecyclePolicies	96
Request Syntax	96
Request Parameters	96
Response Syntax	97
Response Elements	97
Errors	98
See Also	98
ListSecurityConfigs	100
Request Syntax	100
Request Parameters	100
Response Syntax	101
Response Elements	101
Errors	102
See Also	102
ListSecurityPolicies	103
Request Syntax	103
Request Parameters	103
Response Syntax	104
Response Elements	104
Errors	105
See Also	105
ListTagsForResource	107
Request Syntax	107
Request Parameters	107
Response Syntax	107
Response Elements	108
Errors	108
See Also	108
ListVpcEndpoints	110
Request Syntax	110
Request Parameters	110
Response Syntax	111
Response Elements	111
Errors	112
See Also	112
TagResource	113

Request Syntax	113
Request Parameters	113
Response Elements	114
Errors	114
See Also	114
UntagResource	116
Request Syntax	116
Request Parameters	116
Response Elements	117
Errors	117
See Also	117
UpdateAccessPolicy	119
Request Syntax	119
Request Parameters	119
Response Syntax	121
Response Elements	121
Errors	121
See Also	122
UpdateAccountSettings	123
Request Syntax	123
Request Parameters	123
Response Syntax	123
Response Elements	124
Errors	124
See Also	124
UpdateCollection	126
Request Syntax	126
Request Parameters	126
Response Syntax	127
Response Elements	127
Errors	127
See Also	128
UpdateIndex	129
Request Syntax	129
Request Parameters	129
Response Elements	130

Errors	130
See Also	130
UpdateLifecyclePolicy	132
Request Syntax	132
Request Parameters	132
Response Syntax	134
Response Elements	134
Errors	134
See Also	135
UpdateSecurityConfig	136
Request Syntax	136
Request Parameters	136
Response Syntax	138
Response Elements	139
Errors	139
See Also	140
UpdateSecurityPolicy	141
Request Syntax	141
Request Parameters	141
Response Syntax	143
Response Elements	143
Errors	143
See Also	144
UpdateVpcEndpoint	145
Request Syntax	145
Request Parameters	145
Response Syntax	147
Response Elements	147
Errors	147
See Also	148
Data Types	149
AccessPolicyDetail	151
Contents	151
See Also	152
AccessPolicyStats	153
Contents	153

See Also	153
AccessPolicySummary	154
Contents	154
See Also	155
AccountSettingsDetail	156
Contents	156
See Also	156
CapacityLimits	157
Contents	157
See Also	157
CollectionDetail	158
Contents	158
See Also	160
CollectionErrorDetail	162
Contents	162
See Also	163
CollectionFilters	164
Contents	164
See Also	164
CollectionSummary	165
Contents	165
See Also	166
CreateCollectionDetail	167
Contents	167
See Also	169
CreateIamIdentityCenterConfigOptions	170
Contents	170
See Also	170
CreateVpcEndpointDetail	172
Contents	172
See Also	172
DeleteCollectionDetail	174
Contents	174
See Also	174
DeleteVpcEndpointDetail	176
Contents	176

See Also	176
EffectiveLifecyclePolicyDetail	178
Contents	178
See Also	179
EffectiveLifecyclePolicyErrorDetail	180
Contents	180
See Also	180
IamFederationConfigOptions	182
Contents	182
See Also	182
IamIdentityCenterConfigOptions	184
Contents	184
See Also	185
LifecyclePolicyDetail	186
Contents	186
See Also	187
LifecyclePolicyErrorDetail	188
Contents	188
See Also	189
LifecyclePolicyIdentifier	190
Contents	190
See Also	190
LifecyclePolicyResourceIdentifier	191
Contents	191
See Also	191
LifecyclePolicyStats	192
Contents	192
See Also	192
LifecyclePolicySummary	193
Contents	193
See Also	194
SamlConfigOptions	195
Contents	195
See Also	196
SecurityConfigDetail	197
Contents	197

See Also	199
SecurityConfigStats	200
Contents	200
See Also	200
SecurityConfigSummary	201
Contents	201
See Also	202
SecurityPolicyDetail	203
Contents	203
See Also	204
SecurityPolicyStats	205
Contents	205
See Also	205
SecurityPolicySummary	206
Contents	206
See Also	207
Tag	208
Contents	208
See Also	208
UpdateCollectionDetail	209
Contents	209
See Also	210
UpdateIamIdentityCenterConfigOptions	212
Contents	212
See Also	212
UpdateVpcEndpointDetail	213
Contents	213
See Also	214
VpcEndpointDetail	215
Contents	215
See Also	217
VpcEndpointErrorDetail	218
Contents	218
See Also	218
VpcEndpointFilters	220
Contents	220

See Also	220
VpcEndpointSummary	221
Contents	221
See Also	221
Common Parameters	223
Common Errors	226

Welcome

Use the Amazon OpenSearch Serverless API to create, configure, and manage OpenSearch Serverless collections and security policies.

OpenSearch Serverless is an on-demand, pre-provisioned serverless configuration for Amazon OpenSearch Service. OpenSearch Serverless removes the operational complexities of provisioning, configuring, and tuning your OpenSearch clusters. It enables you to easily search and analyze petabytes of data without having to worry about the underlying infrastructure and data management.

To learn more about OpenSearch Serverless, see [What is Amazon OpenSearch Serverless?](#)

This document was last published on August 31, 2025.

Actions

The following actions are supported:

- [BatchGetCollection](#)
- [BatchGetEffectiveLifecyclePolicy](#)
- [BatchGetLifecyclePolicy](#)
- [BatchGetVpcEndpoint](#)
- [CreateAccessPolicy](#)
- [CreateCollection](#)
- [CreateIndex](#)
- [CreateLifecyclePolicy](#)
- [CreateSecurityConfig](#)
- [CreateSecurityPolicy](#)
- [CreateVpcEndpoint](#)
- [DeleteAccessPolicy](#)
- [DeleteCollection](#)
- [DeleteIndex](#)
- [DeleteLifecyclePolicy](#)
- [DeleteSecurityConfig](#)
- [DeleteSecurityPolicy](#)
- [DeleteVpcEndpoint](#)
- [GetAccessPolicy](#)
- [GetAccountSettings](#)
- [GetIndex](#)
- [GetPoliciesStats](#)
- [GetSecurityConfig](#)
- [GetSecurityPolicy](#)
- [ListAccessPolicies](#)
- [ListCollections](#)
- [ListLifecyclePolicies](#)

- [ListSecurityConfigs](#)
- [ListSecurityPolicies](#)
- [ListTagsForResource](#)
- [ListVpcEndpoints](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAccessPolicy](#)
- [UpdateAccountSettings](#)
- [UpdateCollection](#)
- [UpdateIndex](#)
- [UpdateLifecyclePolicy](#)
- [UpdateSecurityConfig](#)
- [UpdateSecurityPolicy](#)
- [UpdateVpcEndpoint](#)

BatchGetCollection

Returns attributes for one or more collections, including the collection endpoint and the OpenSearch Dashboards endpoint. For more information, see [Creating and managing Amazon OpenSearch Serverless collections](#).

Request Syntax

```
{
  "ids": [ "string" ],
  "names": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ids

A list of collection IDs. You can't provide names and IDs in the same request. The ID is part of the collection endpoint. You can also retrieve it using the [ListCollections](#) API.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: [a-z0-9]{3,40}

Required: No

names

A list of collection names. You can't provide names and IDs in the same request.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

Response Syntax

```
{
  "collectionDetails": [
    {
      "arn": "string",
      "collectionEndpoint": "string",
      "createdDate": number,
      "dashboardEndpoint": "string",
      "description": "string",
      "failureCode": "string",
      "failureMessage": "string",
      "id": "string",
      "kmsKeyArn": "string",
      "lastModifiedDate": number,
      "name": "string",
      "standbyReplicas": "string",
      "status": "string",
      "type": "string"
    }
  ],
  "collectionErrorDetails": [
    {
      "errorCode": "string",
      "errorMessage": "string",
      "id": "string",
      "name": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

collectionDetails

Details about each collection.

Type: Array of [CollectionDetail](#) objects

collectionErrorDetails

Error information for the request.

Type: Array of [CollectionErrorDetail](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

Examples

Retrieve attributes from multiple collections

The following example requests attributes from two different collections.

Sample Request

```
POST / HTTP/1.1
Host: aoss.<region>.<domain>
Accept-Encoding: identity
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.0
```

```
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>
X-Amz-Date: <Date>
X-Amz-Target: OpenSearchServerless.BatchGetCollection

{
  "ids": ["1iu5usc4adj5", "1iu5usc4rame"]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
x-amz-crc32: <Checksum>
Content-Type: application/x-amz-json-1.0
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "collectionDetails": [
    {
      "arn": "arn:aws:aoss:us-east-1:123456789012:collection/07tjusf2h91cunochc",
      "collectionEndpoint": "https://07tjusf2h91cunochc.us-east-1.aoss.amazonaws.com",
      "createdDate": 1655422947204,
      "lastModifiedDate": 1655422947204,
      "dashboardEndpoint": "https://07tjusf2h91cunochc.us-east-1.aoss.amazonaws.com/_dashboards",
      "kmsKeyArn": "arn:aws:kms:us-east-1:123456789012:key/1234abcd-12ab-34cd-56ef-1234567890ab",
      "type": "TIMESERIES",
      "description": "Log data",
      "id": "07tjusf2h91cunochc",
      "name": "my-collection",
      "status": "ACTIVE"
    },
    {
      "id": "178ukvtg3i82dvopdid",
      "name": "another-collection",
      "status": "CREATING",
      "type": "TIMESERIES",
      "description": "",
      "arn": "arn:aws:aoss:us-east-1:123456789012:collection/178ukvtg3i82dvopdid",

```

```
        "kmsKeyArn": "arn:aws:kms:us-east-1:123456789012:key/1234abcd-12ab-34cd-56ef-1234567890ab",
        "createdDate": 1667446262828,
        "lastModifiedDate": 1667446300769,
        "collectionEndpoint": "https://178ukvtg3i82dvopdid.us-east-1.aoss.amazonaws.com",
        "dashboardEndpoint": "https://178ukvtg3i82dvopdid.us-east-1.aoss.amazonaws.com/_dashboards"
    }
],
"collectionErrorDetails": []
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchGetEffectiveLifecyclePolicy

Returns a list of successful and failed retrievals for the OpenSearch Serverless indexes. For more information, see [Viewing data lifecycle policies](#).

Request Syntax

```
{
  "resourceIdentifiers": [
    {
      "resource": "string",
      "type": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[resourceIdentifiers](#)

The unique identifiers of policy types and resource names.

Type: Array of [LifecyclePolicyResourceIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

Response Syntax

```
{
  "effectiveLifecyclePolicyDetails": [
    {
      "noMinRetentionPeriod": boolean,
      "policyName": "string",
      "resource": "string",

```

```
    "resourceType": "string",
    "retentionPeriod": "string",
    "type": "string"
  },
  ],
  "effectiveLifecyclePolicyErrorDetails": [
    {
      "errorCode": "string",
      "errorMessage": "string",
      "resource": "string",
      "type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

effectiveLifecyclePolicyDetails

A list of lifecycle policies applied to the OpenSearch Serverless indexes.

Type: Array of [EffectiveLifecyclePolicyDetail](#) objects

effectiveLifecyclePolicyErrorDetails

A list of resources for which retrieval failed.

Type: Array of [EffectiveLifecyclePolicyErrorDetail](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchGetLifecyclePolicy

Returns one or more configured OpenSearch Serverless lifecycle policies. For more information, see [Viewing data lifecycle policies](#).

Request Syntax

```
{
  "identifiers": [
    {
      "name": "string",
      "type": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

identifiers

The unique identifiers of policy types and policy names.

Type: Array of [LifecyclePolicyIdentifier](#) objects

Array Members: Minimum number of 1 item. Maximum number of 40 items.

Required: Yes

Response Syntax

```
{
  "lifecyclePolicyDetails": [
    {
      "createdDate": number,
      "description": "string",
      "lastModifiedDate": number,
```

```
    "name": "string",
    "policy": JSON value,
    "policyVersion": "string",
    "type": "string"
  }
],
"lifecyclePolicyErrorDetails": [
  {
    "errorCode": "string",
    "errorMessage": "string",
    "name": "string",
    "type": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[lifecyclePolicyDetails](#)

A list of lifecycle policies matched to the input policy name and policy type.

Type: Array of [LifecyclePolicyDetail](#) objects

[lifecyclePolicyErrorDetails](#)

A list of lifecycle policy names and policy types for which retrieval failed.

Type: Array of [LifecyclePolicyErrorDetail](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

BatchGetVpcEndpoint

Returns attributes for one or more VPC endpoints associated with the current account. For more information, see [Access Amazon OpenSearch Serverless using an interface endpoint](#).

Request Syntax

```
{
  "ids": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

ids

A list of VPC endpoint identifiers.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: vpce-[0-9a-z]*

Required: Yes

Response Syntax

```
{
  "vpcEndpointDetails": [
    {
      "createdDate": number,
      "failureCode": "string",
      "failureMessage": "string",
      "id": "string",
    }
  ]
}
```

```
    "name": "string",
    "securityGroupIds": [ "string" ],
    "status": "string",
    "subnetIds": [ "string" ],
    "vpcId": "string"
  }
],
"vpcEndpointErrorDetails": [
  {
    "errorCode": "string",
    "errorMessage": "string",
    "id": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[vpcEndpointDetails](#)

Details about the specified VPC endpoint.

Type: Array of [VpcEndpointDetail](#) objects

[vpcEndpointErrorDetails](#)

Error information for a failed request.

Type: Array of [VpcEndpointErrorDetail](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAccessPolicy

Creates a data access policy for OpenSearch Serverless. Access policies limit access to collections and the resources within them, and allow a user to access that data irrespective of the access mechanism or network source. For more information, see [Data access control for Amazon OpenSearch Serverless](#).

Request Syntax

```
{
  "clientToken": "string",
  "description": "string",
  "name": "string",
  "policy": "string",
  "type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

description

A description of the policy. Typically used to store information about the permissions defined in the policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

policy

The JSON policy document to use as the content for the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20480.

Pattern: `. * [\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF] + . *`

Required: Yes

type

The type of policy.

Type: String

Valid Values: `data`

Required: Yes

Response Syntax

```
{
  "accessPolicyDetail": {
    "createdDate": number,
    "description": "string",
    "lastModifiedDate": number,
    "name": "string",
```

```
"policy": JSON value,  
"policyVersion": "string",  
"type": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accessPolicyDetail

Details about the created access policy.

Type: [AccessPolicyDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCollection

Creates a new OpenSearch Serverless collection. For more information, see [Creating and managing Amazon OpenSearch Serverless collections](#).

Request Syntax

```
{
  "clientToken": "string",
  "description": "string",
  "name": "string",
  "standbyReplicas": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ],
  "type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

description

Description of the collection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

name

Name of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

standbyReplicas

Indicates whether standby replicas should be used for a collection.

Type: String

Valid Values: `ENABLED` | `DISABLED`

Required: No

tags

An arbitrary set of tags (key–value pairs) to associate with the OpenSearch Serverless collection.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

type

The type of collection.

Type: String

Valid Values: `SEARCH` | `TIMESERIES` | `VECTORSEARCH`

Required: No

Response Syntax

```
{
  "createCollectionDetail": {
    "arn": "string",
    "createdDate": number,
    "description": "string",
    "id": "string",
    "kmsKeyArn": "string",
    "lastModifiedDate": number,
    "name": "string",
    "standbyReplicas": "string",
    "status": "string",
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[createCollectionDetail](#)

Details about the collection.

Type: [CreateCollectionDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

OcuLimitExceededException

Thrown when the collection you're attempting to create results in a number of search or indexing OCUs that exceeds the account limit.

HTTP Status Code: 400

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

Examples

Create a collection

The following example creates a collection.

Sample Request

```
POST / HTTP/1.1
Host: aoss.<region>.<domain>
Accept-Encoding: identity
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.0
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>
X-Amz-Date: <Date>
X-Amz-Target: OpenSearchServerless.CreateCollection
```

```
{
  "name": "my-collection-name",
  "description": "collection-description",
  "clientToken": "f576fe66-8dd5-11ec-b909-0242ac120004",
  "type": "SEARCH"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
x-amz-crc32: <Checksum>
Content-Type: application/x-amz-json-1.0
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "createCollectionDetail":{
    "arn":"arn:aws:aoss:us-east-1:123456789012:collection/07tjusf2h91cunochc",
    "createdDate":1637012666117,
    "description":"collection-description",
    "kmsKeyArn": "auto",
    "type": "SEARCH",
    "id":"07tjusf2h91cunochc",
    "name":"my-collection-name",
    "status":"CREATING"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateIndex

Creates an index within an OpenSearch Serverless collection. Unlike other OpenSearch indexes, indexes created by this API are automatically configured to conduct automatic semantic enrichment ingestion and search. For more information, see [About automatic semantic enrichment](#) in the *OpenSearch User Guide*.

Request Syntax

```
{
  "id": "string",
  "indexName": "string",
  "indexSchema": JSON value
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The unique identifier of the collection in which to create the index.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: Yes

indexName

The name of the index to create. Index names must be lowercase and can't begin with underscores (`_`) or hyphens (`-`).

Type: String

Required: Yes

indexSchema

The JSON schema definition for the index, including field mappings and settings.

Type: JSON value

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateLifecyclePolicy

Creates a lifecycle policy to be applied to OpenSearch Serverless indexes. Lifecycle policies define the number of days or hours to retain the data on an OpenSearch Serverless index. For more information, see [Creating data lifecycle policies](#).

Request Syntax

```
{
  "clientToken": "string",
  "description": "string",
  "name": "string",
  "policy": "string",
  "type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[description](#)

A description of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

name

The name of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

policy

The JSON policy document to use as the content for the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20480.

Pattern: `. * [ \ u 0 0 0 9 \ u 0 0 0 A \ u 0 0 0 D \ u 0 0 2 0 - \ u 0 0 7 E \ u 0 0 A 1 - \ u 0 0 F F ] + . *`

Required: Yes

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: Yes

Response Syntax

```
{
  "lifecyclePolicyDetail": {
    "createdDate": number,
    "description": "string",
    "lastModifiedDate": number,
    "name": "string",
    "policy": JSON value,
    "policyVersion": "string",
```

```
    "type": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

lifecyclePolicyDetail

Details about the created lifecycle policy.

Type: LifecyclePolicyDetail object

Errors

For information about the errors that are common to all actions, see Common Errors.

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSecurityConfig

Specifies a security configuration for OpenSearch Serverless. For more information, see [SAML authentication for Amazon OpenSearch Serverless](#).

Request Syntax

```
{
  "clientToken": "string",
  "description": "string",
  "iamFederationOptions": {
    "groupAttribute": "string",
    "userAttribute": "string"
  },
  "iamIdentityCenterOptions": {
    "groupAttribute": "string",
    "instanceArn": "string",
    "userAttribute": "string"
  },
  "name": "string",
  "samlOptions": {
    "groupAttribute": "string",
    "metadata": "string",
    "openSearchServerlessEntityId": "string",
    "sessionTimeout": number,
    "userAttribute": "string"
  },
  "type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

description

A description of the security configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

iamFederationOptions

Describes IAM federation options in the form of a key-value map. This field is required if you specify `iamFederation` for the `type` parameter.

Type: [IamFederationConfigOptions](#) object

Required: No

iamIdentityCenterOptions

Describes IAM Identity Center options in the form of a key-value map. This field is required if you specify `iamidentitycenter` for the `type` parameter.

Type: [CreateIamIdentityCenterConfigOptions](#) object

Required: No

name

The name of the security configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

samlOptions

Describes SAML options in the form of a key-value map. This field is required if you specify `SAML` for the `type` parameter.

Type: [SamlConfigOptions](#) object

Required: No

type

The type of security configuration.

Type: String

Valid Values: `saml` | `iamidentitycenter` | `iamfederation`

Required: Yes

Response Syntax

```
{
  "securityConfigDetail": {
    "configVersion": "string",
    "createdDate": number,
    "description": "string",
    "iamFederationOptions": {
      "groupAttribute": "string",
      "userAttribute": "string"
    },
    "iamIdentityCenterOptions": {
      "applicationArn": "string",
      "applicationDescription": "string",
      "applicationName": "string",
      "groupAttribute": "string",
      "instanceArn": "string",
      "userAttribute": "string"
    },
    "id": "string",
    "lastModifiedDate": number,
    "samlOptions": {
      "groupAttribute": "string",
      "metadata": "string",
      "openSearchServerlessEntityId": "string",
      "sessionTimeout": number,
      "userAttribute": "string"
    },
    "type": "string"
  }
}
```

```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[securityConfigDetail](#)

Details about the created security configuration.

Type: [SecurityConfigDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateSecurityPolicy

Creates a security policy to be used by one or more OpenSearch Serverless collections. Security policies provide access to a collection and its OpenSearch Dashboards endpoint from public networks or specific VPC endpoints. They also allow you to secure a collection with a KMS encryption key. For more information, see [Network access for Amazon OpenSearch Serverless](#) and [Encryption at rest for Amazon OpenSearch Serverless](#).

Request Syntax

```
{
  "clientToken": "string",
  "description": "string",
  "name": "string",
  "policy": "string",
  "type": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

description

A description of the policy. Typically used to store information about the permissions defined in the policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

policy

The JSON policy document to use as the content for the new policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20480.

Pattern: `.*[\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]+.*`

Required: Yes

type

The type of security policy.

Type: String

Valid Values: `encryption` | `network`

Required: Yes

Response Syntax

```
{
  "securityPolicyDetail": {
    "createdDate": number,
    "description": "string",
    "lastModifiedDate": number,
    "name": "string",
```

```
"policy": JSON value,  
"policyVersion": "string",  
"type": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

securityPolicyDetail

Details about the created security policy.

Type: [SecurityPolicyDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateVpcEndpoint

Creates an OpenSearch Serverless-managed interface VPC endpoint. For more information, see [Access Amazon OpenSearch Serverless using an interface endpoint](#).

Request Syntax

```
{
  "clientToken": "string",
  "name": "string",
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
  "vpcId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

name

The name of the interface endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: [a-z][a-z0-9-]+

Required: Yes

securityGroupIds

The unique identifiers of the security groups that define the ports, protocols, and sources for inbound traffic that you are authorizing into your endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+\-]+`

Required: No

subnetIds

The ID of one or more subnets from which you'll access OpenSearch Serverless.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `subnet-([0-9a-f]{8}|[0-9a-f]{17})`

Required: Yes

vpcId

The ID of the VPC from which you'll access OpenSearch Serverless.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `vpc-[0-9a-z]*`

Required: Yes

Response Syntax

```
{
```

```
"createVpcEndpointDetail": {  
  "id": "string",  
  "name": "string",  
  "status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createVpcEndpointDetail

Details about the created interface VPC endpoint.

Type: [CreateVpcEndpointDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAccessPolicy

Deletes an OpenSearch Serverless access policy. For more information, see [Data access control for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "name": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[name](#)

The name of the policy to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

[type](#)

The type of policy.

Type: String

Valid Values: data

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCollection

Deletes an OpenSearch Serverless collection. For more information, see [Creating and managing Amazon OpenSearch Serverless collections](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

id

The unique identifier of the collection. For example, 1iu5usc406kd. The ID is part of the collection endpoint. You can also retrieve it using the [ListCollections](#) API.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: [a-z0-9]{3,40}

Required: Yes

Response Syntax

```
{
  "deleteCollectionDetail": {
    "id": "string",
    "name": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deleteCollectionDetail

Details of the deleted collection.

Type: [DeleteCollectionDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

Examples

Delete a collection

The following example deletes a collection.

Sample Request

```
POST / HTTP/1.1
Host: aoss.<region>.<domain>
Accept-Encoding: identity
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.0
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>
X-Amz-Date: <Date>
X-Amz-Target: OpenSearchServerless.DeleteCollection

{
  "id": "07tjusf2h91cunochc",
  "clientToken": "f576fe66-8dd5-11ec-b909-0242ac120004"
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
x-amz-crc32: <Checksum>
Content-Type: application/x-amz-json-1.0
Content-Length: <PayloadSizeBytes>
Date: <Date>

{
  "deleteCollectionDetail":{
```

```
    "id": "07tjusf2h91cunochc",  
    "name": "my-collection",  
    "status": "DELETING"  
  }  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteIndex

Deletes an index from an OpenSearch Serverless collection. Be aware that the index might be configured to conduct automatic semantic enrichment ingestion and search. For more information, see [About automatic semantic enrichment](#).

Request Syntax

```
{
  "id": "string",
  "indexName": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The unique identifier of the collection containing the index to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: Yes

indexName

The name of the index to delete.

Type: String

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteLifecyclePolicy

Deletes an OpenSearch Serverless lifecycle policy. For more information, see [Deleting data lifecycle policies](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "name": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[name](#)

The name of the policy to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

[type](#)

The type of lifecycle policy.

Type: String

Valid Values: retention

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSecurityConfig

Deletes a security configuration for OpenSearch Serverless. For more information, see [SAML authentication for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

id

The security configuration identifier. For SAML the ID will be `saml/<accountId>/<idpProviderName>`. For example, `saml/123456789123/OKTADev`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteSecurityPolicy

Deletes an OpenSearch Serverless security policy.

Request Syntax

```
{  
  "clientToken": "string",  
  "name": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

name

The name of the policy to delete.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

type

The type of policy.

Type: String

Valid Values: encryption | network

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteVpcEndpoint

Deletes an OpenSearch Serverless-managed interface endpoint. For more information, see [Access Amazon OpenSearch Serverless using an interface endpoint](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

id

The VPC endpoint identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `vpce-[0-9a-z]*`

Required: Yes

Response Syntax

```
{
```



```
"deleteVpcEndpointDetail": {  
  "id": "string",  
  "name": "string",  
  "status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

deleteVpcEndpointDetail

Details about the deleted endpoint.

Type: [DeleteVpcEndpointDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccessPolicy

Returns an OpenSearch Serverless access policy. For more information, see [Data access control for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "name": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the access policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: [a-z][a-z0-9-]+

Required: Yes

type

Type type of policy. Currently, the only supported value is data.

Type: String

Valid Values: data

Required: Yes

Response Syntax

```
{
```

```
"accessPolicyDetail": {  
  "createdDate": number,  
  "description": "string",  
  "lastModifiedDate": number,  
  "name": "string",  
  "policy": JSON value,  
  "policyVersion": "string",  
  "type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accessPolicyDetail

Details about the requested access policy.

Type: [AccessPolicyDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccountSettings

Returns account-level settings related to OpenSearch Serverless.

Response Syntax

```
{
  "accountSettingsDetail": {
    "capacityLimits": {
      "maxIndexingCapacityInOCU": number,
      "maxSearchCapacityInOCU": number
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accountSettingsDetail

OpenSearch Serverless-related details for the current account.

Type: [AccountSettingsDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetIndex

Retrieves information about an index in an OpenSearch Serverless collection, including its schema definition. The index might be configured to conduct automatic semantic enrichment ingestion and search. For more information, see [About automatic semantic enrichment](#).

Request Syntax

```
{  
  "id": "string",  
  "indexName": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The unique identifier of the collection containing the index.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: Yes

indexName

The name of the index to retrieve information about.

Type: String

Required: Yes

Response Syntax

```
{
```



```
"indexSchema": JSON value
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[indexSchema](#)

The JSON schema definition for the index, including field mappings and settings.

Type: JSON value

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetPoliciesStats

Returns statistical information about your OpenSearch Serverless access policies, security configurations, and security policies.

Response Syntax

```
{
  "AccessPolicyStats": {
    "DataPolicyCount": number
  },
  "LifecyclePolicyStats": {
    "RetentionPolicyCount": number
  },
  "SecurityConfigStats": {
    "SamlConfigCount": number
  },
  "SecurityPolicyStats": {
    "EncryptionPolicyCount": number,
    "NetworkPolicyCount": number
  },
  "TotalPolicyCount": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AccessPolicyStats](#)

Information about the data access policies in your account.

Type: [AccessPolicyStats](#) object

[LifecyclePolicyStats](#)

Information about the lifecycle policies in your account.

Type: [LifecyclePolicyStats](#) object

SecurityConfigStats

Information about the security configurations in your account.

Type: [SecurityConfigStats](#) object

SecurityPolicyStats

Information about the security policies in your account.

Type: [SecurityPolicyStats](#) object

TotalPolicyCount

The total number of OpenSearch Serverless security policies and configurations in your account.

Type: Long

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSecurityConfig

Returns information about an OpenSearch Serverless security configuration. For more information, see [SAML authentication for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The unique identifier of the security configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

Response Syntax

```
{  
  "securityConfigDetail": {  
    "configVersion": "string",  
    "createdDate": number,  
    "description": "string",  
    "iamFederationOptions": {  
      "groupAttribute": "string",  
      "userAttribute": "string"  
    },  
    "iamIdentityCenterOptions": {  
      "applicationArn": "string",  
      "applicationDescription": "string",  

```

```
    "applicationName": "string",
    "groupAttribute": "string",
    "instanceArn": "string",
    "userAttribute": "string"
  },
  "id": "string",
  "lastModifiedDate": number,
  "samlOptions": {
    "groupAttribute": "string",
    "metadata": "string",
    "openSearchServerlessEntityId": "string",
    "sessionTimeout": number,
    "userAttribute": "string"
  },
  "type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

securityConfigDetail

Details of the requested security configuration.

Type: [SecurityConfigDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSecurityPolicy

Returns information about a configured OpenSearch Serverless security policy. For more information, see [Network access for Amazon OpenSearch Serverless](#) and [Encryption at rest for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "name": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

name

The name of the security policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

type

The type of security policy.

Type: String

Valid Values: `encryption` | `network`

Required: Yes

Response Syntax

```
{
  "securityPolicyDetail": {
    "createdDate": number,
    "description": "string",
    "lastModifiedDate": number,
    "name": "string",
    "policy": JSON value,
    "policyVersion": "string",
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

securityPolicyDetail

Details about the requested security policy.

Type: [SecurityPolicyDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccessPolicies

Returns information about a list of OpenSearch Serverless access policies.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "resource": [ "string" ],  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to get the next page of results. The default is 20.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListAccessPolicies` operation returns a `nextToken`, you can include the returned `nextToken` in subsequent `ListAccessPolicies` operations, which returns results in the next page.

Type: String

Required: No

[resource](#)

Resource filters (can be collections or indexes) that policies can apply to.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: No

type

The type of access policy.

Type: String

Valid Values: data

Required: Yes

Response Syntax

```
{
  "accessPolicySummaries": [
    {
      "createdDate": number,
      "description": "string",
      "lastModifiedDate": number,
      "name": "string",
      "policyVersion": "string",
      "type": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

accessPolicySummaries

Details about the requested access policies.

Type: Array of [AccessPolicySummary](#) objects

nextToken

When `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ListCollections

Lists all OpenSearch Serverless collections. For more information, see [Creating and managing Amazon OpenSearch Serverless collections](#).

Note

Make sure to include an empty request body {} if you don't include any collection filters in the request.

Request Syntax

```
{
  "collectionFilters": {
    "name": "string",
    "status": "string"
  },
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

collectionFilters

A list of filter names and values that you can use for requests.

Type: [CollectionFilters](#) object

Required: No

maxResults

The maximum number of results to return. Default is 20. You can use nextToken to get the next page of results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListCollections` operation returns a `nextToken`, you can include the returned `nextToken` in subsequent `ListCollections` operations, which returns results in the next page.

Type: String

Required: No

Response Syntax

```
{
  "collectionSummaries": [
    {
      "arn": "string",
      "id": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[collectionSummaries](#)

Details about each collection.

Type: Array of [CollectionSummary](#) objects

nextToken

When `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

Examples

Retrieve all collections

The following example lists all collections.

Sample Request

```
POST / HTTP/1.1
Host: aoss.<region>.<domain>
Accept-Encoding: identity
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.0
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>
X-Amz-Date: <Date>
```

```
X-Amz-Target: OpenSearchServerless.ListCollections
{}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
x-amz-crc32: <Checksum>
Content-Type: application/x-amz-json-1.0
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
  "collectionSummaries": [
    {
      "arn": "arn:aws:aoss:us-east-1:123456789012:collection/07tjusf2h91cunochc",
      "id": "07tjusf2h91cunochc",
      "name": "collection-1",
      "status": "ACTIVE"
    },
    {
      "arn": "arn:aws:aoss:us-east-1:123456789012:collection/63hf8klid6904sfcvb",
      "id": "63hf8klid6904sfcvb",
      "name": "collection-2",
      "status": "FAILED"
    },
    {
      "arn": "arn:aws:aoss:us-east-1:123456789012:collection/lo0p4fgjs6fbc87ads",
      "id": "lo0p4fgjs6fbc87ads",
      "name": "collection-3",
      "status": "ACTIVE"
    },
    {
      "arn": "arn:aws:aoss:us-east-1:123456789012:collection/12hd79jbckl6dh4d89",
      "id": "12hd79jbckl6dh4d89",
      "name": "collection-4",
      "status": "DELETING"
    },
    {
      "arn": "arn:aws:aoss:us-east-1:123456789012:collection/17dg8kiybd96dvnd8s",
      "id": "17dg8kiybd96dvnd8s",
      "name": "collection-5",
      "status": "CREATING"
    }
  ]
}
```

```
    ],  
    "nextToken": "MWl1NXVzYzQ0b25q"  
}
```

Retrieve a subset of collections

The following example lists collections with a status of ACTIVE.

Sample Request

```
POST / HTTP/1.1  
Host: aoss.<region>.<domain>  
Accept-Encoding: identity  
Content-Length: <PayloadSizeBytes>  
User-Agent: <UserAgentString>  
Content-Type: application/x-amz-json-1.0  
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,  
    Signature=<Signature>  
X-Amz-Date: <Date>  
X-Amz-Target: OpenSearchServerless.ListCollections  
{  
    "collectionFilters": {  
        "status": "ACTIVE"  
    }  
}
```

Sample Response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: <RequestId>  
x-amz-crc32: <Checksum>  
Content-Type: application/x-amz-json-1.0  
Content-Length: <PayloadSizeBytes>  
Date: <Date>  
{  
    "collectionSummaries": [  
        {  
            "arn": "arn:aws:aoss:us-east-1:123456789012:collection/07tjusf2h91cunochc",  
            "id": "07tjusf2h91cunochc",  
            "name": "collection-1",  
            "status": "ACTIVE"  
        },  
        {
```

```
        "arn": "arn:aws:aoss:us-east-1:123456789012:collection/lo0p4fgjs6fbc87ads",
        "id": "lo0p4fgjs6fbc87ads",
        "name": "collection-3",
        "status": "ACTIVE"
    }
],
"nextToken": "MW11NXVzYzQ0b25q"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListLifecyclePolicies

Returns a list of OpenSearch Serverless lifecycle policies. For more information, see [Viewing data lifecycle policies](#).

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "resources": [ "string" ],  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to get the next page of results. The default is 10.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListLifecyclePolicies` operation returns a `nextToken`, you can include the returned `nextToken` in subsequent `ListLifecyclePolicies` operations, which returns results in the next page.

Type: String

Required: No

[resources](#)

Resource filters that policies can apply to. Currently, the only supported resource type is `index`.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: No

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: Yes

Response Syntax

```
{
  "lifecyclePolicySummaries": [
    {
      "createdDate": number,
      "description": "string",
      "lastModifiedDate": number,
      "name": "string",
      "policyVersion": "string",
      "type": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[lifecyclePolicySummaries](#)

Details about the requested lifecycle policies.

Type: Array of [LifecyclePolicySummary](#) objects

nextToken

When `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

ListSecurityConfigs

Returns information about configured OpenSearch Serverless security configurations. For more information, see [SAML authentication for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use nextToken to get the next page of results. The default is 20.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial ListSecurityConfigs operation returns a nextToken, you can include the returned nextToken in subsequent ListSecurityConfigs operations, which returns results in the next page.

Type: String

Required: No

[type](#)

The type of security configuration.

Type: String

Valid Values: `saml` | `iamidentitycenter` | `iamfederation`

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "securityConfigSummaries": [
    {
      "configVersion": "string",
      "createdDate": number,
      "description": "string",
      "id": "string",
      "lastModifiedDate": number,
      "type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When `nextToken` is returned, there are more results available. The value of `nextToken` is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

securityConfigSummaries

Details about the security configurations in your account.

Type: Array of [SecurityConfigSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListSecurityPolicies

Returns information about configured OpenSearch Serverless security policies.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string",  
  "resource": [ "string" ],  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to get the next page of results. The default is 20.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListSecurityPolicies` operation returns a `nextToken`, you can include the returned `nextToken` in subsequent `ListSecurityPolicies` operations, which returns results in the next page.

Type: String

Required: No

[resource](#)

Resource filters (can be collection or indexes) that policies can apply to.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 1000 items.

Required: No

type

The type of policy.

Type: String

Valid Values: encryption | network

Required: Yes

Response Syntax

```
{
  "nextToken": "string",
  "securityPolicySummaries": [
    {
      "createdDate": number,
      "description": "string",
      "lastModifiedDate": number,
      "name": "string",
      "policyVersion": "string",
      "type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

[securityPolicySummaries](#)

Details about the security policies in your account.

Type: Array of [SecurityPolicySummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns the tags for an OpenSearch Serverless resource. For more information, see [Tagging Amazon OpenSearch Serverless collections](#).

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[resourceArn](#)

The Amazon Resource Name (ARN) of the resource. The resource must be active (not in the DELETING state), and must be owned by the account ID included in the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

Response Syntax

```
{  
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[tags](#)

The tags associated with the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListVpcEndpoints

Returns the OpenSearch Serverless-managed interface VPC endpoints associated with the current account. For more information, see [Access Amazon OpenSearch Serverless using an interface endpoint](#).

Request Syntax

```
{
  "maxResults": number,
  "nextToken": "string",
  "vpcEndpointFilters": {
    "status": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

An optional parameter that specifies the maximum number of results to return. You can use `nextToken` to get the next page of results. The default is 20.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

If your initial `ListVpcEndpoints` operation returns a `nextToken`, you can include the returned `nextToken` in subsequent `ListVpcEndpoints` operations, which returns results in the next page.

Type: String

Required: No

vpcEndpointFilters

Filter the results according to the current status of the VPC endpoint. Possible statuses are CREATING, DELETING, UPDATING, ACTIVE, and FAILED.

Type: [VpcEndpointFilters](#) object

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "vpcEndpointSummaries": [
    {
      "id": "string",
      "name": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

When nextToken is returned, there are more results available. The value of nextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

vpcEndpointSummaries

Details about each VPC endpoint, including the name and current status.

Type: Array of [VpcEndpointSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Associates tags with an OpenSearch Serverless resource. For more information, see [Tagging Amazon OpenSearch Serverless collections](#).

Request Syntax

```
{
  "resourceArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[resourceArn](#)

The Amazon Resource Name (ARN) of the resource. The resource must be active (not in the DELETING state), and must be owned by the account ID included in the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

[tags](#)

A list of tags (key-value pairs) to add to the resource. All tag keys in the request must be unique.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes a tag or set of tags from an OpenSearch Serverless resource. For more information, see [Tagging Amazon OpenSearch Serverless collections](#).

Request Syntax

```
{  
  "resourceArn": "string",  
  "tagKeys": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource to remove tags from. The resource must be active (not in the DELETING state), and must be owned by the account ID included in the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Required: Yes

tagKeys

The tag or set of tags to remove from the resource. All tag keys in the request must be unique.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAccessPolicy

Updates an OpenSearch Serverless access policy. For more information, see [Data access control for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "description": "string",  
  "name": "string",  
  "policy": "string",  
  "policyVersion": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[description](#)

A description of the policy. Typically used to store information about the permissions defined in the policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

policy

The JSON policy document to use as the content for the policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20480.

Pattern: `. * [ \ u 0 0 0 9 \ u 0 0 0 A \ u 0 0 0 D \ u 0 0 2 0 - \ u 0 0 7 E \ u 0 0 A 1 - \ u 0 0 F F ] + . *`

Required: No

policyVersion

The version of the policy being updated.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: `( [ 0 - 9 a - z A - Z + / ] { 4 } ) * ( ( [ 0 - 9 a - z A - Z + / ] { 2 } == ) | ( [ 0 - 9 a - z A - Z + / ] { 3 } = ) ) ?`

Required: Yes

type

The type of policy.

Type: String

Valid Values: `data`

Required: Yes

Response Syntax

```
{
  "accessPolicyDetail": {
    "createdDate": number,
    "description": "string",
    "lastModifiedDate": number,
    "name": "string",
    "policy": JSON value,
    "policyVersion": "string",
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[accessPolicyDetail](#)

Details about the updated access policy.

Type: [AccessPolicyDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAccountSettings

Update the OpenSearch Serverless settings for the current AWS account. For more information, see [Managing capacity limits for Amazon OpenSearch Serverless](#).

Request Syntax

```
{
  "capacityLimits": {
    "maxIndexingCapacityInOCU": number,
    "maxSearchCapacityInOCU": number
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[capacityLimits](#)

The maximum capacity limits for all OpenSearch Serverless collections, in OpenSearch Compute Units (OCUs). These limits are used to scale your collections based on the current workload. For more information, see [Managing capacity limits for Amazon OpenSearch Serverless](#).

Type: [CapacityLimits](#) object

Required: No

Response Syntax

```
{
  "accountSettingsDetail": {
    "capacityLimits": {
      "maxIndexingCapacityInOCU": number,
      "maxSearchCapacityInOCU": number
    }
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[accountSettingsDetail](#)

OpenSearch Serverless-related settings for the current AWS account.

Type: [AccountSettingsDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCollection

Updates an OpenSearch Serverless collection.

Request Syntax

```
{  
  "clientToken": "string",  
  "description": "string",  
  "id": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

description

A description of the collection.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

id

The unique identifier of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: Yes

Response Syntax

```
{
  "updateCollectionDetail": {
    "arn": "string",
    "createdDate": number,
    "description": "string",
    "id": "string",
    "lastModifiedDate": number,
    "name": "string",
    "status": "string",
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[updateCollectionDetail](#)

Details about the updated collection.

Type: [UpdateCollectionDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateIndex

Updates an existing index in an OpenSearch Serverless collection. This operation allows you to modify the index schema, including adding new fields or changing field mappings. You can also enable automatic semantic enrichment ingestion and search. For more information, see [About automatic semantic enrichment](#).

Request Syntax

```
{
  "id": "string",
  "indexName": "string",
  "indexSchema": JSON value
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

id

The unique identifier of the collection containing the index to update.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: Yes

indexName

The name of the index to update.

Type: String

Required: Yes

indexSchema

The updated JSON schema definition for the index, including field mappings and settings.

Type: JSON value

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateLifecyclePolicy

Updates an OpenSearch Serverless access policy. For more information, see [Updating data lifecycle policies](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "description": "string",  
  "name": "string",  
  "policy": "string",  
  "policyVersion": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[description](#)

A description of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

policy

The JSON policy document to use as the content for the lifecycle policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20480.

Pattern: `. * [\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF] + . *`

Required: No

policyVersion

The version of the policy being updated.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: `([0-9a-zA-Z+/{4})*((([0-9a-zA-Z+/{2}]==)|([0-9a-zA-Z+/{3}=)))?`

Required: Yes

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: Yes

Response Syntax

```
{
  "lifecyclePolicyDetail": {
    "createdDate": number,
    "description": "string",
    "lastModifiedDate": number,
    "name": "string",
    "policy": JSON value,
    "policyVersion": "string",
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[lifecyclePolicyDetail](#)

Details about the updated lifecycle policy.

Type: [LifecyclePolicyDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSecurityConfig

Updates a security configuration for OpenSearch Serverless. For more information, see [SAML authentication for Amazon OpenSearch Serverless](#).

Request Syntax

```
{
  "clientToken": "string",
  "configVersion": "string",
  "description": "string",
  "iamFederationOptions": {
    "groupAttribute": "string",
    "userAttribute": "string"
  },
  "iamIdentityCenterOptionsUpdates": {
    "groupAttribute": "string",
    "userAttribute": "string"
  },
  "id": "string",
  "samlOptions": {
    "groupAttribute": "string",
    "metadata": "string",
    "openSearchServerlessEntityId": "string",
    "sessionTimeout": number,
    "userAttribute": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

configVersion

The version of the security configuration to be updated. You can find the most recent version of a security configuration using the `GetSecurityPolicy` command.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/]{4}`)*((`[0-9a-zA-Z+/]{2}`==)|(`[0-9a-zA-Z+/]{3}`=))?

Required: Yes

description

A description of the security configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

iamFederationOptions

Describes IAM federation options in the form of a key-value map for updating an existing security configuration. Use this field to modify IAM federation settings for the security configuration.

Type: [IamFederationConfigOptions](#) object

Required: No

iamIdentityCenterOptionsUpdates

Describes IAM Identity Center options in the form of a key-value map.

Type: [UpdateIamIdentityCenterConfigOptions](#) object

Required: No

id

The security configuration identifier. For SAML the ID will be `saml/<accountId>/<idpProviderName>`. For example, `saml/123456789123/0KTADev`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

samlOptions

SAML options in in the form of a key-value map.

Type: [SamlConfigOptions](#) object

Required: No

Response Syntax

```
{
  "securityConfigDetail": {
    "configVersion": "string",
    "createdDate": number,
    "description": "string",
    "iamFederationOptions": {
      "groupAttribute": "string",
      "userAttribute": "string"
    },
    "iamIdentityCenterOptions": {
      "applicationArn": "string",
      "applicationDescription": "string",
      "applicationName": "string",
      "groupAttribute": "string",
      "instanceArn": "string",
      "userAttribute": "string"
    },
    "id": "string",
    "lastModifiedDate": number,
    "samlOptions": {
      "groupAttribute": "string",
      "metadata": "string",
      "openSearchServerlessEntityId": "string",
      "sessionTimeout": number,
      "userAttribute": "string"
    },
    "type": "string"
  }
```



```
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[securityConfigDetail](#)

Details about the updated security configuration.

Type: [SecurityConfigDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateSecurityPolicy

Updates an OpenSearch Serverless security policy. For more information, see [Network access for Amazon OpenSearch Serverless](#) and [Encryption at rest for Amazon OpenSearch Serverless](#).

Request Syntax

```
{  
  "clientToken": "string",  
  "description": "string",  
  "name": "string",  
  "policy": "string",  
  "policyVersion": "string",  
  "type": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[description](#)

A description of the policy. Typically used to store information about the permissions defined in the policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

policy

The JSON policy document to use as the content for the new policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 20480.

Pattern: `. * [ \ u 0 0 0 9 \ u 0 0 0 A \ u 0 0 0 D \ u 0 0 2 0 - \ u 0 0 7 E \ u 0 0 A 1 - \ u 0 0 F F ] + . *`

Required: No

policyVersion

The version of the policy being updated.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: `( [ 0 - 9 a - z A - Z + / ] { 4 } ) * ( ( [ 0 - 9 a - z A - Z + / ] { 2 } == ) | ( [ 0 - 9 a - z A - Z + / ] { 3 } = ) ) ?`

Required: Yes

type

The type of access policy.

Type: String

Valid Values: `encryption` | `network`

Required: Yes

Response Syntax

```
{
  "securityPolicyDetail": {
    "createdDate": number,
    "description": "string",
    "lastModifiedDate": number,
    "name": "string",
    "policy": JSON value,
    "policyVersion": "string",
    "type": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

securityPolicyDetail

Details about the updated security policy.

Type: [SecurityPolicyDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerErrorException

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ResourceNotFoundException

Thrown when accessing or deleting a resource that does not exist.

HTTP Status Code: 400

ServiceQuotaExceededException

Thrown when you attempt to create more resources than the service allows based on service quotas.

HTTP Status Code: 400

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateVpcEndpoint

Updates an OpenSearch Serverless-managed interface endpoint. For more information, see [Access Amazon OpenSearch Serverless using an interface endpoint](#).

Request Syntax

```
{  
  "addSecurityGroupIds": [ "string" ],  
  "addSubnetIds": [ "string" ],  
  "clientToken": "string",  
  "id": "string",  
  "removeSecurityGroupIds": [ "string" ],  
  "removeSubnetIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[addSecurityGroupIds](#)

The unique identifiers of the security groups to add to the endpoint. Security groups define the ports, protocols, and sources for inbound traffic that you are authorizing into your endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+\-]+`

Required: No

[addSubnetIds](#)

The ID of one or more subnets to add to the endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: subnet-([0-9a-f]{8}|[0-9a-f]{17})

Required: No

clientToken

Unique, case-sensitive identifier to ensure idempotency of the request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

id

The unique identifier of the interface endpoint to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: vpce-[0-9a-z]*

Required: Yes

removeSecurityGroupIds

The unique identifiers of the security groups to remove from the endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: [\w+\-]+

Required: No

[removeSubnetIds](#)

The unique identifiers of the subnets to remove from the endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: subnet-([0-9a-f]{8}|[0-9a-f]{17})

Required: No

Response Syntax

```
{
  "UpdateVpcEndpointDetail": {
    "id": "string",
    "lastModifiedDate": number,
    "name": "string",
    "securityGroupIds": [ "string" ],
    "status": "string",
    "subnetIds": [ "string" ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[UpdateVpcEndpointDetail](#)

Details about the updated VPC endpoint.

Type: [UpdateVpcEndpointDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

When creating a resource, thrown when a resource with the same name already exists or is being created. When deleting a resource, thrown when the resource is not in the ACTIVE or FAILED state.

HTTP Status Code: 400

InternalServerError

Thrown when an error internal to the service occurs while processing a request.

HTTP Status Code: 500

ValidationException

Thrown when the HTTP request contains invalid input or is missing required input.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The OpenSearch Service Serverless API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessPolicyDetail](#)
- [AccessPolicyStats](#)
- [AccessPolicySummary](#)
- [AccountSettingsDetail](#)
- [CapacityLimits](#)
- [CollectionDetail](#)
- [CollectionErrorDetail](#)
- [CollectionFilters](#)
- [CollectionSummary](#)
- [CreateCollectionDetail](#)
- [CreateIamIdentityCenterConfigOptions](#)
- [CreateVpcEndpointDetail](#)
- [DeleteCollectionDetail](#)
- [DeleteVpcEndpointDetail](#)
- [EffectiveLifecyclePolicyDetail](#)
- [EffectiveLifecyclePolicyErrorDetail](#)
- [IamFederationConfigOptions](#)
- [IamIdentityCenterConfigOptions](#)
- [LifecyclePolicyDetail](#)
- [LifecyclePolicyErrorDetail](#)

- [LifecyclePolicyIdentifier](#)
- [LifecyclePolicyResourceIdentifier](#)
- [LifecyclePolicyStats](#)
- [LifecyclePolicySummary](#)
- [SamlConfigOptions](#)
- [SecurityConfigDetail](#)
- [SecurityConfigStats](#)
- [SecurityConfigSummary](#)
- [SecurityPolicyDetail](#)
- [SecurityPolicyStats](#)
- [SecurityPolicySummary](#)
- [Tag](#)
- [UpdateCollectionDetail](#)
- [UpdateIamIdentityCenterConfigOptions](#)
- [UpdateVpcEndpointDetail](#)
- [VpcEndpointDetail](#)
- [VpcEndpointErrorDetail](#)
- [VpcEndpointFilters](#)
- [VpcEndpointSummary](#)

AccessPolicyDetail

Details about an OpenSearch Serverless access policy.

Contents

createdDate

The date the policy was created.

Type: Long

Required: No

description

The description of the policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

lastModifiedDate

The timestamp of when the policy was last modified.

Type: Long

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

policy

The JSON policy document without any whitespaces.

Type: JSON value

Required: No

policyVersion

The version of the policy.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/-]{4}`)*((`[0-9a-zA-Z+/-]{2}=`)|(`[0-9a-zA-Z+/-]{3}=`))?

Required: No

type

The type of access policy.

Type: String

Valid Values: `data`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccessPolicyStats

Statistics for an OpenSearch Serverless access policy.

Contents

DataPolicyCount

The number of data access policies in the current account.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccessPolicySummary

A summary of the data access policy.

Contents

createdDate

The Epoch time when the access policy was created.

Type: Long

Required: No

description

The description of the access policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

lastModifiedDate

The date and time when the collection was last modified.

Type: Long

Required: No

name

The name of the access policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

policyVersion

The version of the policy.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/]{4}`)*((`[0-9a-zA-Z+/]{2}=`)|(`[0-9a-zA-Z+/]{3}=`))?

Required: No

type

The type of access policy. Currently, the only available type is `data`.

Type: String

Valid Values: `data`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AccountSettingsDetail

OpenSearch Serverless-related information for the current account.

Contents

capacityLimits

The maximum capacity limits for all OpenSearch Serverless collections, in OpenSearch Compute Units (OCUs). These limits are used to scale your collections based on the current workload. For more information, see [Managing capacity limits for Amazon OpenSearch Serverless](#).

Type: [CapacityLimits](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CapacityLimits

The maximum capacity limits for all OpenSearch Serverless collections, in OpenSearch Compute Units (OCUs). These limits are used to scale your collections based on the current workload. For more information, see [Managing capacity limits for Amazon OpenSearch Serverless](#).

Contents

maxIndexingCapacityInOCU

The maximum indexing capacity for collections.

Type: Integer

Valid Range: Minimum value of 2.

Required: No

maxSearchCapacityInOCU

The maximum search capacity for collections.

Type: Integer

Valid Range: Minimum value of 2.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CollectionDetail

Details about each OpenSearch Serverless collection, including the collection endpoint and the OpenSearch Dashboards endpoint.

Contents

arn

The Amazon Resource Name (ARN) of the collection.

Type: String

Required: No

collectionEndpoint

Collection-specific endpoint used to submit index, search, and data upload requests to an OpenSearch Serverless collection.

Type: String

Required: No

createdDate

The Epoch time when the collection was created.

Type: Long

Required: No

dashboardEndpoint

Collection-specific endpoint used to access OpenSearch Dashboards.

Type: String

Required: No

description

A description of the collection.

Type: String

Required: No

failureCode

A failure code associated with the request.

Type: String

Required: No

failureMessage

A message associated with the failure code.

Type: String

Required: No

id

A unique identifier for the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: No

kmsKeyArn

The ARN of the AWS KMS key used to encrypt the collection.

Type: String

Required: No

lastModifiedDate

The date and time when the collection was last modified.

Type: Long

Required: No

name

The name of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

standbyReplicas

Details about an OpenSearch Serverless collection.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

status

The current status of the collection.

Type: String

Valid Values: CREATING | DELETING | ACTIVE | FAILED

Required: No

type

The type of collection.

Type: String

Valid Values: SEARCH | TIMESERIES | VECTORSEARCH

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CollectionErrorDetail

Error information for an OpenSearch Serverless request.

Contents

errorCode

The error code for the request. For example, `NOT_FOUND`.

Type: String

Required: No

errorMessage

A description of the error. For example, `The specified Collection is not found.`

Type: String

Required: No

id

If the request contains collection IDs, the response includes the IDs provided in the request.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: No

name

If the request contains collection names, the response includes the names provided in the request.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CollectionFilters

A list of filter keys that you can use for LIST, UPDATE, and DELETE requests to OpenSearch Serverless collections.

Contents

name

The name of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

status

The current status of the collection.

Type: String

Valid Values: CREATING | DELETING | ACTIVE | FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CollectionSummary

Details about each OpenSearch Serverless collection.

Contents

arn

The Amazon Resource Name (ARN) of the collection.

Type: String

Required: No

id

The unique identifier of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: No

name

The name of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

status

The current status of the collection.

Type: String

Valid Values: CREATING | DELETING | ACTIVE | FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateCollectionDetail

Details about the created OpenSearch Serverless collection.

Contents

arn

The Amazon Resource Name (ARN) of the collection.

Type: String

Required: No

createdDate

The Epoch time when the collection was created.

Type: Long

Required: No

description

A description of the collection.

Type: String

Required: No

id

The unique identifier of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: No

kmsKeyArn

The Amazon Resource Name (ARN) of the KMS key with which to encrypt the collection.

Type: String

Required: No

lastModifiedDate

The date and time when the collection was last modified.

Type: Long

Required: No

name

The name of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

standbyReplicas

Creates details about an OpenSearch Serverless collection.

Type: String

Valid Values: ENABLED | DISABLED

Required: No

status

The current status of the collection.

Type: String

Valid Values: CREATING | DELETING | ACTIVE | FAILED

Required: No

type

The type of collection.

Type: String

Valid Values: SEARCH | TIMESERIES | VECTORSEARCH

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreteIamIdentityCenterConfigOptions

Describes IAM Identity Center options for creating an OpenSearch Serverless security configuration in the form of a key-value map.

Contents

instanceArn

The ARN of the IAM Identity Center instance used to integrate with OpenSearch Serverless.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: Yes

groupAttribute

The group attribute for this IAM Identity Center integration. Defaults to `GroupId`.

Type: String

Valid Values: `GroupId` | `GroupName`

Required: No

userAttribute

The user attribute for this IAM Identity Center integration. Defaults to `UserId`.

Type: String

Valid Values: `UserId` | `UserName` | `Email`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateVpcEndpointDetail

Creation details for an OpenSearch Serverless-managed interface endpoint. For more information, see [Access Amazon OpenSearch Serverless using an interface endpoint](#).

Contents

id

The unique identifier of the endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `vpce-[0-9a-z]*`

Required: No

name

The name of the endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

status

The current status in the endpoint creation process.

Type: String

Valid Values: `PENDING` | `DELETING` | `ACTIVE` | `FAILED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeleteCollectionDetail

Details about a deleted OpenSearch Serverless collection.

Contents

id

The unique identifier of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: No

name

The name of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

status

The current status of the collection.

Type: String

Valid Values: CREATING | DELETING | ACTIVE | FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeleteVpcEndpointDetail

Deletion details for an OpenSearch Serverless-managed interface endpoint.

Contents

id

The unique identifier of the endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `vpce-[0-9a-z]*`

Required: No

name

The name of the endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

status

The current status of the endpoint deletion process.

Type: String

Valid Values: `PENDING` | `DELETING` | `ACTIVE` | `FAILED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EffectiveLifecyclePolicyDetail

Error information for an OpenSearch Serverless request.

Contents

noMinRetentionPeriod

The minimum number of index retention days set. That is an optional param that will return as `true` if the minimum number of days or hours is not set to a index resource.

Type: Boolean

Required: No

policyName

The name of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

resource

The name of the OpenSearch Serverless index resource.

Type: String

Required: No

resourceType

The type of OpenSearch Serverless resource. Currently, the only supported resource is `index`.

Type: String

Valid Values: `index`

Required: No

retentionPeriod

The minimum number of index retention in days or hours. This is an optional parameter that will return only if it's set.

Type: String

Required: No

type

The type of lifecycle policy.

Type: String

Valid Values: retention

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EffectiveLifecyclePolicyErrorDetail

Error information for an OpenSearch Serverless request.

Contents

errorCode

The error code for the request.

Type: String

Required: No

errorMessage

A description of the error. For example, The specified Index resource is not found.

Type: String

Required: No

resource

The name of OpenSearch Serverless index resource.

Type: String

Required: No

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IamFederationConfigOptions

Describes IAM federation options for an OpenSearch Serverless security configuration in the form of a key-value map. These options define how OpenSearch Serverless integrates with external identity providers using federation.

Contents

groupAttribute

The group attribute for this IAM federation integration. This attribute is used to map identity provider groups to OpenSearch Serverless permissions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z][A-Za-z0-9_.:/=\-@]*`

Required: No

userAttribute

The user attribute for this IAM federation integration. This attribute is used to identify users in the federated authentication process.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[A-Za-z][A-Za-z0-9_.:/=\-@]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

IamIdentityCenterConfigOptions

Describes IAM Identity Center options for an OpenSearch Serverless security configuration in the form of a key-value map.

Contents

applicationArn

The ARN of the IAM Identity Center application used to integrate with OpenSearch Serverless.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso::\d{12}:application/(sso)?ins-[a-zA-Z0-9-]{16}/apl-[a-zA-Z0-9]{16}`

Required: No

applicationDescription

The description of the IAM Identity Center application used to integrate with OpenSearch Serverless.

Type: String

Required: No

applicationName

The name of the IAM Identity Center application used to integrate with OpenSearch Serverless.

Type: String

Required: No

groupAttribute

The group attribute for this IAM Identity Center integration. Defaults to GroupId.

Type: String

Valid Values: `GroupId` | `GroupName`

Required: No

instanceArn

The ARN of the IAM Identity Center instance used to integrate with OpenSearch Serverless.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 1224.

Pattern: `arn:(aws|aws-us-gov|aws-cn|aws-iso|aws-iso-b):sso:::instance/(sso)?ins-[a-zA-Z0-9-]{16}`

Required: No

userAttribute

The user attribute for this IAM Identity Center integration. Defaults to `UserId`

Type: String

Valid Values: `UserId` | `UserName` | `Email`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyDetail

Details about an OpenSearch Serverless lifecycle policy.

Contents

createdDate

The date the lifecycle policy was created.

Type: Long

Required: No

description

The description of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

lastModifiedDate

The timestamp of when the lifecycle policy was last modified.

Type: Long

Required: No

name

The name of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

policy

The JSON policy document without any whitespaces.

Type: JSON value

Required: No

policyVersion

The version of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/-]{4}`)*((`[0-9a-zA-Z+/-]{2}=`)|(`[0-9a-zA-Z+/-]{3}=`))?

Required: No

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyErrorDetail

Error information for an OpenSearch Serverless request.

Contents

errorCode

The error code for the request. For example, NOT_FOUND.

Type: String

Required: No

errorMessage

A description of the error. For example, The specified Lifecycle Policy is not found.

Type: String

Required: No

name

The name of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: [a-z][a-z0-9-]+

Required: No

type

The type of lifecycle policy.

Type: String

Valid Values: retention

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyIdentifier

The unique identifiers of policy types and policy names.

Contents

name

The name of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: Yes

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyResourceIdentifier

The unique identifiers of policy types and resource names.

Contents

resource

The name of the OpenSearch Serverless index resource.

Type: String

Pattern: `index/[a-z][a-z0-9-]{3,32}/([a-z;0-9&$%][+.\~=\-_a-z;0-9&$%]*)`

Required: Yes

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicyStats

Statistics for an OpenSearch Serverless lifecycle policy.

Contents

RetentionPolicyCount

The number of retention lifecycle policies in the current account.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LifecyclePolicySummary

A summary of the lifecycle policy.

Contents

createdDate

The Epoch time when the lifecycle policy was created.

Type: Long

Required: No

description

The description of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

lastModifiedDate

The date and time when the lifecycle policy was last modified.

Type: Long

Required: No

name

The name of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

policyVersion

The version of the lifecycle policy.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/]{4}`)*((`[0-9a-zA-Z+/]{2}`==)|(`[0-9a-zA-Z+/]{3}`=))?

Required: No

type

The type of lifecycle policy.

Type: String

Valid Values: `retention`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SamlConfigOptions

Describes SAML options for an OpenSearch Serverless security configuration in the form of a key-value map.

Contents

metadata

The XML IdP metadata file generated from your identity provider.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 51200.

Pattern: `.*[\u0009\u000A\u000D\u0020-\u007E\u00A1-\u00FF]+.*`

Required: Yes

groupAttribute

The group attribute for this SAML integration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `.*[\w+=, .@-]+.*`

Required: No

openSearchServerlessEntityId

Custom entity ID attribute to override the default entity ID for this SAML integration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: `aws:opensearch:[0-9]{12}:*.*`

Required: No

sessionTimeout

The session timeout, in minutes. Default is 60 minutes (12 hours).

Type: Integer

Valid Range: Minimum value of 5. Maximum value of 720.

Required: No

userAttribute

A user attribute for this SAML integration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `.*[\w+=, .@-]+.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityConfigDetail

Details about a security configuration for OpenSearch Serverless.

Contents

configVersion

The version of the security configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: ([0-9a-zA-Z+/{4})*((([0-9a-zA-Z+/{2}=) | ([0-9a-zA-Z+/{3}=))?)

Required: No

createdDate

The date the configuration was created.

Type: Long

Required: No

description

The description of the security configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

iamFederationOptions

Describes IAM federation options in the form of a key-value map. Contains configuration details about how OpenSearch Serverless integrates with external identity providers through federation.

Type: [IamFederationConfigOptions](#) object

Required: No

iamIdentityCenterOptions

Describes IAM Identity Center options in the form of a key-value map.

Type: [iamIdentityCenterConfigOptions](#) object

Required: No

id

The unique identifier of the security configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

lastModifiedDate

The timestamp of when the configuration was last modified.

Type: Long

Required: No

samlOptions

SAML options for the security configuration in the form of a key-value map.

Type: [SamlConfigOptions](#) object

Required: No

type

The type of security configuration.

Type: String

Valid Values: `saml` | `iamidentitycenter` | `iamfederation`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityConfigStats

Statistics for an OpenSearch Serverless security configuration.

Contents

SamlConfigCount

The number of security configurations in the current account.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityConfigSummary

A summary of a security configuration for OpenSearch Serverless.

Contents

configVersion

The version of the security configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/-]{4}`)*((`[0-9a-zA-Z+/-]{2}=`)|(`[0-9a-zA-Z+/-]{3}=`))?

Required: No

createdDate

The Epoch time when the security configuration was created.

Type: Long

Required: No

description

The description of the security configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Required: No

id

The unique identifier of the security configuration.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

lastModifiedDate

The timestamp of when the configuration was last modified.

Type: Long

Required: No

type

The type of security configuration.

Type: String

Valid Values: `saml` | `iamidentitycenter` | `iamfederation`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityPolicyDetail

Details about an OpenSearch Serverless security policy.

Contents

createdDate

The date the policy was created.

Type: Long

Required: No

description

The description of the security policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

lastModifiedDate

The timestamp of when the policy was last modified.

Type: Long

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

policy

The JSON policy document without any whitespaces.

Type: JSON value

Required: No

policyVersion

The version of the policy.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/-]{4}`)*((`[0-9a-zA-Z+/-]{2}=`)|(`[0-9a-zA-Z+/-]{3}=`))?

Required: No

type

The type of security policy.

Type: String

Valid Values: `encryption` | `network`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityPolicyStats

Statistics for an OpenSearch Serverless security policy.

Contents

EncryptionPolicyCount

The number of encryption policies in the current account.

Type: Long

Required: No

NetworkPolicyCount

The number of network policies in the current account.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SecurityPolicySummary

A summary of a security policy for OpenSearch Serverless.

Contents

createdDate

The date the policy was created.

Type: Long

Required: No

description

The description of the security policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 1000.

Required: No

lastModifiedDate

The timestamp of when the policy was last modified.

Type: Long

Required: No

name

The name of the policy.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

policyVersion

The version of the policy.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 36.

Pattern: (`[0-9a-zA-Z+/]{4}`)*((`[0-9a-zA-Z+/]{2}=`)|(`[0-9a-zA-Z+/]{3}=`))?

Required: No

type

The type of security policy.

Type: String

Valid Values: `encryption` | `network`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A map of key-value pairs associated to an OpenSearch Serverless resource.

Contents

key

The key to use in the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

value

The value of the tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateCollectionDetail

Details about an updated OpenSearch Serverless collection.

Contents

arn

The Amazon Resource Name (ARN) of the collection.

Type: String

Required: No

createdDate

The date and time when the collection was created.

Type: Long

Required: No

description

The description of the collection.

Type: String

Required: No

id

The unique identifier of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `[a-z0-9]{3,40}`

Required: No

lastModifiedDate

The date and time when the collection was last modified.

Type: Long

Required: No

name

The name of the collection.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

status

The current status of the collection.

Type: String

Valid Values: CREATING | DELETING | ACTIVE | FAILED

Required: No

type

The collection type.

Type: String

Valid Values: SEARCH | TIMESERIES | VECTORSEARCH

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateIamIdentityCenterConfigOptions

Describes IAM Identity Center options for updating an OpenSearch Serverless security configuration in the form of a key-value map.

Contents

groupAttribute

The group attribute for this IAM Identity Center integration. Defaults to `GroupId`.

Type: String

Valid Values: `GroupId` | `GroupName`

Required: No

userAttribute

The user attribute for this IAM Identity Center integration. Defaults to `UserId`.

Type: String

Valid Values: `UserId` | `UserName` | `Email`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateVpcEndpointDetail

Update details for an OpenSearch Serverless-managed interface endpoint.

Contents

id

The unique identifier of the endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `vpce-[0-9a-z]*`

Required: No

lastModifiedDate

The timestamp of when the endpoint was last modified.

Type: Long

Required: No

name

The name of the endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

securityGroupIds

The unique identifiers of the security groups that define the ports, protocols, and sources for inbound traffic that you are authorizing into your endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+\-]+`

Required: No

status

The current status of the endpoint update process.

Type: String

Valid Values: PENDING | DELETING | ACTIVE | FAILED

Required: No

subnetIds

The ID of the subnets from which you access OpenSearch Serverless.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `subnet-( [0-9a-f]{8} | [0-9a-f]{17} )`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcEndpointDetail

Details about an OpenSearch Serverless-managed interface endpoint.

Contents

createdDate

The date the endpoint was created.

Type: Long

Required: No

failureCode

A failure code associated with the request.

Type: String

Required: No

failureMessage

A message associated with the failure code.

Type: String

Required: No

id

The unique identifier of the endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `vpce-[0-9a-z]*`

Required: No

name

The name of the endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

securityGroupIds

The unique identifiers of the security groups that define the ports, protocols, and sources for inbound traffic that you are authorizing into your endpoint.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `[\w+\-]+`

Required: No

status

The current status of the endpoint.

Type: String

Valid Values: PENDING | DELETING | ACTIVE | FAILED

Required: No

subnetIds

The ID of the subnets from which you access OpenSearch Serverless.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 6 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `subnet-([0-9a-f]{8}|[0-9a-f]{17})`

Required: No

vpcId

The ID of the VPC from which you access OpenSearch Serverless.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: vpc-[0-9a-z]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcEndpointErrorDetail

Error information for a failed BatchGetVpcEndpoint request.

Contents

errorCode

The error code for the failed request.

Type: String

Required: No

errorMessage

An error message describing the reason for the failure.

Type: String

Required: No

id

The unique identifier of the VPC endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: vpce-[0-9a-z]*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcEndpointFilters

Filter the results of a `ListVpcEndpoints` request.

Contents

status

The current status of the endpoint.

Type: String

Valid Values: PENDING | DELETING | ACTIVE | FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

VpcEndpointSummary

The VPC endpoint object.

Contents

id

The unique identifier of the endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `vpce-[0-9a-z]*`

Required: No

name

The name of the endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 32.

Pattern: `[a-z][a-z0-9-]+`

Required: No

status

The current status of the endpoint.

Type: String

Valid Values: `PENDING` | `DELETING` | `ACTIVE` | `FAILED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400