



API Reference

AWS PCS



API Version 2023-02-10

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS PCS: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
CreateCluster	3
Request Syntax	3
Request Parameters	4
Response Syntax	6
Response Elements	7
Errors	7
See Also	9
CreateComputeNodeGroup	10
Request Syntax	10
Request Parameters	11
Response Syntax	14
Response Elements	15
Errors	15
See Also	17
CreateQueue	19
Request Syntax	19
Request Parameters	19
Response Syntax	21
Response Elements	21
Errors	21
See Also	23
DeleteCluster	25
Request Syntax	25
Request Parameters	25
Response Elements	26
Errors	26
See Also	27
DeleteComputeNodeGroup	29
Request Syntax	29
Request Parameters	29
Response Elements	30
Errors	30

See Also	31
DeleteQueue	33
Request Syntax	33
Request Parameters	33
Response Elements	34
Errors	34
See Also	35
GetCluster	37
Request Syntax	37
Request Parameters	37
Response Syntax	37
Response Elements	38
Errors	39
See Also	40
GetComputeNodeGroup	42
Request Syntax	42
Request Parameters	42
Response Syntax	42
Response Elements	44
Errors	44
See Also	45
GetQueue	47
Request Syntax	47
Request Parameters	47
Response Syntax	47
Response Elements	48
Errors	48
See Also	50
ListClusters	51
Request Syntax	51
Request Parameters	51
Response Syntax	52
Response Elements	52
Errors	52
See Also	54
ListComputeNodeGroups	55

Request Syntax	55
Request Parameters	55
Response Syntax	56
Response Elements	56
Errors	57
See Also	58
ListQueues	60
Request Syntax	60
Request Parameters	60
Response Syntax	61
Response Elements	61
Errors	62
See Also	63
ListTagsForResource	65
Request Syntax	65
Request Parameters	65
Response Syntax	65
Response Elements	65
Errors	66
See Also	66
RegisterComputeNodeGroupInstance	68
Request Syntax	68
Request Parameters	68
Response Syntax	69
Response Elements	69
Errors	69
See Also	70
TagResource	71
Request Syntax	71
Request Parameters	71
Response Elements	72
Errors	72
See Also	72
UntagResource	74
Request Syntax	74
Request Parameters	74

Response Elements	75
Errors	75
See Also	75
UpdateComputeNodeGroup	76
Request Syntax	76
Request Parameters	76
Response Syntax	79
Response Elements	80
Errors	81
See Also	82
UpdateQueue	84
Request Syntax	84
Request Parameters	84
Response Syntax	85
Response Elements	86
Errors	86
See Also	88
Data Types	89
Cluster	91
Contents	91
See Also	93
ClusterSlurmConfiguration	94
Contents	94
See Also	94
ClusterSlurmConfigurationRequest	95
Contents	95
See Also	95
ClusterSummary	96
Contents	96
See Also	97
ComputeNodeGroup	98
Contents	98
See Also	101
ComputeNodeGroupConfiguration	103
Contents	103
See Also	103

ComputeNodeGroupSlurmConfiguration	104
Contents	104
See Also	104
ComputeNodeGroupSlurmConfigurationRequest	105
Contents	105
See Also	105
ComputeNodeGroupSummary	106
Contents	106
See Also	107
CustomLaunchTemplate	108
Contents	108
See Also	108
Endpoint	109
Contents	109
See Also	110
ErrorInfo	111
Contents	111
See Also	111
InstanceConfig	112
Contents	112
See Also	112
Networking	113
Contents	113
See Also	114
NetworkingRequest	115
Contents	115
See Also	115
Queue	117
Contents	117
See Also	119
QueueSummary	120
Contents	120
See Also	121
ScalingConfiguration	122
Contents	122
See Also	122

ScalingConfigurationRequest	123
Contents	123
See Also	123
Scheduler	124
Contents	124
See Also	124
SchedulerRequest	125
Contents	125
See Also	125
SlurmAuthKey	126
Contents	126
See Also	126
SlurmCustomSetting	127
Contents	127
See Also	127
SpotOptions	128
Contents	128
See Also	128
UpdateComputeNodeGroupSlurmConfigurationRequest	129
Contents	129
See Also	129
ValidationExceptionField	130
Contents	130
See Also	130
Common Parameters	131
Common Errors	134

Welcome

AWS Parallel Computing Service (AWS PCS) is a managed service that makes it easier for you to run and scale your high performance computing (HPC) workloads, and build scientific and engineering models on AWS using Slurm. For more information, see the [AWS Parallel Computing Service User Guide](#).

This reference describes the actions and data types of the service management API. You can use the AWS SDKs to call the API actions in software, or use the AWS Command Line Interface (AWS CLI) to call the API actions manually. These API actions manage the service through an AWS account.

The API actions operate on AWS PCS resources. A *resource* is an entity in AWS that you can work with. AWS services create resources when you use the features of the service. Examples of AWS PCS resources include clusters, compute node groups, and queues. For more information about resources in AWS, see [Resource](#) in the *AWS Resource Explorer User Guide*.

An AWS PCS *compute node* is an Amazon EC2 instance. You don't launch compute nodes directly. AWS PCS uses configuration information that you provide to launch compute nodes in your AWS account. You receive billing charges for your running compute nodes. AWS PCS automatically terminates your compute nodes when you delete the AWS PCS resources related to those compute nodes.

This document was last published on September 26, 2024.

Actions

The following actions are supported:

- [CreateCluster](#)
- [CreateComputeNodeGroup](#)
- [CreateQueue](#)
- [DeleteCluster](#)
- [DeleteComputeNodeGroup](#)
- [DeleteQueue](#)
- [GetCluster](#)
- [GetComputeNodeGroup](#)
- [GetQueue](#)
- [ListClusters](#)
- [ListComputeNodeGroups](#)
- [ListQueues](#)
- [ListTagsForResource](#)
- [RegisterComputeNodeGroupInstance](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateComputeNodeGroup](#)
- [UpdateQueue](#)

CreateCluster

Creates a cluster in your account. AWS PCS creates the cluster controller in a service-owned account. The cluster controller communicates with the cluster resources in your account. The subnets and security groups for the cluster must already exist before you use this API action.

Note

It takes time for AWS PCS to create the cluster. The cluster is in a `Creating` state until it is ready to use. There can only be 1 cluster in a `Creating` state per AWS Region per AWS account. `CreateCluster` fails with a `ServiceQuotaExceededException` if there is already a cluster in a `Creating` state.

Request Syntax

```
{
  "clientToken": "string",
  "clusterName": "string",
  "networking": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ]
  },
  "scheduler": {
    "type": "string",
    "version": "string"
  },
  "size": "string",
  "slurmConfiguration": {
    "scaleDownIdleTimeInSeconds": number,
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  },
  "tags": {
    "string" : "string"
  }
}
```

```
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

clusterName

A name to identify the cluster. Example: MyCluster

Type: String

Length Constraints: Minimum length of 1. Maximum length of 40.

Pattern: (?!pcs_)^(?![A-Za-z0-9]{10}\$)[A-Za-z][A-Za-z0-9-]+

Required: Yes

networking

The networking configuration used to set up the cluster's control plane.

Type: [NetworkingRequest](#) object

Required: Yes

scheduler

The cluster management and job scheduling software associated with the cluster.

Type: [SchedulerRequest](#) object

Required: Yes

size

A value that determines the maximum number of compute nodes in the cluster and the maximum number of jobs (active and queued).

- SMALL: 32 compute nodes and 256 jobs
- MEDIUM: 512 compute nodes and 8192 jobs
- LARGE: 2048 compute nodes and 16,384 jobs

Type: String

Valid Values: SMALL | MEDIUM | LARGE

Required: Yes

slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [ClusterSlurmConfigurationRequest](#) object

Required: No

tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
{
  "cluster": {
    "arn": "string",
    "createdAt": "string",
    "endpoints": [
      {
        "port": "string",
        "privateIpAddress": "string",
        "publicIpAddress": "string",
        "type": "string"
      }
    ],
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "id": "string",
    "modifiedAt": "string",
    "name": "string",
    "networking": {
      "securityGroupIds": [ "string" ],
      "subnetIds": [ "string" ]
    },
    "scheduler": {
      "type": "string",
      "version": "string"
    },
    "size": "string",
    "slurmConfiguration": {
      "authKey": {
        "secretArn": "string",
        "secretVersion": "string"
      },
      "scaleDownIdleTimeInSeconds": number,
      "slurmCustomSettings": [
        {
          "parameterName": "string",
          "parameterValue": "string"
        }
      ]
    }
  }
}
```

```
    ]
  },
  "status": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

cluster

The cluster resource.

Type: [Cluster](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ServiceQuotaExceededException

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.

- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateComputeNodeGroup

Creates a managed set of compute nodes. You associate a compute node group with a cluster through 1 or more AWS PCS queues or as part of the login fleet. A compute node group includes the definition of the compute properties and lifecycle management. AWS PCS uses the information you provide to this API action to launch compute nodes in your account. You can only specify subnets in the same Amazon VPC as your cluster. You receive billing charges for the compute nodes that AWS PCS launches in your account. You must already have a launch template before you call this API. For more information, see [Launch an instance from a launch template](#) in the *Amazon Elastic Compute Cloud User Guide for Linux Instances*.

Request Syntax

```
{
  "amiId": "string",
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupName": "string",
  "customLaunchTemplate": {
    "id": "string",
    "version": "string"
  },
  "iamInstanceProfileArn": "string",
  "instanceConfigs": [
    {
      "instanceType": "string"
    }
  ],
  "purchaseOption": "string",
  "scalingConfiguration": {
    "maxInstanceCount": number,
    "minInstanceCount": number
  },
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  }
},
```

```
"spotOptions": {
  "allocationStrategy": "string"
},
"subnetIds": [ "string" ],
"tags": {
  "string" : "string"
}
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[amild](#)

The ID of the Amazon Machine Image (AMI) that AWS PCS uses to launch compute nodes (Amazon EC2 instances). If you don't provide this value, AWS PCS uses the AMI ID specified in the custom launch template.

Type: String

Pattern: ami-[a-z0-9]+

Required: No

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

[clusterIdentifier](#)

The name or ID of the cluster to create a compute node group in.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

computeGroupName

A name to identify the cluster. Example: MyCluster

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: (?!pcs_)^(?![A-Za-z0-9]{10}\$)[A-Za-z][A-Za-z0-9-]+

Required: Yes

customLaunchTemplate

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

Type: [CustomLaunchTemplate](#) object

Required: Yes

iamInstanceProfileArn

The Amazon Resource Name (ARN) of the IAM instance profile used to pass an IAM role when launching EC2 instances. The role contained in your instance profile must have the `pcs:RegisterComputeNodeGroupInstance` permission. The resource identifier of the ARN must start with `AWSPCS` or it must have `/aws-pcs/` in its path.

Examples

- `arn:aws:iam::111122223333:instance-profile/AWSPCS-example-role-1`
- `arn:aws:iam::111122223333:instance-profile/aws-pcs/example-role-2`

Type: String

Pattern: arn:aws([a-zA-Z-]{0,10})?:iam::[0-9]{12}:instance-profile/.{1,128}

Required: Yes

instanceConfigs

A list of EC2 instance configurations that AWS PCS can provision in the compute node group.

Type: Array of [InstanceConfig](#) objects

Required: Yes

[purchaseOption](#)

Specifies how EC2 instances are purchased on your behalf. AWS PCS supports On-Demand and Spot instances. For more information, see [Instance purchasing options](#) in the *Amazon Elastic Compute Cloud User Guide*. If you don't provide this option, it defaults to On-Demand.

Type: String

Valid Values: ONDEMAND | SPOT

Required: No

[scalingConfiguration](#)

Specifies the boundaries of the compute node group auto scaling.

Type: [ScalingConfigurationRequest](#) object

Required: Yes

[slurmConfiguration](#)

Additional options related to the Slurm scheduler.

Type: [ComputeNodeGroupSlurmConfigurationRequest](#) object

Required: No

[spotOptions](#)

Additional configuration when you specify SPOT as the `purchaseOption` for the `CreateComputeNodeGroup` API action.

Type: [SpotOptions](#) object

Required: No

[subnetIds](#)

The list of subnet IDs where the compute node group launches instances. Subnets must be in the same VPC as the cluster.

Type: Array of strings

Required: Yes

tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
{
  "computeNodeGroup": {
    "amiId": "string",
    "arn": "string",
    "clusterId": "string",
    "createdAt": "string",
    "customLaunchTemplate": {
      "id": "string",
      "version": "string"
    },
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "iamInstanceProfileArn": "string",
    "id": "string",
    "instanceConfigs": [
      {
        "instanceType": "string"
      }
    ],
    "modifiedAt": "string",
```

```
"name": "string",
"purchaseOption": "string",
"scalingConfiguration": {
  "maxInstanceCount": number,
  "minInstanceCount": number
},
"slurmConfiguration": {
  "slurmCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ]
},
"spotOptions": {
  "allocationStrategy": "string"
},
"status": "string",
"subnetIds": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[computeNodeGroup](#)

A compute node group associated with a cluster.

Type: [ComputeNodeGroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ServiceQuotaExceededException

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateQueue

Creates a job queue. You must associate 1 or more compute node groups with the queue. You can associate 1 compute node group with multiple queues.

Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupConfigurations": [
    {
      "computeNodeId": "string"
    }
  ],
  "queueName": "string",
  "tags": {
    "string" : "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

clusterIdentifier

The name or ID of the cluster for which to create a queue.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})`

Required: Yes

computeNodeGroupConfigurations

The list of compute node group configurations to associate with the queue. Queues assign jobs to associated compute node groups.

Type: Array of [ComputeNodeGroupConfiguration](#) objects

Required: No

queueName

A name to identify the queue.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: `(?!pcs_)^(?![A-Za-z0-9]{10}$)[A-Za-z][A-Za-z0-9-]+`

Required: Yes

tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
{
  "queue": {
    "arn": "string",
    "clusterId": "string",
    "computeNodeGroupConfigurations": [
      {
        "computeNodeGroupId": "string"
      }
    ],
    "createdAt": "string",
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "id": "string",
    "modifiedAt": "string",
    "name": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

queue

A queue resource.

Type: [Queue](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ServiceQuotaExceededException

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteCluster

Deletes a cluster and all its linked resources. You must delete all queues and compute node groups associated with the cluster before you can delete the cluster.

Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

[clusterIdentifier](#)

The name or ID of the cluster to delete.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteComputeNodeGroup

Deletes a compute node group. You must delete all queues associated with the compute node group first.

Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

clusterIdentifier

The name or ID of the cluster of the compute node group.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

computeNodeGroupIdentifier

The name or ID of the compute node group to delete.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,25})

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.

- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteQueue

Deletes a job queue. If the compute node group associated with this queue isn't associated with any other queues, AWS PCS terminates all the compute nodes for this queue.

Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "queueIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

clusterIdentifier

The name or ID of the cluster of the queue.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

queueIdentifier

The name or ID of the queue to delete.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,25})

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.

- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetCluster

Returns detailed information about a running cluster in your account. This API action provides networking information, endpoint information for communication with the scheduler, and provisioning status.

Request Syntax

```
{
  "clusterIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clusterIdentifier

The name or ID of the cluster of the queue.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

Response Syntax

```
{
  "cluster": {
    "arn": "string",
    "createdAt": "string",
    "endpoints": [
      {
        "port": "string",
        "privateIpAddress": "string",
        "publicIpAddress": "string",

```

```

        "type": "string"
    }
],
"errorInfo": [
    {
        "code": "string",
        "message": "string"
    }
],
"id": "string",
"modifiedAt": "string",
"name": "string",
"networking": {
    "securityGroupIds": [ "string" ],
    "subnetIds": [ "string" ]
},
"scheduler": {
    "type": "string",
    "version": "string"
},
"size": "string",
"slurmConfiguration": {
    "authKey": {
        "secretArn": "string",
        "secretVersion": "string"
    },
    "scaleDownIdleTimeInSeconds": number,
    "slurmCustomSettings": [
        {
            "parameterName": "string",
            "parameterValue": "string"
        }
    ]
},
"status": "string"
}
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

cluster

The cluster resource.

Type: [Cluster](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetComputeNodeGroup

Returns detailed information about a compute node group. This API action provides networking information, EC2 instance type, compute node group status, and scheduler (such as Slurm) configuration.

Request Syntax

```
{
  "clusterIdentifier": "string",
  "computeNodeGroupIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clusterIdentifier

The name or ID of the cluster.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

computeNodeGroupIdentifier

The name or ID of the compute node group.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,25})

Required: Yes

Response Syntax

```
{
  "computeNodeGroup": {
```

```
"amiId": "string",
"arn": "string",
"clusterId": "string",
"createdAt": "string",
"customLaunchTemplate": {
  "id": "string",
  "version": "string"
},
"errorInfo": [
  {
    "code": "string",
    "message": "string"
  }
],
"iamInstanceProfileArn": "string",
"id": "string",
"instanceConfigs": [
  {
    "instanceType": "string"
  }
],
"modifiedAt": "string",
"name": "string",
"purchaseOption": "string",
"scalingConfiguration": {
  "maxInstanceCount": number,
  "minInstanceCount": number
},
"slurmConfiguration": {
  "slurmCustomSettings": [
    {
      "parameterName": "string",
      "parameterValue": "string"
    }
  ]
},
"spotOptions": {
  "allocationStrategy": "string"
},
"status": "string",
"subnetIds": [ "string" ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

computeNodeGroup

A compute node group associated with a cluster.

Type: [ComputeNodeGroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetQueue

Returns detailed information about a queue. The information includes the compute node groups that the queue uses to schedule jobs.

Request Syntax

```
{
  "clusterIdentifier": "string",
  "queueIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clusterIdentifier

The name or ID of the cluster of the queue.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

queueIdentifier

The name or ID of the queue.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,25})

Required: Yes

Response Syntax

```
{
  "queue": {
```

```
"arn": "string",
"clusterId": "string",
"computeNodeGroupConfigurations": [
  {
    "computeNodeGroupId": "string"
  }
],
"createdAt": "string",
"errorInfo": [
  {
    "code": "string",
    "message": "string"
  }
],
"id": "string",
"modifiedAt": "string",
"name": "string",
"status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

queue

A queue resource.

Type: [Queue](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListClusters

Returns a list of running clusters in your account.

Request Syntax

```
{  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

[maxResults](#)

The maximum number of results that are returned per call. You can use `nextToken` to obtain further pages of results. The default is 10 results, and the maximum allowed page size is 100 results. A value of 0 uses the default.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

[nextToken](#)

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Required: No

Response Syntax

```
{
  "clusters": [
    {
      "arn": "string",
      "createdAt": "string",
      "id": "string",
      "modifiedAt": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clusters

The list of clusters.

Type: Array of [ClusterSummary](#) objects

nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListComputeNodeGroups

Returns a list of all compute node groups associated with a cluster.

Request Syntax

```
{  
  "clusterIdentifier": "string",  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clusterIdentifier

The name or ID of the cluster to list compute node groups for.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

maxResults

The maximum number of results that are returned per call. You can use `nextToken` to obtain further pages of results. The default is 10 results, and the maximum allowed page size is 100 results. A value of 0 uses the default.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the

returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Required: No

Response Syntax

```
{
  "computeNodeGroups": [
    {
      "arn": "string",
      "clusterId": "string",
      "createdAt": "string",
      "id": "string",
      "modifiedAt": "string",
      "name": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

computeNodeGroups

The list of compute node groups for the cluster.

Type: Array of [ComputeNodeGroupSummary](#) objects

nextToken

The value of `nextToken` is a unique pagination token for each page of results returned.

If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination

token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in `ACTIVE` status.
- A cluster to delete is in an unstable state. For example, because it still has `ACTIVE` node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListQueues

Returns a list of all queues associated with a cluster.

Request Syntax

```
{
  "clusterIdentifier": "string",
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clusterIdentifier

The name or ID of the cluster to list queues for.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

maxResults

The maximum number of results that are returned per call. You can use `nextToken` to obtain further pages of results. The default is 10 results, and the maximum allowed page size is 100 results. A value of 0 uses the default.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the

returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "queues": [
    {
      "arn": "string",
      "clusterId": "string",
      "createdAt": "string",
      "id": "string",
      "modifiedAt": "string",
      "name": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

The value of `nextToken` is a unique pagination token for each page of results returned. If `nextToken` is returned, there are more results available. Make the call again using the returned token to retrieve the next page. Keep all other arguments unchanged. Each pagination token expires after 24 hours. Using an expired pagination token returns an HTTP 400 `InvalidToken` error.

Type: String

queues

The list of queues associated with the cluster.

Type: Array of [QueueSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Returns a list of all tags on an AWS PCS resource.

Request Syntax

```
{  
  "resourceArn": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource for which to list tags.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws*:pcs:.*:[0-9]{12}:.*/[a-z0-9_\-]+`

Required: Yes

Response Syntax

```
{  
  "tags": {  
    "string" : "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterComputeNodeGroupInstance

Important

This API action isn't intended for you to use.

AWS PCS uses this API action to register the compute nodes it launches in your account.

Request Syntax

```
{
  "bootstrapId": "string",
  "clusterIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

bootstrapId

The client-generated token to allow for retries.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1000.

Pattern: `[\S]+`

Required: Yes

clusterIdentifier

The name or ID of the cluster to register the compute node group instance in.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})`

Required: Yes

Response Syntax

```
{
  "endpoints": [
    {
      "port": "string",
      "privateIpAddress": "string",
      "publicIpAddress": "string",
      "type": "string"
    }
  ],
  "nodeID": "string",
  "sharedSecret": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

endpoints

The list of endpoints available for interaction with the scheduler.

Type: Array of [Endpoint](#) objects

nodeID

The scheduler node ID for this instance.

Type: String

sharedSecret

For the Slurm scheduler, this is the shared Munge key the scheduler uses to authenticate compute node group instances.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds or edits tags on an AWS PCS resource. Each tag consists of a tag key and a tag value. The tag key and tag value are case-sensitive strings. The tag value can be an empty (null) string. To add a tag, specify a new tag key and a tag value. To edit a tag, specify an existing tag key and a new tag value.

Request Syntax

```
{
  "resourceArn": "string",
  "tags": {
    "string" : "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws*:pcs:.*:[0-9]{12}:.*/[a-z0-9_\-]+`

Required: Yes

tags

1 or more tags added to the resource. Each tag consists of a tag key and tag value. The tag value is optional and can be an empty string.

Type: String to string map

Map Entries: Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Deletes tags from an AWS PCS resource. To delete a tag, specify the tag key and the Amazon Resource Name (ARN) of the AWS PCS resource.

Request Syntax

```
{
  "resourceArn": "string",
  "tagKeys": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1011.

Pattern: `arn:aws*:pcs:.*:[0-9]{12}:.*/[a-z0-9_\-]+`

Required: Yes

tagKeys

1 or more tag keys to remove from the resource. Specify only tag keys and not tag values.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateComputeNodeGroup

Updates a compute node group. You can update many of the fields related to your compute node group including the configurations for networking, compute nodes, and settings specific to your scheduler (such as Slurm).

Request Syntax

```
{
  "amiId": "string",
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupIdentifier": "string",
  "customLaunchTemplate": {
    "id": "string",
    "version": "string"
  },
  "iamInstanceProfileArn": "string",
  "purchaseOption": "string",
  "scalingConfiguration": {
    "maxInstanceCount": number,
    "minInstanceCount": number
  },
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  },
  "spotOptions": {
    "allocationStrategy": "string"
  },
  "subnetIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

amiId

The ID of the Amazon Machine Image (AMI) that AWS PCS uses to launch instances. If not provided, AWS PCS uses the AMI ID specified in the custom launch template.

Type: String

Pattern: `ami-[a-z0-9]+`

Required: No

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

clusterIdentifier

The name or ID of the cluster of the compute node group.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})`

Required: Yes

computeNodeGroupIdentifier

The name or ID of the compute node group.

Type: String

Pattern: `(pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,25})`

Required: Yes

[customLaunchTemplate](#)

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

Type: [CustomLaunchTemplate](#) object

Required: No

[iamInstanceProfileArn](#)

The Amazon Resource Name (ARN) of the IAM instance profile used to pass an IAM role when launching EC2 instances. The role contained in your instance profile must have the `pcs:RegisterComputeNodeGroupInstance` permission. The resource identifier of the ARN must start with `AWSPCS` or it must have `/aws-pcs/` in its path.

Examples

- `arn:aws:iam::111122223333:instance-profile/AWSPCS-example-role-1`
- `arn:aws:iam::111122223333:instance-profile/aws-pcs/example-role-2`

Type: String

Pattern: `arn:aws([a-zA-Z-]{0,10})?:iam::[0-9]{12}:instance-profile/.{1,128}`

Required: No

[purchaseOption](#)

Specifies how EC2 instances are purchased on your behalf. AWS PCS supports On-Demand and Spot instances. For more information, see [Instance purchasing options](#) in the *Amazon Elastic Compute Cloud User Guide*. If you don't provide this option, it defaults to On-Demand.

Type: String

Valid Values: ONDEMAND | SPOT

Required: No

[scalingConfiguration](#)

Specifies the boundaries of the compute node group auto scaling.

Type: [ScalingConfigurationRequest](#) object

Required: No

slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [UpdateComputeNodeGroupSlurmConfigurationRequest](#) object

Required: No

spotOptions

Additional configuration when you specify SPOT as the purchaseOption for the CreateComputeNodeGroup API action.

Type: [SpotOptions](#) object

Required: No

subnetIds

The list of subnet IDs where the compute node group provisions instances. The subnets must be in the same VPC as the cluster.

Type: Array of strings

Required: No

Response Syntax

```
{
  "computeNodeGroup": {
    "amiId": "string",
    "arn": "string",
    "clusterId": "string",
    "createdAt": "string",
    "customLaunchTemplate": {
      "id": "string",
      "version": "string"
    },
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ]
  }
}
```

```
    }
  ],
  "iamInstanceProfileArn": "string",
  "id": "string",
  "instanceConfigs": [
    {
      "instanceType": "string"
    }
  ],
  "modifiedAt": "string",
  "name": "string",
  "purchaseOption": "string",
  "scalingConfiguration": {
    "maxInstanceCount": number,
    "minInstanceCount": number
  },
  "slurmConfiguration": {
    "slurmCustomSettings": [
      {
        "parameterName": "string",
        "parameterValue": "string"
      }
    ]
  },
  "spotOptions": {
    "allocationStrategy": "string"
  },
  "status": "string",
  "subnetIds": [ "string" ]
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

computeNodeGroup

A compute node group associated with a cluster.

Type: [ComputeNodeGroup](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerError

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ServiceQuotaExceededException

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateQueue

Updates the compute node group configuration of a queue. Use this API to change the compute node groups that the queue can send jobs to.

Request Syntax

```
{
  "clientToken": "string",
  "clusterIdentifier": "string",
  "computeNodeGroupConfigurations": [
    {
      "computeNodeId": "string"
    }
  ],
  "queueIdentifier": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, the subsequent retries with the same client token return the result from the original successful request and they have no additional effect. If you don't specify a client token, the AWS CLI and SDK automatically generate 1 for you.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 100.

Required: No

clusterIdentifier

The name or ID of the cluster of the queue.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,40})

Required: Yes

computeNodeGroupConfigurations

The list of compute node group configurations to associate with the queue. Queues assign jobs to associated compute node groups.

Type: Array of [ComputeNodeGroupConfiguration](#) objects

Required: No

queueIdentifier

The name or ID of the queue.

Type: String

Pattern: (pcs_[a-zA-Z0-9]+|[A-Za-z][A-Za-z0-9-]{1,25})

Required: Yes

Response Syntax

```
{
  "queue": {
    "arn": "string",
    "clusterId": "string",
    "computeNodeGroupConfigurations": [
      {
        "computeNodeGroupId": "string"
      }
    ],
    "createdAt": "string",
    "errorInfo": [
      {
        "code": "string",
        "message": "string"
      }
    ],
    "id": "string",
```

```
  "modifiedAt": "string",  
  "name": "string",  
  "status": "string"  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

queue

A queue resource.

Type: [Queue](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

You don't have permission to perform the action.

Examples

- The launch template instance profile doesn't pass `iam:PassRole` verification.
- There is a mismatch between the account ID and cluster ID.
- The cluster ID doesn't exist.
- The EC2 instance isn't present.

HTTP Status Code: 400

ConflictException

Your request has conflicting operations. This can occur if you're trying to perform more than 1 operation on the same resource at the same time.

Examples

- A cluster with the same name already exists.
- A cluster isn't in ACTIVE status.
- A cluster to delete is in an unstable state. For example, because it still has ACTIVE node groups or queues.
- A queue already exists in a cluster.

HTTP Status Code: 400

InternalServerErrorException

AWS PCS can't process your request right now. Try again later.

HTTP Status Code: 500

ResourceNotFoundException

The requested resource can't be found. The cluster, node group, or queue you're attempting to get, update, list, or delete doesn't exist.

Examples

HTTP Status Code: 400

ServiceQuotaExceededException

You exceeded your service quota. Service quotas, also referred to as limits, are the maximum number of service resources or operations for your AWS account. To learn how to increase your service quota, see [Requesting a quota increase](#) in the *Service Quotas User Guide*

Examples

- The max number of clusters or queues has been reached for the account.
- The max number of compute node groups has been reached for the associated cluster.
- The total of maxInstances across all compute node groups has been reached for associated cluster.

HTTP Status Code: 400

ThrottlingException

Your request exceeded a request rate quota. Check the resource's request rate quota and try again.

HTTP Status Code: 400

ValidationException

The request isn't valid.

Examples

- Your request contains malformed JSON or unsupported characters.
- The scheduler version isn't supported.
- There are networking related errors, such as network validation failure.
- AMI type is CUSTOM and the launch template doesn't define the AMI ID, or the AMI type is AL2 and the launch template defines the AMI.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Parallel Computing Service API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Cluster](#)
- [ClusterSlurmConfiguration](#)
- [ClusterSlurmConfigurationRequest](#)
- [ClusterSummary](#)
- [ComputeNodeGroup](#)
- [ComputeNodeGroupConfiguration](#)
- [ComputeNodeGroupSlurmConfiguration](#)
- [ComputeNodeGroupSlurmConfigurationRequest](#)
- [ComputeNodeGroupSummary](#)
- [CustomLaunchTemplate](#)
- [Endpoint](#)
- [ErrorInfo](#)
- [InstanceConfig](#)
- [Networking](#)
- [NetworkingRequest](#)
- [Queue](#)
- [QueueSummary](#)
- [ScalingConfiguration](#)
- [ScalingConfigurationRequest](#)
- [Scheduler](#)

- [SchedulerRequest](#)
- [SlurmAuthKey](#)
- [SlurmCustomSetting](#)
- [SpotOptions](#)
- [UpdateComputeNodeGroupSlurmConfigurationRequest](#)
- [ValidationExceptionField](#)

Cluster

The cluster resource and configuration.

Contents

arn

The unique Amazon Resource Name (ARN) of the cluster.

Type: String

Required: Yes

createdAt

The date and time the resource was created.

Type: Timestamp

Required: Yes

id

The generated unique ID of the cluster.

Type: String

Required: Yes

modifiedAt

The date and time the resource was modified.

Type: Timestamp

Required: Yes

name

The name that identifies the cluster.

Type: String

Required: Yes

networking

The networking configuration for the cluster's control plane.

Type: [Networking](#) object

Required: Yes

scheduler

The cluster management and job scheduling software associated with the cluster.

Type: [Scheduler](#) object

Required: Yes

size

The size of the cluster.

- SMALL: 32 compute nodes and 256 jobs
- MEDIUM: 512 compute nodes and 8192 jobs
- LARGE: 2048 compute nodes and 16,384 jobs

Type: String

Valid Values: SMALL | MEDIUM | LARGE

Required: Yes

status

The provisioning status of the cluster.

Note

The provisioning status doesn't indicate the overall health of the cluster.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED

Required: Yes

endpoints

The list of endpoints available for interaction with the scheduler.

Type: Array of [Endpoint](#) objects

Required: No

errorInfo

The list of errors that occurred during cluster provisioning.

Type: Array of [ErrorInfo](#) objects

Required: No

slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [ClusterSlurmConfiguration](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClusterSlurmConfiguration

Additional options related to the Slurm scheduler.

Contents

authKey

The shared Slurm key for authentication, also known as the **cluster secret**.

Type: [SlurmAuthKey](#) object

Required: No

scaleDownIdleTimeInSeconds

The time before an idle node is scaled down.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

slurmCustomSettings

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClusterSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

Contents

scaleDownIdleTimeInSeconds

The time before an idle node is scaled down.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

slurmCustomSettings

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ClusterSummary

The object returned by the `ListClusters` API action.

Contents

arn

The unique Amazon Resource Name (ARN) of the cluster.

Type: String

Required: Yes

createdAt

The date and time the resource was created.

Type: Timestamp

Required: Yes

id

The generated unique ID of the cluster.

Type: String

Required: Yes

modifiedAt

The date and time the resource was modified.

Type: Timestamp

Required: Yes

name

The name that identifies the cluster.

Type: String

Required: Yes

status

The provisioning status of the cluster.

Note

The provisioning status doesn't indicate the overall health of the cluster.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeNodeGroup

A compute node group associated with a cluster.

Contents

arn

The unique Amazon Resource Name (ARN) of the compute node group.

Type: String

Required: Yes

clusterId

The ID of the cluster of the compute node group.

Type: String

Required: Yes

createdAt

The date and time the resource was created.

Type: Timestamp

Required: Yes

customLaunchTemplate

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

Type: [CustomLaunchTemplate](#) object

Required: Yes

iamInstanceProfileArn

The Amazon Resource Name (ARN) of the IAM instance profile used to pass an IAM role when launching EC2 instances. The role contained in your instance profile must have the `pcs:RegisterComputeNodeGroupInstance` permission. The resource identifier of the ARN must start with `AWSPCS` or it must have `/aws-pcs/` in its path.

Examples

- `arn:aws:iam::111122223333:instance-profile/AWSPCS-example-role-1`
- `arn:aws:iam::111122223333:instance-profile/aws-pcs/example-role-2`

Type: String

Pattern: `arn:aws([a-zA-Z-]{0,10})?:iam::[0-9]{12}:instance-profile/.{1,128}`

Required: Yes

id

The generated unique ID of the compute node group.

Type: String

Required: Yes

instanceConfigs

A list of EC2 instance configurations that AWS PCS can provision in the compute node group.

Type: Array of [InstanceConfig](#) objects

Required: Yes

modifiedAt

The date and time the resource was modified.

Type: Timestamp

Required: Yes

name

The name that identifies the compute node group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: `(?!pcs_)^(?![A-Za-z0-9]{10}$)[A-Za-z][A-Za-z0-9-]+`

Required: Yes

scalingConfiguration

Specifies the boundaries of the compute node group auto scaling.

Type: [ScalingConfiguration](#) object

Required: Yes

status

The provisioning status of the compute node group.

Note

The provisioning status doesn't indicate the overall health of the compute node group.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED | DELETED

Required: Yes

subnetIds

The list of subnet IDs where instances are provisioned by the compute node group. The subnets must be in the same VPC as the cluster.

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: subnet-\w{8,17}

Required: Yes

amiId

The ID of the Amazon Machine Image (AMI) that AWS PCS uses to launch instances. If not provided, AWS PCS uses the AMI ID specified in the custom launch template.

Type: String

Pattern: ami-[a-z0-9]+

Required: No

errorInfo

The list of errors that occurred during compute node group provisioning.

Type: Array of [ErrorInfo](#) objects

Required: No

purchaseOption

Specifies how EC2 instances are purchased on your behalf. AWS PCS supports On-Demand and Spot instances. For more information, see [Instance purchasing options](#) in the *Amazon Elastic Compute Cloud User Guide*. If you don't provide this option, it defaults to On-Demand.

Type: String

Valid Values: ONDEMAND | SPOT

Required: No

slurmConfiguration

Additional options related to the Slurm scheduler.

Type: [ComputeNodeGroupSlurmConfiguration](#) object

Required: No

spotOptions

Additional configuration when you specify SPOT as the purchaseOption for the CreateComputeNodeGroup API action.

Type: [SpotOptions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeNodeGroupConfiguration

The compute node group configuration for a queue.

Contents

`computeNodeGroupId`

The compute node group ID for the compute node group configuration.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeNodeGroupSlurmConfiguration

Additional options related to the Slurm scheduler.

Contents

`slurmCustomSettings`

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeNodeGroupSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

Contents

slurmCustomSettings

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ComputeNodeGroupSummary

The object returned by the `ListComputeNodeGroups` API action.

Contents

arn

The unique Amazon Resource Name (ARN) of the compute node group.

Type: String

Required: Yes

clusterId

The ID of the cluster of the compute node group.

Type: String

Required: Yes

createdAt

The date and time the resource was created.

Type: Timestamp

Required: Yes

id

The generated unique ID of the compute node group.

Type: String

Required: Yes

modifiedAt

The date and time the resource was modified.

Type: Timestamp

Required: Yes

name

The name that identifies the compute node group.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: (?!pcs_)^(?![A-Za-z0-9]{10}\$)[A-Za-z][A-Za-z0-9-]+

Required: Yes

status

The provisioning status of the compute node group.

Note

The provisioning status doesn't indicate the overall health of the compute node group.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED | DELETED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CustomLaunchTemplate

An Amazon EC2 launch template AWS PCS uses to launch compute nodes.

Contents

id

The ID of the EC2 launch template to use to provision instances.

Example: 1t-xxxx

Type: String

Required: Yes

version

The version of the EC2 launch template to use to provision instances.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Endpoint

An endpoint available for interaction with the scheduler.

Contents

port

The endpoint's connection port number.

Example: 1234

Type: String

Required: Yes

privateIpAddress

The endpoint's private IP address.

Example: 2.2.2.2

Type: String

Required: Yes

type

Indicates the type of endpoint running at the specific IP address.

Type: String

Valid Values: SLURMCTLD | SLURMDBD

Required: Yes

publicIpAddress

The endpoint's public IP address.

Example: 1.1.1.1

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ErrorInfo

An error that occurred during resource creation.

Contents

code

The short-form error code.

Type: String

Required: No

message

The detailed error information.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

InstanceConfig

An EC2 instance configuration AWS PCS uses to launch compute nodes.

Contents

instanceType

The EC2 instance type that AWS PCS can provision in the compute node group.

Example: `t2.xlarge`

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Networking

The networking configuration for the cluster's control plane.

Contents

securityGroupIds

The list of security group IDs associated with the Elastic Network Interface (ENI) created in subnets.

The following rules are required:

- Inbound rule 1
 - Protocol: All
 - Ports: All
 - Source: Self
- Outbound rule 1
 - Protocol: All
 - Ports: All
 - Destination: 0.0.0.0/0 (IPv4)
- Outbound rule 2
 - Protocol: All
 - Ports: All
 - Destination: Self

Type: Array of strings

Pattern: `sg-\w{8,17}`

Required: No

subnetIds

The ID of the subnet where AWS PCS creates an Elastic Network Interface (ENI) to enable communication between managed controllers and AWS PCS resources. The subnet must have an available IP address, cannot reside in AWS Outposts, AWS Wavelength, or an AWS Local Zone.

Example: subnet-abcd1234

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: subnet-\w{8,17}

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkingRequest

The networking configuration for the cluster's control plane.

Contents

securityGroupIds

A list of security group IDs associated with the Elastic Network Interface (ENI) created in subnets.

Type: Array of strings

Pattern: `sg-\w{8,17}`

Required: No

subnetIds

The list of subnet IDs where AWS PCS creates an Elastic Network Interface (ENI) to enable communication between managed controllers and AWS PCS resources. Subnet IDs have the form `subnet-0123456789abcdef0`.

Subnets can't be in AWS Outposts, AWS Wavelength or an AWS Local Zone.

Note

AWS PCS currently supports only 1 subnet in this list.

Type: Array of strings

Array Members: Minimum number of 1 item.

Pattern: `subnet-\w{8,17}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Queue

A queue resource.

Contents

arn

The unique Amazon Resource Name (ARN) of the queue.

Type: String

Required: Yes

clusterId

The ID of the cluster of the queue.

Type: String

Required: Yes

computeNodeGroupConfigurations

The list of compute node group configurations associated with the queue. Queues assign jobs to associated compute node groups.

Type: Array of [ComputeNodeGroupConfiguration](#) objects

Required: Yes

createdAt

The date and time the resource was created.

Type: Timestamp

Required: Yes

id

The generated unique ID of the queue.

Type: String

Required: Yes

modifiedAt

The date and time the resource was modified.

Type: Timestamp

Required: Yes

name

The name that identifies the queue.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: (?!pcs_)^(?![A-Za-z0-9]{10}\$)[A-Za-z][A-Za-z0-9-]+

Required: Yes

status

The provisioning status of the queue.

Note

The provisioning status doesn't indicate the overall health of the queue.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED

Required: Yes

errorInfo

The list of errors that occurred during queue provisioning.

Type: Array of [ErrorInfo](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

QueueSummary

The object returned by the `ListQueues` API action.

Contents

arn

The unique Amazon Resource Name (ARN) of the queue.

Type: String

Required: Yes

clusterId

The ID of the cluster of the queue.

Type: String

Required: Yes

createdAt

The date and time the resource was created.

Type: Timestamp

Required: Yes

id

The generated unique ID of the queue.

Type: String

Required: Yes

modifiedAt

The date and time the resource was modified.

Type: Timestamp

Required: Yes

name

The name that identifies the queue.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 25.

Pattern: (?!pcs_)^(?![A-Za-z0-9]{10}\$)[A-Za-z][A-Za-z0-9-]+

Required: Yes

status

The provisioning status of the queue.

Note

The provisioning status doesn't indicate the overall health of the queue.

Type: String

Valid Values: CREATING | ACTIVE | UPDATING | DELETING | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScalingConfiguration

Specifies the boundaries of the compute node group auto scaling.

Contents

maxInstanceCount

The upper bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

minInstanceCount

The lower bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScalingConfigurationRequest

Specifies the boundaries of the compute node group auto scaling.

Contents

maxInstanceCount

The upper bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

minInstanceCount

The lower bound of the number of instances allowed in the compute fleet.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Scheduler

The cluster management and job scheduling software associated with the cluster.

Contents

type

The software AWS PCS uses to manage cluster scaling and job scheduling.

Type: String

Valid Values: SLURM

Required: Yes

version

The version of the specified scheduling software that AWS PCS uses to manage cluster scaling and job scheduling.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SchedulerRequest

The cluster management and job scheduling software associated with the cluster.

Contents

type

The software AWS PCS uses to manage cluster scaling and job scheduling.

Type: String

Valid Values: SLURM

Required: Yes

version

The version of the specified scheduling software that AWS PCS uses to manage cluster scaling and job scheduling.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SlurmAuthKey

The shared Slurm key for authentication, also known as the **cluster secret**.

Contents

secretArn

The Amazon Resource Name (ARN) of the the shared Slurm key.

Type: String

Required: Yes

secretVersion

The version of the shared Slurm key.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SlurmCustomSetting

Additional settings that directly map to Slurm settings.

Contents

parameterName

AWS PCS supports configuration of the following Slurm parameters:

- For **clusters**
 - [Prolog](#)
 - [Epilog](#)
 - [SelectTypeParameters](#)
- For **compute node groups**
 - [Weight](#)
 - [RealMemory](#)

Type: String

Required: Yes

parameterValue

The values for the configured Slurm settings.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SpotOptions

Additional configuration when you specify SPOT as the purchaseOption for the CreateComputeNodeGroup API action.

Contents

allocationStrategy

The Amazon EC2 allocation strategy AWS PCS uses to provision EC2 instances. AWS PCS supports **lowest price**, **capacity optimized**, and **price capacity optimized**. For more information, see [Use allocation strategies to determine how EC2 Fleet or Spot Fleet fulfills Spot and On-Demand capacity](#) in the *Amazon Elastic Compute Cloud User Guide*. If you don't provide this option, it defaults to **price capacity optimized**.

Type: String

Valid Values: lowest-price | capacity-optimized | price-capacity-optimized

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UpdateComputeNodeGroupSlurmConfigurationRequest

Additional options related to the Slurm scheduler.

Contents

slurmCustomSettings

Additional Slurm-specific configuration that directly maps to Slurm settings.

Type: Array of [SlurmCustomSetting](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Stores information about a field in a request that caused an exception.

Contents

message

The message body of the exception.

Type: String

Required: Yes

name

The name of the exception.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400