



Evaluate downgrading Oracle databases to Standard Edition 2 on AWS

AWS Prescriptive Guidance



AWS Prescriptive Guidance: Evaluate downgrading Oracle databases to Standard Edition 2 on AWS

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Introduction	1
Overview	1
Targeted business outcomes	1
Prerequisites and limitations	3
Prerequisites	3
Limitations	3
Product versions	3
Tools	4
Assess your environment	5
Assessing Oracle Database Enterprise Edition by using SQL commands	5
Assessing Oracle Database Enterprise Edition by using AWS SCT	6
Scaling the Oracle assessment	7
Compare features	8
Best practices	17
FAQ	18
How can I migrate from Oracle Database EE to Oracle Database SE2?	18
How can I downgrade my EE Oracle database to SE2 with minimum downtime?	18
Can I have High Availability in my Amazon RDS for Oracle SE2 database?	18
How can I monitor the performance of my Amazon RDS for Oracle SE2 database instance?	18
Can I have encryption on my Amazon RDS for Oracle SE2 database instance?	19
What types of licensing options are available with Amazon RDS for Oracle?	19
Which Oracle Database editions are available with Amazon RDS for Oracle?	19
What are the licensing policies for using Amazon RDS for Oracle?	20
How is Amazon RDS for Oracle supported?	20
How does the license option affect DB instance scaling?	20
How does the license option affect version upgrades?	21
Can I change the licensing option for my DB instance (for example, from BYOL to License Included)?	21
Next steps	22
Downgrading with downtime	22
Downgrading with reduced downtime	23
Resources	24
AWS references	24
Oracle references	24

Video	24
AWS Partners	25
Document history	26
Glossary	27
#	27
A	28
B	31
C	32
D	35
E	39
F	41
G	42
H	43
I	44
L	46
M	47
O	51
P	53
Q	55
R	55
S	58
T	61
U	63
V	63
W	64
Z	65

Evaluate downgrading Oracle databases to Standard Edition 2 on AWS

Lanre Showunmi and Bhavesh Rathod, Amazon Web Services (AWS)

October 2022 ([document history](#))

This document provides guidance for reducing your Oracle licensing costs by downgrading from Oracle Database Enterprise Edition (EE) to Oracle Database Standard Edition 2 (SE2). By following this guide, you can perform an in-depth assessment of your Enterprise Edition Oracle databases. You can then determine which databases can be safely downgraded to Standard Edition 2 during migration to [Amazon Relational Database Service \(Amazon RDS\) for Oracle](#). This guide also applies if you are already running Amazon RDS for Oracle Database EE and you want to downgrade to Oracle Database SE2.

Overview

Oracle Database EE is the default deployment option for production workloads in many organizations. This might be partly to the result of a common misconception that the Oracle Database SE2 is not capable of supporting enterprise-class applications. Both the Enterprise Edition and the Standard Edition 2 Oracle databases share a common code base, so technically they offer similar functionalities.

Oracle Database EE offers additional options, but it's significantly more expensive than Oracle Database SE2. Downgrading to Oracle Database SE2 gives you an opportunity to reduce the overall total cost of ownership of your databases. Applications with no or minimum usage of Enterprise Edition features are good candidates for downgrades to Oracle Database SE2.

This guide does not provide licensing advice. For specific licensing information, consult your own Oracle license agreements. You can engage specialized [AWS Oracle Competency Partners](#) that have helped many AWS customers interpret Oracle licensing and proceed with their migration.

Targeted business outcomes

By using this guide, you can derive the following business outcomes:

-
- **Cost savings on Oracle database licensing fees** – Downgrading to Standard Edition 2 reduces the total cost of running your applications.
 - **Reduced need for significant upfront costs** – Amazon RDS for Oracle offers the License Included option so that you pay only for what you use.
 - **Efficient assessment** – You can perform a bulk assessment of your databases to determine suitability for a downgrade to Standard Edition 2

Prerequisites and limitations

Prerequisites

- No application support requirements for Oracle Database Enterprise Edition (EE)
- Oracle Database EE running in an on-premises data center, or on [Amazon Elastic Compute Cloud \(Amazon EC2\)](#), or on Amazon RDS for Oracle or Amazon RDS Custom for Oracle
- A database client tool, such as Oracle SQL Developer or SQL*Plus, for running SQL commands
- Access to the database and [privileges](#) to run an [AWS Schema Conversion Tool \(AWS SCT\)](#) assessment

Limitations

- Amazon RDS for Oracle has storage size and IOPs limits. For the current maximum, see the [AWS documentation](#).
- Oracle Standard Edition 2 supports a maximum of 16 CPU threads. For currently supported instance classes for Amazon RDS for Oracle Standard Edition 2, see the [AWS documentation](#).
- AWS SCT supports Oracle 10.2 and later.

Product versions

The general logic described in this guide applies to Oracle versions from 9i and later. However, AWS SCT supports only Oracle Database versions 10g and later. To identify feature usage in cases where AWS SCT is not supported, run SQL queries on the source database.

For a current list of supported versions and editions, see [Oracle on Amazon RDS](#) in the AWS documentation. For details on pricing and supported instance classes, see [Amazon RDS for Oracle pricing](#).

AWS services and other tools

- [Amazon Relational Database Service \(Amazon RDS\) for Oracle](#) helps you set up, operate, and scale an Oracle relational database in the AWS Cloud.
- [AWS Schema Conversion Tool \(AWS SCT\)](#) supports heterogeneous database migrations by automatically converting the source database schema and a majority of the custom code to a format that's compatible with the target database. You can use AWS SCT to assess, convert, and copy the database schema of your source Oracle database into a format compatible with Amazon RDS for Oracle. Using AWS SCT, you can analyze the potential cost savings that you can achieve by changing your license type from Oracle Database Enterprise Edition to Oracle Database Standard Edition 2.
- [Oracle SQL Developer](#) is an integrated development environment that simplifies the development and management of Oracle databases in both traditional and cloud-based deployments.
- [SQL*Plus](#) is an interactive tool for running SQL commands on an Oracle database.

If you are working with an AWS consulting team, ask about in-house tooling and scripting built by AWS database specialists. These tools and scripts can help with gathering and reviewing data dictionary information (such as the `DBA_FEATURE_USAGE_STATISTICS` view and the count of bitmap indexes).

Assessing your environment

To assess your Oracle database and find out whether Enterprise Edition features are being used, you can use one of the following approaches:

- SQL commands
- The license-evaluation feature of AWS SCT

Assessing Oracle Database Enterprise Edition by using SQL commands

Oracle tracks the usage of Oracle Database options, Oracle management packs, and their corresponding features in a view called [DBA_FEATURE_USAGE_STATISTICS](#). The view is updated once a week by default, so it might take 7 days to show recent usage data. To get the latest information, manually refresh the view using the `DBMS_FEATURE_USAGE_INTERNAL` package. Your database user requires `EXECUTE` privilege on `DBMS_FEATURE_USAGE_INTERNAL` to refresh the view, and `SELECT ANY DICTIONARY` privilege to query the view.

Oracle provides the script `options_packs_usage_statistics.sql` in [Support document 1317265.1](#). You can use that script to check which options, features, and management packs have been used in the database. Alternatively, you can run the following query to list previously used options and features.

```
-- To view the last refresh date of DBA_FEATURE_USAGE_STATISTICS
select max(last_sample_date) from dba_feature_usage_statistics order by 1;

-- To manually refresh DBA_FEATURE_USAGE_STATISTICS view
exec sys.dbms_feature_usage_internal.exec_db_usage_sampling(sysdate);

-- To list features and options in use
select dbafus1.name, dbafus1.detected_usages, dbafus1.currently_used,
       dbafus1.first_usage_date, dbafus1.last_usage_date, dbafus1.version
from dba_feature_usage_statistics dbafus1
where dbafus1.version = (select max(dbafus2.version)
                        from dba_feature_usage_statistics dbafus2
                        where dbafus2.name = dbafus1.name)
and dbafus1.detected_usages > 0
and dbafus1.dbid = (select dbid from v$database)
```

```
and dbafus1.currently_used='TRUE'
order by dbafus1.name;

-- To check use of parallelism for activities like DMLs, DDLs, index builds, statistics
gathering, Data Pump
select name, value
from gv$sysstat
where
    upper(NAME) like '%PARALLEL OPERATIONS%'
OR
    upper(NAME) like '%PARALLELIZED%'
OR
    upper(NAME) like '%PX%';

-- To identify use of Materialized Views Query Rewrite
select owner, mview_name from dba_mviews
where owner not like '%SYS%'
and rewrite_enabled='Y';

-- To identify bitmap indexes
select * from dba_indexes
where index_type='BITMAP'
and owner not like '%SYS%';

-- To identify non-system use of Partitioning
select * from dba_tab_partitions where table_owner not like '%SYS%';
```

Review the result of the previous query and compare it with [Oracle documentation](#). Investigate each Enterprise Edition feature or option listed in the output to understand their use case and determine appropriate alternatives in Oracle Database Standard Edition 2 where possible.

Assessing Oracle Database Enterprise Edition by using AWS SCT

AWS Schema Conversion Tool (AWS SCT) provides a project-based user interface for assessing, converting, and copying the database schema of your source Oracle database into a format that is compatible with Amazon RDS for Oracle. Using AWS SCT, you can analyze potential cost savings that can be achieved by changing your Oracle Database license type from Enterprise Edition to Standard Edition 2.

The *License evaluation and cloud support* section of the AWS SCT report provides detailed information about Oracle database features in use. This information can help you make informed

decisions while migrating to Amazon RDS for Oracle. For example, the report might say that your Enterprise Edition server uses the Compression feature, and that you must remove dependencies on ColumnStoreIndex and Partitioning. It also lists features, such as InMemoryOLTP, that can't be moved to Amazon RDS for Oracle.

Scaling the Oracle assessment

To evaluate multiple servers, you can run batch assessments with AWS SCT by using the [multiserver assessor](#) option. After assessing each schema, the assessor produces a server-level report that includes the *License evaluation and cloud support* section.

Comparing Oracle Database EE and SE2 features

The following table is a short version of the list of Oracle Database Enterprise Edition (EE) features and possible alternatives in Amazon RDS for Oracle Standard Edition 2 (SE2). For a comprehensive list, see the [Oracle documentation](#).

Functional area	Feature or option	EE	SE2	Notes
High availability	Oracle Data Guard (extra cost)	Yes	No	The Multi-AZ (Availability Zone) feature of Amazon RDS replicates database updates across two Availability Zones to increase durability and availability. Amazon RDS will automatically fail over to the standby for planned maintenance and unplanned disruptions.
High availability	Oracle Active Data Guard	Yes	No	You can serve read-only traffic from a replica database instance by using the change

				data capture (CDC) feature of AWS Database Migration Service (AWS DMS) to replicate changes from your Amazon RDS for Oracle SE2 instance.
High availability	Oracle Real Application Clusters (RAC) One Node (extra cost)	Yes	No	The Amazon RDS Multi-AZ feature applies.

High availability	Rolling upgrades —patch set, database, and operating system	Yes	No	For database software upgrades in Multi-AZ deployments , Amazon RDS simultaneously upgrades both the primary and standby database. For operating system (OS) upgrades in Multi-AZ deployments, Amazon RDS upgrades the standby instance first. It then fails over the primary to the standby before upgrading the primary instance. This reduces the downtime window for OS upgrades.
-------------------	---	-----	----	---

High availability	Block change tracking for fast incremental backup	Yes	No	With Amazon RDS backups , the first snapshot of your DB instance is a full copy. Subsequent backups are incremental backups of blocks that have changed since the last full backup. You can restore your Amazon RDS for Oracle database instance from automated or manual snapshots.
High availability	Parallel backup and recovery	Yes	No	
High availability	FLASHBACK DATABASE command	Yes	No	You can restore your DB instance to any specific time during the backup retention period by using the point-in-time recovery feature of Amazon RDS.

High availability	Online index rebuild	Yes	No	Where possible, plan for these activities during a downtime window.
High availability	Online table organization	Yes	No	
High availability	Online table redefinition	Yes	No	
High availability	Online datafile move	Yes	No	
Manageability	Automatic Workload Repository (AWR)	Yes	No	<p>You can use Oracle Statspack, an option pack in Oracle SE2, in place of Oracle AWR.</p> <p>Amazon RDS Performance Insights is a database performance monitoring and tuning tool built for the cloud. You can use the tool dashboard to detect performance problems by evaluating top waits, top SQL statements, top hosts, and top users.</p>

Manageability	SQL plan management	Yes	Yes	You can use stored outlines, hints, and SQL plan baselines to tune your queries in Amazon RDS for Oracle SE2.
Scalability	CPU restrictions	No	Yes	SE2 is capped at a maximum of two CPU sockets. Each SE2 database is automatically capped to use a maximum of 16 concurrent user threads.

Scalability	Oracle Real Application Clusters (RAC) (extra cost)	Yes	No	<p>You can scale your Amazon RDS for Oracle SE2 instance vertically to address the growing demands of an application.</p> <p>There is minimal downtime when you are scaling up in a Multi-AZ environment. The standby database gets upgraded first, then a failover will occur to the newly sized database.</p> <p>When you scale up in a Single-AZ environment, the instance will be unavailable during the scale operation.</p>
-------------	---	-----	----	---

Security	Column-level and tablespace encryption	Yes	No	Amazon RDS can encrypt your Amazon RDS DB instances . Data that is encrypted at rest includes the underlying storage for DB instances, its automated backups, read replicas, and snapshots.
Snapshots and cloning	Storage Snapshot Optimization	Yes	No	Amazon RDS supports user-initiated snapshot creation. For more information, see Amazon RDS backup and restore .

Data warehousing	Oracle Partitioning	Yes	No	Depending on your specific use case, you can implement a partitioning feature for tables in Oracle Database SE2 by using a single view accessing multiple subtables and the INSTEAD OF trigger. For more information, see the AWS Database blog post Implementing table partitioning in Oracle Standard Edition: Part 1 .
------------------	---------------------	-----	----	---

Best practices

We recommend the following best practices for assessing and downgrading your Oracle Database Enterprise Edition (EE) to Standard Edition 2 (SE2) on Amazon RDS for Oracle.

- **Validate vendor support for Oracle Database SE2** – Confirm that your application is certified to run on Oracle Database SE2. Check directly with the software vendor or their documentation. Downgrading to Oracle Database SE2 without vendor confirmation might invalidate support for an application.
- **Identify the use of Oracle Database EE features for administration activities** – Database or application administrators sometimes rely on Oracle Database EE features to improve operational processes. Examples include online maintenance activities, such as index rebuild, and table move, and parallelism for maintenance activities. Identify usage of such features and make an informed decision. You can modify your operations or apply workarounds where possible to mitigate the loss of Oracle Database EE features.
- **Assess workload patterns of the database** – Oracle Database SE2 automatically restricts usage to a maximum of 16 CPU threads. Analyze your database workload pattern to determine whether the 16 CPU thread limit will negatively impact service levels when you downgrade to Oracle Database SE2. You can use tools such as the Automatic Workload Repository (AWR) reports, "DBA_HIST_*" views, and server-level metrics for this analysis. For more information about the available instance class for Oracle Database SE2, see the [Amazon RDS for Oracle documentation](#).
- **Test your workload against Oracle Database SE2** – Run multiple tests using a representative workload to determine whether the 16-thread limit imposed by Oracle Database SE2 has any negative impact on your workload. Monitor results and tune the database as required.
- **Test database administration activities** – Test activities such as monitoring, performance assessments, tuning, and maintenance tasks to build comfort levels around new ways of working in the Oracle Database SE2 environment.
- **Test the migration process** – Run end-to-end migration tests to build operator confidence, fine-tune the approach, and document every issue and its resolution.

FAQ

How can I migrate from Oracle Database EE to Oracle Database SE2?

Migrating from Oracle Database EE to Oracle Database SE2 requires logical export of data from the Enterprise Edition database and import of the data into the Standard Edition 2 database instance. Use tools such as [Oracle Export/Import](#), [Oracle Data Pump](#), or [Oracle GoldenGate](#) or [AWS Database Migration Service \(AWS DMS\)](#) full load and change data capture (CDC) for reduced downtime.

How can I downgrade my EE Oracle database to SE2 with minimum downtime?

To reduce overall downtime, you can bulk load data into your SE2 database using Oracle Export/Import. You can use logical replication tools such as AWS DMS or Oracle GoldenGate to synchronize your SE2 database.

Can I have High Availability in my Amazon RDS for Oracle SE2 database?

Amazon RDS currently uses synchronous replication technology and automatic failover functionality to provide [Multi-AZ](#) deployments for Oracle DB instances. Multi-AZ deployments are available for all Oracle database editions supported by Amazon RDS.

How can I monitor the performance of my Amazon RDS for Oracle SE2 database instance?

You can monitor your SE2 database instance using [Amazon RDS Performance Insights](#), [Enhanced Monitoring](#), and [Amazon CloudWatch](#). You can also analyze database performance using Oracle Statspack in place of Oracle Automatic Workload Repository (AWR).

Can I have encryption on my Amazon RDS for Oracle SE2 database instance?

Amazon RDS can [encrypt your Amazon RDS DB instances](#). Data that is encrypted at rest includes the underlying storage for DB instances, its automated backups, read replicas, and snapshots. To turn on encryption in transit using [SSL encryption](#) for an Oracle DB instance, add the Oracle SSL option to the option group associated with the Oracle DB instance.

What types of licensing options are available with Amazon RDS for Oracle?

There are two types of licensing options available for using Amazon RDS for Oracle:

- **Bring Your Own License (BYOL)** – In this licensing model, you can use your existing Oracle Database licenses to run Oracle deployments on Amazon RDS. To run a DB instance under the BYOL model, you must have the appropriate Oracle Database license (with Software Update License and Support) for the DB instance class and Oracle Database edition that you want to run. You must also follow Oracle's [licensing policies](#) for Oracle Database software in the Amazon EC2 cloud computing environment. DB instances reside in the Amazon EC2 environment.
- **License Included** – In the License Included service model, you do not need separately purchased Oracle licenses. The Oracle Database software has been licensed by AWS for your use subject to Section 10.3.1 of the [AWS Service Terms](#). License Included pricing is inclusive of software, underlying hardware resources, and Amazon RDS management capabilities.

Which Oracle Database editions are available with Amazon RDS for Oracle?

Amazon RDS currently supports the following Oracle Database editions under each of the licensing models:

- **BYOL** – Enterprise Edition (EE), Standard Edition 2 (SE2)
- **License Included** – Standard Edition 2 (SE2)

What are the licensing policies for using Amazon RDS for Oracle?

- **BYOL** – To run a DB instance under the BYOL model, you must have the appropriate Oracle Database license (with Software Update License and Support) for the DB instance class and Oracle Database edition you want to run. You must also follow Oracle's [licensing policies](#) for Oracle Database software in the Amazon EC2 cloud computing environment. DB instances reside in the Amazon EC2 environment.
- **License Included** – In the License Included service model, you do not need separately purchased Oracle licenses. The Oracle Database software has been licensed by AWS for your use subject to Section 10.3.1 of the [AWS Service Terms](#). License Included pricing is inclusive of software, underlying hardware resources, and Amazon RDS management capabilities.

How is Amazon RDS for Oracle supported?

- **BYOL** – Under this model, you continue to use your active Oracle support account and contact Oracle directly for Oracle Database specific service requests. If you have an active AWS Support account, you can contact AWS Support for Amazon RDS specific issues. Amazon Web Services and Oracle have a multiple-vendor support process for cases that require assistance from both organizations.
- **License Included** – In this model, if you have an active AWS Support account, you should contact AWS Support for both Amazon RDS and Oracle Database specific service requests.

How does the license option affect DB instance scaling?

- **BYOL** – You can scale your DB instances in accordance with the terms of your Oracle licenses.
- **License Included** – DB instances that are running Oracle can be scaled up and down at any point, subject to the prevailing hourly pricing for each DB instance class.

For more information on the scaling implications of Reserved DB instances, see [Reserved DB instances for Amazon RDS](#).

How does the license option affect version upgrades?

- **BYOL** – To use Amazon RDS for Oracle, you should have Software Update License and Support from Oracle.
- **License Included** – The cost of the Software Update License is embedded in the hourly price, enabling access to Oracle Database software updates.

Can I change the licensing option for my DB instance (for example, from BYOL to License Included)?

Yes, you can change your license options through the AWS Command Line Interface (AWS CLI) or through the AWS Management Console. On the Console, choose **Modify Instance**, and select the appropriate option in the **Licensing Model** dropdown list.

Next steps

After you determine that you can safely downgrade a database to Oracle Database Standard Edition 2 (SE2) on Amazon RDS for Oracle, you can migrate the database by using one or a combination of the following tools:

- Oracle import and export utilities can move Oracle data in and out of Oracle databases. Oracle offers two types of database import and export utilities: Oracle Export and Import (for earlier releases) and Oracle Data Pump (available in Oracle Database 10g and later).
- Oracle GoldenGate offers real-time replication capabilities so that you can synchronize your target database after an initial load. This option can help reduce application downtime during go-live.
- AWS Database Migration Service (AWS DMS) helps you migrate relational databases, data warehouses, NoSQL databases, and other types of data stores. You can use AWS DMS to migrate your data into the AWS Cloud, between on-premises instances (through an AWS Cloud setup), or between combinations of cloud and on-premises databases. The change data capture (CDC) option of AWS DMS offers continuous replication, so that you can reduce the total downtime during migration. For information about the Oracle database versions and editions that AWS DMS supports, see the [AWS DMS documentation](#).

Depending on your availability requirements during the downgrade, you can adopt any of the following options to safely downgrade your Enterprise Edition database to Standard Edition 2 on Amazon RDS for Oracle.

Downgrading with downtime

- Use Oracle Data Pump to create consistent export of data from the Enterprise Edition database and import that data into the Standard Edition 2 database. For more information, see [Step by Step Procedure to Convert from Enterprise Edition to Standard Edition \(Doc ID 465189.1\)](#). Oracle credentials are required.
- Use AWS DMS to perform a full load of data from the Enterprise Edition database to the Standard Edition 2 database.
- Use Oracle GoldenGate to perform a full instantiation of the Standard Edition 2 database from the Enterprise Edition database.

Downgrading with reduced downtime

- Use Oracle Data Pump for consistent export and import of the initial load, and use AWS DMS CDC for data synchronization.
- Use Oracle Data Pump for consistent export and import of the initial load, and use Oracle GoldenGate for data synchronization.
- Use AWS DMS for the full load and for data synchronization.
- Use Oracle GoldenGate for full instantiation and for data synchronization.

For more information on migrating Oracle databases to Amazon RDS for Oracle, see the following AWS Prescriptive Guidance documentation:

- [Migrating Oracle databases to the AWS Cloud](#) (guide)
- [Migrate an Oracle database from Amazon EC2 to Amazon RDS for Oracle using AWS DMS](#) (pattern)
- [Migrate an on-premises Oracle database to Amazon RDS for Oracle using Oracle Data Pump](#) (pattern)

Resources

AWS references

- [Amazon RDS for Oracle](#)
- [Amazon RDS for Oracle pricing](#)
- [Amazon RDS documentation](#)
- [Amazon EC2](#)
- [AWS DMS documentation](#)
- [AWS SCT documentation](#)
- [AWS Service Terms](#)
- [Analyzing performance management in Oracle SE using Amazon RDS for Oracle](#) (blog post)
- [Managing your SQL plan in Oracle SE with Amazon RDS for Oracle](#) (blog post)
- [Implementing table partitioning in Oracle Standard Edition: Part 1](#) (blog post)
- [Migrating Oracle databases to the AWS Cloud](#) (guide)
- [Migrate an Oracle database from Amazon EC2 to Amazon RDS for Oracle using AWS DMS](#) (pattern)
- [Migrate an on-premises Oracle database to Amazon RDS for Oracle using Oracle Data Pump](#) (pattern)

Oracle references

- [Oracle Licensing Information](#)
- [Step by Step Procedure to Convert from Enterprise Edition to Standard Edition \(Doc ID 465189.1\)](#), Oracle login required
- [Database Options/Management Packs Usage Reporting for Oracle Databases 11.2 and later \(Doc ID 1317265.1\)](#), Oracle login required

Video

- [Best Practices for Running Oracle Databases on Amazon RDS](#)

AWS Partners

- [AWS Oracle Competency Partners](#)

Document history

The following table describes significant changes to this guide. If you want to be notified about future updates, you can subscribe to an [RSS feed](#).

Change	Description	Date
Multiple updates	On the Prerequisites page, Amazon RDS Custom for Oracle was added as a source option. On the AWS tools and other services page, information was added about AWS-developed tooling and scripts.	October 24, 2023
Initial publication	—	June 30, 2022

AWS Prescriptive Guidance glossary

The following are commonly used terms in strategies, guides, and patterns provided by AWS Prescriptive Guidance. To suggest entries, please use the **Provide feedback** link at the end of the glossary.

Numbers

7 Rs

Seven common migration strategies for moving applications to the cloud. These strategies build upon the 5 Rs that Gartner identified in 2011 and consist of the following:

- **Refactor/re-architect** – Move an application and modify its architecture by taking full advantage of cloud-native features to improve agility, performance, and scalability. This typically involves porting the operating system and database. Example: Migrate your on-premises Oracle database to the Amazon Aurora PostgreSQL-Compatible Edition.
- **Replatform (lift and reshape)** – Move an application to the cloud, and introduce some level of optimization to take advantage of cloud capabilities. Example: Migrate your on-premises Oracle database to Amazon Relational Database Service (Amazon RDS) for Oracle in the AWS Cloud.
- **Repurchase (drop and shop)** – Switch to a different product, typically by moving from a traditional license to a SaaS model. Example: Migrate your customer relationship management (CRM) system to Salesforce.com.
- **Rehost (lift and shift)** – Move an application to the cloud without making any changes to take advantage of cloud capabilities. Example: Migrate your on-premises Oracle database to Oracle on an EC2 instance in the AWS Cloud.
- **Relocate (hypervisor-level lift and shift)** – Move infrastructure to the cloud without purchasing new hardware, rewriting applications, or modifying your existing operations. This migration scenario is specific to VMware Cloud on AWS, which supports virtual machine (VM) compatibility and workload portability between your on-premises environment and AWS. You can use the VMware Cloud Foundation technologies from your on-premises data centers when you migrate your infrastructure to VMware Cloud on AWS. Example: Relocate the hypervisor hosting your Oracle database to VMware Cloud on AWS.
- **Retain (revisit)** – Keep applications in your source environment. These might include applications that require major refactoring, and you want to postpone that work until a later

time, and legacy applications that you want to retain, because there's no business justification for migrating them.

- Retire – Decommission or remove applications that are no longer needed in your source environment.

A

ABAC

See [attribute-based access control](#).

abstracted services

See [managed services](#).

ACID

See [atomicity, consistency, isolation, durability](#).

active-active migration

A database migration method in which the source and target databases are kept in sync (by using a bidirectional replication tool or dual write operations), and both databases handle transactions from connecting applications during migration. This method supports migration in small, controlled batches instead of requiring a one-time cutover. It's more flexible but requires more work than [active-passive migration](#).

active-passive migration

A database migration method in which in which the source and target databases are kept in sync, but only the source database handles transactions from connecting applications while data is replicated to the target database. The target database doesn't accept any transactions during migration.

aggregate function

A SQL function that operates on a group of rows and calculates a single return value for the group. Examples of aggregate functions include SUM and MAX.

AI

See [artificial intelligence](#).

AIOps

See [artificial intelligence operations](#).

anonymization

The process of permanently deleting personal information in a dataset. Anonymization can help protect personal privacy. Anonymized data is no longer considered to be personal data.

anti-pattern

A frequently used solution for a recurring issue where the solution is counter-productive, ineffective, or less effective than an alternative.

application control

A security approach that allows the use of only approved applications in order to help protect a system from malware.

application portfolio

A collection of detailed information about each application used by an organization, including the cost to build and maintain the application, and its business value. This information is key to [the portfolio discovery and analysis process](#) and helps identify and prioritize the applications to be migrated, modernized, and optimized.

artificial intelligence (AI)

The field of computer science that is dedicated to using computing technologies to perform cognitive functions that are typically associated with humans, such as learning, solving problems, and recognizing patterns. For more information, see [What is Artificial Intelligence?](#)

artificial intelligence operations (AIOps)

The process of using machine learning techniques to solve operational problems, reduce operational incidents and human intervention, and increase service quality. For more information about how AIOps is used in the AWS migration strategy, see the [operations integration guide](#).

asymmetric encryption

An encryption algorithm that uses a pair of keys, a public key for encryption and a private key for decryption. You can share the public key because it isn't used for decryption, but access to the private key should be highly restricted.

atomicity, consistency, isolation, durability (ACID)

A set of software properties that guarantee the data validity and operational reliability of a database, even in the case of errors, power failures, or other problems.

attribute-based access control (ABAC)

The practice of creating fine-grained permissions based on user attributes, such as department, job role, and team name. For more information, see [ABAC for AWS](#) in the AWS Identity and Access Management (IAM) documentation.

authoritative data source

A location where you store the primary version of data, which is considered to be the most reliable source of information. You can copy data from the authoritative data source to other locations for the purposes of processing or modifying the data, such as anonymizing, redacting, or pseudonymizing it.

Availability Zone

A distinct location within an AWS Region that is insulated from failures in other Availability Zones and provides inexpensive, low-latency network connectivity to other Availability Zones in the same Region.

AWS Cloud Adoption Framework (AWS CAF)

A framework of guidelines and best practices from AWS to help organizations develop an efficient and effective plan to move successfully to the cloud. AWS CAF organizes guidance into six focus areas called perspectives: business, people, governance, platform, security, and operations. The business, people, and governance perspectives focus on business skills and processes; the platform, security, and operations perspectives focus on technical skills and processes. For example, the people perspective targets stakeholders who handle human resources (HR), staffing functions, and people management. For this perspective, AWS CAF provides guidance for people development, training, and communications to help ready the organization for successful cloud adoption. For more information, see the [AWS CAF website](#) and the [AWS CAF whitepaper](#).

AWS Workload Qualification Framework (AWS WQF)

A tool that evaluates database migration workloads, recommends migration strategies, and provides work estimates. AWS WQF is included with AWS Schema Conversion Tool (AWS SCT). It analyzes database schemas and code objects, application code, dependencies, and performance characteristics, and provides assessment reports.

B

BCP

See [business continuity planning](#).

behavior graph

A unified, interactive view of resource behavior and interactions over time. You can use a behavior graph with Amazon Detective to examine failed logon attempts, suspicious API calls, and similar actions. For more information, see [Data in a behavior graph](#) in the Detective documentation.

big-endian system

A system that stores the most significant byte first. See also [endianness](#).

binary classification

A process that predicts a binary outcome (one of two possible classes). For example, your ML model might need to predict problems such as "Is this email spam or not spam?" or "Is this product a book or a car?"

bloom filter

A probabilistic, memory-efficient data structure that is used to test whether an element is a member of a set.

branch

A contained area of a code repository. The first branch created in a repository is the *main branch*. You can create a new branch from an existing branch, and you can then develop features or fix bugs in the new branch. A branch you create to build a feature is commonly referred to as a *feature branch*. When the feature is ready for release, you merge the feature branch back into the main branch. For more information, see [About branches](#) (GitHub documentation).

break-glass access

In exceptional circumstances and through an approved process, a quick means for a user to gain access to an AWS account that they don't typically have permissions to access. For more information, see the [Implement break-glass procedures](#) indicator in the AWS Well-Architected guidance.

brownfield strategy

The existing infrastructure in your environment. When adopting a brownfield strategy for a system architecture, you design the architecture around the constraints of the current systems and infrastructure. If you are expanding the existing infrastructure, you might blend brownfield and [greenfield](#) strategies.

buffer cache

The memory area where the most frequently accessed data is stored.

business capability

What a business does to generate value (for example, sales, customer service, or marketing). Microservices architectures and development decisions can be driven by business capabilities. For more information, see the [Organized around business capabilities](#) section of the [Running containerized microservices on AWS](#) whitepaper.

business continuity planning (BCP)

A plan that addresses the potential impact of a disruptive event, such as a large-scale migration, on operations and enables a business to resume operations quickly.

C

CAF

See [AWS Cloud Adoption Framework](#).

CCoE

See [Cloud Center of Excellence](#).

CDC

See [change data capture](#).

change data capture (CDC)

The process of tracking changes to a data source, such as a database table, and recording metadata about the change. You can use CDC for various purposes, such as auditing or replicating changes in a target system to maintain synchronization.

chaos engineering

Intentionally introducing failures or disruptive events to test a system's resilience. You can use [AWS Fault Injection Service \(AWS FIS\)](#) to perform experiments that stress your AWS workloads and evaluate their response.

CI/CD

See [continuous integration and continuous delivery](#).

classification

A categorization process that helps generate predictions. ML models for classification problems predict a discrete value. Discrete values are always distinct from one another. For example, a model might need to evaluate whether or not there is a car in an image.

client-side encryption

Encryption of data locally, before the target AWS service receives it.

Cloud Center of Excellence (CCoE)

A multi-disciplinary team that drives cloud adoption efforts across an organization, including developing cloud best practices, mobilizing resources, establishing migration timelines, and leading the organization through large-scale transformations. For more information, see the [CCoE posts](#) on the AWS Cloud Enterprise Strategy Blog.

cloud computing

The cloud technology that is typically used for remote data storage and IoT device management. Cloud computing is commonly connected to [edge computing](#) technology.

cloud operating model

In an IT organization, the operating model that is used to build, mature, and optimize one or more cloud environments. For more information, see [Building your Cloud Operating Model](#).

cloud stages of adoption

The four phases that organizations typically go through when they migrate to the AWS Cloud:

- Project – Running a few cloud-related projects for proof of concept and learning purposes
- Foundation – Making foundational investments to scale your cloud adoption (e.g., creating a landing zone, defining a CCoE, establishing an operations model)
- Migration – Migrating individual applications
- Re-invention – Optimizing products and services, and innovating in the cloud

These stages were defined by Stephen Orban in the blog post [The Journey Toward Cloud-First & the Stages of Adoption](#) on the AWS Cloud Enterprise Strategy blog. For information about how they relate to the AWS migration strategy, see the [migration readiness guide](#).

CMDB

See [configuration management database](#).

code repository

A location where source code and other assets, such as documentation, samples, and scripts, are stored and updated through version control processes. Common cloud repositories include GitHub or AWS CodeCommit. Each version of the code is called a *branch*. In a microservice structure, each repository is devoted to a single piece of functionality. A single CI/CD pipeline can use multiple repositories.

cold cache

A buffer cache that is empty, not well populated, or contains stale or irrelevant data. This affects performance because the database instance must read from the main memory or disk, which is slower than reading from the buffer cache.

cold data

Data that is rarely accessed and is typically historical. When querying this kind of data, slow queries are typically acceptable. Moving this data to lower-performing and less expensive storage tiers or classes can reduce costs.

computer vision

A field of AI used by machines to identify people, places, and things in images with accuracy at or above human levels. Often built with deep learning models, it automates extraction, analysis, classification, and understanding of useful information from a single image or a sequence of images.

configuration management database (CMDB)

A repository that stores and manages information about a database and its IT environment, including both hardware and software components and their configurations. You typically use data from a CMDB in the portfolio discovery and analysis stage of migration.

conformance pack

A collection of AWS Config rules and remediation actions that you can assemble to customize your compliance and security checks. You can deploy a conformance pack as a single entity in

an AWS account and Region, or across an organization, by using a YAML template. For more information, see [Conformance packs](#) in the AWS Config documentation.

continuous integration and continuous delivery (CI/CD)

The process of automating the source, build, test, staging, and production stages of the software release process. CI/CD is commonly described as a pipeline. CI/CD can help you automate processes, improve productivity, improve code quality, and deliver faster. For more information, see [Benefits of continuous delivery](#). CD can also stand for *continuous deployment*. For more information, see [Continuous Delivery vs. Continuous Deployment](#).

D

data at rest

Data that is stationary in your network, such as data that is in storage.

data classification

A process for identifying and categorizing the data in your network based on its criticality and sensitivity. It is a critical component of any cybersecurity risk management strategy because it helps you determine the appropriate protection and retention controls for the data. Data classification is a component of the security pillar in the AWS Well-Architected Framework. For more information, see [Data classification](#).

data drift

A meaningful variation between the production data and the data that was used to train an ML model, or a meaningful change in the input data over time. Data drift can reduce the overall quality, accuracy, and fairness in ML model predictions.

data in transit

Data that is actively moving through your network, such as between network resources.

data minimization

The principle of collecting and processing only the data that is strictly necessary. Practicing data minimization in the AWS Cloud can reduce privacy risks, costs, and your analytics carbon footprint.

data perimeter

A set of preventive guardrails in your AWS environment that help make sure that only trusted identities are accessing trusted resources from expected networks. For more information, see [Building a data perimeter on AWS](#).

data preprocessing

To transform raw data into a format that is easily parsed by your ML model. Preprocessing data can mean removing certain columns or rows and addressing missing, inconsistent, or duplicate values.

data provenance

The process of tracking the origin and history of data throughout its lifecycle, such as how the data was generated, transmitted, and stored.

data subject

An individual whose data is being collected and processed.

data warehouse

A data management system that supports business intelligence, such as analytics. Data warehouses commonly contain large amounts of historical data, and they are typically used for queries and analysis.

database definition language (DDL)

Statements or commands for creating or modifying the structure of tables and objects in a database.

database manipulation language (DML)

Statements or commands for modifying (inserting, updating, and deleting) information in a database.

DDL

See [database definition language](#).

deep ensemble

To combine multiple deep learning models for prediction. You can use deep ensembles to obtain a more accurate prediction or for estimating uncertainty in predictions.

deep learning

An ML subfield that uses multiple layers of artificial neural networks to identify mapping between input data and target variables of interest.

defense-in-depth

An information security approach in which a series of security mechanisms and controls are thoughtfully layered throughout a computer network to protect the confidentiality, integrity, and availability of the network and the data within. When you adopt this strategy on AWS, you add multiple controls at different layers of the AWS Organizations structure to help secure resources. For example, a defense-in-depth approach might combine multi-factor authentication, network segmentation, and encryption.

delegated administrator

In AWS Organizations, a compatible service can register an AWS member account to administer the organization's accounts and manage permissions for that service. This account is called the *delegated administrator* for that service. For more information and a list of compatible services, see [Services that work with AWS Organizations](#) in the AWS Organizations documentation.

deployment

The process of making an application, new features, or code fixes available in the target environment. Deployment involves implementing changes in a code base and then building and running that code base in the application's environments.

development environment

See [environment](#).

detective control

A security control that is designed to detect, log, and alert after an event has occurred. These controls are a second line of defense, alerting you to security events that bypassed the preventative controls in place. For more information, see [Detective controls](#) in *Implementing security controls on AWS*.

development value stream mapping (DVSM)

A process used to identify and prioritize constraints that adversely affect speed and quality in a software development lifecycle. DVSM extends the value stream mapping process originally

designed for lean manufacturing practices. It focuses on the steps and teams required to create and move value through the software development process.

digital twin

A virtual representation of a real-world system, such as a building, factory, industrial equipment, or production line. Digital twins support predictive maintenance, remote monitoring, and production optimization.

dimension table

In a [star schema](#), a smaller table that contains data attributes about quantitative data in a fact table. Dimension table attributes are typically text fields or discrete numbers that behave like text. These attributes are commonly used for query constraining, filtering, and result set labeling.

disaster

An event that prevents a workload or system from fulfilling its business objectives in its primary deployed location. These events can be natural disasters, technical failures, or the result of human actions, such as unintentional misconfiguration or a malware attack.

disaster recovery (DR)

The strategy and process you use to minimize downtime and data loss caused by a [disaster](#). For more information, see [Disaster Recovery of Workloads on AWS: Recovery in the Cloud](#) in the AWS Well-Architected Framework.

DML

See [database manipulation language](#).

domain-driven design

An approach to developing a complex software system by connecting its components to evolving domains, or core business goals, that each component serves. This concept was introduced by Eric Evans in his book, *Domain-Driven Design: Tackling Complexity in the Heart of Software* (Boston: Addison-Wesley Professional, 2003). For information about how you can use domain-driven design with the strangler fig pattern, see [Modernizing legacy Microsoft ASP.NET \(ASMX\) web services incrementally by using containers and Amazon API Gateway](#).

DR

See [disaster recovery](#).

drift detection

Tracking deviations from a baselined configuration. For example, you can use AWS CloudFormation to [detect drift in system resources](#), or you can use AWS Control Tower to [detect changes in your landing zone](#) that might affect compliance with governance requirements.

DVSM

See [development value stream mapping](#).

E

EDA

See [exploratory data analysis](#).

edge computing

The technology that increases the computing power for smart devices at the edges of an IoT network. When compared with [cloud computing](#), edge computing can reduce communication latency and improve response time.

encryption

A computing process that transforms plaintext data, which is human-readable, into ciphertext.

encryption key

A cryptographic string of randomized bits that is generated by an encryption algorithm. Keys can vary in length, and each key is designed to be unpredictable and unique.

endianness

The order in which bytes are stored in computer memory. Big-endian systems store the most significant byte first. Little-endian systems store the least significant byte first.

endpoint

See [service endpoint](#).

endpoint service

A service that you can host in a virtual private cloud (VPC) to share with other users. You can create an endpoint service with AWS PrivateLink and grant permissions to other AWS accounts

or to AWS Identity and Access Management (IAM) principals. These accounts or principals can connect to your endpoint service privately by creating interface VPC endpoints. For more information, see [Create an endpoint service](#) in the Amazon Virtual Private Cloud (Amazon VPC) documentation.

envelope encryption

The process of encrypting an encryption key with another encryption key. For more information, see [Envelope encryption](#) in the AWS Key Management Service (AWS KMS) documentation.

environment

An instance of a running application. The following are common types of environments in cloud computing:

- development environment – An instance of a running application that is available only to the core team responsible for maintaining the application. Development environments are used to test changes before promoting them to upper environments. This type of environment is sometimes referred to as a *test environment*.
- lower environments – All development environments for an application, such as those used for initial builds and tests.
- production environment – An instance of a running application that end users can access. In a CI/CD pipeline, the production environment is the last deployment environment.
- upper environments – All environments that can be accessed by users other than the core development team. This can include a production environment, preproduction environments, and environments for user acceptance testing.

epic

In agile methodologies, functional categories that help organize and prioritize your work. Epics provide a high-level description of requirements and implementation tasks. For example, AWS CAF security epics include identity and access management, detective controls, infrastructure security, data protection, and incident response. For more information about epics in the AWS migration strategy, see the [program implementation guide](#).

exploratory data analysis (EDA)

The process of analyzing a dataset to understand its main characteristics. You collect or aggregate data and then perform initial investigations to find patterns, detect anomalies,

and check assumptions. EDA is performed by calculating summary statistics and creating data visualizations.

F

fact table

The central table in a [star schema](#). It stores quantitative data about business operations. Typically, a fact table contains two types of columns: those that contain measures and those that contain a foreign key to a dimension table.

fail fast

A philosophy that uses frequent and incremental testing to reduce the development lifecycle. It is a critical part of an agile approach.

fault isolation boundary

In the AWS Cloud, a boundary such as an Availability Zone, AWS Region, control plane, or data plane that limits the effect of a failure and helps improve the resilience of workloads. For more information, see [AWS Fault Isolation Boundaries](#).

feature branch

See [branch](#).

features

The input data that you use to make a prediction. For example, in a manufacturing context, features could be images that are periodically captured from the manufacturing line.

feature importance

How significant a feature is for a model's predictions. This is usually expressed as a numerical score that can be calculated through various techniques, such as Shapley Additive Explanations (SHAP) and integrated gradients. For more information, see [Machine learning model interpretability with :AWS](#).

feature transformation

To optimize data for the ML process, including enriching data with additional sources, scaling values, or extracting multiple sets of information from a single data field. This enables the ML

model to benefit from the data. For example, if you break down the “2021-05-27 00:15:37” date into “2021”, “May”, “Thu”, and “15”, you can help the learning algorithm learn nuanced patterns associated with different data components.

FGAC

See [fine-grained access control](#).

fine-grained access control (FGAC)

The use of multiple conditions to allow or deny an access request.

flash-cut migration

A database migration method that uses continuous data replication through [change data capture](#) to migrate data in the shortest time possible, instead of using a phased approach. The objective is to keep downtime to a minimum.

G

geo blocking

See [geographic restrictions](#).

geographic restrictions (geo blocking)

In Amazon CloudFront, an option to prevent users in specific countries from accessing content distributions. You can use an allow list or block list to specify approved and banned countries. For more information, see [Restricting the geographic distribution of your content](#) in the CloudFront documentation.

Gitflow workflow

An approach in which lower and upper environments use different branches in a source code repository. The Gitflow workflow is considered legacy, and the [trunk-based workflow](#) is the modern, preferred approach.

greenfield strategy

The absence of existing infrastructure in a new environment. When adopting a greenfield strategy for a system architecture, you can select all new technologies without the restriction of compatibility with existing infrastructure, also known as [brownfield](#). If you are expanding the existing infrastructure, you might blend brownfield and greenfield strategies.

guardrail

A high-level rule that helps govern resources, policies, and compliance across organizational units (OUs). *Preventive guardrails* enforce policies to ensure alignment to compliance standards. They are implemented by using service control policies and IAM permissions boundaries. *Detective guardrails* detect policy violations and compliance issues, and generate alerts for remediation. They are implemented by using AWS Config, AWS Security Hub, Amazon GuardDuty, AWS Trusted Advisor, Amazon Inspector, and custom AWS Lambda checks.

H

HA

See [high availability](#).

heterogeneous database migration

Migrating your source database to a target database that uses a different database engine (for example, Oracle to Amazon Aurora). Heterogeneous migration is typically part of a re-architecting effort, and converting the schema can be a complex task. [AWS provides AWS SCT](#) that helps with schema conversions.

high availability (HA)

The ability of a workload to operate continuously, without intervention, in the event of challenges or disasters. HA systems are designed to automatically fail over, consistently deliver high-quality performance, and handle different loads and failures with minimal performance impact.

historian modernization

An approach used to modernize and upgrade operational technology (OT) systems to better serve the needs of the manufacturing industry. A *historian* is a type of database that is used to collect and store data from various sources in a factory.

homogeneous database migration

Migrating your source database to a target database that shares the same database engine (for example, Microsoft SQL Server to Amazon RDS for SQL Server). Homogeneous migration is typically part of a rehosting or replatforming effort. You can use native database utilities to migrate the schema.

hot data

Data that is frequently accessed, such as real-time data or recent translational data. This data typically requires a high-performance storage tier or class to provide fast query responses.

hotfix

An urgent fix for a critical issue in a production environment. Due to its urgency, a hotfix is usually made outside of the typical DevOps release workflow.

hypercare period

Immediately following cutover, the period of time when a migration team manages and monitors the migrated applications in the cloud in order to address any issues. Typically, this period is 1–4 days in length. At the end of the hypercare period, the migration team typically transfers responsibility for the applications to the cloud operations team.

I

laC

See [infrastructure as code](#).

identity-based policy

A policy attached to one or more IAM principals that defines their permissions within the AWS Cloud environment.

idle application

An application that has an average CPU and memory usage between 5 and 20 percent over a period of 90 days. In a migration project, it is common to retire these applications or retain them on premises.

IIoT

See [industrial Internet of Things](#).

immutable infrastructure

A model that deploys new infrastructure for production workloads instead of updating, patching, or modifying the existing infrastructure. Immutable infrastructures are inherently

more consistent, reliable, and predictable than [mutable infrastructure](#). For more information, see the [Deploy using immutable infrastructure](#) best practice in the AWS Well-Architected Framework.

inbound (ingress) VPC

In an AWS multi-account architecture, a VPC that accepts, inspects, and routes network connections from outside an application. The [AWS Security Reference Architecture](#) recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

incremental migration

A cutover strategy in which you migrate your application in small parts instead of performing a single, full cutover. For example, you might move only a few microservices or users to the new system initially. After you verify that everything is working properly, you can incrementally move additional microservices or users until you can decommission your legacy system. This strategy reduces the risks associated with large migrations.

infrastructure

All of the resources and assets contained within an application's environment.

infrastructure as code (IaC)

The process of provisioning and managing an application's infrastructure through a set of configuration files. IaC is designed to help you centralize infrastructure management, standardize resources, and scale quickly so that new environments are repeatable, reliable, and consistent.

industrial Internet of Things (IIoT)

The use of internet-connected sensors and devices in the industrial sectors, such as manufacturing, energy, automotive, healthcare, life sciences, and agriculture. For more information, see [Building an industrial Internet of Things \(IIoT\) digital transformation strategy](#).

inspection VPC

In an AWS multi-account architecture, a centralized VPC that manages inspections of network traffic between VPCs (in the same or different AWS Regions), the internet, and on-premises networks. The [AWS Security Reference Architecture](#) recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

Internet of Things (IoT)

The network of connected physical objects with embedded sensors or processors that communicate with other devices and systems through the internet or over a local communication network. For more information, see [What is IoT?](#)

interpretability

A characteristic of a machine learning model that describes the degree to which a human can understand how the model's predictions depend on its inputs. For more information, see [Machine learning model interpretability with AWS](#).

IoT

See [Internet of Things](#).

IT information library (ITIL)

A set of best practices for delivering IT services and aligning these services with business requirements. ITIL provides the foundation for ITSM.

IT service management (ITSM)

Activities associated with designing, implementing, managing, and supporting IT services for an organization. For information about integrating cloud operations with ITSM tools, see the [operations integration guide](#).

ITIL

See [IT information library](#).

ITSM

See [IT service management](#).

L

label-based access control (LBAC)

An implementation of mandatory access control (MAC) where the users and the data itself are each explicitly assigned a security label value. The intersection between the user security label and data security label determines which rows and columns can be seen by the user.

landing zone

A landing zone is a well-architected, multi-account AWS environment that is scalable and secure. This is a starting point from which your organizations can quickly launch and deploy workloads and applications with confidence in their security and infrastructure environment. For more information about landing zones, see [Setting up a secure and scalable multi-account AWS environment](#).

large migration

A migration of 300 or more servers.

LBAC

See [label-based access control](#).

least privilege

The security best practice of granting the minimum permissions required to perform a task. For more information, see [Apply least-privilege permissions](#) in the IAM documentation.

lift and shift

See [7 Rs](#).

little-endian system

A system that stores the least significant byte first. See also [endianness](#).

lower environments

See [environment](#).

M

machine learning (ML)

A type of artificial intelligence that uses algorithms and techniques for pattern recognition and learning. ML analyzes and learns from recorded data, such as Internet of Things (IoT) data, to generate a statistical model based on patterns. For more information, see [Machine Learning](#).

main branch

See [branch](#).

managed services

AWS services for which AWS operates the infrastructure layer, the operating system, and platforms, and you access the endpoints to store and retrieve data. Amazon Simple Storage Service (Amazon S3) and Amazon DynamoDB are examples of managed services. These are also known as *abstracted services*.

MAP

See [Migration Acceleration Program](#).

mechanism

A complete process in which you create a tool, drive adoption of the tool, and then inspect the results in order to make adjustments. A mechanism is a cycle that reinforces and improves itself as it operates. For more information, see [Building mechanisms](#) in the AWS Well-Architected Framework.

member account

All AWS accounts other than the management account that are part of an organization in AWS Organizations. An account can be a member of only one organization at a time.

microservice

A small, independent service that communicates over well-defined APIs and is typically owned by small, self-contained teams. For example, an insurance system might include microservices that map to business capabilities, such as sales or marketing, or subdomains, such as purchasing, claims, or analytics. The benefits of microservices include agility, flexible scaling, easy deployment, reusable code, and resilience. For more information, see [Integrating microservices by using AWS serverless services](#).

microservices architecture

An approach to building an application with independent components that run each application process as a microservice. These microservices communicate through a well-defined interface by using lightweight APIs. Each microservice in this architecture can be updated, deployed, and scaled to meet demand for specific functions of an application. For more information, see [Implementing microservices on AWS](#).

Migration Acceleration Program (MAP)

An AWS program that provides consulting support, training, and services to help organizations build a strong operational foundation for moving to the cloud, and to help offset the initial

cost of migrations. MAP includes a migration methodology for executing legacy migrations in a methodical way and a set of tools to automate and accelerate common migration scenarios.

migration at scale

The process of moving the majority of the application portfolio to the cloud in waves, with more applications moved at a faster rate in each wave. This phase uses the best practices and lessons learned from the earlier phases to implement a *migration factory* of teams, tools, and processes to streamline the migration of workloads through automation and agile delivery. This is the third phase of the [AWS migration strategy](#).

migration factory

Cross-functional teams that streamline the migration of workloads through automated, agile approaches. Migration factory teams typically include operations, business analysts and owners, migration engineers, developers, and DevOps professionals working in sprints. Between 20 and 50 percent of an enterprise application portfolio consists of repeated patterns that can be optimized by a factory approach. For more information, see the [discussion of migration factories](#) and the [Cloud Migration Factory guide](#) in this content set.

migration metadata

The information about the application and server that is needed to complete the migration. Each migration pattern requires a different set of migration metadata. Examples of migration metadata include the target subnet, security group, and AWS account.

migration pattern

A repeatable migration task that details the migration strategy, the migration destination, and the migration application or service used. Example: Rehost migration to Amazon EC2 with AWS Application Migration Service.

Migration Portfolio Assessment (MPA)

An online tool that provides information for validating the business case for migrating to the AWS Cloud. MPA provides detailed portfolio assessment (server right-sizing, pricing, TCO comparisons, migration cost analysis) as well as migration planning (application data analysis and data collection, application grouping, migration prioritization, and wave planning). The [MPA tool](#) (requires login) is available free of charge to all AWS consultants and APN Partner consultants.

Migration Readiness Assessment (MRA)

The process of gaining insights about an organization's cloud readiness status, identifying strengths and weaknesses, and building an action plan to close identified gaps, using the AWS CAF. For more information, see the [migration readiness guide](#). MRA is the first phase of the [AWS migration strategy](#).

migration strategy

The approach used to migrate a workload to the AWS Cloud. For more information, see the [7 Rs](#) entry in this glossary and see [Mobilize your organization to accelerate large-scale migrations](#).

ML

See [machine learning](#).

MPA

See [Migration Portfolio Assessment](#).

modernization

Transforming an outdated (legacy or monolithic) application and its infrastructure into an agile, elastic, and highly available system in the cloud to reduce costs, gain efficiencies, and take advantage of innovations. For more information, see [Strategy for modernizing applications in the AWS Cloud](#).

modernization readiness assessment

An evaluation that helps determine the modernization readiness of an organization's applications; identifies benefits, risks, and dependencies; and determines how well the organization can support the future state of those applications. The outcome of the assessment is a blueprint of the target architecture, a roadmap that details development phases and milestones for the modernization process, and an action plan for addressing identified gaps. For more information, see [Evaluating modernization readiness for applications in the AWS Cloud](#).

monolithic applications (monoliths)

Applications that run as a single service with tightly coupled processes. Monolithic applications have several drawbacks. If one application feature experiences a spike in demand, the entire architecture must be scaled. Adding or improving a monolithic application's features also becomes more complex when the code base grows. To address these issues, you can use a microservices architecture. For more information, see [Decomposing monoliths into microservices](#).

multiclass classification

A process that helps generate predictions for multiple classes (predicting one of more than two outcomes). For example, an ML model might ask "Is this product a book, car, or phone?" or "Which product category is most interesting to this customer?"

mutable infrastructure

A model that updates and modifies the existing infrastructure for production workloads. For improved consistency, reliability, and predictability, the AWS Well-Architected Framework recommends the use of [immutable infrastructure](#) as a best practice.

O

OAC

See [origin access control](#).

OAI

See [origin access identity](#).

OCM

See [organizational change management](#).

offline migration

A migration method in which the source workload is taken down during the migration process. This method involves extended downtime and is typically used for small, non-critical workloads.

OI

See [operations integration](#).

OLA

See [operational-level agreement](#).

online migration

A migration method in which the source workload is copied to the target system without being taken offline. Applications that are connected to the workload can continue to function during the migration. This method involves zero to minimal downtime and is typically used for critical production workloads.

operational-level agreement (OLA)

An agreement that clarifies what functional IT groups promise to deliver to each other, to support a service-level agreement (SLA).

operational readiness review (ORR)

A checklist of questions and associated best practices that help you understand, evaluate, prevent, or reduce the scope of incidents and possible failures. For more information, see [Operational Readiness Reviews \(ORR\)](#) in the AWS Well-Architected Framework.

operations integration (OI)

The process of modernizing operations in the cloud, which involves readiness planning, automation, and integration. For more information, see the [operations integration guide](#).

organization trail

A trail that's created by AWS CloudTrail that logs all events for all AWS accounts in an organization in AWS Organizations. This trail is created in each AWS account that's part of the organization and tracks the activity in each account. For more information, see [Creating a trail for an organization](#) in the CloudTrail documentation.

organizational change management (OCM)

A framework for managing major, disruptive business transformations from a people, culture, and leadership perspective. OCM helps organizations prepare for, and transition to, new systems and strategies by accelerating change adoption, addressing transitional issues, and driving cultural and organizational changes. In the AWS migration strategy, this framework is called *people acceleration*, because of the speed of change required in cloud adoption projects. For more information, see the [OCM guide](#).

origin access control (OAC)

In CloudFront, an enhanced option for restricting access to secure your Amazon Simple Storage Service (Amazon S3) content. OAC supports all S3 buckets in all AWS Regions, server-side encryption with AWS KMS (SSE-KMS), and dynamic PUT and DELETE requests to the S3 bucket.

origin access identity (OAI)

In CloudFront, an option for restricting access to secure your Amazon S3 content. When you use OAI, CloudFront creates a principal that Amazon S3 can authenticate with. Authenticated principals can access content in an S3 bucket only through a specific CloudFront distribution. See also [OAC](#), which provides more granular and enhanced access control.

ORR

See [operational readiness review](#).

outbound (egress) VPC

In an AWS multi-account architecture, a VPC that handles network connections that are initiated from within an application. The [AWS Security Reference Architecture](#) recommends setting up your Network account with inbound, outbound, and inspection VPCs to protect the two-way interface between your application and the broader internet.

P

permissions boundary

An IAM management policy that is attached to IAM principals to set the maximum permissions that the user or role can have. For more information, see [Permissions boundaries](#) in the IAM documentation.

personally identifiable information (PII)

Information that, when viewed directly or paired with other related data, can be used to reasonably infer the identity of an individual. Examples of PII include names, addresses, and contact information.

PII

See [personally identifiable information](#).

playbook

A set of predefined steps that capture the work associated with migrations, such as delivering core operations functions in the cloud. A playbook can take the form of scripts, automated runbooks, or a summary of processes or steps required to operate your modernized environment.

policy

An object that can define permissions (see [identity-based policy](#)), specify access conditions (see [resource-based policy](#)), or define the maximum permissions for all accounts in an organization in AWS Organizations (see [service control policy](#)).

polyglot persistence

Independently choosing a microservice's data storage technology based on data access patterns and other requirements. If your microservices have the same data storage technology, they can encounter implementation challenges or experience poor performance. Microservices are more easily implemented and achieve better performance and scalability if they use the data store best adapted to their requirements. For more information, see [Enabling data persistence in microservices](#).

portfolio assessment

A process of discovering, analyzing, and prioritizing the application portfolio in order to plan the migration. For more information, see [Evaluating migration readiness](#).

predicate

A query condition that returns true or false, commonly located in a WHERE clause.

predicate pushdown

A database query optimization technique that filters the data in the query before transfer. This reduces the amount of data that must be retrieved and processed from the relational database, and it improves query performance.

preventative control

A security control that is designed to prevent an event from occurring. These controls are a first line of defense to help prevent unauthorized access or unwanted changes to your network. For more information, see [Preventative controls](#) in *Implementing security controls on AWS*.

principal

An entity in AWS that can perform actions and access resources. This entity is typically a root user for an AWS account, an IAM role, or a user. For more information, see *Principal* in [Roles terms and concepts](#) in the IAM documentation.

Privacy by Design

An approach in system engineering that takes privacy into account throughout the whole engineering process.

private hosted zones

A container that holds information about how you want Amazon Route 53 to respond to DNS queries for a domain and its subdomains within one or more VPCs. For more information, see [Working with private hosted zones](#) in the Route 53 documentation.

proactive control

A [security control](#) designed to prevent the deployment of noncompliant resources. These controls scan resources before they are provisioned. If the resource is not compliant with the control, then it isn't provisioned. For more information, see the [Controls reference guide](#) in the AWS Control Tower documentation and see [Proactive controls](#) in *Implementing security controls on AWS*.

production environment

See [environment](#).

pseudonymization

The process of replacing personal identifiers in a dataset with placeholder values. Pseudonymization can help protect personal privacy. Pseudonymized data is still considered to be personal data.

Q

query plan

A series of steps, like instructions, that are used to access the data in a SQL relational database system.

query plan regression

When a database service optimizer chooses a less optimal plan than it did before a given change to the database environment. This can be caused by changes to statistics, constraints, environment settings, query parameter bindings, and updates to the database engine.

R

RACI matrix

See [responsible, accountable, consulted, informed \(RACI\)](#).

ransomware

A malicious software that is designed to block access to a computer system or data until a payment is made.

RASCI matrix

See [responsible, accountable, consulted, informed \(RACI\)](#).

RCAC

See [row and column access control](#).

read replica

A copy of a database that's used for read-only purposes. You can route queries to the read replica to reduce the load on your primary database.

re-architect

See [7 Rs](#).

recovery point objective (RPO)

The maximum acceptable amount of time since the last data recovery point. This determines what is considered an acceptable loss of data between the last recovery point and the interruption of service.

recovery time objective (RTO)

The maximum acceptable delay between the interruption of service and restoration of service.

refactor

See [7 Rs](#).

Region

A collection of AWS resources in a geographic area. Each AWS Region is isolated and independent of the others to provide fault tolerance, stability, and resilience. For more information, see [Managing AWS Regions](#) in *AWS General Reference*.

regression

An ML technique that predicts a numeric value. For example, to solve the problem of "What price will this house sell for?" an ML model could use a linear regression model to predict a house's sale price based on known facts about the house (for example, the square footage).

rehost

See [7 Rs](#).

release

In a deployment process, the act of promoting changes to a production environment.

relocate

See [7 Rs](#).

replatform

See [7 Rs](#).

repurchase

See [7 Rs](#).

resource-based policy

A policy attached to a resource, such as an Amazon S3 bucket, an endpoint, or an encryption key. This type of policy specifies which principals are allowed access, supported actions, and any other conditions that must be met.

responsible, accountable, consulted, informed (RACI) matrix

A matrix that defines the roles and responsibilities for all parties involved in migration activities and cloud operations. The matrix name is derived from the responsibility types defined in the matrix: responsible (R), accountable (A), consulted (C), and informed (I). The support (S) type is optional. If you include support, the matrix is called a *RASCI matrix*, and if you exclude it, it's called a *RACI matrix*.

responsive control

A security control that is designed to drive remediation of adverse events or deviations from your security baseline. For more information, see [Responsive controls](#) in *Implementing security controls on AWS*.

retain

See [7 Rs](#).

retire

See [7 Rs](#).

rotation

The process of periodically updating a [secret](#) to make it more difficult for an attacker to access the credentials.

row and column access control (RCAC)

The use of basic, flexible SQL expressions that have defined access rules. RCAC consists of row permissions and column masks.

RPO

See [recovery point objective](#).

RTO

See [recovery time objective](#).

runbook

A set of manual or automated procedures required to perform a specific task. These are typically built to streamline repetitive operations or procedures with high error rates.

S

SAML 2.0

An open standard that many identity providers (IdPs) use. This feature enables federated single sign-on (SSO), so users can log into the AWS Management Console or call the AWS API operations without you having to create user in IAM for everyone in your organization. For more information about SAML 2.0-based federation, see [About SAML 2.0-based federation](#) in the IAM documentation.

SCP

See [service control policy](#).

secret

In AWS Secrets Manager, confidential or restricted information, such as a password or user credentials, that you store in encrypted form. It consists of the secret value and its metadata. The secret value can be binary, a single string, or multiple strings. For more information, see [Secret](#) in the Secrets Manager documentation.

security control

A technical or administrative guardrail that prevents, detects, or reduces the ability of a threat actor to exploit a security vulnerability. There are four primary types of security controls: [preventative](#), [detective](#), [responsive](#), and [proactive](#).

security hardening

The process of reducing the attack surface to make it more resistant to attacks. This can include actions such as removing resources that are no longer needed, implementing the security best practice of granting least privilege, or deactivating unnecessary features in configuration files.

security information and event management (SIEM) system

Tools and services that combine security information management (SIM) and security event management (SEM) systems. A SIEM system collects, monitors, and analyzes data from servers, networks, devices, and other sources to detect threats and security breaches, and to generate alerts.

security response automation

A predefined and programmed action that is designed to automatically respond to or remediate a security event. These automations serve as [detective](#) or [responsive](#) security controls that help you implement AWS security best practices. Examples of automated response actions include modifying a VPC security group, patching an Amazon EC2 instance, or rotating credentials.

server-side encryption

Encryption of data at its destination, by the AWS service that receives it.

service control policy (SCP)

A policy that provides centralized control over permissions for all accounts in an organization in AWS Organizations. SCPs define guardrails or set limits on actions that an administrator can delegate to users or roles. You can use SCPs as allow lists or deny lists, to specify which services or actions are permitted or prohibited. For more information, see [Service control policies](#) in the AWS Organizations documentation.

service endpoint

The URL of the entry point for an AWS service. You can use the endpoint to connect programmatically to the target service. For more information, see [AWS service endpoints](#) in *AWS General Reference*.

service-level agreement (SLA)

An agreement that clarifies what an IT team promises to deliver to their customers, such as service uptime and performance.

service-level indicator (SLI)

A measurement of a performance aspect of a service, such as its error rate, availability, or throughput.

service-level objective (SLO)

A target metric that represents the health of a service, as measured by a [service-level indicator](#).

shared responsibility model

A model describing the responsibility you share with AWS for cloud security and compliance. AWS is responsible for security *of* the cloud, whereas you are responsible for security *in* the cloud. For more information, see [Shared responsibility model](#).

SIEM

See [security information and event management system](#).

single point of failure (SPOF)

A failure in a single, critical component of an application that can disrupt the system.

SLA

See [service-level agreement](#).

SLI

See [service-level indicator](#).

SLO

See [service-level objective](#).

split-and-seed model

A pattern for scaling and accelerating modernization projects. As new features and product releases are defined, the core team splits up to create new product teams. This helps scale your organization's capabilities and services, improves developer productivity, and supports rapid

innovation. For more information, see [Phased approach to modernizing applications in the AWS Cloud](#).

SPOF

See [single point of failure](#).

star schema

A database organizational structure that uses one large fact table to store transactional or measured data and uses one or more smaller dimensional tables to store data attributes. This structure is designed for use in a [data warehouse](#) or for business intelligence purposes.

strangler fig pattern

An approach to modernizing monolithic systems by incrementally rewriting and replacing system functionality until the legacy system can be decommissioned. This pattern uses the analogy of a fig vine that grows into an established tree and eventually overcomes and replaces its host. The pattern was [introduced by Martin Fowler](#) as a way to manage risk when rewriting monolithic systems. For an example of how to apply this pattern, see [Modernizing legacy Microsoft ASP.NET \(ASMX\) web services incrementally by using containers and Amazon API Gateway](#).

subnet

A range of IP addresses in your VPC. A subnet must reside in a single Availability Zone.

symmetric encryption

An encryption algorithm that uses the same key to encrypt and decrypt the data.

synthetic testing

Testing a system in a way that simulates user interactions to detect potential issues or to monitor performance. You can use [Amazon CloudWatch Synthetics](#) to create these tests.

T

tags

Key-value pairs that act as metadata for organizing your AWS resources. Tags can help you manage, identify, organize, search for, and filter resources. For more information, see [Tagging your AWS resources](#).

target variable

The value that you are trying to predict in supervised ML. This is also referred to as an *outcome variable*. For example, in a manufacturing setting the target variable could be a product defect.

task list

A tool that is used to track progress through a runbook. A task list contains an overview of the runbook and a list of general tasks to be completed. For each general task, it includes the estimated amount of time required, the owner, and the progress.

test environment

See [environment](#).

training

To provide data for your ML model to learn from. The training data must contain the correct answer. The learning algorithm finds patterns in the training data that map the input data attributes to the target (the answer that you want to predict). It outputs an ML model that captures these patterns. You can then use the ML model to make predictions on new data for which you don't know the target.

transit gateway

A network transit hub that you can use to interconnect your VPCs and on-premises networks. For more information, see [What is a transit gateway](#) in the AWS Transit Gateway documentation.

trunk-based workflow

An approach in which developers build and test features locally in a feature branch and then merge those changes into the main branch. The main branch is then built to the development, preproduction, and production environments, sequentially.

trusted access

Granting permissions to a service that you specify to perform tasks in your organization in AWS Organizations and in its accounts on your behalf. The trusted service creates a service-linked role in each account, when that role is needed, to perform management tasks for you. For more information, see [Using AWS Organizations with other AWS services](#) in the AWS Organizations documentation.

tuning

To change aspects of your training process to improve the ML model's accuracy. For example, you can train the ML model by generating a labeling set, adding labels, and then repeating these steps several times under different settings to optimize the model.

two-pizza team

A small DevOps team that you can feed with two pizzas. A two-pizza team size ensures the best possible opportunity for collaboration in software development.

U

uncertainty

A concept that refers to imprecise, incomplete, or unknown information that can undermine the reliability of predictive ML models. There are two types of uncertainty: *Epistemic uncertainty* is caused by limited, incomplete data, whereas *aleatoric uncertainty* is caused by the noise and randomness inherent in the data. For more information, see the [Quantifying uncertainty in deep learning systems](#) guide.

undifferentiated tasks

Also known as *heavy lifting*, work that is necessary to create and operate an application but that doesn't provide direct value to the end user or provide competitive advantage. Examples of undifferentiated tasks include procurement, maintenance, and capacity planning.

upper environments

See [environment](#).

V

vacuuming

A database maintenance operation that involves cleaning up after incremental updates to reclaim storage and improve performance.

version control

Processes and tools that track changes, such as changes to source code in a repository.

VPC peering

A connection between two VPCs that allows you to route traffic by using private IP addresses. For more information, see [What is VPC peering](#) in the Amazon VPC documentation.

vulnerability

A software or hardware flaw that compromises the security of the system.

W

warm cache

A buffer cache that contains current, relevant data that is frequently accessed. The database instance can read from the buffer cache, which is faster than reading from the main memory or disk.

warm data

Data that is infrequently accessed. When querying this kind of data, moderately slow queries are typically acceptable.

window function

A SQL function that performs a calculation on a group of rows that relate in some way to the current record. Window functions are useful for processing tasks, such as calculating a moving average or accessing the value of rows based on the relative position of the current row.

workload

A collection of resources and code that delivers business value, such as a customer-facing application or backend process.

workstream

Functional groups in a migration project that are responsible for a specific set of tasks. Each workstream is independent but supports the other workstreams in the project. For example, the portfolio workstream is responsible for prioritizing applications, wave planning, and collecting migration metadata. The portfolio workstream delivers these assets to the migration workstream, which then migrates the servers and applications.

WORM

See [write once, read many](#).

WQF

See [AWS Workload Qualification Framework](#).

write once, read many (WORM)

A storage model that writes data a single time and prevents the data from being deleted or modified. Authorized users can read the data as many times as needed, but they cannot change it. This data storage infrastructure is considered [immutable](#).

Z

zero-day exploit

An attack, typically malware, that takes advantage of a [zero-day vulnerability](#).

zero-day vulnerability

An unmitigated flaw or vulnerability in a production system. Threat actors can use this type of vulnerability to attack the system. Developers frequently become aware of the vulnerability as a result of the attack.

zombie application

An application that has an average CPU and memory usage below 5 percent. In a migration project, it is common to retire these applications.