



API Reference

AWS RAM



API Version 2018-01-04

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

AWS RAM: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AcceptResourceShareInvitation	4
Request Syntax	4
URI Request Parameters	4
Request Body	4
Response Syntax	5
Response Elements	5
Errors	6
Examples	7
See Also	8
AssociateResourceShare	10
Request Syntax	10
URI Request Parameters	10
Request Body	10
Response Syntax	12
Response Elements	12
Errors	13
Examples	15
See Also	17
AssociateResourceSharePermission	19
Request Syntax	19
URI Request Parameters	19
Request Body	19
Response Syntax	21
Response Elements	21
Errors	22
Examples	23
See Also	24
CreatePermission	25
Request Syntax	25
URI Request Parameters	25
Request Body	25
Response Syntax	27

Response Elements	28
Errors	28
See Also	30
CreatePermissionVersion	31
Request Syntax	31
URI Request Parameters	31
Request Body	31
Response Syntax	32
Response Elements	33
Errors	34
See Also	35
CreateResourceShare	37
Request Syntax	37
URI Request Parameters	37
Request Body	37
Response Syntax	40
Response Elements	40
Errors	41
See Also	43
DeletePermission	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	44
Response Elements	45
Errors	45
See Also	47
DeletePermissionVersion	48
Request Syntax	48
URI Request Parameters	48
Request Body	49
Response Syntax	49
Response Elements	49
Errors	50
See Also	51
DeleteResourceShare	53

Request Syntax	53
URI Request Parameters	53
Request Body	53
Response Syntax	54
Response Elements	54
Errors	54
See Also	56
DisassociateResourceShare	57
Request Syntax	57
URI Request Parameters	57
Request Body	57
Response Syntax	59
Response Elements	59
Errors	60
See Also	61
DisassociateResourceSharePermission	63
Request Syntax	63
URI Request Parameters	63
Request Body	63
Response Syntax	64
Response Elements	64
Errors	65
See Also	66
EnableSharingWithAwsOrganization	67
Request Syntax	67
URI Request Parameters	67
Request Body	67
Response Syntax	67
Response Elements	67
Errors	68
See Also	68
GetPermission	70
Request Syntax	70
URI Request Parameters	70
Request Body	70
Response Syntax	71

Response Elements	71
Errors	72
See Also	72
GetResourcePolicies	74
Request Syntax	74
URI Request Parameters	74
Request Body	74
Response Syntax	75
Response Elements	76
Errors	76
See Also	77
GetResourceShareAssociations	79
Request Syntax	79
URI Request Parameters	79
Request Body	79
Response Syntax	81
Response Elements	82
Errors	82
See Also	83
GetResourceShareInvitations	85
Request Syntax	85
URI Request Parameters	85
Request Body	85
Response Syntax	86
Response Elements	87
Errors	88
Examples	89
See Also	90
GetResourceShares	92
Request Syntax	92
URI Request Parameters	92
Request Body	92
Response Syntax	95
Response Elements	95
Errors	96
See Also	97

ListPendingInvitationResources	98
Request Syntax	98
URI Request Parameters	98
Request Body	98
Response Syntax	100
Response Elements	100
Errors	101
See Also	102
ListPermissionAssociations	103
Request Syntax	103
URI Request Parameters	103
Request Body	103
Response Syntax	106
Response Elements	106
Errors	107
See Also	107
ListPermissions	109
Request Syntax	109
URI Request Parameters	109
Request Body	109
Response Syntax	111
Response Elements	111
Errors	112
See Also	113
ListPermissionVersions	114
Request Syntax	114
URI Request Parameters	114
Request Body	114
Response Syntax	115
Response Elements	116
Errors	116
See Also	118
ListPrincipals	119
Request Syntax	119
URI Request Parameters	119
Request Body	119

Response Syntax	122
Response Elements	122
Errors	123
See Also	124
ListReplacePermissionAssociationsWork	125
Request Syntax	125
URI Request Parameters	125
Request Body	125
Response Syntax	127
Response Elements	127
Errors	128
See Also	128
ListResources	130
Request Syntax	130
URI Request Parameters	130
Request Body	130
Response Syntax	133
Response Elements	133
Errors	134
See Also	135
ListResourceSharePermissions	136
Request Syntax	136
URI Request Parameters	136
Request Body	136
Response Syntax	137
Response Elements	138
Errors	138
See Also	140
ListResourceTypes	141
Request Syntax	141
URI Request Parameters	141
Request Body	141
Response Syntax	142
Response Elements	143
Errors	143
See Also	144

PromotePermissionCreatedFromPolicy	145
Request Syntax	145
URI Request Parameters	146
Request Body	146
Response Syntax	147
Response Elements	147
Errors	148
See Also	149
PromoteResourceShareCreatedFromPolicy	150
Request Syntax	150
URI Request Parameters	150
Request Body	150
Response Syntax	151
Response Elements	151
Errors	151
See Also	153
RejectResourceShareInvitation	154
Request Syntax	154
URI Request Parameters	154
Request Body	154
Response Syntax	155
Response Elements	155
Errors	156
See Also	157
ReplacePermissionAssociations	159
Request Syntax	159
URI Request Parameters	159
Request Body	159
Response Syntax	161
Response Elements	161
Errors	162
See Also	163
SetDefaultPermissionVersion	164
Request Syntax	164
URI Request Parameters	164
Request Body	164

Response Syntax	165
Response Elements	165
Errors	166
See Also	167
TagResource	168
Request Syntax	168
URI Request Parameters	168
Request Body	168
Response Syntax	169
Response Elements	169
Errors	169
See Also	170
UntagResource	172
Request Syntax	172
URI Request Parameters	172
Request Body	172
Response Syntax	173
Response Elements	173
Errors	173
See Also	174
UpdateResourceShare	175
Request Syntax	175
URI Request Parameters	175
Request Body	175
Response Syntax	176
Response Elements	177
Errors	177
See Also	179
Data Types	180
AssociatedPermission	181
Contents	181
See Also	183
Principal	184
Contents	184
See Also	185
ReplacePermissionAssociationsWork	186

Contents	186
See Also	188
Resource	189
Contents	189
See Also	191
ResourceShare	192
Contents	192
See Also	194
ResourceShareAssociation	195
Contents	195
See Also	197
ResourceShareInvitation	198
Contents	198
See Also	199
ResourceSharePermissionDetail	201
Contents	201
See Also	204
ResourceSharePermissionSummary	205
Contents	205
See Also	208
ServiceNameAndResourceType	209
Contents	209
See Also	210
Tag	211
Contents	211
See Also	211
TagFilter	213
Contents	213
See Also	213
Common Parameters	215
Common Errors	218

Welcome

This is the *AWS Resource Access Manager API Reference*. This documentation provides descriptions and syntax for each of the actions and data types in AWS RAM. AWS RAM is a service that helps you securely share your AWS resources to other AWS accounts. If you use AWS Organizations to manage your accounts, then you can share your resources with your entire organization or to organizational units (OUs). For supported resource types, you can also share resources with individual AWS Identity and Access Management (IAM) roles and users.

Note

The HTTP query examples in this guide do not show every header field that might be included in the response; you might see others. Only the ones with relevance to the example are included.

To learn more about AWS RAM, see the following resources:

- [AWS Resource Access Manager product page](#)
- [AWS Resource Access Manager User Guide](#)

This document was last published on August 31, 2025.

Actions

The following actions are supported:

- [AcceptResourceShareInvitation](#)
- [AssociateResourceShare](#)
- [AssociateResourceSharePermission](#)
- [CreatePermission](#)
- [CreatePermissionVersion](#)
- [CreateResourceShare](#)
- [DeletePermission](#)
- [DeletePermissionVersion](#)
- [DeleteResourceShare](#)
- [DisassociateResourceShare](#)
- [DisassociateResourceSharePermission](#)
- [EnableSharingWithAwsOrganization](#)
- [GetPermission](#)
- [GetResourcePolicies](#)
- [GetResourceShareAssociations](#)
- [GetResourceShareInvitations](#)
- [GetResourceShares](#)
- [ListPendingInvitationResources](#)
- [ListPermissionAssociations](#)
- [ListPermissions](#)
- [ListPermissionVersions](#)
- [ListPrincipals](#)
- [ListReplacePermissionAssociationsWork](#)
- [ListResources](#)
- [ListResourceSharePermissions](#)
- [ListResourceTypes](#)
- [PromotePermissionCreatedFromPolicy](#)

- [PromoteResourceShareCreatedFromPolicy](#)
- [RejectResourceShareInvitation](#)
- [ReplacePermissionAssociations](#)
- [SetDefaultPermissionVersion](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateResourceShare](#)

AcceptResourceShareInvitation

Accepts an invitation to a resource share from another AWS account. After you accept the invitation, the resources included in the resource share are available to interact with in the relevant AWS Management Consoles and tools.

Request Syntax

```
POST /acceptresourceinvitation HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "resourceShareInvitationArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[resourceShareInvitationArn](#)

The [Amazon Resource Name \(ARN\)](#) of the invitation that you want to accept.

Type: String

Required: Yes

[clientToken](#)

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "resourceShareInvitation": {
    "invitationTimestamp": number,
    "receiverAccountId": "string",
    "receiverArn": "string",
    "resourceShareArn": "string",
    "resourceShareAssociations": [
      {
        "associatedEntity": "string",
        "associationType": "string",
        "creationTime": number,
        "external": boolean,
        "lastUpdatedTime": number,
        "resourceShareArn": "string",
        "resourceShareName": "string",
        "status": "string",
        "statusMessage": "string"
      }
    ],
    "resourceShareInvitationArn": "string",
    "resourceShareName": "string",
    "senderAccountId": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

resourceShareInvitation

An object that contains information about the specified invitation.

Type: [ResourceShareInvitation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ResourceShareInvitationAlreadyAcceptedException

The operation failed because the specified invitation was already accepted.

HTTP Status Code: 400

ResourceShareInvitationAlreadyRejectedException

The operation failed because the specified invitation was already rejected.

HTTP Status Code: 400

ResourceShareInvitationArnNotFoundException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) for an invitation was not found.

HTTP Status Code: 400

ResourceShareInvitationExpiredException

The operation failed because the specified invitation is past its expiration date and time.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

Examples

Note

The examples show the JSON payloads of the request and response pretty printed with white spaces and line breaks for ease of reading.

The following example shows the AWS account 111111111111 accepting a resource share invitation for a resource share that is in the AWS Region us-east-1 and was from 999999999999.

Sample Request

```
POST /acceptresourceshareinvitation HTTP/1.1
Host: ram.us-east-1.amazonaws.com (http://ram.us-east-1.amazonaws.com/)
X-Amz-Date: 20210922T220735Z
Accept-Encoding: identity
User-Agent: <UserAgentString>
Content-Length: <PayloadSizeBytes>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>>

{"resourceShareInvitationArn": "arn:aws:ram:us-east-1:999999999999:resource-share-
invitation/1e3477be-4a95-46b4-bbe0-c400156cd8e6"}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Wed, 22 Sep 2021 22:07:35 GMT
Content-Type: application/json
Content-Length: <PayloadSizeBytes>

{
  "resourceShareInvitation": {
    "invitationTimestamp": 1632348455.62,
    "receiverAccountId": "111111111111",
    "resourceShareArn": "arn:aws:ram:us-east-1:999999999999:resource-
share/27d09b4b-5e12-41d1-a4f2-19ded10982e2",
    "resourceShareInvitationArn": "arn:aws:ram:us-east-1:999999999999:resource-
share-invitation/1e3477be-4a95-46b4-bbe0-c400156cd8e6",
    "resourceShareName": "MyLicenseShare",
    "senderAccountId": "999999999999",
    "status": "ACCEPTED"
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateResourceShare

Adds the specified list of principals and list of resources to a resource share. Principals that already have access to this resource share immediately receive access to the added resources. Newly added principals immediately receive access to the resources shared in this resource share.

Request Syntax

```
POST /associateresourceshare HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "principals": [ "string" ],
  "resourceArns": [ "string" ],
  "resourceShareArn": "string",
  "sources": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share that you want to add principals or resources to.

Type: String

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you

also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

[principals](#)

Specifies a list of principals to whom you want to the resource share. This can be null if you want to add only resources.

What the principals can do with the resources in the share is determined by the AWS RAM permissions that you associate with the resource share. See [AssociateResourceSharePermission](#).

You can include the following values:

- An AWS account ID, for example: 123456789012
- An [Amazon Resource Name \(ARN\)](#) of an organization in AWS Organizations, for example: `arn:aws:organizations::123456789012:organization/o-exampleorgid`
- An ARN of an organizational unit (OU) in AWS Organizations, for example: `arn:aws:organizations::123456789012:ou/o-exampleorgid/ou-examplerootid-exampleouid123`
- An ARN of an IAM role, for example: `arn:aws:iam::123456789012:role/rolename`
- An ARN of an IAM user, for example: `arn:aws:iam::123456789012:user/username`
- A service principal name, for example: `service-id.amazonaws.com`

Note

Not all resource types can be shared with IAM roles and users. For more information, see [Sharing with IAM roles and users](#) in the *AWS Resource Access Manager User Guide*.

Type: Array of strings

Required: No

resourceArns

Specifies a list of [Amazon Resource Names \(ARNs\)](#) of the resources that you want to share. This can be null if you want to add only principals.

Type: Array of strings

Required: No

sources

Specifies from which source accounts the service principal has access to the resources in this resource share.

Type: Array of strings

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "resourceShareAssociations": [
    {
      "associatedEntity": "string",
      "associationType": "string",
      "creationTime": number,
      "external": boolean,
      "lastUpdatedTime": number,
      "resourceShareArn": "string",
      "resourceShareName": "string",
      "status": "string",
      "statusMessage": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

resourceShareAssociations

An array of objects that contain information about the associations.

Type: Array of [ResourceShareAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidStateTransitionException

The operation failed because the requested operation isn't valid for the resource share in its current state.

HTTP Status Code: 400

InvalidStateTransitionException

The operation failed because the requested operation isn't valid for the resource share in its current state.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ResourceShareLimitExceededException

The operation failed because it would exceed the limit for resource shares for your account. You can associate up to 100 resources per call. To view the limits for your AWS account, see the [AWS RAM page in the Service Quotas console](#).

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

ThrottlingException

The operation failed because it exceeded the rate at which you are allowed to perform this operation. Please try again later.

HTTP Status Code: 429

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

Examples

Note

The examples show the JSON payloads of the request and response pretty printed with white spaces and line breaks for ease of reading.

Example 1: add a principal to a resource share

The following example illustrates adding an organizational unit (OU) as a principal to a resource share that exists in the AWS Region `us-east-1`. After running this command, all AWS accounts in the specified OU can access the resources in the resource share.

Sample Request

```
POST /associateresourceshare HTTP/1.1
Accept-Encoding: identity
User-Agent: <UserAgentString>
Content-Length: <PayloadSizeBytes>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>>
X-Amz-Date: 20210923T200946Z

{
  "principals": [
    "arn:aws:organizations::999999999999:ou/o-12345abcde/ou-12ab-1234abcd"
  ],
```

```
"resourceShareArn": "arn:aws:ram:us-east-1:999999999999:resource-
share/27d09b4b-5e12-41d1-a4f2-19ded10982e2"
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Thu, 23 Sep 2021 20:09:46 GMT
Content-Type: application/json
Content-Length: <PayloadSizeBytes>

{
  "resourceShareAssociations": [
    {
      "associatedEntity": "arn:aws:organizations::999999999999:ou/o-12345abcde/
ou-12ab-1234abcd",
      "associationType": "PRINCIPAL",
      "external": false,
      "resourceShareArn": "arn:aws:ram:us-east-1:999999999999:resource-
share/27d09b4b-5e12-41d1-a4f2-19ded10982e2",
      "status": "ASSOCIATING"
    }
  ]
}
```

Example 2: Add a new resource to a resource share

The following example illustrates adding an additional AWS License Manager configuration to a resource share. After running this command, all AWS accounts that can access the resource share can use the new resource.

Sample Request

```
POST /associateresourceshare HTTP/1.1
Accept-Encoding: identity
User-Agent: <UserAgentString>
Content-Length: <PayloadSizeBytes>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>>
X-Amz-Date: 20210924T190541Z
{
```

```
{
  "resourceShareArn": "arn:aws:ram:us-east-1:999999999999:resource-
share/27d09b4b-5e12-41d1-a4f2-19ded10982e2",
  "resourceArns": [
    "arn:aws:license-manager:us-east-1:999999999999:license-
configuration:lic-36be0485f5ae379cc74cf8e9242ab143"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 24 Sep 2021 19:05:42 GMT
Content-Type: application/json
Content-Length: <PayloadSizeBytes>

{
  "resourceShareAssociations": [
    {
      "associatedEntity": "arn:aws:license-manager:us-
east-1:999999999999:license-configuration:lic-36be0485f5ae379cc74cf8e9242ab143",
      "associationType": "RESOURCE",
      "external": false,
      "resourceShareArn": "arn:aws:ram:us-east-1:999999999999:resource-
share/27d09b4b-5e12-41d1-a4f2-19ded10982e2",
      "status": "ASSOCIATING"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateResourceSharePermission

Adds or replaces the AWS RAM permission for a resource type included in a resource share. You can have exactly one permission associated with each resource type in the resource share. You can add a new AWS RAM permission only if there are currently no resources of that resource type currently in the resource share.

Request Syntax

```
POST /associateresourcesharepermission HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "permissionArn": "string",
  "permissionVersion": number,
  "replace": boolean,
  "resourceShareArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

permissionArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the AWS RAM permission to associate with the resource share. To find the ARN for a permission, use either the [ListPermissions](#) operation or go to the [Permissions library](#) page in the AWS RAM console and then choose the name of the permission. The ARN is displayed on the detail page.

Type: String

Required: Yes

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share to which you want to add or replace permissions.

Type: String

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

permissionVersion

Specifies the version of the AWS RAM permission to associate with the resource share. You can specify *only* the version that is currently set as the default version for the permission. If you also set the `replace` parameter to `true`, then this operation updates an outdated version of the permission to the current default version.

Note

You don't need to specify this parameter because the default behavior is to use the version that is currently set as the default version for the permission. This parameter is supported for backwards compatibility.

Type: Integer

Required: No

replace

Specifies whether the specified permission should replace the existing permission associated with the resource share. Use `true` to replace the current permissions. Use `false` to add the permission to a resource share that currently doesn't have a permission. The default value is `false`.

Note

A resource share can have only one permission per resource type. If a resource share already has a permission for the specified resource type and you don't set `replace` to `true` then the operation returns an error. This helps prevent accidental overwriting of a permission.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken`

request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

returnValue

A return value of `true` indicates that the request succeeded. A value of `false` indicates that the request failed.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

Examples

Note

The examples show the JSON payloads of the request and response pretty printed with white spaces and line breaks for ease of reading.

Example

The following example command replaces the permission for the relevant resource type in the specified resource share. You don't need to specify the resource type, it is automatically inferred from the specified permission.

Sample Request

```
POST /associateresourcesharepermission HTTP/1.1
X-Amz-Date: 20210924T194101Z
Accept-Encoding: identity
User-Agent: <UserAgentString>
Content-Length: <PayloadSizeBytes>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>>

{
  "resourceShareArn": "arn:aws:ram:us-east-1:999999999999:resource-
share/27d09b4b-5e12-41d1-a4f2-19dedEXAMPLE",
```

```
"permissionArn": "arn:aws:ram::aws:permission/
AWSRAMPermissionGlueDatabaseReadWrite",
  "replace": true
}
```

Sample Response

```
HTTP/1.1 200 OK
Date: Fri, 24 Sep 2021 19:41:02 GMT
Content-Type: application/json
Content-Length: <PayloadSizeBytes>

{
  "returnValue":true
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePermission

Creates a customer managed permission for a specified resource type that you can attach to resource shares. It is created in the AWS Region in which you call the operation.

Request Syntax

```
POST /createpermission HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "name": "string",
  "policyTemplate": "string",
  "resourceType": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

name

Specifies the name of the customer managed permission. The name must be unique within the AWS Region.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 36.

Pattern: `[\w.-]*`

Required: Yes

policyTemplate

A string in JSON format string that contains the following elements of a resource-based policy:

- **Effect:** must be set to ALLOW.
- **Action:** specifies the actions that are allowed by this customer managed permission. The list must contain only actions that are supported by the specified resource type. For a list of all actions supported by each resource type, see [Actions, resources, and condition keys for AWS services](#) in the *AWS Identity and Access Management User Guide*.
- **Condition:** (optional) specifies conditional parameters that must evaluate to true when a user attempts an action for that action to be allowed. For more information about the Condition element, see [IAM policies: Condition element](#) in the *AWS Identity and Access Management User Guide*.

This template can't include either the Resource or Principal elements. Those are both filled in by AWS RAM when it instantiates the resource-based policy on each resource shared using this managed permission. The Resource comes from the ARN of the specific resource that you are sharing. The Principal comes from the list of identities added to the resource share.

Type: String

Required: Yes

resourceType

Specifies the name of the resource type that this customer managed permission applies to.

The format is `<service-code>:<resource-type>` and is not case sensitive. For example, to specify an Amazon EC2 Subnet, you can use the string `ec2:subnet`. To see the list of valid values for this parameter, query the [ListResourceTypes](#) operation.

Type: String

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you

also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

[tags](#)

Specifies a list of one or more tag key and value pairs to attach to the permission.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "clientToken": "string",
  "permission": {
    "arn": "string",
    "creationTime": number,
    "defaultVersion": boolean,
    "featureSet": "string",
    "isResourceTypeDefault": boolean,
    "lastUpdatedTime": number,
    "name": "string",
    "permissionType": "string",
    "resourceType": "string",
    "status": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  }
}
```

```
    ],  
    "version": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

permission

A structure with information about this customer managed permission.

Type: [ResourceSharePermissionSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidPolicyException

The operation failed because a policy you specified isn't valid.

HTTP Status Code: 400

MalformedPolicyTemplateException

The operation failed because the policy template that you provided isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

PermissionAlreadyExistsException

The operation failed because a permission with the specified name already exists in the requested AWS Region. Choose a different name.

HTTP Status Code: 409

PermissionLimitExceededException

The operation failed because it would exceed the maximum number of permissions you can create in each AWS Region. To view the limits for your AWS account, see the [AWS RAM page in the Service Quotas console](#).

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePermissionVersion

Creates a new version of the specified customer managed permission. The new version is automatically set as the default version of the customer managed permission. New resource shares automatically use the default permission. Existing resource shares continue to use their original permission versions, but you can use [ReplacePermissionAssociations](#) to update them.

If the specified customer managed permission already has the maximum of 5 versions, then you must delete one of the existing versions before you can create a new one.

Request Syntax

```
POST /createpermissionversion HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "permissionArn": "string",
  "policyTemplate": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[permissionArn](#)

Specifies the [Amazon Resource Name \(ARN\)](#) of the customer managed permission you're creating a new version for.

Type: String

Required: Yes

[policyTemplate](#)

A string in JSON format string that contains the following elements of a resource-based policy:

- **Effect:** must be set to ALLOW.
- **Action:** specifies the actions that are allowed by this customer managed permission. The list must contain only actions that are supported by the specified resource type. For a list of all actions supported by each resource type, see [Actions, resources, and condition keys for AWS services](#) in the *AWS Identity and Access Management User Guide*.
- **Condition:** (optional) specifies conditional parameters that must evaluate to true when a user attempts an action for that action to be allowed. For more information about the Condition element, see [IAM policies: Condition element](#) in the *AWS Identity and Access Management User Guide*.

This template can't include either the `Resource` or `Principal` elements. Those are both filled in by AWS RAM when it instantiates the resource-based policy on each resource shared using this managed permission. The `Resource` comes from the ARN of the specific resource that you are sharing. The `Principal` comes from the list of identities added to the resource share.

Type: String

Required: Yes

[clientToken](#)

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "clientToken": "string",
  "permission": {
    "arn": "string",
    "creationTime": number,
    "defaultVersion": boolean,
    "featureSet": "string",
    "isResourceTypeDefault": boolean,
    "lastUpdatedTime": number,
    "name": "string",
    "permission": "string",
    "permissionType": "string",
    "resourceType": "string",
    "status": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "version": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

permission

Information about a AWS RAM managed permission.

Type: [ResourceSharePermissionDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidPolicyException

The operation failed because a policy you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

MalformedPolicyTemplateException

The operation failed because the policy template that you provided isn't valid.

HTTP Status Code: 400

PermissionVersionsLimitExceededException

The operation failed because it would exceed the limit for the number of versions you can have for a permission. To view the limits for your AWS account, see the [AWS RAM page in the Service Quotas console](#).

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResourceShare

Creates a resource share. You can provide a list of the [Amazon Resource Names \(ARNs\)](#) for the resources that you want to share, a list of principals you want to share the resources with, and the permissions to grant those principals.

Note

Sharing a resource makes it available for use by principals outside of the AWS account that created the resource. Sharing doesn't change any permissions or quotas that apply to the resource in the account that created it.

Request Syntax

```
POST /createresourceshare HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "allowExternalPrincipals": boolean,
  "clientToken": "string",
  "name": "string",
  "permissionArns": [ "string" ],
  "principals": [ "string" ],
  "resourceArns": [ "string" ],
  "sources": [ "string" ],
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

name

Specifies the name of the resource share.

Type: String

Required: Yes

allowExternalPrincipals

Specifies whether principals outside your organization in AWS Organizations can be associated with a resource share. A value of `true` lets you share with individual AWS accounts that are *not* in your organization. A value of `false` only has meaning if your account is a member of an AWS Organization. The default value is `true`.

Type: Boolean

Required: No

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

permissionArns

Specifies the [Amazon Resource Names \(ARNs\)](#) of the AWS RAM permission to associate with the resource share. If you do not specify an ARN for the permission, AWS RAM automatically attaches the default version of the permission for each resource type. You can associate only one permission with each resource type included in the resource share.

Type: Array of strings

Required: No

principals

Specifies a list of one or more principals to associate with the resource share.

You can include the following values:

- An AWS account ID, for example: 123456789012
- An [Amazon Resource Name \(ARN\)](#) of an organization in AWS Organizations, for example: `arn:aws:organizations::123456789012:organization/o-exampleorgid`
- An ARN of an organizational unit (OU) in AWS Organizations, for example: `arn:aws:organizations::123456789012:ou/o-exampleorgid/ou-examplerootid-exampleouid123`
- An ARN of an IAM role, for example: `arn:aws:iam::123456789012:role/rolename`
- An ARN of an IAM user, for example: `arn:aws:iam::123456789012:user/username`
- A service principal name, for example: `service-id.amazonaws.com`

Note

Not all resource types can be shared with IAM roles and users. For more information, see [Sharing with IAM roles and users](#) in the *AWS Resource Access Manager User Guide*.

Type: Array of strings

Required: No

resourceArns

Specifies a list of one or more ARNs of the resources to associate with the resource share.

Type: Array of strings

Required: No

sources

Specifies from which source accounts the service principal has access to the resources in this resource share.

Type: Array of strings

Required: No

tags

Specifies one or more tags to attach to the resource share itself. It doesn't attach the tags to the resources associated with the resource share.

Type: Array of [Tag](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "resourceShare": {
    "allowExternalPrincipals": boolean,
    "creationTime": number,
    "featureSet": "string",
    "lastUpdatedTime": number,
    "name": "string",
    "owningAccountId": "string",
    "resourceShareArn": "string",
    "status": "string",
    "statusMessage": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ]
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

resourceShare

An object with information about the new resource share.

Type: [ResourceShare](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidStateTransitionException

The operation failed because the requested operation isn't valid for the resource share in its current state.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ResourceShareLimitExceededException

The operation failed because it would exceed the limit for resource shares for your account. You can associate up to 100 resources per call. To view the limits for your AWS account, see the [AWS RAM page in the Service Quotas console](#).

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

TagPolicyViolationException

The operation failed because the specified tag key is a reserved word and can't be used.

HTTP Status Code: 400

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePermission

Deletes the specified customer managed permission in the AWS Region in which you call this operation. You can delete a customer managed permission only if it isn't attached to any resource share. The operation deletes all versions associated with the customer managed permission.

Request Syntax

```
DELETE /deletepermission?clientToken=clientToken&permissionArn=permissionArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an IdempotentParameterMismatch error.

permissionArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the customer managed permission that you want to delete.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "clientToken": "string",
  "permissionStatus": "string",
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

[permissionStatus](#)

This operation is performed asynchronously, and this response parameter indicates the current status.

Type: String

Valid Values: ATTACHABLE | UNATTACHABLE | DELETING | DELETED

[returnValue](#)

A boolean that indicates whether the delete operations succeeded.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePermissionVersion

Deletes one version of a customer managed permission. The version you specify must not be attached to any resource share and must not be the default version for the permission.

If a customer managed permission has the maximum of 5 versions, then you must delete at least one version before you can create another.

Request Syntax

```
DELETE /deletepermissionversion?  
clientToken=clientToken&permissionArn=permissionArn&permissionVersion=permissionVersion  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an IdempotentParameterMismatch error.

permissionArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the permission with the version you want to delete.

Required: Yes

permissionVersion

Specifies the version number to delete.

You can't delete the default version for a customer managed permission.

You can't delete a version if it's the only version of the permission. You must either first create another version, or delete the permission completely.

You can't delete a version if it is attached to any resource shares. If the version is the default, you must first use [SetDefaultPermissionVersion](#) to set a different version as the default for the customer managed permission, and then use [AssociateResourceSharePermission](#) to update your resource shares to use the new default version.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "permissionStatus": "string",
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

permissionStatus

This operation is performed asynchronously, and this response parameter indicates the current status.

Type: String

Valid Values: ATTACHABLE | UNATTACHABLE | DELETING | DELETED

returnValue

A boolean value that indicates whether the operation is successful.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourceShare

Deletes the specified resource share.

Important

This doesn't delete any of the resources that were associated with the resource share; it only stops the sharing of those resources through this resource share.

Request Syntax

```
DELETE /deleteresourceshare?clientToken=clientToken&resourceShareArn=resourceShareArn  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an IdempotentParameterMismatch error.

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share to delete.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

returnValue

A return value of `true` indicates that the request succeeded. A value of `false` indicates that the request failed.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidStateTransitionException

The operation failed because the requested operation isn't valid for the resource share in its current state.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateResourceShare

Removes the specified principals or resources from participating in the specified resource share.

Request Syntax

```
POST /disassociateresourceshare HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "principals": [ "string" ],
  "resourceArns": [ "string" ],
  "resourceShareArn": "string",
  "sources": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceShareArn

Specifies [Amazon Resource Name \(ARN\)](#) of the resource share that you want to remove resources or principals from.

Type: String

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

principals

Specifies a list of one or more principals that no longer are to have access to the resources in this resource share.

You can include the following values:

- An AWS account ID, for example: 123456789012
- An [Amazon Resource Name \(ARN\)](#) of an organization in AWS Organizations, for example: `arn:aws:organizations::123456789012:organization/o-exampleorgid`
- An ARN of an organizational unit (OU) in AWS Organizations, for example: `arn:aws:organizations::123456789012:ou/o-exampleorgid/ou-examplepleroootid-exampleouid123`
- An ARN of an IAM role, for example: `arn:aws:iam::123456789012:role/rolename`
- An ARN of an IAM user, for example: `arn:aws:iam::123456789012:user/username`
- A service principal name, for example: `service-id.amazonaws.com`

Note

Not all resource types can be shared with IAM roles and users. For more information, see [Sharing with IAM roles and users](#) in the *AWS Resource Access Manager User Guide*.

Type: Array of strings

Required: No

resourceArns

Specifies a list of [Amazon Resource Names \(ARNs\)](#) for one or more resources that you want to remove from the resource share. After the operation runs, these resources are no longer shared with principals associated with the resource share.

Type: Array of strings

Required: No

[sources](#)

Specifies from which source accounts the service principal no longer has access to the resources in this resource share.

Type: Array of strings

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "resourceShareAssociations": [
    {
      "associatedEntity": "string",
      "associationType": "string",
      "creationTime": number,
      "external": boolean,
      "lastUpdatedTime": number,
      "resourceShareArn": "string",
      "resourceShareName": "string",
      "status": "string",
      "statusMessage": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[clientToken](#)

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken`

request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

resourceShareAssociations

An array of objects with information about the updated associations for this resource share.

Type: Array of [ResourceShareAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidStateTransitionException

The operation failed because the requested operation isn't valid for the resource share in its current state.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ResourceShareLimitExceededException

The operation failed because it would exceed the limit for resource shares for your account. You can associate up to 100 resources per call. To view the limits for your AWS account, see the [AWS RAM page in the Service Quotas console](#).

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateResourceSharePermission

Removes a managed permission from a resource share. Permission changes take effect immediately. You can remove a managed permission from a resource share only if there are currently no resources of the relevant resource type currently attached to the resource share.

Request Syntax

```
POST /disassociateresourcesharepermission HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "permissionArn": "string",
  "resourceShareArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

permissionArn

The [Amazon Resource Name \(ARN\)](#) of the managed permission to disassociate from the resource share. Changes to permissions take effect immediately.

Type: String

Required: Yes

resourceShareArn

The [Amazon Resource Name \(ARN\)](#) of the resource share that you want to remove the managed permission from.

Type: String

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

returnValue

A return value of `true` indicates that the request succeeded. A value of `false` indicates that the request failed.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidStateTransitionException

The operation failed because the requested operation isn't valid for the resource share in its current state.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

EnableSharingWithAwsOrganization

Enables resource sharing within your organization in AWS Organizations. This operation creates a service-linked role called `AWSServiceRoleForResourceAccessManager` that has the IAM managed policy named `AWSResourceAccessManagerServiceRolePolicy` attached. This role permits AWS RAM to retrieve information about the organization and its structure. This lets you share resources with all of the accounts in the calling account's organization by specifying the organization ID, or all of the accounts in an organizational unit (OU) by specifying the OU ID. Until you enable sharing within the organization, you can specify only individual AWS accounts, or for supported resource types, IAM roles and users.

You must call this operation from an IAM role or user in the organization's management account.

Request Syntax

```
POST /enablessharingwithawsorganization HTTP/1.1
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

returnValue

A return value of `true` indicates that the request succeeded. A value of `false` indicates that the request failed.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetPermission

Retrieves the contents of a managed permission in JSON format.

Request Syntax

```
POST /getpermission HTTP/1.1
Content-type: application/json

{
  "permissionArn": "string",
  "permissionVersion": number
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[permissionArn](#)

Specifies the [Amazon Resource Name \(ARN\)](#) of the permission whose contents you want to retrieve. To find the ARN for a permission, use either the [ListPermissions](#) operation or go to the [Permissions library](#) page in the AWS RAM console and then choose the name of the permission. The ARN is displayed on the detail page.

Type: String

Required: Yes

[permissionVersion](#)

Specifies the version number of the AWS RAM permission to retrieve. If you don't specify this parameter, the operation retrieves the default version.

To see the list of available versions, use [ListPermissionVersions](#).

Type: Integer

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "permission": {
    "arn": "string",
    "creationTime": number,
    "defaultVersion": boolean,
    "featureSet": "string",
    "isResourceTypeDefault": boolean,
    "lastUpdatedTime": number,
    "name": "string",
    "permission": "string",
    "permissionType": "string",
    "resourceType": "string",
    "status": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "version": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

permission

An object with details about the permission.

Type: [ResourceSharePermissionDetail](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourcePolicies

Retrieves the resource policies for the specified resources that you own and have shared.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /getresourcepolicies HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "principal": "string",
  "resourceArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceArns

Specifies the [Amazon Resource Names \(ARNs\)](#) of the resources whose policies you want to retrieve.

Type: Array of strings

Required: Yes

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

principal

Specifies the principal.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "nextToken": "string",  
  "policies": [ "string" ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

policies

An array of resource policy documents in JSON format.

Type: Array of strings

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for NextToken isn't valid. You must specify a value you received in the NextToken response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ResourceArnNotFoundException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) was not found.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V3](#)

GetResourceShareAssociations

Retrieves the lists of resources and principals that associated for resource shares that you own.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /getresourceshareassociations HTTP/1.1
Content-type: application/json
```

```
{
  "associationStatus": "string",
  "associationType": "string",
  "maxResults": number,
  "nextToken": "string",
  "principal": "string",
  "resourceArn": "string",
  "resourceShareArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

associationType

Specifies whether you want to retrieve the associations that involve a specified resource or principal.

- **PRINCIPAL** – list the principals whose associations you want to see.

- RESOURCE – list the resources whose associations you want to see.

Type: String

Valid Values: PRINCIPAL | RESOURCE

Required: Yes

associationStatus

Specifies that you want to retrieve only associations that have this status.

Type: String

Valid Values: ASSOCIATING | ASSOCIATED | FAILED | DISASSOCIATING | DISASSOCIATED

Required: No

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Required: No

principal

Specifies the ID of the principal whose resource shares you want to retrieve. This can be an AWS account ID, an organization ID, an organizational unit ID, or the [Amazon Resource Name \(ARN\)](#) of an individual IAM role or user.

You cannot specify this parameter if the association type is RESOURCE.

Type: String

Required: No

resourceArn

Specifies the [Amazon Resource Name \(ARN\)](#) of a resource whose resource shares you want to retrieve.

You cannot specify this parameter if the association type is PRINCIPAL.

Type: String

Required: No

resourceShareArns

Specifies a list of [Amazon Resource Names \(ARNs\)](#) of the resource share whose associations you want to retrieve.

Type: Array of strings

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "resourceShareAssociations": [
    {
```

```
"associatedEntity": "string",  
"associationType": "string",  
"creationTime": number,  
"external": boolean,  
"lastUpdatedTime": number,  
"resourceShareArn": "string",  
"resourceShareName": "string",  
"status": "string",  
"statusMessage": "string"  
}  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

resourceShareAssociations

An array of objects that contain the details about the associations.

Type: Array of [ResourceShareAssociation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for NextToken isn't valid. You must specify a value you received in the NextToken response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourceShareInvitations

Retrieves details about invitations that you have received for resource shares.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /getresourceshareinvitations HTTP/1.1
Content-type: application/json

{
  "maxResults": number,
  "nextToken": "string",
  "resourceShareArns": [ "string" ],
  "resourceShareInvitationArns": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that

the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

[nextToken](#)

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

[resourceShareArns](#)

Specifies that you want details about invitations only for the resource shares described by this list of [Amazon Resource Names \(ARNs\)](#)

Type: Array of strings

Required: No

[resourceShareInvitationArns](#)

Specifies the [Amazon Resource Names \(ARNs\)](#) of the resource share invitations you want information about.

Type: Array of strings

Required: No

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "nextToken": "string",
  "resourceShareInvitations": [
    {
      "invitationTimestamp": number,
      "receiverAccountId": "string",
      "receiverArn": "string",
      "resourceShareArn": "string",
      "resourceShareAssociations": [
        {
          "associatedEntity": "string",
          "associationType": "string",
          "creationTime": number,
          "external": boolean,
          "lastUpdatedTime": number,
          "resourceShareArn": "string",
          "resourceShareName": "string",
          "status": "string",
          "statusMessage": "string"
        }
      ],
      "resourceShareInvitationArn": "string",
      "resourceShareName": "string",
      "senderAccountId": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

resourceShareInvitations

An array of objects that contain the details about the invitations.

Type: Array of [ResourceShareInvitation](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidMaxResultsException

The operation failed because the specified value for `MaxResults` isn't valid.

HTTP Status Code: 400

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ResourceShareInvitationArnNotFoundException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) for an invitation was not found.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

Examples

Note

The examples show the JSON payloads of the request and response pretty printed with white spaces and line breaks for ease of reading.

Example

The following example shows an AWS account 111111111111 retrieving a list of its currently available invitations in the us-east-1 Region. The response includes one PENDING invitation from AWS account 999999999999.

Sample Request

```
POST /getresourceshareinvitations HTTP/1.1
Host: ram.us-east-1.amazonaws.com
Accept-Encoding: identity
User-Agent: <UserAgentString>
Content-Length: <PayloadSizeBytes>
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
  Signature=<Signature>>
```

Sample Response

```
HTTP/1.1 200 OK
Date: Wed, 22 Sep 2021 21:11:46 GMT
Content-Type: application/json
Content-Length: <PayloadSizeBytes>

{
  "resourceShareInvitations": [
    {
      "invitationTimestamp": 1632342984.382,
      "receiverAccountId": "111111111111",
      "resourceShareArn": "arn:aws:ram:us-east-1:999999999999:resource-
share/27d09b4b-5e12-41d1-a4f2-19ded10982e2",
      "resourceShareInvitationArn": "arn:aws:ram:us-east-1:999999999999:resource-
share-invitation/1e3477be-4a95-46b4-bbe0-c400156cd8e6",
      "resourceShareName": "MyLicenseShare",
      "senderAccountId": "999999999999",
      "status": "PENDING"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourceShares

Retrieves details about the resource shares that you own or that are shared with you.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /getresourceshares HTTP/1.1
Content-type: application/json

{
  "maxResults": number,
  "name": "string",
  "nextToken": "string",
  "permissionArn": "string",
  "permissionVersion": number,
  "resourceOwner": "string",
  "resourceShareArns": [ "string" ],
  "resourceShareStatus": "string",
  "tagFilters": [
    {
      "tagKey": "string",
      "tagValues": [ "string" ]
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceOwner

Specifies that you want to retrieve details of only those resource shares that match the following:

- **SELF** – resource shares that your account shares with other accounts
- **OTHER-ACCOUNTS** – resource shares that other accounts share with your account

Type: String

Valid Values: SELF | OTHER-ACCOUNTS

Required: Yes

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

name

Specifies the name of an individual resource share that you want to retrieve details about.

Type: String

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

permissionArn

Specifies that you want to retrieve details of only those resource shares that use the managed permission with this [Amazon Resource Name \(ARN\)](#).

Type: String

Required: No

permissionVersion

Specifies that you want to retrieve details for only those resource shares that use the specified version of the managed permission.

Type: Integer

Required: No

resourceShareArns

Specifies the [Amazon Resource Names \(ARNs\)](#) of individual resource shares that you want information about.

Type: Array of strings

Required: No

resourceShareStatus

Specifies that you want to retrieve details of only those resource shares that have this status.

Type: String

Valid Values: PENDING | ACTIVE | FAILED | DELETING | DELETED

Required: No

tagFilters

Specifies that you want to retrieve details of only those resource shares that match the specified tag keys and values.

Type: Array of [TagFilter](#) objects

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "resourceShares": [
    {
      "allowExternalPrincipals": boolean,
      "creationTime": number,
      "featureSet": "string",
      "lastUpdatedTime": number,
      "name": "string",
      "owningAccountId": "string",
      "resourceShareArn": "string",
      "status": "string",
      "statusMessage": "string",
      "tags": [
        {
          "key": "string",
          "value": "string"
        }
      ]
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the

operation to get the next part of the output. You should repeat this until the `NextToken` response element comes back as `null`. This indicates that this is the last page of results.

Type: String

[resourceShares](#)

An array of objects that contain the information about the resource shares.

Type: Array of [ResourceShare](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPendingInvitationResources

Lists the resources in a resource share that is shared with you but for which the invitation is still PENDING. That means that you haven't accepted or rejected the invitation and the invitation hasn't expired.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listpendinginvitationresources HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "resourceRegionScope": "string",
  "resourceShareInvitationArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceShareInvitationArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the invitation. You can use [GetResourceShareInvitations](#) to find the ARN of the invitation.

Type: String

Required: Yes

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

resourceRegionScope

Specifies that you want the results to include only resources that have the specified scope.

- ALL – the results include both global and regional resources or resource types.
- GLOBAL – the results include only global resources or resource types.
- REGIONAL – the results include only regional resources or resource types.

The default value is ALL.

Type: String

Valid Values: ALL | REGIONAL | GLOBAL

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "resources": [
    {
      "arn": "string",
      "creationTime": number,
      "lastUpdatedTime": number,
      "resourceGroupArn": "string",
      "resourceRegionScope": "string",
      "resourceShareArn": "string",
      "status": "string",
      "statusMessage": "string",
      "type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

resources

An array of objects that contain the information about the resources included the specified resource share.

Type: Array of [Resource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for NextToken isn't valid. You must specify a value you received in the NextToken response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

MissingRequiredParameterException

The operation failed because a required input parameter is missing.

HTTP Status Code: 400

ResourceShareInvitationAlreadyRejectedException

The operation failed because the specified invitation was already rejected.

HTTP Status Code: 400

ResourceShareInvitationArnNotFoundException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) for an invitation was not found.

HTTP Status Code: 400

ResourceShareInvitationExpiredException

The operation failed because the specified invitation is past its expiration date and time.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPermissionAssociations

Lists information about the managed permission and its associations to any resource shares that use this managed permission. This lets you see which resource shares use which versions of the specified managed permission.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listpermissionassociations HTTP/1.1
Content-type: application/json
```

```
{
  "associationStatus": "string",
  "defaultVersion": boolean,
  "featureSet": "string",
  "maxResults": number,
  "nextToken": "string",
  "permissionArn": "string",
  "permissionVersion": number,
  "resourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

associationStatus

Specifies that you want to list only those associations with resource shares that match this status.

Type: String

Valid Values: ASSOCIATING | ASSOCIATED | FAILED | DISASSOCIATING | DISASSOCIATED

Required: No

defaultVersion

When `true`, specifies that you want to list only those associations with resource shares that use the default version of the specified managed permission.

When `false` (the default value), lists associations with resource shares that use any version of the specified managed permission.

Type: Boolean

Required: No

featureSet

Specifies that you want to list only those associations with resource shares that have a `featureSet` with this value.

Type: String

Valid Values: CREATED_FROM_POLICY | PROMOTING_TO_STANDARD | STANDARD

Required: No

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results

available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

[nextToken](#)

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

[permissionArn](#)

Specifies the [Amazon Resource Name \(ARN\)](#) of the managed permission.

Type: String

Required: No

[permissionVersion](#)

Specifies that you want to list only those associations with resource shares that use this version of the managed permission. If you don't provide a value for this parameter, then the operation returns information about associations with resource shares that use any version of the managed permission.

Type: Integer

Required: No

[resourceType](#)

Specifies that you want to list only those associations with resource shares that include at least one resource of this resource type.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "permissions": [
    {
      "arn": "string",
      "defaultVersion": boolean,
      "featureSet": "string",
      "lastUpdatedTime": number,
      "permissionVersion": "string",
      "resourceShareArn": "string",
      "resourceType": "string",
      "status": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

permissions

A structure with information about this customer managed permission.

Type: Array of [AssociatedPermission](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPermissions

Retrieves a list of available AWS RAM permissions that you can use for the supported resource types.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listpermissions HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "permissionType": "string",
  "resourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request

parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

[nextToken](#)

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

[permissionType](#)

Specifies that you want to list only permissions of this type:

- `AWS` – returns only AWS managed permissions.
- `LOCAL` – returns only customer managed permissions
- `ALL` – returns both AWS managed permissions and customer managed permissions.

If you don't specify this parameter, the default is `ALL`.

Type: String

Valid Values: `ALL` | `AWS_MANAGED` | `CUSTOMER_MANAGED`

Required: No

[resourceType](#)

Specifies that you want to list only those permissions that apply to the specified resource type. This parameter is not case sensitive.

For example, to list only permissions that apply to Amazon EC2 subnets, specify `ec2:subnet`. You can use the [ListResourceTypes](#) operation to get the specific string required.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "permissions": [
    {
      "arn": "string",
      "creationTime": number,
      "defaultVersion": boolean,
      "featureSet": "string",
      "isResourceTypeDefault": boolean,
      "lastUpdatedTime": number,
      "name": "string",
      "permissionType": "string",
      "resourceType": "string",
      "status": "string",
      "tags": [
        {
          "key": "string",
          "value": "string"
        }
      ],
      "version": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the `NextToken` request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the `NextToken` response element comes back as `null`. This indicates that this is the last page of results.

Type: String

permissions

An array of objects with information about the permissions.

Type: Array of [ResourceSharePermissionSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPermissionVersions

Lists the available versions of the specified AWS RAM permission.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listpermissionversions HTTP/1.1
Content-type: application/json

{
  "maxResults": number,
  "nextToken": "string",
  "permissionArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

permissionArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the AWS RAM permission whose versions you want to list. You can use the `permissionVersion` parameter on the [AssociateResourceSharePermission](#) operation to specify a non-default version to attach.

Type: String

Required: Yes

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "permissions": [
    {
      "arn": "string",
      "creationTime": number,
      "defaultVersion": boolean,
      "featureSet": "string",
```

```
    "isResourceTypeDefault": boolean,
    "lastUpdatedTime": number,
    "name": "string",
    "permissionType": "string",
    "resourceType": "string",
    "status": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "version": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the `NextToken` request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the `NextToken` response element comes back as `null`. This indicates that this is the last page of results.

Type: String

[permissions](#)

An array of objects that contain details for each of the available versions.

Type: Array of [ResourceSharePermissionSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPrincipals

Lists the principals that you are sharing resources with or that are sharing resources with you.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listprincipals HTTP/1.1
Content-type: application/json

{
  "maxResults": number,
  "nextToken": "string",
  "principals": [ "string" ],
  "resourceArn": "string",
  "resourceOwner": "string",
  "resourceShareArns": [ "string" ],
  "resourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceOwner

Specifies that you want to list information for only resource shares that match the following:

- **SELF** – principals that your account is sharing resources with

- **OTHER-ACCOUNTS** – principals that are sharing resources with your account

Type: String

Valid Values: SELF | OTHER-ACCOUNTS

Required: Yes

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

principals

Specifies that you want to list information for only the listed principals.

You can include the following values:

- An AWS account ID, for example: 123456789012

- An [Amazon Resource Name \(ARN\)](#) of an organization in AWS Organizations, for example: `arn:aws:organizations::123456789012:organization/o-exampleorgid`
- An ARN of an organizational unit (OU) in AWS Organizations, for example: `arn:aws:organizations::123456789012:ou/o-exampleorgid/ou-examplerootid-exampleouid123`
- An ARN of an IAM role, for example: `arn:aws:iam::123456789012:role/rolename`
- An ARN of an IAM user, for example: `arn:aws:iam::123456789012:user/username`
- A service principal name, for example: `service-id.amazonaws.com`

Note

Not all resource types can be shared with IAM roles and users. For more information, see [Sharing with IAM roles and users](#) in the *AWS Resource Access Manager User Guide*.

Type: Array of strings

Required: No

[resourceArn](#)

Specifies that you want to list principal information for the resource share with the specified [Amazon Resource Name \(ARN\)](#).

Type: String

Required: No

[resourceShareArns](#)

Specifies that you want to list information for only principals associated with the resource shares specified by a list the [Amazon Resource Names \(ARNs\)](#).

Type: Array of strings

Required: No

[resourceType](#)

Specifies that you want to list information for only principals associated with resource shares that include the specified resource type.

For a list of valid values, query the [ListResourceTypes](#) operation.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "principals": [
    {
      "creationTime": number,
      "external": boolean,
      "id": "string",
      "lastUpdatedTime": number,
      "resourceShareArn": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

[principals](#)

An array of objects that contain the details about the principals.

Type: Array of [Principal](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListReplacePermissionAssociationsWork

Retrieves the current status of the asynchronous tasks performed by AWS RAM when you perform the [ReplacePermissionAssociationsWork](#) operation.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listreplacepermissionassociationswork HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "status": "string",
  "workIds": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[maxResults](#)

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request

parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

status

Specifies that you want to see only the details about requests with a status that matches this value.

Type: String

Valid Values: `IN_PROGRESS` | `COMPLETED` | `FAILED`

Required: No

workIds

A list of IDs. These values come from the `id` field of the `replacePermissionAssociationsWorkstructure` returned by the [ReplacePermissionAssociations](#) operation.

Type: Array of strings

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "replacePermissionAssociationsWorks": [
    {
      "creationTime": number,
      "fromPermissionArn": "string",
      "fromPermissionVersion": "string",
      "id": "string",
      "lastUpdatedTime": number,
      "status": "string",
      "statusMessage": "string",
      "toPermissionArn": "string",
      "toPermissionVersion": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

[replacePermissionAssociationsWorks](#)

An array of data structures that provide details of the matching work IDs.

Type: Array of [ReplacePermissionAssociationsWork](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for NextToken isn't valid. You must specify a value you received in the NextToken response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResources

Lists the resources that you added to a resource share or the resources that are shared with you.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listresources HTTP/1.1
Content-type: application/json

{
  "maxResults": number,
  "nextToken": "string",
  "principal": "string",
  "resourceArns": [ "string" ],
  "resourceOwner": "string",
  "resourceRegionScope": "string",
  "resourceShareArns": [ "string" ],
  "resourceType": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceOwner

Specifies that you want to list only the resource shares that match the following:

- **SELF** – resources that your account shares with other accounts

- **OTHER-ACCOUNTS** – resources that other accounts share with your account

Type: String

Valid Values: SELF | OTHER-ACCOUNTS

Required: Yes

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Required: No

principal

Specifies that you want to list only the resource shares that are associated with the specified principal.

Type: String

Required: No

resourceArns

Specifies that you want to list only the resource shares that include resources with the specified [Amazon Resource Names \(ARNs\)](#).

Type: Array of strings

Required: No

resourceRegionScope

Specifies that you want the results to include only resources that have the specified scope.

- ALL – the results include both global and regional resources or resource types.
- GLOBAL – the results include only global resources or resource types.
- REGIONAL – the results include only regional resources or resource types.

The default value is ALL.

Type: String

Valid Values: ALL | REGIONAL | GLOBAL

Required: No

resourceShareArns

Specifies that you want to list only resources in the resource shares identified by the specified [Amazon Resource Names \(ARNs\)](#).

Type: Array of strings

Required: No

resourceType

Specifies that you want to list only the resource shares that include resources of the specified resource type.

For valid values, query the [ListResourceTypes](#) operation.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "resources": [
    {
      "arn": "string",
      "creationTime": number,
      "lastUpdatedTime": number,
      "resourceGroupArn": "string",
      "resourceRegionScope": "string",
      "resourceShareArn": "string",
      "status": "string",
      "statusMessage": "string",
      "type": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the NextToken request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the NextToken response element comes back as null. This indicates that this is the last page of results.

Type: String

resources

An array of objects that contain information about the resources.

Type: Array of [Resource](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for NextToken isn't valid. You must specify a value you received in the NextToken response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidResourceTypeException

The operation failed because the specified resource type isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceSharePermissions

Lists the AWS RAM permissions that are associated with a resource share.

Note

Always check the `NextToken` response parameter for a `null` value when calling a paginated operation. These operations can occasionally return an empty set of results even when there are more results available. The `NextToken` response parameter value is `null` *only* when there are no more results to display.

Request Syntax

```
POST /listresourcepermissions HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string",
  "resourceShareArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share for which you want to retrieve the associated permissions.

Type: String

Required: Yes

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the `NextToken` response element is returned with a value (not null). Include the specified value as the `NextToken` request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check `NextToken` after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

nextToken

Specifies that you want to receive the next page of results. Valid only if you received a `NextToken` response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's `NextToken` response to request the next page of results.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "permissions": [
    {
      "arn": "string",
      "creationTime": number,
      "defaultVersion": boolean,
      "featureSet": "string",
```

```
    "isResourceTypeDefault": boolean,
    "lastUpdatedTime": number,
    "name": "string",
    "permissionType": "string",
    "resourceType": "string",
    "status": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "version": "string"
  }
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

If present, this value indicates that more output is available than is included in the current response. Use this value in the `NextToken` request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the `NextToken` response element comes back as `null`. This indicates that this is the last page of results.

Type: String

[permissions](#)

An array of objects that describe the permissions associated with the resource share.

Type: Array of [ResourceSharePermissionSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceTypes

Lists the resource types that can be shared by AWS RAM.

Request Syntax

```
POST /listresourcetypes HTTP/1.1
Content-type: application/json

{
  "maxResults": number,
  "nextToken": "string",
  "resourceRegionScope": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

maxResults

Specifies the total number of results that you want included on each page of the response. If you do not include this parameter, it defaults to a value that is specific to the operation. If additional items exist beyond the number you specify, the NextToken response element is returned with a value (not null). Include the specified value as the NextToken request parameter in the next call to the operation to get the next part of the results. Note that the service might return fewer results than the maximum even when there are more results available. You should check NextToken after every operation to ensure that you receive all of the results.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 500.

Required: No

[nextToken](#)

Specifies that you want to receive the next page of results. Valid only if you received a NextToken response in the previous request. If you did, it indicates that more output is available. Set this parameter to the value provided by the previous call's NextToken response to request the next page of results.

Type: String

Required: No

[resourceRegionScope](#)

Specifies that you want the results to include only resources that have the specified scope.

- ALL – the results include both global and regional resources or resource types.
- GLOBAL – the results include only global resources or resource types.
- REGIONAL – the results include only regional resources or resource types.

The default value is ALL.

Type: String

Valid Values: ALL | REGIONAL | GLOBAL

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "nextToken": "string",
  "resourceTypes": [
    {
      "resourceRegionScope": "string",
      "resourceType": "string",
      "serviceName": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken

If present, this value indicates that more output is available than is included in the current response. Use this value in the `NextToken` request parameter in a subsequent call to the operation to get the next part of the output. You should repeat this until the `NextToken` response element comes back as `null`. This indicates that this is the last page of results.

Type: String

resourceTypes

An array of objects that contain information about the resource types that can be shared using AWS RAM.

Type: Array of [ServiceNameAndResourceType](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidNextTokenException

The operation failed because the specified value for `NextToken` isn't valid. You must specify a value you received in the `NextToken` response of a previous call to this operation.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PromotePermissionCreatedFromPolicy

When you attach a resource-based policy to a resource, AWS RAM automatically creates a resource share of `featureSet=CREATED_FROM_POLICY` with a managed permission that has the same IAM permissions as the original resource-based policy. However, this type of managed permission is visible to only the resource share owner, and the associated resource share can't be modified by using AWS RAM.

This operation creates a separate, fully manageable customer managed permission that has the same IAM permissions as the original resource-based policy. You can associate this customer managed permission to any resource shares.

Before you use [PromoteResourceShareCreatedFromPolicy](#), you should first run this operation to ensure that you have an appropriate customer managed permission that can be associated with the promoted resource share.

Note

- The original `CREATED_FROM_POLICY` policy isn't deleted, and resource shares using that original policy aren't automatically updated.
- You can't modify a `CREATED_FROM_POLICY` resource share so you can't associate the new customer managed permission by using `ReplacePermissionsAssociations`. However, if you use [PromoteResourceShareCreatedFromPolicy](#), that operation automatically associates the fully manageable customer managed permission to the newly promoted `STANDARD` resource share.
- After you promote a resource share, if the original `CREATED_FROM_POLICY` managed permission has no other associations to A resource share, then AWS RAM automatically deletes it.

Request Syntax

```
POST /promotepermissioncreatedfrompolicy HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
```

```
"name": "string",  
"permissionArn": "string"  
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

name

Specifies a name for the promoted customer managed permission.

Type: String

Required: Yes

permissionArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the CREATED_FROM_POLICY permission that you want to promote. You can get this [Amazon Resource Name \(ARN\)](#) by calling the [ListResourceSharePermissions](#) operation.

Type: String

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an IdempotentParameterMismatch error.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "permission": {
    "arn": "string",
    "creationTime": number,
    "defaultVersion": boolean,
    "featureSet": "string",
    "isResourceTypeDefault": boolean,
    "lastUpdatedTime": number,
    "name": "string",
    "permissionType": "string",
    "resourceType": "string",
    "status": "string",
    "tags": [
      {
        "key": "string",
        "value": "string"
      }
    ],
    "version": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken`

request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

[permission](#)

Information about an AWS RAM permission.

Type: [ResourceSharePermissionSummary](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

MissingRequiredParameterException

The operation failed because a required input parameter is missing.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PromoteResourceShareCreatedFromPolicy

When you attach a resource-based policy to a resource, AWS RAM automatically creates a resource share of `featureSet=CREATED_FROM_POLICY` with a managed permission that has the same IAM permissions as the original resource-based policy. However, this type of managed permission is visible to only the resource share owner, and the associated resource share can't be modified by using AWS RAM.

This operation promotes the resource share to a STANDARD resource share that is fully manageable in AWS RAM. When you promote a resource share, you can then manage the resource share in AWS RAM and it becomes visible to all of the principals you shared it with.

Important

Before you perform this operation, you should first run [PromotePermissionCreatedFromPolicy](#) to ensure that you have an appropriate customer managed permission that can be associated with this resource share after its is promoted. If this operation can't find a managed permission that exactly matches the existing `CREATED_FROM_POLICY` permission, then this operation fails.

Request Syntax

```
POST /promoteresharecreatedfrompolicy?resourceShareArn=resourceShareArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share to promote.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[returnValue](#)

A return value of `true` indicates that the request succeeded. A value of `false` indicates that the request failed.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

InvalidStateTransitionException

The operation failed because the requested operation isn't valid for the resource share in its current state.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

MissingRequiredParameterException

The operation failed because a required input parameter is missing.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ResourceShareLimitExceededException

The operation failed because it would exceed the limit for resource shares for your account. You can associate up to 100 resources per call. To view the limits for your AWS account, see the [AWS RAM page in the Service Quotas console](#).

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

UnmatchedPolicyPermissionException

There isn't an existing managed permission defined in AWS RAM that has the same IAM permissions as the resource-based policy attached to the resource. You should first run [PromotePermissionCreatedFromPolicy](#) to create that managed permission.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RejectResourceShareInvitation

Rejects an invitation to a resource share from another AWS account.

Request Syntax

```
POST /rejectresourceinvitation HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "resourceShareInvitationArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[resourceShareInvitationArn](#)

Specifies the [Amazon Resource Name \(ARN\)](#) of the invitation that you want to reject.

Type: String

Required: Yes

[clientToken](#)

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same ClientToken, but with different parameters, the retry fails with an IdempotentParameterMismatch error.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "resourceShareInvitation": {
    "invitationTimestamp": number,
    "receiverAccountId": "string",
    "receiverArn": "string",
    "resourceShareArn": "string",
    "resourceShareAssociations": [
      {
        "associatedEntity": "string",
        "associationType": "string",
        "creationTime": number,
        "external": boolean,
        "lastUpdatedTime": number,
        "resourceShareArn": "string",
        "resourceShareName": "string",
        "status": "string",
        "statusMessage": "string"
      }
    ],
    "resourceShareInvitationArn": "string",
    "resourceShareName": "string",
    "senderAccountId": "string",
    "status": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

resourceShareInvitation

An object that contains the details about the rejected invitation.

Type: [ResourceShareInvitation](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ResourceShareInvitationAlreadyAcceptedException

The operation failed because the specified invitation was already accepted.

HTTP Status Code: 400

ResourceShareInvitationAlreadyRejectedException

The operation failed because the specified invitation was already rejected.

HTTP Status Code: 400

ResourceShareInvitationArnNotFoundException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) for an invitation was not found.

HTTP Status Code: 400

ResourceShareInvitationExpiredException

The operation failed because the specified invitation is past its expiration date and time.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ReplacePermissionAssociations

Updates all resource shares that use a managed permission to a different managed permission. This operation always applies the default version of the target managed permission. You can optionally specify that the update applies to only resource shares that currently use a specified version. This enables you to update to the latest version, without changing the which managed permission is used.

You can use this operation to update all of your resource shares to use the current default version of the permission by specifying the same value for the `fromPermissionArn` and `toPermissionArn` parameters.

You can use the optional `fromPermissionVersion` parameter to update only those resources that use a specified version of the managed permission to the new managed permission.

Important

To successfully perform this operation, you must have permission to update the resource-based policy on all affected resource types.

Request Syntax

```
POST /replacepermissionassociations HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "clientToken": "string",
  "fromPermissionArn": "string",
  "fromPermissionVersion": number,
  "toPermissionArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

fromPermissionArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the managed permission that you want to replace.

Type: String

Required: Yes

toPermissionArn

Specifies the ARN of the managed permission that you want to associate with resource shares in place of the one specified by `fromPermissionArn` and `fromPermissionVersion`.

The operation always associates the version that is currently the default for the specified managed permission.

Type: String

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

fromPermissionVersion

Specifies that you want to update the permissions for only those resource shares that use the specified version of the managed permission.

Type: Integer

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "replacePermissionAssociationsWork": {
    "creationTime": number,
    "fromPermissionArn": "string",
    "fromPermissionVersion": "string",
    "id": "string",
    "lastUpdatedTime": number,
    "status": "string",
    "statusMessage": "string",
    "toPermissionArn": "string",
    "toPermissionVersion": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

replacePermissionAssociationsWork

Specifies a data structure that you can use to track the asynchronous tasks that AWS RAM performs to complete this operation. You can use the [ListReplacePermissionAssociationsWork](#) operation and pass the `id` value returned in this structure.

Type: [ReplacePermissionAssociationsWork](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SetDefaultPermissionVersion

Designates the specified version number as the default version for the specified customer managed permission. New resource shares automatically use this new default permission. Existing resource shares continue to use their original permission version, but you can use [ReplacePermissionAssociations](#) to update them.

Request Syntax

```
POST /setdefaultpermissionversion HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "permissionArn": "string",
  "permissionVersion": number
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[permissionArn](#)

Specifies the [Amazon Resource Name \(ARN\)](#) of the customer managed permission whose default version you want to change.

Type: String

Required: Yes

[permissionVersion](#)

Specifies the version number that you want to designate as the default for customer managed permission. To see a list of all available version numbers, use [ListPermissionVersions](#).

Type: Integer

Required: Yes

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "returnValue": boolean
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

returnValue

A boolean value that indicates whether the operation was successful.

Type: Boolean

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds the specified tag keys and values to a resource share or managed permission. If you choose a resource share, the tags are attached to only the resource share, not to the resources that are in the resource share.

The tags on a managed permission are the same for all versions of the managed permission.

Request Syntax

```
POST /tagresource HTTP/1.1
Content-type: application/json
```

```
{
  "resourceArn": "string",
  "resourceShareArn": "string",
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

tags

A list of one or more tag key and value pairs. The tag key must be present and not be an empty string. The tag value must be present but can be an empty string.

Type: Array of [Tag](#) objects

Required: Yes

resourceArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the managed permission that you want to add tags to. You must specify *either* `resourceArn`, or `resourceShareArn`, but not both.

Type: String

Required: No

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share that you want to add tags to. You must specify *either* `resourceShareArn`, or `resourceArn`, but not both.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ResourceArnNotFoundException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) was not found.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

TagLimitExceededException

The operation failed because it would exceed the limit for tags for your AWS account.

HTTP Status Code: 400

TagPolicyViolationException

The operation failed because the specified tag key is a reserved word and can't be used.

HTTP Status Code: 400

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes the specified tag key and value pairs from the specified resource share or managed permission.

Request Syntax

```
POST /untagresource HTTP/1.1
Content-type: application/json
```

```
{
  "resourceArn": "string",
  "resourceShareArn": "string",
  "tagKeys": [ "string" ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

tagKeys

Specifies a list of one or more tag keys that you want to remove.

Type: Array of strings

Required: Yes

resourceArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the managed permission that you want to remove tags from. You must specify either `resourceArn`, or `resourceShareArn`, but not both.

Type: String

Required: No

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share that you want to remove tags from. The tags are removed from the resource share, not the resources in the resource share. You must specify either `resourceShareArn`, or `resourceArn`, but not both.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateResourceShare

Modifies some of the properties of the specified resource share.

Request Syntax

```
POST /updateresourceshare HTTP/1.1
Content-type: application/json

{
  "allowExternalPrincipals": boolean,
  "clientToken": "string",
  "name": "string",
  "resourceShareArn": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

resourceShareArn

Specifies the [Amazon Resource Name \(ARN\)](#) of the resource share that you want to modify.

Type: String

Required: Yes

allowExternalPrincipals

Specifies whether principals outside your organization in AWS Organizations can be associated with a resource share.

Type: Boolean

Required: No

clientToken

Specifies a unique, case-sensitive identifier that you provide to ensure the idempotency of the request. This lets you safely retry the request without accidentally performing the same operation a second time. Passing the same value to a later call to an operation requires that you also pass the same value for all other parameters. We recommend that you use a [UUID type of value](#).

If you don't provide this value, then AWS generates a random one for you.

If you retry the operation with the same `ClientToken`, but with different parameters, the retry fails with an `IdempotentParameterMismatch` error.

Type: String

Required: No

name

If specified, the new name that you want to attach to the resource share.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "clientToken": "string",
  "resourceShare": {
    "allowExternalPrincipals": boolean,
    "creationTime": number,
    "featureSet": "string",
    "lastUpdatedTime": number,
    "name": "string",
    "owningAccountId": "string",
    "resourceShareArn": "string",
    "status": "string",
    "statusMessage": "string",
```

```
  "tags": [  
    {  
      "key": "string",  
      "value": "string"  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

clientToken

The idempotency identifier associated with this request. If you want to repeat the same operation in an idempotent manner then you must include this value in the `clientToken` request parameter of that later call. All other parameters must also have the same values that you used in the first call.

Type: String

resourceShare

Information about the resource share.

Type: [ResourceShare](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

IdempotentParameterMismatchException

The operation failed because the client token input parameter matched one that was used with a previous call to the operation, but at least one of the other input parameters is different from the previous call.

HTTP Status Code: 400

InvalidClientTokenException

The operation failed because the specified client token isn't valid.

HTTP Status Code: 400

InvalidParameterException

The operation failed because a parameter you specified isn't valid.

HTTP Status Code: 400

MalformedArnException

The operation failed because the specified [Amazon Resource Name \(ARN\)](#) has a format that isn't valid.

HTTP Status Code: 400

MissingRequiredParameterException

The operation failed because a required input parameter is missing.

HTTP Status Code: 400

OperationNotPermittedException

The operation failed because the requested operation isn't permitted.

HTTP Status Code: 400

ServerInternalException

The operation failed because the service could not respond to the request due to an internal problem. Try again later.

HTTP Status Code: 500

ServiceUnavailableException

The operation failed because the service isn't available. Try again later.

HTTP Status Code: 503

UnknownResourceException

The operation failed because a specified resource couldn't be found.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS RAM API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AssociatedPermission](#)
- [Principal](#)
- [ReplacePermissionAssociationsWork](#)
- [Resource](#)
- [ResourceShare](#)
- [ResourceShareAssociation](#)
- [ResourceShareInvitation](#)
- [ResourceSharePermissionDetail](#)
- [ResourceSharePermissionSummary](#)
- [ServiceNameAndResourceType](#)
- [Tag](#)
- [TagFilter](#)

AssociatedPermission

An object that describes a managed permission associated with a resource share.

Contents

Note

In the following list, the required parameters are described first.

arn

The [Amazon Resource Name \(ARN\)](#) of the associated managed permission.

Type: String

Required: No

defaultVersion

Indicates whether the associated resource share is using the default version of the permission.

Type: Boolean

Required: No

featureSet

Indicates what features are available for this resource share. This parameter can have one of the following values:

- **STANDARD** – A resource share that supports all functionality. These resource shares are visible to all principals you share the resource share with. You can modify these resource shares in AWS RAM using the console or APIs. This resource share might have been created by AWS RAM, or it might have been **CREATED_FROM_POLICY** and then promoted.
- **CREATED_FROM_POLICY** – The customer manually shared a resource by attaching a resource-based policy. That policy did not match any existing managed permissions, so AWS RAM created this customer managed permission automatically on the customer's behalf based on the attached policy document. This type of resource share is visible only to the AWS account that created it. You can't modify it in AWS RAM unless you promote it. For more information, see [PromoteResourceShareCreatedFromPolicy](#).

- **PROMOTING_TO_STANDARD** – This resource share was originally `CREATED_FROM_POLICY`, but the customer ran the [PromoteResourceShareCreatedFromPolicy](#) and that operation is still in progress. This value changes to `STANDARD` when complete.

Type: String

Valid Values: `CREATED_FROM_POLICY` | `PROMOTING_TO_STANDARD` | `STANDARD`

Required: No

lastUpdatedTime

The date and time when the association between the permission and the resource share was last updated.

Type: Timestamp

Required: No

permissionVersion

The version of the permission currently associated with the resource share.

Type: String

Required: No

resourceShareArn

The [Amazon Resource Name \(ARN\)](#) of a resource share associated with this permission.

Type: String

Required: No

resourceType

The resource type to which this permission applies.

Type: String

Required: No

status

The current status of the association between the permission and the resource share. The following are the possible values:

- ATTACHABLE – This permission or version can be associated with resource shares.
- UNATTACHABLE – This permission or version can't currently be associated with resource shares.
- DELETING – This permission or version is in the process of being deleted.
- DELETED – This permission or version is deleted.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Principal

Describes a principal for use with AWS Resource Access Manager.

Contents

Note

In the following list, the required parameters are described first.

creationTime

The date and time when the principal was associated with the resource share.

Type: Timestamp

Required: No

external

Indicates the relationship between the AWS account the principal belongs to and the account that owns the resource share:

- **True** – The two accounts belong to same organization.
- **False** – The two accounts do not belong to the same organization.

Type: Boolean

Required: No

id

The ID of the principal that can be associated with a resource share.

Type: String

Required: No

lastUpdatedTime

The date and time when the association between the resource share and the principal was last updated.

Type: Timestamp

Required: No

resourceShareArn

The [Amazon Resource Name \(ARN\)](#) of a resource share the principal is associated with.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReplacePermissionAssociationsWork

A structure that represents the background work that AWS RAM performs when you invoke the [ReplacePermissionAssociations](#) operation.

Contents

Note

In the following list, the required parameters are described first.

creationTime

The date and time when this asynchronous background task was created.

Type: Timestamp

Required: No

fromPermissionArn

The [Amazon Resource Name \(ARN\)](#) of the managed permission that this background task is replacing.

Type: String

Required: No

fromPermissionVersion

The version of the managed permission that this background task is replacing.

Type: String

Required: No

id

The unique identifier for the background task associated with one [ReplacePermissionAssociations](#) request.

Type: String

Required: No

lastUpdatedTime

The date and time when the status of this background task was last updated.

Type: Timestamp

Required: No

status

Specifies the current status of the background tasks for the specified ID. The output is one of the following strings:

- IN_PROGRESS
- COMPLETED
- FAILED

Type: String

Valid Values: IN_PROGRESS | COMPLETED | FAILED

Required: No

statusMessage

Specifies the reason for a FAILED status. This field is present only when there status is FAILED.

Type: String

Required: No

toPermissionArn

The ARN of the managed permission that this background task is associating with the resource shares in place of the managed permission and version specified in `fromPermissionArn` and `fromPermissionVersion`.

Type: String

Required: No

toPermissionVersion

The version of the managed permission that this background task is associating with the resource shares. This is always the version that is currently the default for this managed permission.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Resource

Describes a resource associated with a resource share in AWS RAM.

Contents

Note

In the following list, the required parameters are described first.

arn

The [Amazon Resource Name \(ARN\)](#) of the resource.

Type: String

Required: No

creationTime

The date and time when the resource was associated with the resource share.

Type: Timestamp

Required: No

lastUpdatedTime

The date and time when the association between the resource and the resource share was last updated.

Type: Timestamp

Required: No

resourceGroupArn

The [Amazon Resource Name \(ARN\)](#) of the resource group. This value is available only if the resource is part of a resource group.

Type: String

Required: No

resourceRegionScope

Specifies the scope of visibility of this resource:

- **REGIONAL** – The resource can be accessed only by using requests that target the AWS Region in which the resource exists.
- **GLOBAL** – The resource can be accessed from any AWS Region.

Type: String

Valid Values: REGIONAL | GLOBAL

Required: No

resourceShareArn

The [Amazon Resource Name \(ARN\)](#) of the resource share this resource is associated with.

Type: String

Required: No

status

The current status of the resource.

Type: String

Valid Values: AVAILABLE | ZONAL_RESOURCE_INACCESSIBLE | LIMIT_EXCEEDED | UNAVAILABLE | PENDING

Required: No

statusMessage

A message about the status of the resource.

Type: String

Required: No

type

The resource type. This takes the form of: `service-code:resource-code`, and is case-insensitive. For example, an Amazon EC2 Subnet would be represented by the string `ec2:subnet`.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceShare

Describes a resource share in AWS RAM.

Contents

Note

In the following list, the required parameters are described first.

allowExternalPrincipals

Indicates whether principals outside your organization in AWS Organizations can be associated with a resource share.

- **True** – the resource share can be shared with any AWS account.
- **False** – the resource share can be shared with only accounts in the same organization as the account that owns the resource share.

Type: Boolean

Required: No

creationTime

The date and time when the resource share was created.

Type: Timestamp

Required: No

featureSet

Indicates what features are available for this resource share. This parameter can have one of the following values:

- **STANDARD** – A resource share that supports all functionality. These resource shares are visible to all principals you share the resource share with. You can modify these resource shares in AWS RAM using the console or APIs. This resource share might have been created by AWS RAM, or it might have been **CREATED_FROM_POLICY** and then promoted.
- **CREATED_FROM_POLICY** – The customer manually shared a resource by attaching a resource-based policy. That policy did not match any existing managed permissions, so AWS

RAM created this customer managed permission automatically on the customer's behalf based on the attached policy document. This type of resource share is visible only to the AWS account that created it. You can't modify it in AWS RAM unless you promote it. For more information, see [PromoteResourceShareCreatedFromPolicy](#).

- **PROMOTING_TO_STANDARD** – This resource share was originally `CREATED_FROM_POLICY`, but the customer ran the [PromoteResourceShareCreatedFromPolicy](#) and that operation is still in progress. This value changes to `STANDARD` when complete.

Type: String

Valid Values: `CREATED_FROM_POLICY` | `PROMOTING_TO_STANDARD` | `STANDARD`

Required: No

lastUpdatedTime

The date and time when the resource share was last updated.

Type: Timestamp

Required: No

name

The name of the resource share.

Type: String

Required: No

owningAccountId

The ID of the AWS account that owns the resource share.

Type: String

Required: No

resourceShareArn

The [Amazon Resource Name \(ARN\)](#) of the resource share

Type: String

Required: No

status

The current status of the resource share.

Type: String

Valid Values: PENDING | ACTIVE | FAILED | DELETING | DELETED

Required: No

statusMessage

A message about the status of the resource share.

Type: String

Required: No

tags

The tag key and value pairs attached to the resource share.

Type: Array of [Tag](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceShareAssociation

Describes an association between a resource share and either a principal or a resource.

Contents

Note

In the following list, the required parameters are described first.

associatedEntity

The associated entity. This can be either of the following:

- For a resource association, this is the [Amazon Resource Name \(ARN\)](#) of the resource.
- For principal associations, this is one of the following:
 - The ID of an AWS account
 - The [Amazon Resource Name \(ARN\)](#) of an organization in AWS Organizations
 - The ARN of an organizational unit (OU) in AWS Organizations
 - The ARN of an IAM role
 - The ARN of an IAM user

Type: String

Required: No

associationType

The type of entity included in this association.

Type: String

Valid Values: PRINCIPAL | RESOURCE

Required: No

creationTime

The date and time when the association was created.

Type: Timestamp

Required: No

external

Indicates whether the principal belongs to the same organization in AWS Organizations as the AWS account that owns the resource share.

Type: Boolean

Required: No

lastUpdatedTime

The date and time when the association was last updated.

Type: Timestamp

Required: No

resourceShareArn

The [Amazon Resource Name \(ARN\)](#) of the resource share.

Type: String

Required: No

resourceShareName

The name of the resource share.

Type: String

Required: No

status

The current status of the association.

Type: String

Valid Values: ASSOCIATING | ASSOCIATED | FAILED | DISASSOCIATING | DISASSOCIATED

Required: No

statusMessage

A message about the status of the association.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceShareInvitation

Describes an invitation for an AWS account to join a resource share.

Contents

Note

In the following list, the required parameters are described first.

invitationTimestamp

The date and time when the invitation was sent.

Type: Timestamp

Required: No

receiverAccountId

The ID of the AWS account that received the invitation.

Type: String

Required: No

receiverArn

The [Amazon Resource Name \(ARN\)](#) of the IAM user or role that received the invitation.

Type: String

Required: No

resourceShareArn

The [Amazon Resource Name \(ARN\)](#) of the resource share

Type: String

Required: No

resourceShareAssociations

This member has been deprecated.

To view the resources associated with a pending resource share invitation, use [ListPendingInvitationResources](#).

Type: Array of [ResourceShareAssociation](#) objects

Required: No

resourceShareInvitationArn

The [Amazon Resource Name \(ARN\)](#) of the invitation.

Type: String

Required: No

resourceShareName

The name of the resource share.

Type: String

Required: No

senderAccountId

The ID of the AWS account that sent the invitation.

Type: String

Required: No

status

The current status of the invitation.

Type: String

Valid Values: PENDING | ACCEPTED | REJECTED | EXPIRED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceSharePermissionDetail

Information about a AWS RAM managed permission.

Contents

Note

In the following list, the required parameters are described first.

arn

The [Amazon Resource Name \(ARN\)](#) of this AWS RAM managed permission.

Type: String

Required: No

creationTime

The date and time when the permission was created.

Type: Timestamp

Required: No

defaultVersion

Specifies whether the version of the permission represented in this response is the default version for this permission.

Type: Boolean

Required: No

featureSet

Indicates what features are available for this resource share. This parameter can have one of the following values:

- **STANDARD** – A resource share that supports all functionality. These resource shares are visible to all principals you share the resource share with. You can modify these resource

shares in AWS RAM using the console or APIs. This resource share might have been created by AWS RAM, or it might have been **CREATED_FROM_POLICY** and then promoted.

- **CREATED_FROM_POLICY** – The customer manually shared a resource by attaching a resource-based policy. That policy did not match any existing managed permissions, so AWS RAM created this customer managed permission automatically on the customer's behalf based on the attached policy document. This type of resource share is visible only to the AWS account that created it. You can't modify it in AWS RAM unless you promote it. For more information, see [PromoteResourceShareCreatedFromPolicy](#).
- **PROMOTING_TO_STANDARD** – This resource share was originally **CREATED_FROM_POLICY**, but the customer ran the [PromoteResourceShareCreatedFromPolicy](#) and that operation is still in progress. This value changes to **STANDARD** when complete.

Type: String

Valid Values: **CREATED_FROM_POLICY** | **PROMOTING_TO_STANDARD** | **STANDARD**

Required: No

isResourceTypeDefault

Specifies whether the version of the permission represented in this response is the default version for all resources of this resource type.

Type: Boolean

Required: No

lastUpdatedTime

The date and time when the permission was last updated.

Type: Timestamp

Required: No

name

The name of this permission.

Type: String

Required: No

permission

The permission's effect and actions in JSON format. The `effect` indicates whether the specified actions are allowed or denied. The `actions` list the operations to which the principal is granted or denied access.

Type: String

Required: No

permissionType

The type of managed permission. This can be one of the following values:

- `AWS_MANAGED` – AWS created and manages this managed permission. You can associate it with your resource shares, but you can't modify it.
- `CUSTOMER_MANAGED` – You, or another principal in your account created this managed permission. You can associate it with your resource shares and create new versions that have different permissions.

Type: String

Valid Values: `CUSTOMER_MANAGED` | `AWS_MANAGED`

Required: No

resourceType

The resource type to which this permission applies.

Type: String

Required: No

status

The current status of the association between the permission and the resource share. The following are the possible values:

- `ATTACHABLE` – This permission or version can be associated with resource shares.
- `UNATTACHABLE` – This permission or version can't currently be associated with resource shares.
- `DELETING` – This permission or version is in the process of being deleted.
- `DELETED` – This permission or version is deleted.

Type: String

Valid Values: ATTACHABLE | UNATTACHABLE | DELETING | DELETED

Required: No

tags

The tag key and value pairs attached to the resource share.

Type: Array of [Tag](#) objects

Required: No

version

The version of the permission described in this response.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceSharePermissionSummary

Information about an AWS RAM permission.

Contents

Note

In the following list, the required parameters are described first.

arn

The [Amazon Resource Name \(ARN\)](#) of the permission you want information about.

Type: String

Required: No

creationTime

The date and time when the permission was created.

Type: Timestamp

Required: No

defaultVersion

Specifies whether the version of the managed permission used by this resource share is the default version for this managed permission.

Type: Boolean

Required: No

featureSet

Indicates what features are available for this resource share. This parameter can have one of the following values:

- **STANDARD** – A resource share that supports all functionality. These resource shares are visible to all principals you share the resource share with. You can modify these resource

shares in AWS RAM using the console or APIs. This resource share might have been created by AWS RAM, or it might have been **CREATED_FROM_POLICY** and then promoted.

- **CREATED_FROM_POLICY** – The customer manually shared a resource by attaching a resource-based policy. That policy did not match any existing managed permissions, so AWS RAM created this customer managed permission automatically on the customer's behalf based on the attached policy document. This type of resource share is visible only to the AWS account that created it. You can't modify it in AWS RAM unless you promote it. For more information, see [PromoteResourceShareCreatedFromPolicy](#).
- **PROMOTING_TO_STANDARD** – This resource share was originally **CREATED_FROM_POLICY**, but the customer ran the [PromoteResourceShareCreatedFromPolicy](#) and that operation is still in progress. This value changes to **STANDARD** when complete.

Type: String

Valid Values: **CREATED_FROM_POLICY** | **PROMOTING_TO_STANDARD** | **STANDARD**

Required: No

isResourceTypeDefault

Specifies whether the managed permission associated with this resource share is the default managed permission for all resources of this resource type.

Type: Boolean

Required: No

lastUpdatedTime

The date and time when the permission was last updated.

Type: Timestamp

Required: No

name

The name of this managed permission.

Type: String

Required: No

permissionType

The type of managed permission. This can be one of the following values:

- `AWS_MANAGED` – AWS created and manages this managed permission. You can associate it with your resource shares, but you can't modify it.
- `CUSTOMER_MANAGED` – You, or another principal in your account created this managed permission. You can associate it with your resource shares and create new versions that have different permissions.

Type: String

Valid Values: `CUSTOMER_MANAGED` | `AWS_MANAGED`

Required: No

resourceType

The type of resource to which this permission applies. This takes the form of: `service-code:resource-code`, and is case-insensitive. For example, an Amazon EC2 Subnet would be represented by the string `ec2:subnet`.

Type: String

Required: No

status

The current status of the permission.

Type: String

Required: No

tags

A list of the tag key value pairs currently attached to the permission.

Type: Array of [Tag](#) objects

Required: No

version

The version of the permission associated with this resource share.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceNameAndResourceType

Information about a shareable resource type and the AWS service to which resources of that type belong.

Contents

Note

In the following list, the required parameters are described first.

resourceRegionScope

Specifies the scope of visibility of resources of this type:

- **REGIONAL** – The resource can be accessed only by using requests that target the AWS Region in which the resource exists.
- **GLOBAL** – The resource can be accessed from any AWS Region.

Type: String

Valid Values: REGIONAL | GLOBAL

Required: No

resourceType

The type of the resource. This takes the form of: `service-code:resource-code`, and is case-insensitive. For example, an Amazon EC2 Subnet would be represented by the string `ec2:subnet`.

Type: String

Required: No

serviceName

The name of the AWS service to which resources of this type belong.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

A structure containing a tag. A tag is metadata that you can attach to your resources to help organize and categorize them. You can also use them to help you secure your resources. For more information, see [Controlling access to AWS resources using tags](#).

For more information about tags, see [Tagging AWS resources](#) in the *AWS General Reference Guide*.

Contents

Note

In the following list, the required parameters are described first.

key

The key, or name, attached to the tag. Every tag must have a key. Key names are case sensitive.

Type: String

Required: No

value

The string value attached to the tag. The value can be an empty string. Key values are case sensitive.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TagFilter

A tag key and optional list of possible values that you can use to filter results for tagged resources.

Note

Multiple tag filters are evaluated as an OR condition.

Contents

Note

In the following list, the required parameters are described first.

tagKey

The tag key. This must have a valid string value and can't be empty.

Type: String

Required: No

tagValues

A list of zero or more tag values. If no values are provided, then the filter matches any tag with the specified key, regardless of its value.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400