



API Reference

# AWS Security Incident Response



**API Version 2018-05-10**

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# AWS Security Incident Response: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome</b> .....	<b>1</b>
<b>Actions</b> .....	<b>2</b>
BatchGetMemberAccountDetails .....	3
Request Syntax .....	3
URI Request Parameters .....	3
Request Body .....	3
Response Syntax .....	4
Response Elements .....	5
Errors .....	5
See Also .....	6
CancelMembership .....	7
Request Syntax .....	7
URI Request Parameters .....	7
Request Body .....	7
Response Syntax .....	7
Response Elements .....	7
Errors .....	8
See Also .....	9
CloseCase .....	10
Request Syntax .....	10
URI Request Parameters .....	10
Request Body .....	10
Response Syntax .....	10
Response Elements .....	10
Errors .....	11
See Also .....	12
CreateCase .....	13
Request Syntax .....	13
URI Request Parameters .....	14
Request Body .....	14
Response Syntax .....	17
Response Elements .....	17
Errors .....	18
See Also .....	19

---

CreateCaseComment .....	20
Request Syntax .....	20
URI Request Parameters .....	20
Request Body .....	20
Response Syntax .....	21
Response Elements .....	21
Errors .....	22
See Also .....	23
CreateMembership .....	24
Request Syntax .....	24
URI Request Parameters .....	24
Request Body .....	24
Response Syntax .....	26
Response Elements .....	26
Errors .....	27
See Also .....	28
GetCase .....	29
Request Syntax .....	29
URI Request Parameters .....	29
Request Body .....	29
Response Syntax .....	29
Response Elements .....	30
Errors .....	34
See Also .....	35
GetCaseAttachmentDownloadUrl .....	36
Request Syntax .....	36
URI Request Parameters .....	36
Request Body .....	36
Response Syntax .....	36
Response Elements .....	37
Errors .....	37
See Also .....	38
GetCaseAttachmentUploadUrl .....	39
Request Syntax .....	39
URI Request Parameters .....	39
Request Body .....	39

---

Response Syntax .....	40
Response Elements .....	41
Errors .....	41
See Also .....	42
GetMembership .....	43
Request Syntax .....	43
URI Request Parameters .....	43
Request Body .....	43
Response Syntax .....	43
Response Elements .....	44
Errors .....	46
See Also .....	47
ListCaseEdits .....	49
Request Syntax .....	49
URI Request Parameters .....	49
Request Body .....	49
Response Syntax .....	50
Response Elements .....	50
Errors .....	51
See Also .....	52
ListCases .....	53
Request Syntax .....	53
URI Request Parameters .....	53
Request Body .....	53
Response Syntax .....	54
Response Elements .....	54
Errors .....	55
See Also .....	56
ListComments .....	57
Request Syntax .....	57
URI Request Parameters .....	57
Request Body .....	57
Response Syntax .....	58
Response Elements .....	58
Errors .....	59
See Also .....	60

---

ListMemberships .....	61
Request Syntax .....	61
URI Request Parameters .....	61
Request Body .....	61
Response Syntax .....	62
Response Elements .....	62
Errors .....	62
See Also .....	63
ListTagsForResource .....	65
Request Syntax .....	65
URI Request Parameters .....	65
Request Body .....	65
Response Syntax .....	65
Response Elements .....	65
Errors .....	66
See Also .....	67
TagResource .....	68
Request Syntax .....	68
URI Request Parameters .....	68
Request Body .....	68
Response Syntax .....	69
Response Elements .....	69
Errors .....	69
See Also .....	70
UntagResource .....	71
Request Syntax .....	71
URI Request Parameters .....	71
Request Body .....	71
Response Syntax .....	71
Response Elements .....	72
Errors .....	72
See Also .....	73
UpdateCase .....	74
Request Syntax .....	74
URI Request Parameters .....	75
Request Body .....	75

Response Syntax .....	79
Response Elements .....	79
Errors .....	80
See Also .....	81
UpdateCaseComment .....	82
Request Syntax .....	82
URI Request Parameters .....	82
Request Body .....	82
Response Syntax .....	83
Response Elements .....	83
Errors .....	84
See Also .....	85
UpdateCaseStatus .....	86
Request Syntax .....	86
URI Request Parameters .....	86
Request Body .....	87
Response Syntax .....	87
Response Elements .....	87
Errors .....	88
See Also .....	89
UpdateMembership .....	90
Request Syntax .....	90
URI Request Parameters .....	90
Request Body .....	91
Response Syntax .....	91
Response Elements .....	91
Errors .....	92
See Also .....	93
UpdateResolverType .....	94
Request Syntax .....	94
URI Request Parameters .....	94
Request Body .....	94
Response Syntax .....	95
Response Elements .....	95
Errors .....	96
See Also .....	97

<b>Data Types</b> .....	<b>98</b>
CaseAttachmentAttributes .....	99
Contents .....	99
See Also .....	100
CaseEditItem .....	101
Contents .....	101
See Also .....	101
GetMembershipAccountDetailError .....	103
Contents .....	103
See Also .....	103
GetMembershipAccountDetailItem .....	104
Contents .....	104
See Also .....	104
ImpactedAwsRegion .....	106
Contents .....	106
See Also .....	106
IncidentResponder .....	107
Contents .....	107
See Also .....	107
ListCasesItem .....	109
Contents .....	109
See Also .....	111
ListCommentsItem .....	112
Contents .....	112
See Also .....	113
ListMembershipItem .....	114
Contents .....	114
See Also .....	115
OptInFeature .....	116
Contents .....	116
See Also .....	116
ThreatActorIp .....	117
Contents .....	117
See Also .....	117
ValidationExceptionField .....	118
Contents .....	118



---

See Also .....	118
Watcher .....	119
Contents .....	119
See Also .....	119
<b>Common Parameters .....</b>	<b>120</b>
<b>Common Errors .....</b>	<b>123</b>

# Welcome

This guide documents the action and response elements for use of the service.

This document was last published on March 12, 2025.

# Actions

The following actions are supported:

- [BatchGetMemberAccountDetails](#)
- [CancelMembership](#)
- [CloseCase](#)
- [CreateCase](#)
- [CreateCaseComment](#)
- [CreateMembership](#)
- [GetCase](#)
- [GetCaseAttachmentDownloadUrl](#)
- [GetCaseAttachmentUploadUrl](#)
- [GetMembership](#)
- [ListCaseEdits](#)
- [ListCases](#)
- [ListComments](#)
- [ListMemberships](#)
- [ListTagsForResource](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateCase](#)
- [UpdateCaseComment](#)
- [UpdateCaseStatus](#)
- [UpdateMembership](#)
- [UpdateResolverType](#)

# BatchGetMemberAccountDetails

Provides information on whether the supplied account IDs are associated with a membership.

## Note

AWS account ID's may appear less than 12 characters and need to be zero-prepended. An example would be 123123123 which is nine digits, and with zero-prepend would be 000123123123. Not zero-prepending to 12 digits could result in errors.

## Request Syntax

```
POST /v1/membership/membershipId/batch-member-details HTTP/1.1
Content-type: application/json

{
  "accountIds": [ "string" ]
}
```

## URI Request Parameters

The request uses the following URI parameters.

### membershipId

Required element used in combination with BatchGetMemberAccountDetails to identify the membership ID to query.

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: m-[a-z0-9]{10,32}

Required: Yes

## Request Body

The request accepts the following data in JSON format.

## accountIds

Optional element to query the membership relationship status to a provided list of account IDs.

### Note

AWS account ID's may appear less than 12 characters and need to be zero-prepended. An example would be 123123123 which is nine digits, and with zero-prepend would be 000123123123. Not zero-prepending to 12 digits could result in errors.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "errors": [
    {
      "accountId": "string",
      "error": "string",
      "message": "string"
    }
  ],
  "items": [
    {
      "accountId": "string",
      "relationshipStatus": "string",
      "relationshipType": "string"
    }
  ]
}
```

```
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### errors

The response element providing error messages for requests to `GetMembershipAccountDetails`.

Type: Array of [GetMembershipAccountDetailError](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

### items

The response element providing responses for requests to `GetMembershipAccountDetails`.

Type: Array of [GetMembershipAccountDetailItem](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerError**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CancelMembership

Cancels an existing membership.

## Request Syntax

```
PUT /v1/membership/membershipId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### membershipId

Required element used in combination with `CancelMembershipRequest` to identify the membership ID to cancel.

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: `m-[a-z0-9]{10,32}`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "membershipId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.



The following data is returned in JSON format by the service.

### membershipId

The response element providing responses for requests to `CancelMembershipRequest`.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: `m-[a-z0-9]{10,32}`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CloseCase

Closes an existing case.

## Request Syntax

```
POST /v1/cases/caseId/close-case HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element used in combination with CloseCase to identify the case ID to close.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "caseStatus": "string",
  "closedDate": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### caseStatus

A response element providing responses for requests to CloseCase. This element responds Closed if successful.

Type: String

Valid Values: Submitted | Acknowledged | Detection and Analysis | Containment, Eradication and Recovery | Post-incident Activities | Ready to Close | Closed

### closedDate

A response element providing responses for requests to CloseCase. This element responds with the ISO-8601 formatted timestamp of the moment when the case was closed.

Type: Timestamp

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateCase

Creates a new case.

## Request Syntax

```
POST /v1/create-case HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "description": "string",
  "engagementType": "string",
  "impactedAccounts": [ "string" ],
  "impactedAwsRegions": [
    {
      "region": "string"
    }
  ],
  "impactedServices": [ "string" ],
  "reportedIncidentStartDate": number,
  "resolverType": "string",
  "tags": {
    "string" : "string"
  },
  "threatActorIpAddresses": [
    {
      "ipAddress": "string",
      "userAgent": "string"
    }
  ],
  "title": "string",
  "watchers": [
    {
      "email": "string",
      "jobTitle": "string",
      "name": "string"
    }
  ]
}
```


## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### clientToken

 **Note**

The `clientToken` field is an idempotency key used to ensure that repeated attempts for a single action will be ignored by the server during retries. A caller supplied unique ID (typically a UUID) should be provided.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

### description

Required element used in combination with `CreateCase`

to provide a description for the new case.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

Required: Yes

### engagementType

Required element used in combination with `CreateCase` to provide an engagement type for the new cases. Available engagement types include `Security Incident | Investigation`

Type: String

Valid Values: `Security Incident | Investigation`

Required: Yes

### impactedAccounts

Required element used in combination with CreateCase to provide a list of impacted accounts.

#### Note

AWS account ID's may appear less than 12 characters and need to be zero-prepended. An example would be 123123123 which is nine digits, and with zero-prepend would be 000123123123. Not zero-prepending to 12 digits could result in errors.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Fixed length of 12.

Pattern: `[0-9]{12}`

Required: Yes

### impactedAwsRegions

An optional element used in combination with CreateCase to provide a list of impacted regions.

Type: Array of [ImpactedAwsRegion](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

### impactedServices

An optional element used in combination with CreateCase to provide a list of services impacted.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 600 items.

Length Constraints: Minimum length of 3. Maximum length of 50.

Pattern: `[a-zA-Z0-9 - . ( ) : ]+`



Required: No

### reportedIncidentStartDate

Required element used in combination with CreateCase to provide an initial start date for the unauthorized activity.

Type: Timestamp

Required: Yes

### resolverType

Required element used in combination with CreateCase to identify the resolver type.

Type: String

Valid Values: AWS | Self

Required: Yes

### tags

An optional element used in combination with CreateCase to add customer specified tags to a case.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

### threatActorIpAddresses

An optional element used in combination with CreateCase to provide a list of suspicious internet protocol addresses associated with unauthorized activity.

Type: Array of [ThreatActorIp](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## title

Required element used in combination with CreateCase to provide a title for the new case.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: Yes

## watchers

Required element used in combination with CreateCase to provide a list of entities to receive notifications for case updates.

Type: Array of [Watcher](#) objects

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Required: Yes

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "caseId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### caseId

A response element providing responses for requests to CreateCase. This element responds with the case ID.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateCaseComment

Adds a comment to an existing case.

## Request Syntax

```
POST /v1/cases/caseId/create-comment HTTP/1.1
Content-type: application/json

{
  "body": "string",
  "clientToken": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element used in combination with CreateCaseComment to specify a case ID.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### body

Required element used in combination with CreateCaseComment to add content for the new comment.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12000.

Required: Yes

### clientToken

#### Note

The `clientToken` field is an idempotency key used to ensure that repeated attempts for a single action will be ignored by the server during retries. A caller supplied unique ID (typically a UUID) should be provided.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "commentId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### commentId

Response element indicating the new comment ID.

Type: String

Length Constraints: Fixed length of 6.

Pattern: `\d{6}`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# CreateMembership

Creates a new membership.

## Request Syntax

```
POST /v1/membership HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "incidentResponseTeam": [
    {
      "email": "string",
      "jobTitle": "string",
      "name": "string"
    }
  ],
  "membershipName": "string",
  "optInFeatures": [
    {
      "featureName": "string",
      "isEnabled": boolean
    }
  ],
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

## clientToken

### Note

The `clientToken` field is an idempotency key used to ensure that repeated attempts for a single action will be ignored by the server during retries. A caller supplied unique ID (typically a UUID) should be provided.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

## incidentResponseTeam

Required element used in combination with `CreateMembership` to add customer incident response team members and trusted partners to the membership.

Type: Array of [IncidentResponder](#) objects

Array Members: Minimum number of 2 items. Maximum number of 10 items.

Required: Yes

## membershipName

Required element used in combination with `CreateMembership` to create a name for the membership.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 50.

Required: Yes

## optInFeatures

Optional element to enable the monitoring and investigation opt-in features for the service.

Type: Array of [OptInFeature](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

### tags

Optional element for customer configured tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "membershipId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### membershipId

Response element for CreateMembership providing the newly created membership ID.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: m-[a-z0-9]{10,32}

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetCase

Returns the attributes of a case.

## Request Syntax

```
GET /v1/cases/caseId/get-case HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element for GetCase to identify the requested case ID.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "actualIncidentStartDate": number,
  "caseArn": "string",
  "caseAttachments": [
    {
      "attachmentId": "string",
      "attachmentStatus": "string",
      "createdDate": number,
```

```
    "creator": "string",
    "fileName": "string"
  }
],
"caseStatus": "string",
"closedDate": number,
"closureCode": "string",
"createdDate": number,
"description": "string",
"engagementType": "string",
"impactedAccounts": [ "string" ],
"impactedAwsRegions": [
  {
    "region": "string"
  }
],
"impactedServices": [ "string" ],
"lastUpdatedDate": number,
"pendingAction": "string",
"reportedIncidentStartDate": number,
"resolverType": "string",
"threatActorIpAddresses": [
  {
    "ipAddress": "string",
    "userAgent": "string"
  }
],
"title": "string",
"watchers": [
  {
    "email": "string",
    "jobTitle": "string",
    "name": "string"
  }
]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### actualIncidentStartDate

Response element for GetCase that provides the actual incident start date as identified by data analysis during the investigation.

Type: Timestamp

### caseArn

Response element for GetCase that provides the case ARN

Type: String

Length Constraints: Minimum length of 12. Maximum length of 80.

Pattern: `arn:aws:security-ir:\w+?-\w+?-\d+:[0-9]{12}:case/[0-9]{10}`

### caseAttachments

Response element for GetCase that provides a list of current case attachments.

Type: Array of [CaseAttachmentAttributes](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

### caseStatus

Response element for GetCase that provides the case status. Options for statuses include Submitted | Detection and Analysis | Eradication, Containment and Recovery | Post-Incident Activities | Closed

Type: String

Valid Values: Submitted | Acknowledged | Detection and Analysis | Containment, Eradication and Recovery | Post-incident Activities | Ready to Close | Closed

### closedDate

Response element for GetCase that provides the date a specified case was closed.

Type: Timestamp

### closureCode

Response element for GetCase that provides the summary code for why a case was closed.



Type: String

Valid Values: Investigation Completed | Not Resolved | False Positive | Duplicate

### createdDate

Response element for GetCase that provides the date the case was created.

Type: Timestamp

### description

Response element for GetCase that provides contents of the case description.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

### engagementType

Response element for GetCase that provides the engagement type. Options for engagement type include Active Security Event | Investigations

Type: String

Valid Values: Security Incident | Investigation

### impactedAccounts

Response element for GetCase that provides a list of impacted accounts.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

### impactedAwsRegions

Response element for GetCase that provides the impacted regions.

Type: Array of [ImpactedAwsRegion](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

## impactedServices

Response element for GetCase that provides a list of impacted services.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 600 items.

Length Constraints: Minimum length of 3. Maximum length of 50.

Pattern: [a-zA-Z0-9 - . ( ) : ]+

## lastUpdatedDate

Response element for GetCase that provides the date a case was last modified.

Type: Timestamp

## pendingAction

Response element for GetCase that identifies the case is waiting on customer input.

Type: String

Valid Values: Customer | None

## reportedIncidentStartDate

Response element for GetCase that provides the customer provided incident start date.

Type: Timestamp

## resolverType

Response element for GetCase that provides the current resolver types.

Type: String

Valid Values: AWS | Self

## threatActorIpAddresses

Response element for GetCase that provides a list of suspicious IP addresses associated with unauthorized activity.

Type: Array of [ThreatActorIp](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

### title

Response element for GetCase that provides the case title.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

### watchers

Response element for GetCase that provides a list of Watchers added to the case.

Type: Array of [Watcher](#) objects

Array Members: Minimum number of 0 items. Maximum number of 30 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetCaseAttachmentDownloadUrl

Returns a Pre-Signed URL for uploading attachments into a case.

## Request Syntax

```
GET /v1/cases/caseId/get-presigned-url/attachmentId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### attachmentId

Required element for GetCaseAttachmentDownloadUrl to identify the attachment ID for downloading an attachment.

Pattern: `[0-9a-fA-F]{8}\b-[0-9a-fA-F]{4}\b-[0-9a-fA-F]{4}\b-[0-9a-fA-F]{4}\b-[0-9a-fA-F]{12}`

Required: Yes

### caseId

Required element for GetCaseAttachmentDownloadUrl to identify the case ID for downloading an attachment from.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 201
```

```
Content-type: application/json

{
  "attachmentPresignedUrl": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### attachmentPresignedUrl

Response element providing the Amazon S3 presigned URL to download an attachment.

Type: String

Pattern: `https?://(?:www.)?[a-zA-Z0-9@:._+~#=-]{2,256}\.[a-z]{2,6}\b(?:[-a-zA-Z0-9@:%_+.~#?&/=]{0,2048})`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

## ResourceNotFoundException

HTTP Status Code: 404

## SecurityIncidentResponseNotActiveException

HTTP Status Code: 400

## ServiceQuotaExceededException

HTTP Status Code: 402

## ThrottlingException

HTTP Status Code: 429

## ValidationException

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetCaseAttachmentUploadUrl

Uploads an attachment to a case.

## Request Syntax

```
POST /v1/cases/caseId/get-presigned-url HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "contentLength": number,
  "fileName": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element for GetCaseAttachmentUploadUrl to identify the case ID for uploading an attachment.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.



## clientToken

### Note

The `clientToken` field is an idempotency key used to ensure that repeated attempts for a single action will be ignored by the server during retries. A caller supplied unique ID (typically a UUID) should be provided.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

## contentLength

Required element for `GetCaseAttachmentUploadUrl` to identify the size of the file attachment.

Type: Long

Valid Range: Minimum value of 1. Maximum value of 104857600.

Required: Yes

## fileName

Required element for `GetCaseAttachmentUploadUrl` to identify the file name of the attachment to upload.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9._-]+`

Required: Yes

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{  
  "attachmentPresignedUrl": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### attachmentPresignedUrl

Response element providing the Amazon S3 presigned URL to upload the attachment.

Type: String

Pattern: `https?://(?:www.)?[a-zA-Z0-9@:._+~#=-]{2,256}\.[a-z]{2,6}\b(?:[-a-zA-Z0-9@:%_+~#?&/=]{0,2048})`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetMembership

Returns the attributes of a membership.

## Request Syntax

```
GET /v1/membership/membershipId HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### membershipId

Required element for GetMembership to identify the membership ID to query.

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: m-[a-z0-9]{10,32}

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "accountId": "string",
  "customerType": "string",
  "incidentResponseTeam": [
    {
      "email": "string",
      "jobTitle": "string",
      "name": "string"
    }
  ]
}
```

```
    }
  ],
  "membershipActivationTimestamp": number,
  "membershipArn": "string",
  "membershipDeactivationTimestamp": number,
  "membershipId": "string",
  "membershipName": "string",
  "membershipStatus": "string",
  "numberOfAccountsCovered": number,
  "optInFeatures": [
    {
      "featureName": "string",
      "isEnabled": boolean
    }
  ],
  "region": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### accountId

Response element for GetMembership that provides the account configured to manage the membership.

Type: String

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

### customerType

Response element for GetMembership that provides the configured membership type. Options include Standalone | Organizations.

Type: String

Valid Values: Standalone | Organization

## incidentResponseTeam

Response element for GetMembership that provides the configured membership incident response team members.

Type: Array of [IncidentResponder](#) objects

Array Members: Minimum number of 2 items. Maximum number of 10 items.

## membershipActivationTimestamp

Response element for GetMembership that provides the configured membership activation timestamp.

Type: Timestamp

## membershipArn

Response element for GetMembership that provides the membership ARN.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 80.

Pattern: `arn:aws:security-ir:\w+?-\w+?-\d+:[0-9]{12}:membership/m-[a-z0-9]{10,32}`

## membershipDeactivationTimestamp

Response element for GetMembership that provides the configured membership name deactivation timestamp.

Type: Timestamp

## membershipId

Response element for GetMembership that provides the queried membership ID.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: `m-[a-z0-9]{10,32}`

## membershipName

Response element for GetMembership that provides the configured membership name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 50.

### membershipStatus

Response element for GetMembership that provides the current membership status.

Type: String

Valid Values: Active | Cancelled | Terminated

### numberOfAccountsCovered

Response element for GetMembership that provides the number of accounts in the membership.

Type: Long

### optInFeatures

Response element for GetMembership that provides the if opt-in features have been enabled.

Type: Array of [OptInFeature](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

### region

Response element for GetMembership that provides the region configured to manage the membership.

Type: String

Valid Values: af-south-1 | ap-east-1 | ap-northeast-1 | ap-northeast-2 | ap-northeast-3 | ap-south-1 | ap-south-2 | ap-southeast-1 | ap-southeast-2 | ap-southeast-3 | ap-southeast-4 | ap-southeast-5 | ca-central-1 | ca-west-1 | cn-north-1 | cn-northwest-1 | eu-central-1 | eu-central-2 | eu-north-1 | eu-south-1 | eu-south-2 | eu-west-1 | eu-west-2 | eu-west-3 | il-central-1 | me-central-1 | me-south-1 | sa-east-1 | us-east-1 | us-east-2 | us-west-1 | us-west-2

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## **AccessDeniedException**

HTTP Status Code: 403

## **ConflictException**

HTTP Status Code: 409

## **InternalServerErrorException**

HTTP Status Code: 500

## **InvalidTokenException**

HTTP Status Code: 423

## **ResourceNotFoundException**

HTTP Status Code: 404

## **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

## **ServiceQuotaExceededException**

HTTP Status Code: 402

## **ThrottlingException**

HTTP Status Code: 429

## **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:



- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListCaseEdits

Views the case history for edits made to a designated case.

## Request Syntax

```
POST /v1/cases/caseId/list-case-edits HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element used with ListCaseEdits to identify the case to query.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### maxResults

Optional element to identify how many results to obtain. There is a maximum value of 25.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

## nextToken

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2000.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "action": "string",
      "eventTimestamp": number,
      "message": "string",
      "principal": "string"
    }
  ],
  "nextToken": "string",
  "total": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### items

Response element for ListCaseEdits that includes the action, event timestamp, message, and principal for the response.

Type: Array of [CaseEditItem](#) objects

### nextToken

Type: String

### **total**

Response element for ListCaseEdits that identifies the total number of edits.

Type: Integer

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

## ValidationException

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListCases

Lists all cases the requester has access to.

## Request Syntax

```
POST /v1/list-cases HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### maxResults

Optional element for ListCases to limit the number of responses.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

### nextToken

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2000.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "caseArn": "string",
      "caseId": "string",
      "caseStatus": "string",
      "closedDate": number,
      "createdDate": number,
      "engagementType": "string",
      "lastUpdatedDate": number,
      "pendingAction": "string",
      "resolverType": "string",
      "title": "string"
    }
  ],
  "nextToken": "string",
  "total": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### items

Response element for ListCases that includes caseARN, caseID, caseStatus, closedDate, createdDate, engagementType, lastUpdatedDate, pendingAction, resolverType, and title for each response.

Type: Array of [ListCasesItem](#) objects

### nextToken

Type: String

## **total**

Response element for ListCases providing the total number of responses.

Type: Long

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429



## ValidationException

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListComments

Returns comments for a designated case.

## Request Syntax

```
POST /v1/cases/caseId/list-comments HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element for ListComments to designate the case to query.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### maxResults

Optional element for ListComments to limit the number of responses.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

## nextToken

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2000.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "body": "string",
      "commentId": "string",
      "createdDate": number,
      "creator": "string",
      "lastUpdatedBy": "string",
      "lastUpdatedDate": number
    }
  ],
  "nextToken": "string",
  "total": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### items

Response element for ListComments providing the body, commentID, createDate, creator, lastUpdatedBy and lastUpdatedDate for each response.

Type: Array of [ListCommentsItem](#) objects

## nextToken

Type: String

## total

Response element for ListComments identifying the number of responses.

Type: Integer

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

## ThrottlingException

HTTP Status Code: 429

## ValidationException

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListMemberships

Returns the memberships that the calling principal can access.

## Request Syntax

```
POST /v1/memberships HTTP/1.1
Content-type: application/json
```

```
{
  "maxResults": number,
  "nextToken": "string"
}
```

## URI Request Parameters

The request does not use any URI parameters.

## Request Body

The request accepts the following data in JSON format.

### maxResults

Request element for ListMemberships to limit the number of responses.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 25.

Required: No

### nextToken

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2000.

Required: No

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "accountId": "string",
      "membershipArn": "string",
      "membershipId": "string",
      "membershipStatus": "string",
      "region": "string"
    }
  ],
  "nextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### items

Request element for ListMemberships including the accountId, membershipARN, membershipID, membershipStatus, and region for each response.

Type: Array of [ListMembershipItem](#) objects

### nextToken

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)



- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTagsForResource

Returns currently configured tags on a resource.

## Request Syntax

```
GET /v1/tags/resourceArn HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

Required element for ListTagsForResource to provide the ARN to identify a specific resource.

Length Constraints: Minimum length of 12. Maximum length of 1010.

Pattern: `arn:aws:security-ir:\w+?-\w+?-\d+:[0-9]{12}:(membership/m-[a-z0-9]{10,32}|case/[0-9]{10})`

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## tags

Response element for ListTagsForResource providing content for each configured tag.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

## ServiceQuotaExceededException

HTTP Status Code: 402

## ThrottlingException

HTTP Status Code: 429

## ValidationException

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Adds a tag(s) to a designated resource.

## Request Syntax

```
POST /v1/tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

Required element for TagResource to identify the ARN for the resource to add a tag to.

Length Constraints: Minimum length of 12. Maximum length of 1010.

Pattern: `arn:aws:security-ir:\w+?-\w+?-\d+:[0-9]{12}:(membership/m-[a-z0-9]{10,32}|case/[0-9]{10})`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### tags

Required element for ListTagsForResource to provide the content for a tag.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

## Response Syntax

```
HTTP/1.1 204
```

## Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Removes a tag(s) from a designate resource.

## Request Syntax

```
DELETE /v1/tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

## URI Request Parameters

The request uses the following URI parameters.

### resourceArn

Required element for UntagResource to identify the ARN for the resource to remove a tag from.

Length Constraints: Minimum length of 12. Maximum length of 1010.

Pattern: `arn:aws:security-ir:\w+?-\w+?-\d+:[0-9]{12}:(membership/m-[a-z0-9]{10,32}|case/[0-9]{10})`

Required: Yes

### tagKeys

Required element for UntagResource to identify tag to remove.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

## Request Body

The request does not have a request body.

## Response Syntax

```
HTTP/1.1 200
```



## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateCase

Updates an existing case.

## Request Syntax

```
POST /v1/cases/caseId/update-case HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "actualIncidentStartDate": number,
  "description": "string",
  "engagementType": "string",
  "impactedAccountsToAdd": [ "string" ],
  "impactedAccountsToDelete": [ "string" ],
  "impactedAwsRegionsToAdd": [
    {
      "region": "string"
    }
  ],
  "impactedAwsRegionsToDelete": [
    {
      "region": "string"
    }
  ],
  "impactedServicesToAdd": [ "string" ],
  "impactedServicesToDelete": [ "string" ],
  "reportedIncidentStartDate": number,
  "threatActorIpAddressesToAdd": [
    {
      "ipAddress": "string",
      "userAgent": "string"
    }
  ],
  "threatActorIpAddressesToDelete": [
    {
      "ipAddress": "string",
      "userAgent": "string"
    }
  ],
  "title": "string",
  "watchersToAdd": [
    {
```

```
    "email": "string",
    "jobTitle": "string",
    "name": "string"
  }
],
"watchersToDelete": [
  {
    "email": "string",
    "jobTitle": "string",
    "name": "string"
  }
]
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element for UpdateCase to identify the case ID for updates.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### actualIncidentStartDate

Optional element for UpdateCase to provide content for the incident start date field.

Type: Timestamp

Required: No

### description

Optional element for UpdateCase to provide content for the description field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 8000.

Required: No

### engagementType

Optional element for UpdateCase to provide content for the engagement type field.  
Available engagement types include Security Incident | Investigation.

Type: String

Valid Values: Security Incident | Investigation

Required: No

### impactedAccountsToAdd

Optional element for UpdateCase to provide content to add accounts impacted.

#### Note

AWS account ID's may appear less than 12 characters and need to be zero-prepended. An example would be 123123123 which is nine digits, and with zero-prepend would be 000123123123. Not zero-prepending to 12 digits could result in errors.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

Required: No

### impactedAccountsToDelete

Optional element for UpdateCase to provide content to add accounts impacted.

**Note**

AWS account ID's may appear less than 12 characters and need to be zero-prepended. An example would be 123123123 which is nine digits, and with zero-prepend would be 000123123123. Not zero-prepending to 12 digits could result in errors.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

Required: No

**impactedAwsRegionsToAdd**

Optional element for UpdateCase to provide content to add regions impacted.

Type: Array of [ImpactedAwsRegion](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

**impactedAwsRegionsToDelete**

Optional element for UpdateCase to provide content to remove regions impacted.

Type: Array of [ImpactedAwsRegion](#) objects

Array Members: Minimum number of 0 items. Maximum number of 50 items.

Required: No

**impactedServicesToAdd**

Optional element for UpdateCase to provide content to add services impacted.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 600 items.

Length Constraints: Minimum length of 3. Maximum length of 50.

Pattern: [a-zA-Z0-9 - . ( ) : ]+

Required: No

### impactedServicesToDelete

Optional element for UpdateCase to provide content to remove services impacted.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 600 items.

Length Constraints: Minimum length of 3. Maximum length of 50.

Pattern: [a-zA-Z0-9 - . ( ) : ]+

Required: No

### reportedIncidentStartDate

Optional element for UpdateCase to provide content for the customer reported incident start date field.

Type: Timestamp

Required: No

### threatActorIpAddressesToAdd

Optional element for UpdateCase to provide content to add additional suspicious IP addresses related to a case.

Type: Array of [ThreatActorIp](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

### threatActorIpAddressesToDelete

Optional element for UpdateCase to provide content to remove suspicious IP addresses from a case.

Type: Array of [ThreatActorIp](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

### [title](#)

Optional element for UpdateCase to provide content for the title field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

### [watchersToAdd](#)

Optional element for UpdateCase to provide content to add additional watchers to a case.

Type: Array of [Watcher](#) objects

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Required: No

### [watchersToDelete](#)

Optional element for UpdateCase to provide content to remove existing watchers from a case.

Type: Array of [Watcher](#) objects

Array Members: Minimum number of 0 items. Maximum number of 30 items.

Required: No

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.



## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateCaseComment

Updates an existing case comment.

## Request Syntax

```
PUT /v1/cases/caseId/update-case-comment/commentId HTTP/1.1  
Content-type: application/json
```

```
{  
  "body": "string"  
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element for UpdateCaseComment to identify the case ID containing the comment to be updated.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

### commentId

Required element for UpdateCaseComment to identify the case ID to be updated.

Length Constraints: Fixed length of 6.

Pattern: `\d{6}`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

## body

Required element for UpdateCaseComment to identify the content for the comment to be updated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12000.

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "body": "string",
  "commentId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### body

Response element for UpdateCaseComment providing the updated comment content.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12000.

### commentId

Response element for UpdateCaseComment providing the updated comment ID.

Type: String

Length Constraints: Fixed length of 6.

Pattern: `\d{6}`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateCaseStatus

Updates the state transitions for a designated cases.

**Self-managed:** the following states are available for self-managed cases.

- Submitted → Detection and Analysis
- Detection and Analysis → Containment, Eradication, and Recovery
- Detection and Analysis → Post-incident Activities
- Containment, Eradication, and Recovery → Detection and Analysis
- Containment, Eradication, and Recovery → Post-incident Activities
- Post-incident Activities → Containment, Eradication, and Recovery
- Post-incident Activities → Detection and Analysis
- Any → Closed

**AWS supported:** You must use the `CloseCase` API to close.

## Request Syntax

```
POST /v1/cases/caseId/update-case-status HTTP/1.1
Content-type: application/json
```

```
{
  "caseStatus": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element for `UpdateCaseStatus` to identify the case to update.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10, 32}.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### caseStatus

Required element for UpdateCaseStatus to identify the status for a case. Options include Submitted | Detection and Analysis | Containment, Eradication and Recovery | Post-incident Activities.

Type: String

Valid Values: Submitted | Detection and Analysis | Containment, Eradication and Recovery | Post-incident Activities

Required: Yes

## Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "caseStatus": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

### caseStatus

Response element for UpdateCaseStatus showing the newly configured status.

Type: String



Valid Values: Submitted | Detection and Analysis | Containment, Eradication and Recovery | Post-incident Activities

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateMembership

Updates membership configuration.

## Request Syntax

```
PUT /v1/membership/membershipId/update-membership HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "incidentResponseTeam": [
    {
      "email": "string",
      "jobTitle": "string",
      "name": "string"
    }
  ],
  "membershipName": "string",
  "optInFeatures": [
    {
      "featureName": "string",
      "isEnabled": boolean
    }
  ]
}
```

## URI Request Parameters

The request uses the following URI parameters.

### membershipId

Required element for UpdateMembership to identify the membership to update.

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: m-[a-z0-9]{10,32}

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### incidentResponseTeam

Optional element for UpdateMembership to update the membership name.

Type: Array of [IncidentResponder](#) objects

Array Members: Minimum number of 2 items. Maximum number of 10 items.

Required: No

### membershipName

Optional element for UpdateMembership to update the membership name.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 50.

Required: No

### optInFeatures

Optional element for UpdateMembership to enable or disable opt-in features for the service.

Type: Array of [OptInFeature](#) objects

Array Members: Minimum number of 1 item. Maximum number of 2 items.

Required: No

## Response Syntax

```
HTTP/1.1 200
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

### **ValidationException**

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateResolverType

Updates the resolver type for a case.

## Important

This is a one-way action and cannot be reversed.

## Request Syntax

```
POST /v1/cases/caseId/update-resolver-type HTTP/1.1
Content-type: application/json
```

```
{
  "resolverType": "string"
}
```

## URI Request Parameters

The request uses the following URI parameters.

### caseId

Required element for UpdateResolverType to identify the case to update.

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

## Request Body

The request accepts the following data in JSON format.

### resolverType

Required element for UpdateResolverType to identify the new resolver.

Type: String

Valid Values: AWS | Self

Required: Yes

## Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "caseId": "string",
  "caseStatus": "string",
  "resolverType": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### caseId

Response element for UpdateResolver identifying the case ID being updated.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

### caseStatus

Response element for UpdateResolver identifying the current status of the case.

Type: String

Valid Values: Submitted | Acknowledged | Detection and Analysis | Containment, Eradication and Recovery | Post-incident Activities | Ready to Close | Closed



## **resolverType**

Response element for UpdateResolver identifying the current resolver of the case.

Type: String

Valid Values: AWS | Self

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

HTTP Status Code: 403

### **ConflictException**

HTTP Status Code: 409

### **InternalServerErrorException**

HTTP Status Code: 500

### **InvalidTokenException**

HTTP Status Code: 423

### **ResourceNotFoundException**

HTTP Status Code: 404

### **SecurityIncidentResponseNotActiveException**

HTTP Status Code: 400

### **ServiceQuotaExceededException**

HTTP Status Code: 402

### **ThrottlingException**

HTTP Status Code: 429

## ValidationException

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The Security Incident Response API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [CaseAttachmentAttributes](#)
- [CaseEditItem](#)
- [GetMembershipAccountDetailError](#)
- [GetMembershipAccountDetailItem](#)
- [ImpactedAwsRegion](#)
- [IncidentResponder](#)
- [ListCasesItem](#)
- [ListCommentsItem](#)
- [ListMembershipItem](#)
- [OptInFeature](#)
- [ThreatActorIp](#)
- [ValidationExceptionField](#)
- [Watcher](#)

# CaseAttachmentAttributes

## Contents

### attachmentId

Type: String

Pattern: `[0-9a-fA-F]{8}\b-[0-9a-fA-F]{4}\b-[0-9a-fA-F]{4}\b-[0-9a-fA-F]{4}\b-[0-9a-fA-F]{12}`

Required: Yes

### attachmentStatus

Type: String

Valid Values: Verified | Failed | Pending

Required: Yes

### createdDate

Type: Timestamp

Required: Yes

### creator

Type: String

Pattern: `.*(^internal:midway:([a-z]{3,8}|svc-mw-[0-9]{12}[a-zA-Z0-9-]{5,20}))$|^external:aws:\d{12}$).*`

Required: Yes

### fileName

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: `[a-zA-Z0-9._-]+`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# CaseEditItem

## Contents

### action

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### eventTimestamp

Type: Timestamp

Required: No

### message

Type: String

Length Constraints: Minimum length of 10. Maximum length of 4096.

Required: No

### principal

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# GetMembershipAccountDetailError

## Contents

### accountId

Type: String

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

Required: Yes

### error

Type: String

Required: Yes

### message

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# GetMembershipAccountDetailItem

## Contents

### accountId

Type: String

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

Required: No

### relationshipStatus

Type: String

Valid Values: Associated | Disassociated

Required: No

### relationshipType

Type: String

Valid Values: Organization

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ImpactedAwsRegion

## Contents

### region

Type: String

Valid Values: af-south-1 | ap-east-1 | ap-northeast-1 | ap-northeast-2 | ap-northeast-3 | ap-south-1 | ap-south-2 | ap-southeast-1 | ap-southeast-2 | ap-southeast-3 | ap-southeast-4 | ap-southeast-5 | ca-central-1 | ca-west-1 | cn-north-1 | cn-northwest-1 | eu-central-1 | eu-central-2 | eu-north-1 | eu-south-1 | eu-south-2 | eu-west-1 | eu-west-2 | eu-west-3 | il-central-1 | me-central-1 | me-south-1 | sa-east-1 | us-east-1 | us-east-2 | us-west-1 | us-west-2

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IncidentResponder

## Contents

### email

Type: String

Length Constraints: Minimum length of 6. Maximum length of 254.

Pattern: `[a-zA-Z0-9.!#$%&'*/=?^_`{|}~-]+@[a-zA-Z0-9-]+(?:\.[a-zA-Z0-9-]+)*`

Required: Yes

### jobTitle

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: Yes

### name

Type: String

Length Constraints: Minimum length of 3. Maximum length of 50.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ListCasesItem

## Contents

### caseId

Type: String

Length Constraints: Minimum length of 10. Maximum length of 32.

Pattern: `\d{10,32}.*`

Required: Yes

### caseArn

Type: String

Length Constraints: Minimum length of 12. Maximum length of 80.

Pattern: `arn:aws:security-ir:\w+?-\w+?-\d+:[0-9]{12}:case/[0-9]{10}`

Required: No

### caseStatus

Type: String

Valid Values: Submitted | Acknowledged | Detection and Analysis | Containment, Eradication and Recovery | Post-incident Activities | Ready to Close | Closed

Required: No

### closedDate

Type: Timestamp

Required: No

**createdDate**

Type: Timestamp

Required: No

**engagementType**

Type: String

Valid Values: Security Incident | Investigation

Required: No

**lastUpdatedDate**

Type: Timestamp

Required: No

**pendingAction**

Type: String

Valid Values: Customer | None

Required: No

**resolverType**

Type: String

Valid Values: AWS | Self

Required: No

**title**

Type: String

Length Constraints: Minimum length of 1. Maximum length of 300.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ListCommentsItem

## Contents

### commentId

Type: String

Length Constraints: Fixed length of 6.

Pattern: `\d{6}`

Required: Yes

### body

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12000.

Required: No

### createdDate

Type: Timestamp

Required: No

### creator

Type: String

Pattern: `.*(^internal:midway:([a-z]{3,8}|svc-mw-[0-9]{12}[a-zA-Z0-9-]{5,20}))$|^external:aws:\d{12}$).*`

Required: No

### lastUpdatedBy

Type: String

Pattern: `.*(^internal:midway:([a-z]{3,8}|svc-mw-[0-9]{12}[a-zA-Z0-9-]{5,20}))|(^external:aws:\d{12}$).*`

Required: No

## **lastUpdatedDate**

Type: Timestamp

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ListMembershipItem

## Contents

### membershipId

Type: String

Length Constraints: Minimum length of 12. Maximum length of 34.

Pattern: m-[a-z0-9]{10,32}

Required: Yes

### accountId

Type: String

Length Constraints: Fixed length of 12.

Pattern: [0-9]{12}

Required: No

### membershipArn

Type: String

Length Constraints: Minimum length of 12. Maximum length of 80.

Pattern: arn:aws:security-ir:\w+?-\w+?-\d+:[0-9]{12}:membership/m-[a-z0-9]{10,32}

Required: No

### membershipStatus

Type: String

Valid Values: Active | Cancelled | Terminated

Required: No

## region

Type: String

Valid Values: af-south-1 | ap-east-1 | ap-northeast-1 | ap-northeast-2 | ap-northeast-3 | ap-south-1 | ap-south-2 | ap-southeast-1 | ap-southeast-2 | ap-southeast-3 | ap-southeast-4 | ap-southeast-5 | ca-central-1 | ca-west-1 | cn-north-1 | cn-northwest-1 | eu-central-1 | eu-central-2 | eu-north-1 | eu-south-1 | eu-south-2 | eu-west-1 | eu-west-2 | eu-west-3 | il-central-1 | me-central-1 | me-south-1 | sa-east-1 | us-east-1 | us-east-2 | us-west-1 | us-west-2

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# OptInFeature

## Contents

### featureName

Type: String

Valid Values: Triage

Required: Yes

### isEnabled

Type: Boolean

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ThreatActorIp

## Contents

### ipAddress

Type: String

Pattern: `(?:((?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?))|((?:[A-F0-9]{1,4}:){7}[A-F0-9]{1,4})|((?:[A-F0-9]{1,4}:){6}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(?:25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)`

Required: Yes

### userAgent

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ValidationExceptionField

## Contents

### message

Type: String

Required: Yes

### name

Type: String

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Watcher

## Contents

### email

Type: String

Length Constraints: Minimum length of 6. Maximum length of 254.

Pattern: `[a-zA-Z0-9.!#$%&'*/=?^_`{|}~-]+@[a-zA-Z0-9-]+(?:\.[a-zA-Z0-9-]+)*`

Required: Yes

### jobTitle

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

### name

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-Date**

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 403

## **ExpiredTokenException**

The security token included in the request is expired

HTTP Status Code: 403

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 403

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **MalformedHttpRequestException**

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 401

## **OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

### **RequestAbortedException**

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

### **RequestEntityTooLargeException**

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

### **RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

### **RequestTimeoutException**

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

### **ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

### **ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

### **UnrecognizedClientException**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

**UnknownOperationException**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400