



Amazon SES Mail Manager API Reference

# Amazon SES Mail Manager API



**API Version 2023-10-17**

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# Amazon SES Mail Manager API: Amazon SES Mail Manager API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

---

# Table of Contents

<b>Welcome .....</b>	<b>1</b>
<b>Actions .....</b>	<b>2</b>
<b>CreateAddonInstance .....</b>	<b>4</b>
Request Syntax .....	4
Request Parameters .....	4
Response Syntax .....	5
Response Elements .....	5
Errors .....	5
See Also .....	6
<b>CreateAddonSubscription .....</b>	<b>7</b>
Request Syntax .....	7
Request Parameters .....	7
Response Syntax .....	8
Response Elements .....	8
Errors .....	8
See Also .....	9
<b>CreateArchive .....</b>	<b>10</b>
Request Syntax .....	10
Request Parameters .....	10
Response Syntax .....	11
Response Elements .....	11
Errors .....	12
See Also .....	13
<b>CreateIngressPoint .....</b>	<b>14</b>
Request Syntax .....	14
Request Parameters .....	14
Response Syntax .....	16
Response Elements .....	16
Errors .....	16
See Also .....	17
<b>CreateRelay .....</b>	<b>18</b>
Request Syntax .....	18
Request Parameters .....	18
Response Syntax .....	20

---

Response Elements .....	20
Errors .....	20
See Also .....	21
CreateRuleSet .....	22
Request Syntax .....	22
Request Parameters .....	22
Response Syntax .....	23
Response Elements .....	24
Errors .....	24
See Also .....	24
CreateTrafficPolicy .....	26
Request Syntax .....	26
Request Parameters .....	26
Response Syntax .....	28
Response Elements .....	28
Errors .....	28
See Also .....	29
DeleteAddonInstance .....	30
Request Syntax .....	30
Request Parameters .....	30
Response Elements .....	30
Errors .....	30
See Also .....	31
DeleteAddonSubscription .....	32
Request Syntax .....	32
Request Parameters .....	32
Response Elements .....	32
Errors .....	32
See Also .....	33
DeleteArchive .....	34
Request Syntax .....	34
Request Parameters .....	34
Response Elements .....	34
Errors .....	34
See Also .....	35
DeleteIngressPoint .....	36

---

Request Syntax .....	36
Request Parameters .....	36
Response Elements .....	36
Errors .....	36
See Also .....	37
DeleteRelay .....	38
Request Syntax .....	38
Request Parameters .....	38
Response Elements .....	38
Errors .....	38
See Also .....	39
DeleteRuleSet .....	40
Request Syntax .....	40
Request Parameters .....	40
Response Elements .....	40
Errors .....	40
See Also .....	41
DeleteTrafficPolicy .....	42
Request Syntax .....	42
Request Parameters .....	42
Response Elements .....	42
Errors .....	42
See Also .....	43
GetAddonInstance .....	44
Request Syntax .....	44
Request Parameters .....	44
Response Syntax .....	44
Response Elements .....	44
Errors .....	45
See Also .....	46
GetAddonSubscription .....	47
Request Syntax .....	47
Request Parameters .....	47
Response Syntax .....	47
Response Elements .....	47
Errors .....	48

---

See Also .....	48
GetArchive .....	50
Request Syntax .....	50
Request Parameters .....	50
Response Syntax .....	50
Response Elements .....	51
Errors .....	52
See Also .....	53
GetArchiveExport .....	54
Request Syntax .....	54
Request Parameters .....	54
Response Syntax .....	54
Response Elements .....	55
Errors .....	56
See Also .....	56
GetArchiveMessage .....	58
Request Syntax .....	58
Request Parameters .....	58
Response Syntax .....	58
Response Elements .....	58
Errors .....	59
See Also .....	59
GetArchiveMessageContent .....	60
Request Syntax .....	60
Request Parameters .....	60
Response Syntax .....	60
Response Elements .....	60
Errors .....	61
See Also .....	61
GetArchiveSearch .....	63
Request Syntax .....	63
Request Parameters .....	63
Response Syntax .....	63
Response Elements .....	64
Errors .....	65
See Also .....	65

---

GetArchiveSearchResults .....	67
Request Syntax .....	67
Request Parameters .....	67
Response Syntax .....	67
Response Elements .....	68
Errors .....	68
See Also .....	69
GetIngressPoint .....	70
Request Syntax .....	70
Request Parameters .....	70
Response Syntax .....	70
Response Elements .....	71
Errors .....	73
See Also .....	73
GetRelay .....	74
Request Syntax .....	74
Request Parameters .....	74
Response Syntax .....	74
Response Elements .....	75
Errors .....	76
See Also .....	76
GetRuleSet .....	78
Request Syntax .....	78
Request Parameters .....	78
Response Syntax .....	78
Response Elements .....	79
Errors .....	80
See Also .....	80
GetTrafficPolicy .....	82
Request Syntax .....	82
Request Parameters .....	82
Response Syntax .....	82
Response Elements .....	83
Errors .....	84
See Also .....	84
ListAddonInstances .....	86

---

Request Syntax .....	86
Request Parameters .....	86
Response Syntax .....	86
Response Elements .....	87
Errors .....	87
See Also .....	88
ListAddonSubscriptions .....	89
Request Syntax .....	89
Request Parameters .....	89
Response Syntax .....	89
Response Elements .....	90
Errors .....	90
See Also .....	91
ListArchiveExports .....	92
Request Syntax .....	92
Request Parameters .....	92
Response Syntax .....	93
Response Elements .....	93
Errors .....	94
See Also .....	94
ListArchives .....	96
Request Syntax .....	96
Request Parameters .....	96
Response Syntax .....	97
Response Elements .....	97
Errors .....	97
See Also .....	98
ListArchiveSearches .....	99
Request Syntax .....	99
Request Parameters .....	99
Response Syntax .....	100
Response Elements .....	100
Errors .....	101
See Also .....	101
ListIngressPoints .....	103
Request Syntax .....	103



---

Request Parameters .....	103
Response Syntax .....	103
Response Elements .....	104
Errors .....	104
See Also .....	105
ListRelays .....	106
Request Syntax .....	106
Request Parameters .....	106
Response Syntax .....	106
Response Elements .....	107
Errors .....	107
See Also .....	108
ListRuleSets .....	109
Request Syntax .....	109
Request Parameters .....	109
Response Syntax .....	109
Response Elements .....	110
Errors .....	110
See Also .....	111
ListTagsForResource .....	112
Request Syntax .....	112
Request Parameters .....	112
Response Syntax .....	112
Response Elements .....	113
Errors .....	113
See Also .....	113
ListTrafficPolicies .....	115
Request Syntax .....	115
Request Parameters .....	115
Response Syntax .....	115
Response Elements .....	116
Errors .....	116
See Also .....	117
StartArchiveExport .....	118
Request Syntax .....	118
Request Parameters .....	118

Response Syntax .....	119
Response Elements .....	120
Errors .....	120
See Also .....	121
StartArchiveSearch .....	122
Request Syntax .....	122
Request Parameters .....	122
Response Syntax .....	123
Response Elements .....	123
Errors .....	124
See Also .....	124
StopArchiveExport .....	126
Request Syntax .....	126
Request Parameters .....	126
Response Elements .....	126
Errors .....	126
See Also .....	127
StopArchiveSearch .....	128
Request Syntax .....	128
Request Parameters .....	128
Response Elements .....	128
Errors .....	128
See Also .....	129
TagResource .....	130
Request Syntax .....	130
Request Parameters .....	130
Response Elements .....	131
Errors .....	131
See Also .....	131
UntagResource .....	133
Request Syntax .....	133
Request Parameters .....	133
Response Elements .....	134
Errors .....	134
See Also .....	134
UpdateArchive .....	136

Request Syntax .....	136
Request Parameters .....	136
Response Elements .....	137
Errors .....	137
See Also .....	138
<b>UpdateIngressPoint .....</b>	<b>139</b>
Request Syntax .....	139
Request Parameters .....	139
Response Elements .....	140
Errors .....	141
See Also .....	141
<b>UpdateRelay .....</b>	<b>142</b>
Request Syntax .....	142
Request Parameters .....	142
Response Elements .....	143
Errors .....	143
See Also .....	144
<b>UpdateRuleSet .....</b>	<b>145</b>
Request Syntax .....	145
Request Parameters .....	145
Response Elements .....	146
Errors .....	146
See Also .....	147
<b>UpdateTrafficPolicy .....</b>	<b>148</b>
Request Syntax .....	148
Request Parameters .....	148
Response Elements .....	149
Errors .....	149
See Also .....	150
<b>Data Types .....</b>	<b>151</b>
<b>AddHeaderAction .....</b>	<b>154</b>
Contents .....	154
See Also .....	154
<b>AddonInstance .....</b>	<b>155</b>
Contents .....	155
See Also .....	156

AddonSubscription .....	157
Contents .....	157
See Also .....	157
Analysis .....	159
Contents .....	159
See Also .....	159
Archive .....	160
Contents .....	160
See Also .....	161
ArchiveAction .....	162
Contents .....	162
See Also .....	162
ArchiveBooleanExpression .....	163
Contents .....	163
See Also .....	163
ArchiveBooleanToEvaluate .....	164
Contents .....	164
See Also .....	164
ArchiveFilterCondition .....	165
Contents .....	165
See Also .....	165
ArchiveFilters .....	166
Contents .....	166
See Also .....	166
ArchiveRetention .....	167
Contents .....	167
See Also .....	167
ArchiveStringExpression .....	168
Contents .....	168
See Also .....	168
ArchiveStringToEvaluate .....	170
Contents .....	170
See Also .....	170
DeliverToMailboxAction .....	171
Contents .....	171
See Also .....	172

DropAction .....	173
Contents .....	173
See Also .....	173
ExportDestinationConfiguration .....	174
Contents .....	174
See Also .....	174
ExportStatus .....	175
Contents .....	175
See Also .....	175
ExportSummary .....	177
Contents .....	177
See Also .....	177
IngressAnalysis .....	178
Contents .....	178
See Also .....	178
IngressBooleanExpression .....	179
Contents .....	179
See Also .....	179
IngressBooleanToEvaluate .....	180
Contents .....	180
See Also .....	180
IngressIpToEvaluate .....	181
Contents .....	181
See Also .....	181
IngressIpv4Expression .....	182
Contents .....	182
See Also .....	182
IngressPoint .....	184
Contents .....	184
See Also .....	185
IngressPointAuthConfiguration .....	186
Contents .....	186
See Also .....	186
IngressPointConfiguration .....	187
Contents .....	187
See Also .....	187

IngressPointPasswordConfiguration .....	189
Contents .....	189
See Also .....	189
IngressStringExpression .....	190
Contents .....	190
See Also .....	190
IngressStringToEvaluate .....	192
Contents .....	192
See Also .....	192
IngressTlsProtocolExpression .....	193
Contents .....	193
See Also .....	193
IngressTlsProtocolToEvaluate .....	195
Contents .....	195
See Also .....	195
MessageBody .....	196
Contents .....	196
See Also .....	196
NoAuthentication .....	197
Contents .....	197
See Also .....	197
PolicyCondition .....	198
Contents .....	198
See Also .....	199
PolicyStatement .....	200
Contents .....	200
See Also .....	200
Relay .....	201
Contents .....	201
See Also .....	201
RelayAction .....	203
Contents .....	203
See Also .....	203
RelayAuthentication .....	205
Contents .....	205
See Also .....	205

ReplaceRecipientAction .....	207
Contents .....	207
See Also .....	207
Row .....	208
Contents .....	208
See Also .....	210
Rule .....	211
Contents .....	211
See Also .....	212
RuleAction .....	213
Contents .....	213
See Also .....	214
RuleBooleanExpression .....	215
Contents .....	215
See Also .....	215
RuleBooleanToEvaluate .....	216
Contents .....	216
See Also .....	216
RuleCondition .....	217
Contents .....	217
See Also .....	218
RuleDmarcExpression .....	219
Contents .....	219
See Also .....	219
RuleIpExpression .....	221
Contents .....	221
See Also .....	222
RuleIpToEvaluate .....	223
Contents .....	223
See Also .....	223
RuleNumberExpression .....	224
Contents .....	224
See Also .....	224
RuleNumberToEvaluate .....	226
Contents .....	226
See Also .....	226

RuleSet .....	227
Contents .....	227
See Also .....	227
RuleStringExpression .....	229
Contents .....	229
See Also .....	230
RuleStringToEvaluate .....	231
Contents .....	231
See Also .....	231
RuleVerdictExpression .....	232
Contents .....	232
See Also .....	233
RuleVerdictToEvaluate .....	234
Contents .....	234
See Also .....	234
S3Action .....	235
Contents .....	235
See Also .....	236
S3ExportDestinationConfiguration .....	237
Contents .....	237
See Also .....	237
SearchStatus .....	238
Contents .....	238
See Also .....	238
SearchSummary .....	240
Contents .....	240
See Also .....	240
SendAction .....	241
Contents .....	241
See Also .....	241
Tag .....	242
Contents .....	242
See Also .....	242
TrafficPolicy .....	243
Contents .....	243
See Also .....	243



<b>Common Parameters .....</b>	<b>245</b>
<b>Common Errors .....</b>	<b>248</b>

# Welcome

Welcome to the Amazon SES Mail Manager API Reference. This guide provides information about the Amazon SES Mail Manager API, including supported operations, data types, parameters, and schemas.

The Amazon SES Mail Manager API contains operations and data types that comprise the Mail Manager feature of [Amazon Simple Email Service \(SES\)](#).

Mail Manager is a set of Amazon SES email gateway features designed to help you strengthen your organization's email infrastructure, simplify email workflow management, and streamline email compliance control. To learn more, see the [Mail Manager chapter](#) in the *Amazon SES Developer Guide*.

The Amazon SES Mail Manager API is available in several AWS Regions and it provides an endpoint for each of these Regions. For more information, see [Amazon SES endpoints and quotas](#) in the *Amazon Web Services General Reference*. To learn more about AWS Regions, see [Managing AWS Regions](#) in the *Amazon Web Services General Reference*.

This document was last published on June 25, 2024.

# Actions

The following actions are supported:

- [CreateAddonInstance](#)
- [CreateAddonSubscription](#)
- [CreateArchive](#)
- [CreateIngressPoint](#)
- [CreateRelay](#)
- [CreateRuleSet](#)
- [CreateTrafficPolicy](#)
- [DeleteAddonInstance](#)
- [DeleteAddonSubscription](#)
- [DeleteArchive](#)
- [DeleteIngressPoint](#)
- [DeleteRelay](#)
- [DeleteRuleSet](#)
- [DeleteTrafficPolicy](#)
- [GetAddonInstance](#)
- [GetAddonSubscription](#)
- [GetArchive](#)
- [GetArchiveExport](#)
- [GetArchiveMessage](#)
- [GetArchiveMessageContent](#)
- [GetArchiveSearch](#)
- [GetArchiveSearchResults](#)
- [GetIngressPoint](#)
- [GetRelay](#)
- [GetRuleSet](#)
- [GetTrafficPolicy](#)
- [ListAddonInstances](#)

- [ListAddonSubscriptions](#)
- [ListArchiveExports](#)
- [ListArchives](#)
- [ListArchiveSearches](#)
- [ListIngressPoints](#)
- [ListRelays](#)
- [ListRuleSets](#)
- [ListTagsForResource](#)
- [ListTrafficPolicies](#)
- [StartArchiveExport](#)
- [StartArchiveSearch](#)
- [StopArchiveExport](#)
- [StopArchiveSearch](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateArchive](#)
- [UpdateIngressPoint](#)
- [UpdateRelay](#)
- [UpdateRuleSet](#)
- [UpdateTrafficPolicy](#)

# CreateAddonInstance

Creates an Add On instance for the subscription indicated in the request. The resulting Amazon Resource Name (ARN) can be used in a conditional statement for a rule set or traffic policy.

## Request Syntax

```
{
  "AddonSubscriptionId": "string",
  "ClientToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [AddonSubscriptionId](#)

The unique ID of a previously created subscription that an Add On instance is created for. You can only have one instance per subscription.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^as-[a-zA-Z0-9]{1,64}$`

Required: Yes

### [ClientToken](#)

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": {"key1":"value1", "key2":"value2"} }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{  
  "AddonInstanceId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### AddonInstanceId

The unique ID of the Add On instance created by this API.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^ai-[a-zA-Z0-9]{1,64}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

## ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateAddonSubscription

Creates a subscription for an Add On representing the acceptance of its terms of use and additional pricing. The subscription can then be used to create an instance for use in rule sets or traffic policies.

## Request Syntax

```
{
  "AddonName": "string",
  "ClientToken": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### AddonName

The name of the Add On to subscribe to. You can only have one subscription for each Add On name.

Type: String

Required: Yes

### ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No



## Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": {"key1": "value1", "key2": "value2"} }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{
  "AddonSubscriptionId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [AddonSubscriptionId](#)

The unique ID of the Add On subscription created by this API.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^as-[a-zA-Z0-9]{1,64}$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateArchive

Creates a new email archive resource for storing and retaining emails.

## Request Syntax

```
{
  "ArchiveName": "string",
  "ClientToken": "string",
  "KmsKeyArn": "string",
  "Retention": { ... },
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveName

A unique name for the new archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]$`

Required: Yes

### ClientToken

A unique token Amazon SES uses to recognize retries of this request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### KmsKeyArn

The Amazon Resource Name (ARN) of the KMS key for encrypting emails in the archive.

Type: String

Pattern: `^arn:aws(|-cn|-us-gov):kms:[a-z0-9-]{1,20}:[0-9]{12}:(key|alias)/.+`

Required: No

### Retention

The period for retaining emails in the archive before automatic deletion.

Type: [ArchiveRetention](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

### Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{
  "ArchiveId": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Archived

The unique identifier for the newly created archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateIngressPoint

Provision a new ingress endpoint resource.

## Request Syntax

```
{
  "ClientToken": "string",
  "IngressPointConfiguration": { ... },
  "IngressPointName": "string",
  "RuleSetId": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TrafficPolicyId": "string",
  "Type": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### IngressPointConfiguration

If you choose an Authenticated ingress endpoint, you must configure either an SMTP password or a secret ARN.

Type: [IngressPointConfiguration](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

### IngressPointName

A user friendly name for an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

Required: Yes

### RuleSetId

The identifier of an existing rule set that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

### TrafficPolicyId

The identifier of an existing traffic policy that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.



Required: Yes

## Type

The type of the ingress endpoint to create.

Type: String

Valid Values: OPEN | AUTH

Required: Yes

## Response Syntax

```
{  
  "IngressPointId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### IngressPointId

The unique identifier for a previously created ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateRelay

Creates a relay resource which can be used in rules to relay incoming emails to defined relay destinations.

## Request Syntax

```
{
  "Authentication": { ... },
  "ClientToken": "string",
  "RelayName": "string",
  "ServerName": "string",
  "ServerPort": number,
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [Authentication](#)

Authentication for the relay destination server—specify the secretARN where the SMTP credentials are stored.

Type: [RelayAuthentication](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### [ClientToken](#)

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

### RelayName

The unique name of the relay resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-_$]`

Required: Yes

### ServerName

The destination relay server address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-\.]`

Required: Yes

### ServerPort

The destination relay server port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: Yes

### Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{  
  "RelayId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### RelayId

A unique identifier of the created relay resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-]+$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateRuleSet

Provision a new rule set.

## Request Syntax

```
{
  "ClientToken": "string",
  "Rules": [
    {
      "Actions": [
        { ... }
      ],
      "Conditions": [
        { ... }
      ],
      "Name": "string",
      "Unless": [
        { ... }
      ]
    }
  ],
  "RuleSetName": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## Rules

Conditional rules that are evaluated for determining actions on email.

Type: Array of [Rule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: Yes

## RuleSetName

A user-friendly name for the rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9_.-]+$`

Required: Yes

## Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## Response Syntax

```
{
  "RuleSetId": "string"
}
```



## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### RuleSetId

The identifier of the created rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateTrafficPolicy

Provision a new traffic policy resource.

## Request Syntax

```
{
  "ClientToken": "string",
  "DefaultAction": "string",
  "MaxMessageSizeBytes": number,
  "PolicyStatements": [
    {
      "Action": "string",
      "Conditions": [
        { ... }
      ]
    }
  ],
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ],
  "TrafficPolicyName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ClientToken

A unique token that Amazon SES uses to recognize subsequent retries of the same request.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: No

## DefaultAction

Default action instructs the traffic policy to either Allow or Deny (block) messages that fall outside of (or not addressed by) the conditions of your policy statements

Type: String

Valid Values: ALLOW | DENY

Required: Yes

## MaxMessageSizeBytes

The maximum message size in bytes of email which is allowed in by this traffic policy—anything larger will be blocked.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

## PolicyStatements

Conditional statements for filtering email traffic.

Type: Array of [PolicyStatement](#) objects

Required: Yes

## Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

## TrafficPolicyName

A user-friendly name for the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

Required: Yes

## Response Syntax

```
{  
  "TrafficPolicyId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [TrafficPolicyId](#)

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteAddonInstance

Deletes an Add On instance.

## Request Syntax

```
{  
  "AddonInstanceId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### AddonInstanceId

The Add On instance ID to delete.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^ai-[a-zA-Z0-9]{1,64}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteAddonSubscription

Deletes an Add On subscription.

## Request Syntax

```
{  
  "AddonSubscriptionId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### AddonSubscriptionId

The Add On subscription ID to delete.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^as-[a-zA-Z0-9]{1,64}$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteArchive

Initiates deletion of an email archive. This changes the archive state to pending deletion. In this state, no new emails can be added, and existing archived emails become inaccessible (search, export, download). The archive and all of its contents will be permanently deleted 30 days after entering the pending deletion state, regardless of the configured retention period.

## Request Syntax

```
{  
  "ArchiveId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveId

The identifier of the archive to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteIngressPoint

Delete an ingress endpoint resource.

## Request Syntax

```
{  
  "IngressPointId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### IngressPointId

The identifier of the ingress endpoint resource that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteRelay

Deletes an existing relay resource.

## Request Syntax

```
{  
  "RelayId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### RelayId

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-]+$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DeleteRuleSet

Delete a rule set.

## Request Syntax

```
{  
  "RuleSetId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### RuleSetId

The identifier of an existing rule set resource to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteTrafficPolicy

Delete a traffic policy resource.

## Request Syntax

```
{  
  "TrafficPolicyId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### TrafficPolicyId

The identifier of the traffic policy that you want to delete.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAddonInstance

Gets detailed information about an Add On instance.

## Request Syntax

```
{  
  "AddonInstanceId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [AddonInstanceId](#)

The Add On instance ID to retrieve information for.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^ai-[a-zA-Z0-9]{1,64}$`

Required: Yes

## Response Syntax

```
{  
  "AddonInstanceArn": "string",  
  "AddonName": "string",  
  "AddonSubscriptionId": "string",  
  "CreatedTimestamp": number  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### AddonInstanceArn

The Amazon Resource Name (ARN) of the Add On instance.

Type: String

### AddonName

The name of the Add On provider associated to the subscription of the instance.

Type: String

### AddonSubscriptionId

The subscription ID associated to the instance.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^as-[a-zA-Z0-9]{1,64}$`

### CreatedTimestamp

The timestamp of when the Add On instance was created.

Type: Timestamp

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetAddonSubscription

Gets detailed information about an Add On subscription.

## Request Syntax

```
{  
  "AddonSubscriptionId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### AddonSubscriptionId

The Add On subscription ID to retrieve information for.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^as-[a-zA-Z0-9]{1,64}$`

Required: Yes

## Response Syntax

```
{  
  "AddonName": "string",  
  "AddonSubscriptionArn": "string",  
  "CreatedTimestamp": number  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.



The following data is returned in JSON format by the service.

### AddonName

The name of the Add On for the subscription.

Type: String

### AddonSubscriptionArn

Amazon Resource Name (ARN) for the subscription.

Type: String

### CreatedTimestamp

The timestamp of when the Add On subscription was created.

Type: Timestamp

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetArchive

Retrieves the full details and current state of a specified email archive.

## Request Syntax

```
{  
  "ArchiveId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveId

The identifier of the archive to retrieve.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

## Response Syntax

```
{  
  "ArchiveArn": "string",  
  "ArchiveId": "string",  
  "ArchiveName": "string",  
  "ArchiveState": "string",  
  "CreatedTimestamp": number,  
  "KmsKeyArn": "string",  
  "LastUpdatedTimestamp": number,  
  "Retention": { ... }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### ArchiveArn

The Amazon Resource Name (ARN) of the archive.

Type: String

### ArchiveId

The unique identifier of the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

### ArchiveName

The unique name assigned to the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]$`

### ArchiveState

The current state of the archive:

- **ACTIVE** – The archive is ready and available for use.
- **PENDING\_DELETION** – The archive has been marked for deletion and will be permanently deleted in 30 days. No further modifications can be made in this state.

Type: String

Valid Values: **ACTIVE** | **PENDING\_DELETION**

### CreatedTimestamp

The timestamp of when the archive was created.

Type: Timestamp

### KmsKeyArn

The Amazon Resource Name (ARN) of the KMS key used to encrypt the archive.

Type: String

Pattern: `^arn:aws(|-cn|-us-gov):kms:[a-z0-9-]{1,20}:[0-9]{12}:(key|alias)/.+`

### LastUpdatedTimestamp

The timestamp of when the archive was modified.

Type: Timestamp

### Retention

The retention period for emails in this archive.

Type: [ArchiveRetention](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetArchiveExport

Retrieves the details and current status of a specific email archive export job.

## Request Syntax

```
{  
  "ExportId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ExportId

The identifier of the export job to get details for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

## Response Syntax

```
{  
  "ArchiveId": "string",  
  "ExportDestinationConfiguration": { ... },  
  "Filters": {  
    "Include": [  
      { ... }  
    ],  
    "Unless": [  
      { ... }  
    ]  
  },  
  "FromTimestamp": number,
```

```
"MaxResults": number,
"Status": {
  "CompletionTimestamp": number,
  "ErrorMessage": "string",
  "State": "string",
  "SubmissionTimestamp": number
},
"ToTimestamp": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Archived

The identifier of the archive the email export was performed from.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: `^a-[\w]{1,64}$`

### ExportDestinationConfiguration

Where the exported emails are being delivered.

Type: [ExportDestinationConfiguration](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

### Filters

The criteria used to filter emails included in the export.

Type: [ArchiveFilters](#) object

### FromTimestamp

The start of the timestamp range the exported emails cover.

Type: Timestamp



## MaxResults

The maximum number of email items included in the export.

Type: Integer

## Status

The current status of the export job.

Type: [ExportStatus](#) object

## ToTimestamp

The end of the date range the exported emails cover.

Type: Timestamp

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetArchiveMessage

Returns a pre-signed URL that provides temporary download access to the specific email message stored in the archive.

## Request Syntax

```
{  
  "ArchivedMessageId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchivedMessageId

The unique identifier of the archived email message.

Type: String

Required: Yes

## Response Syntax

```
{  
  "MessageDownloadLink": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### MessageDownloadLink

A pre-signed URL to temporarily download the full message content.

Type: String

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetArchiveMessageContent

Returns the textual content of a specific email message stored in the archive. Attachments are not included.

## Request Syntax

```
{  
  "ArchivedMessageId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchivedMessageId

The unique identifier of the archived email message.

Type: String

Required: Yes

## Response Syntax

```
{  
  "Body": {  
    "Html": "string",  
    "MessageMalformed": boolean,  
    "Text": "string"  
  }  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## **Body**

The textual body content of the email message.

Type: [MessageBody](#) object

## **Errors**

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetArchiveSearch

Retrieves the details and current status of a specific email archive search job.

## Request Syntax

```
{  
  "SearchId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### SearchId

The identifier of the search job to get details for.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

## Response Syntax

```
{  
  "ArchiveId": "string",  
  "Filters": {  
    "Include": [  
      { ... }  
    ],  
    "Unless": [  
      { ... }  
    ]  
  },  
  "FromTimestamp": number,  
  "MaxResults": number,
```



```
"Status": {  
  "CompletionTimestamp": number,  
  "ErrorMessage": "string",  
  "State": "string",  
  "SubmissionTimestamp": number  
},  
"ToTimestamp": number  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Archived

The identifier of the archive the email search was performed in.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: `^a-[\w]{1,64}$`

### Filters

The criteria used to filter emails included in the search.

Type: [ArchiveFilters](#) object

### FromTimestamp

The start timestamp of the range the searched emails cover.

Type: Timestamp

### MaxResults

The maximum number of search results to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

## Status

The current status of the search job.

Type: [SearchStatus](#) object

## ToTimestamp

The end timestamp of the range the searched emails cover.

Type: Timestamp

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetArchiveSearchResults

Returns the results of a completed email archive search job.

## Request Syntax

```
{  
  "SearchId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### SearchId

The identifier of the completed search job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

## Response Syntax

```
{  
  "Rows": [  
    {  
      "ArchivedMessageId": "string",  
      "Cc": "string",  
      "Date": "string",  
      "From": "string",  
      "HasAttachments": boolean,  
      "InReplyTo": "string",  
      "MessageId": "string",  
      "ReceivedHeaders": [ "string" ],  
      "ReceivedTimestamp": number,  
      "Subject": "string",
```

```
    "To": "string",
    "XMailer": "string",
    "XOriginalMailer": "string",
    "XPriority": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Rows

The list of email result objects matching the search criteria.

Type: Array of [Row](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetIngressPoint

Fetch ingress endpoint resource attributes.

## Request Syntax

```
{  
  "IngressPointId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### IngressPointId

The identifier of an ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{  
  "AResult": "string",  
  "CreatedTimestamp": number,  
  "IngressPointArn": "string",  
  "IngressPointAuthConfiguration": {  
    "IngressPointPasswordConfiguration": {  
      "PreviousSmtppasswordExpiryTimestamp": number,  
      "PreviousSmtppasswordVersion": "string",  
      "SmtppasswordVersion": "string"  
    },  
    "SecretArn": "string"  
  },  
  "IngressPointId": "string",
```

```
"IngressPointName": "string",
"LastUpdatedTimestamp": number,
"RuleSetId": "string",
"Status": "string",
"TrafficPolicyId": "string",
"Type": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [ARecord](#)

The DNS A Record that identifies your ingress endpoint. Configure your DNS Mail Exchange (MX) record with this value to route emails to Mail Manager.

Type: String

### [CreatedTimestamp](#)

The timestamp of when the ingress endpoint was created.

Type: Timestamp

### [IngressPointArn](#)

The Amazon Resource Name (ARN) of the ingress endpoint resource.

Type: String

### [IngressPointAuthConfiguration](#)

The authentication configuration of the ingress endpoint resource.

Type: [IngressPointAuthConfiguration](#) object

### [IngressPointId](#)

The identifier of an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.



## IngressPointName

A user friendly name for the ingress endpoint.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

## LastUpdatedTimestamp

The timestamp of when the ingress endpoint was last updated.

Type: Timestamp

## RuleSetId

The identifier of a rule set resource associated with the ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

## Status

The status of the ingress endpoint resource.

Type: String

Valid Values: PROVISIONING | DEPROVISIONING | UPDATING | ACTIVE | CLOSED | FAILED

## TrafficPolicyId

The identifier of the traffic policy resource associated with the ingress endpoint.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

## Type

The type of ingress endpoint.

Type: String

Valid Values: OPEN | AUTH

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetRelay

Fetch the relay resource and its attributes.

## Request Syntax

```
{  
  "RelayId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### RelayId

A unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-]+$`

Required: Yes

## Response Syntax

```
{  
  "Authentication": { ... },  
  "CreatedTimestamp": number,  
  "LastModifiedTimestamp": number,  
  "RelayArn": "string",  
  "RelayId": "string",  
  "RelayName": "string",  
  "ServerName": "string",  
  "ServerPort": number  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Authentication

The authentication attribute—contains the secret ARN where the customer relay server credentials are stored.

Type: [RelayAuthentication](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

### CreatedTimestamp

The timestamp of when the relay was created.

Type: Timestamp

### LastModifiedTimestamp

The timestamp of when relay was last updated.

Type: Timestamp

### RelayArn

The Amazon Resource Name (ARN) of the relay.

Type: String

### RelayId

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-]+$`

### RelayName

The unique name of the relay.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-_$]`

### ServerName

The destination relay server address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-\.\.]+$`

### ServerPort

The destination relay server port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetRuleSet

Fetch attributes of a rule set.

## Request Syntax

```
{  
  "RuleSetId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### RuleSetId

The identifier of an existing rule set to be retrieved.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{  
  "CreatedDate": number,  
  "LastModificationDate": number,  
  "Rules": [  
    {  
      "Actions": [  
        { ... }  
      ],  
      "Conditions": [  
        { ... }  
      ],  
      "Name": "string",  
      "Unless": [  

```

```
        { ... }
      ]
    }
  ],
  "RuleSetArn": "string",
  "RuleSetId": "string",
  "RuleSetName": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### CreatedDate

The date of when the rule set was created.

Type: Timestamp

### LastModificationDate

The date of when the rule set was last modified.

Type: Timestamp

### Rules

The rules contained in the rule set.

Type: Array of [Rule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

### RuleSetArn

The Amazon Resource Name (ARN) of the rule set resource.

Type: String

### RuleSetId

The identifier of the rule set resource.

Type: String



Length Constraints: Minimum length of 1. Maximum length of 100.

### RuleSetName

A user-friendly name for the rule set resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9_.-]+$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# GetTrafficPolicy

Fetch attributes of a traffic policy resource.

## Request Syntax

```
{  
  "TrafficPolicyId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [TrafficPolicyId](#)

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## Response Syntax

```
{  
  "CreatedTimestamp": number,  
  "DefaultAction": "string",  
  "LastUpdatedTimestamp": number,  
  "MaxMessageSizeBytes": number,  
  "PolicyStatements": [  
    {  
      "Action": "string",  
      "Conditions": [  
        { ... }  
      ]  
    }  
  ],  
}
```

```
"TrafficPolicyArn": "string",  
"TrafficPolicyId": "string",  
"TrafficPolicyName": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### CreatedTimestamp

The timestamp of when the traffic policy was created.

Type: Timestamp

### DefaultAction

The default action of the traffic policy.

Type: String

Valid Values: ALLOW | DENY

### LastUpdatedTimestamp

The timestamp of when the traffic policy was last updated.

Type: Timestamp

### MaxMessageSizeBytes

The maximum message size in bytes of email which is allowed in by this traffic policy—anything larger will be blocked.

Type: Integer

Valid Range: Minimum value of 1.

### PolicyStatements

The list of conditions which are in the traffic policy resource.

Type: Array of [PolicyStatement](#) objects

### TrafficPolicyArn

The Amazon Resource Name (ARN) of the traffic policy resource.

Type: String

### TrafficPolicyId

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

### TrafficPolicyName

A user-friendly name for the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListAddonInstances

Lists all Add On instances in your account.

## Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### PageSize

The maximum number of ingress endpoint resources that are returned per call. You can use NextToken to obtain further ingress endpoints.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
```

```
"AddonInstances": [  
  {  
    "AddonInstanceArn": "string",  
    "AddonInstanceId": "string",  
    "AddonName": "string",  
    "AddonSubscriptionId": "string",  
    "CreatedTimestamp": number  
  }  
],  
"NextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### AddonInstances

The list of ingress endpoints.

Type: Array of [AddonInstance](#) objects

### NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400



## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListAddonSubscriptions

Lists all Add On subscriptions in your account.

## Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### PageSize

The maximum number of ingress endpoint resources that are returned per call. You can use NextToken to obtain further ingress endpoints.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
```

```
"AddonSubscriptions": [  
  {  
    "AddonName": "string",  
    "AddonSubscriptionArn": "string",  
    "AddonSubscriptionId": "string",  
    "CreatedTimestamp": number  
  }  
],  
"NextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### AddonSubscriptions

The list of ingress endpoints.

Type: Array of [AddonSubscription](#) objects

### NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListArchiveExports

Returns a list of email archive export jobs.

## Request Syntax

```
{  
  "ArchiveId": "string",  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveId

The identifier of the archive.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: `^a-[\w]{1,64}$`

Required: Yes

### NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

## PageSize

The maximum number of archive export jobs that are returned per call. You can use `NextToken` to obtain further pages of archives.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
  "Exports": [
    {
      "ExportId": "string",
      "Status": {
        "CompletionTimestamp": number,
        "ErrorMessage": "string",
        "State": "string",
        "SubmissionTimestamp": number
      }
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Exports

The list of export job identifiers and statuses.

Type: Array of [ExportSummary](#) objects

### NextToken

If present, use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

### ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListArchives

Returns a list of all email archives in your account.

## Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### PageSize

The maximum number of archives that are returned per call. You can use NextToken to obtain further pages of archives.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
  "Archives": [
    {
      "ArchiveId": "string",
      "ArchiveName": "string",
      "ArchiveState": "string",
      "LastUpdatedTimestamp": number
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [Archives](#)

The list of archive details.

Type: Array of [Archive](#) objects

### [NextToken](#)

If present, use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListArchiveSearches

Returns a list of email archive search jobs.

## Request Syntax

```
{  
  "ArchiveId": "string",  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveId

The identifier of the archive.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: `^a-[\w]{1,64}$`

Required: Yes

### NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

## PageSize

The maximum number of archive search jobs that are returned per call. You can use `NextToken` to obtain further pages of archives.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
  "NextToken": "string",
  "Searches": [
    {
      "SearchId": "string",
      "Status": {
        "CompletionTimestamp": number,
        "ErrorMessage": "string",
        "State": "string",
        "SubmissionTimestamp": number
      }
    }
  ]
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### NextToken

If present, use to retrieve the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

## [Searches](#)

The list of search job identifiers and statuses.

Type: Array of [SearchSummary](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListIngressPoints

List all ingress endpoint resources.

## Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### PageSize

The maximum number of ingress endpoint resources that are returned per call. You can use NextToken to obtain further ingress endpoints.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
```



```
"IngressPoints": [  
  {  
    "ARecord": "string",  
    "IngressPointId": "string",  
    "IngressPointName": "string",  
    "Status": "string",  
    "Type": "string"  
  }  
],  
"NextToken": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### IngressPoints

The list of ingress endpoints.

Type: Array of [IngressPoint](#) objects

### NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListRelays

Lists all the existing relay resources.

## Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### PageSize

The number of relays to be returned in one request.

Type: Integer

Required: No

## Response Syntax

```
{
```

```
"NextToken": "string",
"Relays": [
  {
    "LastModifiedTimestamp": number,
    "RelayId": "string",
    "RelayName": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken](#)

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

### [Relays](#)

The list of returned relays.

Type: Array of [Relay](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListRuleSets

List rule sets for this account.

## Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### PageSize

The maximum number of rule set resources that are returned per call. You can use NextToken to obtain further rule sets.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
```

```
"NextToken": "string",
"RuleSets": [
  {
    "LastModificationDate": number,
    "RuleSetId": "string",
    "RuleSetName": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken](#)

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

### [RuleSets](#)

The list of rule sets.

Type: Array of [RuleSet](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# ListTagsForResource

Retrieves the list of tags (keys and values) assigned to the resource.

## Request Syntax

```
{  
  "ResourceArn": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ResourceArn

The Amazon Resource Name (ARN) of the resource to retrieve tags from.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1011.

Pattern: `^arn:aws(|-cn|-us-gov):ses:[a-z0-9-]{1,20}:[0-9]{12}:(mailmanager-|addon-).+$`

Required: Yes

## Response Syntax

```
{  
  "Tags": [  
    {  
      "Key": "string",  
      "Value": "string"  
    }  
  ]  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": {"key1":"value1", "key2":"value2"} }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListTrafficPolicies

List traffic policy resources.

## Request Syntax

```
{  
  "NextToken": "string",  
  "PageSize": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### NextToken

If you received a pagination token from a previous call to this API, you can provide it here to continue paginating through the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: No

### PageSize

The maximum number of traffic policy resources that are returned per call. You can use NextToken to obtain further traffic policies.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 50.

Required: No

## Response Syntax

```
{
```

```
"NextToken": "string",
"TrafficPolicies": [
  {
    "DefaultAction": "string",
    "TrafficPolicyId": "string",
    "TrafficPolicyName": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### NextToken

If NextToken is returned, there are more results available. The value of NextToken is a unique pagination token for each page. Make the call again using the returned token to retrieve the next page.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

### TrafficPolicies

The list of traffic policies.

Type: Array of [TrafficPolicy](#) objects

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartArchiveExport

Initiates an export of emails from the specified archive.

## Request Syntax

```
{
  "ArchiveId": "string",
  "ExportDestinationConfiguration": { ... },
  "Filters": {
    "Include": [
      { ... }
    ],
    "Unless": [
      { ... }
    ]
  },
  "FromTimestamp": number,
  "MaxResults": number,
  "ToTimestamp": number
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveId

The identifier of the archive to export emails from.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: `^a-[\w]{1,64}$`

Required: Yes

### ExportDestinationConfiguration

Details on where to deliver the exported email data.

Type: [ExportDestinationConfiguration](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### [Filters](#)

Criteria to filter which emails are included in the export.

Type: [ArchiveFilters](#) object

Required: No

### [FromTimestamp](#)

The start of the timestamp range to include emails from.

Type: Timestamp

Required: Yes

### [MaxResults](#)

The maximum number of email items to include in the export.

Type: Integer

Required: No

### [ToTimestamp](#)

The end of the timestamp range to include emails from.

Type: Timestamp

Required: Yes

## Response Syntax

```
{
  "ExportId": "string"
}
```



## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### ExportId

The unique identifier for the initiated export job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StartArchiveSearch

Initiates a search across emails in the specified archive.

## Request Syntax

```
{
  "ArchiveId": "string",
  "Filters": {
    "Include": [
      { ... }
    ],
    "Unless": [
      { ... }
    ]
  },
  "FromTimestamp": number,
  "MaxResults": number,
  "ToTimestamp": number
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveId

The identifier of the archive to search emails in.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 66.

Pattern: `^a-[\w]{1,64}$`

Required: Yes

### Filters

Criteria to filter which emails are included in the search results.

Type: [ArchiveFilters](#) object

Required: No

### FromTimestamp

The start timestamp of the range to search emails from.

Type: Timestamp

Required: Yes

### MaxResults

The maximum number of search results to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 1000.

Required: Yes

### ToTimestamp

The end timestamp of the range to search emails from.

Type: Timestamp

Required: Yes

## Response Syntax

```
{  
  "SearchId": "string"  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### SearchId

The unique identifier for the initiated search job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### **ThrottlingException**

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# StopArchiveExport

Stops an in-progress export of emails from an archive.

## Request Syntax

```
{  
  "ExportId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ExportId

The identifier of the export job to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

## ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# StopArchiveSearch

Stops an in-progress archive search job.

## Request Syntax

```
{  
  "SearchId": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### SearchId

The identifier of the search job to stop.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **AccessDeniedException**

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

## ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# TagResource

Adds one or more tags (keys and values) to a specified resource.

## Request Syntax

```
{
  "ResourceArn": "string",
  "Tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ResourceArn

The Amazon Resource Name (ARN) of the resource that you want to tag.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1011.

Pattern: `^arn:aws(|-cn|-us-gov):ses:[a-z0-9-]{1,20}:[0-9]{12}:(mailmanager-|addon-).+$`

Required: Yes

### Tags

The tags used to organize, track, or control access for the resource. For example, { "tags": { "key1": "value1", "key2": "value2" } }.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ServiceQuotaExceededException**

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UntagResource

Remove one or more tags (keys and values) from a specified resource.

## Request Syntax

```
{  
  "ResourceArn": "string",  
  "TagKeys": [ "string" ]  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ResourceArn

The Amazon Resource Name (ARN) of the resource that you want to untag.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 1011.

Pattern: `^arn:aws(|-cn|-us-gov):ses:[a-z0-9-]{1,20}:[0-9]{12}:(mailmanager-|addon-).+$`

Required: Yes

### TagKeys

The keys of the key-value pairs for the tag or tags you want to remove from the specified resource.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9/_\+=\.\:@\-\-]+$`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# UpdateArchive

Updates the attributes of an existing email archive.

## Request Syntax

```
{  
  "ArchiveId": "string",  
  "ArchiveName": "string",  
  "Retention": { ... }  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### ArchiveId

The identifier of the archive to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

### ArchiveName

A new, unique name for the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]$`

Required: No

### Retention

A new retention period for emails in the archive.

Type: [ArchiveRetention](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### AccessDeniedException

Occurs when a user is denied access to a specific resource or action.

HTTP Status Code: 400

### ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

### ServiceQuotaExceededException

Occurs when an operation exceeds a predefined service quota or limit.

HTTP Status Code: 400

### ThrottlingException

Occurs when a service's request rate limit is exceeded, resulting in throttling of further requests.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateIngressPoint

Update attributes of a provisioned ingress endpoint resource.

## Request Syntax

```
{
  "IngressPointConfiguration": { ... },
  "IngressPointId": "string",
  "IngressPointName": "string",
  "RuleSetId": "string",
  "StatusToUpdate": "string",
  "TrafficPolicyId": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### IngressPointConfiguration

If you choose an Authenticated ingress endpoint, you must configure either an SMTP password or a secret ARN.

Type: [IngressPointConfiguration](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

### IngressPointId

The identifier for the ingress endpoint you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## IngressPointName

A user friendly name for the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

Required: No

## RuleSetId

The identifier of an existing rule set that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

## StatusToUpdate

The update status of an ingress endpoint.

Type: String

Valid Values: ACTIVE | CLOSED

Required: No

## TrafficPolicyId

The identifier of an existing traffic policy that you attach to an ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

### ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateRelay

Updates the attributes of an existing relay resource.

## Request Syntax

```
{  
  "Authentication": { ... },  
  "RelayId": "string",  
  "RelayName": "string",  
  "ServerName": "string",  
  "ServerPort": number  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### [Authentication](#)

Authentication for the relay destination server—specify the secretARN where the SMTP credentials are stored.

Type: [RelayAuthentication](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: No

### [RelayId](#)

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-]+$`

Required: Yes

## RelayName

The name of the relay resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-_$]`

Required: No

## ServerName

The destination relay server address.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-\.]`

Required: No

## ServerPort

The destination relay server port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ConflictException

The request configuration has conflicts. For details, see the accompanying error message.



HTTP Status Code: 400

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateRuleSet

Update attributes of an already provisioned rule set.

## Request Syntax

```
{
  "Rules": [
    {
      "Actions": [
        { ... }
      ],
      "Conditions": [
        { ... }
      ],
      "Name": "string",
      "Unless": [
        { ... }
      ]
    }
  ],
  "RuleSetId": "string",
  "RuleSetName": "string"
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### Rules

A new set of rules to replace the current rules of the rule set—these rules will override all the rules of the rule set.

Type: Array of [Rule](#) objects

Array Members: Minimum number of 0 items. Maximum number of 40 items.

Required: No

## RuleSetId

The identifier of a rule set you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

## RuleSetName

A user-friendly name for the rule set resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9_.-]+$`

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

### **ConflictException**

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

### **ResourceNotFoundException**

Occurs when a requested resource is not found.

HTTP Status Code: 400

### **ValidationException**

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# UpdateTrafficPolicy

Update attributes of an already provisioned traffic policy resource.

## Request Syntax

```
{  
  "DefaultAction": "string",  
  "MaxMessageSizeBytes": number,  
  "PolicyStatements": [  
    {  
      "Action": "string",  
      "Conditions": [  
        { ... }  
      ]  
    }  
  ],  
  "TrafficPolicyId": "string",  
  "TrafficPolicyName": "string"  
}
```

## Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#).

The request accepts the following data in JSON format.

### DefaultAction

Default action instructs the traffic policy to either Allow or Deny (block) messages that fall outside of (or not addressed by) the conditions of your policy statements

Type: String

Valid Values: ALLOW | DENY

Required: No

### MaxMessageSizeBytes

The maximum message size in bytes of email which is allowed in by this traffic policy—anything larger will be blocked.

Type: Integer

Valid Range: Minimum value of 1.

Required: No

### PolicyStatements

The list of conditions to be updated for filtering email traffic.

Type: Array of [PolicyStatement](#) objects

Required: No

### TrafficPolicyId

The identifier of the traffic policy that you want to update.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### TrafficPolicyName

A user-friendly name for the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

For information about the errors that are common to all actions, see [Common Errors](#).

## ConflictException

The request configuration has conflicts. For details, see the accompanying error message.

HTTP Status Code: 400

## ResourceNotFoundException

Occurs when a requested resource is not found.

HTTP Status Code: 400

## ValidationException

The request validation has failed. For details, see the accompanying error message.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The MailManager API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AddHeaderAction](#)
- [AddonInstance](#)
- [AddonSubscription](#)
- [Analysis](#)
- [Archive](#)
- [ArchiveAction](#)
- [ArchiveBooleanExpression](#)
- [ArchiveBooleanToEvaluate](#)
- [ArchiveFilterCondition](#)
- [ArchiveFilters](#)
- [ArchiveRetention](#)
- [ArchiveStringExpression](#)
- [ArchiveStringToEvaluate](#)
- [DeliverToMailboxAction](#)
- [DropAction](#)
- [ExportDestinationConfiguration](#)
- [ExportStatus](#)
- [ExportSummary](#)
- [IngressAnalysis](#)
- [IngressBooleanExpression](#)



- [IngressBooleanToEvaluate](#)
- [IngressIpToEvaluate](#)
- [IngressIpv4Expression](#)
- [IngressPoint](#)
- [IngressPointAuthConfiguration](#)
- [IngressPointConfiguration](#)
- [IngressPointPasswordConfiguration](#)
- [IngressStringExpression](#)
- [IngressStringToEvaluate](#)
- [IngressTlsProtocolExpression](#)
- [IngressTlsProtocolToEvaluate](#)
- [MessageBody](#)
- [NoAuthentication](#)
- [PolicyCondition](#)
- [PolicyStatement](#)
- [Relay](#)
- [RelayAction](#)
- [RelayAuthentication](#)
- [ReplaceRecipientAction](#)
- [Row](#)
- [Rule](#)
- [RuleAction](#)
- [RuleBooleanExpression](#)
- [RuleBooleanToEvaluate](#)
- [RuleCondition](#)
- [RuleDmarcExpression](#)
- [RuleIpExpression](#)
- [RuleIpToEvaluate](#)
- [RuleNumberExpression](#)
- [RuleNumberToEvaluate](#)

- [RuleSet](#)
- [RuleStringExpression](#)
- [RuleStringToEvaluate](#)
- [RuleVerdictExpression](#)
- [RuleVerdictToEvaluate](#)
- [S3Action](#)
- [S3ExportDestinationConfiguration](#)
- [SearchStatus](#)
- [SearchSummary](#)
- [SendAction](#)
- [Tag](#)
- [TrafficPolicy](#)

# AddHeaderAction

The action to add a header to a message. When executed, this action will add the given header to the message.

## Contents

### HeaderName

The name of the header to add to an email. The header must be prefixed with "X-". Headers are added regardless of whether the header name pre-existed in the email.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[xX]\-[a-zA-Z0-9\-\ ]+$`

Required: Yes

### HeaderValue

The value of the header to add to the email.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AddonInstance

An Add On instance represents a specific configuration of an Add On.

## Contents

### AddonInstanceArn

The Amazon Resource Name (ARN) of the Add On instance.

Type: String

Required: No

### AddonInstanceId

The unique ID of the Add On instance.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^ai-[a-zA-Z0-9]{1,64}$`

Required: No

### AddonName

The name of the Add On for the instance.

Type: String

Required: No

### AddonSubscriptionId

The subscription ID for the instance.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^as-[a-zA-Z0-9]{1,64}$`

Required: No

## CreatedTimestamp

The timestamp of when the Add On instance was created.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# AddonSubscription

A subscription for an Add On representing the acceptance of its terms of use and additional pricing.

## Contents

### AddonName

The name of the Add On.

Type: String

Required: No

### AddonSubscriptionArn

The Amazon Resource Name (ARN) of the Add On subscription.

Type: String

Required: No

### AddonSubscriptionId

The unique ID of the Add On subscription.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 67.

Pattern: `^as-[a-zA-Z0-9]{1,64}$`

Required: No

### CreatedTimestamp

The timestamp of when the Add On subscription was created.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Analysis

The result of an analysis can be used in conditions to trigger actions. Analyses can inspect the email content and report a certain aspect of the email.

## Contents

### Analyzer

The Amazon Resource Name (ARN) of an Add On.

Type: String

Pattern: `^[a-zA-Z0-9: _/+ =, @. # - ]+$`

Required: Yes

### ResultField

The returned value from an Add On.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z0-9_ ]+$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# Archive

An archive resource for storing and retaining emails.

## Contents

### ArchiveId

The unique identifier of the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 66.

Required: Yes

### ArchiveName

The unique name assigned to the archive.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `^[a-zA-Z0-9][a-zA-Z0-9_-]*[a-zA-Z0-9]$`

Required: No

### ArchiveState

The current state of the archive:

- **ACTIVE** – The archive is ready and available for use.
- **PENDING\_DELETION** – The archive has been marked for deletion and will be permanently deleted in 30 days. No further modifications can be made in this state.

Type: String

Valid Values: **ACTIVE** | **PENDING\_DELETION**

Required: No

### LastUpdatedTimestamp

The timestamp of when the archive was last updated.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ArchiveAction

The action to archive the email by delivering the email to an Amazon SES archive.

## Contents

### TargetArchive

The identifier of the archive to send the email to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9: _/+=, @. #- ]+$`

Required: Yes

### ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the specified archive has been deleted.

Type: String

Valid Values: CONTINUE | DROP

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ArchiveBooleanExpression

A boolean expression to evaluate email attribute values.

## Contents

### Evaluate

The email attribute value to evaluate.

Type: [ArchiveBooleanToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The boolean operator to use for evaluation.

Type: String

Valid Values: IS\_TRUE | IS\_FALSE

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ArchiveBooleanToEvaluate

The attribute to evaluate in a boolean expression.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### Attribute

The name of the email attribute to evaluate.

Type: String

Valid Values: HAS\_ATTACHMENTS

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ArchiveFilterCondition

A filter condition used to include or exclude emails when exporting from or searching an archive.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### BooleanExpression

A boolean expression to evaluate against email attributes.

Type: [ArchiveBooleanExpression](#) object

Required: No

### StringExpression

A string expression to evaluate against email attributes.

Type: [ArchiveStringExpression](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ArchiveFilters

A set of filter conditions to include and/or exclude emails.

## Contents

### Include

The filter conditions for emails to include.

Type: Array of [ArchiveFilterCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

### Unless

The filter conditions for emails to exclude.

Type: Array of [ArchiveFilterCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ArchiveRetention

The retention policy for an email archive that specifies how long emails are kept before being automatically deleted.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## RetentionPeriod

The enum value sets the period for retaining emails in an archive.

Type: String

Valid Values: THREE\_MONTHS | SIX\_MONTHS | NINE\_MONTHS | ONE\_YEAR | EIGHTEEN\_MONTHS | TWO\_YEARS | THIRTY\_MONTHS | THREE\_YEARS | FOUR\_YEARS | FIVE\_YEARS | SIX\_YEARS | SEVEN\_YEARS | EIGHT\_YEARS | NINE\_YEARS | TEN\_YEARS | PERMANENT

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# ArchiveStringExpression

A string expression to evaluate an email attribute value against one or more string values.

## Contents

### Evaluate

The attribute of the email to evaluate.

Type: [ArchiveStringToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The operator to use when evaluating the string values.

Type: String

Valid Values: CONTAINS

Required: Yes

### Values

The list of string values to evaluate the email attribute against.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# ArchiveStringToEvaluate

Specifies the email attribute to evaluate in a string expression.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Attribute

The name of the email attribute to evaluate.

Type: String

Valid Values: TO | FROM | CC | SUBJECT

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DeliverToMailboxAction

This action to delivers an email to a mailbox.

## Contents

### MailboxArn

The Amazon Resource Name (ARN) of a WorkMail organization to deliver the email to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9: _/+=, @. #-]+$`

Required: Yes

### RoleArn

The Amazon Resource Name (ARN) of an IAM role to use to execute this action. The role must have access to the `workmail:DeliverToMailbox` API.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9: _/+=, @. #-]+$`

Required: Yes

### ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the mailbox ARN is no longer valid.

Type: String

Valid Values: `CONTINUE` | `DROP`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DropAction

This action causes processing to stop and the email to be dropped. If the action applies only to certain recipients, only those recipients are dropped, and processing continues for other recipients.

## Contents

The members of this exception structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportDestinationConfiguration

The destination configuration for delivering exported email data.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## S3

Configuration for delivering to an Amazon S3 bucket.

Type: [S3ExportDestinationConfiguration](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportStatus

The current status of an archive export job.

## Contents

### CompletionTimestamp

The timestamp of when the export job completed (if finished).

Type: Timestamp

Required: No

### ErrorMessage

An error message if the export job failed.

Type: String

Required: No

### State

The current state of the export job.

Type: String

Valid Values: QUEUED | PREPROCESSING | PROCESSING | COMPLETED | FAILED | CANCELLED

Required: No

### SubmissionTimestamp

The timestamp of when the export job was submitted.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:



- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ExportSummary

Summary statuses of an archive export job.

## Contents

### ExportId

The unique identifier of the export job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

### Status

The current status of the export job.

Type: [ExportStatus](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressAnalysis

The Add On ARN and its returned value that is evaluated in a policy statement's conditional expression to either deny or block the incoming email.

## Contents

### Analyzer

The Amazon Resource Name (ARN) of an Add On.

Type: String

Pattern: `^[a-zA-Z0-9: _/+ =, @. # - ]+$`

Required: Yes

### ResultField

The returned value from an Add On.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^[a-zA-Z0-9_ ]+$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressBooleanExpression

The structure for a boolean condition matching on the incoming mail.

## Contents

### Evaluate

The operand on which to perform a boolean condition operation.

Type: [IngressBooleanToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The matching operator for a boolean condition expression.

Type: String

Valid Values: IS\_TRUE | IS\_FALSE

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressBooleanToEvaluate

The union type representing the allowed types of operands for a boolean condition.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Analysis

The structure type for a boolean condition stating the Add On ARN and its returned value.

Type: [IngressAnalysis](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressIpToEvaluate

The structure for an IP based condition matching on the incoming mail.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### Attribute

An enum type representing the allowed attribute types for an IP condition.

Type: String

Valid Values: SENDER\_IP

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressIpv4Expression

The union type representing the allowed types for the left hand side of an IP condition.

## Contents

### Evaluate

The left hand side argument of an IP condition expression.

Type: [IngressIpToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The matching operator for an IP condition expression.

Type: String

Valid Values: CIDR\_MATCHES | NOT\_CIDR\_MATCHES

Required: Yes

### Values

The right hand side argument of an IP condition expression.

Type: Array of strings

Pattern: `^((25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)\.){3}(25[0-5]|2[0-4][0-9]|[01]?[0-9][0-9]?)/([0-9]|[12][0-9]|3[0-2])$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# IngressPoint

The structure of an ingress endpoint resource.

## Contents

### IngressPointId

The identifier of the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### IngressPointName

A user friendly name for the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

Required: Yes

### Status

The status of the ingress endpoint resource.

Type: String

Valid Values: PROVISIONING | DEPROVISIONING | UPDATING | ACTIVE | CLOSED | FAILED

Required: Yes

### Type

The type of ingress endpoint resource.

Type: String

Valid Values: OPEN | AUTH

Required: Yes

### **ARecord**

The DNS A Record that identifies your ingress endpoint. Configure your DNS Mail Exchange (MX) record with this value to route emails to Mail Manager.

Type: String

Required: No

## **See Also**

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressPointAuthConfiguration

The authentication configuration for the ingress endpoint resource.

## Contents

### IngressPointPasswordConfiguration

The ingress endpoint password configuration for the ingress endpoint resource.

Type: [IngressPointPasswordConfiguration](#) object

Required: No

### SecretArn

The ingress endpoint SecretsManager::Secret ARN configuration for the ingress endpoint resource.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-us-gov):secretsmanager:[a-z0-9-]+:\d{12}:secret:[a-zA-Z0-9/_+=, .@-]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressPointConfiguration

The configuration of the ingress endpoint resource.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### SecretArn

The SecretsManager::Secret ARN of the ingress endpoint resource.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-us-gov):secretsmanager:[a-z0-9-]+:\d{12}:secret:[a-zA-Z0-9/_+=, .@-]+$`

Required: No

### Smtppassword

The password of the ingress endpoint resource.

Type: String

Length Constraints: Minimum length of 8. Maximum length of 64.

Pattern: `^[A-Za-z0-9!@#$%^&*()_+\-=\[\]\{\}|\.,?]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressPointPasswordConfiguration

The password configuration of the ingress endpoint resource.

## Contents

### PreviousSmtppasswordExpiryTimestamp

The previous password expiry timestamp of the ingress endpoint resource.

Type: Timestamp

Required: No

### PreviousSmtppasswordVersion

The previous password version of the ingress endpoint resource.

Type: String

Required: No

### SmtppasswordVersion

The current password expiry timestamp of the ingress endpoint resource.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressStringExpression

The structure for a string based condition matching on the incoming mail.

## Contents

### Evaluate

The left hand side argument of a string condition expression.

Type: [IngressStringToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The matching operator for a string condition expression.

Type: String

Valid Values: EQUALS | NOT\_EQUALS | STARTS\_WITH | ENDS\_WITH | CONTAINS

Required: Yes

### Values

The right hand side argument of a string condition expression.

Type: Array of strings

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)





# IngressStringToEvaluate

The union type representing the allowed types for the left hand side of a string condition.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Attribute

The enum type representing the allowed attribute types for a string condition.

Type: String

Valid Values: RECIPIENT

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# IngressTlsProtocolExpression

The structure for a TLS related condition matching on the incoming mail.

## Contents

### Evaluate

The left hand side argument of a TLS condition expression.

Type: [IngressTlsProtocolToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The matching operator for a TLS condition expression.

Type: String

Valid Values: MINIMUM\_TLS\_VERSION | IS

Required: Yes

### Value

The right hand side argument of a TLS condition expression.

Type: String

Valid Values: TLS1\_2 | TLS1\_3

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# IngressTlsProtocolToEvaluate

The union type representing the allowed types for the left hand side of a TLS condition.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Attribute

The enum type representing the allowed attribute types for the TLS condition.

Type: String

Valid Values: TLS\_PROTOCOL

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MessageBody

The textual body content of an email message.

## Contents

### Html

The HTML body content of the message.

Type: String

Required: No

### MessageMalformed

A flag indicating if the email was malformed.

Type: Boolean

Required: No

### Text

The plain text body content of the message.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# NoAuthentication

Explicitly indicate that the relay destination server does not require SMTP credential authentication.

## Contents

The members of this exception structure are context-dependent.

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# PolicyCondition

The email traffic filtering conditions which are contained in a traffic policy resource.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### BooleanExpression

This represents a boolean type condition matching on the incoming mail. It performs the boolean operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressBooleanExpression](#) object

Required: No

### IpExpression

This represents an IP based condition matching on the incoming mail. It performs the operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressIpv4Expression](#) object

Required: No

### StringExpression

This represents a string based condition matching on the incoming mail. It performs the string operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressStringExpression](#) object

Required: No

### TlsExpression

This represents a TLS based condition matching on the incoming mail. It performs the operation configured in 'Operator' and evaluates the 'Protocol' object against the 'Value'.

Type: [IngressTlsProtocolExpression](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# PolicyStatement

The structure containing traffic policy conditions and actions.

## Contents

### Action

The action that informs a traffic policy resource to either allow or block the email if it matches a condition in the policy statement.

Type: String

Valid Values: ALLOW | DENY

Required: Yes

### Conditions

The list of conditions to apply to incoming messages for filtering email traffic.

Type: Array of [PolicyCondition](#) objects

Array Members: Minimum number of 1 item.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Relay

The relay resource that can be used as a rule to relay receiving emails to the destination relay server.

## Contents

### LastModifiedTimestamp

The timestamp of when the relay was last modified.

Type: Timestamp

Required: No

### RelayId

The unique relay identifier.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-]+$`

Required: No

### RelayName

The unique relay name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9-_$]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RelayAction

The action relays the email via SMTP to another specific SMTP server.

## Contents

### Relay

The identifier of the relay resource to be used when relaying an email.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9:_/+=, @. #-]+`

Required: Yes

### ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the specified relay has been deleted.

Type: String

Valid Values: CONTINUE | DROP

Required: No

### MailFrom

This action specifies whether to preserve or replace original mail from address while relaying received emails to a destination server.

Type: String

Valid Values: REPLACE | PRESERVE

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RelayAuthentication

Authentication for the relay destination server—specify the `secretARN` where the SMTP credentials are stored, or specify an empty `NoAuthentication` structure if the relay destination server does not require SMTP credential authentication.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### NoAuthentication

Keep an empty structure if the relay destination server does not require SMTP credential authentication.

Type: [NoAuthentication](#) object

Required: No

### SecretArn

The ARN of the secret created in secrets manager where the relay server's SMTP credentials are stored.

Type: String

Pattern: `^arn:(aws|aws-cn|aws-us-gov):secretsmanager:[a-z0-9-]+:\d{12}:secret:[a-zA-Z0-9/_+=, .@-]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ReplaceRecipientAction

This action replaces the email envelope recipients with the given list of recipients. If the condition of this action applies only to a subset of recipients, only those recipients are replaced with the recipients specified in the action. The message contents and headers are unaffected by this action, only the envelope recipients are updated.

## Contents

### ReplaceWith

This action specifies the replacement recipient email addresses to insert.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 0. Maximum length of 254.

Pattern: `^[0-9A-Za-z@+.-]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



## Row

A result row containing metadata for an archived email message.

## Contents

### ArchivedMessageId

The unique identifier of the archived message.

Type: String

Required: No

### Cc

The email addresses in the CC header.

Type: String

Required: No

### Date

The date the email was sent.

Type: String

Required: No

### From

The email address of the sender.

Type: String

Required: No

### HasAttachments

A flag indicating if the email has attachments.

Type: Boolean

Required: No

**InReplyTo**

The email message ID this is a reply to.

Type: String

Required: No

**MessageId**

The unique message ID of the email.

Type: String

Required: No

**ReceivedHeaders**

The received headers from the email delivery path.

Type: Array of strings

Required: No

**ReceivedTimestamp**

The timestamp of when the email was received.

Type: Timestamp

Required: No

**Subject**

The subject header value of the email.

Type: String

Required: No

**To**

The email addresses in the To header.

Type: String

Required: No

## XMailer

The user agent that sent the email.

Type: String

Required: No

## XOriginalMailer

The original user agent that sent the email.

Type: String

Required: No

## XPriority

The priority level of the email.

Type: String

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Rule

A rule contains conditions, "unless conditions" and actions. For each envelope recipient of an email, if all conditions match and none of the "unless conditions" match, then all of the actions are executed sequentially. If no conditions are provided, the rule always applies and the actions are implicitly executed. If only "unless conditions" are provided, the rule applies if the email does not match the evaluation of the "unless conditions".

## Contents

### Actions

The list of actions to execute when the conditions match the incoming email, and none of the "unless conditions" match.

Type: Array of [RuleAction](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

### Conditions

The conditions of this rule. All conditions must match the email for the actions to be executed. An empty list of conditions means that all emails match, but are still subject to any "unless conditions"

Type: Array of [RuleCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

### Name

The user-friendly name of the rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[a-zA-Z0-9_.-]+$`

Required: No

## Unless

The "unless conditions" of this rule. None of the conditions can match the email for the actions to be executed. If any of these conditions do match the email, then the actions are not executed.

Type: Array of [RuleCondition](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleAction

The action for a rule to take. Only one of the contained actions can be set.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### AddHeader

This action adds a header. This can be used to add arbitrary email headers.

Type: [AddHeaderAction](#) object

Required: No

### Archive

This action archives the email. This can be used to deliver an email to an archive.

Type: [ArchiveAction](#) object

Required: No

### DeliverToMailbox

This action delivers an email to a WorkMail mailbox.

Type: [DeliverToMailboxAction](#) object

Required: No

### Drop

This action terminates the evaluation of rules in the rule set.

Type: [DropAction](#) object

Required: No

## Relay

This action relays the email to another SMTP server.

Type: [RelayAction](#) object

Required: No

## ReplaceRecipient

The action replaces certain or all recipients with a different set of recipients.

Type: [ReplaceRecipientAction](#) object

Required: No

## Send

This action sends the email to the internet.

Type: [SendAction](#) object

Required: No

## WriteToS3

This action writes the MIME content of the email to an S3 bucket.

Type: [S3Action](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleBooleanExpression

A boolean expression to be used in a rule condition.

## Contents

### Evaluate

The operand on which to perform a boolean condition operation.

Type: [RuleBooleanToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The matching operator for a boolean condition expression.

Type: String

Valid Values: IS\_TRUE | IS\_FALSE

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# RuleBooleanToEvaluate

The union type representing the allowed types of operands for a boolean condition.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Attribute

The boolean type representing the allowed attribute types for an email.

Type: String

Valid Values: READ\_RECEIPT\_REQUESTED | TLS | TLS\_WRAPPED

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleCondition

The conditional expression used to evaluate an email for determining if a rule action should be taken.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

### BooleanExpression

The condition applies to a boolean expression passed in this field.

Type: [RuleBooleanExpression](#) object

Required: No

### DmarcExpression

The condition applies to a DMARC policy expression passed in this field.

Type: [RuleDmarcExpression](#) object

Required: No

### IpExpression

The condition applies to an IP address expression passed in this field.

Type: [RuleIpExpression](#) object

Required: No

### NumberExpression

The condition applies to a number expression passed in this field.

Type: [RuleNumberExpression](#) object

Required: No

## StringExpression

The condition applies to a string expression passed in this field.

Type: [RuleStringExpression](#) object

Required: No

## VerdictExpression

The condition applies to a verdict expression passed in this field.

Type: [RuleVerdictExpression](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleDmarcExpression

A DMARC policy expression. The condition matches if the given DMARC policy matches that of the incoming email.

## Contents

### Operator

The operator to apply to the DMARC policy of the incoming email.

Type: String

Valid Values: EQUALS | NOT\_EQUALS

Required: Yes

### Values

The values to use for the given DMARC policy operator. For the operator EQUALS, if multiple values are given, they are evaluated as an OR. That is, if any of the given values match, the condition is deemed to match. For the operator NOT\_EQUALS, if multiple values are given, they are evaluated as an AND. That is, only if the email's DMARC policy is not equal to any of the given values, then the condition is deemed to match.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Valid Values: NONE | QUARANTINE | REJECT

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# RuleIpExpression

An IP address expression matching certain IP addresses within a given range of IP addresses.

## Contents

### Evaluate

The IP address to evaluate in this condition.

Type: [RuleIpToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The operator to evaluate the IP address.

Type: String

Valid Values: CIDR\_MATCHES | NOT\_CIDR\_MATCHES

Required: Yes

### Values

The IP CIDR blocks in format "x.y.z.w/n" (eg 10.0.0.0/8) to match with the email's IP address. For the operator CIDR\_MATCHES, if multiple values are given, they are evaluated as an OR. That is, if the IP address is contained within any of the given CIDR ranges, the condition is deemed to match. For NOT\_CIDR\_MATCHES, if multiple CIDR ranges are given, the condition is deemed to match if the IP address is not contained in any of the given CIDR ranges.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 18.

Pattern: `^(([0-9]|.|/)*)$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleIpToEvaluate

The IP address to evaluate for this condition.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Attribute

The attribute of the email to evaluate.

Type: String

Valid Values: SOURCE\_IP

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# RuleNumberExpression

A number expression to match numeric conditions with integers from the incoming email.

## Contents

### Evaluate

The number to evaluate in a numeric condition expression.

Type: [RuleNumberToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The operator for a numeric condition expression.

Type: String

Valid Values: EQUALS | NOT\_EQUALS | LESS\_THAN | GREATER\_THAN | LESS\_THAN\_OR\_EQUAL | GREATER\_THAN\_OR\_EQUAL

Required: Yes

### Value

The value to evaluate in a numeric condition expression.

Type: Double

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

# RuleNumberToEvaluate

The number to evaluate in a numeric condition expression.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Attribute

An email attribute that is used as the number to evaluate.

Type: String

Valid Values: MESSAGE\_SIZE

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleSet

A rule set contains a list of rules that are evaluated in order. Each rule is evaluated sequentially for each email.

## Contents

### LastModificationDate

The last modification date of the rule set.

Type: Timestamp

Required: No

### RuleSetId

The identifier of the rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: No

### RuleSetName

A user-friendly name for the rule set.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Pattern: `^[a-zA-Z0-9_.-]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleStringExpression

A string expression is evaluated against strings or substrings of the email.

## Contents

### Evaluate

The string to evaluate in a string condition expression.

Type: [RuleStringToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The matching operator for a string condition expression.

Type: String

Valid Values: EQUALS | NOT\_EQUALS | STARTS\_WITH | ENDS\_WITH | CONTAINS

Required: Yes

### Values

The string(s) to be evaluated in a string condition expression. For all operators, except for NOT\_EQUALS, if multiple values are given, the values are processed as an OR. That is, if any of the values match the email's string using the given operator, the condition is deemed to match. However, for NOT\_EQUALS, the condition is only deemed to match if none of the given strings match the email's string.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Length Constraints: Minimum length of 1. Maximum length of 4096.

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleStringToEvaluate

The string to evaluate in a string condition expression.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Attribute

The email attribute to evaluate in a string condition expression.

Type: String

Valid Values: MAIL\_FROM | HELO | RECIPIENT | SENDER | FROM | SUBJECT | TO | CC

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# RuleVerdictExpression

A verdict expression is evaluated against verdicts of the email.

## Contents

### Evaluate

The verdict to evaluate in a verdict condition expression.

Type: [RuleVerdictToEvaluate](#) object

**Note:** This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

### Operator

The matching operator for a verdict condition expression.

Type: String

Valid Values: EQUALS | NOT\_EQUALS

Required: Yes

### Values

The values to match with the email's verdict using the given operator. For the EQUALS operator, if multiple values are given, the condition is deemed to match if any of the given verdicts match that of the email. For the NOT\_EQUALS operator, if multiple values are given, the condition is deemed to match if none of the given verdicts match the verdict of the email.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Valid Values: PASS | FAIL | GRAY | PROCESSING\_FAILED

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# RuleVerdictToEvaluate

The verdict to evaluate in a verdict condition expression.

## Contents

### Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

## Analysis

The Add On ARN and its returned value to evaluate in a verdict condition expression.

Type: [Analysis](#) object

Required: No

## Attribute

The email verdict attribute to evaluate in a string verdict expression.

Type: String

Valid Values: SPF | DKIM

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# S3Action

Writes the MIME content of the email to an S3 bucket.

## Contents

### RoleArn

The Amazon Resource Name (ARN) of the IAM Role to use while writing to S3. This role must have access to the `s3:PutObject`, `kms:Encrypt`, and `kms:GenerateDataKey` APIs for the given bucket.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9:_/+=, @. #-]+$`

Required: Yes

### S3Bucket

The bucket name of the S3 bucket to write to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^[a-zA-Z0-9.-]+$`

Required: Yes

### ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the specified the bucket has been deleted.

Type: String

Valid Values: CONTINUE | DROP

Required: No

## S3Prefix

The S3 prefix to use for the write to the s3 bucket.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 62.

Pattern: `^[a-zA-Z0-9!_.*'()/-]+$`

Required: No

## S3SseKmsKeyId

The KMS Key ID to use to encrypt the message in S3.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9-:/]+$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# S3ExportDestinationConfiguration

The configuration for exporting email data to an Amazon S3 bucket.

## Contents

### S3Location

The S3 location to deliver the exported email data.

Type: String

Pattern: `^s3://[a-zA-Z0-9.-]{3,63}(/[a-zA-Z0-9!_.*'()/-]*)*$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SearchStatus

The current status of an archive search job.

## Contents

### CompletionTimestamp

The timestamp of when the search completed (if finished).

Type: Timestamp

Required: No

### ErrorMessage

An error message if the search failed.

Type: String

Required: No

### State

The current state of the search job.

Type: String

Valid Values: QUEUED | RUNNING | COMPLETED | FAILED | CANCELLED

Required: No

### SubmissionTimestamp

The timestamp of when the search was submitted.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# SearchSummary

Summary details of an archive search job.

## Contents

### SearchId

The unique identifier of the search job.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Required: No

### Status

The current status of the search job.

Type: [SearchStatus](#) object

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# SendAction

Sends the email to the internet using the ses:SendRawEmail API.

## Contents

### RoleArn

The Amazon Resource Name (ARN) of the role to use for this action. This role must have access to the ses:SendRawEmail API.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9: _/+=, @. #- ]+$`

Required: Yes

### ActionFailurePolicy

A policy that states what to do in the case of failure. The action will fail if there are configuration errors. For example, the caller does not have the permissions to call the sendRawEmail API.

Type: String

Valid Values: CONTINUE | DROP

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Tag

A key-value pair (the value is optional), that you can define and assign to AWS resources.

## Contents

### Key

The key of the key-value tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^[a-zA-Z0-9/_\+=\.\:@\-\ ]+$`

Required: Yes

### Value

The value of the key-value tag.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^[a-zA-Z0-9/_\+=\.\:@\-\ ]*$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# TrafficPolicy

The structure of a traffic policy resource which is a container for policy statements.

## Contents

### DefaultAction

Default action instructs the traffic policy to either Allow or Deny (block) messages that fall outside of (or not addressed by) the conditions of your policy statements

Type: String

Valid Values: ALLOW | DENY

Required: Yes

### TrafficPolicyId

The identifier of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

### TrafficPolicyName

A user-friendly name of the traffic policy resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `^[A-Za-z0-9_\-]+$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

## Action

The action to be performed.

Type: string

Required: Yes

## Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

## X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

## X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4\_request"). The value is expressed in the following format: *access\_key/YYYYMMDD/region/service/aws4\_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-Date**

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

### **X-Amz-Security-Token**

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

### **X-Amz-Signature**

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

### **X-Amz-SignedHeaders**

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional



# Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

## **AccessDeniedException**

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## **IncompleteSignature**

The request signature does not conform to AWS standards.

HTTP Status Code: 400

## **InternalFailure**

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

## **InvalidAction**

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

## **InvalidClientTokenId**

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

## **NotAuthorized**

You do not have permission to perform this action.

HTTP Status Code: 400

## **OptInRequired**

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

**RequestExpired**

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

**ServiceUnavailable**

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

**ThrottlingException**

The request was denied due to request throttling.

HTTP Status Code: 400

**ValidationError**

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400