



API Reference

Amazon VPC Lattice



API Version 2022-11-30

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon VPC Lattice: API Reference

Copyright © 2025 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
BatchUpdateRule	5
Request Syntax	5
URI Request Parameters	5
Request Body	6
Response Syntax	6
Response Elements	7
Errors	7
See Also	8
CreateAccessLogSubscription	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	11
Response Elements	11
Errors	13
See Also	13
CreateListener	15
Request Syntax	15
URI Request Parameters	15
Request Body	15
Response Syntax	17
Response Elements	18
Errors	19
See Also	20
CreateResourceConfiguration	22
Request Syntax	22
URI Request Parameters	22
Request Body	22
Response Syntax	25
Response Elements	26
Errors	29
See Also	30

CreateResourceGateway	31
Request Syntax	31
URI Request Parameters	31
Request Body	31
Response Syntax	34
Response Elements	34
Errors	36
See Also	37
CreateRule	38
Request Syntax	38
URI Request Parameters	38
Request Body	39
Response Syntax	40
Response Elements	41
Errors	42
See Also	43
CreateService	45
Request Syntax	45
URI Request Parameters	45
Request Body	45
Response Syntax	47
Response Elements	47
Errors	49
See Also	50
CreateServiceNetwork	52
Request Syntax	52
URI Request Parameters	52
Request Body	52
Response Syntax	54
Response Elements	54
Errors	55
See Also	56
CreateServiceNetworkResourceAssociation	58
Request Syntax	58
URI Request Parameters	58
Request Body	58

Response Syntax	59
Response Elements	60
Errors	61
See Also	62
CreateServiceNetworkServiceAssociation	63
Request Syntax	63
URI Request Parameters	63
Request Body	63
Response Syntax	65
Response Elements	65
Errors	66
See Also	67
CreateServiceNetworkVpcAssociation	69
Request Syntax	69
URI Request Parameters	69
Request Body	69
Response Syntax	71
Response Elements	71
Errors	73
See Also	74
CreateTargetGroup	75
Request Syntax	75
URI Request Parameters	76
Request Body	76
Response Syntax	77
Response Elements	78
Errors	79
See Also	80
DeleteAccessLogSubscription	82
Request Syntax	82
URI Request Parameters	82
Request Body	82
Response Syntax	82
Response Elements	82
Errors	82
See Also	83

DeleteAuthPolicy	85
Request Syntax	85
URI Request Parameters	85
Request Body	85
Response Syntax	85
Response Elements	85
Errors	86
See Also	86
DeleteListener	88
Request Syntax	88
URI Request Parameters	88
Request Body	88
Response Syntax	88
Response Elements	89
Errors	89
See Also	90
DeleteResourceConfiguration	91
Request Syntax	91
URI Request Parameters	91
Request Body	91
Response Syntax	91
Response Elements	91
Errors	91
See Also	92
DeleteResourceEndpointAssociation	94
Request Syntax	94
URI Request Parameters	94
Request Body	94
Response Syntax	94
Response Elements	95
Errors	96
See Also	97
DeleteResourceGateway	98
Request Syntax	98
URI Request Parameters	98
Request Body	98

Response Syntax	98
Response Elements	99
Errors	100
See Also	100
DeleteResourcePolicy	102
Request Syntax	102
URI Request Parameters	102
Request Body	102
Response Syntax	102
Response Elements	102
Errors	102
See Also	103
DeleteRule	105
Request Syntax	105
URI Request Parameters	105
Request Body	106
Response Syntax	106
Response Elements	106
Errors	106
See Also	107
DeleteService	108
Request Syntax	108
URI Request Parameters	108
Request Body	108
Response Syntax	108
Response Elements	109
Errors	110
See Also	111
DeleteServiceNetwork	112
Request Syntax	112
URI Request Parameters	112
Request Body	112
Response Syntax	112
Response Elements	112
Errors	113
See Also	113

DeleteServiceNetworkResourceAssociation	115
Request Syntax	115
URI Request Parameters	115
Request Body	115
Response Syntax	115
Response Elements	116
Errors	116
See Also	117
DeleteServiceNetworkServiceAssociation	119
Request Syntax	119
URI Request Parameters	119
Request Body	119
Response Syntax	119
Response Elements	120
Errors	120
See Also	121
DeleteServiceNetworkVpcAssociation	123
Request Syntax	123
URI Request Parameters	123
Request Body	123
Response Syntax	123
Response Elements	124
Errors	124
See Also	125
DeleteTargetGroup	127
Request Syntax	127
URI Request Parameters	127
Request Body	127
Response Syntax	127
Response Elements	128
Errors	128
See Also	129
DeregisterTargets	131
Request Syntax	131
URI Request Parameters	131
Request Body	131

Response Syntax	132
Response Elements	132
Errors	133
See Also	133
GetAccessLogSubscription	135
Request Syntax	135
URI Request Parameters	135
Request Body	135
Response Syntax	135
Response Elements	136
Errors	137
See Also	138
GetAuthPolicy	140
Request Syntax	140
URI Request Parameters	140
Request Body	140
Response Syntax	140
Response Elements	141
Errors	141
See Also	142
GetListener	144
Request Syntax	144
URI Request Parameters	144
Request Body	144
Response Syntax	144
Response Elements	145
Errors	147
See Also	148
GetResourceConfiguration	149
Request Syntax	149
URI Request Parameters	149
Request Body	149
Response Syntax	149
Response Elements	150
Errors	153
See Also	154

GetResourceGateway	155
Request Syntax	155
URI Request Parameters	155
Request Body	155
Response Syntax	155
Response Elements	156
Errors	158
See Also	158
GetResourcePolicy	160
Request Syntax	160
URI Request Parameters	160
Request Body	160
Response Syntax	160
Response Elements	161
Errors	161
See Also	162
GetRule	163
Request Syntax	163
URI Request Parameters	163
Request Body	164
Response Syntax	164
Response Elements	164
Errors	166
See Also	167
GetService	168
Request Syntax	168
URI Request Parameters	168
Request Body	168
Response Syntax	168
Response Elements	169
Errors	171
See Also	172
GetServiceNetwork	173
Request Syntax	173
URI Request Parameters	173
Request Body	173

Response Syntax	173
Response Elements	174
Errors	175
See Also	176
GetServiceNetworkResourceAssociation	177
Request Syntax	177
URI Request Parameters	177
Request Body	177
Response Syntax	177
Response Elements	178
Errors	181
See Also	182
GetServiceNetworkServiceAssociation	183
Request Syntax	183
URI Request Parameters	183
Request Body	183
Response Syntax	183
Response Elements	184
Errors	187
See Also	188
GetServiceNetworkVpcAssociation	189
Request Syntax	189
URI Request Parameters	189
Request Body	189
Response Syntax	189
Response Elements	190
Errors	192
See Also	193
GetTargetGroup	194
Request Syntax	194
URI Request Parameters	194
Request Body	194
Response Syntax	194
Response Elements	195
Errors	197
See Also	198

ListAccessLogSubscriptions	199
Request Syntax	199
URI Request Parameters	199
Request Body	199
Response Syntax	200
Response Elements	200
Errors	201
See Also	201
ListListeners	203
Request Syntax	203
URI Request Parameters	203
Request Body	203
Response Syntax	203
Response Elements	204
Errors	204
See Also	205
ListResourceConfigurations	207
Request Syntax	207
URI Request Parameters	207
Request Body	208
Response Syntax	208
Response Elements	208
Errors	209
See Also	209
ListResourceEndpointAssociations	211
Request Syntax	211
URI Request Parameters	211
Request Body	212
Response Syntax	212
Response Elements	213
Errors	213
See Also	214
ListResourceGateways	215
Request Syntax	215
URI Request Parameters	215
Request Body	215

Response Syntax	215
Response Elements	216
Errors	216
See Also	217
ListRules	218
Request Syntax	218
URI Request Parameters	218
Request Body	219
Response Syntax	219
Response Elements	219
Errors	220
See Also	220
ListServiceNetworkResourceAssociations	222
Request Syntax	222
URI Request Parameters	222
Request Body	223
Response Syntax	223
Response Elements	224
Errors	224
See Also	225
ListServiceNetworks	226
Request Syntax	226
URI Request Parameters	226
Request Body	226
Response Syntax	226
Response Elements	227
Errors	227
See Also	228
ListServiceNetworkServiceAssociations	229
Request Syntax	229
URI Request Parameters	229
Request Body	230
Response Syntax	230
Response Elements	231
Errors	231
See Also	232

ListServiceNetworkVpcAssociations	233
Request Syntax	233
URI Request Parameters	233
Request Body	234
Response Syntax	234
Response Elements	234
Errors	235
See Also	235
ListServiceNetworkVpcEndpointAssociations	237
Request Syntax	237
URI Request Parameters	237
Request Body	237
Response Syntax	238
Response Elements	238
Errors	238
See Also	239
ListServices	240
Request Syntax	240
URI Request Parameters	240
Request Body	240
Response Syntax	240
Response Elements	241
Errors	241
See Also	242
ListTagsForResource	243
Request Syntax	243
URI Request Parameters	243
Request Body	243
Response Syntax	243
Response Elements	243
Errors	244
See Also	245
ListTargetGroups	246
Request Syntax	246
URI Request Parameters	246
Request Body	246

Response Syntax	247
Response Elements	247
Errors	248
See Also	248
ListTargets	250
Request Syntax	250
URI Request Parameters	250
Request Body	251
Response Syntax	251
Response Elements	251
Errors	252
See Also	253
PutAuthPolicy	254
Request Syntax	254
URI Request Parameters	254
Request Body	254
Response Syntax	255
Response Elements	255
Errors	256
See Also	256
PutResourcePolicy	258
Request Syntax	258
URI Request Parameters	258
Request Body	258
Response Syntax	259
Response Elements	259
Errors	259
See Also	260
RegisterTargets	261
Request Syntax	261
URI Request Parameters	261
Request Body	261
Response Syntax	262
Response Elements	262
Errors	263
See Also	264

TagResource	265
Request Syntax	265
URI Request Parameters	265
Request Body	265
Response Syntax	266
Response Elements	266
Errors	266
See Also	267
UntagResource	268
Request Syntax	268
URI Request Parameters	268
Request Body	268
Response Syntax	268
Response Elements	269
Errors	269
See Also	269
UpdateAccessLogSubscription	271
Request Syntax	271
URI Request Parameters	271
Request Body	271
Response Syntax	272
Response Elements	272
Errors	273
See Also	274
UpdateListener	276
Request Syntax	276
URI Request Parameters	276
Request Body	277
Response Syntax	277
Response Elements	277
Errors	279
See Also	280
UpdateResourceConfiguration	281
Request Syntax	281
URI Request Parameters	281
Request Body	281

Response Syntax	282
Response Elements	283
Errors	285
See Also	286
UpdateResourceGateway	287
Request Syntax	287
URI Request Parameters	287
Request Body	287
Response Syntax	288
Response Elements	288
Errors	290
See Also	291
UpdateRule	292
Request Syntax	292
URI Request Parameters	292
Request Body	293
Response Syntax	294
Response Elements	294
Errors	295
See Also	296
UpdateService	298
Request Syntax	298
URI Request Parameters	298
Request Body	298
Response Syntax	299
Response Elements	299
Errors	301
See Also	302
UpdateServiceNetwork	303
Request Syntax	303
URI Request Parameters	303
Request Body	303
Response Syntax	304
Response Elements	304
Errors	305
See Also	306

UpdateServiceNetworkVpcAssociation	307
Request Syntax	307
URI Request Parameters	307
Request Body	307
Response Syntax	308
Response Elements	308
Errors	309
See Also	310
UpdateTargetGroup	312
Request Syntax	312
URI Request Parameters	312
Request Body	312
Response Syntax	313
Response Elements	314
Errors	315
See Also	316
Data Types	317
AccessLogSubscriptionSummary	319
Contents	319
See Also	321
ArnResource	322
Contents	322
See Also	322
DnsEntry	323
Contents	323
See Also	323
DnsResource	324
Contents	324
See Also	324
FixedResponseAction	325
Contents	325
See Also	325
ForwardAction	326
Contents	326
See Also	326
HeaderMatch	327

Contents	327
See Also	327
HeaderMatchType	329
Contents	329
See Also	330
HealthCheckConfig	331
Contents	331
See Also	333
HttpMatch	334
Contents	334
See Also	334
IpResource	336
Contents	336
See Also	336
ListenerSummary	337
Contents	337
See Also	338
Matcher	339
Contents	339
See Also	339
PathMatch	340
Contents	340
See Also	340
PathMatchType	341
Contents	341
See Also	341
ResourceConfigurationDefinition	343
Contents	343
See Also	343
ResourceConfigurationSummary	345
Contents	345
See Also	347
ResourceEndpointAssociationSummary	348
Contents	348
See Also	350
ResourceGatewaySummary	351

Contents	351
See Also	353
RuleAction	354
Contents	354
See Also	354
RuleMatch	355
Contents	355
See Also	355
RuleSummary	356
Contents	356
See Also	357
RuleUpdate	358
Contents	358
See Also	359
RuleUpdateFailure	360
Contents	360
See Also	360
RuleUpdateSuccess	362
Contents	362
See Also	363
ServiceNetworkEndpointAssociation	365
Contents	365
See Also	366
ServiceNetworkResourceAssociationSummary	367
Contents	367
See Also	370
ServiceNetworkServiceAssociationSummary	371
Contents	371
See Also	374
ServiceNetworkSummary	375
Contents	375
See Also	376
ServiceNetworkVpcAssociationSummary	378
Contents	378
See Also	380
ServiceSummary	381

Contents	381
See Also	383
SharingConfig	384
Contents	384
See Also	384
Target	385
Contents	385
See Also	385
TargetFailure	386
Contents	386
See Also	387
TargetGroupConfig	388
Contents	388
See Also	389
TargetGroupSummary	391
Contents	391
See Also	394
TargetSummary	395
Contents	395
See Also	396
ValidationExceptionField	397
Contents	397
See Also	397
WeightedTargetGroup	398
Contents	398
See Also	398
Common Parameters	400
Common Errors	403

Welcome

Amazon VPC Lattice is a fully managed application networking service that you use to connect, secure, and monitor all of your services across multiple accounts and virtual private clouds (VPCs). Amazon VPC Lattice interconnects your microservices and legacy services within a logical boundary, so that you can discover and manage them more efficiently. For more information, see the [Amazon VPC Lattice User Guide](#)

This document was last published on September 3, 2025.

Actions

The following actions are supported:

- [BatchUpdateRule](#)
- [CreateAccessLogSubscription](#)
- [CreateListener](#)
- [CreateResourceConfiguration](#)
- [CreateResourceGateway](#)
- [CreateRule](#)
- [CreateService](#)
- [CreateServiceNetwork](#)
- [CreateServiceNetworkResourceAssociation](#)
- [CreateServiceNetworkServiceAssociation](#)
- [CreateServiceNetworkVpcAssociation](#)
- [CreateTargetGroup](#)
- [DeleteAccessLogSubscription](#)
- [DeleteAuthPolicy](#)
- [DeleteListener](#)
- [DeleteResourceConfiguration](#)
- [DeleteResourceEndpointAssociation](#)
- [DeleteResourceGateway](#)
- [DeleteResourcePolicy](#)
- [DeleteRule](#)
- [DeleteService](#)
- [DeleteServiceNetwork](#)
- [DeleteServiceNetworkResourceAssociation](#)
- [DeleteServiceNetworkServiceAssociation](#)
- [DeleteServiceNetworkVpcAssociation](#)
- [DeleteTargetGroup](#)
- [DeregisterTargets](#)

- [GetAccessLogSubscription](#)
- [GetAuthPolicy](#)
- [GetListener](#)
- [GetResourceConfiguration](#)
- [GetResourceGateway](#)
- [GetResourcePolicy](#)
- [GetRule](#)
- [GetService](#)
- [GetServiceNetwork](#)
- [GetServiceNetworkResourceAssociation](#)
- [GetServiceNetworkServiceAssociation](#)
- [GetServiceNetworkVpcAssociation](#)
- [GetTargetGroup](#)
- [ListAccessLogSubscriptions](#)
- [ListListeners](#)
- [ListResourceConfigurations](#)
- [ListResourceEndpointAssociations](#)
- [ListResourceGateways](#)
- [ListRules](#)
- [ListServiceNetworkResourceAssociations](#)
- [ListServiceNetworks](#)
- [ListServiceNetworkServiceAssociations](#)
- [ListServiceNetworkVpcAssociations](#)
- [ListServiceNetworkVpcEndpointAssociations](#)
- [ListServices](#)
- [ListTagsForResource](#)
- [ListTargetGroups](#)
- [ListTargets](#)
- [PutAuthPolicy](#)
- [PutResourcePolicy](#)

- [RegisterTargets](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAccessLogSubscription](#)
- [UpdateListener](#)
- [UpdateResourceConfiguration](#)
- [UpdateResourceGateway](#)
- [UpdateRule](#)
- [UpdateService](#)
- [UpdateServiceNetwork](#)
- [UpdateServiceNetworkVpcAssociation](#)
- [UpdateTargetGroup](#)

BatchUpdateRule

Updates the listener rules in a batch. You can use this operation to change the priority of listener rules. This can be useful when bulk updating or swapping rule priority.

Required permissions: `vpc-lattice:UpdateRule`

For more information, see [How Amazon VPC Lattice works with IAM](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
PATCH /services/serviceIdentifier/listeners/listenerIdentifier/rules HTTP/1.1
Content-type: application/json
```

```
{
  "rules": [
    {
      "action": { ... },
      "match": { ... },
      "priority": number,
      "ruleIdentifier": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

listenerIdentifier

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}$))`

Required: Yes

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

rules

The rules for the specified listener.

Type: Array of [RuleUpdate](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "successful": [
    {
      "action": { ... },
      "arn": "string",
      "id": "string",
      "isDefault": boolean,
      "match": { ... },
      "name": "string",
      "priority": number
    }
  ],
}
```

```
"unsuccessful": [  
  {  
    "failureCode": "string",  
    "failureMessage": "string",  
    "ruleIdentifier": "string"  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[successful](#)

The rules that were successfully updated.

Type: Array of [RuleUpdateSuccess](#) objects

[unsuccessful](#)

The rules that the operation couldn't update.

Type: Array of [RuleUpdateFailure](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAccessLogSubscription

Enables access logs to be sent to Amazon CloudWatch, Amazon S3, and Amazon Kinesis Data Firehose. The service network owner can use the access logs to audit the services in the network. The service network owner can only see access logs from clients and services that are associated with their service network. Access log entries represent traffic originated from VPCs associated with that network. For more information, see [Access logs](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
POST /accesslogsubscriptions HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "destinationArn": "string",
  "resourceIdentifier": "string",
  "serviceNetworkLogType": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*[!~]+.*`

Required: No

destinationArn

The Amazon Resource Name (ARN) of the destination. The supported destination types are CloudWatch Log groups, Kinesis Data Firehose delivery streams, and Amazon S3 buckets.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?){2}:([^\/*].*)?`

Required: Yes

resourceIdentifier

The ID or ARN of the service network or service.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 200.

Pattern: `(((((sn)|(svc)|(rcfg))-[0-9a-z]{17}))|(arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?){2}:((servicenetwork/sn)|(resourceconfiguration/rcfg)|(service/svc))-[0-9a-z]{17})))`

Required: Yes

serviceNetworkLogType

The type of log that monitors your Amazon VPC Lattice service networks.

Type: String

Valid Values: SERVICE | RESOURCE

Required: No

tags

The tags for the access log subscription.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "destinationArn": "string",
  "id": "string",
  "resourceArn": "string",
  "resourceId": "string",
  "serviceNetworkLogType": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the access log subscription.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:accesslogsubscription/als-[0-9a-z]{17}`

destinationArn

The Amazon Resource Name (ARN) of the log destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)?{2}:([^\/.]*)?`

id

The ID of the access log subscription.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `als-[0-9a-z]{17}`

resourceArn

The Amazon Resource Name (ARN) of the service network or service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)?{2}:((servicenetwork/sn)|(service/svc)|(resourceconfiguration/rcfg))-[0-9a-z]{17}`

resourceId

The ID of the service network or service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 50.

Pattern: `((sn)|(svc))-[0-9a-z]{17}`

serviceNetworkLogType

The type of log that monitors your Amazon VPC Lattice service networks.

Type: String

Valid Values: SERVICE | RESOURCE

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateListener

Creates a listener for a service. Before you start using your Amazon VPC Lattice service, you must add one or more listeners. A listener is a process that checks for connection requests to your services. For more information, see [Listeners](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
POST /services/serviceIdentifier/listeners HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "defaultAction": { ... },
  "name": "string",
  "port": number,
  "protocol": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `. * [ ! ~ ] + . *`

Required: No

defaultAction

The action for the default rule. Each listener has a default rule. The default rule is used if no other rules match.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

name

The name of the listener. A listener name must be unique within a service. The valid characters are a-z, 0-9, and hyphens (-). You can't use a hyphen as the first or last character, or immediately after another hyphen.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!listener-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: Yes

port

The listener port. You can specify a value from 1 to 65535. For HTTP, the default is 80. For HTTPS, the default is 443.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

protocol

The listener protocol.

Type: String

Valid Values: HTTP | HTTPS | TLS_PASSTHROUGH

Required: Yes

tags

The tags for the listener.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "arn": "string",
  "defaultAction": { ... },
  "id": "string",
  "name": "string",
  "port": number,
  "protocol": "string",
  "serviceArn": "string",
  "serviceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the listener.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}`

defaultAction

The action for the default rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

id

The ID of the listener.

Type: String

Length Constraints: Fixed length of 26.

Pattern: `listener-[0-9a-z]{17}`

name

The name of the listener.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!listener-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

port

The port number of the listener.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

protocol

The protocol of the listener.

Type: String

Valid Values: HTTP | HTTPS | TLS_PASSTHROUGH

serviceArn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

serviceId

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResourceConfiguration

Creates a resource configuration. A resource configuration defines a specific resource. You can associate a resource configuration with a service network or a VPC endpoint.

Request Syntax

```
POST /resourceconfigurations HTTP/1.1
Content-type: application/json

{
  "allowAssociationToShareableServiceNetwork": boolean,
  "clientToken": "string",
  "name": "string",
  "portRanges": [ "string" ],
  "protocol": "string",
  "resourceConfigurationDefinition": { ... },
  "resourceConfigurationGroupIdentifier": "string",
  "resourceGatewayIdentifier": "string",
  "tags": {
    "string" : "string"
  },
  "type": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[allowAssociationToShareableServiceNetwork](#)

(SINGLE, GROUP, ARN) Specifies whether the resource configuration can be associated with a sharable service network. The default is false.

Type: Boolean

Required: No

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `. * [ ! ~ ] + . *`

Required: No

name

The name of the resource configuration. The name must be unique within the account. The valid characters are a-z, 0-9, and hyphens (-). You can't use a hyphen as the first or last character, or immediately after another hyphen.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rcfg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: Yes

portRanges

(SINGLE, GROUP, CHILD) The TCP port ranges that a consumer can use to access a resource configuration (for example: 1-65535). You can separate port ranges using commas (for example: 1,2,22-30).

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 11.

Pattern: `((\d{1,5}\-\d{1,5})|(\d+))`

Required: No

protocol

(SINGLE, GROUP) The protocol accepted by the resource configuration.

Type: String

Valid Values: TCP

Required: No

resourceConfigurationDefinition

Identifies the resource configuration in one of the following ways:

- **Amazon Resource Name (ARN)** - Supported resource-types that are provisioned by AWS services, such as RDS databases, can be identified by their ARN.
- **Domain name** - Any domain name that is publicly resolvable.
- **IP address** - For IPv4 and IPv6, only IP addresses in the VPC are supported.

Type: [ResourceConfigurationDefinition](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

resourceConfigurationGroupIdentifier

(CHILD) The ID or ARN of the parent resource configuration of type GROUP. This is used to associate a child resource configuration with a group resource configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))`

Required: No

resourceGatewayIdentifier

(SINGLE, GROUP, ARN) The ID or ARN of the resource gateway used to connect to the resource configuration. For a child resource configuration, this value is inherited from the parent resource configuration.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((rgw-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:resourcegateway/rgw-[0-9a-z]{17}))`

Required: No

tags

The tags for the resource configuration.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The type of resource configuration. A resource configuration can be one of the following types:

- **SINGLE** - A single resource.
- **GROUP** - A group of resources. You must create a group resource configuration before you create a child resource configuration.
- **CHILD** - A single resource that is part of a group resource configuration.
- **ARN** - An AWS resource.

Type: String

Valid Values: GROUP | CHILD | SINGLE | ARN

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "allowAssociationToShareableServiceNetwork": boolean,
  "arn": "string",
```

```
"createdAt": "string",  
"failureReason": "string",  
"id": "string",  
"name": "string",  
"portRanges": [ "string" ],  
"protocol": "string",  
"resourceConfigurationDefinition": { ... },  
"resourceConfigurationGroupId": "string",  
"resourceGatewayId": "string",  
"status": "string",  
"type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[allowAssociationToShareableServiceNetwork](#)

Specifies whether the resource configuration can be associated with a sharable service network.

Type: Boolean

[arn](#)

The Amazon Resource Name (ARN) of the resource configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\:
\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

[createdAt](#)

The date and time that the resource configuration was created, in ISO-8601 format.

Type: Timestamp

[failureReason](#)

The reason that the request failed.

Type: String

id

The ID of the resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

name

The name of the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rcfg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

portRanges

The port range.

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 11.

Pattern: `((\d{1,5}\-\d{1,5})|(\d+))`

protocol

The protocol.

Type: String

Valid Values: TCP

resourceConfigurationDefinition

Identifies the resource configuration in one of the following ways:

- **Amazon Resource Name (ARN)** - Supported resource-types that are provisioned by AWS services, such as RDS databases, can be identified by their ARN.
- **Domain name** - Any domain name that is publicly resolvable.

- **IP address** - For IPv4 and IPv6, only IP addresses in the VPC are supported.

Type: [ResourceConfigurationDefinition](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

[resourceConfigurationGroupId](#)

The ID of the parent resource configuration of type GROUP.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

[resourceGatewayId](#)

The ID of the resource gateway associated with the resource configuration.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

[status](#)

The current status of the resource configuration.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS |
DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

[type](#)

The type of resource configuration. A resource configuration can be one of the following types:

- **SINGLE** - A single resource.
- **GROUP** - A group of resources. You must create a group resource configuration before you create a child resource configuration.
- **CHILD** - A single resource that is part of a group resource configuration.
- **ARN** - An AWS resource.

Type: String

Valid Values: GROUP | CHILD | SINGLE | ARN

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateResourceGateway

A resource gateway is a point of ingress into the VPC where a resource resides. It spans multiple Availability Zones. For your resource to be accessible from all Availability Zones, you should create your resource gateways to span as many Availability Zones as possible. A VPC can have multiple resource gateways.

Request Syntax

```
POST /resourcegateways HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "ipAddressType": "string",
  "name": "string",
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
  "tags": {
    "string" : "string"
  },
  "vpcIdentifier": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `. * [ ! ~ ] + . *`

Required: No

ipAddressType

A resource gateway can have IPv4, IPv6 or dualstack addresses. The IP address type of a resource gateway must be compatible with the subnets of the resource gateway and the IP address type of the resource, as described here:

- **IPv4**Assign IPv4 addresses to your resource gateway network interfaces. This option is supported only if all selected subnets have IPv4 address ranges, and the resource also has an IPv4 address.
- **IPv6**Assign IPv6 addresses to your resource gateway network interfaces. This option is supported only if all selected subnets are IPv6 only subnets, and the resource also has an IPv6 address.
- **Dualstack**Assign both IPv4 and IPv6 addresses to your resource gateway network interfaces. This option is supported only if all selected subnets have both IPv4 and IPv6 address ranges, and the resource either has an IPv4 or IPv6 address.

The IP address type of the resource gateway is independent of the IP address type of the client or the VPC endpoint through which the resource is accessed.

Type: String

Valid Values: `IPv4` | `IPv6` | `DUALSTACK`

Required: No

name

The name of the resource gateway.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rgw-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: Yes

securityGroupIds

The IDs of the security groups to apply to the resource gateway. The security groups must be in the same VPC.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-(([0-9a-z]{8})|([0-9a-z]{17}))`

Required: No

subnetIds

The IDs of the VPC subnets in which to create the resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Required: No

tags

The tags for the resource gateway.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

vpIdentifier

The ID of the VPC for the resource gateway.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: `vpc-(([0-9a-z]{8})|([0-9a-z]{17}))`

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "ipAddressType": "string",
  "name": "string",
  "securityGroupIds": [ "string" ],
  "status": "string",
  "subnetIds": [ "string" ],
  "vpcIdentifier": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the resource gateway.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourcegateway/rgw-[0-9a-z]{17}`

id

The ID of the resource gateway.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

ipAddressType

The type of IP address for the resource gateway.

Type: String

Valid Values: IPV4 | IPV6 | DUALSTACK

name

The name of the resource gateway.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: (?!\rgw-)(?![-])(?!.*[-]\$)(?!.*[-]{2})[a-z0-9-]+

securityGroupIds

The IDs of the security groups for the resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: sg-(([\0-9a-z]{8})|([\0-9a-z]{17}))

status

The status of the resource gateway.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

subnetIds

The IDs of the resource gateway subnets.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

vpIdentifier

The ID of the VPC.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: `vpc-(([0-9a-z]{8})|([0-9a-z]{17}))`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRule

Creates a listener rule. Each listener has a default rule for checking connection requests, but you can define additional rules. Each rule consists of a priority, one or more actions, and one or more conditions. For more information, see [Listener rules](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
POST /services/serviceIdentifier/listeners/listenerIdentifier/rules HTTP/1.1
Content-type: application/json
```

```
{
  "action": { ... },
  "clientToken": "string",
  "match": { ... },
  "name": "string",
  "priority": number,
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

[listenerIdentifier](#)

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}\$))

Required: Yes

[serviceIdentifier](#)

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))`

Required: Yes

Request Body

The request accepts the following data in JSON format.

action

The action for the default rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `. * [ ! ~ ] + . *`

Required: No

match

The rule match.

Type: [RuleMatch](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

name

The name of the rule. The name must be unique within the listener. The valid characters are a-z, 0-9, and hyphens (-). You can't use a hyphen as the first or last character, or immediately after another hyphen.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!rule-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: Yes

priority

The priority assigned to the rule. Each rule for a specific listener must have a unique priority. The lower the priority number the higher the priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Required: Yes

tags

The tags for the rule.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "action": { ... },
  "arn": "string",
  "id": "string",
  "match": { ... },
  "name": "string",
  "priority": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

action

The rule action.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

arn

The Amazon Resource Name (ARN) of the rule.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}`

id

The ID of the rule.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 22.

Pattern: `rule-[0-9a-z]{17}`

match

The rule match. The `RuleMatch` must be an `HttpMatch`. This means that the rule should be an exact match on HTTP constraints which are made up of the HTTP method, path, and header.

Type: [RuleMatch](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

name

The name of the rule.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!rule-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

priority

The priority assigned to the rule. The lower the priority number the higher the priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateService

Creates a service. A service is any software application that can run on instances containers, or serverless functions within an account or virtual private cloud (VPC).

For more information, see [Services](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
POST /services HTTP/1.1
Content-type: application/json

{
  "authType": "string",
  "certificateArn": "string",
  "clientToken": "string",
  "customDomainName": "string",
  "name": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

authType

The type of IAM policy.

- NONE: The resource does not use an IAM policy. This is the default.
- AWS_IAM: The resource uses an IAM policy. When this type is used, auth is enabled and an auth policy is required.

Type: String

Valid Values: NONE | AWS_IAM

Required: No

certificateArn

The Amazon Resource Name (ARN) of the certificate.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: (arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?)?){2}:certificate/[0-9a-z-]+)?

Required: No

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: .*[!~]+.*

Required: No

customDomainName

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Required: No

name

The name of the service. The name must be unique within the account. The valid characters are a-z, 0-9, and hyphens (-). You can't use a hyphen as the first or last character, or immediately after another hyphen.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: Yes

tags

The tags for the service.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "authType": "string",
  "certificateArn": "string",
  "customDomainName": "string",
  "dnsEntry": {
    "domainName": "string",
    "hostedZoneId": "string"
  },
  "id": "string",
  "name": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

[authType](#)

The type of IAM policy.

Type: String

Valid Values: NONE | AWS_IAM

[certificateArn](#)

The Amazon Resource Name (ARN) of the certificate.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `(arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?)?){2}:certificate/[0-9a-z-]+)?`

[customDomainName](#)

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

[dnsEntry](#)

The public DNS name of the service.

Type: [DnsEntry](#) object

id

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

name

The name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-])((?!.*[-]){2})[a-z0-9-]+`

status

The status. If the status is `CREATE_FAILED`, you must delete and recreate the service.

Type: String

Valid Values: `ACTIVE` | `CREATE_IN_PROGRESS` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceNetwork

Creates a service network. A service network is a logical boundary for a collection of services. You can associate services and VPCs with a service network.

For more information, see [Service networks](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
POST /servicenetworks HTTP/1.1
Content-type: application/json

{
  "authType": "string",
  "clientToken": "string",
  "name": "string",
  "sharingConfig": {
    "enabled": boolean
  },
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

authType

The type of IAM policy.

- NONE: The resource does not use an IAM policy. This is the default.
- AWS_IAM: The resource uses an IAM policy. When this type is used, auth is enabled and an auth policy is required.

Type: String

Valid Values: NONE | AWS_IAM

Required: No

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*[!-~]+.*`

Required: No

name

The name of the service network. The name must be unique to the account. The valid characters are a-z, 0-9, and hyphens (-). You can't use a hyphen as the first or last character, or immediately after another hyphen.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: Yes

sharingConfig

Specify if the service network should be enabled for sharing.

Type: [SharingConfig](#) object

Required: No

tags

The tags for the service network.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "arn": "string",
  "authType": "string",
  "id": "string",
  "name": "string",
  "sharingConfig": {
    "enabled": boolean
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+\:vpc-lattice:[a-zA-Z0-9\-\-]+\:d{12}:servicenetwork/sn-[0-9a-z]{17}`

authType

The type of IAM policy.

Type: String

Valid Values: NONE | AWS_IAM

id

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

name

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

sharingConfig

Specifies if the service network is enabled for sharing.

Type: [SharingConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceNetworkResourceAssociation

Associates the specified service network with the specified resource configuration. This allows the resource configuration to receive connections through the service network, including through a service network VPC endpoint.

Request Syntax

```
POST /servicenetworkresourceassociations HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "resourceConfigurationIdentifier": "string",
  "serviceNetworkIdentifier": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `.*[!-~]+.*`

Required: No

[resourceConfigurationIdentifier](#)

The ID of the resource configuration to associate with the service network.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))`

Required: Yes

[serviceNetworkIdentifier](#)

The ID of the service network to associate with the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 2048.

Required: Yes

[tags](#)

A key-value pair to associate with a resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json
```

```
{
  "arn": "string",
```



```
"createdBy": "string",  
"id": "string",  
"status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 22. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
\d{12}:servicenetworkresourceassociation/snra-[0-9a-f]{17}`

[createdBy](#)

The ID of the account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

[id](#)

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snra-[0-9a-f]{17}`

[status](#)

The status of the association.

Type: String

Valid Values: CREATE_IN_PROGRESS | ACTIVE | PARTIAL | DELETE_IN_PROGRESS |
CREATE_FAILED | DELETE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceNetworkServiceAssociation

Associates the specified service with the specified service network. For more information, see [Manage service associations](#) in the *Amazon VPC Lattice User Guide*.

You can't use this operation if the service and service network are already associated or if there is a disassociation or deletion in progress. If the association fails, you can retry the operation by deleting the association and recreating it.

You cannot associate a service and service network that are shared with a caller. The caller must own either the service or the service network.

As a result of this operation, the association is created in the service network account and the association owner account.

Request Syntax

```
POST /servicenetworkserviceassociations HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "clientToken": "string",
  "serviceIdentifier": "string",
  "serviceNetworkIdentifier": "string",
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `. * [ ! ~ ] + . *`

Required: No

serviceIdentifier

The ID or ARN of the service.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))`

Required: Yes

serviceNetworkIdentifier

The ID or ARN of the service network. You must use an ARN if the resources are in different accounts.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: `((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}))`

Required: Yes

tags

The tags for the association.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "createdBy": "string",
  "customDomainName": "string",
  "dnsEntry": {
    "domainName": "string",
    "hostedZoneId": "string"
  },
  "id": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:
d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}`

[createdBy](#)

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

[customDomainName](#)

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

[dnsEntry](#)

The DNS name of the service.

Type: [DnsEntry](#) object

[id](#)

The ID of the association.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((snsa-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}))`

[status](#)

The association status.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateServiceNetworkVpcAssociation

Associates a VPC with a service network. When you associate a VPC with the service network, it enables all the resources within that VPC to be clients and communicate with other services in the service network. For more information, see [Manage VPC associations](#) in the *Amazon VPC Lattice User Guide*.

You can't use this operation if there is a disassociation in progress. If the association fails, retry by deleting the association and recreating it.

As a result of this operation, the association gets created in the service network account and the VPC owner account.

If you add a security group to the service network and VPC association, the association must continue to always have at least one security group. You can add or edit security groups at any time. However, to remove all security groups, you must first delete the association and recreate it without security groups.

Request Syntax

```
POST /servicenetworkvpcassociations HTTP/1.1
Content-type: application/json
```

```
{
  "clientToken": "string",
  "securityGroupIds": [ "string" ],
  "serviceNetworkIdentifier": "string",
  "tags": {
    "string" : "string"
  },
  "vpcIdentifier": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `. * [ ! - ~ ] + . *`

Required: No

securityGroupIds

The IDs of the security groups. Security groups aren't added by default. You can add a security group to apply network level controls to control which resources in a VPC are allowed to access the service network and its services. For more information, see [Control traffic to resources using security groups](#) in the *Amazon VPC User Guide*.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-(( [0-9a-z]{8} ) | ( [0-9a-z]{17} ))`

Required: No

serviceNetworkIdentifier

The ID or ARN of the service network. You must use an ARN if the resources are in different accounts.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: `((sn-[0-9a-z]{17}) | (arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}))`

Required: Yes

[tags](#)

The tags for the association.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

[vpIdentifier](#)

The ID of the VPC.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: `vpc-([0-9a-z]{8})|([0-9a-z]{17})`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "createdBy": "string",
  "id": "string",
  "securityGroupIds": [ "string" ],
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}`

createdBy

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snva-[0-9a-z]{17}`

securityGroupIds

The IDs of the security groups.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-((( [0-9a-z]{8} ) | ( [0-9a-z]{17} ) ) )`

status

The association status.

Type: String

Valid Values: CREATE_IN_PROGRESS | ACTIVE | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTargetGroup

Creates a target group. A target group is a collection of targets, or compute resources, that run your application or service. A target group can only be used by a single service.

For more information, see [Target groups](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
POST /targetgroups HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "config": {
    "healthCheck": {
      "enabled": boolean,
      "healthCheckIntervalSeconds": number,
      "healthCheckTimeoutSeconds": number,
      "healthyThresholdCount": number,
      "matcher": { ... },
      "path": "string",
      "port": number,
      "protocol": "string",
      "protocolVersion": "string",
      "unhealthyThresholdCount": number
    },
    "ipAddressType": "string",
    "lambdaEventStructureVersion": "string",
    "port": number,
    "protocol": "string",
    "protocolVersion": "string",
    "vpcIdentifier": "string"
  },
  "name": "string",
  "tags": {
    "string" : "string"
  },
  "type": "string"
}
```


URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. If you retry a request that completed successfully using the same client token and parameters, the retry succeeds without performing any actions. If the parameters aren't identical, the retry fails.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `. * [ ! - ~ ] + . *`

Required: No

config

The target group configuration.

Type: [TargetGroupConfig](#) object

Required: No

name

The name of the target group. The name must be unique within the account. The valid characters are a-z, 0-9, and hyphens (-). You can't use a hyphen as the first or last character, or immediately after another hyphen.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `(?!tg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: Yes

tags

The tags for the target group.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: No

type

The type of target group.

Type: String

Valid Values: IP | LAMBDA | INSTANCE | ALB

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "arn": "string",
  "config": {
    "healthCheck": {
      "enabled": boolean,
      "healthCheckIntervalSeconds": number,
      "healthCheckTimeoutSeconds": number,
      "healthyThresholdCount": number,
      "matcher": { ... },
      "path": "string",
      "port": number,
      "protocol": "string",
      "protocolVersion": "string",
      "unhealthyThresholdCount": number
```

```
    },  
    "ipAddressType": "string",  
    "lambdaEventStructureVersion": "string",  
    "port": number,  
    "protocol": "string",  
    "protocolVersion": "string",  
    "vpcIdentifier": "string"  
  },  
  "id": "string",  
  "name": "string",  
  "status": "string",  
  "type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the target group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:targetgroup/tg-[0-9a-z]{17}`

[config](#)

The target group configuration.

Type: [TargetGroupConfig](#) object

[id](#)

The ID of the target group.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `tg-[0-9a-z]{17}`

name

The name of the target group.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `(?!tg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

status

The status. You can retry the operation if the status is `CREATE_FAILED`. However, if you retry it while the status is `CREATE_IN_PROGRESS`, there is no change in the status.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

type

The type of target group.

Type: String

Valid Values: `IP` | `LAMBDA` | `INSTANCE` | `ALB`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAccessLogSubscription

Deletes the specified access log subscription.

Request Syntax

```
DELETE /accesslogsubscriptions/accessLogSubscriptionIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

accessLogSubscriptionIdentifier

The ID or ARN of the access log subscription.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((als-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
d{12}:accesslogsubscription/als-[0-9a-z]{17}))`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAuthPolicy

Deletes the specified auth policy. If an auth is set to `AWS_IAM` and the auth policy is deleted, all requests are denied. If you are trying to remove the auth policy completely, you must set the auth type to `NONE`. If auth is enabled on the resource, but no auth policy is set, all requests are denied.

Request Syntax

```
DELETE /authpolicy/resourceIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceIdentifier

The ID or ARN of the resource.

Length Constraints: Minimum length of 17. Maximum length of 200.

Pattern: (((sn)|(svc)|(rcfg))-[0-9a-z]{17})|(arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?)?){2}:((servicenetwork/sn)|(resourceconfiguration/rcfg)|(service/svc))-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteListener

Deletes the specified listener.

Request Syntax

```
DELETE /services/serviceIdentifier/listeners/listenerIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

listenerIdentifier

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}\$))

Required: Yes

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourceConfiguration

Deletes the specified resource configuration.

Request Syntax

```
DELETE /resourceconfigurations/resourceConfigurationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceConfigurationIdentifier

The ID or ARN of the resource configuration.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourceEndpointAssociation

Disassociates the resource configuration from the resource VPC endpoint.

Request Syntax

```
DELETE /resourceendpointassociations/resourceEndpointAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceEndpointAssociationIdentifier

The ID or ARN of the association.

Length Constraints: Minimum length of 21. Maximum length of 2048.

Pattern: ((*rea*-[0-9a-f]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceendpointassociation/*rea*-[0-9a-f]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "resourceConfigurationArn": "string",
  "resourceConfigurationId": "string",
  "vpcEndpointId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 21. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
d{12}:resourceendpointassociation/rea-[0-9a-f]{17}`

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rea-[0-9a-f]{17}`

resourceConfigurationArn

The Amazon Resource Name (ARN) of the resource configuration associated with the VPC endpoint of type resource.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

resourceConfigurationId

The ID of the resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

vpcEndpointId

The ID of the resource VPC endpoint that is associated with the resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `vpce-[0-9a-f]{17}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourceGateway

Deletes the specified resource gateway.

Request Syntax

```
DELETE /resourcegateways/resourceGatewayIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceGatewayIdentifier

The ID or ARN of the resource gateway.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((rgw-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:resourcegateway/rgw-[0-9a-z]{17}))`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "id": "string",
  "name": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the resource gateway.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourcegateway/rgw-[0-9a-z]{17}`

id

The ID of the resource gateway.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

name

The name of the resource gateway.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rgw-)(?![-])(?!.*[-])((?!.*[-]{2}))[a-z0-9-]+`

status

The status of the resource gateway.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteResourcePolicy

Deletes the specified resource policy.

Request Syntax

```
DELETE /resourcepolicy/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?)
{2}:((servicenetwork/sn)|(service/svc)|(resourceconfiguration/rcfg))-
[0-9a-z]{17}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRule

Deletes a listener rule. Each listener has a default rule for checking connection requests, but you can define additional rules. Each rule consists of a priority, one or more actions, and one or more conditions. You can delete additional listener rules, but you cannot delete the default rule.

For more information, see [Listener rules](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
DELETE /services/serviceIdentifier/listeners/listenerIdentifier/rules/ruleIdentifier
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

listenerIdentifier

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}\$))

Required: Yes

ruleIdentifier

The ID or ARN of the rule.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((rule-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}\$))

Required: Yes

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteService

Deletes a service. A service can't be deleted if it's associated with a service network. If you delete a service, all resources related to the service, such as the resource policy, auth policy, listeners, listener rules, and access log subscriptions, are also deleted. For more information, see [Delete a service](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
DELETE /services/serviceIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[serviceIdentifier](#)

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "name": "string",
```

```
"status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

[id](#)

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

[name](#)

The name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

[status](#)

The status. You can retry the operation if the status is `DELETE_FAILED`. However, if you retry it while the status is `DELETE_IN_PROGRESS`, the status doesn't change.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | DELETE_IN_PROGRESS |
CREATE_FAILED | DELETE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceNetwork

Deletes a service network. You can only delete the service network if there is no service or VPC associated with it. If you delete a service network, all resources related to the service network, such as the resource policy, auth policy, and access log subscriptions, are also deleted. For more information, see [Delete a service network](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
DELETE /servicenetworks/serviceNetworkIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceNetworkIdentifier

The ID or ARN of the service network.

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: ((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceNetworkResourceAssociation

Deletes the association between a service network and a resource configuration.

Request Syntax

```
DELETE /servicenetworkresourceassociations/serviceNetworkResourceAssociationIdentifier
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[serviceNetworkResourceAssociationIdentifier](#)

The ID of the association.

Length Constraints: Minimum length of 22. Maximum length of 2048.

Pattern: ((snra-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkresourceassociation/snra-[0-9a-f]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "id": "string",
  "status": "string"
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 22. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkresourceassociation/snra-[0-9a-f]{17}`

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snra-[0-9a-f]{17}`

status

The status of the association.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `PARTIAL` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceNetworkServiceAssociation

Deletes the association between a service and a service network. This operation fails if an association is still in progress.

Request Syntax

```
DELETE /servicenetworkserviceassociations/serviceNetworkServiceAssociationIdentifier
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceNetworkServiceAssociationIdentifier

The ID or ARN of the association.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((snsa-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "id": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:
d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}`

id

The ID of the association.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((snsa-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:
d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}))`

status

The status. You can retry the operation if the status is `DELETE_FAILED`. However, if you retry it when the status is `DELETE_IN_PROGRESS`, there is no change in the status.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteServiceNetworkVpcAssociation

Disassociates the VPC from the service network. You can't disassociate the VPC if there is a create or update association in progress.

Request Syntax

```
DELETE /servicenetworkvpcassociations/serviceNetworkVpcAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceNetworkVpcAssociationIdentifier

The ID or ARN of the association.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((snva-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "id": "string",
  "status": "string"
}
```


Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}`

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snva-[0-9a-z]{17}`

status

The status. You can retry the operation if the status is `DELETE_FAILED`. However, if you retry it while the status is `DELETE_IN_PROGRESS`, there is no change in the status.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `UPDATE_IN_PROGRESS` |
`DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED` | `UPDATE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTargetGroup

Deletes a target group. You can't delete a target group if it is used in a listener rule or if the target group creation is in progress.

Request Syntax

```
DELETE /targetgroups/targetGroupIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

targetGroupIdentifier

The ID or ARN of the target group.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((tg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "id": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the target group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}`

id

The ID of the target group.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `tg-[0-9a-z]{17}`

status

The status. You can retry the operation if the status is `DELETE_FAILED`. However, if you retry it while the status is `DELETE_IN_PROGRESS`, the status doesn't change.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeregisterTargets

Deregisters the specified targets from the specified target group.

Request Syntax

```
POST /targetgroups/targetGroupIdentifier/deregistertargets HTTP/1.1
Content-type: application/json
```

```
{
  "targets": [
    {
      "id": "string",
      "port": number
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

targetGroupIdentifier

The ID or ARN of the target group.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((tg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+:\d{12}:targetgroup/tg-[0-9a-z]{17})))

Required: Yes

Request Body

The request accepts the following data in JSON format.

targets

The targets to deregister.

Type: Array of [Target](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "successful": [
    {
      "id": "string",
      "port": number
    }
  ],
  "unsuccessful": [
    {
      "failureCode": "string",
      "failureMessage": "string",
      "id": "string",
      "port": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

successful

The targets that were successfully deregistered.

Type: Array of [Target](#) objects

unsuccessful

The targets that the operation couldn't deregister.

Type: Array of [TargetFailure](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAccessLogSubscription

Retrieves information about the specified access log subscription.

Request Syntax

```
GET /accesslogsubscriptions/accessLogSubscriptionIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[accessLogSubscriptionIdentifier](#)

The ID or ARN of the access log subscription.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((als-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:accesslogsubscription/als-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "createdAt": "string",
  "destinationArn": "string",
  "id": "string",
  "lastUpdatedAt": "string",
  "resourceArn": "string",
  "resourceId": "string",
```

```
"serviceNetworkLogType": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the access log subscription.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
\d{12}:accesslogsubscription/als-[0-9a-z]{17}`

[createdAt](#)

The date and time that the access log subscription was created, in ISO-8601 format.

Type: Timestamp

[destinationArn](#)

The Amazon Resource Name (ARN) of the access log destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn(:[a-z0-9]+([\.-][a-z0-9]+)*){2}(:([a-z0-9]+([\.-][a-z0-9]+)*)?)
{2}:([^\./].*)?`

[id](#)

The ID of the access log subscription.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `a1s-[0-9a-z]{17}`

lastUpdatedAt

The date and time that the access log subscription was last updated, in ISO-8601 format.

Type: Timestamp

resourceArn

The Amazon Resource Name (ARN) of the service network or service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)
{2}:((servicenetwork/sn)|(service/svc)|(resourceconfiguration/rcfg))-
[0-9a-z]{17}`

resourceId

The ID of the service network or service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 50.

Pattern: `((sn)|(svc))-[0-9a-z]{17}`

serviceNetworkLogType

The log type for the service network.

Type: String

Valid Values: SERVICE | RESOURCE

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAuthPolicy

Retrieves information about the auth policy for the specified service or service network.

Request Syntax

```
GET /authpolicy/resourceIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceIdentifier

The ID or ARN of the service network or service.

Length Constraints: Minimum length of 17. Maximum length of 200.

Pattern: (((sn)|(svc)|(rcfg))-[0-9a-z]{17})|(arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)?){2}:((servicenetwork/sn)|(resourceconfiguration/rcfg)|(service/svc))-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "createdAt": "string",
  "lastUpdatedAt": "string",
  "policy": "string",
  "state": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

createdAt

The date and time that the auth policy was created, in ISO-8601 format.

Type: Timestamp

lastUpdatedAt

The date and time that the auth policy was last updated, in ISO-8601 format.

Type: Timestamp

policy

The auth policy.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000.

state

The state of the auth policy. The auth policy is only active when the auth type is set to `AWS_IAM`. If you provide a policy, then authentication and authorization decisions are made based on this policy and the client's IAM policy. If the auth type is `NONE`, then any auth policy that you provide remains inactive. For more information, see [Create a service network](#) in the *Amazon VPC Lattice User Guide*.

Type: String

Valid Values: Active | Inactive

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetListener

Retrieves information about the specified listener for the specified service.

Request Syntax

```
GET /services/serviceIdentifier/listeners/listenerIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

listenerIdentifier

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}\$))

Required: Yes

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Content-type: application/json

```
{
  "arn": "string",
  "createdAt": "string",
  "defaultAction": { ... },
  "id": "string",
  "lastUpdatedAt": "string",
  "name": "string",
  "port": number,
  "protocol": "string",
  "serviceArn": "string",
  "serviceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the listener.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}`

[createdAt](#)

The date and time that the listener was created, in ISO-8601 format.

Type: Timestamp

[defaultAction](#)

The actions for the default listener rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

id

The ID of the listener.

Type: String

Length Constraints: Fixed length of 26.

Pattern: `listener-[0-9a-z]{17}`

lastUpdatedAt

The date and time that the listener was last updated, in ISO-8601 format.

Type: Timestamp

name

The name of the listener.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!listener-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

port

The listener port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

protocol

The listener protocol.

Type: String

Valid Values: HTTP | HTTPS | TLS_PASSTHROUGH

serviceArn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

serviceId

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourceConfiguration

Retrieves information about the specified resource configuration.

Request Syntax

```
GET /resourceconfigurations/resourceConfigurationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceConfigurationIdentifier

The ID of the resource configuration.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "allowAssociationToShareableServiceNetwork": boolean,
  "amazonManaged": boolean,
  "arn": "string",
  "createdAt": "string",
  "customDomainName": "string",
  "failureReason": "string",
  "id": "string",
```

```
"lastUpdatedAt": "string",
"name": "string",
"portRanges": [ "string" ],
"protocol": "string",
"resourceConfigurationDefinition": { ... },
"resourceConfigurationGroupId": "string",
"resourceGatewayId": "string",
"status": "string",
"type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[allowAssociationToShareableServiceNetwork](#)

Specifies whether the resource configuration is associated with a sharable service network.

Type: Boolean

[amazonManaged](#)

Indicates whether the resource configuration was created and is managed by Amazon.

Type: Boolean

[arn](#)

The Amazon Resource Name (ARN) of the resource configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:
\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

[createdAt](#)

The date and time that the resource configuration was created, in ISO-8601 format.

Type: Timestamp

customDomainName

The custom domain name of the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

failureReason

The reason the create-resource-configuration request failed.

Type: String

id

The ID of the resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

lastUpdatedAt

The most recent date and time that the resource configuration was updated, in ISO-8601 format.

Type: Timestamp

name

The name of the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rcfg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

portRanges

The TCP port ranges that a consumer can use to access a resource configuration. You can separate port ranges with a comma. Example: 1-65535 or 1,2,22-30

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 11.

Pattern: `((\d{1,5}\-\d{1,5})|(\d+))`

protocol

The TCP protocol accepted by the specified resource configuration.

Type: String

Valid Values: TCP

resourceConfigurationDefinition

The resource configuration.

Type: [ResourceConfigurationDefinition](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

resourceConfigurationGroupId

The ID of the group resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

resourceGatewayId

The ID of the resource gateway used to connect to the resource configuration in a given VPC. You can specify the resource gateway identifier only for resource configurations with type SINGLE, GROUP, or ARN.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

status

The status of the resource configuration.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS |
DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

type

The type of resource configuration.

- SINGLE - A single resource.
- GROUP - A group of resources.
- CHILD - A single resource that is part of a group resource configuration.
- ARN - An AWS resource.

Type: String

Valid Values: GROUP | CHILD | SINGLE | ARN

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourceGateway

Retrieves information about the specified resource gateway.

Request Syntax

```
GET /resourcegateways/resourceGatewayIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceGatewayIdentifier

The ID of the resource gateway.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((rgw-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourcegateway/rgw-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "createdAt": "string",
  "id": "string",
  "ipAddressType": "string",
  "lastUpdatedAt": "string",
  "name": "string",
  "securityGroupIds": [ "string" ],
```



```
"status": "string",  
"subnetIds": [ "string" ],  
"vpcId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the resource gateway.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourcegateway/
rgw-[0-9a-z]{17}`

createdAt

The date and time that the resource gateway was created, in ISO-8601 format.

Type: Timestamp

id

The ID of the resource gateway.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

ipAddressType

The type of IP address for the resource gateway.

Type: String

Valid Values: IPV4 | IPV6 | DUALSTACK

lastUpdatedAt

The date and time that the resource gateway was last updated, in ISO-8601 format.

Type: Timestamp

name

The name of the resource gateway.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rgw-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

securityGroupIds

The security group IDs associated with the resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-((([0-9a-z]{8})|([0-9a-z]{17})))`

status

The status for the resource gateway.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

subnetIds

The IDs of the VPC subnets for resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

vpId

The ID of the VPC for the resource gateway.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: `vpc-(([0-9a-z]{8})|([0-9a-z]{17}))`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetResourcePolicy

Retrieves information about the specified resource policy. The resource policy is an IAM policy created on behalf of the resource owner when they share a resource.

Request Syntax

```
GET /resourcepolicy/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the service network or service.

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)
{2}:((servicenetwork/sn)|(service/svc)|(resourceconfiguration/rcfg))-
[0-9a-z]{17}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

policy

An IAM policy.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Pattern: `.*\S.*`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRule

Retrieves information about the specified listener rules. You can also retrieve information about the default listener rule. For more information, see [Listener rules](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
GET /services/serviceIdentifier/listeners/listenerIdentifier/rules/ruleIdentifier
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

listenerIdentifier

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}\$))

Required: Yes

ruleIdentifier

The ID or ARN of the listener rule.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((rule-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}\$))

Required: Yes

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "action": { ... },
  "arn": "string",
  "createdAt": "string",
  "id": "string",
  "isDefault": boolean,
  "lastUpdatedAt": "string",
  "match": { ... },
  "name": "string",
  "priority": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

action

The action for the default rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

arn

The Amazon Resource Name (ARN) of the listener.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}`

createdAt

The date and time that the listener rule was created, in ISO-8601 format.

Type: Timestamp

id

The ID of the listener.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 22.

Pattern: `rule-[0-9a-z]{17}`

isDefault

Indicates whether this is the default rule.

Type: Boolean

lastUpdatedAt

The date and time that the listener rule was last updated, in ISO-8601 format.

Type: Timestamp

match

The rule match.

Type: [RuleMatch](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

name

The name of the listener.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!rule-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

priority

The priority level for the specified rule.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetService

Retrieves information about the specified service.

Request Syntax

```
GET /services/serviceIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "authType": "string",
  "certificateArn": "string",
  "createdAt": "string",
  "customDomainName": "string",
  "dnsEntry": {
    "domainName": "string",
```

```
    "hostedZoneId": "string"
  },
  "failureCode": "string",
  "failureMessage": "string",
  "id": "string",
  "lastUpdatedAt": "string",
  "name": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

authType

The type of IAM policy.

Type: String

Valid Values: NONE | AWS_IAM

certificateArn

The Amazon Resource Name (ARN) of the certificate.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `(arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?)?){2}:certificate/[0-9a-z-]+)?`

createdAt

The date and time that the service was created, in ISO-8601 format.

Type: Timestamp

customDomainName

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

dnsEntry

The DNS name of the service.

Type: [DnsEntry](#) object

failureCode

The failure code.

Type: String

failureMessage

The failure message.

Type: String

id

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: svc-[0-9a-z]{17}

lastUpdatedAt

The date and time that the service was last updated, in ISO-8601 format.

Type: Timestamp

name

The name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-])$)(?!.*[-]{2})[a-z0-9-]+`

status

The status of the service.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | DELETE_IN_PROGRESS |
CREATE_FAILED | DELETE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceNetwork

Retrieves information about the specified service network.

Request Syntax

```
GET /servicenetworks/serviceNetworkIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

serviceNetworkIdentifier

The ID or ARN of the service network.

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: ((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "authType": "string",
  "createdAt": "string",
  "id": "string",
  "lastUpdatedAt": "string",
  "name": "string",
  "numberOfAssociatedServices": number,
```

```
"numberOfAssociatedVPCs": number,  
"sharingConfig": {  
  "enabled": boolean  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

[authType](#)

The type of IAM policy.

Type: String

Valid Values: NONE | AWS_IAM

[createdAt](#)

The date and time that the service network was created, in ISO-8601 format.

Type: Timestamp

[id](#)

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

lastUpdatedAt

The date and time of the last update, in ISO-8601 format.

Type: Timestamp

name

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

numberOfAssociatedServices

The number of services associated with the service network.

Type: Long

numberOfAssociatedVPCs

The number of VPCs associated with the service network.

Type: Long

sharingConfig

Specifies if the service network is enabled for sharing.

Type: [SharingConfig](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceNetworkResourceAssociation

Retrieves information about the specified association between a service network and a resource configuration.

Request Syntax

```
GET /servicenetworkresourceassociations/serviceNetworkResourceAssociationIdentifier
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[serviceNetworkResourceAssociationIdentifier](#)

The ID of the association.

Length Constraints: Minimum length of 22. Maximum length of 2048.

Pattern: ((snra-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkresourceassociation/snra-[0-9a-f]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "createdAt": "string",
  "createdBy": "string",
  "dnsEntry": {
```

```
    "domainName": "string",
    "hostedZoneId": "string"
  },
  "failureCode": "string",
  "failureReason": "string",
  "id": "string",
  "isManagedAssociation": boolean,
  "lastUpdatedAt": "string",
  "privateDnsEntry": {
    "domainName": "string",
    "hostedZoneId": "string"
  },
  "resourceConfigurationArn": "string",
  "resourceConfigurationId": "string",
  "resourceConfigurationName": "string",
  "serviceNetworkArn": "string",
  "serviceNetworkId": "string",
  "serviceNetworkName": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 22. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:servicenetworkresourceassociation/snra-[0-9a-f]{17}`

[createdAt](#)

The date and time that the association was created, in ISO-8601 format.

Type: Timestamp

createdBy

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

dnsEntry

The DNS entry for the service.

Type: [DnsEntry](#) object

failureCode

The failure code.

Type: String

failureReason

The reason the association request failed.

Type: String

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snra-[0-9a-f]{17}`

isManagedAssociation

Indicates whether the association is managed by Amazon.

Type: Boolean

lastUpdatedAt

The most recent date and time that the association was updated, in ISO-8601 format.

Type: Timestamp

[privateDnsEntry](#)

The private DNS entry for the service.

Type: [DnsEntry](#) object

[resourceConfigurationArn](#)

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

[resourceConfigurationId](#)

The ID of the resource configuration that is associated with the service network.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

[resourceConfigurationName](#)

The name of the resource configuration that is associated with the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rcfg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

[serviceNetworkArn](#)

The Amazon Resource Name (ARN) of the service network that is associated with the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 2048.

serviceNetworkId

The ID of the service network that is associated with the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 2048.

serviceNetworkName

The name of the service network that is associated with the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 100.

status

The status of the association.

Type: String

Valid Values: CREATE_IN_PROGRESS | ACTIVE | PARTIAL | DELETE_IN_PROGRESS |
CREATE_FAILED | DELETE_FAILED

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceNetworkServiceAssociation

Retrieves information about the specified association between a service network and a service.

Request Syntax

```
GET /servicenetworkserviceassociations/serviceNetworkServiceAssociationIdentifier
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[serviceNetworkServiceAssociationIdentifier](#)

The ID or ARN of the association.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((snsa-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "createdAt": "string",
  "createdBy": "string",
  "customDomainName": "string",
  "dnsEntry": {
    "domainName": "string",
```

```
    "hostedZoneId": "string",
  },
  "failureCode": "string",
  "failureMessage": "string",
  "id": "string",
  "serviceArn": "string",
  "serviceId": "string",
  "serviceName": "string",
  "serviceNetworkArn": "string",
  "serviceNetworkId": "string",
  "serviceNetworkName": "string",
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}`

createdAt

The date and time that the association was created, in ISO-8601 format.

Type: Timestamp

createdBy

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

customDomainName

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

dnsEntry

The DNS name of the service.

Type: [DnsEntry](#) object

failureCode

The failure code.

Type: String

failureMessage

The failure message.

Type: String

id

The ID of the service network and service association.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((snsa-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}))`

serviceArn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

serviceId

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

serviceName

The name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-])$)(?!.*[-]{2})[a-z0-9\-\+]`

serviceNetworkArn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

serviceNetworkId

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

serviceNetworkName

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

status

The status of the association.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetServiceNetworkVpcAssociation

Retrieves information about the specified association between a service network and a VPC.

Request Syntax

```
GET /servicenetworkvpcassociations/serviceNetworkVpcAssociationIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[serviceNetworkVpcAssociationIdentifier](#)

The ID or ARN of the association.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((snva-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "createdAt": "string",
  "createdBy": "string",
  "failureCode": "string",
  "failureMessage": "string",
  "id": "string",
  "lastUpdatedAt": "string",
```

```
"securityGroupIds": [ "string" ],  
"serviceNetworkArn": "string",  
"serviceNetworkId": "string",  
"serviceNetworkName": "string",  
"status": "string",  
"vpcId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
\d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}`

[createdAt](#)

The date and time that the association was created, in ISO-8601 format.

Type: Timestamp

[createdBy](#)

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

[failureCode](#)

The failure code.

Type: String

failureMessage

The failure message.

Type: String

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snva-[0-9a-z]{17}`

lastUpdatedAt

The date and time that the association was last updated, in ISO-8601 format.

Type: Timestamp

securityGroupIds

The IDs of the security groups.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-((( [0-9a-z]{8} ) | ( [0-9a-z]{17} ) ) )`

serviceNetworkArn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

serviceNetworkId

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

serviceName

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

status

The status of the association.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `UPDATE_IN_PROGRESS` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED` | `UPDATE_FAILED`

vpcId

The ID of the VPC.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: `vpc-(([0-9a-z]{8})|([0-9a-z]{17}))`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTargetGroup

Retrieves information about the specified target group.

Request Syntax

```
GET /targetgroups/targetGroupIdentifier HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[targetGroupIdentifier](#)

The ID or ARN of the target group.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((tg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "config": {
    "healthCheck": {
      "enabled": boolean,
      "healthCheckIntervalSeconds": number,
      "healthCheckTimeoutSeconds": number,
      "healthyThresholdCount": number,
      "matcher": { ... },
```

```
    "path": "string",
    "port": number,
    "protocol": "string",
    "protocolVersion": "string",
    "unhealthyThresholdCount": number
  },
  "ipAddressType": "string",
  "lambdaEventStructureVersion": "string",
  "port": number,
  "protocol": "string",
  "protocolVersion": "string",
  "vpcIdentifier": "string"
},
"createdAt": "string",
"failureCode": "string",
"failureMessage": "string",
"id": "string",
"lastUpdatedAt": "string",
"name": "string",
"serviceArns": [ "string" ],
"status": "string",
"type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the target group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}`

config

The target group configuration.

Type: [TargetGroupConfig](#) object

[createdAt](#)

The date and time that the target group was created, in ISO-8601 format.

Type: Timestamp

[failureCode](#)

The failure code.

Type: String

[failureMessage](#)

The failure message.

Type: String

[id](#)

The ID of the target group.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `tg-[0-9a-z]{17}`

[lastUpdatedAt](#)

The date and time that the target group was last updated, in ISO-8601 format.

Type: Timestamp

[name](#)

The name of the target group.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `(?!tg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

[serviceArns](#)

The Amazon Resource Names (ARNs) of the service.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

status

The status.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

type

The target group type.

Type: String

Valid Values: `IP` | `LAMBDA` | `INSTANCE` | `ALB`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListAccessLogSubscriptions

Lists the access log subscriptions for the specified service network or service.

Request Syntax

```
GET /accesslogsubscriptions?  
maxResults=maxResults&nextToken=nextToken&resourceIdentifier=resourceIdentifier  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

resourceIdentifier

The ID or ARN of the service network or service.

Length Constraints: Minimum length of 17. Maximum length of 200.

Pattern: (((sn)|(svc)|(rcfg))-[0-9a-z]{17})|(arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)?){2}:((servicenetwork/sn)|(resourceconfiguration/rcfg)|(service/svc))-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "destinationArn": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "resourceArn": "string",
      "resourceId": "string",
      "serviceNetworkLogType": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the access log subscriptions.

Type: Array of [AccessLogSubscriptionSummary](#) objects

nextToken

A pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListListeners

Lists the listeners for the specified service.

Request Syntax

```
GET /services/serviceIdentifier/listeners?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[maxResults](#)

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

[nextToken](#)

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

[serviceIdentifier](#)

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```



```
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "name": "string",
      "port": number,
      "protocol": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the listeners.

Type: Array of [ListenerSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceConfigurations

Lists the resource configurations owned by or shared with this account.

Request Syntax

```
GET /resourceconfigurations?  
maxResults=maxResults&nextToken=nextToken&resourceConfigurationGroupIdentifier=resourceConfigur  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

resourceConfigurationGroupIdentifier

The ID of the resource configuration of type Group.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))

resourceGatewayIdentifier

The ID of the resource gateway for the resource configuration.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((rgw-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
\d{12}:resourcegateway/rgw-[0-9a-z]{17}))

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "amazonManaged": boolean,
      "arn": "string",
      "createdAt": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "name": "string",
      "resourceConfigurationGroupId": "string",
      "resourceGatewayId": "string",
      "status": "string",
      "type": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the resource configurations.

Type: Array of [ResourceConfigurationSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceEndpointAssociations

Lists the associations for the specified VPC endpoint.

Request Syntax

```
GET /resourceendpointassociations?  
maxResults=maxResults&nextToken=nextToken&resourceConfigurationIdentifier=resourceConfigurationIdentifier  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

resourceConfigurationIdentifier

The ID for the resource configuration associated with the VPC endpoint.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))

Required: Yes

resourceEndpointAssociationIdentifier

The ID of the association.

Length Constraints: Minimum length of 21. Maximum length of 2048.

Pattern: ((rea-[0-9a-f]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceendpointassociation/rea-[0-9a-f]{17}))

vpcEndpointId

The ID of the VPC endpoint in the association.

Length Constraints: Fixed length of 22.

Pattern: vpce-[0-9a-f]{17}

vpcEndpointOwner

The owner of the VPC endpoint in the association.

Length Constraints: Fixed length of 12.

Pattern: \d{12}

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "createdBy": "string",
      "id": "string",
      "resourceConfigurationArn": "string",
      "resourceConfigurationId": "string",
      "resourceConfigurationName": "string",
      "vpcEndpointId": "string",
      "vpcEndpointOwner": "string"
    }
  ],
  "nextToken": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[items](#)

Information about the VPC endpoint associations.

Type: Array of [ResourceEndpointAssociationSummary](#) objects

[nextToken](#)

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListResourceGateways

Lists the resource gateways that you own or that were shared with you.

Request Syntax

```
GET /resourcegateways?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

If there are additional results, a pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "id": "string",
      "ipAddressType": "string",
      "lastUpdatedAt": "string",
```

```
    "name": "string",
    "securityGroupIds": [ "string" ],
    "status": "string",
    "subnetIds": [ "string" ],
    "vpcIdentifier": "string"
  }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the resource gateways.

Type: Array of [ResourceGatewaySummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRules

Lists the rules for the specified listener.

Request Syntax

```
GET /services/serviceIdentifier/listeners/listenerIdentifier/rules?  
maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

listenerIdentifier

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}\$))

Required: Yes

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "id": "string",
      "isDefault": boolean,
      "lastUpdatedAt": "string",
      "name": "string",
      "priority": number
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the rules.

Type: Array of [RuleSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceNetworkResourceAssociations

Lists the associations between a service network and a resource configuration.

Request Syntax

```
GET /servicenetworkresourceassociations?
includeChildren=includeChildren&maxResults=maxResults&nextToken=nextToken&resourceConfigurationIdentifier=
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

includeChildren

Include service network resource associations of the child resource configuration with the grouped resource configuration.

The type is boolean and the default value is false.

maxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

If there are additional results, a pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

resourceConfigurationIdentifier

The ID of the resource configuration.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))

serviceNetworkIdentifier

The ID of the service network.

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: ((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}))

Request Body

The request does not have a request body.

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "createdBy": "string",
      "dnsEntry": {
        "domainName": "string",
        "hostedZoneId": "string"
      },
      "failureCode": "string",
      "id": "string",
      "isManagedAssociation": boolean,
      "privateDnsEntry": {
        "domainName": "string",
        "hostedZoneId": "string"
      },
      "resourceConfigurationArn": "string",
      "resourceConfigurationId": "string",
      "resourceConfigurationName": "string",
      "serviceNetworkArn": "string",
      "serviceNetworkId": "string",
      "serviceNetworkName": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the associations.

Type: Array of [ServiceNetworkResourceAssociationSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceNetworks

Lists the service networks owned by or shared with this account. The account ID in the ARN shows which account owns the service network.

Request Syntax

```
GET /servicenetworks?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "id": "string",
```

```
    "lastUpdatedAt": "string",  
    "name": "string",  
    "numberOfAssociatedResourceConfigurations": number,  
    "numberOfAssociatedServices": number,  
    "numberOfAssociatedVPCs": number  
  }  
],  
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the service networks.

Type: Array of [ServiceNetworkSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceNetworkServiceAssociations

Lists the associations between a service network and a service. You can filter the list either by service or service network. You must provide either the service network identifier or the service identifier.

Every association in Amazon VPC Lattice has a unique Amazon Resource Name (ARN), such as when a service network is associated with a VPC or when a service is associated with a service network. If the association is for a resource is shared with another account, the association includes the local account ID as the prefix in the ARN.

Request Syntax

```
GET /servicenetworkserviceassociations?
maxResults=maxResults&nextToken=nextToken&serviceIdentifier=serviceIdentifier&serviceNetworkId=
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:service/svc-[0-9a-z]{17}))

serviceNetworkIdentifier

The ID or ARN of the service network.

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: ((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17})))

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "createdBy": "string",
      "customDomainName": "string",
      "dnsEntry": {
        "domainName": "string",
        "hostedZoneId": "string"
      },
      "id": "string",
      "serviceArn": "string",
      "serviceId": "string",
      "serviceName": "string",
      "serviceNetworkArn": "string",
      "serviceNetworkId": "string",
      "serviceNetworkName": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the associations.

Type: Array of [ServiceNetworkServiceAssociationSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceNetworkVpcAssociations

Lists the associations between a service network and a VPC. You can filter the list either by VPC or service network. You must provide either the ID of the service network identifier or the ID of the VPC.

Request Syntax

```
GET /servicenetworkvpcassociations?
maxResults=maxResults&nextToken=nextToken&serviceNetworkIdentifier=serviceNetworkIdentifier&vpcIdentifier=vpcIdentifier
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

serviceNetworkIdentifier

The ID or ARN of the service network.

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: ((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}))

vpcIdentifier

The ID or ARN of the VPC.

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: vpc-(([0-9a-z]{8})|([0-9a-z]{17}))

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "createdBy": "string",
      "id": "string",
      "lastUpdatedAt": "string",
      "serviceNetworkArn": "string",
      "serviceNetworkId": "string",
      "serviceNetworkName": "string",
      "status": "string",
      "vpcId": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the associations.

Type: Array of [ServiceNetworkVpcAssociationSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServiceNetworkVpcEndpointAssociations

Lists the associations between a service network and a VPC endpoint.

Request Syntax

```
GET /servicenetworkvpcendpointassociations?  
maxResults=maxResults&nextToken=nextToken&serviceNetworkIdentifier=serviceNetworkIdentifier  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum page size.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

If there are additional results, a pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

serviceNetworkIdentifier

The ID of the service network associated with the VPC endpoint.

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: ((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
\d{12}:servicenetwork/sn-[0-9a-z]{17}))

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "createdAt": "string",
      "id": "string",
      "serviceNetworkArn": "string",
      "state": "string",
      "vpcEndpointId": "string",
      "vpcEndpointOwnerId": "string",
      "vpcId": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the association between the VPC endpoint and service network.

Type: Array of [ServiceNetworkEndpointAssociation](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListServices

Lists the services owned by the caller account or shared with the caller account.

Request Syntax

```
GET /services?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "customDomainName": "string",
      "dnsEntry": {
        "domainName": "string",
```

```
    "hostedZoneId": "string",
  },
  "id": "string",
  "lastUpdatedAt": "string",
  "name": "string",
  "status": "string"
}
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the services.

Type: Array of [ServiceSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Lists the tags for the specified resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1224.

Pattern: `arn:[a-z0-9][-.a-z0-9]{0,62}:vpc-lattice:([a-z0-9][-.a-z0-9]{0,62})?:\d{12}?:[^/].{0,1023}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

Information about the tags.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTargetGroups

Lists your target groups. You can narrow your search by using the filters below in your request.

Request Syntax

```
GET /targetgroups?  
maxResults=maxResults&nextToken=nextToken&targetGroupType=targetGroupType&vpcIdentifier=vpcIdentifier  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

targetGroupType

The target group type.

Valid Values: IP | LAMBDA | INSTANCE | ALB

vpcIdentifier

The ID or ARN of the VPC.

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: vpc-(([0-9a-z]{8})|([0-9a-z]{17}))

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "items": [
    {
      "arn": "string",
      "createdAt": "string",
      "id": "string",
      "ipAddressType": "string",
      "lambdaEventStructureVersion": "string",
      "lastUpdatedAt": "string",
      "name": "string",
      "port": number,
      "protocol": "string",
      "serviceArns": [ "string" ],
      "status": "string",
      "type": "string",
      "vpcIdentifier": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the target groups.

Type: Array of [TargetGroupSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTargets

Lists the targets for the target group. By default, all targets are included. You can use this API to check the health status of targets. You can also filter the results by target.

Request Syntax

```
POST /targetgroups/targetGroupIdentifier/listtargets?
maxResults=maxResults&nextToken=nextToken HTTP/1.1
Content-type: application/json
```

```
{
  "targets": [
    {
      "id": "string",
      "port": number
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to return.

Valid Range: Minimum value of 1. Maximum value of 100.

nextToken

A pagination token for the next page of results.

Length Constraints: Minimum length of 1. Maximum length of 2048.

targetGroupIdentifier

The ID or ARN of the target group.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((tg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

targets

The targets.

Type: Array of [Target](#) objects

Array Members: Minimum number of 0 items. Maximum number of 20 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "items": [
    {
      "id": "string",
      "port": number,
      "reasonCode": "string",
      "status": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

items

Information about the targets.

Type: Array of [TargetSummary](#) objects

nextToken

If there are additional results, a pagination token for the next page of results.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutAuthPolicy

Creates or updates the auth policy. The policy string in JSON must not contain newlines or blank lines.

For more information, see [Auth policies](#) in the *Amazon VPC Lattice User Guide*.

Request Syntax

```
PUT /authpolicy/resourceIdentifier HTTP/1.1
Content-type: application/json

{
  "policy": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[resourceIdentifier](#)

The ID or ARN of the service network or service for which the policy is created.

Length Constraints: Minimum length of 17. Maximum length of 200.

Pattern: (((sn)|(svc)|(rcfg))-[0-9a-z]{17})|(arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)?){2}:((servicenetwork/sn)|(resourceconfiguration/rcfg)|(service/svc))-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

[policy](#)

The auth policy. The policy string in JSON must not contain newlines or blank lines.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "policy": "string",
  "state": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[policy](#)

The auth policy. The policy string in JSON must not contain newlines or blank lines.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 10000.

[state](#)

The state of the auth policy. The auth policy is only active when the auth type is set to `AWS_IAM`. If you provide a policy, then authentication and authorization decisions are made based on this policy and the client's IAM policy. If the Auth type is `NONE`, then, any auth policy that you provide remains inactive. For more information, see [Create a service network](#) in the *Amazon VPC Lattice User Guide*.

Type: String

Valid Values: Active | Inactive

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

PutResourcePolicy

Attaches a resource-based permission policy to a service or service network. The policy must contain the same actions and condition statements as the AWS Resource Access Manager permission for sharing services and service networks.

Request Syntax

```
PUT /resourcepolicy/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "policy": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ID or ARN of the service network or service for which the policy is created.

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)`
`{2}:(servicenetwork/sn)|(service/svc)|(resourceconfiguration/rcfg))-`
`[0-9a-z]{17}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

policy

An IAM policy. The policy string in JSON must not contain newlines or blank lines.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 10000.

Pattern: `.*\S.*`

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RegisterTargets

Registers the targets with the target group. If it's a Lambda target, you can only have one target in a target group.

Request Syntax

```
POST /targetgroups/targetGroupIdentifier/registertargets HTTP/1.1
Content-type: application/json
```

```
{
  "targets": [
    {
      "id": "string",
      "port": number
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

targetGroupIdentifier

The ID or ARN of the target group.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((tg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

targets

The targets.

Type: Array of [Target](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "successful": [
    {
      "id": "string",
      "port": number
    }
  ],
  "unsuccessful": [
    {
      "failureCode": "string",
      "failureMessage": "string",
      "id": "string",
      "port": number
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[successful](#)

The targets that were successfully registered.

Type: Array of [Target](#) objects

[unsuccessful](#)

The targets that were not registered.

Type: Array of [TargetFailure](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds the specified tags to the specified resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1224.

Pattern: `arn:[a-z0-9][-.a-z0-9]{0,62}:vpc-lattice:([a-z0-9][-.a-z0-9]{0,62})?:\d{12}?:[^/].{0,1023}`

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

The tags for the resource.

Type: String to string map

Map Entries: Minimum number of 0 items. Maximum number of 200 items.

Key Length Constraints: Minimum length of 1. Maximum length of 128.

Value Length Constraints: Minimum length of 0. Maximum length of 256.

Required: Yes

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes the specified tags from the specified resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The Amazon Resource Name (ARN) of the resource.

Length Constraints: Minimum length of 0. Maximum length of 1224.

Pattern: `arn:[a-z0-9][-.a-z0-9]{0,62}:vpc-lattice:([a-z0-9][-.a-z0-9]{0,62})?:\d{12}?:[^/].{0,1023}`

Required: Yes

tagKeys

The tag keys of the tags to remove.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAccessLogSubscription

Updates the specified access log subscription.

Request Syntax

```
PATCH /accesslogsubscriptions/accessLogSubscriptionIdentifier HTTP/1.1
Content-type: application/json

{
  "destinationArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

accessLogSubscriptionIdentifier

The ID or ARN of the access log subscription.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((als-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:accesslogsubscription/als-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

destinationArn

The Amazon Resource Name (ARN) of the access log destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?)?{2}:([^\/.]*))?`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "destinationArn": "string",
  "id": "string",
  "resourceArn": "string",
  "resourceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the access log subscription.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-.]+:vpc-lattice:[a-zA-Z0-9\-.]+:\d{12}:accesslogsubscription/als-[0-9a-z]{17}`

destinationArn

The Amazon Resource Name (ARN) of the access log destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)`
`{2}:([^\/.]*)?`

id

The ID of the access log subscription.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `als-[0-9a-z]{17}`

resourceArn

The Amazon Resource Name (ARN) of the access log subscription.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn(:[a-z0-9]+([.-][a-z0-9]+)*){2}(:([a-z0-9]+([.-][a-z0-9]+)*)?)`
`{2}:((servicenetwork/sn)|(service/svc)|(resourceconfiguration/rcfg))-`
`[0-9a-z]{17}`

resourceId

The ID of the resource.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 50.

Pattern: `((sn)|(svc))-[0-9a-z]{17}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateListener

Updates the specified listener for the specified service.

Request Syntax

```
PATCH /services/serviceIdentifier/listeners/listenerIdentifier HTTP/1.1
Content-type: application/json

{
  "defaultAction": { ... }
}
```

URI Request Parameters

The request uses the following URI parameters.

[listenerIdentifier](#)

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}\$))

Required: Yes

[serviceIdentifier](#)

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

defaultAction

The action for the default rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "defaultAction": { ... },
  "id": "string",
  "name": "string",
  "port": number,
  "protocol": "string",
  "serviceArn": "string",
  "serviceId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the listener.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}`

defaultAction

The action for the default rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

id

The ID of the listener.

Type: String

Length Constraints: Fixed length of 26.

Pattern: `listener-[0-9a-z]{17}`

name

The name of the listener.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!listener-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

port

The listener port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

protocol

The protocol of the listener.

Type: String

Valid Values: HTTP | HTTPS | TLS_PASSTHROUGH

serviceArn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

serviceId

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateResourceConfiguration

Updates the specified resource configuration.

Request Syntax

```
PATCH /resourceconfigurations/resourceConfigurationIdentifier HTTP/1.1
Content-type: application/json

{
  "allowAssociationToShareableServiceNetwork": boolean,
  "portRanges": [ "string" ],
  "resourceConfigurationDefinition": { ... }
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceConfigurationIdentifier

The ID of the resource configuration.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ((rcfg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

allowAssociationToShareableServiceNetwork

Indicates whether to add the resource configuration to service networks that are shared with other accounts.

Type: Boolean

Required: No

portRanges

The TCP port ranges that a consumer can use to access a resource configuration. You can separate port ranges with a comma. Example: 1-65535 or 1,2,22-30

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 11.

Pattern: `((\d{1,5}\-\d{1,5})|(\d+))`

Required: No

resourceConfigurationDefinition

Identifies the resource configuration in one of the following ways:

- **Amazon Resource Name (ARN)** - Supported resource-types that are provisioned by AWS services, such as RDS databases, can be identified by their ARN.
- **Domain name** - Any domain name that is publicly resolvable.
- **IP address** - For IPv4 and IPv6, only IP addresses in the VPC are supported.

Type: [ResourceConfigurationDefinition](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{
  "allowAssociationToShareableServiceNetwork": boolean,
  "arn": "string",
  "id": "string",
  "name": "string",
  "portRanges": [ "string" ],
  "protocol": "string",
  "resourceConfigurationDefinition": { ... },
```

```
"resourceConfigurationGroupId": "string",  
"resourceGatewayId": "string",  
"status": "string",  
"type": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

allowAssociationToShareableServiceNetwork

Indicates whether to add the resource configuration to service networks that are shared with other accounts.

Type: Boolean

arn

The Amazon Resource Name (ARN) of the resource configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

id

The ID of the resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

name

The name of the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rcfg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

portRanges

The TCP port ranges that a consumer can use to access a resource configuration. You can separate port ranges with a comma. Example: 1-65535 or 1,2,22-30

Type: Array of strings

Length Constraints: Minimum length of 1. Maximum length of 11.

Pattern: `((\d{1,5}\-\d{1,5})|(\d+))`

protocol

The TCP protocol accepted by the specified resource configuration.

Type: String

Valid Values: TCP

resourceConfigurationDefinition

The resource configuration.

Type: [ResourceConfigurationDefinition](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

resourceConfigurationGroupId

The ID of the group resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

resourceGatewayId

The ID of the resource gateway associated with the resource configuration.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

status

The status of the resource configuration.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

type

The type of resource configuration.

- SINGLE - A single resource.
- GROUP - A group of resources.
- CHILD - A single resource that is part of a group resource configuration.
- ARN - An AWS resource.

Type: String

Valid Values: GROUP | CHILD | SINGLE | ARN

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateResourceGateway

Updates the specified resource gateway.

Request Syntax

```
PATCH /resourcegateways/resourceGatewayIdentifier HTTP/1.1
Content-type: application/json
```

```
{
  "securityGroupIds": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceGatewayIdentifier

The ID or ARN of the resource gateway.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((rgw-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourcegateway/rgw-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

securityGroupIds

The IDs of the security groups associated with the resource gateway.

Type: Array of strings

Array Members: Minimum number of 0 items. Maximum number of 5 items.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: sg-(([0-9a-z]{8})|([0-9a-z]{17}))

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "id": "string",
  "ipAddressType": "string",
  "name": "string",
  "securityGroupIds": [ "string" ],
  "status": "string",
  "subnetIds": [ "string" ],
  "vpcId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the resource gateway.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourcegateway/rgw-[0-9a-z]{17}

id

The ID of the resource gateway.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

ipAddressType

The type of IP address used by the resource gateway.

Type: String

Valid Values: IPV4 | IPV6

name

The name of the resource gateway.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rgw-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

securityGroupIds

The IDs of the security groups associated with the resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-((( [0-9a-z]{8} )) | ( [0-9a-z]{17} ))`

status

The status of the resource gateway.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

subnetIds

The IDs of the VPC subnets for the resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

vpclId

The ID of the VPC for the resource gateway.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: `vpc-(([0-9a-z]{8})|([0-9a-z]{17}))`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRule

Updates a specified rule for the listener. You can't modify a default listener rule. To modify a default listener rule, use `UpdateListener`.

Request Syntax

```
PATCH /services/serviceIdentifier/listeners/listenerIdentifier/rules/ruleIdentifier
HTTP/1.1
Content-type: application/json

{
  "action": { ... },
  "match": { ... },
  "priority": number
}
```

URI Request Parameters

The request uses the following URI parameters.

listenerIdentifier

The ID or ARN of the listener.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((listener-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}$))`

Required: Yes

ruleIdentifier

The ID or ARN of the rule.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((rule-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}$))`

Required: Yes

[serviceIdentifier](#)

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

[action](#)

Information about the action for the specified listener rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[match](#)

The rule match.

Type: [RuleMatch](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

[priority](#)

The rule priority. A listener can't have multiple rules with the same priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "action": { ... },
  "arn": "string",
  "id": "string",
  "isDefault": boolean,
  "match": { ... },
  "name": "string",
  "priority": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[action](#)

Information about the action for the specified listener rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

[arn](#)

The Amazon Resource Name (ARN) of the listener.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}`

[id](#)

The ID of the listener.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 22.

Pattern: `rule-[0-9a-z]{17}`

isDefault

Indicates whether this is the default rule.

Type: Boolean

match

The rule match.

Type: [RuleMatch](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

name

The name of the listener.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!rule-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

priority

The rule priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateService

Updates the specified service.

Request Syntax

```
PATCH /services/serviceIdentifier HTTP/1.1
Content-type: application/json

{
  "authType": "string",
  "certificateArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

serviceIdentifier

The ID or ARN of the service.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((svc-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

authType

The type of IAM policy.

- **NONE:** The resource does not use an IAM policy. This is the default.
- **AWS_IAM:** The resource uses an IAM policy. When this type is used, auth is enabled and an auth policy is required.

Type: String

Valid Values: NONE | AWS_IAM

Required: No

certificateArn

The Amazon Resource Name (ARN) of the certificate.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: (arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?){2}:certificate/[0-9a-z-]+)?

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "arn": "string",
  "authType": "string",
  "certificateArn": "string",
  "customDomainName": "string",
  "id": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

authType

The type of IAM policy.

Type: String

Valid Values: NONE | AWS_IAM

certificateArn

The Amazon Resource Name (ARN) of the certificate.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `(arn(:[a-z0-9]+(\.[a-z0-9]+)*){2}(:([a-z0-9]+(\.[a-z0-9]+)*)?)?){2}:certificate/[0-9a-z-]+)?`

customDomainName

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

id

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

name

The name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-])$)(?!.*[-]{2})[a-z0-9-]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceNetwork

Updates the specified service network.

Request Syntax

```
PATCH /servicenetworks/serviceNetworkIdentifier HTTP/1.1
Content-type: application/json
```

```
{
  "authType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

serviceNetworkIdentifier

The ID or ARN of the service network.

Length Constraints: Minimum length of 3. Maximum length of 2048.

Pattern: ((sn-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

authType

The type of IAM policy.

- **NONE:** The resource does not use an IAM policy. This is the default.
- **AWS_IAM:** The resource uses an IAM policy. When this type is used, auth is enabled and an auth policy is required.

Type: String

Valid Values: NONE | AWS_IAM

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "authType": "string",
  "id": "string",
  "name": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

authType

The type of IAM policy.

Type: String

Valid Values: NONE | AWS_IAM

id

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

name

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateServiceNetworkVpcAssociation

Updates the service network and VPC association. If you add a security group to the service network and VPC association, the association must continue to have at least one security group. You can add or edit security groups at any time. However, to remove all security groups, you must first delete the association and then recreate it without security groups.

Request Syntax

```
PATCH /servicenetworkvpcassociations/serviceNetworkVpcAssociationIdentifier HTTP/1.1
Content-type: application/json

{
  "securityGroupIds": [ "string" ]
}
```

URI Request Parameters

The request uses the following URI parameters.

serviceNetworkVpcAssociationIdentifier

The ID or ARN of the association.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((snva-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

securityGroupIds

The IDs of the security groups.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-([0-9a-z]{8})|([0-9a-z]{17})`

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "arn": "string",
  "createdBy": "string",
  "id": "string",
  "securityGroupIds": [ "string" ],
  "status": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[arn](#)

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}`

[createdBy](#)

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snva-[0-9a-z]{17}`

securityGroupIds

The IDs of the security groups.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: `sg-((( [0-9a-z]{8} ) | ( [0-9a-z]{17} ) ) )`

status

The status. You can retry the operation if the status is `DELETE_FAILED`. However, if you retry it while the status is `DELETE_IN_PROGRESS`, there is no change in the status.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `UPDATE_IN_PROGRESS` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED` | `UPDATE_FAILED`

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerErrorException

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTargetGroup

Updates the specified target group.

Request Syntax

```
PATCH /targetgroups/targetGroupIdentifier HTTP/1.1
Content-type: application/json
```

```
{
  "healthCheck": {
    "enabled": boolean,
    "healthCheckIntervalSeconds": number,
    "healthCheckTimeoutSeconds": number,
    "healthyThresholdCount": number,
    "matcher": { ... },
    "path": "string",
    "port": number,
    "protocol": "string",
    "protocolVersion": "string",
    "unhealthyThresholdCount": number
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

targetGroupIdentifier

The ID or ARN of the target group.

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: ((tg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:
d{12}:targetgroup/tg-[0-9a-z]{17}))

Required: Yes

Request Body

The request accepts the following data in JSON format.

healthCheck

The health check configuration.

Type: [HealthCheckConfig](#) object

Required: Yes

Response Syntax

HTTP/1.1 200

Content-type: application/json

```
{
  "arn": "string",
  "config": {
    "healthCheck": {
      "enabled": boolean,
      "healthCheckIntervalSeconds": number,
      "healthCheckTimeoutSeconds": number,
      "healthyThresholdCount": number,
      "matcher": { ... },
      "path": "string",
      "port": number,
      "protocol": "string",
      "protocolVersion": "string",
      "unhealthyThresholdCount": number
    },
    "ipAddressType": "string",
    "lambdaEventStructureVersion": "string",
    "port": number,
    "protocol": "string",
    "protocolVersion": "string",
    "vpcIdentifier": "string"
  },
  "id": "string",
  "name": "string",
  "status": "string",
  "type": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

arn

The Amazon Resource Name (ARN) of the target group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}`

config

The target group configuration.

Type: [TargetGroupConfig](#) object

id

The ID of the target group.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `tg-[0-9a-z]{17}`

name

The name of the target group.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `(?!tg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9\-\+]`

status

The status.

Type: String

Valid Values: CREATE_IN_PROGRESS | ACTIVE | DELETE_IN_PROGRESS |
CREATE_FAILED | DELETE_FAILED

type

The target group type.

Type: String

Valid Values: IP | LAMBDA | INSTANCE | ALB

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

The user does not have sufficient access to perform this action.

HTTP Status Code: 403

ConflictException

The request conflicts with the current state of the resource. Updating or deleting a resource can cause an inconsistent state.

HTTP Status Code: 409

InternalServerError

An unexpected error occurred while processing the request.

HTTP Status Code: 500

ResourceNotFoundException

The request references a resource that does not exist.

HTTP Status Code: 404

ServiceQuotaExceededException

The request would cause a service quota to be exceeded.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The input does not satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for Kotlin](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon VPC Lattice API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AccessLogSubscriptionSummary](#)
- [ArnResource](#)
- [DnsEntry](#)
- [DnsResource](#)
- [FixedResponseAction](#)
- [ForwardAction](#)
- [HeaderMatch](#)
- [HeaderMatchType](#)
- [HealthCheckConfig](#)
- [HttpMatch](#)
- [IpResource](#)
- [ListenerSummary](#)
- [Matcher](#)
- [PathMatch](#)
- [PathMatchType](#)
- [ResourceConfigurationDefinition](#)
- [ResourceConfigurationSummary](#)
- [ResourceEndpointAssociationSummary](#)
- [ResourceGatewaySummary](#)
- [RuleAction](#)

- [RuleMatch](#)
- [RuleSummary](#)
- [RuleUpdate](#)
- [RuleUpdateFailure](#)
- [RuleUpdateSuccess](#)
- [ServiceNetworkEndpointAssociation](#)
- [ServiceNetworkResourceAssociationSummary](#)
- [ServiceNetworkServiceAssociationSummary](#)
- [ServiceNetworkSummary](#)
- [ServiceNetworkVpcAssociationSummary](#)
- [ServiceSummary](#)
- [SharingConfig](#)
- [Target](#)
- [TargetFailure](#)
- [TargetGroupConfig](#)
- [TargetGroupSummary](#)
- [TargetSummary](#)
- [ValidationExceptionField](#)
- [WeightedTargetGroup](#)

AccessLogSubscriptionSummary

Summary information about an access log subscription.

Contents

arn

The Amazon Resource Name (ARN) of the access log subscription

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:accesslogsubscription/als-[0-9a-z]{17}`

Required: Yes

createdAt

The date and time that the access log subscription was created, in ISO-8601 format.

Type: Timestamp

Required: Yes

destinationArn

The Amazon Resource Name (ARN) of the destination.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn(:[a-z0-9]+([\.-][a-z0-9]+)*){2}(:([a-z0-9]+([\.-][a-z0-9]+)*)?)\d{2}:([^\./].*)?`

Required: Yes

id

The ID of the access log subscription.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `als-[0-9a-z]{17}`

Required: Yes

lastUpdatedAt

The date and time that the access log subscription was last updated, in ISO-8601 format.

Type: Timestamp

Required: Yes

resourceArn

The Amazon Resource Name (ARN) of the service or service network.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 200.

Pattern: `arn(:[a-z0-9]+(.[a-z0-9]+)*){2}(:([a-z0-9]+(.[a-z0-9]+)*)?)
{2}:((servicenetwork/sn)|(service/svc)|(resourceconfiguration/rcfg))-
[0-9a-z]{17}`

Required: Yes

resourceId

The ID of the service or service network.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 50.

Pattern: `((sn)|(svc))-[0-9a-z]{17}`

Required: Yes

serviceNetworkLogType

Log type of the service network.

Type: String

Valid Values: SERVICE | RESOURCE

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ArnResource

The Amazon Resource Name (ARN) of the resource.

Contents

arn

The Amazon Resource Name (ARN) of the resource.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9][-.a-z0-9]{0,62}:[a-z0-9][-.a-z0-9]{0,62}:([a-z0-9][-.a-z0-9]{0,62})?:\d{12}?:[^/]{0,1023}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DnsEntry

Describes the DNS information of a service.

Contents

domainName

The domain name of the service.

Type: String

Required: No

hostedZoneId

The ID of the hosted zone.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DnsResource

The DNS name of the resource.

Contents

domainName

The domain name of the resource.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Required: No

ipAddressType

The type of IP address. Dualstack is currently not supported.

Type: String

Valid Values: IPV4 | IPV6 | DUALSTACK

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

FixedResponseAction

Describes an action that returns a custom HTTP response.

Contents

statusCode

The HTTP response code. Only 404 and 500 status codes are supported.

Type: Integer

Valid Range: Minimum value of 100. Maximum value of 599.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ForwardAction

Describes a forward action. You can use forward actions to route requests to one or more target groups.

Contents

targetGroups

The target groups. Traffic matching the rule is forwarded to the specified target groups. With forward actions, you can assign a weight that controls the prioritization and selection of each target group. This means that requests are distributed to individual target groups based on their weights. For example, if two target groups have the same weight, each target group receives half of the traffic.

The default value is 1. This means that if only one target group is provided, there is no need to set the weight; 100% of the traffic goes to that target group.

Type: Array of [WeightedTargetGroup](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HeaderMatch

Describes the constraints for a header match. Matches incoming requests with rule based on request header value before applying rule action.

Contents

match

The header match type.

Type: [HeaderMatchType](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

name

The name of the header.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 100.

Required: Yes

caseSensitive

Indicates whether the match is case sensitive.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

HeaderMatchType

Describes a header match type.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

contains

A contains type match.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

exact

An exact type match.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

prefix

A prefix type match. Matches the value with the prefix.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HealthCheckConfig

Describes the health check configuration of a target group. Health check configurations aren't used for target groups of type LAMBDA or ALB.

Contents

enabled

Indicates whether health checking is enabled.

Type: Boolean

Required: No

healthCheckIntervalSeconds

The approximate amount of time, in seconds, between health checks of an individual target. The range is 5–300 seconds. The default is 30 seconds.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 300.

Required: No

healthCheckTimeoutSeconds

The amount of time, in seconds, to wait before reporting a target as unhealthy. The range is 1–120 seconds. The default is 5 seconds.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 120.

Required: No

healthyThresholdCount

The number of consecutive successful health checks required before considering an unhealthy target healthy. The range is 2–10. The default is 5.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

matcher

The codes to use when checking for a successful response from a target.

Type: [Matcher](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

path

The destination for health checks on the targets. If the protocol version is HTTP/1.1 or HTTP/2, specify a valid URI (for example, /path?query). The default path is /. Health checks are not supported if the protocol version is gRPC, however, you can choose HTTP/1.1 or HTTP/2 and specify a valid URI.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `.*(^/[a-zA-Z0-9@:%_+~#?&/=-]*$|^$)).*`

Required: No

port

The port used when performing health checks on targets. The default setting is the port that a target receives traffic on.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 65535.

Required: No

protocol

The protocol used when performing health checks on targets. The possible protocols are HTTP and HTTPS. The default is HTTP.

Type: String

Valid Values: HTTP | HTTPS | TCP

Required: No

protocolVersion

The protocol version used when performing health checks on targets. The possible protocol versions are HTTP1 and HTTP2.

Type: String

Valid Values: HTTP1 | HTTP2

Required: No

unhealthyThresholdCount

The number of consecutive failed health checks required before considering a target unhealthy. The range is 2–10. The default is 2.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 10.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

HttpMatch

Describes criteria that can be applied to incoming requests.

Contents

headerMatches

The header matches. Matches incoming requests with rule based on request header value before applying rule action.

Type: Array of [HeaderMatch](#) objects

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Required: No

method

The HTTP method type.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16.

Required: No

pathMatch

The path match.

Type: [PathMatch](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

IpResource

Describes an IP resource.

Contents

ipAddress

The IP address of the IP resource.

Type: String

Length Constraints: Minimum length of 4. Maximum length of 39.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ListenerSummary

Summary information about a listener.

Contents

arn

The Amazon Resource Name (ARN) of the listener.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the listener was created, in ISO-8601 format.

Type: Timestamp

Required: No

id

The ID of the listener.

Type: String

Length Constraints: Fixed length of 26.

Pattern: `listener-[0-9a-z]{17}`

Required: No

lastUpdatedAt

The date and time that the listener was last updated, in ISO-8601 format.

Type: Timestamp

Required: No

name

The name of the listener.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!listener-)(?![-])(?!.*[-])$)(?!.*[-]{2})[a-z0-9-]+`

Required: No

port

The listener port.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

protocol

The listener protocol.

Type: String

Valid Values: HTTP | HTTPS | TLS_PASSTHROUGH

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Matcher

Describes the codes to use when checking for a successful response from a target for health checks.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

httpCode

The HTTP code to use when checking for a successful response from a target.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2000.

Pattern: `.*([0-9- , ]+$|(^$)).*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PathMatch

Describes the conditions that can be applied when matching a path for incoming requests.

Contents

match

The type of path match.

Type: [PathMatchType](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: Yes

caseSensitive

Indicates whether the match is case sensitive.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PathMatchType

Describes a path match type. Each rule can include only one of the following types of paths.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

exact

An exact match of the path.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `/[a-zA-Z0-9@:%_+~#?&/=-]*`

Required: No

prefix

A prefix match of the path.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Pattern: `/[a-zA-Z0-9@:%_+~#?&/=-]*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceConfigurationDefinition

Describes a resource configuration.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

arnResource

The Amazon Resource Name (ARN) of the resource.

Type: [ArnResource](#) object

Required: No

dnsResource

The DNS name of the resource.

Type: [DnsResource](#) object

Required: No

ipResource

The IP resource.

Type: [IpResource](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceConfigurationSummary

Summary information about a resource configuration.

Contents

amazonManaged

Indicates whether the resource configuration was created and is managed by Amazon.

Type: Boolean

Required: No

arn

The Amazon Resource Name (ARN) of the resource configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the resource configuration was created, in ISO-8601 format.

Type: Timestamp

Required: No

id

The ID of the resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

Required: No

lastUpdatedAt

The most recent date and time that the resource configuration was updated, in ISO-8601 format.

Type: Timestamp

Required: No

name

The name of the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: (?!rcfg-)(?![-])(?!.*[-]\$)(?!.*[-]{2})[a-z0-9-]+

Required: No

resourceConfigurationGroupId

The ID of the group resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: rcfg-[0-9a-z]{17}

Required: No

resourceGatewayId

The ID of the resource gateway.

Type: String

Length Constraints: Fixed length of 21.

Pattern: rgw-[0-9a-z]{17}

Required: No

status

The status of the resource configuration.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

Required: No

type

The type of resource configuration.

- SINGLE - A single resource.
- GROUP - A group of resources. You must create a group resource configuration before you create a child resource configuration.
- CHILD - A single resource that is part of a group resource configuration.
- ARN - An AWS resource.

Type: String

Valid Values: GROUP | CHILD | SINGLE | ARN

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceEndpointAssociationSummary

Summary information about a VPC endpoint association.

Contents

arn

The Amazon Resource Name (ARN) of the VPC endpoint association.

Type: String

Length Constraints: Minimum length of 21. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourceendpointassociation/rea-[0-9a-f]{17}`

Required: No

createdAt

The date and time that the VPC endpoint association was created, in ISO-8601 format.

Type: Timestamp

Required: No

createdBy

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

Required: No

id

The ID of the VPC endpoint association.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rea-[0-9a-f]{17}`

Required: No

resourceConfigurationArn

The Amazon Resource Name (ARN) of the resource configuration.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+:\d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

Required: No

resourceConfigurationId

The ID of the resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

Required: No

resourceConfigurationName

The name of the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rcfg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]{3,40}`

Required: No

vpcEndpointId

The ID of the VPC endpoint.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `vpce-[0-9a-f]{17}`

Required: No

vpcEndpointOwner

The owner of the VPC endpoint.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `\d{12}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResourceGatewaySummary

Summary information about a resource gateway.

Contents

arn

The Amazon Resource Name (ARN) of the resource gateway.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:resourcegateway/rgw-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the VPC endpoint association was created, in ISO-8601 format.

Type: Timestamp

Required: No

id

The ID of the resource gateway.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `rgw-[0-9a-z]{17}`

Required: No

ipAddressType

The type of IP address used by the resource gateway.

Type: String

Valid Values: IPV4 | IPV6 | DUALSTACK

Required: No

lastUpdatedAt

The most recent date and time that the resource gateway was updated, in ISO-8601 format.

Type: Timestamp

Required: No

name

The name of the resource gateway.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: (?!rgw-)(?![-])(?!.*[-]\$)(?!.*[-]{2})[a-z0-9-]+

Required: No

securityGroupIds

The IDs of the security groups applied to the resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Pattern: sg-((([0-9a-z]{8}))|([0-9a-z]{17})))

Required: No

status

The name of the resource gateway.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | UPDATE_IN_PROGRESS |
DELETE_IN_PROGRESS | CREATE_FAILED | UPDATE_FAILED | DELETE_FAILED

Required: No

subnetIds

The IDs of the VPC subnets for the resource gateway.

Type: Array of strings

Length Constraints: Minimum length of 5. Maximum length of 200.

Required: No

vpcIdentifier

The ID of the VPC for the resource gateway.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: vpc-(([0-9a-z]{8})|([0-9a-z]{17}))

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleAction

Describes the action for a rule.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

fixedResponse

The fixed response action. The rule returns a custom HTTP response.

Type: [FixedResponseAction](#) object

Required: No

forward

The forward action. Traffic that matches the rule is forwarded to the specified target groups.

Type: [ForwardAction](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleMatch

Describes a rule match.

Contents

Important

This data type is a UNION, so only one of the following members can be specified when used or returned.

httpMatch

The HTTP criteria that a rule must match.

Type: [HttpMatch](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleSummary

Summary information about a listener rule.

Contents

arn

The Amazon Resource Name (ARN) of the rule.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the listener rule was created, in ISO-8601 format.

Type: Timestamp

Required: No

id

The ID of the rule.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 22.

Pattern: `rule-[0-9a-z]{17}`

Required: No

isDefault

Indicates whether this is the default listener rule.

Type: Boolean

Required: No

lastUpdatedAt

The date and time that the listener rule was last updated, in ISO-8601 format.

Type: Timestamp

Required: No

name

The name of the rule.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!rule-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: No

priority

The priority of the rule.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleUpdate

Describes a rule update.

Contents

ruleIdentifier

The ID or ARN of the rule.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((rule-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}$))`

Required: Yes

action

The rule action.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

match

The rule match.

Type: [RuleMatch](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

priority

The rule priority. A listener can't have multiple rules with the same priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleUpdateFailure

Describes a rule update that failed.

Contents

failureCode

The failure code.

Type: String

Required: No

failureMessage

The failure message.

Type: String

Required: No

ruleIdentifier

The ID or ARN of the rule.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `((rule-[0-9a-z]{17})|(^arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}$))`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RuleUpdateSuccess

Describes a successful rule update.

Contents

action

The action for the rule.

Type: [RuleAction](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

arn

The Amazon Resource Name (ARN) of the listener.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}/listener/listener-[0-9a-z]{17}/rule/rule-[0-9a-z]{17}`

Required: No

id

The ID of the listener.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 22.

Pattern: `rule-[0-9a-z]{17}`

Required: No

isDefault

Indicates whether this is the default rule.

Type: Boolean

Required: No

match

The rule match.

Type: [RuleMatch](#) object

Note: This object is a Union. Only one member of this object can be specified or returned.

Required: No

name

The name of the listener.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?!rule-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: No

priority

The rule priority.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 2000.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceNetworkEndpointAssociation

Describes the association between a service network and a VPC endpoint.

Contents

createdAt

The date and time that the association was created, in ISO-8601 format.

Type: Timestamp

Required: No

id

The ID of the association.

Type: String

Required: No

serviceNetworkArn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

Required: No

state

The state of the association.

Type: String

Required: No

vpcEndpointId

The ID of the VPC endpoint associated with the service network.

Type: String

Required: No

vpcEndpointOwnerId

The owner of the VPC endpoint associated with the service network.

Type: String

Required: No

vpcId

The ID of the VPC for the association.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceNetworkResourceAssociationSummary

Summary information about an association between a service network and a resource configuration.

Contents

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 22. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkresourceassociation/snra-[0-9a-f]{17}`

Required: No

createdAt

The date and time that the association was created, in ISO-8601 format.

Type: Timestamp

Required: No

createdBy

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

Required: No

dnsEntry

The DNS entry for the service.

Type: [DnsEntry](#) object

Required: No

failureCode

The failure code.

Type: String

Required: No

id

The ID of the association between the service network and resource configuration.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snra-[0-9a-f]{17}`

Required: No

isManagedAssociation

Specifies whether the association is managed by Amazon.

Type: Boolean

Required: No

privateDnsEntry

The private DNS entry for the service.

Type: [DnsEntry](#) object

Required: No

resourceConfigurationArn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9f\-\-]+:vpc-lattice:[a-zA-Z0-9\-\-]+\:
d{12}:resourceconfiguration/rcfg-[0-9a-z]{17}`

Required: No

resourceConfigurationId

The ID of the resource configuration associated with the service network.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `rcfg-[0-9a-z]{17}`

Required: No

resourceConfigurationName

The name of the resource configuration associated with the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!rcfg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: No

serviceNetworkArn

The Amazon Resource Name (ARN) of the service network associated with the resource configuration.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 2048.

Required: No

serviceNetworkId

The ID of the service network associated with the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 2048.

Required: No

serviceNetworkName

The name of the service network associated with the resource configuration.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 100.

Required: No

status

The status of the service network's association with the resource configuration. If the deletion fails, try to delete again.

Type: String

Valid Values: CREATE_IN_PROGRESS | ACTIVE | PARTIAL | DELETE_IN_PROGRESS | CREATE_FAILED | DELETE_FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceNetworkServiceAssociationSummary

Summary information about an association between a service network and a service.

Contents

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the association was created, in ISO-8601 format.

Type: Timestamp

Required: No

createdBy

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

Required: No

customDomainName

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Required: No

dnsEntry

The DNS information.

Type: [DnsEntry](#) object

Required: No

id

The ID of the association.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((snsa-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkserviceassociation/snsa-[0-9a-z]{17}))`

Required: No

serviceArn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

Required: No

serviceId

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

Required: No

serviceName

The name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: No

serviceNetworkArn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

Required: No

serviceNetworkId

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

Required: No

serviceNetworkName

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: No

status

The status of the service network's association with the service. If the deletion fails, try to delete again.

Type: String

Valid Values: `CREATE_IN_PROGRESS` | `ACTIVE` | `DELETE_IN_PROGRESS` | `CREATE_FAILED` | `DELETE_FAILED`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceNetworkSummary

Summary information about a service network.

Contents

arn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the service network was created, in ISO-8601 format.

Type: Timestamp

Required: No

id

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

Required: No

lastUpdatedAt

The date and time that the service network was last updated, in ISO-8601 format.

Type: Timestamp

Required: No

name

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: `(?![-])(?!.*[-])((?!.*[-]{2}))[a-z0-9-]+`

Required: No

numberOfAssociatedResourceConfigurations

The number of resource configurations associated with a service network.

Type: Long

Required: No

numberOfAssociatedServices

The number of services associated with the service network.

Type: Long

Required: No

numberOfAssociatedVPCs

The number of VPCs associated with the service network.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

ServiceNetworkVpcAssociationSummary

Summary information about an association between a service network and a VPC.

Contents

arn

The Amazon Resource Name (ARN) of the association.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetworkvpcassociation/snva-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the association was created, in ISO-8601 format.

Type: Timestamp

Required: No

createdBy

The account that created the association.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 12.

Pattern: `[0-9]{12}`

Required: No

id

The ID of the association.

Type: String

Length Constraints: Fixed length of 22.

Pattern: `snva-[0-9a-z]{17}`

Required: No

lastUpdatedAt

The date and time that the association was last updated, in ISO-8601 format.

Type: Timestamp

Required: No

serviceNetworkArn

The Amazon Resource Name (ARN) of the service network.

Type: String

Length Constraints: Minimum length of 32. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:servicenetwork/sn-[0-9a-z]{17}`

Required: No

serviceNetworkId

The ID of the service network.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `sn-[0-9a-z]{17}`

Required: No

serviceNetworkName

The name of the service network.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 63.

Pattern: (?![-])(?!.*[-]\$)(?!.*[-]{2})[a-z0-9-]+

Required: No

status

The status.

Type: String

Valid Values: CREATE_IN_PROGRESS | ACTIVE | UPDATE_IN_PROGRESS | DELETE_IN_PROGRESS | CREATE_FAILED | DELETE_FAILED | UPDATE_FAILED

Required: No

vpclId

The ID of the VPC.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: vpc-(([0-9a-z]{8})|([0-9a-z]{17}))

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ServiceSummary

Summary information about a service.

Contents

arn

The Amazon Resource Name (ARN) of the service.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the service was created, in ISO-8601 format.

Type: Timestamp

Required: No

customDomainName

The custom domain name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 255.

Required: No

dnsEntry

The DNS information.

Type: [DnsEntry](#) object

Required: No

id

The ID of the service.

Type: String

Length Constraints: Fixed length of 21.

Pattern: `svc-[0-9a-z]{17}`

Required: No

lastUpdatedAt

The date and time that the service was last updated, in ISO-8601 format.

Type: Timestamp

Required: No

name

The name of the service.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 40.

Pattern: `(?!svc-)(?![-])(?!.*[-])((?!.*[-]{2})[a-z0-9-])+`

Required: No

status

The status.

Type: String

Valid Values: ACTIVE | CREATE_IN_PROGRESS | DELETE_IN_PROGRESS |
CREATE_FAILED | DELETE_FAILED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SharingConfig

Specifies if the service network should be enabled for sharing.

Contents

enabled

Specifies if the service network is enabled for sharing.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Target

Describes a target.

Contents

id

The ID of the target. If the target group type is `INSTANCE`, this is an instance ID. If the target group type is `IP`, this is an IP address. If the target group type is `LAMBDA`, this is the ARN of a Lambda function. If the target group type is `ALB`, this is the ARN of an Application Load Balancer.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 200.

Required: Yes

port

The port on which the target is listening. For HTTP, the default is 80. For HTTPS, the default is 443.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetFailure

Describes a target failure.

Contents

failureCode

The failure code.

Type: String

Required: No

failureMessage

The failure message.

Type: String

Required: No

id

The ID of the target. If the target group type is `INSTANCE`, this is an instance ID. If the target group type is `IP`, this is an IP address. If the target group type is `LAMBDA`, this is the ARN of a Lambda function. If the target group type is `ALB`, this is the ARN of an Application Load Balancer.

Type: String

Required: No

port

The port on which the target is listening. This parameter doesn't apply if the target is a Lambda function.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetGroupConfig

Describes the configuration of a target group.

For more information, see [Target groups](#) in the *Amazon VPC Lattice User Guide*.

Contents

healthCheck

The health check configuration. Not supported if the target group type is LAMBDA or ALB.

Type: [HealthCheckConfig](#) object

Required: No

ipAddressType

The type of IP address used for the target group. Supported only if the target group type is IP. The default is IPV4.

Type: String

Valid Values: IPV4 | IPV6

Required: No

lambdaEventStructureVersion

The version of the event structure that your Lambda function receives. Supported only if the target group type is LAMBDA. The default is V1.

Type: String

Valid Values: V1 | V2

Required: No

port

The port on which the targets are listening. For HTTP, the default is 80. For HTTPS, the default is 443. Not supported if the target group type is LAMBDA.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

protocol

The protocol to use for routing traffic to the targets. The default is the protocol of the target group. Not supported if the target group type is LAMBDA.

Type: String

Valid Values: HTTP | HTTPS | TCP

Required: No

protocolVersion

The protocol version. The default is HTTP1. Not supported if the target group type is LAMBDA.

Type: String

Valid Values: HTTP1 | HTTP2 | GRPC

Required: No

vpIdentifier

The ID of the VPC. Not supported if the target group type is LAMBDA.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: vpc-(([0-9a-z]{8})|([0-9a-z]{17}))

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

TargetGroupSummary

Summary information about a target group.

For more information, see [Target groups](#) in the *Amazon VPC Lattice User Guide*.

Contents

arn

The ARN (Amazon Resource Name) of the target group.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:targetgroup/tg-[0-9a-z]{17}`

Required: No

createdAt

The date and time that the target group was created, in ISO-8601 format.

Type: Timestamp

Required: No

id

The ID of the target group.

Type: String

Length Constraints: Fixed length of 20.

Pattern: `tg-[0-9a-z]{17}`

Required: No

ipAddressType

The type of IP address used for the target group. The possible values are IPV4 and IPV6. This is an optional parameter. If not specified, the default is IPV4.

Type: String

Valid Values: IPV4 | IPV6

Required: No

lambdaEventStructureVersion

The version of the event structure that your Lambda function receives. Supported only if the target group type is LAMBDA.

Type: String

Valid Values: V1 | V2

Required: No

lastUpdatedAt

The date and time that the target group was last updated, in ISO-8601 format.

Type: Timestamp

Required: No

name

The name of the target group.

Type: String

Length Constraints: Minimum length of 3. Maximum length of 128.

Pattern: `(?!tg-)(?![-])(?!.*[-]$)(?!.*[-]{2})[a-z0-9-]+`

Required: No

port

The port of the target group.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

protocol

The protocol of the target group.

Type: String

Valid Values: HTTP | HTTPS | TCP

Required: No

serviceArns

The Amazon Resource Names (ARNs) of the service.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+]:\d{12}:service/svc-[0-9a-z]{17}`

Required: No

status

The status.

Type: String

Valid Values: CREATE_IN_PROGRESS | ACTIVE | DELETE_IN_PROGRESS | CREATE_FAILED | DELETE_FAILED

Required: No

type

The target group type.

Type: String

Valid Values: IP | LAMBDA | INSTANCE | ALB

Required: No

vpclIdentifier

The ID of the VPC of the target group.

Type: String

Length Constraints: Minimum length of 5. Maximum length of 50.

Pattern: `vpc-(([0-9a-z]{8})|([0-9a-z]{17}))`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TargetSummary

Summary information about a target.

Contents

id

The ID of the target. If the target group type is `INSTANCE`, this is an instance ID. If the target group type is `IP`, this is an IP address. If the target group type is `LAMBDA`, this is the ARN of a Lambda function. If the target type is `ALB`, this is the ARN of an Application Load Balancer.

Type: String

Required: No

port

The port on which the target is listening.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 65535.

Required: No

reasonCode

The code for why the target status is what it is.

Type: String

Required: No

status

The status of the target.

- **DRAINING**: The target is being deregistered. No new connections are sent to this target while current connections are being drained. The default draining time is 5 minutes.
- **UNAVAILABLE**: Health checks are unavailable for the target group.
- **HEALTHY**: The target is healthy.
- **UNHEALTHY**: The target is unhealthy.

- **INITIAL:** Initial health checks on the target are being performed.
- **UNUSED:** Target group is not used in a service.

Type: String

Valid Values: DRAINING | UNAVAILABLE | HEALTHY | UNHEALTHY | INITIAL |
UNUSED

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Describes a validation failure.

Contents

message

Additional information about why the validation failed.

Type: String

Required: Yes

name

The name of the validation exception.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

WeightedTargetGroup

Describes the weight of a target group.

Contents

targetGroupIdentifier

The ID or ARN of the target group.

Type: String

Length Constraints: Minimum length of 17. Maximum length of 2048.

Pattern: `((tg-[0-9a-z]{17})|(arn:[a-z0-9\-\+]:vpc-lattice:[a-zA-Z0-9\-\+:\d{12}:targetgroup/tg-[0-9a-z]{17})))`

Required: Yes

weight

Only required if you specify multiple target groups for a forward action. The weight determines how requests are distributed to the target group. For example, if you specify two target groups, each with a weight of 10, each target group receives half the requests. If you specify two target groups, one with a weight of 10 and the other with a weight of 20, the target group with a weight of 20 receives twice as many requests as the other target group. If there's only one target group specified, then the default value is 100.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 999.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400