



API Reference

WorkSpacesWeb



API Version 2020-07-08

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

WorkSpacesWeb: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Actions	2
AssociateBrowserSettings	5
Request Syntax	5
URI Request Parameters	5
Request Body	5
Response Syntax	5
Response Elements	6
Errors	6
See Also	7
AssociateIpAccessSettings	9
Request Syntax	9
URI Request Parameters	9
Request Body	9
Response Syntax	9
Response Elements	10
Errors	10
See Also	11
AssociateNetworkSettings	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	13
Response Elements	14
Errors	14
See Also	15
AssociateTrustStore	17
Request Syntax	17
URI Request Parameters	17
Request Body	17
Response Syntax	17
Response Elements	18
Errors	18
See Also	19

AssociateUserAccessLoggingSettings	20
Request Syntax	20
URI Request Parameters	20
Request Body	20
Response Syntax	20
Response Elements	21
Errors	21
See Also	22
AssociateUserSettings	24
Request Syntax	24
URI Request Parameters	24
Request Body	24
Response Syntax	24
Response Elements	25
Errors	25
See Also	26
CreateBrowserSettings	28
Request Syntax	28
URI Request Parameters	28
Request Body	28
Response Syntax	30
Response Elements	30
Errors	30
See Also	31
CreateIdentityProvider	33
Request Syntax	33
URI Request Parameters	33
Request Body	33
Response Syntax	36
Response Elements	36
Errors	36
See Also	37
CreateIapAccessSettings	39
Request Syntax	39
URI Request Parameters	39
Request Body	39

Response Syntax	41
Response Elements	42
Errors	42
See Also	43
CreateNetworkSettings	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	46
Response Elements	46
Errors	46
See Also	47
CreatePortal	49
Request Syntax	49
URI Request Parameters	49
Request Body	49
Response Syntax	51
Response Elements	51
Errors	52
See Also	53
CreateTrustStore	54
Request Syntax	54
URI Request Parameters	54
Request Body	54
Response Syntax	55
Response Elements	55
Errors	56
See Also	57
CreateUserAccessLoggingSettings	58
Request Syntax	58
URI Request Parameters	58
Request Body	58
Response Syntax	59
Response Elements	59
Errors	60
See Also	61

CreateUserSettings	62
Request Syntax	62
URI Request Parameters	63
Request Body	63
Response Syntax	66
Response Elements	66
Errors	66
See Also	67
DeleteBrowserSettings	69
Request Syntax	69
URI Request Parameters	69
Request Body	69
Response Syntax	69
Response Elements	69
Errors	69
See Also	70
DeleteIdentityProvider	72
Request Syntax	72
URI Request Parameters	72
Request Body	72
Response Syntax	72
Response Elements	72
Errors	72
See Also	73
DeleteTpAccessSettings	75
Request Syntax	75
URI Request Parameters	75
Request Body	75
Response Syntax	75
Response Elements	75
Errors	75
See Also	76
DeleteNetworkSettings	78
Request Syntax	78
URI Request Parameters	78
Request Body	78

Response Syntax	78
Response Elements	78
Errors	78
See Also	79
DeletePortal	81
Request Syntax	81
URI Request Parameters	81
Request Body	81
Response Syntax	81
Response Elements	81
Errors	81
See Also	82
DeleteTrustStore	84
Request Syntax	84
URI Request Parameters	84
Request Body	84
Response Syntax	84
Response Elements	84
Errors	84
See Also	85
DeleteUserAccessLoggingSettings	87
Request Syntax	87
URI Request Parameters	87
Request Body	87
Response Syntax	87
Response Elements	87
Errors	87
See Also	88
DeleteUserSettings	90
Request Syntax	90
URI Request Parameters	90
Request Body	90
Response Syntax	90
Response Elements	90
Errors	90
See Also	91

DisassociateBrowserSettings	93
Request Syntax	93
URI Request Parameters	93
Request Body	93
Response Syntax	93
Response Elements	93
Errors	93
See Also	94
DisassociateIpAccessSettings	96
Request Syntax	96
URI Request Parameters	96
Request Body	96
Response Syntax	96
Response Elements	96
Errors	96
See Also	97
DisassociateNetworkSettings	99
Request Syntax	99
URI Request Parameters	99
Request Body	99
Response Syntax	99
Response Elements	99
Errors	99
See Also	100
DisassociateTrustStore	102
Request Syntax	102
URI Request Parameters	102
Request Body	102
Response Syntax	102
Response Elements	102
Errors	102
See Also	103
DisassociateUserAccessLoggingSettings	105
Request Syntax	105
URI Request Parameters	105
Request Body	105

Response Syntax	105
Response Elements	105
Errors	105
See Also	106
DisassociateUserSettings	108
Request Syntax	108
URI Request Parameters	108
Request Body	108
Response Syntax	108
Response Elements	108
Errors	108
See Also	109
GetBrowserSettings	111
Request Syntax	111
URI Request Parameters	111
Request Body	111
Response Syntax	111
Response Elements	112
Errors	112
See Also	113
GetIdentityProvider	114
Request Syntax	114
URI Request Parameters	114
Request Body	114
Response Syntax	114
Response Elements	115
Errors	115
See Also	116
GetIpAccessSettings	117
Request Syntax	117
URI Request Parameters	117
Request Body	117
Response Syntax	117
Response Elements	118
Errors	118
See Also	119

GetNetworkSettings	120
Request Syntax	120
URI Request Parameters	120
Request Body	120
Response Syntax	120
Response Elements	121
Errors	121
See Also	122
GetPortal	123
Request Syntax	123
URI Request Parameters	123
Request Body	123
Response Syntax	123
Response Elements	124
Errors	124
See Also	125
GetPortalServiceProviderMetadata	126
Request Syntax	126
URI Request Parameters	126
Request Body	126
Response Syntax	126
Response Elements	126
Errors	127
See Also	128
GetTrustStore	129
Request Syntax	129
URI Request Parameters	129
Request Body	129
Response Syntax	129
Response Elements	130
Errors	130
See Also	131
GetTrustStoreCertificate	132
Request Syntax	132
URI Request Parameters	132
Request Body	132

Response Syntax	132
Response Elements	133
Errors	133
See Also	134
GetUserAccessLoggingSettings	135
Request Syntax	135
URI Request Parameters	135
Request Body	135
Response Syntax	135
Response Elements	136
Errors	136
See Also	137
GetUserSettings	138
Request Syntax	138
URI Request Parameters	138
Request Body	138
Response Syntax	138
Response Elements	139
Errors	139
See Also	140
ListBrowserSettings	141
Request Syntax	141
URI Request Parameters	141
Request Body	141
Response Syntax	141
Response Elements	142
Errors	142
See Also	143
ListIdentityProviders	144
Request Syntax	144
URI Request Parameters	144
Request Body	144
Response Syntax	145
Response Elements	145
Errors	145
See Also	146

ListIpAccessSettings	147
Request Syntax	147
URI Request Parameters	147
Request Body	147
Response Syntax	147
Response Elements	148
Errors	148
See Also	149
ListNetworkSettings	150
Request Syntax	150
URI Request Parameters	150
Request Body	150
Response Syntax	150
Response Elements	151
Errors	151
See Also	152
ListPortals	153
Request Syntax	153
URI Request Parameters	153
Request Body	153
Response Syntax	153
Response Elements	154
Errors	154
See Also	155
ListTagsForResource	156
Request Syntax	156
URI Request Parameters	156
Request Body	156
Response Syntax	156
Response Elements	157
Errors	157
See Also	158
ListTrustStoreCertificates	159
Request Syntax	159
URI Request Parameters	159
Request Body	159

Response Syntax	160
Response Elements	160
Errors	161
See Also	161
ListTrustStores	163
Request Syntax	163
URI Request Parameters	163
Request Body	163
Response Syntax	163
Response Elements	164
Errors	164
See Also	165
ListUserAccessLoggingSettings	166
Request Syntax	166
URI Request Parameters	166
Request Body	166
Response Syntax	166
Response Elements	167
Errors	167
See Also	168
ListUserSettings	169
Request Syntax	169
URI Request Parameters	169
Request Body	169
Response Syntax	169
Response Elements	170
Errors	171
See Also	171
TagResource	173
Request Syntax	173
URI Request Parameters	173
Request Body	173
Response Syntax	174
Response Elements	174
Errors	174
See Also	175

UntagResource	176
Request Syntax	176
URI Request Parameters	176
Request Body	176
Response Syntax	176
Response Elements	177
Errors	177
See Also	177
UpdateBrowserSettings	179
Request Syntax	179
URI Request Parameters	179
Request Body	179
Response Syntax	180
Response Elements	180
Errors	181
See Also	181
UpdateIdentityProvider	183
Request Syntax	183
URI Request Parameters	183
Request Body	183
Response Syntax	186
Response Elements	186
Errors	186
See Also	187
UpdateIpAccessSettings	188
Request Syntax	188
URI Request Parameters	188
Request Body	188
Response Syntax	190
Response Elements	190
Errors	190
See Also	191
UpdateNetworkSettings	193
Request Syntax	193
URI Request Parameters	193
Request Body	193

Response Syntax	195
Response Elements	195
Errors	195
See Also	196
UpdatePortal	197
Request Syntax	197
URI Request Parameters	197
Request Body	197
Response Syntax	198
Response Elements	199
Errors	199
See Also	200
UpdateTrustStore	201
Request Syntax	201
URI Request Parameters	201
Request Body	201
Response Syntax	202
Response Elements	202
Errors	203
See Also	204
UpdateUserAccessLoggingSettings	205
Request Syntax	205
URI Request Parameters	205
Request Body	205
Response Syntax	206
Response Elements	206
Errors	207
See Also	207
UpdateUserSettings	209
Request Syntax	209
URI Request Parameters	209
Request Body	210
Response Syntax	212
Response Elements	213
Errors	213
See Also	214

Data Types	215
BrowserSettings	217
Contents	217
See Also	218
BrowserSettingsSummary	219
Contents	219
See Also	219
Certificate	220
Contents	220
See Also	221
CertificateSummary	222
Contents	222
See Also	223
CookieSpecification	224
Contents	224
See Also	224
CookieSynchronizationConfiguration	226
Contents	226
See Also	226
IdentityProvider	227
Contents	227
See Also	229
IdentityProviderSummary	230
Contents	230
See Also	231
IpAccessSettings	232
Contents	232
See Also	233
IpAccessSettingsSummary	234
Contents	234
See Also	235
IpRule	236
Contents	236
See Also	236
NetworkSettings	237
Contents	237

See Also	238
NetworkSettingsSummary	239
Contents	239
See Also	239
Portal	241
Contents	241
See Also	245
PortalSummary	246
Contents	246
See Also	249
Tag	251
Contents	251
See Also	251
TrustStore	252
Contents	252
See Also	252
TrustStoreSummary	254
Contents	254
See Also	254
UserAccessLoggingSettings	255
Contents	255
See Also	256
UserAccessLoggingSettingsSummary	257
Contents	257
See Also	257
UserSettings	259
Contents	259
See Also	261
UserSettingsSummary	262
Contents	262
See Also	264
ValidationExceptionField	265
Contents	265
See Also	265
Common Parameters	266
Common Errors	269

Welcome

WorkSpaces Web is a low cost, fully managed WorkSpace built specifically to facilitate secure, web-based workloads. WorkSpaces Web makes it easy for customers to safely provide their employees with access to internal websites and SaaS web applications without the administrative burden of appliances or specialized client software. WorkSpaces Web provides simple policy tools tailored for user interactions, while offloading common tasks like capacity management, scaling, and maintaining browser images.

This document was last published on March 20, 2024.

Actions

The following actions are supported:

- [AssociateBrowserSettings](#)
- [AssociateIpAccessSettings](#)
- [AssociateNetworkSettings](#)
- [AssociateTrustStore](#)
- [AssociateUserAccessLoggingSettings](#)
- [AssociateUserSettings](#)
- [CreateBrowserSettings](#)
- [CreateIdentityProvider](#)
- [CreateIpAccessSettings](#)
- [CreateNetworkSettings](#)
- [CreatePortal](#)
- [CreateTrustStore](#)
- [CreateUserAccessLoggingSettings](#)
- [CreateUserSettings](#)
- [DeleteBrowserSettings](#)
- [DeleteIdentityProvider](#)
- [DeleteIpAccessSettings](#)
- [DeleteNetworkSettings](#)
- [DeletePortal](#)
- [DeleteTrustStore](#)
- [DeleteUserAccessLoggingSettings](#)
- [DeleteUserSettings](#)
- [DisassociateBrowserSettings](#)
- [DisassociateIpAccessSettings](#)
- [DisassociateNetworkSettings](#)
- [DisassociateTrustStore](#)
- [DisassociateUserAccessLoggingSettings](#)

- [DisassociateUserSettings](#)
- [GetBrowserSettings](#)
- [GetIdentityProvider](#)
- [GetIpAccessSettings](#)
- [GetNetworkSettings](#)
- [GetPortal](#)
- [GetPortalServiceProviderMetadata](#)
- [GetTrustStore](#)
- [GetTrustStoreCertificate](#)
- [GetUserAccessLoggingSettings](#)
- [GetUserSettings](#)
- [ListBrowserSettings](#)
- [ListIdentityProviders](#)
- [ListIpAccessSettings](#)
- [ListNetworkSettings](#)
- [ListPortals](#)
- [ListTagsForResource](#)
- [ListTrustStoreCertificates](#)
- [ListTrustStores](#)
- [ListUserAccessLoggingSettings](#)
- [ListUserSettings](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateBrowserSettings](#)
- [UpdateIdentityProvider](#)
- [UpdateIpAccessSettings](#)
- [UpdateNetworkSettings](#)
- [UpdatePortal](#)
- [UpdateTrustStore](#)
- [UpdateUserAccessLoggingSettings](#)

- [UpdateUserSettings](#)

AssociateBrowserSettings

Associates a browser settings resource with a web portal.

Request Syntax

```
PUT /portals/portalArn/browserSettings?browserSettingsArn=browserSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[browserSettingsArn](#)

The ARN of the browser settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

[portalArn](#)

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "browserSettingsArnportalArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[**browserSettingsArn**](#)

The ARN of the browser settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

[**portalArn**](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[**AccessDeniedException**](#)

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateIpAccessSettings

Associates an IP access settings resource with a web portal.

Request Syntax

```
PUT /portals/portalArn/ipAccessSettings?ipAccessSettingsArn=ipAccessSettingsArn
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ipAccessSettingsArn

The ARN of the IP access settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "ipAccessSettingsArn": "string",
  "portalArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ipAccessSettingsArn](#)

The ARN of the IP access settings resource.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateNetworkSettings

Associates a network settings resource with a web portal.

Request Syntax

```
PUT /portals/portalArn/networkSettings?networkSettingsArn=networkSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

networkSettingsArn

The ARN of the network settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
    "networkSettingsArnportalArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[networkSettingsArn](#)

The ARN of the network settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateTrustStore

Associates a trust store with a web portal.

Request Syntax

```
PUT /portals/portalArn/trustStores?trustStoreArn=trustStoreArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

trustStoreArn

The ARN of the trust store.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json
```

```
{  
  "portalArn": "string",  
  "trustStoreArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

[trustStoreArn](#)

The ARN of the trust store.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateUserAccessLoggingSettings

Associates a user access logging settings resource with a web portal.

Request Syntax

```
PUT /portals/portalArn/userAccessLoggingSettings?  
userAccessLoggingSettingsArn=userAccessLoggingSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

userAccessLoggingSettingsArn

The ARN of the user access logging settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "portalArnuserAccessLoggingSettingsArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

[userAccessLoggingSettingsArn](#)

The ARN of the user access logging settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

AssociateUserSettings

Associates a user settings resource with a web portal.

Request Syntax

```
PUT /portals/portalArn/userSettings?userSettingsArn=userSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

userSettingsArn

The ARN of the user settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

```
Content-type: application/json

{
  "portalArnuserSettingsArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

[userSettingsArn](#)

The ARN of the user settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateBrowserSettings

Creates a browser settings resource that can be associated with a web portal. Once associated with a web portal, browser settings control how the browser will behave once a user starts a streaming session for the web portal.

Request Syntax

```
POST /browserSettings HTTP/1.1
Content-type: application/json

{
  "additionalEncryptionContextbrowserPolicyclientTokencustomerManagedKeytagsKeyValue
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

additionalEncryptionContext

Additional encryption context of the browser settings.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 131072.

Key Pattern: `^[\s\S]*$`

Value Length Constraints: Minimum length of 0. Maximum length of 131072.

Value Pattern: `^[\s\S]*$`

Required: No

browserPolicy

A JSON string containing Chrome Enterprise policies that will be applied to all streaming sessions.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 131072.

Pattern: `\{[\S\s]*\}\s*`

Required: Yes

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

customerManagedKey

The custom managed key of the browser settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:[\w+=\/, .@-]+:kms:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:key\/[a-zA-Z0-9\-\-]+\+$`

Required: No

tags

The tags to add to the browser settings resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "browserSettingsArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[browserSettingsArn](#)

The ARN of the browser settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateIdentityProvider

Creates an identity provider resource that is then associated with a web portal.

Request Syntax

```
POST /identityProviders HTTP/1.1
Content-type: application/json

{
  "clientTokenidentityProviderDetailsidentityProviderNameidentityProviderTypeportalArn
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[identityProviderDetails](#)

The identity provider details. The following list describes the provider detail keys for each identity provider type.

- For Google and Login with Amazon:

- client_id
- client_secret
- authorize_scopes

- For Facebook:

- client_id
- client_secret
- authorize_scopes
- api_version

- For Sign in with Apple:

- client_id
- team_id
- key_id
- private_key
- authorize_scopes

- For OIDC providers:

- client_id
- client_secret
- attributes_request_method
- oidc_issuer
- authorize_scopes
- authorize_url *if not available from discovery URL specified by oidc_issuer key*
- token_url *if not available from discovery URL specified by oidc_issuer key*
- attributes_url *if not available from discovery URL specified by oidc_issuer key*
- jwks_uri *if not available from discovery URL specified by oidc_issuer key*

- For SAML providers:

- `IDPSignout` (boolean) *optional*
- `IDPInit` (boolean) *optional*
- `RequestSigningAlgorithm` (string) *optional* - Only accepts `rsa-sha256`
- `EncryptedResponses` (boolean) *optional*

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 131072.

Key Pattern: `^[\s\S]*$`

Value Length Constraints: Minimum length of 0. Maximum length of 131072.

Value Pattern: `^[\s\S]*$`

Required: Yes

[identityProviderName](#)

The identity provider name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[^_][\p{L}\p{M}\p{S}\p{N}\p{P}][^_]+$`

Required: Yes

[identityProviderType](#)

The identity provider type.

Type: String

Valid Values: SAML | Facebook | Google | LoginWithAmazon | SignInWithApple | OIDC

Required: Yes

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/,.@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "identityProviderArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[**identityProviderArn**](#)

The ARN of the identity provider.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/,.@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36}){2,}\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

[**AccessDeniedException**](#)

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateIpAccessSettings

Creates an IP access settings resource that can be associated with a web portal.

Request Syntax

```
POST /ipAccessSettings HTTP/1.1
Content-type: application/json

{
  "additionalEncryptionContextclientTokencustomerManagedKeydescriptiondisplayNameipRulesdescriptionipRangetagsKeyValue
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

additionalEncryptionContext

Additional encryption context of the IP access settings.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 131072.

Key Pattern: `^[\s\S]*$`

Value Length Constraints: Minimum length of 0. Maximum length of 131072.

Value Pattern: `^[\s\S]*$`

Required: No

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

customerManagedKey

The custom managed key of the IP access settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: `^arn:[\w+=\/, .@-]+:kms:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:key\/[a-zA-Z0-9\-\-]+$`

Required: No

description

The description of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^ .+\$

Required: No

displayName

The display name of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ .+\$

Required: No

ipRules

The IP rules of the IP access settings.

Type: Array of [IpRule](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

tags

The tags to add to the browser settings resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ipAccessSettingsArn": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ipAccessSettingsArn](#)

The ARN of the IP access settings resource.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateNetworkSettings

Creates a network settings resource that can be associated with a web portal. Once associated with a web portal, network settings define how streaming instances will connect with your specified VPC.

Request Syntax

```
POST /networkSettings HTTP/1.1
Content-type: application/json

{
  "clientTokensecurityGroupIdssubnetIdstagsKeyValuevpcId
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

securityGroupIds

One or more security groups used to control access from streaming instances to your VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[\w+\-]+\$

Required: Yes

subnetIds

The subnets in which network interfaces are created to connect streaming instances to your VPC. At least two of these subnets must be in different availability zones.

Type: Array of strings

Array Members: Minimum number of 2 items. Maximum number of 3 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^subnet-([0-9a-f]{8}|[0-9a-f]{17})\$

Required: Yes

tags

The tags to add to the network settings resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

vpcId

The VPC that streaming instances will connect to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^vpc-[0-9a-z]*\$

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "networkSettingsArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

networkSettingsArn

The ARN of the network settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreatePortal

Creates a web portal.

Request Syntax

```
POST /portals HTTP/1.1
Content-type: application/json

{
  "additionalEncryptionContextauthenticationTypeclientTokencustomerManagedKeydisplayNametagsKeyValue
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

additionalEncryptionContext

The additional encryption context of the portal.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 131072.

Key Pattern: ^[\s\S]*\$

Value Length Constraints: Minimum length of 0. Maximum length of 131072.

Value Pattern: ^[\s\S]*\$

Required: No

[authenticationType](#)

The type of authentication integration points used when signing into the web portal. Defaults to Standard.

Standard web portals are authenticated directly through your identity provider. You need to call `CreateIdentityProvider` to integrate your identity provider with your web portal. User and group access to your web portal is controlled through your identity provider.

IAM Identity Center web portals are authenticated through AWS IAM Identity Center. They provide additional features, such as IdP-initiated authentication. Identity sources (including external identity provider integration), plus user and group access to your web portal, can be configured in the IAM Identity Center.

Type: String

Valid Values: Standard | IAM_Identity_Center

Required: No

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[customerManagedKey](#)

The customer managed key of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:kms:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:key\/[a-zA-Z0-9\-\-]+\\$

Required: No

[displayName](#)

The name of the web portal. This is not visible to users who log into the web portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ .+\\$

Required: No

[tags](#)

The tags to add to the web portal. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "portalArn": "string",
  "portalEndpoint": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-\-]\{36\}\)+\$

[portalEndpoint](#)

The endpoint URL of the web portal that users access in order to start streaming sessions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^[a-zA-Z0-9]?((?!-)([A-Za-z0-9-]*[A-Za-z0-9])\.\.)+[a-zA-Z0-9]+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateTrustStore

Creates a trust store that can be associated with a web portal. A trust store contains certificate authority (CA) certificates. Once associated with a web portal, the browser in a streaming session will recognize certificates that have been issued using any of the CAs in the trust store. If your organization has internal websites that use certificates issued by private CAs, you should add the private CA certificate to the trust store.

Request Syntax

```
POST /trustStores HTTP/1.1
Content-type: application/json

{
  "certificateListblob ],
  "clientTokenstring",
  "tagsKeystring",
      "Valuestring"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[certificateList](#)

A list of CA certificates to be added to the trust store.

Type: Array of Base64-encoded binary data objects

Required: Yes

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

tags

The tags to add to the trust store. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "trustStoreArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

trustStoreArn

The ARN of the trust store.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-zA-Z0-9\-_]{36}\)+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUserAccessLoggingSettings

Creates a user access logging settings resource that can be associated with a web portal.

Request Syntax

```
POST /userAccessLoggingSettings HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "kinesisStreamArn": "string",
  "tags": [
    {
      "Key": "string",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

kinesisStreamArn

The ARN of the Kinesis stream.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:[\w+=/, .@-]+:kinesis:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:stream/.
+

Required: Yes

tags

The tags to add to the user settings resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "userAccessLoggingSettingsArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[userAccessLoggingSettingsArn](#)

The ARN of the user access logging settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-zA-Z0-9\-_]{36}\)+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateUserSettings

Creates a user settings resource that can be associated with a web portal. Once associated with a web portal, user settings control how users can transfer data between a streaming session and their local devices.

Request Syntax

```
POST /userSettings HTTP/1.1
Content-type: application/json

{
    "additionalEncryptionContextclientTokencookieSynchronizationConfigurationallowlistdomainnamepathblocklistdomainnamepathcopyAllowedcustomerManagedKeydisconnectTimeoutInMinutesdownloadAllowedidleDisconnectTimeoutInMinutespasteAllowedprintAllowedtagsKey
```

```
        "Value": "string"
    }
],
"uploadAllowed": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

[additionalEncryptionContext](#)

The additional encryption context of the user settings.

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 131072.

Key Pattern: ^[\s\S]*\$

Value Length Constraints: Minimum length of 0. Maximum length of 131072.

Value Pattern: ^[\s\S]*\$

Required: No

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[cookieSynchronizationConfiguration](#)

The configuration that specifies which cookies should be synchronized from the end user's local browser to the remote browser.

Type: [CookieSynchronizationConfiguration](#) object

Required: No

[copyAllowed](#)

Specifies whether the user can copy text from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: Yes

[customerManagedKey](#)

The customer managed key used to encrypt sensitive information in the user settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:kms:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:key\/[a-zA-Z0-9-]+\\$

Required: No

[disconnectTimeoutInMinutes](#)

The amount of time that a streaming session remains active after users disconnect.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 600.

Required: No

[downloadAllowed](#)

Specifies whether the user can download files from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: Yes

idleDisconnectTimeoutInMinutes

The amount of time that users can be idle (inactive) before they are disconnected from their streaming session and the disconnect timeout interval begins.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 60.

Required: No

pasteAllowed

Specifies whether the user can paste text from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: Yes

printAllowed

Specifies whether the user can print to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: Yes

tags

The tags to add to the user settings resource. A tag is a key-value pair.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: No

uploadAllowed

Specifies whether the user can upload files from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "userSettingsArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[userSettingsArn](#)

The ARN of the user settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteBrowserSettings

Deletes browser settings.

Request Syntax

```
DELETE /browserSettings/browserSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[browserSettingsArn](#)

The ARN of the browser settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteIdentityProvider

Deletes the identity provider.

Request Syntax

```
DELETE /identityProviders/identityProviderArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

identityProviderArn

The ARN of the identity provider.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36}){2,}\\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteIpAccessSettings

Deletes IP access settings.

Request Syntax

```
DELETE /ipAccessSettings/ipAccessSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ipAccessSettingsArn

The ARN of the IP access settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteNetworkSettings

Deletes network settings.

Request Syntax

```
DELETE /networkSettings/networkSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[networkSettingsArn](#)

The ARN of the network settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeletePortal

Deletes a web portal.

Request Syntax

```
DELETE /portals/portalArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteTrustStore

Deletes the trust store.

Request Syntax

```
DELETE /trustStores/trustStoreArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

trustStoreArn

The ARN of the trust store.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteUserAccessLoggingSettings

Deletes user access logging settings.

Request Syntax

```
DELETE /userAccessLoggingSettings/userAccessLoggingSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[userAccessLoggingSettingsArn](#)

The ARN of the user access logging settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteUserSettings

Deletes user settings.

Request Syntax

```
DELETE /userSettings/userSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[userSettingsArn](#)

The ARN of the user settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateBrowserSettings

Disassociates browser settings from a web portal.

Request Syntax

```
DELETE /portals/portalArn/browserSettings HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateIpAccessSettings

Disassociates IP access settings from a web portal.

Request Syntax

```
DELETE /portals/portalArn/ipAccessSettings HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateNetworkSettings

Disassociates network settings from a web portal.

Request Syntax

```
DELETE /portals/portalArn/networkSettings HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateTrustStore

Disassociates a trust store from a web portal.

Request Syntax

```
DELETE /portals/portalArn/trustStores HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateUserAccessLoggingSettings

Disassociates user access logging settings from a web portal.

Request Syntax

```
DELETE /portals/portalArn/userAccessLoggingSettings HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DisassociateUserSettings

Disassociates user settings from a web portal.

Request Syntax

```
DELETE /portals/portalArn/userSettings HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetBrowserSettings

Gets browser settings.

Request Syntax

```
GET /browserSettings/browserSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[browserSettingsArn](#)

The ARN of the browser settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "browserSettings": {
    "associatedPortalArns": [ "string" ],
    "browserPolicy": "string",
    "browserSettingsArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

browserSettings

The browser settings.

Type: [BrowserSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetIdentityProvider

Gets the identity provider.

Request Syntax

```
GET /identityProviders/identityProviderArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

identityProviderArn

The ARN of the identity provider.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\){2,}\\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "identityProvider": {
    "identityProviderArn": "string",
    "identityProviderDetails": {
      "string": "string"
    },
    "identityProviderName": "string",
  }
}
```

```
    "identityProviderType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[identityProvider](#)

The identity provider.

Type: [IdentityProvider](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetIpAccessSettings

Gets the IP access settings.

Request Syntax

```
GET /ipAccessSettings/ipAccessSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ipAccessSettingsArn

The ARN of the IP access settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ipAccessSettings": {
    "associatedPortalArns": [ "string" ],
    "creationDate": number,
    "description": "string",
    "displayName": "string",
    "ipAccessSettingsArn": "string",
    "ipRules": [
```

```
{  
    "description": "string",  
    "ipRange": "string"  
}  
]  
}  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ipAccessSettings](#)

The IP access settings.

Type: [IpAccessSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetNetworkSettings

Gets the network settings.

Request Syntax

```
GET /networkSettings/networkSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

networkSettingsArn

The ARN of the network settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "networkSettingsassociatedPortalArnsstring" ],
    "networkSettingsArnstring",
    "securityGroupIdsstring" ],
    "subnetIdsstring" ],
    "vpcIdstring"
  }
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[networkSettings](#)

The network settings.

Type: [NetworkSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetPortal

Gets the web portal.

Request Syntax

```
GET /portals/portalArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "portalauthenticationTypebrowserSettingsArnbrowserTypecreationDatedisplayNameipAccessSettingsArn
```

```
"networkSettingsArnportalArnportalEndpointportalStatusrendererTypestatusReasontrustStoreArnuserAccessLoggingSettingsArnuserSettingsArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

portal

The web portal.

Type: [Portal](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetPortalServiceProviderMetadata

Gets the service provider metadata.

Request Syntax

```
GET /portalIdp/portalArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "portalArn": "string",
  "serviceProviderSamlMetadata": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[portalArn](#)

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

[serviceProviderSamlMetadata](#)

The service provider SAML metadata.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 204800.

Pattern: ^ . +\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrustStore

Gets the trust store.

Request Syntax

```
GET /trustStores/trustStoreArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

trustStoreArn

The ARN of the trust store.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "trustStore": {
    "associatedPortalArnsstring" ],
    "trustStoreArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[trustStore](#)

The trust store.

Type: [TrustStore](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetTrustStoreCertificate

Gets the trust store certificate.

Request Syntax

```
GET /trustStores/trustStoreArn/certificate?thumbprint=thumbprint HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[thumbprint](#)

The thumbprint of the trust store certificate.

Length Constraints: Fixed length of 64.

Pattern: ^[A-Fa-f0-9]{64}\$

Required: Yes

[trustStoreArn](#)

The ARN of the trust store certificate.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{  
  "certificate": {  
    "body": "blob",  
    "issuer": "string",  
    "notValidAfter": number,  
    "notValidBefore": number,  
    "subject": "string",  
    "thumbprint": "string"  
  },  
  "trustStoreArn": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[certificate](#)

The certificate of the trust store certificate.

Type: [Certificate](#) object

[trustStoreArn](#)

The ARN of the trust store certificate.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetUserAccessLoggingSettings

Gets user access logging settings.

Request Syntax

```
GET /userAccessLoggingSettings/userAccessLoggingSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

userAccessLoggingSettingsArn

The ARN of the user access logging settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "userAccessLoggingSettings": {
    "associatedPortalArns": [ "string" ],
    "kinesisStreamArn": "string",
    "userAccessLoggingSettingsArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[userAccessLoggingSettings](#)

The user access logging settings.

Type: [UserAccessLoggingSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetUserSettings

Gets user settings.

Request Syntax

```
GET /userSettings/userSettingsArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[userSettingsArn](#)

The ARN of the user settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "userSettingsassociatedPortalArnsstring" ],
    "cookieSynchronizationConfigurationallowlistdomainstring",
```

```
        "name": "string",
        "path": "string"
    },
],
"blocklist": [
    {
        "domain": "string",
        "name": "string",
        "path": "string"
    }
]
},
"copyAllowed": "string",
"disconnectTimeoutInMinutes": number,
"downloadAllowed": "string",
"idleDisconnectTimeoutInMinutes": number,
"pasteAllowed": "string",
"printAllowed": "string",
"uploadAllowed": "string",
"userSettingsArn": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[userSettings](#)

The user settings.

Type: [UserSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListBrowserSettings

Retrieves a list of browser settings.

Request Syntax

```
GET /browserSettings?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "browserSettings": [
    {
      "browserSettingsArn": "string"
    }
  ],
}
```

```
    "nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[browserSettings](#)

The browser settings.

Type: Array of [BrowserSettingsSummary](#) objects

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListIdentityProviders

Retrieves a list of identity providers for a specific web portal.

Request Syntax

```
GET /portals/portalArn/identityProviders?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "identityProvidersidentityProviderArnstring",
      "identityProviderNamestring",
      "identityProviderTypestring"
    }
  \\\],
  "nextTokenstring
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[**identityProviders**](#)

The identity providers.

Type: Array of [IdentityProviderSummary](#) objects

[**nextToken**](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListIpAccessSettings

Retrieves a list of IP access settings.

Request Syntax

```
GET /ipAccessSettings?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "ipAccessSettings": [
    {
      "creationDatenumber,
      "descriptionstring",
      "displayNamestring",
```

```
        "ipAccessSettingsArn": "string"
    }
],
"nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ipAccessSettings](#)

The IP access settings.

Type: Array of [IpAccessSettingsSummary](#) objects

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListNetworkSettings

Retrieves a list of network settings.

Request Syntax

```
GET /networkSettings?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "networkSettings": [
        {
            "networkSettingsArnvpcId": "string"
        }
    ]
}
```

```
],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[networkSettings](#)

The network settings.

Type: Array of [NetworkSettingsSummary](#) objects

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListPortals

Retrieves a list or web portals.

Request Syntax

```
GET /portals?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\\$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "nextToken": "string",
    "portals": [
        {
            "authenticationType": "string",
```

```
        "browserSettingsArn": "string",
        "browserType": "string",
        "creationDate": number,
        "displayName": "string",
        "ipAccessSettingsArn": "string",
        "networkSettingsArn": "string",
        "portalArn": "string",
        "portalEndpoint": "string",
        "portalStatus": "string",
        "rendererType": "string",
        "trustStoreArn": "string",
        "userAccessLoggingSettingsArn": "string",
        "userSettingsArn": "string"
    }
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

[portals](#)

The portals in the list.

Type: Array of [PortalSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

Retrieves a list of tags for a resource.

Request Syntax

```
GET /tags/resourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "tags": [
    {
      "KeyValue
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[tags](#)

The tags of the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTrustStoreCertificates

Retrieves a list of trust store certificates.

Request Syntax

```
GET /trustStores/trustStoreArn/certificates?maxResults=maxResults&nextToken=nextToken
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

trustStoreArn

The ARN of the trust store

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "certificateListissuernotValidAfternotValidBeforesubjectthumbprintnextTokentrustStoreArn
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[certificateList](#)

The certificate list.

Type: Array of [CertificateSummary](#) objects

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.>

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

[trustStoreArn](#)

The ARN of the trust store.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]\{36\})+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTrustStores

Retrieves a list of trust stores.

Request Syntax

```
GET /trustStores?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json
```

```
{
  "nextTokentrustStorestrustStoreArn
```

```
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

[trustStores](#)

The trust stores.

Type: Array of [TrustStoreSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListUserAccessLoggingSettings

Retrieves a list of user access logging settings.

Request Syntax

```
GET /userAccessLoggingSettings?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "nextToken": "string",
    "userAccessLoggingSettings": [
        {
            "kinesisStreamArn": "string",
            "userAccessLoggingSettingsArn": "string"
        }
    ]
}
```

```
    }  
]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

[userAccessLoggingSettings](#)

The user access logging settings.

Type: Array of [UserAccessLoggingSettingsSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListUserSettings

Retrieves a list of user settings.

Request Syntax

```
GET /userSettings?maxResults=maxResults&nextToken=nextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

maxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1.

nextToken

The pagination token used to retrieve the next page of results for this operation.

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "nextToken": "string",
    "userSettings": [
        {
            "cookieSynchronizationConfiguration": {
                "allowlist
```

```
        "domain": "string",
        "name": "string",
        "path": "string"
    }
],
"blocklist": [
    {
        "domain": "string",
        "name": "string",
        "path": "string"
    }
]
},
"copyAllowed": "string",
"disconnectTimeoutInMinutes": number,
"downloadAllowed": "string",
"idleDisconnectTimeoutInMinutes": number,
"pasteAllowed": "string",
"printAllowed": "string",
"uploadAllowed": "string",
"userSettingsArn": "string"
}
]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[nextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Pattern: ^\S+\$

[userSettings](#)

The user settings.

Type: Array of [UserSettingsSummary](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

Adds or overwrites one or more tags for the specified resource.

Request Syntax

```
POST /tags/resourceArn HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "tags": [
    {
      "Keystring",
      "Value": "string"
    }
  ]
}
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-zA-Z0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request,

if the original request completes successfully, subsequent retries with the same client token returns the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

tags

The tags of the resource.

Type: Array of [Tag](#) objects

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Required: Yes

Response Syntax

HTTP/1.1 200

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

TooManyTagsException

There are too many tags.

HTTP Status Code: 400

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

Removes one or more tags from the specified resource.

Request Syntax

```
DELETE /tags/resourceArn?tagKeys=tagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

resourceArn

The ARN of the resource.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-.]+:[a-zA-Z0-9\-.]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-.]{36})+\$

Required: Yes

tagKeys

The list of tag keys to remove from the resource.

Array Members: Minimum number of 0 items. Maximum number of 200 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^([\p{L}\p{Z}\p{N}_.:/=+\-@\"]*)\$

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateBrowserSettings

Updates browser settings.

Request Syntax

```
PATCH /browserSettings/browserSettingsArn HTTP/1.1
Content-type: application/json

{
  "browserPolicyclientToken
```

URI Request Parameters

The request uses the following URI parameters.

browserSettingsArn

The ARN of the browser settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

browserPolicy

A JSON string containing Chrome Enterprise policies that will be applied to all streaming sessions.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 131072.

Pattern: \{[\S\s]*\}\s*

Required: No

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token return the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "browserSettings": {
    "associatedPortalArns": [ "string" ],
    "browserPolicy": "string",
    "browserSettingsArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

browserSettings

The browser settings.

Type: [BrowserSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateIdentityProvider

Updates the identity provider.

Request Syntax

```
PATCH /identityProviders/identityProviderArn HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "identityProviderDetails": {
    "string": "string"
  },
  "identityProviderName": "string",
  "identityProviderType": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

identityProviderArn

The ARN of the identity provider.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36}){2,}\\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request,

if the original request completes successfully, subsequent retries with the same client token return the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

identityProviderDetails

The details of the identity provider. The following list describes the provider detail keys for each identity provider type.

- For Google and Login with Amazon:

- `client_id`
- `client_secret`
- `authorize_scopes`

- For Facebook:

- `client_id`
- `client_secret`
- `authorize_scopes`
- `api_version`

- For Sign in with Apple:

- `client_id`
- `team_id`
- `key_id`
- `private_key`
- `authorize_scopes`

- For OIDC providers:

- `client_id`
- `client_secret`
- `attributes_request_method`
- `oidc_issuer`

- `authorize_scopes`
- `authorize_url` if not available from discovery URL specified by `oidc_issuer` key
- `token_url` if not available from discovery URL specified by `oidc_issuer` key
- `attributes_url` if not available from discovery URL specified by `oidc_issuer` key
- `jwks_uri` if not available from discovery URL specified by `oidc_issuer` key
- For SAML providers:
 - `MetadataFile` OR `MetadataURL`
 - `IDPSignout` (boolean) *optional*
 - `IDPInit` (boolean) *optional*
 - `RequestSigningAlgorithm` (string) *optional* - Only accepts `rsa-sha256`
 - `EncryptedResponses` (boolean) *optional*

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 131072.

Key Pattern: `^[\s\S]*$`

Value Length Constraints: Minimum length of 0. Maximum length of 131072.

Value Pattern: `^[\s\S]*$`

Required: No

[identityProviderName](#)

The name of the identity provider.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: `^[^_][\p{L}\p{M}\p{S}\p{N}\p{P}][^_]+$`

Required: No

[identityProviderType](#)

The type of the identity provider.

Type: String

Valid Values: SAML | Facebook | Google | LoginWithAmazon | SignInWithApple | OIDC

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "identityProvider": {
    "identityProviderArnidentityProviderDetails": {
      "string" : "string"
    },
    "identityProviderName": "string",
    "identityProviderType": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

identityProvider

The identity provider.

Type: [IdentityProvider](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateIpAccessSettings

Updates IP access settings.

Request Syntax

```
PATCH /ipAccessSettings/ipAccessSettingsArn HTTP/1.1
Content-type: application/json

{
    "clientTokendescriptiondisplayNameipRulesdescriptionipRange
```

URI Request Parameters

The request uses the following URI parameters.

ipAccessSettingsArn

The ARN of the IP access settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

clientToken

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token return the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

description

The description of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^ . +\$

Required: No

displayName

The display name of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ . +\$

Required: No

ipRules

The updated IP rules of the IP access settings.

Type: Array of [IpRule](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "ipAccessSettings": {
        "associatedPortalArns": [ "string" ],
        "creationDate": number,
        "description": "string",
        "displayName": "string",
        "ipAccessSettingsArn": "string",
        "ipRules": [
            {
                "description": "string",
                "ipRange": "string"
            }
        ]
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[ipAccessSettings](#)

The IP access settings.

Type: [IpAccessSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateNetworkSettings

Updates network settings.

Request Syntax

```
PATCH /networkSettings/networkSettingsArn HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "securityGroupIds": [ "string" ],
  "subnetIds": [ "string" ],
  "vpcId": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[networkSettingsArn](#)

The ARN of the network settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token return the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

securityGroupIds

One or more security groups used to control access from streaming instances to your VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[\w+\-]+\$

Required: No

subnetIds

The subnets in which network interfaces are created to connect streaming instances to your VPC. At least two of these subnets must be in different availability zones.

Type: Array of strings

Array Members: Minimum number of 2 items. Maximum number of 3 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^subnet-([0-9a-f]{8}|[0-9a-f]{17})\$

Required: No

vpcId

The VPC that streaming instances will connect to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^vpc-[0-9a-z]*\$

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
    "networkSettings": {
        "associatedPortalArns": [ "string" ],
        "networkSettingsArn": "string",
        "securityGroupIds": [ "string" ],
        "subnetIds": [ "string" ],
        "vpcId": "string"
    }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[networkSettings](#)

The network settings.

Type: [NetworkSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdatePortal

Updates a web portal.

Request Syntax

```
PUT /portals/portalArn HTTP/1.1
Content-type: application/json

{
  "authenticationType": "string",
  "displayName": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

portalArn

The ARN of the web portal.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

authenticationType

The type of authentication integration points used when signing into the web portal. Defaults to Standard.

Standard web portals are authenticated directly through your identity provider. You need to call `CreateIdentityProvider` to integrate your identity provider with your web portal. User and group access to your web portal is controlled through your identity provider.

IAM Identity Center web portals are authenticated through AWS IAM Identity Center. They provide additional features, such as IdP-initiated authentication. Identity sources (including external identity provider integration), plus user and group access to your web portal, can be configured in the IAM Identity Center.

Type: String

Valid Values: Standard | IAM_Identity_Center

Required: No

displayName

The name of the web portal. This is not visible to users who log into the web portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ . +\$

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "portal": {
    "authenticationType": "string",
    "browserSettingsArn": "string",
    "browserType": "string",
    "creationDate": number,
    "displayName": "string",
    "ipAccessSettingsArn": "string",
    "networkSettingsArn": "string",
    "portalArn": "string",
    "portalEndpoint": "string",
    "portalStatus": "string",
    "rendererType": "string",
    "statusReason": "string",
    "trustStoreArn": "string",
```

```
    "userAccessLoggingSettingsArn": "string",
    "userSettingsArn": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[portal](#)

The web portal.

Type: [Portal](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

ConflictException

There is a conflict.

HTTP Status Code: 409

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateTrustStore

Updates the trust store.

Request Syntax

```
PATCH /trustStores/trustStoreArn HTTP/1.1
Content-type: application/json

{
  "certificatesToAddblob ],
  "certificatesToDeletestring" ],
  "clientTokenstring"
}
```

URI Request Parameters

The request uses the following URI parameters.

trustStoreArn

The ARN of the trust store.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\//, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\//[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

certificatesToAdd

A list of CA certificates to add to the trust store.

Type: Array of Base64-encoded binary data objects

Required: No

[certificatesToDelete](#)

A list of CA certificates to delete from a trust store.

Type: Array of strings

Length Constraints: Fixed length of 64.

Pattern: ^[A-Fa-f0-9]{64}\$

Required: No

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token return the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "trustStoreArn": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[trustStoreArn](#)

The ARN of the trust store.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ServiceQuotaExceededException

The service quota has been exceeded.

HTTP Status Code: 402

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateUserAccessLoggingSettings

Updates the user access logging settings.

Request Syntax

```
PATCH /userAccessLoggingSettings/userAccessLoggingSettingsArn HTTP/1.1
Content-type: application/json

{
  "clientToken": "string",
  "kinesisStreamArn": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

[userAccessLoggingSettingsArn](#)

The ARN of the user access logging settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token return the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

kinesisStreamArn

The ARN of the Kinesis stream.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:[\w+=/, .@-]+:kinesis:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:stream/.
+

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "userAccessLoggingSettings": {
    "associatedPortalArns": [ "string" ],
    "kinesisStreamArn": "string",
    "userAccessLoggingSettingsArn": "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

userAccessLoggingSettings

The user access logging settings.

Type: [UserAccessLoggingSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerException

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateUserSettings

Updates the user settings.

Request Syntax

```
PATCH /userSettings/userSettingsArn HTTP/1.1
Content-type: application/json

{
  "clientTokencookieSynchronizationConfigurationallowlistdomainnamepathblocklistdomainnamepathcopyAlloweddisconnectTimeoutInMinutesdownloadAllowedidleDisconnectTimeoutInMinutespasteAllowedprintAlloweduploadAllowed
```

URI Request Parameters

The request uses the following URI parameters.

[userSettingsArn](#)

The ARN of the user settings.

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]\{36}\)+\$

Required: Yes

Request Body

The request accepts the following data in JSON format.

[clientToken](#)

A unique, case-sensitive identifier that you provide to ensure the idempotency of the request. Idempotency ensures that an API request completes only once. With an idempotent request, if the original request completes successfully, subsequent retries with the same client token return the result from the original successful request.

If you do not specify a client token, one is automatically generated by the AWS SDK.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 512.

Required: No

[cookieSynchronizationConfiguration](#)

The configuration that specifies which cookies should be synchronized from the end user's local browser to the remote browser.

If the allowlist and blocklist are empty, the configuration becomes null.

Type: [CookieSynchronizationConfiguration](#) object

Required: No

[copyAllowed](#)

Specifies whether the user can copy text from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

[disconnectTimeoutInMinutes](#)

The amount of time that a streaming session remains active after users disconnect.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 600.

Required: No

[downloadAllowed](#)

Specifies whether the user can download files from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

[idleDisconnectTimeoutInMinutes](#)

The amount of time that users can be idle (inactive) before they are disconnected from their streaming session and the disconnect timeout interval begins.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 60.

Required: No

[pasteAllowed](#)

Specifies whether the user can paste text from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: No

printAllowed

Specifies whether the user can print to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

uploadAllowed

Specifies whether the user can upload files from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "userSettings": {
    "associatedPortalArns": [ "string" ],
    "cookieSynchronizationConfiguration": {
      "allowlist": [
        {
          "domain": "string",
          "name": "string",
          "path": "string"
        }
      ],
      "blocklist": [
        {
          "domain": "string",
          "name": "string",
          "path": "string"
        }
      ]
    }
  }
}
```

```
    },
    "copyAllowed": "string",
    "disconnectTimeoutInMinutes": number,
    "downloadAllowed": "string",
    "idleDisconnectTimeoutInMinutes": number,
    "pasteAllowed": "string",
    "printAllowed": "string",
    "uploadAllowed": "string",
    "userSettingsArn": "string"
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[userSettings](#)

The user settings.

Type: [UserSettings](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access is denied.

HTTP Status Code: 403

InternalServerError

There is an internal server error.

HTTP Status Code: 500

ResourceNotFoundException

The resource cannot be found.

HTTP Status Code: 404

ThrottlingException

There is a throttling error.

HTTP Status Code: 429

ValidationException

There is a validation error.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon WorkSpaces Web API contains several data types that various actions use. This section describes each data type in detail.

 **Note**

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [BrowserSettings](#)
- [BrowserSettingsSummary](#)
- [Certificate](#)
- [CertificateSummary](#)
- [CookieSpecification](#)
- [CookieSynchronizationConfiguration](#)
- [IdentityProvider](#)
- [IdentityProviderSummary](#)
- [IpAccessSettings](#)
- [IpAccessSettingsSummary](#)
- [IpRule](#)
- [NetworkSettings](#)
- [NetworkSettingsSummary](#)
- [Portal](#)
- [PortalSummary](#)
- [Tag](#)
- [TrustStore](#)
- [TrustStoreSummary](#)
- [UserAccessLoggingSettings](#)
- [UserAccessLoggingSettingsSummary](#)

- [UserSettings](#)
- [UserSettingsSummary](#)
- [ValidationExceptionField](#)

BrowserSettings

The browser settings resource that can be associated with a web portal. Once associated with a web portal, browser settings control how the browser will behave once a user starts a streaming session for the web portal.

Contents

browserSettingsArn

The ARN of the browser settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

associatedPortalArns

A list of web portal ARNs that this browser settings is associated with.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: No

browserPolicy

A JSON string containing Chrome Enterprise policies that will be applied to all streaming sessions.

Type: String

Length Constraints: Minimum length of 2. Maximum length of 131072.

Pattern: \{[\S\s]*\}\s*

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

BrowserSettingsSummary

The summary for browser settings.

Contents

browserSettingsArn

The ARN of the browser settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Certificate

The certificate.

Contents

body

The body of the certificate.

Type: Base64-encoded binary data object

Required: No

issuer

The entity that issued the certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^\S+\\$

Required: No

notValidAfter

The certificate is not valid after this date.

Type: Timestamp

Required: No

notValidBefore

The certificate is not valid before this date.

Type: Timestamp

Required: No

subject

The entity the certificate belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^\S+\\$

Required: No

thumbprint

A hexadecimal identifier for the certificate.

Type: String

Length Constraints: Fixed length of 64.

Pattern: ^[A-Fa-f0-9]{64}\\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CertificateSummary

The summary of the certificate.

Contents

issuer

The entity that issued the certificate.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^\S+\\$

Required: No

notValidAfter

The certificate is not valid after this date.

Type: Timestamp

Required: No

notValidBefore

The certificate is not valid before this date.

Type: Timestamp

Required: No

subject

The entity the certificate belongs to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^\S+\\$

Required: No

thumbprint

A hexadecimal identifier for the certificate.

Type: String

Length Constraints: Fixed length of 64.

Pattern: ^[A-Fa-f0-9]{64}\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CookieSpecification

Specifies a single cookie or set of cookies in an end user's browser.

Contents

domain

The domain of the cookie.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 253.

Pattern: `^(\\.?)\\([a-zA-Z0-9](\\([a-zA-Z0-9-]\\{0,61\\}[a-zA-Z0-9])?\\.)*[a-zA-Z0-9][a-zA-Z0-9-]\\{0,61\\}[a-zA-Z0-9]$`

Required: Yes

name

The name of the cookie.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

path

The path of the cookie.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2000.

Pattern: `^/(\\S)*$`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CookieSynchronizationConfiguration

The configuration that specifies which cookies should be synchronized from the end user's local browser to the remote browser.

Contents

allowlist

The list of cookie specifications that are allowed to be synchronized to the remote browser.

Type: Array of [CookieSpecification](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: Yes

blocklist

The list of cookie specifications that are blocked from being synchronized to the remote browser.

Type: Array of [CookieSpecification](#) objects

Array Members: Minimum number of 0 items. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IdentityProvider

The identity provider.

Contents

identityProviderArn

The ARN of the identity provider.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\){2,}\\$

Required: Yes

identityProviderDetails

The identity provider details. The following list describes the provider detail keys for each identity provider type.

- For Google and Login with Amazon:

- client_id
- client_secret
- authorize_scopes

- For Facebook:

- client_id
- client_secret
- authorize_scopes
- api_version

- For Sign in with Apple:

- client_id
- team_id
- key_id
- private_key

- `authorize_scopes`
- For OIDC providers:
 - `client_id`
 - `client_secret`
 - `attributes_request_method`
 - `oidc_issuer`
 - `authorize_scopes`
 - `authorize_url` *if not available from discovery URL specified by oidc_issuer key*
 - `token_url` *if not available from discovery URL specified by oidc_issuer key*
 - `attributes_url` *if not available from discovery URL specified by oidc_issuer key*
 - `jwks_uri` *if not available from discovery URL specified by oidc_issuer key*
- For SAML providers:
 - `MetadataFile` OR `MetadataURL`
 - `IDPSignout` (boolean) *optional*
 - `IDPInit` (boolean) *optional*
 - `RequestSigningAlgorithm` (string) *optional* - Only accepts `rsa-sha256`
 - `EncryptedResponses` (boolean) *optional*

Type: String to string map

Key Length Constraints: Minimum length of 0. Maximum length of 131072.

Key Pattern: `^[\s\S]*$`

Value Length Constraints: Minimum length of 0. Maximum length of 131072.

Value Pattern: `^[\s\S]*$`

Required: No

identityProviderName

The identity provider name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^[_][\p{L}\p{M}\p{S}\p{N}\p{P}][_]+\$

Required: No

identityProviderType

The identity provider type.

Type: String

Valid Values: SAML | Facebook | Google | LoginWithAmazon | SignInWithApple | OIDC

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IdentityProviderSummary

The summary of the identity provider.

Contents

identityProviderArn

The ARN of the identity provider.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36}){2,}\\$

Required: Yes

identityProviderName

The identity provider name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^[_][\p{L}\p{M}\p{S}\p{N}\p{P}][^_]+\$

Required: No

identityProviderType

The identity provider type.

Type: String

Valid Values: SAML | Facebook | Google | LoginWithAmazon | SignInWithApple | OIDC

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IpAccessSettings

The IP access settings resource that can be associated with a web portal.

Contents

ipAccessSettingsArn

The ARN of the IP access settings resource.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: Yes

associatedPortalArns

A list of web portal ARNs that this IP access settings resource is associated with.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: No

creationDate

The creation date timestamp of the IP access settings.

Type: Timestamp

Required: No

description

The description of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^ .+\$

Required: No

displayName

The display name of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ .+\$

Required: No

ipRules

The IP rules of the IP access settings.

Type: Array of [IpRule](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IpAccessSettingsSummary

The summary of IP access settings.

Contents

ipAccessSettingsArn

The ARN of IP access settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]{36}\)+\$

Required: Yes

creationDate

The creation date timestamp of the IP access settings.

Type: Timestamp

Required: No

description

The description of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^ .+\$

Required: No

displayName

The display name of the IP access settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ .+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

IpRule

The IP rules of the IP access settings.

Contents

ipRange

The IP range of the IP rule.

Type: String

Pattern: ^\d{1,3}\.\d{1,3}\.\d{1,3}\.\d{1,3}(?:/([0-9]|1[2][0-9]|3[0-2])|)\$

Required: Yes

description

The description of the IP rule.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: ^ .+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkSettings

A network settings resource that can be associated with a web portal. Once associated with a web portal, network settings define how streaming instances will connect with your specified VPC.

Contents

networkSettingsArn

The ARN of the network settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]\{36\})+\$

Required: Yes

associatedPortalArns

A list of web portal ARNs that this network settings is associated with.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]\{36\})+\$

Required: No

securityGroupIds

One or more security groups used to control access from streaming instances to your VPC.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 5 items.

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: ^[\w+\-_]+\\$

Required: No

subnetIds

The subnets in which network interfaces are created to connect streaming instances to your VPC. At least two of these subnets must be in different availability zones.

Type: Array of strings

Array Members: Minimum number of 2 items. Maximum number of 3 items.

Length Constraints: Minimum length of 1. Maximum length of 32.

Pattern: ^subnet-([0-9a-f]{8}|[0-9a-f]{17})\$

Required: No

vpcId

The VPC that streaming instances will connect to.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^vpc-[0-9a-z]*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

NetworkSettingsSummary

The summary of network settings.

Contents

networkSettingsArn

The ARN of the network settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-\-]{36}\)+\$

Required: Yes

vpcId

The VPC ID of the network settings.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Pattern: ^vpc-[0-9a-z]*\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Portal

The web portal.

Contents

portalArn

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

authenticationType

The type of authentication integration points used when signing into the web portal. Defaults to Standard.

Standard web portals are authenticated directly through your identity provider. You need to call `CreateIdentityProvider` to integrate your identity provider with your web portal. User and group access to your web portal is controlled through your identity provider.

IAM Identity Center web portals are authenticated through AWS IAM Identity Center. They provide additional features, such as IdP-initiated authentication. Identity sources (including external identity provider integration), plus user and group access to your web portal, can be configured in the IAM Identity Center.

Type: String

Valid Values: Standard | IAM_Identity_Center

Required: No

browserSettingsArn

The ARN of the browser settings that is associated with this web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-\-]\{36\}\)+\$

Required: No

browserType

The browser that users see when using a streaming session.

Type: String

Valid Values: Chrome

Required: No

creationDate

The creation date of the web portal.

Type: Timestamp

Required: No

displayName

The name of the web portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ .+\$

Required: No

ipAccessSettingsArn

The ARN of the IP access settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: No

networkSettingsArn

The ARN of the network settings that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: No

portalEndpoint

The endpoint URL of the web portal that users access in order to start streaming sessions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^[a-zA-Z0-9]?((?!-)([A-Za-z0-9-]*[A-Za-z0-9])\.)+[a-zA-Z0-9]+\$

Required: No

portalStatus

The status of the web portal.

Type: String

Valid Values: Incomplete | Pending | Active

Required: No

rendererType

The renderer that is used in streaming sessions.

Type: String

Valid Values: AppStream

Required: No

statusReason

A message that explains why the web portal is in its current status.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1024.

Pattern: .*

Required: No

trustStoreArn

The ARN of the trust store that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: No

userAccessLoggingSettingsArn

The ARN of the user access logging settings that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: No

userSettingsArn

The ARN of the user settings that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-\-]\{36\}\)+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

PortalSummary

The summary of the portal.

Contents

portalArn

The ARN of the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

authenticationType

The type of authentication integration points used when signing into the web portal. Defaults to Standard.

Standard web portals are authenticated directly through your identity provider. You need to call `CreateIdentityProvider` to integrate your identity provider with your web portal. User and group access to your web portal is controlled through your identity provider.

IAM Identity Center web portals are authenticated through AWS IAM Identity Center. They provide additional features, such as IdP-initiated authentication. Identity sources (including external identity provider integration), plus user and group access to your web portal, can be configured in the IAM Identity Center.

Type: String

Valid Values: Standard | IAM_Identity_Center

Required: No

browserSettingsArn

The ARN of the browser settings that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-\-]\{36\}\)+\$

Required: No

browserType

The browser type of the web portal.

Type: String

Valid Values: Chrome

Required: No

creationDate

The creation date of the web portal.

Type: Timestamp

Required: No

displayName

The name of the web portal.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: ^ . +\$

Required: No

ipAccessSettingsArn

The ARN of the IP access settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: No

networkSettingsArn

The ARN of the network settings that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]{36})+\$

Required: No

portalEndpoint

The endpoint URL of the web portal that users access in order to start streaming sessions.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 253.

Pattern: ^[a-zA-Z0-9]?((?!-)([A-Za-z0-9-]*[A-Za-z0-9])\.)+[a-zA-Z0-9]+\$

Required: No

portalStatus

The status of the web portal.

Type: String

Valid Values: Incomplete | Pending | Active

Required: No

rendererType

The renderer that is used in streaming sessions.

Type: String

Valid Values: AppStream

Required: No

trustStoreArn

The ARN of the trust that is associated with this web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]\{36\})+\$

Required: No

userAccessLoggingSettingsArn

The ARN of the user access logging settings that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]\{36\})+\$

Required: No

userSettingsArn

The ARN of the user settings that is associated with the web portal.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]\{36\})+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Tag

The tag.

Contents

Key

The key of the tag.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 128.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/-@]*)$`

Required: Yes

Value

The value of the tag

Type: String

Length Constraints: Minimum length of 0. Maximum length of 256.

Pattern: `^([\p{L}\p{Z}\p{N}_.:/-@]*)$`

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustStore

A trust store that can be associated with a web portal. A trust store contains certificate authority (CA) certificates. Once associated with a web portal, the browser in a streaming session will recognize certificates that have been issued using any of the CAs in the trust store. If your organization has internal websites that use certificates issued by private CAs, you should add the private CA certificate to the trust store.

Contents

trustStoreArn

The ARN of the trust store.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: Yes

associatedPortalArns

A list of web portal ARNs that this trust store is associated with.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TrustStoreSummary

The summary of the trust store.

Contents

trustStoreArn

The ARN of the trust store.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]{36})+\$

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserAccessLoggingSettings

A user access logging settings resource that can be associated with a web portal.

Contents

userAccessLoggingSettingsArn

The ARN of the user access logging settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]\{36}\)+\$

Required: Yes

associatedPortalArns

A list of web portal ARNs that this user access logging settings is associated with.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-\-]+:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-\-]\{36}\)+\$

Required: No

kinesisStreamArn

The ARN of the Kinesis stream.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:[\w+=/, .@-]+:kinesis:[a-zA-Z0-9\-\-]*:[a-zA-Z0-9]{1,12}:stream/.+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserAccessLoggingSettingsSummary

The summary of user access logging settings.

Contents

userAccessLoggingSettingsArn

The ARN of the user access logging settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]\{36\})+\$

Required: Yes

kinesisStreamArn

The ARN of the Kinesis stream.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: arn:[\w+=/, .@-]+:kinesis:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:stream/.+

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserSettings

A user settings resource that can be associated with a web portal. Once associated with a web portal, user settings control how users can transfer data between a streaming session and their local devices.

Contents

userSettingsArn

The ARN of the user settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]\{36}\)+\$

Required: Yes

associatedPortalArns

A list of web portal ARNs that this user settings is associated with.

Type: Array of strings

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+(\/[a-fA-F0-9\-_]\{36}\)+\$

Required: No

cookieSynchronizationConfiguration

The configuration that specifies which cookies should be synchronized from the end user's local browser to the remote browser.

Type: [CookieSynchronizationConfiguration](#) object

Required: No

copyAllowed

Specifies whether the user can copy text from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

disconnectTimeoutInMinutes

The amount of time that a streaming session remains active after users disconnect.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 600.

Required: No

downloadAllowed

Specifies whether the user can download files from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

idleDisconnectTimeoutInMinutes

The amount of time that users can be idle (inactive) before they are disconnected from their streaming session and the disconnect timeout interval begins.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 60.

Required: No

pasteAllowed

Specifies whether the user can paste text from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: No

printAllowed

Specifies whether the user can print to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

uploadAllowed

Specifies whether the user can upload files from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

UserSettingsSummary

The summary of user settings.

Contents

userSettingsArn

The ARN of the user settings.

Type: String

Length Constraints: Minimum length of 20. Maximum length of 2048.

Pattern: ^arn:[\w+=\/, .@-]+:[a-zA-Z0-9\-_]+:[a-zA-Z0-9\-_]*:[a-zA-Z0-9]{1,12}:[a-zA-Z]+\(\/[a-fA-F0-9\-_]\{36\}\)+\$

Required: Yes

cookieSynchronizationConfiguration

The configuration that specifies which cookies should be synchronized from the end user's local browser to the remote browser.

Type: [CookieSynchronizationConfiguration](#) object

Required: No

copyAllowed

Specifies whether the user can copy text from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

disconnectTimeoutInMinutes

The amount of time that a streaming session remains active after users disconnect.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 600.

Required: No

downloadAllowed

Specifies whether the user can download files from the streaming session to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

idleDisconnectTimeoutInMinutes

The amount of time that users can be idle (inactive) before they are disconnected from their streaming session and the disconnect timeout interval begins.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 60.

Required: No

pasteAllowed

Specifies whether the user can paste text from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: No

printAllowed

Specifies whether the user can print to the local device.

Type: String

Valid Values: Disabled | Enabled

Required: No

uploadAllowed

Specifies whether the user can upload files from the local device to the streaming session.

Type: String

Valid Values: Disabled | Enabled

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ValidationExceptionField

Information about a field passed inside a request that resulted in an exception.

Contents

message

The message describing why the field failed validation.

Type: String

Required: Yes

name

The name of the field that failed validation.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request").

The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 403

ExpiredTokenException

The security token included in the request is expired

HTTP Status Code: 403

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 403

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

MalformedHttpRequestException

Problems with the request at the HTTP level, e.g. we can't decompress the body according to the decompression algorithm specified by the content-encoding.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 401

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestAbortedException

Convenient exception that can be used when a request is aborted before a reply is sent back (e.g. client closed connection).

HTTP Status Code: 400

RequestEntityTooLargeException

Problems with the request at the HTTP level. The request entity is too large.

HTTP Status Code: 413

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

RequestTimeoutException

Problems with the request at the HTTP level. Reading the Request timed out.

HTTP Status Code: 408

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

UnrecognizedClientException

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

UnknownOperationException

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 404

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400