
AWS Snowball

API Reference



Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Job Management API	1
API Endpoint	1
API Version	2
API Permission Policy Reference	2
Creating an IAM Role for Snowball and Snowball Edge	4
Actions	7
CancelCluster	8
Request Syntax	8
Request Parameters	8
Response Elements	8
Errors	8
See Also	9
CancelJob	10
Request Syntax	10
Request Parameters	10
Response Elements	10
Errors	10
See Also	11
CreateAddress	12
Request Syntax	12
Request Parameters	12
Response Syntax	12
Response Elements	12
Errors	13
See Also	13
CreateCluster	14
Request Syntax	14
Request Parameters	14
Response Syntax	17
Response Elements	17
Errors	17
See Also	18
CreateJob	19
Request Syntax	19
Request Parameters	20
Response Syntax	22
Response Elements	23
Errors	23
See Also	23
CreateReturnShippingLabel	25
Request Syntax	25
Request Parameters	25
Response Syntax	25
Response Elements	25
Errors	26
See Also	26
DescribeAddress	28
Request Syntax	28
Request Parameters	28
Response Syntax	28
Response Elements	28
Errors	29
See Also	29
DescribeAddresses	30

Request Syntax	30
Request Parameters	30
Response Syntax	30
Response Elements	31
Errors	31
See Also	31
DescribeCluster	33
Request Syntax	33
Request Parameters	33
Response Syntax	33
Response Elements	34
Errors	34
See Also	34
DescribeJob	36
Request Syntax	36
Request Parameters	36
Response Syntax	36
Response Elements	39
Errors	39
See Also	39
DescribeReturnShippingLabel	40
Request Syntax	40
Request Parameters	40
Response Syntax	40
Response Elements	40
Errors	41
See Also	41
GetJobManifest	42
Request Syntax	42
Request Parameters	42
Response Syntax	42
Response Elements	42
Errors	43
See Also	43
GetJobUnlockCode	44
Request Syntax	44
Request Parameters	44
Response Syntax	44
Response Elements	44
Errors	45
See Also	45
GetSnowballUsage	46
Response Syntax	46
Response Elements	46
Errors	46
See Also	46
GetSoftwareUpdates	47
Request Syntax	47
Request Parameters	47
Response Syntax	47
Response Elements	47
Errors	48
See Also	48
ListClusterJobs	49
Request Syntax	49
Request Parameters	49
Response Syntax	49

Response Elements	50
Errors	50
See Also	50
ListClusters	52
Request Syntax	52
Request Parameters	52
Response Syntax	52
Response Elements	52
Errors	53
See Also	53
ListCompatibleImages	54
Request Syntax	54
Request Parameters	54
Response Syntax	54
Response Elements	55
Errors	55
See Also	55
ListJobs	56
Request Syntax	56
Request Parameters	56
Response Syntax	56
Response Elements	57
Errors	57
See Also	57
UpdateCluster	58
Request Syntax	58
Request Parameters	58
Response Elements	60
Errors	60
See Also	60
UpdateJob	62
Request Syntax	62
Request Parameters	62
Response Elements	64
Errors	64
See Also	65
UpdateJobShipmentState	66
Request Syntax	66
Request Parameters	66
Response Elements	66
Errors	66
See Also	67
Data Types	68
Address	69
Contents	69
See Also	71
ClusterListEntry	72
Contents	72
See Also	72
ClusterMetadata	73
Contents	73
See Also	75
CompatibleImage	76
Contents	76
See Also	76
DataTransfer	77
Contents	77

See Also	77
DeviceConfiguration	78
Contents	78
See Also	78
Ec2AmiResource	79
Contents	79
See Also	79
EventTriggerDefinition	80
Contents	80
See Also	80
INDTaxDocuments	81
Contents	81
See Also	81
JobListEntry	82
Contents	82
See Also	83
JobLogs	84
Contents	84
See Also	84
JobMetadata	86
Contents	86
See Also	89
JobResource	90
Contents	90
See Also	90
KeyRange	91
Contents	91
See Also	91
LambdaResource	92
Contents	92
See Also	92
Notification	93
Contents	93
See Also	93
S3Resource	94
Contents	94
See Also	94
Shipment	95
Contents	95
See Also	95
ShippingDetails	96
Contents	96
See Also	96
SnowconeDeviceConfiguration	97
Contents	97
See Also	97
TaxDocuments	98
Contents	98
See Also	98
WirelessConnection	99
Contents	99
See Also	99
Common Parameters	100
Common Errors	102

Job Management API Reference

The job management API for AWS Snowball is a network protocol based on HTTP (RFC 2616). For more information on this RFC, see [HTTP \(RFC 2616\)](#) on the IETF website. For each call to the job management API, you make an HTTP request to the region-specific job management API endpoint for the AWS Region where you want to manage jobs. The API uses JSON (RFC 4627) documents for HTTP request/response bodies.

Note

API calls made within the US regions for listing jobs or describing addresses return all jobs or addresses within the US for that account.

The job management API for Snowball is an RPC model. In this model, there is a fixed set of operations and the syntax for each operation is known to clients without any previous interaction. Following, you can find a description of each API operation using an abstract RPC notation, with an operation name that does not appear on the wire. For each operation, the topic specifies the mapping to HTTP request elements.

The specific job management operation to which a given request maps is determined by a combination of the request's method (GET, PUT, POST, or DELETE) and which of the various patterns its Request-URI matches. If the operation is PUT or POST, Snowball extracts call arguments from the Request-URI path segment, query parameters, and the JSON object in the request body.

Although the operation name, such as `CreateJob`, doesn't appear on the wire, these operation names are meaningful in AWS Identity and Access Management (IAM) policies. The operation name is also used to name commands in command-line tools and elements of the AWS SDK APIs. For example, the AWS Command Line Interface (AWS CLI) command `create-job` maps to the `CreateJob` operation. The operation name also appears in CloudTrail logs for Snowball API calls.

For information on installing and setting up the AWS CLI, including specifying what regions you want to make AWS CLI calls against, see the [AWS Command Line Interface User Guide](#).

Note

The job management API provides programmatic access to the same functionality available in the [AWS Snowball Management Console](#), that is to create and manage jobs for Snowball. To transfer data locally with a Snowball appliance, use the Snowball client or the S3 SDK Adapter for Snowball. For more information, see [Transferring Data with a Snowball](#) in the *AWS Snowball User Guide*.

If you use a Snowball Edge, use the Snowball client to unlock the appliance. For more information, see [Using the Snowball Client](#) in the *AWS Snowball Developer Guide*.

API Endpoint

The API endpoint is the Domain Name Service (DNS) name used as a host in the HTTP URI for the API calls. These API endpoints are region-specific and take the following form.

```
snowball.aws-region.amazonaws.com
```

For example, the Snowball API endpoint for the US West (Oregon) Region is the following.

```
snowball.us-west-2.amazonaws.com
```

For a list of AWS Regions that Snowball supports (where you can create and manage jobs), see [AWS Import/Export](#) in the *AWS General Reference*.

The region-specific API endpoint defines the scope of the Snowball resources that are accessible when you make an API call. For example, when you call the `ListJobs` operation using the preceding endpoint, you get a list of jobs in the US West (Oregon) Region that have been created in your account.

API Version

The version of the API being used for a call is identified by the first path segment of the request URI, and its form is an ISO 8601 date. The documentation describes API version 2016-06-30.

API Permission Policy Reference

The following policies are needed for creating jobs with the job management API for Snowball.

Role Trust Policy for Creating Jobs

Using the job management API to create jobs requires the following trust policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Sid": "",
      "Effect": "Allow",
      "Principal": {
        "Service": "importexport.amazonaws.com"
      },
      "Action": "sts:AssumeRole",
      "Condition": {
        "StringEquals": {
          "sts:ExternalId": "AWSIE"
        }
      }
    }
  ]
}
```

Note

To learn more about trust policies, see [Modifying a Role](#) in the IAM User Guide.

Role Policy for Creating Import Jobs

Creating an import job requires the following role policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:ListBucketMultipartUploads"
      ],
      "Resource": "arn:aws:s3::*:*"
    }
  ],
}
```



```
{
  "Effect": "Allow",
  "Action": [
    "s3:GetBucketPolicy",
    "s3:PutObject",
    "s3:AbortMultipartUpload",
    "s3:ListMultipartUploadParts",
    "s3:PutObjectAcl"
  ],
  "Resource": "arn:aws:s3::*"
},
{
  "Effect": "Allow",
  "Action": [
    "snowball:*"
  ],
  "Resource": [
    "*"
  ]
}
]
```

Role Policy for Creating Export Jobs

Creating an export job requires the following role policy.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:GetObject",
        "s3:ListBucket"
      ],
      "Resource": "arn:aws:s3::*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "snowball:*"
      ],
      "Resource": [
        "*"
      ]
    }
  ]
}
```

Amazon S3 Bucket Policy Principal for Creating Jobs

In some cases, the Amazon S3 buckets that you use with Snowball have bucket policies in place that require listing the role session name of the assumed role. In these cases, you need to specify a principal in those policies that identifies `AWSImportExport-Validation`. The following Amazon S3 bucket policy example demonstrates how to do so.

Example

```
{
  "Version": "2012-10-17",
```

```
"Statement": {
  "Sid": "Allow AWS Snowball To Create Jobs",
  "Effect": "Deny",
  "NotPrincipal": {
    "AWS": [
      "arn:aws:iam::111122223333:role/rolename",
      "arn:aws:sts::111122223333:assumed-role/rolename/AWSImportExport-Validation",
      "arn:aws:iam::111122223333:root"
    ]
  },
  "Action": "S3:*",
  "Resource": ["arn:aws:s3:::examplebucket/*"]
}
```

In this policy example, we deny access to all principals except the one named in the `NotPrincipal` element. For more information on how to use `NotPrincipal`, see [NotPrincipal](#) in the *IAM User Guide*.

Note

For jobs in AWS GovCloud (US), Snowball uses `AWSIEJob` as the role session name of the assumed role.

Creating an IAM Role for Snowball and Snowball Edge

An IAM role policy must be created with read and write permissions for your Amazon S3 buckets. The IAM role must also have a trust relationship with Snowball. Having a trust relationship means that AWS can write the data in the Snowball and in your Amazon S3 buckets, depending on whether you're importing or exporting data.

When you create a job in the AWS Snow Family Management Console, creating the necessary IAM role occurs in step 4 in the **Permission** section. This process is automatic. The IAM role that you allow Snowball to assume is only used to write your data to your bucket when the Snowball with your transferred data arrives at AWS. The following procedure outlines that process.

To create the IAM role for your import job

1. Sign in to the AWS Management Console and open the AWS Snowball console at <https://console.aws.amazon.com/importexport/>.
2. Choose **Create job**.
3. In the first step, fill out the details for your import job into Amazon S3, and then choose **Next**.
4. In the second step, under **Permission**, choose **Create/Select IAM Role**.

The IAM Management Console opens, showing the IAM role that AWS uses to copy objects into your specified Amazon S3 buckets.

5. Review the details on this page, and then choose **Allow**.

You return to the AWS Snow Family Management Console, where **Selected IAM role ARN** contains the Amazon Resource Name (ARN) for the IAM role that you just created.

6. Choose **Next** to finish creating your IAM role.

The preceding procedure creates an IAM role that has write permissions for the Amazon S3 buckets that you plan to import your data into. The IAM role that is created has one of the following structures, depending on whether it's for an import job or export job.

IAM Role for an Import Job

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:ListBucketMultipartUploads"
      ],
      "Resource": "arn:aws:s3:::*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketPolicy",
        "s3:PutObject",
        "s3:AbortMultipartUpload",
        "s3:ListMultipartUploadParts",
        "s3:PutObjectAcl"
      ],
      "Resource": "arn:aws:s3:::*"
    }
  ]
}
```

If you use server-side encryption with AWS KMS–managed keys (SSE-KMS) to encrypt the Amazon S3 buckets associated with your import job, you also need to add the following statement to your IAM role.

```
{
  "Effect": "Allow",
  "Action": [
    "kms:GenerateDataKey"
  ],
  "Resource": "arn:aws:s3:::SSEKMSEncryptedBucketName"
}
```

IAM Role for an Export Job

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": [
        "s3:GetBucketLocation",
        "s3:GetBucketPolicy",
        "s3:GetObject",
        "s3:ListBucket"
      ],
      "Resource": "arn:aws:s3:::*"
    }
  ]
}
```

If you use server-side encryption with AWS KMS–managed keys to encrypt the Amazon S3 buckets associated with your export job, you also need to add the following statement to your IAM role.

```
{
```

```
"Effect": "Allow",  
"Action": [  
    "kms:Decrypt"  
],  
"Resource": "arn:aws:s3:::SSEKMSEncryptedBucketName"  
}
```

Actions

The following actions are supported:

- [CancelCluster](#) (p. 8)
- [CancelJob](#) (p. 10)
- [CreateAddress](#) (p. 12)
- [CreateCluster](#) (p. 14)
- [CreateJob](#) (p. 19)
- [CreateReturnShippingLabel](#) (p. 25)
- [DescribeAddress](#) (p. 28)
- [DescribeAddresses](#) (p. 30)
- [DescribeCluster](#) (p. 33)
- [DescribeJob](#) (p. 36)
- [DescribeReturnShippingLabel](#) (p. 40)
- [GetJobManifest](#) (p. 42)
- [GetJobUnlockCode](#) (p. 44)
- [GetSnowballUsage](#) (p. 46)
- [GetSoftwareUpdates](#) (p. 47)
- [ListClusterJobs](#) (p. 49)
- [ListClusters](#) (p. 52)
- [ListCompatibleImages](#) (p. 54)
- [ListJobs](#) (p. 56)
- [UpdateCluster](#) (p. 58)
- [UpdateJob](#) (p. 62)
- [UpdateJobShipmentState](#) (p. 66)

CancelCluster

Cancels a cluster job. You can only cancel a cluster job while it's in the `AwaitingQuorum` status. You'll have at least an hour after creating a cluster job to cancel it.

Request Syntax

```
{  
  "ClusterId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 100).

The request accepts the following data in JSON format.

ClusterId (p. 8)

The 39-character ID for the cluster that you want to cancel, for example `CID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 102).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) (p. 19) or [UpdateJob](#) (p. 62) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelJob

Cancel the specified job. You can only cancel a job before its `JobState` value changes to `PreparingAppliance`. Requesting the `ListJobs` or `DescribeJob` action returns a job's `JobState` as part of the response element data returned.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

JobId (p. 10)

The 39-character job ID for the job that you want to cancel, for example `JID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `(M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob \(p. 19\)](#) or [UpdateJob \(p. 62\)](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateAddress

Creates an address for a Snow device to be shipped to. Addresses are validated at the time of creation. The address you provide must be located within the serviceable area of your region. If the address is invalid or unsupported, then an exception is thrown.

Request Syntax

```
{
  "Address": {
    "AddressId": "string",
    "City": "string",
    "Company": "string",
    "Country": "string",
    "IsRestricted": boolean,
    "Landmark": "string",
    "Name": "string",
    "PhoneNumber": "string",
    "PostalCode": "string",
    "PrefectureOrDistrict": "string",
    "StateOrProvince": "string",
    "Street1": "string",
    "Street2": "string",
    "Street3": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

Address (p. 12)

The address that you want the Snow device shipped to.

Type: [Address \(p. 69\)](#) object

Required: Yes

Response Syntax

```
{
  "AddressId": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[AddressId \(p. 12\)](#)

The automatically generated ID for a specific address. You'll use this ID when you create a job to specify which address you want the Snow device for that job shipped to.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidAddressException

The address provided was invalid. Check the address with your region's carrier, and try again.

HTTP Status Code: 400

UnsupportedAddressException

The address is either outside the serviceable area for your region, or an error occurred. Check the address with your region's carrier and try again. If the issue persists, contact AWS Support.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateCluster

Creates an empty cluster. Each cluster supports five nodes. You use the [CreateJob \(p. 19\)](#) action separately to create the jobs for each of these nodes. The cluster does not ship until these five node jobs have been created.

Request Syntax

```
{
  "AddressId": "string",
  "Description": "string",
  "ForwardingAddressId": "string",
  "JobType": "string",
  "KmsKeyARN": "string",
  "Notification": {
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        }
      }
    ]
  },
  "RoleARN": "string",
  "ShippingOption": "string",
  "SnowballType": "string",
  "TaxDocuments": {
    "IND": {
      "GSTIN": "string"
    }
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

AddressId (p. 14)

The ID for the address that you want the cluster shipped to.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Description (p. 14)

An optional description of this specific cluster, for example `Environmental Data Cluster-01`.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ForwardingAddressId (p. 14)

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

JobType (p. 14)

The type of job for this cluster. Currently, the only job type supported for clusters is `LOCAL_USE`.

Type: String

Valid Values: `IMPORT` | `EXPORT` | `LOCAL_USE`

Required: Yes

KmsKeyARN (p. 14)

The `KmsKeyARN` value that you want to associate with this cluster. `KmsKeyARN` values are created by using the [CreateKey](#) API action in AWS Key Management Service (AWS KMS).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:kms:.*:[0-9]{12}:key/.*`

Required: No

Notification (p. 14)

The Amazon Simple Notification Service (Amazon SNS) notification settings for this cluster.

Type: [Notification \(p. 93\)](#) object

Required: No

Resources (p. 14)

The resources associated with the cluster job. These resources include Amazon S3 buckets and optional AWS Lambda functions written in the Python language.

Type: [JobResource \(p. 90\)](#) object

Required: Yes

RoleARN (p. 14)

The `RoleARN` that you want to associate with this cluster. `RoleArn` values are created by using the [CreateRole](#) API action in AWS Identity and Access Management (IAM).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam::[0-9]{12}:role/.*`

Required: Yes

ShippingOption (p. 14)

The shipping speed for each node in this cluster. This speed doesn't dictate how soon you'll get each Snowball Edge device, rather it represents how quickly each device moves to its destination while in transit. Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow device are delivered in one to seven days.
- In the United States of America (US), you have access to one-day shipping and two-day shipping.
- In Australia, you have access to express shipping. Typically, devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow device are delivered in one to seven days.
- In the US, you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: Yes

SnowballType (p. 14)

The type of AWS Snow Family device to use for this cluster.

Note

For cluster jobs, AWS Snow Family currently supports only the `EDGE` device type.

Type: String

Valid Values: `STANDARD` | `EDGE` | `EDGE_C` | `EDGE_CG` | `EDGE_S` | `SNC1_HDD`

Required: No

TaxDocuments (p. 14)

The tax documents required in your AWS Region.

Type: [TaxDocuments \(p. 98\)](#) object

Required: No

Response Syntax

```
{  
  "ClusterId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ClusterId (p. 17)

The automatically generated ID for a cluster.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

Ec2RequestFailedException

Your IAM user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType \(p. 16\)](#) value supports your [CreateJob:JobType \(p. 21\)](#), and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob \(p. 19\)](#) or [UpdateJob \(p. 62\)](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateJob

Creates a job to import or export data between Amazon S3 and your on-premises data center. Your AWS account must have the right trust policies and permissions in place to create a job for a Snow device. If you're creating a job for a node in a cluster, you only need to provide the `clusterId` value; the other job attributes are inherited from the cluster.

Note

Only the Snowball; Edge device type is supported when ordering clustered jobs.

The device capacity is optional.

Availability of device types differ by AWS Region. For more information about region availability, see [AWS Regional Services](#).

Request Syntax

```
{
  "AddressId": "string",
  "ClusterId": "string",
  "Description": "string",
  "DeviceConfiguration": {
    "SnowconeDeviceConfiguration": {
      "WirelessConnection": {
        "IsWifiEnabled": boolean
      }
    }
  },
  "ForwardingAddressId": "string",
  "JobType": "string",
  "KmsKeyARN": "string",
  "Notification": {
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        }
      }
    ]
  },
  "RoleARN": "string",
```

```
"ShippingOption": "string",
"SnowballCapacityPreference": "string",
"SnowballType": "string",
"TaxDocuments": {
  "IND": {
    "GSTIN": "string"
  }
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

[AddressId \(p. 19\)](#)

The ID for the address that you want the Snow device shipped to.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

[ClusterId \(p. 19\)](#)

The ID of a cluster. If you're creating a job for a node in a cluster, you need to provide only this `clusterId` value. The other job attributes are inherited from the cluster.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

[Description \(p. 19\)](#)

Defines an optional description of this specific job, for example `Important Photos 2016-08-11`.

Type: String

Length Constraints: Minimum length of 1.

Required: No

[DeviceConfiguration \(p. 19\)](#)

Defines the device configuration for an AWS Snowcone job.

Type: [DeviceConfiguration \(p. 78\)](#) object

Required: No

[ForwardingAddressId \(p. 19\)](#)

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

JobType (p. 19)

Defines the type of job that you're creating.

Type: String

Valid Values: `IMPORT` | `EXPORT` | `LOCAL_USE`

Required: No

KmsKeyARN (p. 19)

The `KmsKeyARN` that you want to associate with this job. `KmsKeyARNs` are created using the [CreateKey](#) AWS Key Management Service (KMS) API action.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:kms:.*:[0-9]{12}:key/.*`

Required: No

Notification (p. 19)

Defines the Amazon Simple Notification Service (Amazon SNS) notification settings for this job.

Type: [Notification \(p. 93\)](#) object

Required: No

Resources (p. 19)

Defines the Amazon S3 buckets associated with this job.

With `IMPORT` jobs, you specify the bucket or buckets that your transferred data will be imported into.

With `EXPORT` jobs, you specify the bucket or buckets that your transferred data will be exported from. Optionally, you can also specify a `KeyRange` value. If you choose to export a range, you define the length of the range by providing either an inclusive `BeginMarker` value, an inclusive `EndMarker` value, or both. Ranges are UTF-8 binary sorted.

Type: [JobResource \(p. 90\)](#) object

Required: No

RoleARN (p. 19)

The `RoleARN` that you want to associate with this job. `RoleArns` are created using the [CreateRole](#) AWS Identity and Access Management (IAM) API action.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam:.*:[0-9]{12}:role/.*`

Required: No

ShippingOption (p. 19)

The shipping speed for this job. This speed doesn't dictate how soon you'll get the Snow device, rather it represents how quickly the Snow device moves to its destination while in transit. Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow devices are delivered in one to seven days.
- In the US, you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

SnowballCapacityPreference (p. 19)

If your job is being created in one of the US regions, you have the option of specifying what size Snow device you'd like for this job. In all other regions, Snowballs come with 80 TB in storage capacity.

Type: String

Valid Values: `T50` | `T80` | `T100` | `T42` | `T98` | `T8` | `NoPreference`

Required: No

SnowballType (p. 19)

The type of AWS Snow Family device to use for this job.

Note

For cluster jobs, AWS Snow Family currently supports only the `EDGE` device type.

The type of AWS Snow device to use for this job. Currently, the only supported device type for cluster jobs is `EDGE`.

For more information, see [Snowball Edge Device Options](#) in the Snowball Edge Developer Guide.

Type: String

Valid Values: `STANDARD` | `EDGE` | `EDGE_C` | `EDGE_CG` | `EDGE_S` | `SNC1_HDD`

Required: No

TaxDocuments (p. 19)

The tax documents required in your AWS Region.

Type: [TaxDocuments \(p. 98\)](#) object

Required: No

Response Syntax

```
{  
  "JobId": "string"
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobId (p. 22)

The automatically generated ID for a job, for example `JID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `(M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 102).

ClusterLimitExceededException

Job creation failed. Currently, clusters support five nodes. If you have less than five nodes for your cluster and you have more nodes to create for this cluster, try again and create jobs until your cluster has exactly five nodes.

HTTP Status Code: 400

Ec2RequestFailedException

Your IAM user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType](#) (p. 16) value supports your [CreateJob:JobType](#) (p. 21), and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob](#) (p. 19) or [UpdateJob](#) (p. 62) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateReturnShippingLabel

Creates a shipping label that will be used to return the Snow device to AWS.

Request Syntax

```
{  
  "JobId": "string",  
  "ShippingOption": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 100).

The request accepts the following data in JSON format.

JobId (p. 25)

The ID for a job that you want to create the return shipping label for. For example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

ShippingOption (p. 25)

The shipping speed for a particular job. This speed doesn't dictate how soon the device is returned to AWS. This speed represents how quickly it moves to its destination while in transit. Regional shipping speeds are as follows:

Type: String

Valid Values: SECOND_DAY | NEXT_DAY | EXPRESS | STANDARD

Required: No

Response Syntax

```
{  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Status (p. 25)

The status information of the task on a Snow device that is being returned to AWS.

Type: String

Valid Values: `InProgress` | `TimedOut` | `Succeeded` | `Failed`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

ConflictException

You get this exception when you call `CreateReturnShippingLabel` more than once when other requests are not completed.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType \(p. 16\)](#) value supports your [CreateJob:JobType \(p. 21\)](#), and try again.

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

ReturnShippingLabelAlreadyExistsException

You get this exception if you call `CreateReturnShippingLabel` and a valid return shipping label already exists. In this case, use `DescribeReturnShippingLabel` to get the url.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAddress

Takes an `AddressId` and returns specific details about that address in the form of an `Address` object.

Request Syntax

```
{  
  "AddressId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 100).

The request accepts the following data in JSON format.

AddressId (p. 28)

The automatically generated ID for a specific address.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "Address": {  
    "AddressId": "string",  
    "City": "string",  
    "Company": "string",  
    "Country": "string",  
    "IsRestricted": boolean,  
    "Landmark": "string",  
    "Name": "string",  
    "PhoneNumber": "string",  
    "PostalCode": "string",  
    "PrefectureOrDistrict": "string",  
    "StateOrProvince": "string",  
    "Street1": "string",  
    "Street2": "string",  
    "Street3": "string"  
  }  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Address \(p. 28\)](#)

The address that you want the Snow device(s) associated with a specific job to be shipped to.

Type: [Address \(p. 69\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeAddresses

Returns a specified number of ADDRESS objects. Calling this API in one of the US regions will return addresses from the list of all addresses associated with this account in all US regions.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 30)

The number of ADDRESS objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken (p. 30)

HTTP requests are stateless. To identify what object comes "next" in the list of ADDRESS objects, you have the option of specifying a value for NextToken as the starting point for your list of returned addresses.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{  
  "Addresses": [  
    {  
      "AddressId": "string",  
      "City": "string",  
      "Company": "string",  
      "Country": "string",  
      "IsRestricted": boolean,  
      "Landmark": "string",  
      "Name": "string",  
      "PhoneNumber": "string",  
      "PostalCode": "string",  
      "PrefectureOrDistrict": "string",  
      "StateOrProvince": "string",  
    }  
  ]  
}
```

```
    "Street1": "string",  
    "Street2": "string",  
    "Street3": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Addresses (p. 30)

The Snow device shipping addresses that were created for this account.

Type: Array of [Address \(p. 69\)](#) objects

NextToken (p. 30)

HTTP requests are stateless. If you use the automatically generated `NextToken` value in your next `DescribeAddresses` call, your list of returned addresses will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidNextTokenException

The `NextToken` string was altered unexpectedly, and the operation has stopped. Run the operation without changing the `NextToken` string, and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeCluster

Returns information about a specific cluster including shipping information, cluster status, and other important metadata.

Request Syntax

```
{  
  "ClusterId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 100).

The request accepts the following data in JSON format.

ClusterId (p. 33)

The automatically generated ID for a cluster.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "ClusterMetadata": {  
    "AddressId": "string",  
    "ClusterId": "string",  
    "ClusterState": "string",  
    "CreationDate": number,  
    "Description": "string",  
    "ForwardingAddressId": "string",  
    "JobType": "string",  
    "KmsKeyARN": "string",  
    "Notification": {  
      "JobStatesToNotify": [ "string" ],  
      "NotifyAll": boolean,  
      "SnsTopicARN": "string"  
    },  
    "Resources": {  
      "Ec2AmiResources": [  
        {  
          "AmiId": "string",  
          "SnowballAmiId": "string"  
        }  
      ],  
      "LambdaResources": [  
        {  
          "EventTriggers": [  

```

```
    {
      "EventResourceARN": "string"
    }
  ],
  "LambdaArn": "string"
},
],
"S3Resources": [
  {
    "BucketArn": "string",
    "KeyRange": {
      "BeginMarker": "string",
      "EndMarker": "string"
    }
  }
]
},
"RoleARN": "string",
"ShippingOption": "string",
"SnowballType": "string",
"TaxDocuments": {
  "IND": {
    "GSTIN": "string"
  }
}
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ClusterMetadata (p. 33)

Information about a specific cluster, including shipping information, cluster status, and other important metadata.

Type: [ClusterMetadata \(p. 73\)](#) object

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeJob

Returns information about a specific job including shipping information, job status, and other important metadata.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 100).

The request accepts the following data in JSON format.

JobId (p. 36)

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Response Syntax

```
{  
  "JobMetadata": {  
    "AddressId": "string",  
    "ClusterId": "string",  
    "CreationDate": number,  
    "DataTransferProgress": {  
      "BytesTransferred": number,  
      "ObjectsTransferred": number,  
      "TotalBytes": number,  
      "TotalObjects": number  
    },  
    "Description": "string",  
    "DeviceConfiguration": {  
      "SnowconeDeviceConfiguration": {  
        "WirelessConnection": {  
          "IsWifiEnabled": boolean  
        }  
      }  
    },  
    "ForwardingAddressId": "string",  
    "JobId": "string",  
    "JobLogInfo": {  
      "JobCompletionReportURI": "string",  
      "JobFailureLogURI": "string",  
    }  
  }  
}
```

```

    "JobSuccessLogURI": "string"
  },
  "JobState": "string",
  "JobType": "string",
  "KmsKeyARN": "string",
  "Notification": {
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        }
      }
    ]
  },
  "RoleARN": "string",
  "ShippingDetails": {
    "InboundShipment": {
      "Status": "string",
      "TrackingNumber": "string"
    },
    "OutboundShipment": {
      "Status": "string",
      "TrackingNumber": "string"
    },
    "ShippingOption": "string"
  },
  "SnowballCapacityPreference": "string",
  "SnowballType": "string",
  "TaxDocuments": {
    "IND": {
      "GSTIN": "string"
    }
  }
},
"SubJobMetadata": [
  {
    "AddressId": "string",
    "ClusterId": "string",
    "CreationDate": number,
    "DataTransferProgress": {
      "BytesTransferred": number,
      "ObjectsTransferred": number,
      "TotalBytes": number,

```

```

    "TotalObjects": number
  },
  "Description": "string",
  "DeviceConfiguration": {
    "SnowconeDeviceConfiguration": {
      "WirelessConnection": {
        "IsWifiEnabled": boolean
      }
    }
  },
  "ForwardingAddressId": "string",
  "JobId": "string",
  "JobLogInfo": {
    "JobCompletionReportURI": "string",
    "JobFailureLogURI": "string",
    "JobSuccessLogURI": "string"
  },
  "JobState": "string",
  "JobType": "string",
  "KmsKeyARN": "string",
  "Notification": {
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        }
      }
    ]
  },
  "RoleARN": "string",
  "ShippingDetails": {
    "InboundShipment": {
      "Status": "string",
      "TrackingNumber": "string"
    },
    "OutboundShipment": {
      "Status": "string",
      "TrackingNumber": "string"
    },
    "ShippingOption": "string"
  },
  "SnowballCapacityPreference": "string",
  "SnowballType": "string",

```

```
    "TaxDocuments": {  
      "IND": {  
        "GSTIN": "string"  
      }  
    }  
  }  
]
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobMetadata (p. 36)

Information about a specific job, including shipping information, job status, and other important metadata.

Type: [JobMetadata \(p. 86\)](#) object

SubJobMetadata (p. 36)

Information about a specific job part (in the case of an export job), including shipping information, job status, and other important metadata.

Type: Array of [JobMetadata \(p. 86\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DescribeReturnShippingLabel

Information on the shipping label of a Snow device that is being returned to AWS.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

JobId (p. 40)

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Response Syntax

```
{  
  "ExpirationDate": number,  
  "Status": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ExpirationDate (p. 40)

The expiration date of the current return shipping label.

Type: Timestamp

Status (p. 40)

The status information of the task on a Snow device that is being returned to AWS.

Type: String

Valid Values: `InProgress` | `TimedOut` | `Succeeded` | `Failed`

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

ConflictException

You get this exception when you call `CreateReturnShippingLabel` more than once when other requests are not completed.

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetJobManifest

Returns a link to an Amazon S3 presigned URL for the manifest file associated with the specified `JobId` value. You can access the manifest file for up to 60 minutes after this request has been made. To access the manifest file after 60 minutes have passed, you'll have to make another call to the `GetJobManifest` action.

The manifest is an encrypted file that you can download after your job enters the `WithCustomer` status. The manifest is decrypted by using the `UnlockCode` code value, when you pass both values to the Snow device through the Snowball client when the client is started for the first time.

As a best practice, we recommend that you don't save a copy of an `UnlockCode` value in the same location as the manifest file for that job. Saving these separately helps prevent unauthorized parties from gaining access to the Snow device associated with that job.

The credentials of a given job, including its manifest file and unlock code, expire 90 days after the job is created.

Request Syntax

```
{
  "JobId": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

JobId (p. 42)

The ID for a job that you want to get the manifest file for, for example `JID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `(M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Response Syntax

```
{
  "ManifestURI": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ManifestURI (p. 42)

The Amazon S3 presigned URL for the manifest file associated with the specified `JobId` value.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetJobUnlockCode

Returns the `UnlockCode` code value for the specified job. A particular `UnlockCode` value can be accessed for up to 90 days after the associated job has been created.

The `UnlockCode` value is a 29-character code with 25 alphanumeric characters and 4 hyphens. This code is used to decrypt the manifest file when it is passed along with the manifest to the Snow device through the Snowball client when the client is started for the first time.

As a best practice, we recommend that you don't save a copy of the `UnlockCode` in the same location as the manifest file for that job. Saving these separately helps prevent unauthorized parties from gaining access to the Snow device associated with that job.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

JobId (p. 44)

The ID for the job that you want to get the `UnlockCode` value for, for example `JID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `(M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Response Syntax

```
{  
  "UnlockCode": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UnlockCode (p. 44)

The `UnlockCode` value for the specified job. The `UnlockCode` value can be accessed for up to 90 days after the job has been created.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSnowballUsage

Returns information about the Snow Family service limit for your account, and also the number of Snow devices your account has in use.

The default service limit for the number of Snow devices that you can have at one time is 1. If you want to increase your service limit, contact AWS Support.

Response Syntax

```
{
  "SnowballLimit": number,
  "SnowballsInUse": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

SnowballLimit (p. 46)

The service limit for number of Snow devices this account can have at once. The default service limit is 1 (one).

Type: Integer

SnowballsInUse (p. 46)

The number of Snow devices that this account is currently using.

Type: Integer

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 102).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetSoftwareUpdates

Returns an Amazon S3 presigned URL for an update file associated with a specified `JobId`.

Request Syntax

```
{  
  "JobId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

JobId (p. 47)

The ID for a job that you want to get the software update file for, for example `JID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `(M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

Response Syntax

```
{  
  "UpdatesURI": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

UpdatesURI (p. 47)

The Amazon S3 presigned URL for the update file associated with the specified `JobId` value. The software update will be available for 2 days after this request is made. To access an update after the 2 days have passed, you'll have to make another call to `GetSoftwareUpdates`.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListClusterJobs

Returns an array of `JobListEntry` objects of the specified length. Each `JobListEntry` object is for a job in the specified cluster and contains a job's state, a job's ID, and other information.

Request Syntax

```
{  
  "ClusterId": "string",  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

ClusterId (p. 49)

The 39-character ID for the cluster that you want to list, for example `CID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Fixed length of 39.

Pattern: `CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: Yes

MaxResults (p. 49)

The number of `JobListEntry` objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken (p. 49)

HTTP requests are stateless. To identify what object comes "next" in the list of `JobListEntry` objects, you have the option of specifying `NextToken` as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{
```

```
"JobListEntries": [  
  {  
    "CreationDate": number,  
    "Description": "string",  
    "IsMaster": boolean,  
    "JobId": "string",  
    "JobState": "string",  
    "JobType": "string",  
    "SnowballType": "string"  
  }  
],  
"NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobListEntries (p. 49)

Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of export jobs.

Type: Array of [JobListEntry](#) (p. 82) objects

NextToken (p. 49)

HTTP requests are stateless. If you use the automatically generated `NextToken` value in your next `ListClusterJobsResult` call, your list of returned jobs will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 102).

InvalidNextTokenException

The `NextToken` string was altered unexpectedly, and the operation has stopped. Run the operation without changing the `NextToken` string, and try again.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListClusters

Returns an array of `ClusterListEntry` objects of the specified length. Each `ClusterListEntry` object contains a cluster's state, a cluster's ID, and other important status information.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 52)

The number of `ClusterListEntry` objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken (p. 52)

HTTP requests are stateless. To identify what object comes "next" in the list of `ClusterListEntry` objects, you have the option of specifying `NextToken` as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{  
  "ClusterListEntries": [  
    {  
      "ClusterId": "string",  
      "ClusterState": "string",  
      "CreationDate": number,  
      "Description": "string"  
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

ClusterListEntries (p. 52)

Each `ClusterListEntry` object contains a cluster's state, a cluster's ID, and other important status information.

Type: Array of [ClusterListEntry \(p. 72\)](#) objects

NextToken (p. 52)

HTTP requests are stateless. If you use the automatically generated `NextToken` value in your next `ClusterListEntry` call, your list of returned clusters will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidNextTokenException

The `NextToken` string was altered unexpectedly, and the operation has stopped. Run the operation without changing the `NextToken` string, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListCompatibleImages

This action returns a list of the different Amazon EC2 Amazon Machine Images (AMIs) that are owned by your AWS account that would be supported for use on a Snow device. Currently, supported AMIs are based on the CentOS 7 (x86_64) - with Updates HVM, Ubuntu Server 14.04 LTS (HVM), and Ubuntu 16.04 LTS - Xenial (HVM) images, available on the AWS Marketplace.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

MaxResults (p. 54)

The maximum number of results for the list of compatible images. Currently, a Snowball Edge device can store 10 AMIs.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken (p. 54)

HTTP requests are stateless. To identify what object comes "next" in the list of compatible images, you can specify a value for `NextToken` as the starting point for your list of returned images.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{  
  "CompatibleImages": [  
    {  
      "AmiId": "string",  
      "Name": "string"  
    }  
  ],  
  "NextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

CompatibleImages (p. 54)

A JSON-formatted object that describes a compatible AMI, including the ID and name for a Snow device AMI.

Type: Array of [CompatibleImage \(p. 76\)](#) objects

NextToken (p. 54)

Because HTTP requests are stateless, this is the starting point for your next list of returned images.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

Ec2RequestFailedException

Your IAM user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidNextTokenException

The `NextToken` string was altered unexpectedly, and the operation has stopped. Run the operation without changing the `NextToken` string, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListJobs

Returns an array of `JobListEntry` objects of the specified length. Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of export jobs. Calling this API action in one of the US regions will return jobs from the list of all jobs associated with this account in all US regions.

Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 100).

The request accepts the following data in JSON format.

MaxResults (p. 56)

The number of `JobListEntry` objects to return.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

NextToken (p. 56)

HTTP requests are stateless. To identify what object comes "next" in the list of `JobListEntry` objects, you have the option of specifying `NextToken` as the starting point for your returned list.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Response Syntax

```
{  
  "JobListEntries": [  
    {  
      "CreationDate": number,  
      "Description": "string",  
      "IsMaster": boolean,  
      "JobId": "string",  
      "JobState": "string",  
      "JobType": "string",  
      "SnowballType": "string"  
    }  
  ],  
  "NextToken": "string"  
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

JobListEntries (p. 56)

Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of export jobs.

Type: Array of [JobListEntry](#) (p. 82) objects

NextToken (p. 56)

HTTP requests are stateless. If you use this automatically generated `NextToken` value in your next `ListJobs` call, your returned `JobListEntry` objects will start from this point in the array.

Type: String

Length Constraints: Minimum length of 1.

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 102).

InvalidNextTokenException

The `NextToken` string was altered unexpectedly, and the operation has stopped. Run the operation without changing the `NextToken` string, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateCluster

While a cluster's `ClusterState` value is in the `AwaitingQuorum` state, you can update some of the information associated with a cluster. Once the cluster changes to a different job state, usually 60 minutes after the cluster being created, this action is no longer available.

Request Syntax

```
{
  "AddressId": "string",
  "ClusterId": "string",
  "Description": "string",
  "ForwardingAddressId": "string",
  "Notification": {
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        }
      }
    ]
  },
  "RoleARN": "string",
  "ShippingOption": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 100).

The request accepts the following data in JSON format.

[AddressId](#) (p. 58)

The ID of the updated [Address](#) (p. 69) object.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

ClusterId (p. 58)

The cluster ID of the cluster that you want to update, for example CID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: CID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Description (p. 58)

The updated description of this cluster.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ForwardingAddressId (p. 58)

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Notification (p. 58)

The new or updated [Notification \(p. 93\)](#) object.

Type: [Notification \(p. 93\)](#) object

Required: No

Resources (p. 58)

The updated arrays of [JobResource \(p. 90\)](#) objects that can include updated [S3Resource \(p. 94\)](#) objects or [LambdaResource \(p. 92\)](#) objects.

Type: [JobResource \(p. 90\)](#) object

Required: No

RoleARN (p. 58)

The new role Amazon Resource Name (ARN) that you want to associate with this cluster. To create a role ARN, use the [CreateRole](#) API action in AWS Identity and Access Management (IAM).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam::[0-9]{12}:role/.*`

Required: No

ShippingOption (p. 58)

The updated shipping option value of this cluster's [ShippingDetails \(p. 96\)](#) object.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

Ec2RequestFailedException

Your IAM user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType \(p. 16\)](#) value supports your [CreateJob:JobType \(p. 21\)](#), and try again.

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob \(p. 19\)](#) or [UpdateJob \(p. 62\)](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateJob

While a job's `JobState` value is `New`, you can update some of the information associated with a job. Once the job changes to a different job state, usually within 60 minutes of the job being created, this action is no longer available.

Request Syntax

```
{
  "AddressId": "string",
  "Description": "string",
  "ForwardingAddressId": "string",
  "JobId": "string",
  "Notification": {
    "JobStatesToNotify": [ "string" ],
    "NotifyAll": boolean,
    "SnsTopicARN": "string"
  },
  "Resources": {
    "Ec2AmiResources": [
      {
        "AmiId": "string",
        "SnowballAmiId": "string"
      }
    ],
    "LambdaResources": [
      {
        "EventTriggers": [
          {
            "EventResourceARN": "string"
          }
        ],
        "LambdaArn": "string"
      }
    ],
    "S3Resources": [
      {
        "BucketArn": "string",
        "KeyRange": {
          "BeginMarker": "string",
          "EndMarker": "string"
        }
      }
    ]
  },
  "RoleARN": "string",
  "ShippingOption": "string",
  "SnowballCapacityPreference": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

AddressId (p. 62)

The ID of the updated [Address \(p. 69\)](#) object.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

Description (p. 62)

The updated description of this job's [JobMetadata \(p. 86\)](#) object.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ForwardingAddressId (p. 62)

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

JobId (p. 62)

The job ID of the job that you want to update, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

Notification (p. 62)

The new or updated [Notification \(p. 93\)](#) object.

Type: [Notification \(p. 93\)](#) object

Required: No

Resources (p. 62)

The updated [JobResource](#) object, or the updated [JobResource \(p. 90\)](#) object.

Type: [JobResource \(p. 90\)](#) object

Required: No

RoleARN (p. 62)

The new role Amazon Resource Name (ARN) that you want to associate with this job. To create a role ARN, use the [CreateRoleAWS Identity and Access Management \(IAM\) API action](#).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam::[0-9]{12}:role/.*`

Required: No

ShippingOption (p. 62)

The updated shipping option value of this job's [ShippingDetails \(p. 96\)](#) object.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

SnowballCapacityPreference (p. 62)

The updated `SnowballCapacityPreference` of this job's [JobMetadata \(p. 86\)](#) object. The 50 TB Snowballs are only available in the US regions.

Type: String

Valid Values: `T50` | `T80` | `T100` | `T42` | `T98` | `T8` | `NoPreference`

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

ClusterLimitExceededException

Job creation failed. Currently, clusters support five nodes. If you have less than five nodes for your cluster and you have more nodes to create for this cluster, try again and create jobs until your cluster has exactly five nodes.

HTTP Status Code: 400

Ec2RequestFailedException

Your IAM user lacks the necessary Amazon EC2 permissions to perform the attempted action.

HTTP Status Code: 400

InvalidInputCombinationException

Job or cluster creation failed. One or more inputs were invalid. Confirm that the [CreateCluster:SnowballType \(p. 16\)](#) value supports your [CreateJob:JobType \(p. 21\)](#), and try again.

HTTP Status Code: 400

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

KMSRequestFailedException

The provided AWS Key Management Service key lacks the permissions to perform the specified [CreateJob \(p. 19\)](#) or [UpdateJob \(p. 62\)](#) action.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateJobShipmentState

Updates the state when a the shipment states changes to a different state.

Request Syntax

```
{  
  "JobId": "string",  
  "ShipmentState": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 100\)](#).

The request accepts the following data in JSON format.

JobId (p. 66)

The job ID of the job whose shipment date you want to update, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Fixed length of 39.

Pattern: (M|J)ID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: Yes

ShipmentState (p. 66)

The state of a device when it is being shipped.

Set to `RECEIVED` when the device arrives at your location.

Set to `RETURNED` when you have returned the device to AWS.

Type: String

Valid Values: `RECEIVED` | `RETURNED`

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 102\)](#).

InvalidJobStateException

The action can't be performed because the job's current state doesn't allow that action to be performed.

HTTP Status Code: 400

InvalidResourceException

The specified resource can't be found. Check the information you provided in your last request, and try again.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The Amazon Import/Export Snowball API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Address](#) (p. 69)
- [ClusterListEntry](#) (p. 72)
- [ClusterMetadata](#) (p. 73)
- [CompatibleImage](#) (p. 76)
- [DataTransfer](#) (p. 77)
- [DeviceConfiguration](#) (p. 78)
- [Ec2AmiResource](#) (p. 79)
- [EventTriggerDefinition](#) (p. 80)
- [INDTaxDocuments](#) (p. 81)
- [JobListEntry](#) (p. 82)
- [JobLogs](#) (p. 84)
- [JobMetadata](#) (p. 86)
- [JobResource](#) (p. 90)
- [KeyRange](#) (p. 91)
- [LambdaResource](#) (p. 92)
- [Notification](#) (p. 93)
- [S3Resource](#) (p. 94)
- [Shipment](#) (p. 95)
- [ShippingDetails](#) (p. 96)
- [SnowconeDeviceConfiguration](#) (p. 97)
- [TaxDocuments](#) (p. 98)
- [WirelessConnection](#) (p. 99)

Address

The address that you want the Snow device(s) associated with a specific job to be shipped to. Addresses are validated at the time of creation. The address you provide must be located within the serviceable area of your region. Although no individual elements of the `Address` are required, if the address is invalid or unsupported, then an exception is thrown.

Contents

AddressId

The unique ID for an address.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

City

The city in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Company

The name of the company to receive a Snow device at an address.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Country

The country in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

IsRestricted

This field is not supported in your region.

Type: Boolean

Required: No

Landmark

This field is no longer used and the value is ignored.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Name

The name of a person to receive a Snow device at an address.

Type: String

Length Constraints: Minimum length of 1.

Required: No

PhoneNumber

The phone number associated with an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

PostalCode

The postal code in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

PrefectureOrDistrict

This field is no longer used and the value is ignored.

Type: String

Length Constraints: Minimum length of 1.

Required: No

StateOrProvince

The state or province in an address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Street1

The first line in a street address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Street2

The second line in a street address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Street3

The third line in a street address that a Snow device is to be delivered to.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

ClusterListEntry

Contains a cluster's state, a cluster's ID, and other important information.

Contents

ClusterId

The 39-character ID for the cluster that you want to list, for example `CID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ClusterState

The current state of this cluster. For information about the state of a specific node, see [JobListEntry:JobState \(p. 82\)](#).

Type: String

Valid Values: `AwaitingQuorum` | `Pending` | `InUse` | `Complete` | `Cancelled`

Required: No

CreationDate

The creation date for this cluster.

Type: Timestamp

Required: No

Description

Defines an optional description of the cluster, for example `Environmental Data Cluster-01`.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

ClusterMetadata

Contains metadata about a specific cluster.

Contents

AddressId

The automatically generated ID for a specific address.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

ClusterId

The automatically generated ID for a cluster.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ClusterState

The current status of the cluster.

Type: String

Valid Values: `AwaitingQuorum` | `Pending` | `InUse` | `Complete` | `Cancelled`

Required: No

CreationDate

The creation date for this cluster.

Type: Timestamp

Required: No

Description

The optional description of the cluster.

Type: String

Length Constraints: Minimum length of 1.

Required: No

ForwardingAddressId

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

JobType

The type of job for this cluster. Currently, the only job type supported for clusters is LOCAL_USE.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: No

KmsKeyARN

The `KmsKeyARN` Amazon Resource Name (ARN) associated with this cluster. This ARN was created using the [CreateKey](#) API action in AWS Key Management Service (AWS KMS).

Type: String

Length Constraints: Maximum length of 255.

Pattern: arn:aws.*:kms:.*:[0-9]{12}:key/.*

Required: No

Notification

The Amazon Simple Notification Service (Amazon SNS) notification settings for this cluster.

Type: [Notification \(p. 93\)](#) object

Required: No

Resources

The arrays of [JobResource \(p. 90\)](#) objects that can include updated [S3Resource \(p. 94\)](#) objects or [LambdaResource \(p. 92\)](#) objects.

Type: [JobResource \(p. 90\)](#) object

Required: No

RoleARN

The role ARN associated with this cluster. This ARN was created using the [CreateRole](#) API action in AWS Identity and Access Management (IAM).

Type: String

Length Constraints: Maximum length of 255.

Pattern: arn:aws.*:iam:.*:[0-9]{12}:role/.*

Required: No

ShippingOption

The shipping speed for each node in this cluster. This speed doesn't dictate how soon you'll get each device, rather it represents how quickly each device moves to its destination while in transit. Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, devices shipped express are delivered in about a day.

- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow devices are delivered in one to seven days.
- In the US, you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

SnowballType

The type of AWS Snow device to use for this cluster.

Note

For cluster jobs, AWS Snow Family currently supports only the `EDGE` device type.

Type: String

Valid Values: `STANDARD` | `EDGE` | `EDGE_C` | `EDGE_CG` | `EDGE_S` | `SNC1_HDD`

Required: No

TaxDocuments

The tax documents required in your AWS Region.

Type: [TaxDocuments \(p. 98\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

CompatibleImage

A JSON-formatted object that describes a compatible Amazon Machine Image (AMI), including the ID and name for a Snow device AMI. This AMI is compatible with the device's physical hardware requirements, and it should be able to be run in an SBE1 instance on the device.

Contents

Amild

The unique identifier for an individual Snow device AMI.

Type: String

Length Constraints: Minimum length of 1.

Required: No

Name

The optional name of a compatible image.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

DataTransfer

Defines the real-time status of a Snow device's data transfer while the device is at AWS. This data is only available while a job has a `JobState` value of `InProgress`, for both import and export jobs.

Contents

BytesTransferred

The number of bytes transferred between a Snow device and Amazon S3.

Type: Long

Required: No

ObjectsTransferred

The number of objects transferred between a Snow device and Amazon S3.

Type: Long

Required: No

TotalBytes

The total bytes of data for a transfer between a Snow device and Amazon S3. This value is set to 0 (zero) until all the keys that will be transferred have been listed.

Type: Long

Required: No

TotalObjects

The total number of objects for a transfer between a Snow device and Amazon S3. This value is set to 0 (zero) until all the keys that will be transferred have been listed.

Type: Long

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

DeviceConfiguration

The container for `SnowconeDeviceConfiguration`.

Contents

SnowconeDeviceConfiguration

Returns information about the device configuration for an AWS Snowcone job.

Type: [SnowconeDeviceConfiguration \(p. 97\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

Ec2AmiResource

A JSON-formatted object that contains the IDs for an Amazon Machine Image (AMI), including the Amazon EC2 AMI ID and the Snow device AMI ID. Each AMI has these two IDs to simplify identifying the AMI in both the AWS Cloud and on the device.

Contents

Amild

The ID of the AMI in Amazon EC2.

Type: String

Length Constraints: Minimum length of 12. Maximum length of 21.

Pattern: `(ami-[0-9a-f]{8})|(ami-[0-9a-f]{17})`

Required: Yes

SnowballAmild

The ID of the AMI on the Snow device.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

EventTriggerDefinition

The container for the [EventTriggerDefinition:EventResourceARN](#) (p. 80).

Contents

EventResourceARN

The Amazon Resource Name (ARN) for any local Amazon S3 resource that is an AWS Lambda function's event trigger associated with this job.

Type: String

Length Constraints: Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

INDTaxDocuments

The tax documents required in AWS Regions in India.

Contents

GSTIN

The Goods and Services Tax (GST) documents required in AWS Regions in India.

Type: String

Pattern: `\d{2}[A-Z]{5}\d{4}[A-Z]{1}[A-Z\d]{1}[Z]{1}[A-Z\d]{1}`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

JobListEntry

Each `JobListEntry` object contains a job's state, a job's ID, and a value that indicates whether the job is a job part, in the case of an export job.

Contents

CreationDate

The creation date for this job.

Type: Timestamp

Required: No

Description

The optional description of this specific job, for example `Important Photos 2016-08-11`.

Type: String

Length Constraints: Minimum length of 1.

Required: No

IsMaster

A value that indicates that this job is a main job. A main job represents a successful request to create an export job. Main jobs aren't associated with any Snowballs. Instead, each main job will have at least one job part, and each job part is associated with a Snowball. It might take some time before the job parts associated with a particular main job are listed, because they are created after the main job is created.

Type: Boolean

Required: No

JobId

The automatically generated ID for a job, for example `JID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Minimum length of 1.

Required: No

JobState

The current state of this job.

Type: String

Valid Values: `New` | `PreparingAppliance` | `PreparingShipment` | `InTransitToCustomer` | `WithCustomer` | `InTransitToAWS` | `WithAWSSortingFacility` | `WithAWS` | `InProgress` | `Complete` | `Cancelled` | `Listing` | `Pending`

Required: No

JobType

The type of job.

Type: String

Valid Values: `IMPORT` | `EXPORT` | `LOCAL_USE`

Required: No

SnowballType

The type of device used with this job.

Type: String

Valid Values: `STANDARD` | `EDGE` | `EDGE_C` | `EDGE_CG` | `EDGE_S` | `SNC1_HDD`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

JobLogs

Contains job logs. Whenever a Snow device is used to import data into or export data out of Amazon S3, you'll have the option of downloading a PDF job report. Job logs are returned as a part of the response syntax of the `DescribeJob` action in the `JobMetadata` data type. The job logs can be accessed for up to 60 minutes after this request has been made. To access any of the job logs after 60 minutes have passed, you'll have to make another call to the `DescribeJob` action.

For import jobs, the PDF job report becomes available at the end of the import process. For export jobs, your job report typically becomes available while the Snow device for your job part is being delivered to you.

The job report provides you insight into the state of your Amazon S3 data transfer. The report includes details about your job or job part for your records.

For deeper visibility into the status of your transferred objects, you can look at the two associated logs: a success log and a failure log. The logs are saved in comma-separated value (CSV) format, and the name of each log includes the ID of the job or job part that the log describes.

Contents

JobCompletionReportURI

A link to an Amazon S3 presigned URL where the job completion report is located.

Type: String

Length Constraints: Minimum length of 1.

Required: No

JobFailureLogURI

A link to an Amazon S3 presigned URL where the job failure log is located.

Type: String

Length Constraints: Minimum length of 1.

Required: No

JobSuccessLogURI

A link to an Amazon S3 presigned URL where the job success log is located.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)

- [AWS SDK for Ruby V3](#)

JobMetadata

Contains information about a specific job including shipping information, job status, and other important metadata. This information is returned as a part of the response syntax of the `DescribeJob` action.

Contents

AddressId

The ID for the address that you want the Snow device shipped to.

Type: String

Length Constraints: Fixed length of 40.

Pattern: `ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}`

Required: No

ClusterId

The 39-character ID for the cluster, for example `CID123e4567-e89b-12d3-a456-426655440000`.

Type: String

Length Constraints: Minimum length of 1.

Required: No

CreationDate

The creation date for this job.

Type: Timestamp

Required: No

DataTransferProgress

A value that defines the real-time status of a Snow device's data transfer while the device is at AWS. This data is only available while a job has a `JobState` value of `InProgress`, for both import and export jobs.

Type: [DataTransfer \(p. 77\)](#) object

Required: No

Description

The description of the job, provided at job creation.

Type: String

Length Constraints: Minimum length of 1.

Required: No

DeviceConfiguration

The container for `SnowconeDeviceConfiguration`.

Type: [DeviceConfiguration \(p. 78\)](#) object

Required: No

ForwardingAddressId

This field is not supported in your region.

Type: String

Length Constraints: Fixed length of 40.

Pattern: ADID[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12}

Required: No

JobId

The automatically generated ID for a job, for example JID123e4567-e89b-12d3-a456-426655440000.

Type: String

Length Constraints: Minimum length of 1.

Required: No

JobLogInfo

Links to Amazon S3 presigned URLs for the job report and logs. For import jobs, the PDF job report becomes available at the end of the import process. For export jobs, your job report typically becomes available while the Snow device for your job part is being delivered to you.

Type: [JobLogs \(p. 84\)](#) object

Required: No

JobState

The current status of the jobs.

Type: String

Valid Values: New | PreparingAppliance | PreparingShipment | InTransitToCustomer | WithCustomer | InTransitToAWS | WithAWSSortingFacility | WithAWS | InProgress | Complete | Cancelled | Listing | Pending

Required: No

JobType

The type of job.

Type: String

Valid Values: IMPORT | EXPORT | LOCAL_USE

Required: No

KmsKeyARN

The Amazon Resource Name (ARN) for the AWS Key Management Service (AWS KMS) key associated with this job. This ARN was created using the [CreateKey](#) API action in AWS KMS.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:kms:.*:[0-9]{12}:key/.*`

Required: No

Notification

The Amazon Simple Notification Service (Amazon SNS) notification settings associated with a specific job. The `Notification` object is returned as a part of the response syntax of the `DescribeJob` action in the `JobMetadata` data type.

Type: [Notification \(p. 93\)](#) object

Required: No

Resources

An array of `S3Resource` objects. Each `S3Resource` object represents an Amazon S3 bucket that your transferred data will be exported from or imported into.

Type: [JobResource \(p. 90\)](#) object

Required: No

RoleARN

The role ARN associated with this job. This ARN was created using the [CreateRole](#) API action in AWS Identity and Access Management (IAM).

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:iam::[0-9]{12}:role/.*`

Required: No

ShippingDetails

A job's shipping information, including inbound and outbound tracking numbers and shipping speed options.

Type: [ShippingDetails \(p. 96\)](#) object

Required: No

SnowballCapacityPreference

The Snow device capacity preference for this job, specified at job creation. In US regions, you can choose between 50 TB and 80 TB Snowballs. All other regions use 80 TB capacity Snowballs.

Type: String

Valid Values: `T50` | `T80` | `T100` | `T42` | `T98` | `T8` | `NoPreference`

Required: No

SnowballType

The type of device used with this job.

Type: String

Valid Values: `STANDARD` | `EDGE` | `EDGE_C` | `EDGE_CG` | `EDGE_S` | `SNC1_HDD`

Required: No

TaxDocuments

The metadata associated with the tax documents required in your AWS Region.

Type: [TaxDocuments \(p. 98\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

JobResource

Contains an array of AWS resource objects. Each object represents an Amazon S3 bucket, an AWS Lambda function, or an Amazon Machine Image (AMI) based on Amazon EC2 that is associated with a particular job.

Contents

Ec2AmiResources

The Amazon Machine Images (AMIs) associated with this job.

Type: Array of [Ec2AmiResource](#) (p. 79) objects

Required: No

LambdaResources

The Python-language Lambda functions for this job.

Type: Array of [LambdaResource](#) (p. 92) objects

Required: No

S3Resources

An array of [S3Resource](#) objects.

Type: Array of [S3Resource](#) (p. 94) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

KeyRange

Contains a key range. For export jobs, a `S3Resource` object can have an optional `KeyRange` value. The length of the range is defined at job creation, and has either an inclusive `BeginMarker`, an inclusive `EndMarker`, or both. Ranges are UTF-8 binary sorted.

Contents

BeginMarker

The key that starts an optional key range for an export job. Ranges are inclusive and UTF-8 binary sorted.

Type: String

Length Constraints: Minimum length of 1.

Required: No

EndMarker

The key that ends an optional key range for an export job. Ranges are inclusive and UTF-8 binary sorted.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

LambdaResource

Identifies

Contents

EventTriggers

The array of ARNs for [S3Resource \(p. 94\)](#) objects to trigger the [LambdaResource \(p. 92\)](#) objects associated with this job.

Type: Array of [EventTriggerDefinition \(p. 80\)](#) objects

Required: No

LambdaArn

An Amazon Resource Name (ARN) that represents an AWS Lambda function to be triggered by PUT object actions on the associated local Amazon S3 resource.

Type: String

Length Constraints: Maximum length of 255.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

Notification

The Amazon Simple Notification Service (Amazon SNS) notification settings associated with a specific job. The `Notification` object is returned as a part of the response syntax of the `DescribeJob` action in the `JobMetadata` data type.

When the notification settings are defined during job creation, you can choose to notify based on a specific set of job states using the `JobStatesToNotify` array of strings, or you can specify that you want to have Amazon SNS notifications sent out for all job states with `NotifyAll` set to true.

Contents

JobStatesToNotify

The list of job states that will trigger a notification for this job.

Type: Array of strings

Valid Values: `New` | `PreparingAppliance` | `PreparingShipment` | `InTransitToCustomer` | `WithCustomer` | `InTransitToAWS` | `WithAWSSortingFacility` | `WithAWS` | `InProgress` | `Complete` | `Cancelled` | `Listing` | `Pending`

Required: No

NotifyAll

Any change in job state will trigger a notification for this job.

Type: Boolean

Required: No

SnsTopicARN

The new SNS `TopicArn` that you want to associate with this job. You can create Amazon Resource Names (ARNs) for topics by using the [CreateTopic](#) Amazon SNS API action.

You can subscribe email addresses to an Amazon SNS topic through the AWS Management Console, or by using the [Subscribe](#) AWS Simple Notification Service (SNS) API action.

Type: String

Length Constraints: Maximum length of 255.

Pattern: `arn:aws.*:sns:.*:[0-9]{12}:.*`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

S3Resource

Each `S3Resource` object represents an Amazon S3 bucket that your transferred data will be exported from or imported into. For export jobs, this object can have an optional `KeyRange` value. The length of the range is defined at job creation, and has either an inclusive `BeginMarker`, an inclusive `EndMarker`, or both. Ranges are UTF-8 binary sorted.

Contents

BucketArn

The Amazon Resource Name (ARN) of an Amazon S3 bucket.

Type: String

Length Constraints: Maximum length of 255.

Required: No

KeyRange

For export jobs, you can provide an optional `KeyRange` within a specific Amazon S3 bucket. The length of the range is defined at job creation, and has either an inclusive `BeginMarker`, an inclusive `EndMarker`, or both. Ranges are UTF-8 binary sorted.

Type: [KeyRange \(p. 91\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

Shipment

The `Status` and `TrackingNumber` information for an inbound or outbound shipment.

Contents

Status

Status information for a shipment.

Type: String

Length Constraints: Minimum length of 1.

Required: No

TrackingNumber

The tracking number for this job. Using this tracking number with your region's carrier's website, you can track a Snow device as the carrier transports it.

For India, the carrier is Amazon Logistics. For all other regions, UPS is the carrier.

Type: String

Length Constraints: Minimum length of 1.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

ShippingDetails

A job's shipping information, including inbound and outbound tracking numbers and shipping speed options.

Contents

InboundShipment

The `Status` and `TrackingNumber` values for a Snow device being returned to AWS for a particular job.

Type: [Shipment \(p. 95\)](#) object

Required: No

OutboundShipment

The `Status` and `TrackingNumber` values for a Snow device being delivered to the address that you specified for a particular job.

Type: [Shipment \(p. 95\)](#) object

Required: No

ShippingOption

The shipping speed for a particular job. This speed doesn't dictate how soon you'll get the Snow device from the job's creation date. This speed represents how quickly it moves to its destination while in transit. Regional shipping speeds are as follows:

- In Australia, you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day.
- In the European Union (EU), you have access to express shipping. Typically, Snow devices shipped express are delivered in about a day. In addition, most countries in the EU have access to standard shipping, which typically takes less than a week, one way.
- In India, Snow device are delivered in one to seven days.
- In the United States of America (US), you have access to one-day shipping and two-day shipping.

Type: String

Valid Values: `SECOND_DAY` | `NEXT_DAY` | `EXPRESS` | `STANDARD`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

SnowconeDeviceConfiguration

Specifies the device configuration for an AWS Snowcone job.

Contents

WirelessConnection

Configures the wireless connection for the AWS Snowcone device.

Type: [WirelessConnection \(p. 99\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

TaxDocuments

The tax documents required in your AWS Region.

Contents

IND

The tax documents required in AWS Regions in India.

Type: [INDTaxDocuments \(p. 81\)](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

WirelessConnection

Configures the wireless connection on an AWS Snowcone device.

Contents

IsWifiEnabled

Enables the Wi-Fi adapter on an AWS Snowcone device.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400