
AWS Application Discovery Service

API Reference

API Version 2015-11-01



AWS Application Discovery Service: API Reference

Copyright © 2018 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Querying Discovered Configuration Items	2
Using the DescribeConfigurationsAction	2
Using the ListConfigurationsAction	4
Actions	14
AssociateConfigurationItemsToApplication	15
Request Syntax	15
Request Parameters	15
Response Elements	15
Errors	15
Example	16
See Also	16
CreateApplication	17
Request Syntax	17
Request Parameters	17
Response Syntax	17
Response Elements	17
Errors	17
Example	18
See Also	18
CreateTags	20
Request Syntax	20
Request Parameters	20
Response Elements	20
Errors	20
Example	21
See Also	21
DeleteApplications	23
Request Syntax	23
Request Parameters	23
Response Elements	23
Errors	23
Example	24
See Also	24
DeleteTags	25
Request Syntax	25
Request Parameters	25
Response Elements	25
Errors	25
Example	26
See Also	26
DescribeAgents	28
Request Syntax	28
Request Parameters	28
Response Syntax	29
Response Elements	29
Errors	29
Example	30
See Also	31
DescribeConfigurations	32
Request Syntax	32
Request Parameters	32
Response Syntax	32
Response Elements	32

Errors	33
Example	33
See Also	34
DescribeContinuousExports	35
Request Syntax	35
Request Parameters	35
Response Syntax	35
Response Elements	36
Errors	36
Example	37
See Also	37
DescribeExportConfigurations	39
Request Syntax	39
Request Parameters	39
Response Syntax	39
Response Elements	40
Errors	40
See Also	40
DescribeExportTasks	42
Request Syntax	42
Request Parameters	42
Response Syntax	43
Response Elements	43
Errors	43
Example	44
See Also	45
DescribeTags	46
Request Syntax	46
Request Parameters	46
Response Syntax	47
Response Elements	47
Errors	47
Example	48
See Also	48
DisassociateConfigurationItemsFromApplication	50
Request Syntax	50
Request Parameters	50
Response Elements	50
Errors	50
Example	51
See Also	51
ExportConfigurations	52
Response Syntax	52
Response Elements	52
Errors	52
See Also	53
GetDiscoverySummary	54
Response Syntax	54
Response Elements	54
Errors	55
Example	55
See Also	56
ListConfigurations	57
Request Syntax	57
Request Parameters	57
Response Syntax	58
Response Elements	58

Errors	58
Example	59
See Also	60
ListServerNeighbors	61
Request Syntax	61
Request Parameters	61
Response Syntax	62
Response Elements	62
Errors	62
Example	63
See Also	63
StartContinuousExport	65
Response Syntax	65
Response Elements	65
Errors	65
Example	66
See Also	66
StartDataCollectionByAgentIds	68
Request Syntax	68
Request Parameters	68
Response Syntax	68
Response Elements	68
Errors	69
Example	69
See Also	70
StartExportTask	71
Request Syntax	71
Request Parameters	71
Response Syntax	72
Response Elements	72
Errors	72
Example	73
See Also	74
StopContinuousExport	75
Request Syntax	75
Request Parameters	75
Response Syntax	75
Response Elements	75
Errors	75
Example	76
See Also	77
StopDataCollectionByAgentIds	78
Request Syntax	78
Request Parameters	78
Response Syntax	78
Response Elements	78
Errors	78
Example	79
See Also	79
UpdateApplication	81
Request Syntax	81
Request Parameters	81
Response Elements	81
Errors	81
Example	82
See Also	82
Data Types	83

AgentConfigurationStatus	84
Contents	84
See Also	84
AgentInfo	85
Contents	85
See Also	86
AgentNetworkInfo	87
Contents	87
See Also	87
ConfigurationTag	88
Contents	88
See Also	88
ContinuousExportDescription	89
Contents	89
See Also	90
CustomerAgentInfo	92
Contents	92
See Also	93
CustomerConnectorInfo	94
Contents	94
See Also	95
ExportFilter	96
Contents	96
See Also	96
ExportInfo	97
Contents	97
See Also	98
Filter	99
Contents	99
See Also	99
NeighborConnectionDetail	100
Contents	100
See Also	100
OrderByElement	101
Contents	101
See Also	101
Tag	102
Contents	102
See Also	102
TagFilter	103
Contents	103
See Also	103
Common Parameters	104
Common Errors	106

Welcome

AWS Application Discovery Service helps you plan application migration projects by automatically identifying servers, virtual machines (VMs), software, and software dependencies running in your on-premises data centers. Application Discovery Service also collects application performance data, which can help you assess the outcome of your migration. The data collected by Application Discovery Service is securely retained in an AWS-hosted and managed database in the cloud. You can export the data as a CSV or XML file into your preferred visualization tool or cloud-migration solution to plan your migration. For more information, see [AWS Application Discovery Service FAQ](#).

Application Discovery Service offers the following two modes of operation:

- **Agentless discovery** mode is recommended for environments that use VMware vCenter Server. This mode doesn't require you to install an agent on each host. Agentless discovery gathers server information regardless of the operating systems, which minimizes the time required for initial on-premises infrastructure assessment. Agentless discovery doesn't collect information about software and software dependencies. It also doesn't work in non-VMware environments.
- **Agent-based discovery** mode collects a richer set of data than agentless discovery by using the AWS Application Discovery Agent, which you install on one or more hosts in your data center. The agent captures infrastructure and application information, including an inventory of installed software applications, system and process performance, resource utilization, and network dependencies between workloads. The information collected by agents is secured at rest and in transit to the Application Discovery Service database in the cloud.

We recommend that you use agent-based discovery for non-VMware environments and to collect information about software and software dependencies. You can also run agent-based and agentless discovery simultaneously. Use agentless discovery to quickly complete the initial infrastructure assessment and then install agents on select hosts.

Application Discovery Service integrates with application discovery solutions from AWS Partner Network (APN) partners. Third-party application discovery tools can query Application Discovery Service and write to the Application Discovery Service database using a public API. You can then import the data into either a visualization tool or cloud-migration solution.

Important

Application Discovery Service doesn't gather sensitive information. All data is handled according to the [AWS Privacy Policy](#). You can operate Application Discovery Service offline to inspect collected data before it is shared with the service.

Your AWS account must be granted access to Application Discovery Service, a process called *whitelisting*. This is true for AWS partners and customers alike. To request access, [sign up for Application Discovery Service](#).

This API reference provides descriptions, syntax, and usage examples for each of the actions and data types for Application Discovery Service. The topic for each action shows the API request parameters and the response. Alternatively, you can use one of the AWS SDKs to access an API that is tailored to the programming language or platform that you're using. For more information, see [AWS SDKs](#).

This guide is intended for use with the [Application Discovery Service User Guide](#).

Querying Discovered Configuration Items

A *configuration item* is an IT asset that was discovered in your data center by an agent or the connector. When you use Application Discovery Service, you can specify filters and query specific configuration items for server, application, process, and connection assets.

The tables in the following sections list the available input filters and output sorting options for two Application Discovery Service actions:

- DescribeConfigurations
- ListConfigurations

The filtering and sorting options are organized by the type of asset to which apply (server, application, process, or connection).

Using the DescribeConfigurationsAction

The DescribeConfigurationsaction retrieves attributes for a list of configuration IDs. All the supplied IDs must be for the same asset type (server, application, process, or connection). Output fields are specific to the asset type selected. For example, the output for a server configuration item includes a list of attributes about the server, such as host name, operating system, and number of network cards. For more information about command syntax, see [DescribeConfigurations](#).

The DescribeConfigurationsaction does not support filtering.

Output fields for DescribeConfigurations

The following tables, organized by asset type, list the supported output fields of the DescribeConfigurationsaction. The ones marked as mandatory are always present in the output.

Server assets

Field	Mandatory
server.agentId	
server.applications	
server.applications.hasMoreValues	
server.configurationId	✓
server.cpuType	
server.hostName	
server.hypervisor	
server.networkInterfaceInfo	
server.networkInterfaceInfo.hasMoreValues	

Field	Mandatory
server.osName	
server.osVersion	
server.tags	
server.tags.hasMoreValues	
server.timeOfCreation	✓
server.type	
server.performance.avgCpuUsagePct	
server.performance.avgDiskReadIOPS	
server.performance.avgDiskReadsPerSecondInKB	
server.performance.avgDiskWriteIOPS	
server.performance.avgDiskWritesPerSecondInKB	
server.performance.avgFreeRAMInKB	
server.performance.avgNetworkReadsPerSecondInKB	
server.performance.avgNetworkWritesPerSecondInKB	
server.performance.maxCpuUsagePct	
server.performance.maxDiskReadIOPS	
server.performance.maxDiskReadsPerSecondInKB	
server.performance.maxDiskWriteIOPS	
server.performance.maxDiskWritesPerSecondInKB	
server.performance.maxNetworkReadsPerSecondInKB	
server.performance.maxNetworkWritesPerSecondInKB	
server.performance.minFreeRAMInKB	
server.performance.numCores	
server.performance.numCpus	
server.performance.numDisks	
server.performance.numNetworkCards	
server.performance.totalRAMInKB	

Process assets

Field	Mandatory
process.commandLine	

Field	Mandatory
<code>process.configurationId</code>	✓
<code>process.name</code>	
<code>process.path</code>	
<code>process.timeOfCreation</code>	✓

Application assets

Field	Mandatory
<code>application.configurationId</code>	✓
<code>application.description</code>	
<code>application.lastModifiedTime</code>	✓
<code>application.name</code>	✓
<code>application.serverCount</code>	✓
<code>application.timeOfCreation</code>	✓

Using the ListConfigurationsAction

The `ListConfigurationsAction` retrieves a list of configuration items according to the criteria that you specify in a filter. For more information about command syntax, see [ListConfigurations](#).

Output fields for ListConfigurations

The following tables, organized by asset type, list the supported output fields of the `ListConfigurationsAction`. The ones marked as mandatory are always present in the output.

Server assets

Field	Mandatory
<code>server.configurationId</code>	✓
<code>server.agentId</code>	
<code>server.hostName</code>	
<code>server.osName</code>	
<code>server.osVersion</code>	
<code>server.timeOfCreation</code>	✓
<code>server.type</code>	

Process assets

Field	Mandatory
process.commandLine	
process.configurationId	✓
process.name	
process.path	
process.timeOfCreation	✓
server.agentId	
server.configurationId	✓

Application assets

Field	Mandatory
application.configurationId	✓
application.description	
application.name	✓
application.serverCount	✓
application.timeOfCreation	✓
application.lastModifiedTime	✓

Connection assets

Field	Mandatory
connection.destinationIp	✓
connection.destinationPort	✓
connection.ipVersion	✓
connection.latestTimestamp	✓
connection.occurrence	✓
connection.sourceIp	✓
connection.transportProtocol	
destinationProcess.configurationId	
destinationProcess.name	
destinationServer.configurationId	
destinationServer.hostName	

Field	Mandatory
sourceProcess.configurationId	
sourceProcess.name	
sourceServer.configurationId	
sourceServer.hostName	

Supported filters for ListConfigurations

The following tables, organized by asset type, list the supported filters for the ListConfigurationsaction. Filters and values are in a key/value relationship defined by one of the supported logical conditions. You can sort the output of the indicated filters.

Server assets

Filter	Supported conditions	Supported values	Supported sorting
server.configurationId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • Any valid server configuration ID 	None
server.hostName	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
server.osName	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
server.osVersion	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
server.agentId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • String 	None
server.connectorId	<ul style="list-style-type: none"> • EQUALS 	<ul style="list-style-type: none"> • String 	None

Filter	Supported conditions	Supported values	Supported sorting
	<ul style="list-style-type: none"> NOT_EQUALS EQ NE 		
server.type	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE 	String with one of the following values: <ul style="list-style-type: none"> EC2 OTHER VMWARE_VM VMWARE_HOST VMWARE_VM_TEMPLATE 	None
server.vmWareInfo.moreInfo	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.vmWareInfo.vcenterId	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.vmWareInfo.hostName	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.networkInterfaceId	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.networkInterfaceId	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None

Filter	Supported conditions	Supported values	Supported sorting
server.networkInterfaces.virtualSwitchId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	• String	None
server.networkInterfaces.ipAddress	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	• String	None
server.networkInterfaces.macAddress	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	• String	None
server.performance.avgCpuUsagePct	<ul style="list-style-type: none"> • GE • LE • GT • LT 	• Percentage	None
server.performance.totalDiskFreeSizeInKB	<ul style="list-style-type: none"> • GE • LE • GT • LT 	• Double	None
server.performance.avgFreeRAMInKB	<ul style="list-style-type: none"> • GE • LE • GT • LT 	• Double	None
server.tag.value	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	• String	None

Filter	Supported conditions	Supported values	Supported sorting
server.tag.key	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.application.name	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.application.description	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.application.configurationId	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE 	<ul style="list-style-type: none"> Any valid application configuration ID 	None
server.process.configurationId	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE 	<ul style="list-style-type: none"> ProcessId 	None
server.process.name	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None
server.process.command	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	None

Application assets

Filter	Supported conditions	Supported values	Supported sorting
application.configurationId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • ApplicationId 	None
application.name	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
application.description	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
application.serverConfiguration	Filtering not supported.	Filtering not supported.	<ul style="list-style-type: none"> • ASC • DESC
application.timeOfCreation	Filtering not supported.	Filtering not supported.	<ul style="list-style-type: none"> • ASC • DESC
application.lastModified	Filtering not supported.	Filtering not supported.	<ul style="list-style-type: none"> • ASC • DESC
server.configurationId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • ServerId 	None

Process assets

Filter	Supported conditions	Supported values	Supported sorting
process.configurationId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • ProcessId 	
process.name	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC

Filter	Supported conditions	Supported values	Supported sorting
<code>process.commandLine</code>	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
<code>server.configurationId</code>	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • ServerId 	
<code>server.hostName</code>	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
<code>server.osName</code>	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
<code>server.osVersion</code>	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
<code>server.agentId</code>	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	

Connection assets

Filter	Supported conditions	Supported values	Supported sorting
<code>connection.sourceIp</code>	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ 	<ul style="list-style-type: none"> • IP 	<ul style="list-style-type: none"> • ASC • DESC

Filter	Supported conditions	Supported values	Supported sorting
	<ul style="list-style-type: none"> NE CONTAINS NOT_CONTAINS 		
connection.destinationIp	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> IP 	<ul style="list-style-type: none"> ASC DESC
connection.destinationPort	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE 	<ul style="list-style-type: none"> Integer 	<ul style="list-style-type: none"> ASC DESC
sourceServer.configurationId	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE 	<ul style="list-style-type: none"> ServerId 	
sourceServer.hostName	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	<ul style="list-style-type: none"> ASC DESC
destinationServer.osName	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	<ul style="list-style-type: none"> ASC DESC
destinationServer.osVersion	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	<ul style="list-style-type: none"> ASC DESC
destinationServer.agentId	<ul style="list-style-type: none"> EQUALS NOT_EQUALS EQ NE CONTAINS NOT_CONTAINS 	<ul style="list-style-type: none"> String 	

Filter	Supported conditions	Supported values	Supported sorting
sourceProcess.configurationId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • ProcessId 	
sourceProcess.name	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
sourceProcess.commandLine	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
destinationProcess.configurationId	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE 	<ul style="list-style-type: none"> • ProcessId 	
destinationProcess.name	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC
destinationprocess.commandLine	<ul style="list-style-type: none"> • EQUALS • NOT_EQUALS • EQ • NE • CONTAINS • NOT_CONTAINS 	<ul style="list-style-type: none"> • String 	<ul style="list-style-type: none"> • ASC • DESC

Actions

The following actions are supported:

- [AssociateConfigurationItemsToApplication](#) (p. 15)
- [CreateApplication](#) (p. 17)
- [CreateTags](#) (p. 20)
- [DeleteApplications](#) (p. 23)
- [DeleteTags](#) (p. 25)
- [DescribeAgents](#) (p. 28)
- [DescribeConfigurations](#) (p. 32)
- [DescribeContinuousExports](#) (p. 35)
- [DescribeExportConfigurations](#) (p. 39)
- [DescribeExportTasks](#) (p. 42)
- [DescribeTags](#) (p. 46)
- [DisassociateConfigurationItemsFromApplication](#) (p. 50)
- [ExportConfigurations](#) (p. 52)
- [GetDiscoverySummary](#) (p. 54)
- [ListConfigurations](#) (p. 57)
- [ListServerNeighbors](#) (p. 61)
- [StartContinuousExport](#) (p. 65)
- [StartDataCollectionByAgentIds](#) (p. 68)
- [StartExportTask](#) (p. 71)
- [StopContinuousExport](#) (p. 75)
- [StopDataCollectionByAgentIds](#) (p. 78)
- [UpdateApplication](#) (p. 81)

AssociateConfigurationItemsToApplication

Associates one or more configuration items with an application.

Request Syntax

```
{  
  "applicationConfigurationId": "string",  
  "configurationIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

applicationConfigurationId (p. 15)

The configuration ID of an application with which items are to be associated.

Type: String

Required: Yes

configurationIds (p. 15)

The ID of each configuration item to be associated with an application.

Type: Array of strings

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Associate configuration items to an application

The following example associates two Application Discovery Service discovered resources specified by their configuration ids to the application identified by the value passed to the parameter `applicationConfigurationId` in the request.

Sample Request

```
{
  "applicationConfigurationId": "d-application-0039038d504694533",
  "configurationIds": [
    "d-server-0025db43a885966c8",
    "d-server-0f0a32a0db4217bd6"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

CreateApplication

Creates an application with the given name and description.

Request Syntax

```
{  
  "description": "string",  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

description (p. 17)

Description of the application to be created.

Type: String

Required: No

name (p. 17)

Name of the application to be created.

Type: String

Required: Yes

Response Syntax

```
{  
  "configurationId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

configurationId (p. 17)

Configuration ID of an application to be created.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Create an application

The following example creates an application specified by value passed the required parameter of `name` as well as a description passed to the optional parameter `description` in the request.

Sample Request

```
{
  "name": "PeopleSoft_phase1",
  "description": "components related to payroll app to be migrated"
}
```

Sample Response

```
{
  "configurationId": "d-application-0282ccd1ba7c211ca"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

CreateTags

Creates one or more tags for configuration items. Tags are metadata that help you categorize IT assets. This API accepts a list of multiple configuration items.

Request Syntax

```
{
  "configurationIds": [ "string" ],
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

configurationIds (p. 20)

A list of configuration items that you want to tag.

Type: Array of strings

Required: Yes

tags (p. 20)

Tags that you want to associate with one or more configuration items. Specify the tags that you want to create in a *key-value* format. For example:

```
{"key": "serverType", "value": "webServer"}
```

Type: Array of [Tag \(p. 102\)](#) objects

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified configuration ID was not located. Verify the configuration ID and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Create tags for configuration items

The following example creates two tags, each with a key/value pair, and associates both tags to two Application Discovery Service discovered resources specified by the values passed to the parameter `configurationIds` in the request.

Sample Request

```
{
  "configurationIds": [
    "d-server-08a4bce106f63340e",
    "d-server-04dadef51d0a728f3"
  ],
  "tags": [
    {
      "key": "ServerLocation",
      "value": "Warehouse"
    },
    {
      "key": "MigrationPhase",
      "value": "PH1"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteApplications

Deletes a list of applications and their associations with configuration items.

Request Syntax

```
{  
  "configurationIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

configurationIds (p. 23)

Configuration ID of an application to be deleted.

Type: Array of strings

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Delete applications

The following example deletes two applications as specified by the values passed to the parameter `configurationIds` in the request.

Sample Request

```
{
  "configurationIds": [
    "d-application-022b024aa42685464",
    "d-application-0ce38f881a50d2ac1"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DeleteTags

Deletes the association between configuration items and one or more tags. This API accepts a list of multiple configuration items.

Request Syntax

```
{
  "configurationIds": [ "string" ],
  "tags": [
    {
      "key": "string",
      "value": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

configurationIds (p. 25)

A list of configuration items with tags that you want to delete.

Type: Array of strings

Required: Yes

tags (p. 25)

Tags that you want to delete from one or more configuration items. Specify the tags that you want to delete in a *key-value* format. For example:

```
{"key": "serverType", "value": "webServer"}
```

Type: Array of [Tag \(p. 102\)](#) objects

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified configuration ID was not located. Verify the configuration ID and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Delete tags

The following example deletes a specific tag identified by its key/value pair from the server as specified by the values passed to the required parameter `configurationIds` in the request. Since the parameter `tags` is not required, just passing values to `configurationIds` would delete all tags associated with the identified server.

Sample Request

```
{
  "configurationIds": [
    "d-server-08a4bce106f63340e"
  ],
  "tags": [
    {
      "key": "ServerHostType",
      "value": "OracleProdDB"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)

- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeAgents

Lists agents or connectors as specified by ID or other filters. All agents/connectors associated with your user account can be listed if you call `DescribeAgents` as is without passing any parameters.

Request Syntax

```
{
  "agentIds": [ "string" ],
  "filters": [
    {
      "condition": "string",
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

agentIds (p. 28)

The agent or the Connector IDs for which you want information. If you specify no IDs, the system returns information about all agents/Connectors associated with your AWS user account.

Type: Array of strings

Required: No

filters (p. 28)

You can filter the request using various logical operators and a *key-value* format. For example:

```
{"key": "collectionStatus", "value": "STARTED"}
```

Type: Array of [Filter \(p. 99\)](#) objects

Required: No

maxResults (p. 28)

The total number of agents/Connectors to return in a single page of output. The maximum value is 100.

Type: Integer

Required: No

nextToken (p. 28)

Token to retrieve the next set of results. For example, if you previously specified 100 IDs for `DescribeAgentsRequest$agentIds` but set `DescribeAgentsRequest$maxResults` to 10, you received a set of 10 results along with a token. Use that token in this query to get the next set of 10.

Type: String

Required: No

Response Syntax

```
{
  "agentsInfo": [
    {
      "agentId": "string",
      "agentNetworkInfoList": [
        {
          "ipAddress": "string",
          "macAddress": "string"
        }
      ],
      "agentType": "string",
      "collectionStatus": "string",
      "connectorId": "string",
      "health": "string",
      "hostName": "string",
      "lastHealthPingTime": "string",
      "registeredTime": "string",
      "version": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

agentsInfo (p. 29)

Lists agents or the Connector by ID or lists all agents/Connectors associated with your user account if you did not specify an agent/Connector ID. The output includes agent/Connector IDs, IP addresses, media access control (MAC) addresses, agent/Connector health, host name where the agent/Connector resides, and the version number of each agent/Connector.

Type: Array of [AgentInfo](#) (p. 85) objects

nextToken (p. 29)

Token to retrieve the next set of results. For example, if you specified 100 IDs for `DescribeAgentsRequest$agentIds` but set `DescribeAgentsRequest$maxResults` to 10, you received a set of 10 results along with this token. Use this token in the next query to retrieve the next set of 10.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 106).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Describe agents that are running

The following example describes all agents that are currently running by passing object array values to the parameter `filters` where `condition` is "EQUALS", `name` is "health", and `value` is "RUNNING". This results in a descriptive response that lists all agents running in your account.

Sample Request

```
{
  "filters": [
    {
      "condition": "EQUALS",
      "name": "health",
      "values": [ "RUNNING" ]
    }
  ]
}
```

Sample Response

```
{
  "agentsInfo": [
    {
      "agentId": "o-55vu6xeo8zs27b905",
      "hostName": "ip-172-31-24-158.us-west-2.compute.internal",
      "agentNetworkInfoList": [
        {
          "ipAddress": "172.31.24.158",
          "macAddress": "02:7C:B6:F7:82:C4"
        }
      ],
      "version": "2.0.1008.0",
      "health": "RUNNING",
      "lastHealthPingTime": "2018-03-19T22:48:25Z",
      "collectionStatus": "STARTED",
      "agentType": "ONPREMISES",
    }
  ]
}
```

```
    "registeredTime": "2018-01-30T18:54:19Z"
  },
  {
    "agentId": "o-5i6fq7z1fhgokgreg",
    "hostName": "win-gv9i8gpt9t1",
    "agentNetworkInfoList": [
      {
        "ipAddress": "192.168.204.1",
        "macAddress": "00:50:56:C0:00:01"
      },
      {
        "ipAddress": "192.168.64.1",
        "macAddress": "00:50:56:C0:00:08"
      },
      {
        "ipAddress": "172.31.12.174",
        "macAddress": "0A:84:BB:BF:88:8E"
      }
    ],
    "version": "2.0.1008.0",
    "health": "RUNNING",
    "lastHealthPingTime": "2018-03-19T22:29:33Z",
    "collectionStatus": "STARTED",
    "agentType": "ONPREMISES",
    "registeredTime": "2018-03-16T23:54:19Z"
  }
]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeConfigurations

Retrieves attributes for a list of configuration item IDs.

Note

All of the supplied IDs must be for the same asset type from one of the following:

- server
- application
- process
- connection

Output fields are specific to the asset type specified. For example, the output for a *server* configuration item includes a list of attributes about the server, such as host name, operating system, number of network cards, etc.

For a complete list of outputs for each asset type, see [Using the DescribeConfigurations Action](#).

Request Syntax

```
{
  "configurationIds": [ "string" ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

configurationIds (p. 32)

One or more configuration IDs.

Type: Array of strings

Required: Yes

Response Syntax

```
{
  "configurations": [
    {
      "string": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[configurations \(p. 32\)](#)

A key in the response map. The value is an array of data.

Type: Array of string to string maps

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Describe configurations

The following example queries configuration descriptions of two applications as specified by the values passed to the parameter `configurationIds` in the request. Note that the configuration ID's passed meet the requirement that they represent the same asset type, in this example, *application*.

Sample Request

```
{
  "configurationIds": [
    "d-application-0282ccd1ba7c211ca",
    "d-application-034219054305e4a34"
  ]
}
```

Sample Response

```
{
```

```
"configurations": [  
  {  
    "application.configurationId": "d-application-0282ccd1ba7c211ca",  
    "application.description": "ads CreateApplication",  
    "application.lastModifiedTime": "2018-02-27 00:48:16.0",  
    "application.name": "adsdp2",  
    "application.serverCount": "2",  
    "application.timeOfCreation": "2018-02-27 00:48:16.0"  
  },  
  {  
    "application.configurationId": "d-application-034219054305e4a34",  
    "application.description": "ads CreateApplication place holder app",  
    "application.lastModifiedTime": "2018-02-27 23:33:32.0",  
    "application.name": "adsdp2_ph1",  
    "application.serverCount": "0",  
    "application.timeOfCreation": "2018-02-27 23:33:32.0"  
  }  
]  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeContinuousExports

Lists exports as specified by ID. All continuous exports associated with your user account can be listed if you call `DescribeContinuousExports` as is without passing any parameters.

Request Syntax

```
{
  "exportIds": [ "string" ],
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 104).

The request accepts the following data in JSON format.

exportIds (p. 35)

The unique IDs assigned to the exports.

Type: Array of strings

Required: No

maxResults (p. 35)

A number between 1 and 100 specifying the maximum number of continuous export descriptions returned.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

nextToken (p. 35)

The token from the previous call to `DescribeExportTasks`.

Type: String

Required: No

Response Syntax

```
{
  "descriptions": [
    {
      "dataSource": "string",
      "exportId": "string",
      "s3Bucket": "string",
      "schemaStorageConfig": {
        "string": "string"
      }
    }
  ]
}
```

```
    },  
    "startTime": number,  
    "status": "string",  
    "statusDetail": "string",  
    "stopTime": number  
  }  
],  
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

descriptions (p. 35)

A list of continuous export descriptions.

Type: Array of [ContinuousExportDescription \(p. 89\)](#) objects

nextToken (p. 35)

The token from the previous call to `DescribeExportTasks`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

OperationNotPermittedException

This operation is not permitted.

HTTP Status Code: 400

ResourceNotFoundException

The specified configuration ID was not located. Verify the configuration ID and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Describe a continuous export

The following example shows the request and response of describing a particular continuous export specified by passing in a value to `exportId` as well as other filtering parameters.

Sample Request

```
{
  "maxResults": 10,
  "nextToken":
  "rLH9RloHsWvY1sljKfLwlmHioorNIJJ1TC9MDO6HolpInQgsQKfk30Zu5n9YP59JZ5k5NzAqs6YerZWY",
  "exportIds": [
    "continuous-export-181b77c3-7jf3-4610-924e-7acafe5bbc59"
  ]
}
```

Sample Response

```
{
  "descriptions": [
    {
      "exportId": "continuous-export-181b77c3-7jf3-4610-924e-7acafe5bbc59",
      "status": "ACTIVE"
    },
    {
      "schemaStorageConfig": {
        "databaseName": "application_discovery_service_database"
      },
      "startTime": 1531248144.117,
      "exportId": "continuous-export-181b77c3-7jf3-4610-924e-7acafe5bbc59",
      "s3Bucket": "aws-application-discovery-service-92costafer5c9vn0qjane94mi",
      "status": "STOP_IN_PROGRESS",
      "stopTime": 1531248232.085,
      "statusDetail": "",
      "dataSource": "AGENT"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeExportConfigurations

DescribeExportConfigurations is deprecated.

Use instead [DescribeExportTasks](#) .

Request Syntax

```
{  
  "exportIds": [ "string" ],  
  "maxResults": number,  
  "nextToken": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

[exportIds \(p. 39\)](#)

A list of continuous export ids to search for.

Type: Array of strings

Required: No

[maxResults \(p. 39\)](#)

A number between 1 and 100 specifying the maximum number of continuous export descriptions returned.

Type: Integer

Required: No

[nextToken \(p. 39\)](#)

The token from the previous call to describe-export-tasks.

Type: String

Required: No

Response Syntax

```
{  
  "exportsInfo": [  
    {  
      "configurationsDownloadUrl": "string",  
      "exportId": "string",  
      "exportRequestTime": number,  
      "exportStatus": "string",  
      "isTruncated": boolean,  
      "requestedEndTime": number,  
      "requestedStartTime": number,  
    }  
  ]  
}
```

```
    "statusMessage": "string"  
  }  
],  
"nextToken": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[exportsInfo \(p. 39\)](#)

Type: Array of [ExportInfo \(p. 97\)](#) objects

[nextToken \(p. 39\)](#)

The token from the previous call to `describe-export-tasks`.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified configuration ID was not located. Verify the configuration ID and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeExportTasks

Retrieve status of one or more export tasks. You can retrieve the status of up to 100 export tasks.

Request Syntax

```
{
  "exportIds": [ "string" ],
  "filters": [
    {
      "condition": "string",
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters](#) (p. 104).

The request accepts the following data in JSON format.

exportIds (p. 42)

One or more unique identifiers used to query the status of an export request.

Type: Array of strings

Required: No

filters (p. 42)

One or more filters.

- `AgentId` - ID of the agent whose collected data will be exported

Type: Array of [ExportFilter](#) (p. 96) objects

Required: No

maxResults (p. 42)

The maximum number of volume results returned by `DescribeExportTasks` in paginated output. When this parameter is used, `DescribeExportTasks` only returns `maxResults` results in a single page along with a `nextToken` response element.

Type: Integer

Required: No

nextToken (p. 42)

The `nextToken` value returned from a previous paginated `DescribeExportTasks` request where `maxResults` was used and the results exceeded the value of that parameter. Pagination continues from the end of the previous results that returned the `nextToken` value. This value is null when there are no more results to return.

Type: String

Required: No

Response Syntax

```
{
  "exportsInfo": [
    {
      "configurationsDownloadUrl": "string",
      "exportId": "string",
      "exportRequestTime": number,
      "exportStatus": "string",
      "isTruncated": boolean,
      "requestedEndTime": number,
      "requestedStartTime": number,
      "statusMessage": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exportsInfo (p. 43)

Contains one or more sets of export request details. When the status of a request is `SUCCEEDED`, the response includes a URL for an Amazon S3 bucket where you can view the data in a CSV file.

Type: Array of [ExportInfo](#) (p. 97) objects

nextToken (p. 43)

The `nextToken` value to include in a future `DescribeExportTasks` request. When the results of a `DescribeExportTasks` request exceed `maxResults`, this value can be used to retrieve the next page of results. This value is null when there are no more results to return.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 106).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Retrieve status of two specified export tasks

Sample Request

```
POST / HTTP/1.1
Host: discovery.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 109
X-Amz-Target: AWSPoseidonService_V2015_11_01.DescribeExportTasks
X-Amz-Date: 20170308T232123Z
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "exportIds":[
    "export-123a4b56-7c89-01d2-3ef4-example5678f",
    "export-654a3b21-7c89-01d2-3ef4-example8765f"
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 1140
Date: Wed, 08 Mar 2017 23:21:25 GMT

{
  "exportsInfo":[
    {
      "configurationsDownloadUrl":"[URL]",
      "exportId":"export-123a4b56-7c89-01d2-3ef4-example5678f",
      "exportRequestTime":1.489001254713E9,
      "exportStatus":"SUCCEEDED",
    }
  ]
}
```

```
    "statusMessage":"Data export ran successfully and is accessible from the download
URL. The URL will expire in 24 hours. The export data expires in 10 days."
  },
  {
    "configurationsDownloadUrl":"[URL]",
    "exportId":"export-654a3b21-7c89-01d2-3ef4-example8765f",
    "exportRequestTime":1.488920016713E9,
    "exportStatus":"SUCCEEDED",
    "statusMessage":"Data export ran successfully and is accessible from the download
URL. The URL will expire in 24 hours. The export data expires in 10 days."
  }
],
"nextToken":""
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DescribeTags

Retrieves a list of configuration items that have tags as specified by the key-value pairs, name and value, passed to the optional parameter `filters`.

There are three valid tag filter names:

- `tagKey`
- `tagValue`
- `configurationId`

Also, all configuration items associated with your user account that have tags can be listed if you call `DescribeTags` as is without passing any parameters.

Request Syntax

```
{
  "filters": [
    {
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string"
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

filters (p. 46)

You can filter the list using a *key-value* format. You can separate these items by using logical operators. Allowed filters include `tagKey`, `tagValue`, and `configurationId`.

Type: Array of [TagFilter \(p. 103\)](#) objects

Required: No

maxResults (p. 46)

The total number of items to return in a single page of output. The maximum value is 100.

Type: Integer

Required: No

nextToken (p. 46)

A token to start the list. Use this token to get the next set of results.

Type: String

Required: No

Response Syntax

```
{
  "nextToken": "string",
  "tags": [
    {
      "configurationId": "string",
      "configurationType": "string",
      "key": "string",
      "timeOfCreation": number,
      "value": "string"
    }
  ]
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

nextToken (p. 47)

The call returns a token. Use this token to get the next set of results.

Type: String

tags (p. 47)

Depending on the input, this is a list of configuration items tagged with a specific tag, or a list of tags for a specific configuration item.

Type: Array of [ConfigurationTag](#) (p. 88) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 106).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified configuration ID was not located. Verify the configuration ID and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Describe tags that have a particular value

The following example lists configuration items associated with an agent installed on a linux server. This is done by passing object array values to the parameter `filters` where `name` is "tagValue" and `value` is "agent on linux server". This results in a descriptive response that lists configuration item details where the tag value is equal to the value specified in the request.

Sample Request

```
{
  "filters": [
    {
      "name": "tagValue",
      "values": [ "agent on linux server" ]
    }
  ]
}
```

Sample Response

```
{
  "tags": [
    {
      "configurationType": "SERVER",
      "configurationId": "d-server-0c269e353e6d1fb4c",
      "key": "dp2",
      "value": "agent on linux server",
      "timeOfCreation": 1519674610.0
    }
  ],
  "nextToken": "0039038d504694533"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

DisassociateConfigurationItemsFromApplication

Disassociates one or more configuration items from an application.

Request Syntax

```
{  
  "applicationConfigurationId": "string",  
  "configurationIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

applicationConfigurationId (p. 50)

Configuration ID of an application from which each item is disassociated.

Type: String

Required: Yes

configurationIds (p. 50)

Configuration ID of each item to be disassociated from an application.

Type: Array of strings

Required: Yes

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Disassociate configuration items from an application

The following example disassociates two Application Discovery Service discovered resources specified by their configuration ids from the application identified by the value passed to the required parameter `applicationConfigurationId` in the request.

Sample Request

```
{
  "applicationConfigurationId": "d-application-0039038d504694533",
  "configurationIds": [
    "d-server-0025db43a885966c8",
    "d-server-0f0a32a0db4217bd6"
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ExportConfigurations

Deprecated. Use `StartExportTask` instead.

Exports all discovered configuration data to an Amazon S3 bucket or an application that enables you to view and evaluate the data. Data includes tags and tag associations, processes, connections, servers, and system performance. This API returns an export ID that you can query using the `DescribeExportConfigurations` API. The system imposes a limit of two configuration exports in six hours.

Response Syntax

```
{  
  "exportId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

`exportId` (p. 52)

A unique identifier that you can use to query the export status.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

OperationNotPermittedException

This operation is not permitted.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

GetDiscoverySummary

Retrieves a short summary of discovered assets.

This API operation takes no request parameters and is called as is at the command prompt as shown in the example.

Response Syntax

```
{
  "agentSummary": {
    "activeAgents": number,
    "blackListedAgents": number,
    "healthyAgents": number,
    "shutdownAgents": number,
    "totalAgents": number,
    "unhealthyAgents": number,
    "unknownAgents": number
  },
  "applications": number,
  "connectorSummary": {
    "activeConnectors": number,
    "blackListedConnectors": number,
    "healthyConnectors": number,
    "shutdownConnectors": number,
    "totalConnectors": number,
    "unhealthyConnectors": number,
    "unknownConnectors": number
  },
  "servers": number,
  "serversMappedToApplications": number,
  "serversMappedtoTags": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

agentSummary (p. 54)

Details about discovered agents, including agent status and health.

Type: [CustomerAgentInfo](#) (p. 92) object

applications (p. 54)

The number of applications discovered.

Type: Long

connectorSummary (p. 54)

Details about discovered connectors, including connector status and health.

Type: [CustomerConnectorInfo](#) (p. 94) object

servers (p. 54)

The number of servers discovered.

Type: Long

serversMappedToApplications (p. 54)

The number of servers mapped to applications.

Type: Long

serversMappedtoTags (p. 54)

The number of servers mapped to tags.

Type: Long

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Get discovery summary of discovered assets

In the following example `GetDiscoverySummary` is called as is, without any request parameters, directly from the AWS CLI and returns a summary of all discovered assets associated with your account.

Sample Request

```
[1212|ttys000|510]$ aws discovery get-discovery-summary
```

Sample Response

```
{
  "servers": 1370,
  "applications": 125,
  "serversMappedToApplications": 212,
  "serversMappedtoTags": 213,
  "agentSummary": {
    "activeAgents": 3,
    "healthyAgents": 3,
    "blackListedAgents": 0,
    "shutdownAgents": 0,
    "unhealthyAgents": 0,
    "totalAgents": 16,
    "unknownAgents": 13
  },
  "connectorSummary": {
    "activeConnectors": 1,
    "healthyConnectors": 1,
    "blackListedConnectors": 0,
    "shutdownConnectors": 0,
    "unhealthyConnectors": 1,
    "totalConnectors": 2,
    "unknownConnectors": 0
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListConfigurations

Retrieves a list of configuration items as specified by the value passed to the required parameter `configurationType`. Optional filtering may be applied to refine search results.

Request Syntax

```
{
  "configurationType": "string",
  "filters": [
    {
      "condition": "string",
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "maxResults": number,
  "nextToken": "string",
  "orderBy": [
    {
      "fieldName": "string",
      "sortOrder": "string"
    }
  ]
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

`configurationType` (p. 57)

A valid configuration identified by Application Discovery Service.

Type: String

Valid Values: SERVER | PROCESS | CONNECTION | APPLICATION

Required: Yes

`filters` (p. 57)

You can filter the request using various logical operators and a *key-value* format. For example:

```
{"key": "serverType", "value": "webServer"}
```

For a complete list of filter options and guidance about using them with this action, see [Querying Discovered Configuration Items](#).

Type: Array of [Filter \(p. 99\)](#) objects

Required: No

`maxResults` (p. 57)

The total number of items to return. The maximum value is 100.

Type: Integer

Required: No

[nextToken \(p. 57\)](#)

Token to retrieve the next set of results. For example, if a previous call to `ListConfigurations` returned 100 items, but you set `ListConfigurationsRequest$maxResults` to 10, you received a set of 10 results along with a token. Use that token in this query to get the next set of 10.

Type: String

Required: No

[orderBy \(p. 57\)](#)

Certain filter criteria return output that can be sorted in ascending or descending order. For a list of output characteristics for each filter, see [Using the ListConfigurations Action](#).

Type: Array of [OrderByElement \(p. 101\)](#) objects

Required: No

Response Syntax

```
{
  "configurations": [
    {
      "string" : "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[configurations \(p. 58\)](#)

Returns configuration details, including the configuration ID, attribute names, and attribute values.

Type: Array of string to string maps

[nextToken \(p. 58\)](#)

Token to retrieve the next set of results. For example, if your call to `ListConfigurations` returned 100 items, but you set `ListConfigurationsRequest$maxResults` to 10, you received a set of 10 results along with this token. Use this token in the next query to retrieve the next set of 10.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ResourceNotFoundException

The specified configuration ID was not located. Verify the configuration ID and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

List configurations based on server type

The following example lists server configurations where the server type is an EC2 instance. This is done by passing the value "SERVER" to the required parameter `configurationType`. Then, to limit the results to just EC2 servers, object array values are passed to the parameter `filters` where `condition` is "EQUALS", `name` is "server.type", and `values` is "EC2". A sorting refinement is also used in this example by passing values to the parameter `orderBy` that sorts the results by the server's OS name in reverse alphabetical order.

Sample Request

```
{
  "configurationType": "SERVER",
  "filters": [
    {
      "condition": "EQUALS",
      "name": "server.type",
      "values": [ "EC2" ]
    }
  ],
  "orderBy": [
    {
      "fieldName": "server.osName",
      "sortOrder": "DESC"
    }
  ]
}
```

```
}
```

Sample Response

```
{
  "configurations": [
    {
      "server.agentId": "i-0adf772ed9f61445a",
      "server.configurationId": "d-server-062d1f42166d190a4",
      "server.hostName": "WIN-7092JH2AKNB",
      "server.osName": "WindowsOS - Windows Server 2012 R2 x64",
      "server.osVersion": "6.2.9200",
      "server.source": "Agent",
      "server.timeOfCreation": "2017-10-09 20:42:25.0",
      "server.type": "EC2"
    },
    {
      "server.agentId": "i-0243426187d59c9c3",
      "server.configurationId": "d-server-0fc7f9126ed1c2be7",
      "server.hostName": "ip-10-0-0-22.us-west-2.compute.internal",
      "server.osName": "Linux - Red Hat Enterprise Linux Server release 7.3 (Maipo)",
      "server.osVersion": "3.10.0-514.el7.x86_64",
      "server.source": "Agent",
      "server.timeOfCreation": "2017-04-06 19:58:15.0",
      "server.type": "EC2"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

ListServerNeighbors

Retrieves a list of servers that are one network hop away from a specified server.

Request Syntax

```
{  
  "configurationId": "string",  
  "maxResults": number,  
  "neighborConfigurationIds": [ "string" ],  
  "nextToken": "string",  
  "portInformationNeeded": boolean  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

configurationId (p. 61)

Configuration ID of the server for which neighbors are being listed.

Type: String

Required: Yes

maxResults (p. 61)

Maximum number of results to return in a single page of output.

Type: Integer

Required: No

neighborConfigurationIds (p. 61)

List of configuration IDs to test for one-hop-away.

Type: Array of strings

Required: No

nextToken (p. 61)

Token to retrieve the next set of results. For example, if you previously specified 100 IDs for `ListServerNeighborsRequest$neighborConfigurationIds` but set `ListServerNeighborsRequest$maxResults` to 10, you received a set of 10 results along with a token. Use that token in this query to get the next set of 10.

Type: String

Required: No

portInformationNeeded (p. 61)

Flag to indicate if port and protocol information is needed as part of the response.

Type: Boolean

Required: No

Response Syntax

```
{
  "knownDependencyCount": number,
  "neighbors": [
    {
      "connectionsCount": number,
      "destinationPort": number,
      "destinationServerId": "string",
      "sourceServerId": "string",
      "transportProtocol": "string"
    }
  ],
  "nextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

knownDependencyCount (p. 62)

Count of distinct servers that are one hop away from the given server.

Type: Long

neighbors (p. 62)

List of distinct servers that are one hop away from the given server.

Type: Array of [NeighborConnectionDetail](#) (p. 100) objects

nextToken (p. 62)

Token to retrieve the next set of results. For example, if you specified 100 IDs for `ListServerNeighborsRequest$neighborConfigurationIds` but set `ListServerNeighborsRequest$maxResults` to 10, you received a set of 10 results along with this token. Use this token in the next query to retrieve the next set of 10.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 106).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

List server neighbors

The following example requests to find out if there are any server neighbors that are one network hop away from the server specified in the required parameter `configurationId`. Port information is also requested by passing "true" to the boolean parameter `portInformationNeeded` (note that boolean parameters must be passed as all lowercase without any quotes). In this particular example, no server neighbors are found that are one network hop away.

Sample Request

```
{
  "configurationId": "d-server-0974b967a76335589",
  "neighborConfigurationIds": [ "d-server-0c269e353e6d1fb4c", "d-
server-01440c9c5df26ae50" ],
  "portInformationNeeded": true
}
```

Sample Response

```
{
  "neighbors": [],
  "knownDependencyCount": 0
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)

- [AWS SDK for Ruby V2](#)

StartContinuousExport

Start the continuous flow of agent's discovered data into Amazon Athena.

Response Syntax

```
{
  "dataSource": "string",
  "exportId": "string",
  "s3Bucket": "string",
  "schemaStorageConfig": {
    "string": "string"
  },
  "startTime": number
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

dataSource (p. 65)

The type of data collector used to gather this data (currently only offered for AGENT).

Type: String

Valid Values: `AGENT`

exportId (p. 65)

The unique ID assigned to this export.

Type: String

s3Bucket (p. 65)

The name of the s3 bucket where the export data parquet files are stored.

Type: String

schemaStorageConfig (p. 65)

A dictionary which describes how the data is stored.

- `databaseName` - the name of the Glue database used to store the schema.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 252.

startTime (p. 65)

The timestamp representing when the continuous export was started.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

ConflictErrorException

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

OperationNotPermittedException

This operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Start a continuous export

The following example shows the response of starting a continuous export.

Sample Response

```
{
  "startTime": 1531247730.19,
  "dataSource": "AGENT",
  "schemaStorageConfig": {
    "databaseName": "application_discovery_service_database"
  },
  "exportId": "continuous-export-181b77c3-7jf3-4610-924e-7acafe5bbc59",
  "s3Bucket": "aws-application-discovery-service-92costafer5c9vn0qjane94mi"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

StartDataCollectionByAgentIds

Instructs the specified agents or connectors to start collecting data.

Request Syntax

```
{  
  "agentIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

agentIds (p. 68)

The IDs of the agents or connectors from which to start collecting data. If you send a request to an agent/connector ID that you do not have permission to contact, according to your AWS account, the service does not throw an exception. Instead, it returns the error in the *Description* field. If you send a request to multiple agents/connectors and you do not have permission to contact some of those agents/connectors, the system does not throw an exception. Instead, the system shows `Failed` in the *Description* field.

Type: Array of strings

Required: Yes

Response Syntax

```
{  
  "agentsConfigurationStatus": [  
    {  
      "agentId": "string",  
      "description": "string",  
      "operationSucceeded": boolean  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

agentsConfigurationStatus (p. 68)

Information about agents or the connector that were instructed to start collecting data. Information includes the agent/connector ID, a description of the operation performed, and whether the agent/connector configuration was updated.

Type: Array of [AgentConfigurationStatus](#) (p. 84) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#) (p. 106).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Start data collection by agent ids for one connector and one agent

In the following example, multiple agent ids are passed to the required parameter `agentIds` to start one connector and one agent. In the response, the first agent id returned is reported as started successfully, in the second agent id returned, the description reads "Redundant" which means that a request was sent to start an agent that was already running.

Sample Request

```
{
  "agentIds": [ "c-a07gapohc6spvd165", "i-0afec73de85777dd0" ]
}
```

Sample Response

```
{
  "agentsConfigurationStatus": [
    {
      "agentId": "c-a07gapohc6spvd165",
      "operationSucceeded": true,

```

```
        "description": "Succeeded"
      },
      {
        "agentId": "i-0afec73de85777dd0",
        "operationSucceeded": false,
        "description": "Redundant"
      }
    ]
  }
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

StartExportTask

Begins the export of discovered data to an S3 bucket.

If you specify `agentIds` in a filter, the task exports up to 72 hours of detailed data collected by the identified Application Discovery Agent, including network, process, and performance details. A time range for exported agent data may be set by using `startTime` and `endTime`. Export of detailed agent data is limited to five concurrently running exports.

If you do not include an `agentIds` filter, summary data is exported that includes both AWS Agentless Discovery Connector data and summary data from AWS Discovery Agents. Export of summary data is limited to two exports per day.

Request Syntax

```
{
  "endTime": number,
  "exportDataFormat": [ "string" ],
  "filters": [
    {
      "condition": "string",
      "name": "string",
      "values": [ "string" ]
    }
  ],
  "startTime": number
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

[endTime \(p. 71\)](#)

The end timestamp for exported data from the single Application Discovery Agent selected in the filters. If no value is specified, exported data includes the most recent data collected by the agent.

Type: Timestamp

Required: No

[exportDataFormat \(p. 71\)](#)

The file format for the returned export data. Default value is CSV. **Note:** *The GRAPHML option has been deprecated.*

Type: Array of strings

Valid Values: CSV | GRAPHML

Required: No

[filters \(p. 71\)](#)

If a filter is present, it selects the single `agentId` of the Application Discovery Agent for which data is exported. The `agentId` can be found in the results of the `DescribeAgents` API or CLI. If no

filter is present, `startTime` and `endTime` are ignored and exported data includes both Agentless Discovery Connector data and summary data from Application Discovery agents.

Type: Array of [ExportFilter \(p. 96\)](#) objects

Required: No

startTime (p. 71)

The start timestamp for exported data from the single Application Discovery Agent selected in the filters. If no value is specified, data is exported starting from the first data collected by the agent.

Type: Timestamp

Required: No

Response Syntax

```
{  
  "exportId": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

exportId (p. 72)

A unique identifier used to query the status of an export request.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

OperationNotPermittedException

This operation is not permitted.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

In the following example or examples, the Authorization header contents (AUTHPARAMS) must be replaced with an AWS Signature Version 4 signature. For more information about creating these signatures, see [Signature Version 4 Signing Process](#) in the *AWS General Reference*.

You only need to learn how to sign HTTP requests if you intend to manually create them. When you use the [AWS Command Line Interface \(AWS CLI\)](#) or one of the [AWS SDKs](#) to make requests to AWS, these tools automatically sign the requests for you with the access key that you specify when you configure the tools. When you use these tools, you don't need to learn how to sign requests yourself.

Start an export task of summary data filtering for an agentId and a time range

Sample Request

```
POST / HTTP/1.1
Host: discovery.us-west-2.amazonaws.com
Accept-Encoding: identity
Content-Length: 141
X-Amz-Target: AWSPoseidonService_V2015_11_01.StartExportTask
X-Amz-Date: 20170711T004454Z
Content-Type: application/x-amz-json-1.1
Authorization: AUTHPARAMS

{
  "endTime":1499601600,
  "startTime":1499428800,
  "filters":[
    {
      "values":[
        "i-06ea7f227a9ad1b86"
      ],
      "name":"agentIds",
      "condition":"EQUALS"
    }
  ]
}
```

Sample Response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 123a4b56-7c89-01d2-3ef4-example5678f
Content-Type: application/x-amz-json-1.1
Content-Length: 58
Date: Tue, 11 Jul 2017 00:44:54 GMT
```

```
{  
  "exportId": "export-123a4b56-7c89-01d2-3ef4-example5678f"  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

StopContinuousExport

Stop the continuous flow of agent's discovered data into Amazon Athena.

Request Syntax

```
{  
  "exportId": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

exportId (p. 75)

The unique ID assigned to this export.

Type: String

Required: Yes

Response Syntax

```
{  
  "startTime": number,  
  "stopTime": number  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

startTime (p. 75)

Timestamp that represents when this continuous export started collecting data.

Type: Timestamp

stopTime (p. 75)

Timestamp that represents when this continuous export was stopped.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

OperationNotPermittedException

This operation is not permitted.

HTTP Status Code: 400

ResourceInUseException

HTTP Status Code: 400

ResourceNotFoundException

The specified configuration ID was not located. Verify the configuration ID and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Stop a continuous export.

The following example shows the request and response of stopping a particular continuous export specified by passing in a value to `exportId`.

Sample Request

```
{
  "exportId": "continuous-export-181b77c3-7jf3-4610-924e-7acafe5bbc59"
}
```

Sample Response

```
{
  "ApplicationStatus": "IN_PROGRESS",
}
```

```
"LastUpdatedTime": 1493405005.639  
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

StopDataCollectionByAgentIds

Instructs the specified agents or connectors to stop collecting data.

Request Syntax

```
{  
  "agentIds": [ "string" ]  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

agentIds (p. 78)

The IDs of the agents or connectors from which to stop collecting data.

Type: Array of strings

Required: Yes

Response Syntax

```
{  
  "agentsConfigurationStatus": [  
    {  
      "agentId": "string",  
      "description": "string",  
      "operationSucceeded": boolean  
    }  
  ]  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

agentsConfigurationStatus (p. 78)

Information about the agents or connector that were instructed to stop collecting data. Information includes the agent/connector ID, a description of the operation performed, and whether the agent/connector configuration was updated.

Type: Array of [AgentConfigurationStatus \(p. 84\)](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Stop data collection by agent ids for two agents

In the following example, multiple agent ids are passed to the required parameter `agentIds` to stop two agents. In the response, it is reported that both agents were stopped successfully.

Sample Request

```
{
  "agentIds": [ "i-0afec73de85777dd0", "i-0b30b932b328cbd73" ]
}
```

Sample Response

```
{
  "agentsConfigurationStatus": [
    {
      "agentId": "i-0afec73de85777dd0",
      "operationSucceeded": true,
      "description": "Succeeded"
    },
    {
      "agentId": "i-0b30b932b328cbd73",
      "operationSucceeded": true,
      "description": "Succeeded"
    }
  ]
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

UpdateApplication

Updates metadata about an application.

Request Syntax

```
{  
  "configurationId": "string",  
  "description": "string",  
  "name": "string"  
}
```

Request Parameters

For information about the parameters that are common to all actions, see [Common Parameters \(p. 104\)](#).

The request accepts the following data in JSON format.

configurationId (p. 81)

Configuration ID of the application to be updated.

Type: String

Required: Yes

description (p. 81)

New description of the application to be updated.

Type: String

Required: No

name (p. 81)

New name of the application to be updated.

Type: String

Required: No

Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors \(p. 106\)](#).

AuthorizationErrorException

The AWS user account does not have permission to perform the action. Check the IAM policy associated with this account.

HTTP Status Code: 400

InvalidParameterException

One or more parameters are not valid. Verify the parameters and try again.

HTTP Status Code: 400

InvalidParameterValueException

The value of one or more parameters are either invalid or out of range. Verify the parameter values and try again.

HTTP Status Code: 400

ServerInternalErrorException

The server experienced an internal error. Try again.

HTTP Status Code: 500

Example

Update application name and description

In the following example, both the name and the description are changed (updated) of an existing application. The application is identified by passing the application id to the required parameter `configurationId`.

Sample Request

```
{
  "configurationId": "d-application-03767f7bddd6c0531",
  "description": "PSoft financials db migration",
  "name": "payroll_db_migration"
}
```

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for JavaScript](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V2](#)

Data Types

The AWS Application Discovery Service API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [AgentConfigurationStatus](#) (p. 84)
- [AgentInfo](#) (p. 85)
- [AgentNetworkInfo](#) (p. 87)
- [ConfigurationTag](#) (p. 88)
- [ContinuousExportDescription](#) (p. 89)
- [CustomerAgentInfo](#) (p. 92)
- [CustomerConnectorInfo](#) (p. 94)
- [ExportFilter](#) (p. 96)
- [ExportInfo](#) (p. 97)
- [Filter](#) (p. 99)
- [NeighborConnectionDetail](#) (p. 100)
- [OrderByElement](#) (p. 101)
- [Tag](#) (p. 102)
- [TagFilter](#) (p. 103)

AgentConfigurationStatus

Information about agents or connectors that were instructed to start collecting data. Information includes the agent/connector ID, a description of the operation, and whether the agent/connector configuration was updated.

Contents

agentId

The agent/connector ID.

Type: String

Required: No

description

A description of the operation performed.

Type: String

Required: No

operationSucceeded

Information about the status of the `startDataCollection` and `stopDataCollection` operations. The system has recorded the data collection operation. The agent/connector receives this command the next time it polls for a new command.

Type: Boolean

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

AgentInfo

Information about agents or connectors associated with the user's AWS account. Information includes agent or connector IDs, IP addresses, media access control (MAC) addresses, agent or connector health, hostname where the agent or connector resides, and agent version for each agent.

Contents

agentId

The agent or connector ID.

Type: String

Required: No

agentNetworkInfoList

Network details about the host where the agent or connector resides.

Type: Array of [AgentNetworkInfo \(p. 87\)](#) objects

Required: No

agentType

Type of agent.

Type: String

Required: No

collectionStatus

Status of the collection process for an agent or connector.

Type: String

Required: No

connectorId

The ID of the connector.

Type: String

Required: No

health

The health of the agent or connector.

Type: String

Valid Values: `HEALTHY` | `UNHEALTHY` | `RUNNING` | `UNKNOWN` | `BLACKLISTED` | `SHUTDOWN`

Required: No

hostName

The name of the host where the agent or connector resides. The host can be a server or virtual machine.

Type: String

Required: No

lastHealthPingTime

Time since agent or connector health was reported.

Type: String

Required: No

registeredTime

Agent's first registration timestamp in UTC.

Type: String

Required: No

version

The agent or connector version.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

AgentNetworkInfo

Network details about the host where the agent/connector resides.

Contents

ipAddress

The IP address for the host where the agent/connector resides.

Type: String

Required: No

macAddress

The MAC address for the host where the agent/connector resides.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ConfigurationTag

Tags for a configuration item. Tags are metadata that help you categorize IT assets.

Contents

configurationId

The configuration ID for the item to tag. You can specify a list of keys and values.

Type: String

Required: No

configurationType

A type of IT asset to tag.

Type: String

Valid Values: `SERVER` | `PROCESS` | `CONNECTION` | `APPLICATION`

Required: No

key

A type of tag on which to filter. For example, *serverType*.

Type: String

Required: No

timeOfCreation

The time the configuration tag was created in Coordinated Universal Time (UTC).

Type: Timestamp

Required: No

value

A value on which to filter. For example *key = serverType* and *value = web server*.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ContinuousExportDescription

A list of continuous export descriptions.

Contents

dataSource

The type of data collector used to gather this data (currently only offered for AGENT).

Type: String

Valid Values: `AGENT`

Required: No

exportId

The unique ID assigned to this export.

Type: String

Required: No

s3Bucket

The name of the s3 bucket where the export data parquet files are stored.

Type: String

Required: No

schemaStorageConfig

An object which describes how the data is stored.

- `databaseName` - the name of the Glue database used to store the schema.

Type: String to string map

Key Length Constraints: Minimum length of 1. Maximum length of 252.

Required: No

startTime

The timestamp representing when the continuous export was started.

Type: Timestamp

Required: No

status

Describes the status of the export. Can be one of the following values:

- `START_IN_PROGRESS` - setting up resources to start continuous export.
- `START_FAILED` - an error occurred setting up continuous export. To recover, call `start-continuous-export` again.
- `ACTIVE` - data is being exported to the customer bucket.
- `ERROR` - an error occurred during export. To fix the issue, call `stop-continuous-export` and `start-continuous-export`.
- `STOP_IN_PROGRESS` - stopping the export.

- `STOP_FAILED` - an error occurred stopping the export. To recover, call `stop-continuous-export` again.
- `INACTIVE` - the continuous export has been stopped. Data is no longer being exported to the customer bucket.

Type: String

Valid Values: `START_IN_PROGRESS` | `START_FAILED` | `ACTIVE` | `ERROR` | `STOP_IN_PROGRESS` | `STOP_FAILED` | `INACTIVE`

Required: No

statusDetail

Contains information about any errors that have occurred. This data type can have the following values:

- `ACCESS_DENIED` - You don't have permission to start Data Exploration in Amazon Athena. Contact your AWS administrator for help. For more information, see [Setting Up AWS Application Discovery Service](#) in the Application Discovery Service User Guide.
- `DELIVERY_STREAM_LIMIT_FAILURE` - You reached the limit for Amazon Kinesis Data Firehose delivery streams. Reduce the number of streams or request a limit increase and try again. For more information, see [Kinesis Data Streams Limits](#) in the Amazon Kinesis Data Streams Developer Guide.
- `FIREHOSE_ROLE_MISSING` - The Data Exploration feature is in an error state because your IAM User is missing the `AWSApplicationDiscoveryServiceFirehose` role. Turn on Data Exploration in Amazon Athena and try again. For more information, see [Step 3: Provide Application Discovery Service Access to Non-Administrator Users by Attaching Policies](#) in the Application Discovery Service User Guide.
- `FIREHOSE_STREAM_DOES_NOT_EXIST` - The Data Exploration feature is in an error state because your IAM User is missing one or more of the Kinesis data delivery streams.
- `INTERNAL_FAILURE` - The Data Exploration feature is in an error state because of an internal failure. Try again later. If this problem persists, contact AWS Support.
- `S3_BUCKET_LIMIT_FAILURE` - You reached the limit for Amazon S3 buckets. Reduce the number of Amazon S3 buckets or request a limit increase and try again. For more information, see [Bucket Restrictions and Limitations](#) in the Amazon Simple Storage Service Developer Guide.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 255.

Required: No

stopTime

The timestamp that represents when this continuous export was stopped.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)

- [AWS SDK for Ruby V2](#)

CustomerAgentInfo

Inventory data for installed discovery agents.

Contents

activeAgents

Number of active discovery agents.

Type: Integer

Required: Yes

blackListedAgents

Number of blacklisted discovery agents.

Type: Integer

Required: Yes

healthyAgents

Number of healthy discovery agents

Type: Integer

Required: Yes

shutdownAgents

Number of discovery agents with status SHUTDOWN.

Type: Integer

Required: Yes

totalAgents

Total number of discovery agents.

Type: Integer

Required: Yes

unhealthyAgents

Number of unhealthy discovery agents.

Type: Integer

Required: Yes

unknownAgents

Number of unknown discovery agents.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

CustomerConnectorInfo

Inventory data for installed discovery connectors.

Contents

activeConnectors

Number of active discovery connectors.

Type: Integer

Required: Yes

blackListedConnectors

Number of blacklisted discovery connectors.

Type: Integer

Required: Yes

healthyConnectors

Number of healthy discovery connectors.

Type: Integer

Required: Yes

shutdownConnectors

Number of discovery connectors with status SHUTDOWN,

Type: Integer

Required: Yes

totalConnectors

Total number of discovery connectors.

Type: Integer

Required: Yes

unhealthyConnectors

Number of unhealthy discovery connectors.

Type: Integer

Required: Yes

unknownConnectors

Number of unknown discovery connectors.

Type: Integer

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ExportFilter

Used to select which agent's data is to be exported. A single agent ID may be selected for export using the [StartExportTask](#) action.

Contents

condition

Supported condition: `EQUALS`

Type: String

Required: Yes

name

A single `ExportFilter` name. Supported filters: `agentId`.

Type: String

Required: Yes

values

A single `agentId` for a Discovery Agent. An `agentId` can be found using the [DescribeAgents](#) action. Typically an ADS `agentId` is in the form `o-0123456789abcdef0`.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

ExportInfo

Information regarding the export status of discovered data. The value is an array of objects.

Contents

configurationsDownloadUrl

A URL for an Amazon S3 bucket where you can review the exported data. The URL is displayed only if the export succeeded.

Type: String

Required: No

exportId

A unique identifier used to query an export.

Type: String

Required: Yes

exportRequestTime

The time that the data export was initiated.

Type: Timestamp

Required: Yes

exportStatus

The status of the data export job.

Type: String

Valid Values: `FAILED` | `SUCCEEDED` | `IN_PROGRESS`

Required: Yes

isTruncated

If true, the export of agent information exceeded the size limit for a single export and the exported data is incomplete for the requested time range. To address this, select a smaller time range for the export by using `startDate` and `endDate`.

Type: Boolean

Required: No

requestedEndTime

The `endTime` used in the `StartExportTask` request. If no `endTime` was requested, this result does not appear in `ExportInfo`.

Type: Timestamp

Required: No

requestedStartTime

The value of `startTime` parameter in the `StartExportTask` request. If no `startTime` was requested, this result does not appear in `ExportInfo`.

Type: Timestamp

Required: No

statusMessage

A status message provided for API callers.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Filter

A filter that can use conditional operators.

For more information about filters, see [Querying Discovered Configuration Items](#).

Contents

condition

A conditional operator. The following operators are valid: EQUALS, NOT_EQUALS, CONTAINS, NOT_CONTAINS. If you specify multiple filters, the system utilizes all filters as though concatenated by *AND*. If you specify multiple values for a particular filter, the system differentiates the values using *OR*. Calling either *DescribeConfigurations* or *ListConfigurations* returns attributes of matching configuration items.

Type: String

Required: Yes

name

The name of the filter.

Type: String

Required: Yes

values

A string value on which to filter. For example, if you choose the `destinationServer.osVersion` filter name, you could specify `Ubuntu` for the value.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

NeighborConnectionDetail

Details about neighboring servers.

Contents

connectionsCount

The number of open network connections with the neighboring server.

Type: Long

Required: Yes

destinationPort

The destination network port for the connection.

Type: Integer

Required: No

destinationServerId

The ID of the server that accepted the network connection.

Type: String

Required: Yes

sourceServerId

The ID of the server that opened the network connection.

Type: String

Required: Yes

transportProtocol

The network protocol used for the connection.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

OrderByElement

A field and direction for ordered output.

Contents

fieldName

The field on which to order.

Type: String

Required: Yes

sortOrder

Ordering direction.

Type: String

Valid Values: `ASC` | `DESC`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Tag

Metadata that help you categorize IT assets.

Contents

key

The type of tag on which to filter.

Type: String

Required: Yes

value

A value for a tag key on which to filter.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

TagFilter

The tag filter. Valid names are: `tagKey`, `tagValue`, `configurationId`.

Contents

name

A name of the tag filter.

Type: String

Required: Yes

values

Values for the tag filter.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Go](#)
- [AWS SDK for Java](#)
- [AWS SDK for Ruby V2](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signature Version 4 Signing Process](#) in the *Amazon Web Services General Reference*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: `AWS4-HMAC-SHA256`

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: `access_key/YYYYMMDD/region/service/aws4_request`.

For more information, see [Task 2: Create a String to Sign for Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'THHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: `20120325T120000Z`.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is

not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Handling Dates in Signature Version 4](#) in the *Amazon Web Services General Reference*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS Security Token Service, go to [AWS Services That Work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from the AWS Security Token Service, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Task 1: Create a Canonical Request For Signature Version 4](#) in the *Amazon Web Services General Reference*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

InvalidParameterCombination

Parameters that must not be used together were used together.

HTTP Status Code: 400

InvalidParameterValue

An invalid or out-of-range value was supplied for the input parameter.

HTTP Status Code: 400

InvalidQueryParameter

The AWS query string is malformed or does not adhere to AWS standards.

HTTP Status Code: 400

MalformedQueryString

The query string contains a syntax error.

HTTP Status Code: 404

MissingAction

The request is missing an action or a required parameter.

HTTP Status Code: 400

MissingAuthenticationToken

The request must contain either a valid (registered) AWS access key ID or X.509 certificate.

HTTP Status Code: 403

MissingParameter

A required parameter for the specified action is not supplied.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400