



????

# AWS Migration Hub



API 版本 2017-05-31

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

# AWS Migration Hub: ????

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

# Table of Contents

Welcome .....	1
Actions .....	2
AssociateCreatedArtifact .....	3
Request Syntax .....	3
Request Parameters .....	3
Response Elements .....	4
Errors .....	4
Examples .....	6
See Also .....	6
AssociateDiscoveredResource .....	8
Request Syntax .....	8
Request Parameters .....	8
Response Elements .....	9
Errors .....	9
Examples .....	11
See Also .....	11
CreateProgressUpdateStream .....	12
Request Syntax .....	12
Request Parameters .....	12
Response Elements .....	12
Errors .....	13
Examples .....	14
See Also .....	14
DeleteProgressUpdateStream .....	15
Request Syntax .....	15
Request Parameters .....	15
Response Elements .....	16
Errors .....	16
Examples .....	17
See Also .....	18
DescribeApplicationState .....	19
Request Syntax .....	19
Request Parameters .....	19
Response Syntax .....	19

Response Elements .....	19
Errors .....	20
Examples .....	21
See Also .....	22
DescribeMigrationTask .....	23
Request Syntax .....	23
Request Parameters .....	23
Response Syntax .....	23
Response Elements .....	24
Errors .....	24
Examples .....	25
See Also .....	26
DisassociateCreatedArtifact .....	27
Request Syntax .....	27
Request Parameters .....	27
Response Elements .....	28
Errors .....	28
Examples .....	30
See Also .....	30
DisassociateDiscoveredResource .....	32
Request Syntax .....	32
Request Parameters .....	32
Response Elements .....	33
Errors .....	33
Examples .....	34
See Also .....	35
ImportMigrationTask .....	36
Request Syntax .....	36
Request Parameters .....	36
Response Elements .....	37
Errors .....	37
Examples .....	38
See Also .....	39
ListApplicationStates .....	40
Request Syntax .....	40
Request Parameters .....	40

---

Response Syntax .....	41
Response Elements .....	41
Errors .....	42
See Also .....	43
ListCreatedArtifacts .....	44
Request Syntax .....	44
Request Parameters .....	44
Response Syntax .....	45
Response Elements .....	45
Errors .....	46
Examples .....	47
See Also .....	48
ListDiscoveredResources .....	49
Request Syntax .....	49
Request Parameters .....	49
Response Syntax .....	50
Response Elements .....	50
Errors .....	51
Examples .....	52
See Also .....	53
ListMigrationTasks .....	54
Request Syntax .....	54
Request Parameters .....	54
Response Syntax .....	55
Response Elements .....	55
Errors .....	56
Examples .....	57
See Also .....	58
ListProgressUpdateStreams .....	59
Request Syntax .....	59
Request Parameters .....	59
Response Syntax .....	59
Response Elements .....	60
Errors .....	60
Examples .....	61
See Also .....	62

---

NotifyApplicationState .....	63
Request Syntax .....	63
Request Parameters .....	63
Response Elements .....	64
Errors .....	64
Examples .....	66
See Also .....	66
NotifyMigrationTaskState .....	68
Request Syntax .....	68
Request Parameters .....	68
Response Elements .....	70
Errors .....	70
Examples .....	71
See Also .....	72
PutResourceAttributes .....	73
Request Syntax .....	73
Request Parameters .....	74
Response Elements .....	75
Errors .....	75
Examples .....	77
See Also .....	77
Data Types .....	79
ApplicationState .....	80
Contents .....	80
See Also .....	80
CreatedArtifact .....	82
Contents .....	82
See Also .....	82
DiscoveredResource .....	83
Contents .....	83
See Also .....	83
MigrationTask .....	84
Contents .....	84
See Also .....	85
MigrationTaskSummary .....	86
Contents .....	86

---

See Also .....	87
ProgressUpdateStreamSummary .....	88
Contents .....	88
See Also .....	88
ResourceAttribute .....	89
Contents .....	89
See Also .....	90
Task .....	91
Contents .....	91
See Also .....	91

# Welcome

The AWS Migration Hub API methods help to obtain server and application migration status and integrate your resource-specific migration tool by providing a programmatic interface to Migration Hub.

Remember that you must set your AWS Migration Hub home region before you call any of these APIs, or a `HomeRegionNotSetException` error will be returned. Also, you must make the API calls while in your home region.

This document was last published on April 27, 2024.



# Actions

The following actions are supported:

- [AssociateCreatedArtifact](#)
- [AssociateDiscoveredResource](#)
- [CreateProgressUpdateStream](#)
- [DeleteProgressUpdateStream](#)
- [DescribeApplicationState](#)
- [DescribeMigrationTask](#)
- [DisassociateCreatedArtifact](#)
- [DisassociateDiscoveredResource](#)
- [ImportMigrationTask](#)
- [ListApplicationStates](#)
- [ListCreatedArtifacts](#)
- [ListDiscoveredResources](#)
- [ListMigrationTasks](#)
- [ListProgressUpdateStreams](#)
- [NotifyApplicationState](#)
- [NotifyMigrationTaskState](#)
- [PutResourceAttributes](#)

# AssociateCreatedArtifact

Associates a created artifact of an AWS cloud resource, the target receiving the migration, with the migration task performed by a migration tool. This API has the following traits:

- Migration tools can call the `AssociateCreatedArtifact` operation to indicate which AWS artifact is associated with a migration task.
- The created artifact name must be provided in ARN (Amazon Resource Name) format which will contain information about type and region; for example: `arn:aws:ec2:us-east-1:488216288981:image/ami-6d0ba87b`.
- Examples of the AWS resource behind the created artifact are, AMI's, EC2 instance, or DMS endpoint, etc.

## Request Syntax

```
{
  "CreatedArtifact": {
    "Description": "string",
    "Name": "string"
  },
  "DryRun": boolean,
  "MigrationTaskName": "string",
  "ProgressUpdateStream": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CreatedArtifact

An ARN of the AWS resource related to the migration (e.g., AMI, EC2 instance, RDS instance, etc.)

Type: [CreatedArtifact](#) object

Required: Yes

## DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

## MigrationTaskName

Unique identifier that references the migration task. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: Yes

## ProgressUpdateStream

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

## DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

## HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

## InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

## InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

## ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## UnauthorizedOperation

Exception raised to indicate a request was not authorized when the DryRun flag is set to "true".

HTTP Status Code: 400

## Examples

### Associate a created artifact

The following example associates an AWS resource to the migration task identified by the values passed to the required parameters of `MigrationTaskName` and `ProgressUpdateStream` in the request.

### Sample Request

```
{
  "CreatedArtifact": [
    {
      "Description": "Using SMS to migrate server to EC2",
      "Name": "arn:aws:ec2:us-east-1:488216288981:image/ami-6d0ba87b"
    }
  ],
  "DryRun": false,
  "MigrationTaskName": "sms-12de3cf1a",
  "ProgressUpdateStream": "SMS"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# AssociateDiscoveredResource

Associates a discovered resource ID from Application Discovery Service with a migration task.

## Request Syntax

```
{
  "DiscoveredResource": {
    "ConfigurationId": "string",
    "Description": "string"
  },
  "DryRun": boolean,
  "MigrationTaskName": "string",
  "ProgressUpdateStream": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DiscoveredResource

Object representing a Resource.

Type: [DiscoveredResource](#) object

Required: Yes

### DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

### MigrationTaskName

The identifier given to the MigrationTask. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: Yes

### ProgressUpdateStream

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.



HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### PolicyErrorException

Exception raised when there are problems accessing Application Discovery Service (Application Discovery Service); most likely due to a misconfigured policy or the `migrationhub-discovery` role is missing or not configured correctly.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

### UnauthorizedOperation

Exception raised to indicate a request was not authorized when the `DryRun` flag is set to "true".

HTTP Status Code: 400

## Examples

### Associate a discovered resource

The following example associates an AWS Application Discovery Service discovered resource specified by its configuration id and description to the migration task identified by the values passed to the required parameters of `MigrationTaskName` and `ProgressUpdateStream` in the request.

#### Sample Request

```
{
  "ProgressUpdateStream": "SMS",
  "MigrationTaskName": "sms-12de3cf1a",
  "DiscoveredResource": {
    "ConfigurationId": "d-server-0025db43a885966c8",
    "Description": "Amazon Linux AMI release 2016.09"
  }
}
```

### See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# CreateProgressUpdateStream

Creates a progress update stream which is an AWS resource used for access control as well as a namespace for migration task names that is implicitly linked to your AWS account. It must uniquely identify the migration tool as it is used for all updates made by the tool; however, it does not need to be unique for each AWS account because it is scoped to the AWS account.

## Request Syntax

```
{  
  "DryRun": boolean,  
  "ProgressUpdateStreamName": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [DryRun](#)

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

### [ProgressUpdateStreamName](#)

The name of the ProgressUpdateStream. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[^/:|\000-\037]+`

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

### UnauthorizedOperation

Exception raised to indicate a request was not authorized when the DryRun flag is set to "true".

HTTP Status Code: 400

## Examples

### Create a progress update stream

The following example creates a progress update stream identified by the values passed to the required parameter `ProgressUpdateStreamName` in the request.

#### Sample Request

```
{
  "ProgressUpdateStreamName": "SMS",
  "DryRun": false
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DeleteProgressUpdateStream

Deletes a progress update stream, including all of its tasks, which was previously created as an AWS resource used for access control. This API has the following traits:

- The only parameter needed for `DeleteProgressUpdateStream` is the stream name (same as a `CreateProgressUpdateStream` call).
- The call will return, and a background process will asynchronously delete the stream and all of its resources (tasks, associated resources, resource attributes, created artifacts).
- If the stream takes time to be deleted, it might still show up on a `ListProgressUpdateStreams` call.
- `CreateProgressUpdateStream`, `ImportMigrationTask`, `NotifyMigrationTaskState`, and all `Associate[*]` APIs related to the tasks belonging to the stream will throw `"InvalidInputException"` if the stream of the same name is in the process of being deleted.
- Once the stream and all of its resources are deleted, `CreateProgressUpdateStream` for a stream of the same name will succeed, and that stream will be an entirely new logical resource (without any resources associated with the old stream).

## Request Syntax

```
{
  "DryRun": boolean,
  "ProgressUpdateStreamName": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

## ProgressUpdateStreamName

The name of the ProgressUpdateStream. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

### UnauthorizedOperation

Exception raised to indicate a request was not authorized when the `DryRun` flag is set to "true".

HTTP Status Code: 400

## Examples

### Delete a progress update stream

The following example deletes a progress update stream identified by the values passed to the required parameter `ProgressUpdateStreamName` in the request.

#### Sample Request

```
{
  "ProgressUpdateStreamName": "SMS",
  "DryRun": false
}
```



## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeApplicationState

Gets the migration status of an application.

## Request Syntax

```
{  
  "ApplicationId": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [ApplicationId](#)

The configurationId in Application Discovery Service that uniquely identifies the grouped application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^\.{1,1600}$`

Required: Yes

## Response Syntax

```
{  
  "ApplicationStatus": "string",  
  "LastUpdatedTime": number  
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

## ApplicationStatus

Status of the application - Not Started, In-Progress, Complete.

Type: String

Valid Values: NOT\_STARTED | IN\_PROGRESS | COMPLETED

## LastUpdatedTime

The timestamp when the application status was last updated.

Type: Timestamp

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### PolicyErrorException

Exception raised when there are problems accessing Application Discovery Service (Application Discovery Service); most likely due to a misconfigured policy or the migrationhub-discovery role is missing or not configured correctly.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## Examples

### Describe a migration task by listing all associated attributes

The following example lists all of the attributes associated with the values passed to the required parameters of `MigrationTaskName` and `ProgressUpdateStream`.

#### Sample Request

```
{
  "ApplicationId": "d-application-0039038d504694533"
}
```

#### Sample Response

```
{
  "ApplicationStatus": "IN_PROGRESS",
  "LastUpdatedTime": 1493405005.639
}
```

```
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DescribeMigrationTask

Retrieves a list of all attributes associated with a specific migration task.

## Request Syntax

```
{  
  "MigrationTaskName": "string",  
  "ProgressUpdateStream": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### MigrationTaskName

The identifier given to the MigrationTask. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: Yes

### ProgressUpdateStream

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

## Response Syntax

```
{
```

```
"MigrationTask": {
  "MigrationTaskName": "string",
  "ProgressUpdateStream": "string",
  "ResourceAttributeList": [
    {
      "Type": "string",
      "Value": "string"
    }
  ],
  "Task": {
    "ProgressPercent": number,
    "Status": "string",
    "StatusDetail": "string"
  },
  "UpdateDateTime": number
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### MigrationTask

Object encapsulating information about the migration task.

Type: [MigrationTask](#) object

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

## InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

## InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

## ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## Examples

### Describe a migration task by listing all associated attributes

The following example lists all of the attributes associated with the values passed to the required parameters of `MigrationTaskName` and `ProgressUpdateStream`.

### Sample Request

```
{
```



```
"ProgressUpdateStream": "SMS",
"MigrationTaskName": "sms-12de3cf1a"
}
```

## Sample Response

```
{
  "MigrationTask": {
    "ProgressUpdateStream": "SMS",
    "Task": {
      "Status": "IN_PROGRESS",
      "StatusDetail": "Migration: Copying image data",
      "ProgressPercent": 77
    },
    "UpdateDateTime": 1493750385.0,
    "MigrationTaskName": "sms-12de3cf1a"
  }
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# DisassociateCreatedArtifact

Disassociates a created artifact of an AWS resource with a migration task performed by a migration tool that was previously associated. This API has the following traits:

- A migration user can call the `DisassociateCreatedArtifacts` operation to disassociate a created AWS Artifact from a migration task.
- The created artifact name must be provided in ARN (Amazon Resource Name) format which will contain information about type and region; for example: `arn:aws:ec2:us-east-1:488216288981:image/ami-6d0ba87b`.
- Examples of the AWS resource behind the created artifact are, AMI's, EC2 instance, or RDS instance, etc.

## Request Syntax

```
{
  "CreatedArtifactName": "string",
  "DryRun": boolean,
  "MigrationTaskName": "string",
  "ProgressUpdateStream": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### CreatedArtifactName

An ARN of the AWS resource related to the migration (e.g., AMI, EC2 instance, RDS instance, etc.)

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `arn:[a-z-]+:[a-z0-9-]+:(?:[a-z0-9-]+|):(?:[0-9]{12}|):.*`

Required: Yes

## DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

## MigrationTaskName

Unique identifier that references the migration task to be disassociated with the artifact. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: Yes

## ProgressUpdateStream

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## UnauthorizedOperation

Exception raised to indicate a request was not authorized when the `DryRun` flag is set to "true".

HTTP Status Code: 400

## Examples

### Disassociate a created artifact

The following example disassociates an AWS resource from the migration task `d-server-0025db43a885966c8` using its ARN formatted name `geaws:ec2:us-east-1:488216288981:image/ami-6d0ba87b`.

### Sample Request

```
{
  "CreatedArtifactName": "arn:aws:ec2:us-east-1:488216288981:image/ami-6d0ba87b",
  "MigrationTaskName": "sms-12de3cf1a",
  "ProgressUpdateStream": "SMS"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)



# DisassociateDiscoveredResource

Disassociate an Application Discovery Service discovered resource from a migration task.

## Request Syntax

```
{  
  "ConfigurationId": "string",  
  "DryRun": boolean,  
  "MigrationTaskName": "string",  
  "ProgressUpdateStream": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### ConfigurationId

ConfigurationId of the Application Discovery Service resource to be disassociated.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^\.{1,1600}$`

Required: Yes

### DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

### MigrationTaskName

The identifier given to the MigrationTask. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: Yes

### ProgressUpdateStream

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.



HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

### UnauthorizedOperation

Exception raised to indicate a request was not authorized when the `DryRun` flag is set to "true".

HTTP Status Code: 400

## Examples

### Disassociate a discovered resource from the repository

The following example removes the association between the Application Discovery Service `ConfigurationId` and the `MigrationTaskName` by passing its name value to the required parameter `ConfigurationId` as well as the required parameters `MigrationTaskName` and `ProgressUpdateStreamName` which specify the created artifact to disassociate from.

## Sample Request

```
{
  "DryRun": false,
  "MigrationTaskName": "sms-12de3cf1a",
  "ProgressUpdateStream": "SMS",
  "ConfigurationId": "d-server-0025db43a885966c8"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ImportMigrationTask

Registers a new migration task which represents a server, database, etc., being migrated to AWS by a migration tool.

This API is a prerequisite to calling the `NotifyMigrationTaskState` API as the migration tool must first register the migration task with Migration Hub.

## Request Syntax

```
{
  "DryRun": boolean,
  "MigrationTaskName": "string",
  "ProgressUpdateStream": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [DryRun](#)

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

### [MigrationTaskName](#)

Unique identifier that references the migration task. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^: ]+`

Required: Yes

### [ProgressUpdateStream](#)

The name of the ProgressUpdateStream. >

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

## ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## UnauthorizedOperation

Exception raised to indicate a request was not authorized when the `DryRun` flag is set to `"true"`.

HTTP Status Code: 400

## Examples

### Import a migration task to register it with Migration Hub

The following example registers a new migration task with Migration Hub identified by the values passed to the required parameters `MigrationTaskName` and `ProgressUpdateStreamName` in the request.

### Sample Request

```
{
  "MigrationTaskName": "sms-12de3cf1a",
  "ProgressUpdateStream": "SMS"
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListApplicationStates

Lists all the migration statuses for your applications. If you use the optional `ApplicationIds` parameter, only the migration statuses for those applications will be returned.

## Request Syntax

```
{
  "ApplicationIds": [ "string" ],
  "MaxResults": number,
  "NextToken": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [ApplicationIds](#)

The configurationIds from the Application Discovery Service that uniquely identifies your applications.

Type: Array of strings

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^\.{1,1600}$`

Required: No

### [MaxResults](#)

Maximum number of results to be returned per page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

## [NextToken](#)

If a `NextToken` was returned by a previous call, there are more results available. To retrieve the next page of results, make the call again using the returned token in `NextToken`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\_\+\=]{0,2048}$`

Required: No

## Response Syntax

```
{
  "ApplicationStateList": [
    {
      "ApplicationId": "string",
      "ApplicationStatus": "string",
      "LastUpdatedTime": number
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [ApplicationStateList](#)

A list of Applications that exist in Application Discovery Service.

Type: Array of [ApplicationState](#) objects

Array Members: Minimum number of 0 items. Maximum number of 1000 items.



## NextToken

If a `NextToken` was returned by a previous call, there are more results available. To retrieve the next page of results, make the call again using the returned token in `NextToken`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\|\+\=\]{0,2048}$`

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListCreatedArtifacts

Lists the created artifacts attached to a given migration task in an update stream. This API has the following traits:

- Gets the list of the created artifacts while migration is taking place.
- Shows the artifacts created by the migration tool that was associated by the AssociateCreatedArtifact API.
- Lists created artifacts in a paginated interface.

## Request Syntax

```
{  
  "MaxResults": number,  
  "MigrationTaskName": "string",  
  "NextToken": "string",  
  "ProgressUpdateStream": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### MaxResults

Maximum number of results to be returned per page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

### MigrationTaskName

Unique identifier that references the migration task. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `[^:|]+`

Required: Yes

### [NextToken](#)

If a `NextToken` was returned by a previous call, there are more results available. To retrieve the next page of results, make the call again using the returned token in `NextToken`.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\.\_\+\=]{0,2048}$`

Required: No

### [ProgressUpdateStream](#)

The name of the `ProgressUpdateStream`.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[^/:|\000-\037]+`

Required: Yes

## Response Syntax

```
{
  "CreatedArtifactList": [
    {
      "Description": "string",
      "Name": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### CreatedArtifactList

List of created artifacts up to the maximum number of results specified in the request.

Type: Array of [CreatedArtifact](#) objects

### NextToken

If there are more created artifacts than the max result, return the next token to be passed to the next call as a bookmark of where to start from.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\_\.\+]{0,2048}$`

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

## ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## Examples

### List created artifacts associated with a migration task and update stream

The following example lists the created artifact name and its description that is associated with the values passed to the required parameters of `MigrationTaskName` and `ProgressUpdateStream` in the request.

#### Sample Request

```
{
  "ProgressUpdateStream": "SMS",
  "MigrationTaskName": "sms-12de3cf1a",
  "MaxResults": 1
}
```

#### Sample Response

```
{
  "CreatedArtifactList": [
```

```
{
  "Name": "arn:aws:ec2:us-east-1:488216288981:image/ami-6d0ba87b",
  "Description": "Using SMS to migrate server to EC2"
}
]
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListDiscoveredResources

Lists discovered resources associated with the given MigrationTask.

## Request Syntax

```
{  
  "MaxResults": number,  
  "MigrationTaskName": "string",  
  "NextToken": "string",  
  "ProgressUpdateStream": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### MaxResults

The maximum number of results returned per page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 10.

Required: No

### MigrationTaskName

The name of the MigrationTask. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: Yes

### NextToken

If a NextToken was returned by a previous call, there are more results available. To retrieve the next page of results, make the call again using the returned token in NextToken.



Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\|\+\=\]{0,2048}$`

Required: No

### [ProgressUpdateStream](#)

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[/:|\000-\037]+`

Required: Yes

## Response Syntax

```
{
  "DiscoveredResourceList": [
    {
      "ConfigurationId": "string",
      "Description": "string"
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [DiscoveredResourceList](#)

Returned list of discovered resources associated with the given MigrationTask.

Type: Array of [DiscoveredResource](#) objects

## NextToken

If there are more discovered resources than the max result, return the next token to be passed to the next call as a bookmark of where to start from.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\_\+\=]{0,2048}$`

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## Examples

### List discovered resources associated with the given MigrationTask

The following example lists the discovered resource name and its description that is associated with the values passed to the required parameters of MigrationTaskName and ProgressUpdateStream in the request.

#### Sample Request

```
{
  "ProgressUpdateStream": "SMS",
  "MigrationTaskName": "sms-12de3cf1a",
  "NextToken": "",
  "MaxResults": 1
}
```

#### Sample Response

```
{
  "DiscoveredResourceList": [
    {
      "ConfigurationId": "d-server-0025db43a885966c8",
      "Description": "Amazon Linux AMI release 2016.09"
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListMigrationTasks

Lists all, or filtered by resource name, migration tasks associated with the user account making this call. This API has the following traits:

- Can show a summary list of the most recent migration tasks.
- Can show a summary list of migration tasks associated with a given discovered resource.
- Lists migration tasks in a paginated interface.

## Request Syntax

```
{
  "MaxResults": number,
  "NextToken": "string",
  "ResourceName": "string"
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [MaxResults](#)

Value to specify how many results are returned per page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### [NextToken](#)

If a NextToken was returned by a previous call, there are more results available. To retrieve the next page of results, make the call again using the returned token in NextToken.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\_\.\+\\=\]{0,2048}$`

Required: No

### ResourceName

Filter migration tasks by discovered resource name.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^\.{1,1600}$`

Required: No

## Response Syntax

```
{
  "MigrationTaskSummaryList": [
    {
      "MigrationTaskName": "string",
      "ProgressPercent": number,
      "ProgressUpdateStream": "string",
      "Status": "string",
      "StatusDetail": "string",
      "UpdateDateTime": number
    }
  ],
  "NextToken": "string"
}
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### MigrationTaskSummaryList

Lists the migration task's summary which includes: `MigrationTaskName`, `ProgressPercent`, `ProgressUpdateStream`, `Status`, and the `UpdateDateTime` for each task.

Type: Array of MigrationTaskSummary objects

## NextToken

If there are more migration tasks than the max result, return the next token to be passed to the next call as a bookmark of where to start from.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\_\+\=]{0,2048}$`

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### PolicyErrorException

Exception raised when there are problems accessing Application Discovery Service (Application Discovery Service); most likely due to a misconfigured policy or the `migrationhub-discovery` role is missing or not configured correctly.

HTTP Status Code: 400

## ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## Examples

### List a summary of all the migration tasks

The following example lists a summary of the migration tasks associated with the values passed to the optional parameters of `ResourceName` and `MaxResults`.

### Sample Request

```
{
  "MaxResults": 1,
  "ResourceName": "d-server-0025db43a885966c8"
}
```

### Sample Response

```
{
  "MigrationTaskSummaryList": [
    {
      "Status": "COMPLETED",
```



```
    "ProgressUpdateStream": "SMS",
    "StatusDetail": "Replication finished",
    "UpdateDateTime": 1487858882.0,
    "MigrationTaskName": "sms-12de3cf1a"
  }
]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# ListProgressUpdateStreams

Lists progress update streams associated with the user account making this call.

## Request Syntax

```
{  
  "MaxResults": number,  
  "NextToken": "string"  
}
```

## Request Parameters

The request accepts the following data in JSON format.

### [MaxResults](#)

Filter to limit the maximum number of results to list per page.

Type: Integer

Valid Range: Minimum value of 1. Maximum value of 100.

Required: No

### [NextToken](#)

If a NextToken was returned by a previous call, there are more results available. To retrieve the next page of results, make the call again using the returned token in NextToken.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\.\_\/\+\=]{0,2048}$`

Required: No

## Response Syntax

```
{
```

```
"NextToken": "string",
"ProgressUpdateStreamSummaryList": [
  {
    "ProgressUpdateStreamName": "string"
  }
]
```

## Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

### [NextToken](#)

If there are more streams created than the max result, return the next token to be passed to the next call as a bookmark of where to start from.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 2048.

Pattern: `^[a-zA-Z0-9\-\_\+\=]{0,2048}$`

### [ProgressUpdateStreamSummaryList](#)

List of progress update streams up to the max number of results passed in the input.

Type: Array of [ProgressUpdateStreamSummary](#) objects

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

## InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

## InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## Examples

### List progress update streams

The following example lists the progress update streams associated with the account invoking the request and uses the value passed to the optional parameter `MaxResults`.

#### Sample Request

```
{
  "MaxResults": 2
}
```

#### Sample Response

```
{
```

```
"ProgressUpdateStreamSummaryList": [  
  {  
    "ProgressUpdateStreamName": "DMS"  
  },  
  {  
    "ProgressUpdateStreamName": "SMS"  
  }  
],  
"NextToken": "AYADeDJG11y1VuQBWp87zGdqAkkAXwABABVhd3MtY3J5cHRvLXB1YmxpYy1rZ  
XkAREFwM0s3ME1DWDI4NVJ3RG4vQUVnWFZKa2xNQVI1a2RJZXNNQXZnN2Y4M0pMdjN6Ujhka2VE  
Z01RZEFnQ2toUE1Rdz09AAEAB2F3cy1rbXMAS2Fybphd3M6a21z0nVzLXd1c3QtMjo2MzEz0TQ  
0NDA2MDg6a2V5L2UzNmUxYTc5LTUyYTUtNDdhZi05YmZjLWUxZDY2MjMyM2E0MwCnAQEBAHieuD  
SjpG16QpfVpV6L98gI73HcNP7jNyhyIMduHA8a4wAAAH4wfAYJKoZIHvcNAQcGoG8wbQIBADBoB  
gkqhkiG9w0BBwEwHgYJYIZIAWUDBAEuMBEEDGKeYQzVoDEvBo0EDwIBEIA7KbgCu41sT0BeQaU9  
B0chDBz6NGrh3AztXyqwJGczR7Pi00JZUPipWyizD0SwVh/Exbkwm5c1UF3VJ0kCAAAAAAwAABA  
Ac1MGWKEY/ySGi8kJmV1SZ1U6rN/okwmmQCyymv////8AAAAABvAPw0ZhHxJ3B4nsQAAAAbahc0b  
uugm7vytB05AobE5AWiEJaEEz5kMiYQJtzDfwXM8h9GS8kX7ydocfw0yLCMM9/sLa5JaaqY3yVh  
K3m9SwqxBS1BBhNhsjPM0ZFVMB12UcG5CW/Qo2rrzpNA/dVrCIweobaBVrxu4X9Tkvt7qm67ns  
IGQM8SHofcfFRAGcwZQIwElspH+HhwSxyI59eG6a3juJvgbHBNKwIH72N9Si3TZaTyiskL6QUPH5  
Y9PLmtIX7AjEAiZaqz550+EUmxiizH76sVuWoCMReEgFJtSm5NM3trucfj20AiIZ6/MG3bsJ43  
fZ"  
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# NotifyApplicationState

Sets the migration state of an application. For a given application identified by the value passed to `ApplicationId`, its status is set or updated by passing one of three values to `Status`: `NOT_STARTED` | `IN_PROGRESS` | `COMPLETED`.

## Request Syntax

```
{
  "ApplicationId": "string",
  "DryRun": boolean,
  "Status": "string",
  "UpdateDateTime": number
}
```

## Request Parameters

The request accepts the following data in JSON format.

### ApplicationId

The configurationId in Application Discovery Service that uniquely identifies the grouped application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^\.{1,1600}$`

Required: Yes

### DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

### Status

Status of the application - Not Started, In-Progress, Complete.

Type: String

Valid Values: NOT\_STARTED | IN\_PROGRESS | COMPLETED

Required: Yes

### UpdateDateTime

The timestamp when the application state changed.

Type: Timestamp

Required: No

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

## InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

## PolicyErrorException

Exception raised when there are problems accessing Application Discovery Service (Application Discovery Service); most likely due to a misconfigured policy or the `migrationhub-discovery` role is missing or not configured correctly.

HTTP Status Code: 400

## ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

## ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

## ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

## UnauthorizedOperation

Exception raised to indicate a request was not authorized when the `DryRun` flag is set to "true".

HTTP Status Code: 400



## Examples

### Notify the application state to Migration Hub

The following example communicates the migration status to Migration Hub using the values passed to the required parameters `ApplicationId` and `Status`.

#### Note

In this example, the `DryRun` parameter is used and set to "true" in order to show the output of the `DryRunOperation` when the user has appropriate permissions to run the command.

### Sample Request

```
{
  "ApplicationId": "d-application-0039038d504694533",
  "Status": "IN_PROGRESS"
  "DryRun": true
}
```

### Sample Response

```
An error occurred (DryRunOperation) when calling the NotifyApplicationState operation:
  Dry Run was a success!
$
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# NotifyMigrationTaskState

Notifies Migration Hub of the current status, progress, or other detail regarding a migration task. This API has the following traits:

- Migration tools will call the NotifyMigrationTaskState API to share the latest progress and status.
- MigrationTaskName is used for addressing updates to the correct target.
- ProgressUpdateStream is used for access control and to provide a namespace for each migration tool.

## Request Syntax

```
{
  "DryRun": boolean,
  "MigrationTaskName": "string",
  "NextUpdateSeconds": number,
  "ProgressUpdateStream": "string",
  "Task": {
    "ProgressPercent": number,
    "Status": "string",
    "StatusDetail": "string"
  },
  "UpdateDateTime": number
}
```

## Request Parameters

The request accepts the following data in JSON format.

### DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

### MigrationTaskName

Unique identifier that references the migration task. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: Yes

### NextUpdateSeconds

Number of seconds after the UpdateDateTime within which the Migration Hub can expect an update. If Migration Hub does not receive an update within the specified interval, then the migration task will be considered stale.

Type: Integer

Valid Range: Minimum value of 0.

Required: Yes

### ProgressUpdateStream

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: Yes

### Task

Information about the task's progress and status.

Type: [Task](#) object

Required: Yes

### UpdateDateTime

The timestamp when the task was gathered.

Type: Timestamp

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the DryRun flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

### UnauthorizedOperation

Exception raised to indicate a request was not authorized when the `DryRun` flag is set to `"true"`.

HTTP Status Code: 400

## Examples

### Notify the migration task state to Migration Hub

The following example communicates the latest progress and updates to Migration Hub using the values passed to the required parameters `MigrationTaskName` and `ProgressUpdateStream` to tag the correct target and its migration tool. The other parameters in the example are also required to provide details of the task state.

#### Sample Request

```
{
  "MigrationTaskName": "sms-12de3cf1a",
  "NextUpdateSeconds": 60,
  "ProgressUpdateStream": "SMS",
  "Task": {
    "ProgressPercent": 77,
    "Status": "IN_PROGRESS",
    "StatusDetail": "Migration: Copying image data"
  },
  "UpdateDateTime": 1493660853
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# PutResourceAttributes

Provides identifying details of the resource being migrated so that it can be associated in the Application Discovery Service repository. This association occurs asynchronously after `PutResourceAttributes` returns.

## Important

- Keep in mind that subsequent calls to `PutResourceAttributes` will override previously stored attributes. For example, if it is first called with a MAC address, but later, it is desired to add an IP address, it will then be required to call it with both the IP and MAC addresses to prevent overriding the MAC address.
- Note the instructions regarding the special use case of the [ResourceAttributeList](#) parameter when specifying any "VM" related value.

## Note

Because this is an asynchronous call, it will always return 200, whether an association occurs or not. To confirm if an association was found based on the provided details, call `ListDiscoveredResources`.

## Request Syntax

```
{
  "DryRun": boolean,
  "MigrationTaskName": "string",
  "ProgressUpdateStream": "string",
  "ResourceAttributeList": [
    {
      "Type": "string",
      "Value": "string"
    }
  ]
}
```



## Request Parameters

The request accepts the following data in JSON format.

### DryRun

Optional boolean flag to indicate whether any effect should take place. Used to test if the caller has permission to make the call.

Type: Boolean

Required: No

### MigrationTaskName

Unique identifier that references the migration task. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:| ]+

Required: Yes

### ProgressUpdateStream

The name of the ProgressUpdateStream.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037 ]+

Required: Yes

### ResourceAttributeList

Information about the resource that is being migrated. This data will be used to map the task to a resource in the Application Discovery Service repository.

#### Note

Takes the object array of `ResourceAttribute` where the `Type` field is reserved for the following values: `IPV4_ADDRESS` | `IPV6_ADDRESS` | `MAC_ADDRESS` | `FQDN` |

VM\_MANAGER\_ID | VM\_MANAGED\_OBJECT\_REFERENCE | VM\_NAME | VM\_PATH | BIOS\_ID | MOTHERBOARD\_SERIAL\_NUMBER where the identifying value can be a string up to 256 characters.

### Important

- If any "VM" related value is set for a `ResourceAttribute` object, it is required that `VM_MANAGER_ID`, as a minimum, is always set. If `VM_MANAGER_ID` is not set, then all "VM" fields will be discarded and "VM" fields will not be used for matching the migration task to a server in Application Discovery Service repository. See the [Example](#) section below for a use case of specifying "VM" related values.
- If a server you are trying to match has multiple IP or MAC addresses, you should provide as many as you know in separate type/value pairs passed to the `ResourceAttributeList` parameter to maximize the chances of matching.

Type: Array of [ResourceAttribute](#) objects

Array Members: Minimum number of 1 item. Maximum number of 100 items.

Required: Yes

## Response Elements

If the action is successful, the service sends back an HTTP 200 response with an empty HTTP body.

## Errors

### AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

### DryRunOperation

Exception raised to indicate a successfully authorized action when the `DryRun` flag is set to "true".

HTTP Status Code: 400

### HomeRegionNotSetException

The home region is not set. Set the home region to continue.

HTTP Status Code: 400

### InternalServerError

Exception raised when an internal, configuration, or dependency error is encountered.

HTTP Status Code: 500

### InvalidInputException

Exception raised when the provided input violates a policy constraint or is entered in the wrong format or data type.

HTTP Status Code: 400

### ResourceNotFoundException

Exception raised when the request references a resource (Application Discovery Service configuration, update stream, migration task, etc.) that does not exist in Application Discovery Service (Application Discovery Service) or in Migration Hub's repository.

HTTP Status Code: 400

### ServiceUnavailableException

Exception raised when there is an internal, configuration, or dependency error encountered.

HTTP Status Code: 500

### ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

### UnauthorizedOperation

Exception raised to indicate a request was not authorized when the DryRun flag is set to "true".

HTTP Status Code: 400

## Examples

### Put migration resource attributes to associate with resource in repository

The following example sends identifying details of the resource being migrated so that it can be associated with a resource in the Application Discovery Service's repository using the values passed to the required parameters `MigrationTaskName` and `ProgressUpdateStream` to tag the correct target and its migration tool.

The `ResourceAttributeList` parameter is also required to define the resource type and its identifying value. Its `Type` field is reserved for the following values: `IPV4_ADDRESS` | `IPV6_ADDRESS` | `MAC_ADDRESS` | `FQDN` | `VM_MANAGER_ID` | `VM_MANAGED_OBJECT_REFERENCE` | `VM_NAME` | `VM_PATH` | `BIOS_ID` | `MOTHERBOARD_SERIAL_NUMBER` where the identifying value can be a string up to 256 characters.

In this particular example, the user wants to define the resource type by `VM_NAME`, but also has to set the `VM_MANAGER_ID` field as it is always required when setting any other "VM" related fields.

### Sample Request

```
{
  "MigrationTaskName": "canary-4c208ae8-9876-5432-1098-b748dd9179d3",
  "ProgressUpdateStream": "canary-017563f9-1234-5678-9de4-cf9d3378d18d",
  "ResourceAttributeList": [
    {
      "Type": "VM_NAME",
      "Value": "v1.1.1.0-cloudfront"
    },
    {
      "Type": "VM_MANAGER_ID",
      "Value": "a7b4c06d-e12f-1234-9gh7-i5j26k11m2no"
    }
  ]
}
```

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

# Data Types

The AWS Migration Hub API contains several data types that various actions use. This section describes each data type in detail.

## Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [ApplicationState](#)
- [CreatedArtifact](#)
- [DiscoveredResource](#)
- [MigrationTask](#)
- [MigrationTaskSummary](#)
- [ProgressUpdateStreamSummary](#)
- [ResourceAttribute](#)
- [Task](#)

# ApplicationState

The state of an application discovered through Migration Hub import, the AWS Agentless Discovery Connector, or the AWS Application Discovery Agent.

## Contents

### ApplicationId

The configurationId from the Application Discovery Service that uniquely identifies an application.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^\.{1,1600}$`

Required: No

### ApplicationStatus

The current status of an application.

Type: String

Valid Values: NOT\_STARTED | IN\_PROGRESS | COMPLETED

Required: No

### LastUpdatedTime

The timestamp when the application status was last updated.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)



# CreatedArtifact

An ARN of the AWS cloud resource target receiving the migration (e.g., AMI, EC2 instance, RDS instance, etc.).

## Contents

### Name

An ARN that uniquely identifies the result of a migration task.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `arn:[a-z-]+:[a-z0-9-]+:(?:[a-z0-9-]+|):(?:[0-9]{12}|):.*`

Required: Yes

### Description

A description that can be free-form text to record additional detail about the artifact for clarity or for later reference.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^.{0,500}$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# DiscoveredResource

Object representing the on-premises resource being migrated.

## Contents

### ConfigurationId

The configurationId in Application Discovery Service that uniquely identifies the on-premise resource.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 1600.

Pattern: `^\.{1,1600}$`

Required: Yes

### Description

A description that can be free-form text to record additional detail about the discovered resource for clarity or later reference.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^\.{0,500}$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MigrationTask

Represents a migration task in a migration tool.

## Contents

### MigrationTaskName

Unique identifier that references the migration task. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: No

### ProgressUpdateStream

A name that identifies the vendor of the migration tool being used.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: No

### ResourceAttributeList

Information about the resource that is being migrated. This data will be used to map the task to a resource in the Application Discovery Service repository.

Type: Array of [ResourceAttribute](#) objects

Array Members: Minimum number of 0 items. Maximum number of 100 items.

Required: No

### Task

Task object encapsulating task information.

Type: [Task](#) object

Required: No

UpdateDateTime

The timestamp when the task was gathered.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# MigrationTaskSummary

MigrationTaskSummary includes MigrationTaskName, ProgressPercent, ProgressUpdateStream, Status, and UpdateDateTime for each task.

## Contents

### MigrationTaskName

Unique identifier that references the migration task. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: [^:|]+

Required: No

### ProgressPercent

Indication of the percentage completion of the task.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

### ProgressUpdateStream

An AWS resource used for access control. It should uniquely identify the migration tool as it is used for all updates made by the tool.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: [^/:|\000-\037]+

Required: No

### Status

Status of the task.

Type: String

Valid Values: NOT\_STARTED | IN\_PROGRESS | FAILED | COMPLETED

Required: No

### StatusDetail

Detail information of what is being done within the overall status state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^.{0,500}$`

Required: No

### UpdateDateTime

The timestamp when the task was gathered.

Type: Timestamp

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ProgressUpdateStreamSummary

Summary of the AWS resource used for access control that is implicitly linked to your AWS account.

## Contents

### ProgressUpdateStreamName

The name of the ProgressUpdateStream. Do not store personal data in this field.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 50.

Pattern: `[^/:|\000-\037]+`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# ResourceAttribute

Attribute associated with a resource.

Note the corresponding format required per type listed below:

## IPV4

`x.x.x.x`

where x is an integer in the range [0,255]

## IPV6

`y : y : y : y : y : y : y : y`

where y is a hexadecimal between 0 and FFFF. [0, FFFF]

## MAC\_ADDRESS

`^([0-9A-Fa-f]{2}[:-]){5}([0-9A-Fa-f]{2})$`

## FQDN

`^[^<>{}\\|\V? ,=\p{Cntrl}]{1,256}$`

## Contents

### Type

Type of resource.

Type: String

Valid Values: IPV4\_ADDRESS | IPV6\_ADDRESS | MAC\_ADDRESS | FQDN |  
VM\_MANAGER\_ID | VM\_MANAGED\_OBJECT\_REFERENCE | VM\_NAME | VM\_PATH |  
BIOS\_ID | MOTHERBOARD\_SERIAL\_NUMBER

Required: Yes

### Value

Value of the resource type.

Type: String



Length Constraints: Minimum length of 1. Maximum length of 256.

Pattern: `^\{1,256\}$`

Required: Yes

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

# Task

Task object encapsulating task information.

## Contents

### Status

Status of the task - Not Started, In-Progress, Complete.

Type: String

Valid Values: NOT\_STARTED | IN\_PROGRESS | FAILED | COMPLETED

Required: Yes

### ProgressPercent

Indication of the percentage completion of the task.

Type: Integer

Valid Range: Minimum value of 0. Maximum value of 100.

Required: No

### StatusDetail

Details of task status as notified by a migration tool. A tool might use this field to provide clarifying information about the status that is unique to that tool or that explains an error state.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 500.

Pattern: `^.{0,500}$`

Required: No

## See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)